



MEASUREMENT REPORT
GSM / GPRS / EDGE / CDMA / WCDMA

Applicant Name:
LG Electronics USA, Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States


Date of Testing:
2/17 - 3/6/2020
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M2002170021-02-R1.ZNF

FCC ID:	ZNFK300UM
APPLICANT:	LG Electronics USA, Inc.

Application Type: Certification
Model: LM-K300UM
Additional Model(s): LMK300UM, K300UM, LM-K300WM, LMK300WM, K300WM, LM-K300QM6, LMK300QM6, K300QM6, LM-K300QM6, LMK300QM6, K300QM6
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): 22, 24, & 27
Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

Note: This revised Test Report (S/N: 1M2002170021-02-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.



Randy Ortanez
President




FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 1 of 111	

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	PCS - Base Frequency Blocks	6
3.5	PCS - Mobile Frequency Blocks.....	6
3.6	AWS - Base Frequency Blocks	7
3.7	AWS - Mobile Frequency Blocks.....	7
3.8	Radiated Measurements	8
4.0	MEASUREMENT UNCERTAINTY	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS	11
7.0	TEST RESULTS	12
7.1	Summary	12
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	19
7.4	Band Edge Emissions at Antenna Terminal	55
7.5	Peak-Average Ratio	68
7.6	Radiated Power (ERP/EIRP).....	74
7.7	Radiated Spurious Emissions Measurements.....	79
7.8	Frequency Stability / Temperature Variation	96
8.0	CONCLUSION.....	111

FCC ID: ZNFK300UM	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 2 of 111	



MEASUREMENT REPORT

GSM / GPRS / EDGE / CDMA / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	0.826	29.17	1.355	31.32	246KGXW
EDGE850	22H	824.2 - 848.8	0.066	18.21	0.109	20.36	249KG7W
CDMA850	22H	824.70 - 848.31	0.074	18.71	0.122	20.86	1M27F9W
WCDMA850	22H	826.4 - 846.6	0.144	21.59	0.237	23.74	4M18F9W
WCDMA1700	27	1712.4 - 1752.6			0.127	21.03	4M19F9W
GPRS1900	24E	1850.2 - 1909.8			0.811	29.09	245KGXW
EDGE1900	24E	1850.2 - 1909.8			0.221	23.44	246KG7W
CDMA1900	24E	1851.25 - 1908.75			0.217	23.36	1M28F9W
WCDMA1900	24E	1852.4 - 1907.6			0.144	21.59	4M20F9W

EUT Overview

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 3 of 111	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 4 of 111	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFK300UM**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

Test Device Serial No.: 00360, 00368, 00369

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A (BC0, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE).

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFK300UM	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 5 of 111	


3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)


BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

3.5 PCS - Mobile Frequency Blocks

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 6 of 111	



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)


BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

3.6 AWS - Base Frequency Blocks



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 4: 2135 – 2140 MHz (D)


BLOCK 2: 2120 – 2130 MHz (B)

BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 6: 2145 – 2155 MHz (F)

3.7 AWS - Mobile Frequency Blocks



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 7 of 111

3.8 Radiated Measurements

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 8 of 111	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFK300UM	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 9 of 111

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	6/4/2019	Annual	6/4/2020	LTx1
Agilent	E5515C	Wireless Communications Test Set	N/A			GB43193563
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			833855/0010
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	10/16/2019	Annual	10/16/2020	101716
Rohde & Schwarz	HL562E	Ultralog Antenna	3/29/2018	Biennial	3/29/2020	101012
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/9/2019	Annual	7/9/2020	102138
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/8/2019	Annual	7/8/2020	102133
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	8/17/2018	Biennial	8/17/2020	101072
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna	7/16/2018	Biennial	7/16/2020	101073
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	N/A

Table 5-1. Test Equipment

Notes:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 10 of 111	

6.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 11 of 111	

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFK300UM
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / EDGE / CDMA / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Conducted Band Edge / Spurious Emissions	> 43 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1) RSS-139(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a)(5)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d)(4)	RSS-139(6.5)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Radiated Spurious Emissions	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 4.2.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1-ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 12 of 111	

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 13 of 111	




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 14 of 111




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 15 of 111




Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode)




Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 16 of 111




Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-8. Occupied Bandwidth Plot (AWS WCDMA Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 17 of 111



Plot 7-9. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 18 of 111

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Per 24.238(b), 27.53(h)(3), and RSS-133(6.5), RSS-139(6.5), compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 19 of 111


Cellular GPRS Mode




Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)

FCC ID: ZNFK300UM	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 20 of 111




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 21 of 111




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)




Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 22 of 111




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)



Plot 7-17. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)


FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 23 of 111




Plot 7-18. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 24 of 111

PCS GPRS Mode




Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 25 of 111




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 26 of 111




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)




Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 27 of 111




Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode - High Channel)



Plot 7-26. Conducted Spurious Plot (PCS GPRS Mode - High Channel)


FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 28 of 111




Plot 7-27. Conducted Spurious Plot (PCS GPRS Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 29 of 111

Cellular CDMA Mode




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 30 of 111




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 31 of 111




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 32 of 111




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)



Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)


FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 33 of 111




Plot 7-36. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 34 of 111

PCS CDMA Mode




Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)



Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 35 of 111




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 36 of 111



Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)


FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 37 of 111




Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode - High Channel)



Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode - High Channel)


FCC ID: ZNFK300UM	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 38 of 111




Plot 7-45. Conducted Spurious Plot (PCS CDMA Mode - High Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 39 of 111

Cellular WCDMA Mode




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 40 of 111




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 41 of 111




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 42 of 111




Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)


FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 43 of 111




Plot 7-54. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 44 of 111

AWS WCDMA Mode




Plot 7-55. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)



Plot 7-56. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 45 of 111




Plot 7-57. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)




Plot 7-58. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 46 of 111



Plot 7-59. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)




Plot 7-60. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 47 of 111




Plot 7-61. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)



Plot 7-62. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)


FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 48 of 111




Plot 7-63. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 49 of 111

PCS WCDMA Mode




Plot 7-64. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-65. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 50 of 111




Plot 7-66. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-67. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 51 of 111




Plot 7-68. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-69. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFK300UM	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 52 of 111



Plot 7-70. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-71. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 53 of 111

7.4 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. $RBW \geq 1\%$ of the emission bandwidth
4. $VBW \geq 3 \times RBW$
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/RBW$
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b), 24.238(b), 27.53(h)(3), and RSS-132(5.5), RSS-133(6.5), RSS-139(6.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 55 of 111

Cellular GPRS Mode




Plot 7-73. Band Edge Plot (Cellular GPRS Mode - Low Channel)




Plot 7-74. Band Edge Plot (Cellular GPRS Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 56 of 111

PCS GPRS Mode




Plot 7-75. Band Edge Plot (PCS GPRS Mode - Low Channel)




Plot 7-76. 4MHz Span Plot (PCS GPRS Mode - Low Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 57 of 111




Plot 7-77. Band Edge Plot (PCS GPRS Mode - High Channel)



Plot 7-78. 4MHz Span Plot (PCS GPRS Mode - High Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 58 of 111

Cellular CDMA Mode




Plot 7-79. Band Edge Plot (Cellular CDMA Mode - Low Channel)



Plot 7-80. 4MHz Span Plot (Cellular CDMA Mode - Low Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 59 of 111




Plot 7-81. Band Edge Plot (Cellular CDMA Mode - High Channel)




Plot 7-82. 4MHz Span Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 60 of 111

PCS CDMA Mode



Plot 7-83. Band Edge Plot (PCS CDMA Mode - Low Channel)




Plot 7-84. 4MHz Span Plot (PCS CDMA Mode - Low Channel)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 61 of 111




Plot 7-85. Band Edge Plot (PCS CDMA Mode - High Channel)



Plot 7-86. 4MHz Span Plot (PCS CDMA Mode - High Channel)

FCC ID: ZNFK300UM	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 62 of 111

Cellular WCDMA Mode



Plot 7-87. Band Edge Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-88. Band Edge Plot (Cellular WCDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 63 of 111



Plot 7-91. Band Edge Plot (AWS WCDMA Mode - High Channel)




Plot 7-92. 4MHz Span Plot (AWS WCDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 65 of 111



Plot 7-95. Band Edge Plot (PCS WCDMA Mode - High Channel)



Plot 7-96. 4MHz Span Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 67 of 111

7.5 Peak-Average Ratio

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 68 of 111	




Plot 7-97. Peak-Average Ratio Plot (Cellular GPRS Mode)




Plot 7-98. Peak-Average Ratio Plot (EDGE850 Mode)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 69 of 111




Plot 7-99. Peak-Average Ratio Plot (PCS GPRS Mode)




Plot 7-100. Peak-Average Ratio Plot (EDGE1900 Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 70 of 111




Plot 7-101. Peak-Average Ratio Plot (Cellular CDMA Mode)




Plot 7-102. Peak-Average Ratio Plot (PCS CDMA Mode)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 71 of 111




Plot 7-103. Peak-Average Ratio Plot (Cellular WCDMA Mode)



Plot 7-104. Peak-Average Ratio Plot (AWS WCDMA Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 72 of 111



Plot 7-105. Peak-Average Ratio Plot (PCS WCDMA Mode)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 73 of 111

7.6 Radiated Power (ERP/EIRP)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 74 of 111	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 75 of 111

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 76 of 111	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GPRS850	V	136	241	23.68	6.30	27.83	0.607	38.45	-10.62	29.98	0.995	40.61	-10.63
836.60	GPRS850	V	139	249	24.92	6.40	29.17	0.826	38.45	-9.28	31.32	1.355	40.61	-9.29
848.80	GPRS850	V	141	250	24.64	6.50	28.99	0.793	38.45	-9.46	31.14	1.300	40.61	-9.47
836.60	GPRS850	H	224	169	23.11	6.70	27.66	0.583	38.45	-10.79	29.81	0.957	40.61	-10.80
836.60	EDGE850	V	140	251	13.96	6.40	18.21	0.066	38.45	-20.24	20.36	0.109	40.61	-20.25

Table 7-2. ERP/EIRP (Cellular GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.70	CDMA850	V	141	242	12.94	6.30	17.09	0.051	38.45	-21.36	19.24	0.084	40.61	-21.37
836.52	CDMA850	V	142	244	14.46	6.40	18.71	0.074	38.45	-19.74	20.86	0.122	40.61	-19.75
848.31	CDMA850	V	147	248	14.29	6.50	18.64	0.073	38.45	-19.81	20.79	0.120	40.61	-19.82
836.52	CDMA850	H	202	163	13.30	6.70	17.85	0.061	38.45	-20.60	20.00	0.100	40.61	-20.61

Table 7-3. ERP/EIRP (Cellular CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	V	139	252	15.53	6.30	19.68	0.093	38.45	-18.77	21.83	0.152	40.61	-18.78
836.60	WCDMA850	V	141	250	16.86	6.40	21.11	0.129	38.45	-17.34	23.26	0.212	40.61	-17.35
846.60	WCDMA850	V	142	250	17.24	6.50	21.59	0.144	38.45	-16.86	23.74	0.237	40.61	-16.87
846.60	WCDMA850	H	163	11	11.93	6.70	16.48	0.044	38.45	-21.97	18.63	0.073	40.61	-21.98

Table 7-4. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	H	144	338	11.45	9.43	20.88	0.123	30.00	-9.12
1732.60	WCDMA1700	H	150	336	11.72	9.31	21.03	0.127	30.00	-8.97
1752.60	WCDMA1700	H	144	334	11.74	9.21	20.95	0.124	30.00	-9.05
1732.60	WCDMA1700	V	155	53	10.60	9.19	19.79	0.095	30.00	-10.21

Table 7-5. EIRP (AWS WCDMA)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 77 of 111	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	155	134	19.02	9.48	28.50	0.707	33.01	-4.51
1880.00	GPRS1900	H	150	125	19.19	9.90	29.09	0.811	33.01	-3.92
1909.80	GPRS1900	H	141	134	17.70	10.26	27.96	0.625	33.01	-5.05
1880.00	GPRS1900	V	150	134	18.26	10.10	28.36	0.685	33.01	-4.65
1880.00	EDGE1900	H	141	134	13.54	9.90	23.44	0.221	33.01	-9.57

Table 7-6. EIRP (PCS GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	H	155	66	12.63	9.49	22.12	0.163	33.01	-10.89
1880.00	CDMA1900	H	152	67	13.18	9.90	23.08	0.203	33.01	-9.93
1908.75	CDMA1900	H	141	70	13.11	10.25	23.36	0.217	33.01	-9.65
1908.75	CDMA1900	V	141	123	12.72	10.31	23.03	0.201	33.01	-9.98

Table 7-7. EIRP (PCS CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	158	135	11.75	9.51	21.26	0.134	33.01	-11.75
1880.00	WCDMA1900	H	155	133	11.69	9.90	21.59	0.144	33.01	-11.42
1907.60	WCDMA1900	H	145	135	10.93	10.24	21.17	0.131	33.01	-11.84
1880.00	WCDMA1900	V	100	143	10.34	10.10	20.44	0.111	33.01	-12.57

Table 7-8. EIRP (PCS WCDMA)

FCC ID: ZNFK300UM	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 78 of 111

7.7 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 79 of 111	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup < 1GHz




Figure 7-8. Test Instrument & Measurement Setup >1 GHz

Test Notes


- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 80 of 111

- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 81 of 111	

Cellular GPRS Mode



Plot 7-106. Radiated Spurious Plot above 1GHz (Cellular GPRS Mode)

OPERATING FREQUENCY: 824.20 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	154	49	-55.18	8.94	-46.24	-33.2
2472.60	H	145	57	-63.54	9.64	-53.89	-40.9
3296.80	H	-	-	-65.31	9.57	-55.73	-42.7
4121.00	H	-	-	-64.15	10.17	-53.98	-41.0

Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 82 of 111

OPERATING FREQUENCY: 836.60 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	144	51	-54.84	8.95	-45.89	-32.9
2509.80	H	168	54	-60.56	9.75	-50.81	-37.8
3346.40	H	-	-	-65.15	9.60	-55.54	-42.5
4183.00	H	-	-	-65.66	10.35	-55.32	-42.3

Table 7-10. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)


OPERATING FREQUENCY: 848.80 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	186	48	-54.85	8.95	-45.90	-32.9
2546.40	H	199	60	-61.58	9.74	-51.84	-38.8
3395.20	H	-	-	-65.06	9.78	-55.28	-42.3
4244.00	H	-	-	-64.01	10.58	-53.43	-40.4

Table 7-11. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 83 of 111	

Cellular CDMA Mode



Plot 7-107. Radiated Spurious Plot above 1GHz (Cellular CDMA Mode)

OPERATING FREQUENCY: 824.70 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1649.40	H	156	141	-67.80	3.61	-64.19	-51.2
2474.10	H	-	-	-67.31	4.22	-63.09	-50.1
3298.80	H	-	-	-67.84	5.78	-62.06	-49.1

Table 7-12. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 84 of 111

OPERATING FREQUENCY: 836.52 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.04	H	181	130	-68.14	3.62	-64.52	-51.5
2509.56	H	-	-	-67.15	4.33	-62.81	-49.8
3346.08	H	-	-	-67.49	5.92	-61.57	-48.6

Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)


OPERATING FREQUENCY: 848.31 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1696.62	H	171	131	-68.40	3.63	-64.77	-51.8
2544.93	H	-	-	-67.25	4.55	-62.70	-49.7
3393.24	H	-	-	-67.80	6.13	-61.67	-48.7

Table 7-14. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 85 of 111	

Cellular WCDMA Mode



Plot 7-108. Radiated Spurious Plot above 1GHz (Cellular WCDMA Mode)

OPERATING FREQUENCY: 826.40 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	102	146	-68.39	3.61	-64.78	-51.8
2479.20	H	-	-	-66.92	4.23	-62.69	-49.7
3305.60	H	-	-	-68.19	5.80	-62.39	-49.4

Table 7-15. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 86 of 111

OPERATING FREQUENCY: 836.60 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	308	46	-69.08	3.62	-65.46	-52.5
2509.80	H	-	-	-67.04	4.34	-62.70	-49.7
3346.40	H	-	-	-67.54	5.92	-61.62	-48.6

Table 7-16. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)


OPERATING FREQUENCY: 846.60 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	104	43	-68.93	3.63	-65.31	-52.3
2539.80	H	-	-	-67.17	4.52	-62.65	-49.7
3386.40	H	-	-	-67.65	6.10	-61.56	-48.6

Table 7-17. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 87 of 111	

AWS WCDMA Mode



Plot 7-109. Radiated Spurious Plot above 1GHz (AWS WCDMA Mode)

OPERATING FREQUENCY: 1712.40 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3424.80	H	153	357	-69.61	9.83	-59.78	-46.8
5137.20	H	-	-	-75.17	10.69	-64.48	-51.5
6849.60	H	121	317	-72.32	11.64	-60.68	-47.7
8562.00	H	-	-	-71.58	11.14	-60.43	-47.4
10274.40	H	291	94	-69.56	12.21	-57.34	-44.3
11986.80	H	-	-	-70.26	12.55	-57.71	-44.7
13699.20	H	-	-	-67.95	12.08	-55.87	-42.9

Table 7-18. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1-ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 88 of 111

OPERATING FREQUENCY: 1732.60 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	182	15	-75.50	9.88	-65.62	-52.6
5197.80	H	-	-	-75.58	10.76	-64.83	-51.8
6930.40	H	114	304	-73.97	11.74	-62.22	-49.2
8663.00	H	-	-	-71.12	11.02	-60.11	-47.1
10395.60	H	264	97	-69.08	12.44	-56.64	-43.6
12128.20	H	-	-	-71.21	12.96	-58.24	-45.2
13860.80	H	-	-	-67.24	11.99	-55.25	-42.2

Table 7-19. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)


OPERATING FREQUENCY: 1752.60 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3505.20	H	150	25	-70.80	9.92	-60.88	-47.9
5257.80	H	-	-	-75.02	10.72	-64.31	-51.3
7010.40	H	116	310	-72.11	11.86	-60.25	-47.2
8763.00	H	-	-	-71.17	10.98	-60.19	-47.2
10515.60	H	281	85	-70.58	12.60	-57.98	-45.0
12268.20	H	-	-	-70.67	13.16	-57.51	-44.5
14020.80	H	-	-	-66.72	11.71	-55.01	-42.0

Table 7-20. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 89 of 111

PCS GPRS Mode



Plot 7-110. Radiated Spurious Plot above 1GHz (PCS GPRS Mode)

OPERATING FREQUENCY: 1850.20 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	212	146	-57.60	9.58	-48.02	-35.0
5550.60	H	29	361	-62.77	10.94	-51.83	-38.8
7400.80	H	400	319	-57.36	10.96	-46.40	-33.4
9251.00	H	137	306	-46.64	11.63	-35.01	-22.0
11101.20	H	280	74	-44.67	12.74	-31.93	-18.9
12951.40	H	352	61	-55.21	13.30	-41.91	-28.9
14801.60	H	267	63	-47.32	12.45	-34.87	-21.9
16651.80	H	-	-	-70.01	15.45	-54.56	-41.6

Table 7-21. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1-ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 90 of 111

OPERATING FREQUENCY: 1880.00 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	115	13	-58.58	9.37	-49.22	-36.2
5640.00	H	314	20	-59.82	11.17	-48.65	-35.6
7520.00	H	387	315	-58.91	11.11	-47.79	-34.8
9400.00	H	129	303	-43.72	11.57	-32.15	-19.2
11280.00	H	279	66	-48.84	12.72	-36.12	-23.1
13160.00	H	400	59	-60.34	13.15	-47.20	-34.2
15040.00	H	393	370	-61.22	13.52	-47.70	-34.7
16920.00	H	-	-	-67.53	14.36	-53.16	-40.2

Table 7-22. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)


OPERATING FREQUENCY: 1909.80 MHz
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	H	139	6	-62.26	9.30	-52.96	-40.0
5729.40	H	143	370	-58.02	11.39	-46.63	-33.6
7639.20	H	138	48	-60.69	11.33	-49.35	-36.4
9549.00	H	141	308	-43.86	11.79	-32.07	-19.1
11458.80	H	281	65	-58.72	12.82	-45.90	-32.9
13368.60	H	370	117	-57.60	12.78	-44.82	-31.8
15278.40	H	349	320	-63.78	14.90	-48.88	-35.9
17188.20	H	-	-	-65.15	13.32	-51.83	-38.8

Table 7-23. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 91 of 111

PCS CDMA Mode



Plot 7-111. Radiated Spurious Plot above 1GHz (PCS CDMA Mode)

OPERATING FREQUENCY: 1851.25 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3702.50	H	102	151	-72.33	9.58	-62.75	-49.8
5553.75	H	102	324	-69.84	10.95	-58.89	-45.9
7405.00	H	305	317	-66.32	10.96	-55.36	-42.4
9256.25	H	-	-	-71.13	11.63	-59.51	-46.5
11107.50	H	218	32	-68.39	12.74	-55.65	-42.7
12958.75	H	-	-	-68.69	13.30	-55.39	-42.4
14810.00	H	-	-	-67.64	12.47	-55.17	-42.2

Table 7-24. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1-ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 92 of 111

OPERATING FREQUENCY: 1880.00 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	102	149	-73.92	9.37	-64.56	-51.6
5640.00	H	109	331	-73.06	11.17	-61.89	-48.9
7520.00	H	311	313	-68.00	11.11	-56.88	-43.9
9400.00	H	-	-	-69.97	11.57	-58.40	-45.4
11280.00	H	207	25	-69.57	12.72	-56.85	-43.9
13160.00	H	-	-	-69.87	13.15	-56.73	-43.7
15040.00	H	-	-	-69.62	13.52	-56.10	-43.1

Table 7-25. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)


OPERATING FREQUENCY: 1908.75 MHz
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3817.50	H	101	138	-72.47	9.30	-63.17	-50.2
5726.25	H	107	317	-74.65	11.38	-63.27	-50.3
7635.00	H	299	313	-68.45	11.32	-57.13	-44.1
9543.75	H	-	-	-70.73	11.78	-58.95	-45.9
11452.50	H	192	12	-71.07	12.82	-58.25	-45.2
13361.25	H	-	-	-68.89	12.79	-56.10	-43.1
15270.00	H	-	-	-71.75	14.87	-56.88	-43.9

Table 7-26. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 93 of 111

PCS WCDMA Mode



Plot 7-112. Radiated Spurious Plot above 1GHz (PCS WCDMA Mode)

OPERATING FREQUENCY: 1852.40 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	136	11	-72.02	9.57	-62.46	-49.5
5557.20	H	120	323	-71.53	10.95	-60.58	-47.6
7409.60	H	362	315	-66.78	10.96	-55.82	-42.8
9262.00	H	-	-	-71.42	11.63	-59.79	-46.8
11114.40	H	197	7	-68.17	12.74	-55.44	-42.4
12966.80	H	-	-	-70.17	13.29	-56.88	-43.9
14819.20	H	-	-	-68.09	12.49	-55.61	-42.6

Table 7-27. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1-ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 94 of 111

OPERATING FREQUENCY: 1880.00 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	159	10	-71.43	9.37	-62.07	-49.1
5640.00	H	400	329	-72.49	11.17	-61.32	-48.3
7520.00	H	353	308	-67.72	11.11	-56.60	-43.6
9400.00	H	-	-	-71.06	11.57	-59.49	-46.5
11280.00	H	115	345	-67.48	12.72	-54.76	-41.8
13160.00	H	-	-	-70.48	13.15	-57.34	-44.3
15040.00	H	-	-	-69.59	13.52	-56.07	-43.1

Table 7-28. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

OPERATING FREQUENCY: 1907.60 MHz
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	190	142	-72.88	9.30	-63.58	-50.6
5722.80	H	360	9	-75.46	11.37	-64.09	-51.1
7630.40	H	114	1	-70.03	11.31	-58.72	-45.7
9538.00	H	-	-	-71.85	11.76	-60.09	-47.1
11445.60	H	116	343	-70.23	12.82	-57.41	-44.4
13353.20	H	-	-	-69.18	12.79	-56.39	-43.4
15260.80	H	-	-	-71.79	14.85	-56.94	-43.9

Table 7-29. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 95 of 111

7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, RSS-132, and RSS-133, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24, Part 27, and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 96 of 111	

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 4.25 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	836,600,139	139	0.0000166
100 %		- 20	836,600,185	185	0.0000221
100 %		- 10	836,599,631	-369	-0.0000441
100 %		0	836,600,014	14	0.0000017
100 %		+ 10	836,600,136	136	0.0000163
100 %		+ 20	836,600,146	146	0.0000175
100 %		+ 30	836,600,008	8	0.0000010
100 %		+ 40	836,599,710	-290	-0.0000347
100 %		+ 50	836,600,216	216	0.0000258
BATT. ENDPOINT	3.29	+ 20	836,599,986	-14	-0.0000017

Table 7-30. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 97 of 111

Frequency Stability / Temperature Variation




Figure 7-9. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 98 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 4.25 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	836,520,367	367	0.0000439
100 %		- 20	836,520,086	86	0.0000103
100 %		- 10	836,520,020	20	0.0000024
100 %		0	836,519,932	-68	-0.0000081
100 %		+ 10	836,520,025	25	0.0000030
100 %		+ 20	836,520,056	56	0.0000067
100 %		+ 30	836,520,004	4	0.0000005
100 %		+ 40	836,519,698	-302	-0.0000361
100 %		+ 50	836,519,974	-26	-0.0000031
BATT. ENDPOINT		3.29	+ 20	836,520,163	163

Table 7-31. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 99 of 111	

Frequency Stability / Temperature Variation




Figure 7-10. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 100 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 4183
 REFERENCE VOLTAGE: 4.25 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	836,599,812	-188	-0.0000225
100 %		- 20	836,600,033	33	0.0000039
100 %		- 10	836,599,857	-143	-0.0000171
100 %		0	836,600,111	111	0.0000133
100 %		+ 10	836,599,969	-31	-0.0000037
100 %		+ 20	836,600,214	214	0.0000256
100 %		+ 30	836,600,150	150	0.0000179
100 %		+ 40	836,600,137	137	0.0000164
100 %		+ 50	836,600,084	84	0.0000100
BATT. ENDPOINT		3.29	+ 20	836,600,158	158

Table 7-32. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 101 of 111	

Frequency Stability / Temperature Variation




Figure 7-11. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 102 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,732,600,000 Hz
 CHANNEL: 1413
 REFERENCE VOLTAGE: 4.25 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	1,732,599,978	-22	-0.0000013
100 %		- 20	1,732,599,889	-111	-0.0000064
100 %		- 10	1,732,600,067	67	0.0000039
100 %		0	1,732,599,942	-58	-0.0000033
100 %		+ 10	1,732,600,010	10	0.0000006
100 %		+ 20	1,732,599,803	-197	-0.0000114
100 %		+ 30	1,732,600,348	348	0.0000201
100 %		+ 40	1,732,600,248	248	0.0000143
100 %		+ 50	1,732,599,833	-167	-0.0000096
BATT. ENDPOINT	3.29	+ 20	1,732,599,889	-111	-0.0000064

Table 7-33. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 103 of 111	

Frequency Stability / Temperature Variation




Figure 7-12. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 104 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 4.25 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	1,879,999,708	-292	-0.0000155
100 %		- 20	1,880,000,042	42	0.0000022
100 %		- 10	1,880,000,072	72	0.0000038
100 %		0	1,879,999,950	-50	-0.0000027
100 %		+ 10	1,880,000,132	132	0.0000070
100 %		+ 20	1,880,000,279	279	0.0000148
100 %		+ 30	1,880,000,004	4	0.0000002
100 %		+ 40	1,879,999,801	-199	-0.0000106
100 %		+ 50	1,880,000,155	155	0.0000082
BATT. ENDPOINT	3.29	+ 20	1,880,000,022	22	0.0000012

Table 7-34. Frequency Stability Data (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 105 of 111	

Frequency Stability / Temperature Variation




Figure 7-13. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 106 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 4.25 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	1,879,999,996	-4	-0.0000002
100 %		- 20	1,880,000,238	238	0.0000127
100 %		- 10	1,880,000,040	40	0.0000021
100 %		0	1,879,999,777	-223	-0.0000119
100 %		+ 10	1,879,999,993	-7	-0.0000004
100 %		+ 20	1,879,999,730	-270	-0.0000144
100 %		+ 30	1,880,000,323	323	0.0000172
100 %		+ 40	1,880,000,277	277	0.0000147
100 %		+ 50	1,879,999,793	-207	-0.0000110
BATT. ENDPOINT	3.29	+ 20	1,880,000,193	193	0.0000103

Table 7-35. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 107 of 111	

Frequency Stability / Temperature Variation




Figure 7-14. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 108 of 111

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 9400
 REFERENCE VOLTAGE: 4.25 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.25	- 30	1,879,999,936	-64	-0.0000034
100 %		- 20	1,879,999,586	-414	-0.0000220
100 %		- 10	1,879,999,836	-164	-0.0000087
100 %		0	1,880,000,302	302	0.0000161
100 %		+ 10	1,880,000,327	327	0.0000174
100 %		+ 20	1,879,999,951	-49	-0.0000026
100 %		+ 30	1,879,999,959	-41	-0.0000022
100 %		+ 40	1,879,999,731	-269	-0.0000143
100 %		+ 50	1,879,999,751	-249	-0.0000132
BATT. ENDPOINT	3.29	+ 20	1,879,999,892	-108	-0.0000057

Table 7-36. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 109 of 111	

Frequency Stability / Temperature Variation




Figure 7-15. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFK300UM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset		Page 110 of 111

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFK300UM** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules.

FCC ID: ZNFK300UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2002170021-02-R1.ZNF	Test Dates: 2/17 - 3/6/2020	EUT Type: Portable Handset	Page 111 of 111	