

PART 24 MEASUREMENT REPORT

Applicant Name:
 LG Electronics USA, Inc.
 111 Sylvan Avenue, North Building
 Englewood Cliffs, NJ 07632
 United States


Date of Testing:
 12/30/2020 - 1/13/2021
Test Site/Location:
 PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
 1M2012140197-03.ZNF

FCC ID:	ZNFK330PM
Applicant Name:	LG Electronics USA, Inc.

Application Type: Class II Permissive Change
Model: LM-K330PM
Additional Model(s): LM-K330TM, LM-K330MM, LG L460DL, LM-K330QM, LM-K330QM6, LM-K330QN, LM-K330VM, LMK330PM, LMK330TM, LMK330MM, LGL460DL, LMK330QM, LMK330QM6, LMK330QN, LMK330VM, K330PM, K330TM, K330MM, L460DL, K330QM, K330QM6, K330QN, K330VM
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part: 24
Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01
Class II Permissive Change: Please see FCC change document
Original Grant Date: 01/12/2021

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President







FCC ID: ZNFK330PM		PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 1 of 26	

TABLE OF CONTENTS

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Test Configuration	4
2.4	EMI Suppression Device(s)/Modifications	4
3.0	DESCRIPTION OF TESTS	5
3.1	Evaluation Procedure	5
3.2	PCS - Base Frequency Blocks	5
3.3	PCS - Mobile Frequency Blocks.....	5
3.4	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	11
7.1	Summary	11
7.2	Radiated Power (ERP/EIRP).....	12
7.3	Radiated Spurious Emissions Measurements.....	15
	CONCLUSION.....	26

FCC ID: ZNFK330PM	 PCTEST <small>Proud to be part of element</small>	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 2 of 26	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.



1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 3 of 26

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID:ZNFK330PM**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 24.

Test Device Serial No.: 21392, 21384

2.2 Device Capabilities

This device contains the following capabilities:



850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, CDMA/EvDO Rev. 0/A 800/850/1900 (BC10/BC0/BC1), Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 LG	Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 4 of 26	


3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure


The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.



Deviation from Measurement Procedure.....None

3.2 PCS - Base Frequency Blocks



3.3 PCS - Mobile Frequency Blocks



FCC ID: ZNFK330PM	 Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 5 of 26

3.4 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI/TIA-603-E-2016. A half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi];$$

where P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [dBm] - \text{cable loss} [dB]$.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:



$$E_{[dB\mu V/m]} = \text{Measured amplitude level}_{[dBm]} + 107 + \text{Cable Loss}_{[dB]} + \text{Antenna Factor}_{[dB/m]}$$

And

$$\text{EIRP}_{[dBm]} = E_{[dB\mu V/m]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.



Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 6 of 26

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 LG	Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 7 of 26

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	MT8820C	Radio Communication Analyzer	N/A			6201300731
Anritsu	MT8821C	Radio Communication Analyzer	N/A			6200901190
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Keysight Technologies	N9020A	MXA Signal Analyzer	4/29/2019	Annual	8/14/2021	MY54500644
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/10/2020	Annual	2/10/2021	102134

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFK330PM		PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 8 of 26	

6.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

QPSK Modulation



Emission Designator = 8M62G7D

LTE BW = 8.62 MHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D



LTE BW = 8.45 MHz
 W = Amplitude/Angle Modulated
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 LG	Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 9 of 26

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: ZNFK330PM	 PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		 Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 10 of 26

7.0 TEST RESULTS

7.1 Summary



Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFK330PM
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM/GPRS/EDGE/WCDMA/CDMA/LTE

Test Condition	Test Description	FCC Part Section(s)	RSS Section(s)	Test Limit	Test Result	Reference
RADIATED	Effective Radiated Power / Equivalent Isotropic Radiated Power	24.232(c)	RSS-132(5.4)	< 7 Watts max. ERP	PASS	Section 7.2
	Radiated Spurious Emissions	2.1053, 24.238(a)	RSS-133(6.5)	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions	PASS	Section 7.3

Table 7-1. Summary of Test Results

Notes:

All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 LG	Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 11 of 26

7.2 Radiated Power (ERP/EIRP)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 12 of 26

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Radiated Test Setup <1GHz

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest powers is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1".
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 5) This unit was tested with its standard battery.
- 6) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: ZNFK330PM	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	LG	Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 13 of 26	

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
20 MHz	QPSK	1860.0	H	123.0	11.0	9.64	1 / 50	12.65	22.29	0.170	33.01	-10.72
		1882.5	H	118.0	7.0	9.96	1 / 50	12.59	22.55	0.180	33.01	-10.46
		1905.0	H	117.0	5.0	10.24	1 / 50	12.08	22.32	0.171	33.01	-10.69
	16-QAM	1860.0	H	123.0	11.0	9.64	1 / 50	11.40	21.04	0.127	33.01	-11.97
		1882.5	H	118.0	7.0	9.96	100 / 0	11.90	21.86	0.153	33.01	-11.15
		1905.0	H	117.0	5.0	10.24	1 / 50	10.90	21.14	0.130	33.01	-11.87
	64-QAM	1860.0	H	123.0	11.0	9.64	1 / 50	10.40	20.04	0.101	33.01	-12.97
		1882.5	H	118.0	7.0	9.96	1 / 50	10.39	20.35	0.108	33.01	-12.66
		1905.0	H	117.0	5.0	10.24	1 / 50	9.64	19.88	0.097	33.01	-13.13

Table 7-2. EIRP Data (LTE Band 25/2)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	H	115	352	16.50	9.51	26.01	0.399	33.01	-7.00
1880.00	GSM1900	H	107	331	15.92	9.93	25.85	0.384	33.01	-7.16
1909.80	GSM1900	H	114	10	13.26	10.28	23.54	0.226	33.01	-9.47
1850.20	GSM1900	V	256	14	10.70	9.90	20.60	0.115	33.01	-12.41
1850.20	EDGE1900	H	115	352	10.02	9.51	19.53	0.090	33.01	-13.48



Table 7-3. EIRP Data (GPRS PCS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	V	185	230	12.68	9.92	22.60	0.182	33.01	-10.41
1880.00	WCDMA1900	V	180	236	13.35	10.13	23.48	0.223	33.01	-9.53
1907.60	WCDMA1900	V	177	239	11.23	10.33	21.56	0.143	33.01	-11.45
1880.00	WCDMA1900	H	102	328	12.78	10.13	22.91	0.196	33.01	-10.10

Table 7-4. EIRP Data (WCDMA PCS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	H	125	10	14.15	9.52	23.67	0.233	33.01	-9.34
1880.00	CDMA1900	H	117	3	14.71	9.93	24.64	0.291	33.01	-8.37
1908.75	CDMA1900	H	110	3	14.29	10.27	24.56	0.286	33.01	-8.45
1880.00	CDMA1900	V	134	311	14.38	10.13	24.51	0.283	33.01	-8.50

Table 7-5. EIRP Data (CDMA PCS)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 14 of 26	

7.3 Radiated Spurious Emissions Measurements

Test Overview



Radiated spurious emissions measurements are performed using the field strength conversion method described in KDB 971168 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFK330PM	 PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		 Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 15 of 26

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup < 1GHz






Figure 7-3. Test Instrument & Measurement Setup >1 GHz


FCC ID: ZNFK330PM		PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 16 of 26	

Test Notes

- 1) Field strengths are calculated using the Measurement quantity conversions in KDB 971168 Section 5.8.4.
 - b) $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - d) $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
- 2) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest powers is reported in GPRS mode while transmitting with one slot active.
- 3) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1".
- 4) For CDMA, this device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 6) This unit was tested with its standard battery.
- 7) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 8) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 9) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 10) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 17 of 26

LTE Band 25/2



Plot 7-1. Radiated Spurious Plot (LTE Band 25/2)

Bandwidth (MHz):	20
Frequency (MHz):	1860.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3720.0	H	379	323	-69.48	2.45	39.97	-55.29	-13.00	-42.29
5580.0	H	173	123	-76.20	5.06	35.86	-59.39	-13.00	-46.39
7440.0	H	-	-	-78.89	8.98	37.09	-58.17	-13.00	-45.17
9300.0	H	-	-	-79.42	10.94	38.52	-56.74	-13.00	-43.74
11160.0	H	-	-	-79.11	12.64	40.53	-54.72	-13.00	-41.72

Table 7-6. Radiated Spurious Data (LTE Band 25/2 – Low Channel)

Bandwidth (MHz):	20
Frequency (MHz):	1882.5
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3765.0	H	372	219	-74.37	2.86	35.49	-59.77	-13.00	-46.77
5647.5	H	396	21	-80.02	5.01	31.99	-63.27	-13.00	-50.27
7530.0	H	-	-	-80.13	9.39	36.26	-59.00	-13.00	-46.00
9412.5	H	-	-	-82.28	11.98	36.70	-58.56	-13.00	-45.56
11295.0	H	-	-	-82.38	12.95	37.57	-57.69	-13.00	-44.69



Table 7-7. Radiated Spurious Data (LTE Band 25/2 – Mid Channel)

FCC ID: ZNFK330PM		PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 18 of 26


Bandwidth (MHz):	20
Frequency (MHz):	1905.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3810.00	H	385	310	-75.56	2.47	33.91	-61.35	-13.00	-48.35
5715.00	H	145	124	-76.70	4.83	35.13	-60.13	-13.00	-47.13
7620.00	H	-	-	-78.98	9.42	37.44	-57.81	-13.00	-44.81
9525.00	H	-	-	-79.35	11.34	38.99	-56.26	-13.00	-43.26
11430.00	H	-	-	-80.34	13.42	40.08	-55.18	-13.00	-42.18

Table 7-8. Radiated Spurious Data (LTE Band 25/2 – High Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 19 of 26	

GSM/GPRS PCS



Plot 7-2. Radiated Spurious Plot (GPRS PCS)

Mode:	GPRS 1 Tx Slot
Channel:	512
Frequency (MHz):	1850.2

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3700.4	H	152	47	-62.21	2.47	47.26	-47.99	-13.00	-34.99
5550.6	H	353	153	-38.76	4.70	72.94	-22.31	-13.00	-9.31
7400.8	H	269	171	-74.68	9.53	41.85	-53.41	-13.00	-40.41
9251.0	H	397	27	-61.18	10.52	56.34	-38.92	-13.00	-25.92
11101.2	H	-	-	-81.40	13.06	38.66	-56.60	-13.00	-43.60
12951.4	H	-	-	-80.80	14.45	40.65	-54.61	-13.00	-41.61
14801.6	H	-	-	-82.19	17.23	42.04	-53.22	-13.00	-40.22

Table 7-9. Radiated Spurious Data (GPRS PCS – Low Channel)

Mode:	GPRS 1 Tx Slot
Channel:	661
Frequency (MHz):	1880

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3760.0	H	119	27	-63.39	2.78	46.39	-48.87	-13.00	-35.87
5640.0	H	338	151	-73.74	5.01	38.27	-56.99	-13.00	-43.99
7520.0	H	-	-	-78.79	9.28	37.49	-57.77	-13.00	-44.77
9400.0	H	-	-	-80.11	11.92	38.81	-56.45	-13.00	-43.45
11280.0	H	-	-	-79.48	12.92	40.44	-54.82	-13.00	-41.82



Table 7-10. Radiated Spurious Data (GPRS PCS – Mid Channel)

FCC ID: ZNFK330PM	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 20 of 26	


Mode:	GPRS 1 Tx Slot
Channel:	810
Frequency (MHz):	1909.8

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3819.6	H	130	221	-62.81	2.45	46.64	-48.61	-13.00	-35.61
5729.4	H	115	147	-74.15	4.65	37.50	-57.76	-13.00	-44.76
7639.2	H	-	-	-79.15	9.80	37.65	-57.60	-13.00	-44.60
9549.0	H	-	-	-79.06	11.27	39.21	-56.05	-13.00	-43.05
11458.8	H	-	-	-80.39	12.93	39.54	-55.72	-13.00	-42.72

Table 7-11. Radiated Spurious Data (GPRS PCS – High Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 21 of 26	

WCDMA PCS



Plot 7-3. Radiated Spurious Plot (WCDMA PCS)

Mode:	WCDMA RMC
Channel:	9262
Frequency (MHz):	1852.4



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
2403.0	V	277	173	-79.78	-11.96	15.26	-80.00	-13.00	-67.00
5557.2	V	-	-	-80.18	8.77	35.59	-59.67	-13.00	-46.67
7409.6	V	-	-	-81.47	12.13	37.66	-57.59	-13.00	-44.59
9262.0	V	-	-	-82.57	13.95	38.38	-56.88	-13.00	-43.88

Table 7-12. Radiated Spurious Data (WCDMA PCS – Low Channel)

Mode:	WCDMA RMC
Channel:	9400
Frequency (MHz):	1880

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3760.0	V	100	345	-79.59	6.14	33.55	-61.71	-13.00	-48.71
5640.0	V	-	-	-80.18	8.08	34.90	-60.36	-13.00	-47.36
7520.0	V	-	-	-81.47	12.45	37.98	-57.27	-13.00	-44.27
9400.0	V	-	-	-82.57	14.66	39.09	-56.17	-13.00	-43.17



Table 7-13. Radiated Spurious Data (WCDMA PCS – Mid Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 22 of 26	


Mode:	WCDMA RMC
Channel:	9538
Frequency (MHz):	1907.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3815.2	V	204	102	-78.18	5.84	34.66	-60.60	-13.00	-47.60
5722.8	V	-	-	-79.19	8.36	36.17	-59.09	-13.00	-46.09
7630.4	V	-	-	-80.19	12.56	39.37	-55.89	-13.00	-42.89
9538.0	V	-	-	-80.66	14.40	40.74	-54.52	-13.00	-41.52

Table 7-14. Radiated Spurious Data (WCDMA PCS – High Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 23 of 26

CDMA PCS



Plot 7-4. Radiated Spurious Plot (CDMA PCS)

Mode:	CDMA
Channel:	25
Frequency (MHz):	1851.25



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3702.50	V	122	255	-76.15	2.47	33.32	-61.94	-13.00	-48.94
5553.75	V	-	-	-77.20	4.73	34.53	-60.73	-13.00	-47.73
7405.00	V	-	-	-78.23	9.41	38.18	-57.08	-13.00	-44.08
9256.25	V	-	-	-78.49	10.63	39.14	-56.12	-13.00	-43.12

Table 7-15. Radiated Spurious Data (CDMA PCS – Low Channel)

Mode:	CDMA
Channel:	600
Frequency (MHz):	1880

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3760.00	V	116	268	-75.69	2.78	34.09	-61.17	-13.00	-48.17
5640.00	V	-	-	-77.12	5.01	34.89	-60.37	-13.00	-47.37
7520.00	V	-	-	-78.95	9.28	37.33	-57.93	-13.00	-44.93
9400.00	V	-	-	-79.98	11.92	38.94	-56.32	-13.00	-43.32



Table 7-16. Radiated Spurious Data (CDMA PCS – Mid Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 24 of 26	

Mode:	CDMA
Channel:	1175
Frequency (MHz):	1908.75



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3817.50	V	376	126	-73.24	2.46	36.22	-59.04	-13.00	-46.04
5726.25	V	-	-	-77.46	4.61	34.15	-61.10	-13.00	-48.10
7635.00	V	-	-	-81.22	9.73	35.51	-59.74	-13.00	-46.74
9543.75	V	-	-	-80.95	11.26	37.31	-57.95	-13.00	-44.95

Table 7-17. Radiated Spurious Data (CDMA PCS – High Channel)

FCC ID: ZNFK330PM	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset	Page 25 of 26	

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFK330PM** complies with all the requirements of Part 24 of the FCC rules.

FCC ID: ZNFK330PM		PART 24 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2012140197-03.ZNF	Test Dates: 12/30/2020 - 1/13/2021	EUT Type: Portable Handset		Page 26 of 26