



SAR EVALUATION REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

For

GSM/WCDMA/LTE PHONE WITH BT + DTS WLAN b/g/n & NFC

**FCC ID: ZNFK371
Model Name: LG-K371, LGK371, K371**

**Report Number: 16I22670-S1V2
Issue Date: 2/22/2016**

Prepared for

**LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NEW JERSEY 07632**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Date	Revisions	Revised By
V1	2/16/2016	Initial Issue	
V2	2/22/2016	Updated EUT Description Section 2: Updated KDB 447498 version number Section 6.4: Updated Table	Coltyce Sanders

Table of Contents

1.	Attestation of Test Results	5
2.	Test Specification, Methods and Procedures.....	6
3.	Facilities and Accreditation.....	6
4.	SAR Measurement System & Test Equipment	7
4.1.	<i>SAR Measurement System.....</i>	7
4.2.	<i>SAR Scan Procedures.....</i>	8
4.3.	<i>Test Equipment.....</i>	10
5.	Measurement Uncertainty.....	11
6.	Device Under Test (DUT) Information	12
6.1.	<i>DUT Description</i>	12
6.2.	<i>Wireless Technologies.....</i>	12
6.3.	<i>Maximum Output Power from Tune-up Procedure.....</i>	13
6.4.	<i>General LTE SAR Test and Reporting Considerations.....</i>	14
7.	RF Exposure Conditions (Test Configurations).....	15
8.	Dielectric Property Measurements & System Check	16
8.1.	<i>Dielectric Property Measurements</i>	16
8.2.	<i>System Check.....</i>	19
9.	Conducted Output Power Measurements.....	20
9.1.	<i>GSM.....</i>	20
9.2.	<i>W-CDMA.....</i>	21
9.3.	<i>LTE.....</i>	26
9.4.	<i>Wi-Fi 2.4GHz (DTS Band)</i>	34
9.5.	<i>Bluetooth</i>	34
10.	Measured and Reported (Scaled) SAR Results.....	35
10.1.	<i>GSM850.....</i>	37
10.2.	<i>GSM1900.....</i>	37
10.3.	<i>W-CDMA Band II.....</i>	38
10.4.	<i>W-CDMA Band IV</i>	38
10.5.	<i>W-CDMA Band V</i>	38
10.6.	<i>LTE Band 2 (20MHz Bandwidth)</i>	39
10.7.	<i>LTE Band 4 (20MHz Bandwidth)</i>	39
10.8.	<i>LTE Band 5 (10MHz Bandwidth)</i>	40
10.9.	<i>LTE Band 12 (10MHz Bandwidth)</i>	40



10.10. Wi-Fi (DTS Band).....	41
10.11. Bluetooth.....	42
11. SAR Measurement Variability.....	43
12. Simultaneous Transmission SAR Analysis.....	44
12.1. Sum of the SAR for WWAN & Wi-Fi & BT.....	44
Appendixes	45
16I22670-S1V1 SAR_App A Photos & Ant. Locations.....	45
16I22670-S1V1 SAR_App B System Check Plots.....	45
16I22670-S1V1 SAR_App C Highest Test Plots.....	45
16I22670-S1V1 SAR_App D Tissue Ingredients.....	45
16I22670-S1V1 SAR_App E Probe Cal. Certificates	45
16I22670-S1V1 SAR_App F Dipole Cal. Certificates.....	45

1. Attestation of Test Results

Applicant Name	LG ELECTRONICS MOBILECOMM U.S.A., INC.			
FCC ID	ZNFK371			
Model Name	LG-K371, LGK371, K371			
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013			
Exposure Category	SAR Limits (W/Kg)			
	Peak spatial-average(1g of tissue)			
General population / Uncontrolled exposure	1.6			
RF Exposure Conditions	Equipment Class - Highest Reported SAR (W/kg)			
	Licensed	DTS	U-NII	DSS (BT)
Head	0.626	0.476	N/A	N/A
Body-worn	1.032	0.118		
Hotspot				
Simultaneous Tx	1.150			
Date Tested	1/19/2016 to 1/22/2016			
Test Results	Pass			

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.

Approved & Released By:	Prepared By:
	
Devin Chang Senior Engineer UL Verification Services Inc.	Annie Pang Laboratory Technician UL Verification Services Inc.

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures:

- 248227 D01 802.11 Wi-Fi SAR v02r02
- 447498 D01 General RF Exposure Guidance v06
- 447498 D03 Supplement C Cross-Reference v01
- 648474 D04 Handset SAR v01r03
- 690783 D01 SAR Listings on Grants v01r03
- 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- 865664 D02 RF Exposure Reporting v01r02
- 941225 D01 3G SAR Procedures v03r01
- 941225 D05 SAR for LTE Devices v02r05
- 941225 D05A LTE Rel.10 KDB Inquiry Sheet v01r02
- 941225 D06 Hotspot Mode v02r01

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at


47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	
SAR Lab F	
SAR Lab G	
SAR Lab H	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

4.2. SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	Agilent	8753ES	MY40001647	7/28/2016
Dielectric Probe kit	SPEAG	DAK-3.5	1103	2/17/2016
Shorting block	SPEAG	DAK-3.5 Short	SM DAK 200 BA	2/17/2016
Thermometer	Control Company	Traceable	140493798	8/4/2016

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
HP Signal Generator	HP	8665B	3744A01084	5/8/2016
Power Meter	Agilent	N1912A	MY50001018	10/19/2016
Power Sensor	Agilent	E9323A	MY5307005	4/29/2016
Power Sensor	Agilent	E9323A	MY5307007	3/2/2016
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1795093	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2149	N/A
DC Power Supply	Sorensen Ametek	XT15-4	1319A02778	N/A
Synthesized Signal Generator	Agilent	8665B	3546A00784	6/27/2016
Power Meter	HP	437B	3125U09248	9/3/2016
Power Meter	HP	437B	3125U09516	9/17/2016
Power Sensor	Agilent	8481A	2349A36506	9/16/2016
Power Sensor	Agilent	8481A	3318A92374	9/16/2016
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1622052	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2711	N/A
DC Power Supply	Sorensen Ametek	XT 15-4	1319A02780	N/A
E-Field Probe (SAR Lab 1)	SPEAG	EX3DV4	7356	4/22/2016
E-Field Probe (SAR Lab 2)	SPEAG	EX3DV4	3990	3/18/2016
E-Field Probe (SAR Lab 3)	SPEAG	EX3DV4	3773	4/22/2016
E-Field Probe (SAR Lab 4)	SPEAG	EX3DV4	3989	3/17/2016
Data Acquisition Electronics (SAR Lab 1)	SPEAG	DAE3	500	5/22/2016
Data Acquisition Electronics (SAR Lab 2)	SPEAG	DAE4	1257	9/16/2016
Data Acquisition Electronics (SAR Lab 3)	SPEAG	DAE4	1434	4/16/2016
Data Acquisition Electronics (SAR Lab 4)	SPEAG	DAE4	1258	5/14/2016
System Validation Dipole	SPEAG	D750V3	1019	3/11/2016
System Validation Dipole	SPEAG	D835V2	4d142	9/23/2016
System Validation Dipole	SPEAG	D1750V2	1050	4/15/2016
System Validation Dipole	SPEAG	D1900V2	5d163	9/21/2016
System Validation Dipole	SPEAG	D2450V2	706	5/11/2016
Thermometer (SAR Lab 1)	EXTECH	445703	CCS-205	3/20/2016
Thermometer (SAR Lab 2)	EXTECH	445703	CCS-200	3/19/2016
Thermometer (SAR Lab 3)	EXTECH	445703	CCS-237	6/5/2016
Thermometer (SAR Lab 4)	EXTECH	445703	CCS-238	6/5/2016

Other

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Power Meter	Agilent	N1912A	MY55196004	7/1/2016
Power Sensor	Agilent	N1921A	MY53260001	9/24/2016
Base Station Simulator	R & S	CMW500	132910	10/22/2016
Base Station Simulator	R & S	CMW500	135390	4/6/2016

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

6. Device Under Test (DUT) Information

6.1. DUT Description

Device Dimension	Overall (Length x Width): 144.6 mm x 71.5 mm Overall Diagonal: 152.82 mm Display Diagonal: 127.19 mm															
Back Cover	<input type="checkbox"/> Normal Battery Cover <input checked="" type="checkbox"/> Normal Battery Cover with NFC															
Battery Options	<input checked="" type="checkbox"/> Standard – Lithium-ion battery, Rating 3.8Vdc, 8.1Wh <input type="checkbox"/> Extended (large capacity)															
Accessory	Headset															
Wireless Router (Hotspot)	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi-enabled devices. <input checked="" type="checkbox"/> Mobile Hotspot (Wi-Fi 2.4 GHz)															
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other <input checked="" type="checkbox"/> Wi-Fi Direct (Wi-Fi 2.4 GHz)															
Test sample information	<table border="1"> <thead> <tr> <th>S/N</th> <th>IMEI</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>512CYKJ000381</td> <td>354885070003815</td> <td>SAR SAMPLE</td> </tr> <tr> <td>512CYFT000387</td> <td>354885070003872</td> <td>SAR SAMPLE</td> </tr> <tr> <td>512CYNL000383</td> <td>354885070003831</td> <td>CONDUCTED SAMPLE</td> </tr> <tr> <td>512CYEA000388</td> <td>354885070003807</td> <td>WIFI SAMPLE</td> </tr> </tbody> </table>	S/N	IMEI	Notes	512CYKJ000381	354885070003815	SAR SAMPLE	512CYFT000387	354885070003872	SAR SAMPLE	512CYNL000383	354885070003831	CONDUCTED SAMPLE	512CYEA000388	354885070003807	WIFI SAMPLE
S/N	IMEI	Notes														
512CYKJ000381	354885070003815	SAR SAMPLE														
512CYFT000387	354885070003872	SAR SAMPLE														
512CYNL000383	354885070003831	CONDUCTED SAMPLE														
512CYEA000388	354885070003807	WIFI SAMPLE														

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode		Duty Cycle used for SAR testing
GSM	850 1900	Voice (GMSK) GPRS (GMSK) EGPRS (8PSK)	GPRS Multi-Slot Class: <input type="checkbox"/> Class 8 - 1 Up, 4 Down <input checked="" type="checkbox"/> Class 10 - 2 Up, 4 Down <input type="checkbox"/> Class 12 - 4 Up, 4 Down <input type="checkbox"/> Class 33 - 4 Up, 5 Down	GSM Voice: 12.5% (E)GPRS: 1 Slot: 12.5% 2 Slots: 25%
		Does this device support DTM (Dual Transfer Mode)? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
W-CDMA (UMTS)	Band II Band IV Band V	UMTS Rel. 99 (Voice & Data) HSDPA (Rel. 5) HSUPA (Rel. 6)		100%
LTE	FDD Band 2 FDD Band 4 FDD Band 5 FDD Band 12 FDD Band 29 (Rx Only)	QPSK 16QAM <input checked="" type="checkbox"/> Rel. 10 Carrier Aggregation (CA) Downlink Aggregation only		100% (FDD)
		Does this device support SV-LTE (1xRTT-LTE)? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20)		100%
Bluetooth	2.4 GHz	Version 4.1 LE		77.5% (DH5)

6.3. Maximum Output Power from Tune-up Procedure

KDB 447498 sec.4.1.(3) at the maximum rated output power and within the tune-up tolerance range specified for the product, but not more than 2 dB lower than the maximum tune-up tolerance limit

RF Air interface	Mode	Max. RF Output Power (dBm)	
		Burst	Frame
GSM850	Voice/GPRS (1 slot)	33.2	24.2
	GPRS 2 slots	31.7	25.7
	EGPRS 1 slot	27.2	18.2
	EGPRS 2 slots	26.2	20.2
GSM1900	Voice/GPRS (1 slot)	29.7	20.7
	GPRS 2 slots	28.2	22.2
	EGPRS 1 slot	25.7	16.7
	EGPRS 2 slots	24.7	18.7
RF Air interface	Mode	RF Output Power (dBm)	
W-CDMA Band II	R99	22.7	
	HSDPA	22.7	
	HSUPA	22.7	
W-CDMA Band IV	R99	22.7	
	HSDPA	22.7	
	HSUPA	22.7	
W-CDMA Band V	R99	23.7	
	HSDPA	23.7	
	HSUPA	23.7	
LTE Band 2	QPSK	22.7	
	16 QAM	21.7	
LTE Band 4	QPSK	23.2	
	16 QAM	22.2	
LTE Band 5	QPSK	24.4	
	16 QAM	23.4	
LTE Band 12	QPSK	24.4	
	16 QAM	23.4	
RF Air interface	Mode	Channel	RF Output Power (dBm)
WiFi 2.4 GHz	802.11b	All	16.0
	802.11g	All	13.0
	802.11n HT20	All	11.0
Bluetooth		All	9.5
Bluetooth LE		All	0.0

6.4. General LTE SAR Test and Reporting Considerations

Item	Description																																												
Frequency range, Channel Bandwidth, Numbers and Frequencies	Band 2	Frequency range: 1850 - 1910 MHz																																											
		Channel Bandwidth																																											
		20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																						
	Low	18700 /1860	18675/ 1857.5	18650/ 1855	18625/ 1852.5	18615/ 1851.5	18607/ 1850.7																																						
	Mid	18900/ 1880	18900/ 1880	18900/ 1880	18900/ 1880	18900/ 1880	18900/ 1880																																						
	High	19100/ 1900	19125/ 1902.5	19150/ 1905	19175/ 1907.5	19185/ 1908.5	19193/ 1909.3																																						
	Band 4	Frequency range: 1710 - 1755 MHz																																											
		Channel Bandwidth																																											
		20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																						
	Low		20025/ 1717.5	20000/ 1715	19975/ 1712.5	19965/ 1711.5	19957/ 1710.7																																						
	Mid	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5																																						
	High		20325/ 1747.5	20350/ 1750	20375/ 1752.5	20385/ 1753.5	20393/ 1754.3																																						
	Band 5	Frequency range: 824 - 849 MHz																																											
		Channel Bandwidth																																											
		20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																						
	Low				20425/ 826.5	20415/ 825.5	20407/ 824.7																																						
	Mid			20525/ 836.5	20525/ 836.5	20525/ 836.5	20525/ 836.5																																						
	High				20625/ 846.5	20635/ 847.5	20643/ 848.3																																						
	Band 12	Frequency range: 699 - 716 MHz																																											
		Channel Bandwidth																																											
		20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																						
Low				23035/ 701.5	23025/ 700.5	23017/ 699.7																																							
Mid			23095/ 707.5	23095/ 707.5	23095/ 707.5	23095/ 707.5																																							
High				23155/ 713.5	23165/ 714.5	23173/ 715.3																																							
LTE transmitter and antenna implementation	Refer to Appendix A.																																												
Maximum power reduction (MPR)	<p align="center">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> </tbody> </table> <p>MPR Built-in by design A-MPR (additional MPR) was disabled during SAR testing</p>							Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																						
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																							
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																						
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																						
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																						
Power reduction	No																																												
Spectrum plots for RB configurations	A properly configured base station simulator was used for the SAR and power measurements; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																												

7. RF Exposure Conditions (Test Configurations)

Refer to “SAR Photos and Ant locations” Appendix for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

Wireless technologies	RF Exposure Conditions	DUT-to-User Separation	Test Position	Antenna-to-edge/surface	SAR Required	Note
WWAN (Antenna 1)	Head	0 mm	Left Touch	N/A	Yes	
			Left Tilt (15°)	N/A	Yes	
			Right Touch	N/A	Yes	
			Right Tilt (15°)	N/A	Yes	
	Body	10 mm	Rear	N/A	Yes	
			Front	N/A	Yes	
	Hotspot	10 mm	Rear	< 25 mm	Yes	
			Front	< 25 mm	Yes	
			Edge 1 (Top)	> 25 mm	No	1
			Edge 2 (Right)	< 25 mm	Yes	
WWAN (Antenna 2)	Head	0 mm	Left Touch	N/A	Yes	
			Left Tilt (15°)	N/A	Yes	
			Right Touch	N/A	Yes	
			Right Tilt (15°)	N/A	Yes	
	Body	10 mm	Rear	N/A	Yes	
			Front	N/A	Yes	
	Hotspot	10 mm	Rear	< 25 mm	Yes	
			Front	< 25 mm	Yes	
			Edge 1 (Top)	> 25 mm	No	1
			Edge 2 (Right)	> 25 mm	No	1
WLAN (Antenna 4)	Head	0 mm	Left Touch	N/A	Yes	
			Left Tilt (15°)	N/A	Yes	
			Right Touch	N/A	Yes	
			Right Tilt (15°)	N/A	Yes	
	Body	10 mm	Rear	N/A	Yes	
			Front	N/A	Yes	
	Hotspot/Wi-Fi Direct	10 mm	Rear	< 25 mm	Yes	
			Front	< 25 mm	Yes	
			Edge 1 (Top)	< 25 mm	Yes	
			Edge 2 (Right)	< 25 mm	Yes	
			Edge 3 (Bottom)	> 25 mm	No	1
			Edge 4 (Left)	> 25 mm	No	1

Notes:

- SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR.

8. Dielectric Property Measurements & System Check

8.1. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Dielectric Property Measurements Results:**SAR Lab 1**

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit \pm (%)	
1/21/2016	Head 835	e'	39.8600	Relative Permittivity (ϵ_r):	39.86	41.50	-3.95	5
		e"	18.8900	Conductivity (σ):	0.88	0.90	-2.55	5
	Head 820	e'	40.1100	Relative Permittivity (ϵ_r):	40.11	41.60	-3.59	5
		e"	19.0300	Conductivity (σ):	0.87	0.90	-3.43	5
	Head 850	e'	39.7200	Relative Permittivity (ϵ_r):	39.72	41.50	-4.29	5
		e"	18.9200	Conductivity (σ):	0.89	0.92	-2.27	5
1/21/2016	Body 835	e'	52.6800	Relative Permittivity (ϵ_r):	52.68	55.20	-4.57	5
		e"	21.2800	Conductivity (σ):	0.99	0.97	1.86	5
	Body 820	e'	52.8200	Relative Permittivity (ϵ_r):	52.82	55.28	-4.44	5
		e"	21.4800	Conductivity (σ):	0.98	0.97	1.13	5
	Body 850	e'	52.6100	Relative Permittivity (ϵ_r):	52.61	55.16	-4.62	5
		e"	21.3000	Conductivity (σ):	1.01	0.99	1.98	5

SAR Lab 2

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit \pm (%)	
1/20/2016	Head 1750	e'	38.7700	Relative Permittivity (ϵ_r):	38.77	40.08	-3.28	5
		e"	13.9800	Conductivity (σ):	1.36	1.37	-0.63	5
	Head 1710	e'	38.9500	Relative Permittivity (ϵ_r):	38.95	40.15	-2.98	5
		e"	13.9000	Conductivity (σ):	1.32	1.35	-1.84	5
	Head 1755	e'	38.7500	Relative Permittivity (ϵ_r):	38.75	40.08	-3.31	5
		e"	13.9900	Conductivity (σ):	1.37	1.37	-0.48	5
1/20/2016	Body 1750	e'	51.3300	Relative Permittivity (ϵ_r):	51.33	53.44	-3.95	5
		e"	15.1600	Conductivity (σ):	1.48	1.49	-0.74	5
	Body 1710	e'	51.4500	Relative Permittivity (ϵ_r):	51.45	53.54	-3.91	5
		e"	15.0500	Conductivity (σ):	1.43	1.46	-2.09	5
	Body 1755	e'	51.3000	Relative Permittivity (ϵ_r):	51.30	53.43	-3.98	5
		e"	15.1700	Conductivity (σ):	1.48	1.49	-0.60	5

SAR Lab 3

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit \pm (%)	
1/19/2016	Body 1900	e'	52.3700	Relative Permittivity (ϵ_r):	52.37	53.30	-1.74	5
		e"	14.5600	Conductivity (σ):	1.54	1.52	1.20	5
	Body 1850	e'	52.6100	Relative Permittivity (ϵ_r):	52.61	53.30	-1.29	5
		e"	14.4900	Conductivity (σ):	1.49	1.52	-1.94	5
	Body 1910	e'	52.2800	Relative Permittivity (ϵ_r):	52.28	53.30	-1.91	5
		e"	14.5800	Conductivity (σ):	1.55	1.52	1.87	5
1/19/2016	Head 1900	e'	39.0500	Relative Permittivity (ϵ_r):	39.05	40.00	-2.38	5
		e"	13.3900	Conductivity (σ):	1.41	1.40	1.04	5
	Head 1850	e'	39.3100	Relative Permittivity (ϵ_r):	39.31	40.00	-1.72	5
		e"	13.3300	Conductivity (σ):	1.37	1.40	-2.06	5
	Head 1910	e'	39.0400	Relative Permittivity (ϵ_r):	39.04	40.00	-2.40	5
		e"	13.4400	Conductivity (σ):	1.43	1.40	1.95	5

SAR Lab 4

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
1/19/2016	Head 2450	e'	37.5900	Relative Permittivity (ϵ_r):	37.59	39.20	-4.11	5
		e"	13.3300	Conductivity (σ):	1.82	1.80	0.88	5
	Head 2410	e'	37.6400	Relative Permittivity (ϵ_r):	37.64	39.28	-4.17	5
		e"	13.2400	Conductivity (σ):	1.77	1.76	0.78	5
	Head 2475	e'	37.4700	Relative Permittivity (ϵ_r):	37.47	39.17	-4.34	5
		e"	13.4100	Conductivity (σ):	1.85	1.83	1.01	5
1/19/2016	Body 2450	e'	52.0700	Relative Permittivity (ϵ_r):	52.07	52.70	-1.20	5
		e"	14.9100	Conductivity (σ):	2.03	1.95	4.16	5
	Body 2410	e'	52.0800	Relative Permittivity (ϵ_r):	52.08	52.76	-1.29	5
		e"	14.8500	Conductivity (σ):	1.99	1.91	4.32	5
	Body 2475	e'	52.0100	Relative Permittivity (ϵ_r):	52.01	52.67	-1.25	5
		e"	14.9700	Conductivity (σ):	2.06	1.99	3.78	5
1/20/2016	Head 750	e'	40.3200	Relative Permittivity (ϵ_r):	40.32	41.96	-3.91	5
		e"	21.6300	Conductivity (σ):	0.90	0.89	1.00	5
	Head 700	e'	40.9600	Relative Permittivity (ϵ_r):	40.96	42.22	-2.98	5
		e"	21.9800	Conductivity (σ):	0.86	0.89	-3.79	5
	Head 790	e'	39.8600	Relative Permittivity (ϵ_r):	39.86	41.76	-4.54	5
		e"	21.2800	Conductivity (σ):	0.93	0.90	4.31	5
1/20/2016	Body 750	e'	54.1400	Relative Permittivity (ϵ_r):	54.14	55.55	-2.53	5
		e"	23.1800	Conductivity (σ):	0.97	0.96	0.37	5
	Body 700	e'	54.6600	Relative Permittivity (ϵ_r):	54.66	55.74	-1.93	5
		e"	23.6200	Conductivity (σ):	0.92	0.96	-4.16	5
	Body 790	e'	53.7100	Relative Permittivity (ϵ_r):	53.71	55.39	-3.04	5
		e"	22.7600	Conductivity (σ):	1.00	0.97	3.48	5

8.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Room	Date	Tissue Type	Dipole Type _Serial #	Dipole Cal. Due Data	Measured Results for 1g SAR				Measured Results for 10g SAR				Plot No.
					Zoom Scan to 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10 %	Zoom Scan to 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10 %	
1	1/21/2016	Head	D835V2 SN:4d142	9/23/2016	0.95	9.46	9.27	2.05	0.62	6.24	6.01	3.83	
1	1/21/2016	Body	D835V2 SN:4d142	9/23/2016	1.01	10.10	9.41	7.33	0.66	6.64	6.18	7.44	1,2
2	1/20/2016	Head	D1750V2 SN:1050	4/15/2016	3.66	36.60	36.40	0.55	1.93	19.30	19.30	0.00	
2	1/20/2016	Body	D1750V2 SN:1050	4/15/2016	3.85	38.50	37.00	4.05	2.05	20.50	19.90	3.02	3,4
3	1/19/2016	Body	D1900V2 SN:5d163	9/21/2016	3.84	38.40	39.90	-3.76	2.02	20.20	21.00	-3.81	5,6
3	1/19/2016	Head	D1900V2 SN:5d163	9/21/2016	4.13	41.30	40.10	2.99	2.12	21.20	21.00	0.95	
4	1/19/2016	Head	D2450V2 SN:706	5/11/2016	5.18	51.80	52.60	-1.52	2.34	23.40	24.60	-4.88	
4	1/19/2016	Body	D2450V2 SN:706	5/11/2016	5.29	52.90	51.30	3.12	2.43	24.30	24.00	1.25	7,8
4	1/20/2016	Head	D750V3 SN:1019	3/11/2016	0.82	8.21	8.44	-2.73	0.54	5.40	5.50	-1.82	
4	1/20/2016	Body	D750V3 SN:1019	3/11/2016	0.92	9.15	8.53	7.27	0.61	6.10	5.68	7.39	9,10

9. Conducted Output Power Measurements

9.1. GSM

Per KDB 941225 D01 3G SAR Procedures:

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

GSM850 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Max. Pwr	
						Burst (dBm)	Frame (dBm)
850	GPRS (GMSK)	CS1	1	128	824.2	33.2	24.2
				190	836.6	33.2	24.2
				251	848.8	33.2	24.2
			2	128	824.2	31.7	25.7
				190	836.6	31.7	25.7
				251	848.8	31.7	25.7
	EGPRS (8PSK)	MCS5	1	128	824.2	26.8	17.8
				190	836.6	27.0	18.0
				251	848.8	27.1	18.1
			2	128	824.2	26.1	20.1
				190	836.6	26.2	20.2
				251	848.8	26.2	20.2

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- GMSK (GPRS) mode with 2 time slots, based on the output power measurements above.
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

GSM1900 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Max. Pwr	
						Burst (dBm)	Frame (dBm)
1900	GPRS (GMSK)	CS1	1	512	1850.2	29.6	20.6
				661	1880.0	29.4	20.4
				810	1909.8	29.5	20.5
			2	512	1850.2	27.8	21.8
				661	1880.0	27.7	21.7
				810	1909.8	27.8	21.8
	EGPRS (8PSK)	MCS5	1	512	1850.2	25.2	16.2
				661	1880.0	25.2	16.2
				810	1909.8	25.2	16.2
			2	512	1850.2	24.1	18.1
				661	1880.0	24.1	18.1
				810	1909.8	24.1	18.1

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- GMSK (GPRS) mode with 2 time slots, based on the output power measurements above.
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

9.2. W-CDMA

Release 99 Setup Procedures used to establish the test signals

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA Setup Procedures used to establish the test signals

The following 4 Sub-tests were completed according to Release 5 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

Mode	Subtest	HSDPA	HSDPA	HSDPA	HSDPA
		1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	11/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
MPR (dB)	0	0	0.5	0.5	
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
$A_{hs}=\beta_{hs}/\beta_c$	30/15				

HSPA (HSDPA & HSUPA) Setup Procedures used to establish the test signals

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	15/1
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15	56/75	47/15
CM (dB)	1	3	2	3	1	
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	A _{hs} = β_{hs}/β_c	30/15				
HSUPA Specific Settings	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
Reference E-TFCI PO	27	27	27	27	27	
Maximum Channelization Codes	2xSF2				SF4	

W-CDMA Band II Measured Results

Band	Mode		UL Ch No.	Freq. (MHz)	MPR (dB)	Max. Pwr (dBm)
W-CDMA Band II	Rel 99	RMC, 12.2 kbps	9262	1852.4	N/A	22.1
			9400	1880.0	N/A	22.1
			9538	1907.6	N/A	22.1
	HSDPA	Subtest 1	9262	1852.4	0	22.1
			9400	1880.0	0	22.0
			9538	1907.6	0	22.1
		Subtest 2	9262	1852.4	0	22.1
			9400	1880.0	0	22.1
			9538	1907.6	0	22.0
		Subtest 3	9262	1852.4	0.5	21.6
			9400	1880.0	0.5	21.5
			9538	1907.6	0.5	21.6
		Subtest 4	9262	1852.4	0.5	21.6
			9400	1880.0	0.5	21.5
			9538	1907.6	0.5	21.5
	HSUPA	Subtest 1	9262	1852.4	0	21.8
			9400	1880.0	0	21.5
			9538	1907.6	0	21.4
		Subtest 2	9262	1852.4	2	20.6
			9400	1880.0	2	20.2
			9538	1907.6	2	20.0
		Subtest 3	9262	1852.4	1	21.2
			9400	1880.0	1	20.8
			9538	1907.6	1	20.7
		Subtest 4	9262	1852.4	2	20.6
			9400	1880.0	2	20.4
			9538	1907.6	2	20.3
		Subtest 5	9262	1852.4	0	22.2
			9400	1880.0	0	22.1
			9538	1907.6	0	22.1

W-CDMA Band IV Measured Results

Band	Mode		UL Ch No.	Freq. (MHz)	MPR (dB)	Max. Pwr (dBm)	
W-CDMA Band IV	Rel 99	RMC, 12.2 kbps	1312	1712.4	N/A	22.1	
			1413	1732.6	N/A	22.1	
			1513	1752.6	N/A	22.2	
	HSDPA	Subtest 1	1312	1712.4	0	22.0	
			1413	1732.6	0	22.0	
			1513	1752.6	0	22.1	
		Subtest 2	1312	1712.4	0	22.1	
			1413	1732.6	0	22.0	
			1513	1752.6	0	22.1	
		Subtest 3	1312	1712.4	0.5	21.6	
			1413	1732.6	0.5	21.4	
			1513	1752.6	0.5	21.5	
		Subtest 4	1312	1712.4	0.5	21.4	
			1413	1732.6	0.5	21.5	
			1513	1752.6	0.5	21.5	
		HSUPA	Subtest 1	1312	1712.4	0	21.8
				1413	1732.6	0	21.6
				1513	1752.6	0	21.2
	Subtest 2		1312	1712.4	2	19.9	
			1413	1732.6	2	20.3	
			1513	1752.6	2	20.6	
	Subtest 3		1312	1712.4	1	20.9	
			1413	1732.6	1	20.9	
			1513	1752.6	1	20.7	
	Subtest 4		1312	1712.4	2	20.4	
			1413	1732.6	2	20.3	
			1513	1752.6	2	20.7	
	Subtest 5		1312	1712.4	0	22.0	
			1413	1732.6	0	22.1	
			1513	1752.6	0	22.2	

W-CDMA Band V Measured Results

Band	Mode		UL Ch No.	Freq. (MHz)	MPR (dB)	Max. Pwr (dBm)	
W-CDMA Band V	Rel 99	RMC, 12.2 kbps	4132	826.4	N/A	23.4	
			4183	836.6	N/A	23.4	
			4233	846.6	N/A	23.4	
	HSDPA	Subtest 1	4132	826.4	0	23.3	
			4183	836.6	0	23.4	
			4233	846.6	0	23.3	
		Subtest 2	4132	826.4	0	23.2	
			4183	836.6	0	23.2	
			4233	846.6	0	23.2	
		Subtest 3	4132	826.4	0.5	22.2	
			4183	836.6	0.5	22.2	
			4233	846.6	0.5	22.2	
		Subtest 4	4132	826.4	0.5	22.1	
			4183	836.6	0.5	22.3	
			4233	846.6	0.5	22.1	
		HSUPA	Subtest 1	4132	826.4	0	22.8
				4183	836.6	0	23.0
				4233	846.6	0	22.8
	Subtest 2		4132	826.4	2	21.6	
			4183	836.6	2	21.6	
			4233	846.6	2	21.2	
	Subtest 3		4132	826.4	1	22.2	
			4183	836.6	1	22.1	
			4233	846.6	1	21.8	
	Subtest 4		4132	826.4	2	21.7	
			4183	836.6	2	21.7	
			4233	846.6	2	21.6	
	Subtest 5		4132	826.4	0	23.3	
			4183	836.6	0	23.4	
			4233	846.6	0	23.2	

9.3. LTE

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE Band 2 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1860 MHz	1880 MHz	1900 MHz
LTE Band 2	20	QPSK	1	0	0	22.2	22.1	22.3
			1	49	0	22.0	22.2	22.3
			1	99	0	22.0	22.0	22.1
			50	0	1	21.0	21.1	21.1
			50	24	1	20.9	21.0	21.1
			50	50	1	20.9	21.0	21.0
			100	0	1	21.0	21.0	21.0
		16QAM	1	0	1	21.5	21.2	21.3
			1	49	1	21.3	20.7	21.3
			1	99	1	21.2	21.0	20.8
			50	0	2	20.0	20.0	20.1
			50	24	2	19.7	20.0	20.0
			50	50	2	19.7	20.0	20.1
			100	0	2	20.1	19.9	20.1
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1857.5 MHz	1880 MHz	1902.5 MHz
LTE Band 2	15	QPSK	1	0	0	22.2	22.2	22.2
			1	37	0	22.0	22.0	22.2
			1	74	0	21.9	21.9	22.1
			36	0	1	21.0	21.0	21.1
			36	20	1	21.1	20.9	21.0
			36	39	1	20.9	21.0	20.9
			75	0	1	21.0	20.9	21.0
		16QAM	1	0	1	21.3	21.2	21.4
			1	37	1	21.2	21.4	21.3
			1	74	1	21.3	21.4	21.3
			36	0	2	20.0	20.1	20.1
			36	20	2	19.9	20.0	20.0
			36	39	2	19.9	19.9	20.1
			75	0	2	20.0	19.9	20.0
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1855 MHz	1880 MHz	1905 MHz
LTE Band 2	10	QPSK	1	0	0	22.2	22.1	22.2
			1	25	0	22.1	21.9	22.2
			1	49	0	22.1	21.7	22.0
			25	0	1	21.0	21.0	21.0
			25	12	1	20.9	21.0	21.1
			25	25	1	21.0	20.9	21.0
			50	0	1	21.0	20.9	21.0
		16QAM	1	0	1	21.6	21.3	21.3
			1	25	1	21.6	21.2	21.4
			1	49	1	21.5	21.2	21.5
			25	0	2	20.3	20.2	19.9
			25	12	2	20.2	20.3	20.0
			25	25	2	20.1	20.1	19.9
			50	0	2	20.1	19.9	20.0

LTE Band 2 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1852.5 MHz	1880 MHz	1907.5 MHz
LTE Band 2	5	QPSK	1	0	0	21.7	21.7	21.7
			1	12	0	22.1	21.6	22.1
			1	24	0	21.5	21.6	22.0
			12	0	1	21.0	20.9	21.1
			12	7	1	20.9	20.9	21.0
			12	13	1	20.9	20.9	20.9
		16QAM	25	0	1	20.9	20.9	21.0
			1	0	1	20.9	21.0	21.0
			1	12	1	20.8	20.8	21.1
			1	24	1	20.7	20.9	20.9
			12	0	2	19.7	19.7	20.0
			12	7	2	19.8	19.7	19.9
			12	13	2	19.7	19.7	19.9
			25	0	2	20.2	20.0	20.0

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1851.5 MHz	1880 MHz	1908.5 MHz
LTE Band 2	3	QPSK	1	0	0	21.9	21.9	22.1
			1	7	0	22.0	21.9	22.0
			1	14	0	22.0	21.8	22.1
			6	0	1	20.9	20.9	21.0
			6	3	1	21.0	20.9	21.0
			6	5	1	21.0	20.9	21.0
		16QAM	15	0	1	21.0	20.9	21.2
			1	0	1	21.4	21.2	21.0
			1	7	1	21.6	21.3	20.9
			1	14	1	21.6	21.2	21.0
			6	0	2	20.1	20.2	20.1
			6	3	2	20.1	20.2	20.0
			6	5	2	20.1	20.3	20.0
			15	0	2	20.2	19.9	20.0

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1850.7 MHz	1880 MHz	1909.3 MHz
LTE Band 2	1.4	QPSK	1	0	0	22.1	21.7	21.9
			1	2	0	22.1	21.7	21.9
			1	5	0	22.1	22.0	21.9
			3	0	0	22.0	21.9	22.1
			3	1	0	22.1	22.0	22.0
			3	2	0	22.1	22.0	22.0
		16QAM	6	0	1	20.9	20.9	21.1
			1	0	1	21.6	21.2	21.3
			1	2	1	21.6	21.2	21.4
			1	5	1	21.6	21.4	21.2
			3	0	1	21.1	20.8	21.0
			3	1	1	21.1	20.8	21.1
			3	2	1	21.2	20.8	20.9
			6	0	2	20.0	19.6	20.0

LTE Band 4 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1732.5 MHz		
LTE Band 4	20	QPSK	1	0	0			
			1	49	0			
			1	99	0			
			50	0	1			
			50	24	1			
			50	50	1			
		16QAM	100	0	1			
			1	0	1			
			1	49	1			
			1	99	1			
			50	0	2			
			50	24	2			
			50	50	2			
		100	0	2				

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1717.5 MHz	1732.5 MHz	1747.5 MHz
LTE Band 4	15	QPSK	1	0	0	22.6	22.4	22.4
			1	37	0	22.3	22.3	22.3
			1	74	0	22.2	22.1	22.3
			36	0	1	21.4	21.3	21.3
			36	20	1	21.3	21.3	21.2
			36	39	1	21.2	21.2	21.2
			75	0	1	21.1	21.2	21.2
		16QAM	1	0	1	21.8	21.9	21.5
			1	37	1	21.6	21.8	21.3
			1	74	1	21.6	21.7	21.4
			36	0	2	20.5	20.5	20.4
			36	20	2	20.4	20.4	20.2
			36	39	2	20.4	20.1	20.2
			75	0	2	20.0	20.2	20.2

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1715 MHz	1732.5 MHz	1750 MHz
LTE Band 4	10	QPSK	1	0	0	22.3	22.3	22.3
			1	25	0	22.2	22.4	22.3
			1	49	0	22.1	22.0	22.0
			25	0	1	21.3	21.3	21.3
			25	12	1	21.3	21.3	21.2
			25	25	1	21.1	21.1	21.1
		16QAM	50	0	1	21.2	21.3	21.2
			1	0	1	21.6	21.4	21.3
			1	25	1	21.6	21.5	21.5
			1	49	1	21.3	21.3	21.5
			25	0	2	20.2	20.4	20.1
			25	12	2	20.1	20.4	20.2
			25	25	2	20.3	20.2	20.2
			50	0	2	20.4	20.2	20.3

Note(s):

20 MHz Bandwidth does not support at least three non-overlapping channels. When a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing; therefore, the requirement for H, M and L channels may not fully apply per KDB 941225 D05 SAR for LTE Devices

LTE Band 4 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1712.5 MHz	1732.5 MHz	1752.5 MHz
LTE Band 4	5	QPSK	1	0	0	22.2	22.1	22.4
			1	12	0	22.4	22.4	22.3
			1	24	0	22.1	22.1	22.2
			12	0	1	21.3	21.2	21.2
			12	7	1	21.2	21.2	21.2
			12	13	1	21.3	21.2	21.2
			25	0	1	21.3	21.2	21.2
		16QAM	1	0	1	21.5	21.1	21.8
			1	12	1	21.2	21.0	21.5
			1	24	1	21.5	21.1	21.5
			12	0	2	20.4	20.1	20.3
			12	7	2	20.3	20.3	20.2
			12	13	2	20.2	20.1	20.3
			25	0	2	20.3	20.3	20.2
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1711.5 MHz	1732.5 MHz	1753.5 MHz
LTE Band 4	3	QPSK	1	0	0	22.3	22.2	22.3
			1	7	0	22.2	22.4	22.6
			1	14	0	22.2	22.3	22.6
			6	0	1	21.2	21.2	21.3
			6	3	1	21.2	21.2	21.2
			6	5	1	21.3	21.2	21.2
			15	0	1	21.2	21.3	21.2
		16QAM	1	0	1	21.4	21.2	21.6
			1	7	1	21.3	21.1	21.5
			1	14	1	21.4	21.1	21.4
			6	0	2	20.4	20.5	20.2
			6	3	2	20.4	20.5	20.2
			6	5	2	20.4	20.5	19.9
			15	0	2	20.2	20.4	20.2
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						1710.7 MHz	1732.5 MHz	1754.3 MHz
LTE Band 4	1.4	QPSK	1	0	0	22.4	22.1	22.2
			1	2	0	22.4	22.2	22.4
			1	5	0	22.4	22.0	22.2
			3	0	0	22.4	22.3	22.3
			3	1	0	22.4	22.2	22.5
			3	2	0	22.3	22.2	22.3
			6	0	1	21.2	21.2	21.2
		16QAM	1	0	1	21.9	21.5	21.5
			1	2	1	22.0	21.7	21.5
			1	5	1	22.0	21.6	21.4
			3	0	1	21.3	21.3	21.2
			3	1	1	21.1	21.3	21.0
			3	2	1	21.0	21.4	21.1
			6	0	2	20.0	20.4	20.4

LTE Band 5 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						836.5 MHz		
LTE Band 5	10	QPSK	1	0	0		23.7	
			1	24	0		23.9	
			1	49	0		23.8	
			25	0	1		22.7	
			25	12	1		22.7	
			25	24	1		22.7	
		16QAM	1	0	1		23.0	
			1	24	1		23.0	
			1	49	1		23.0	
			25	0	2		21.8	
			25	12	2		21.9	
			25	24	2		21.9	
			50	0	2		21.7	
			50	0	2		21.7	

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						826.5 MHz	836.5 MHz	846.5 MHz
LTE Band 5	5	QPSK	1	0	0	24.0	23.7	23.5
			1	12	0	23.8	23.9	23.8
			1	24	0	23.7	23.7	23.6
			12	0	1	22.8	22.6	22.7
			12	7	1	22.7	22.6	22.7
			12	13	1	22.7	22.7	22.7
		16QAM	25	0	1	22.8	22.7	22.7
			1	0	1	23.2	22.5	22.6
			1	12	1	23.1	22.7	22.2
			1	24	1	22.6	22.9	22.5
			12	0	2	21.7	21.5	21.6
			12	7	2	21.7	21.5	21.6
			12	13	2	21.7	21.6	21.7
			25	0	2	21.8	21.8	21.9

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						825.5 MHz	836.5 MHz	847.5 MHz
LTE Band 5	3	QPSK	1	0	0	23.8	23.8	24.0
			1	8	0	23.7	23.8	23.9
			1	14	0	23.8	23.9	24.1
			8	0	1	22.7	22.7	22.8
			8	4	1	22.7	22.7	22.7
			8	7	1	22.7	22.7	22.7
		16QAM	15	0	1	22.8	22.7	22.8
			1	0	1	23.0	22.6	23.3
			1	8	1	23.1	23.2	23.3
			1	14	1	23.0	23.2	23.3
			8	0	2	21.9	21.9	21.8
			8	4	2	21.8	21.9	21.4
			8	7	2	21.8	21.8	21.6
			15	0	2	21.6	21.5	21.7

Note(s):

10 MHz Bandwidth does not support at least three non-overlapping channels. When a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing; therefore, the requirement for H, M and L channels may not fully apply per KDB 941225 D05 SAR for LTE Devices

LTE Band 5 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						824.7 MHz	836.5 MHz	848.3 MHz
LTE Band 5	1.4	QPSK	1	0	0	23.7	23.5	23.7
			1	3	0	23.9	23.5	23.7
			1	5	0	23.9	23.7	23.6
			3	0	0	23.8	23.7	23.8
			3	1	0	23.9	23.7	23.9
			3	3	0	23.9	23.8	23.9
		16QAM	6	0	1	22.8	22.8	22.6
			1	0	1	23.2	23.2	22.9
			1	3	1	23.3	23.2	23.0
			1	5	1	23.3	23.1	22.9
			3	0	1	22.8	22.6	22.8
			3	1	1	22.8	22.6	22.7
			3	3	1	23.0	22.7	22.9
			6	0	2	22.1	21.4	21.9

LTE Band 12 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						707.5 MHz		
LTE Band 12	10	QPSK	1	0	0		23.9	
			1	25	0		23.9	
			1	49	0		23.9	
			25	0	1		22.9	
			25	12	1		23.1	
			25	25	1		23.0	
			50	0	1		22.9	
		16QAM	1	0	1		23.4	
			1	25	1		23.0	
			1	49	1		23.3	
			25	0	2		22.2	
			25	12	2		22.0	
			25	25	2		22.0	
			50	0	2		22.0	
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						700.5 MHz	707.5 MHz	714.5 MHz
LTE Band 12	5	QPSK	1	0	0	24.1	24.1	23.8
			1	12	0	24.0	24.3	23.9
			1	24	0	24.1	23.8	23.9
			12	0	1	23.0	23.1	22.9
			12	7	1	22.9	23.0	23.0
			12	13	1	22.9	22.9	22.9
			25	0	1	22.9	22.9	22.9
		16QAM	1	0	1	23.0	23.1	22.8
			1	12	1	23.3	23.1	22.8
			1	24	1	23.3	23.2	22.9
			12	0	2	22.0	21.9	21.8
			12	7	2	22.1	22.0	21.9
			12	13	2	22.1	21.9	21.8
			25	0	2	22.1	22.1	21.9
Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						700.5 MHz	707.5 MHz	714.5 MHz
LTE Band 12	3	QPSK	1	0	0	23.9	24.1	24.0
			1	8	0	23.9	24.3	24.0
			1	14	0	24.0	24.2	23.9
			8	0	1	23.0	23.1	22.8
			8	4	1	23.0	23.0	22.9
			8	7	1	23.1	23.0	22.9
			15	0	1	23.0	23.0	22.9
		16QAM	1	0	1	23.2	23.0	23.3
			1	8	1	23.1	23.0	23.2
			1	14	1	23.2	23.4	23.3
			8	0	2	22.1	22.3	22.0
			8	4	2	22.2	22.0	21.8
			8	7	2	22.1	22.0	21.8
			15	0	2	22.1	22.1	21.9

Note(s):

10 MHz Bandwidth does not support at least three non-overlapping channels. When a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing; therefore, the requirement for H, M and L channels may not fully apply per KDB 941225 D05 SAR for LTE Devices

LTE Band 12 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	MPR	Max. Avg Pwr (dBm)		
						700.5 MHz	707.5 MHz	714.5 MHz
LTE Band 12	1.4	QPSK	1	0	0	23.9	24.2	24.0
			1	3	0	23.9	24.2	24.0
			1	5	0	24.2	24.3	23.8
			3	0	0	24.1	24.0	23.9
			3	1	0	24.0	24.1	24.0
			3	3	0	24.1	24.3	24.0
		16QAM	6	0	1	23.0	23.1	23.0
			1	0	1	23.4	23.4	23.1
			1	3	1	23.3	23.4	23.3
			1	5	1	23.2	23.3	23.1
			3	0	1	23.2	22.9	22.9
			3	1	1	23.1	23.0	22.7
			3	3	1	23.1	23.1	22.8
			6	0	2	21.8	21.9	21.9

9.4. Wi-Fi 2.4GHz (DTS Band)

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)
2.4	802.11b	1 Mbps	1	2412	16.0	16.0	Yes	
			6	2437	16.0			
			11	2462	16.0			
	802.11g	6 Mbps	1	2412	Not Required	12.0	No	1
			6	2437		13.0		
			11	2462				
	802.11n (HT20)	6.5 Mbps	1	2412	Not Required	11.0	No	1
			6	2437				
			11	2462				

Note(s):

- Output Power and SAR is not required for 802.11g/n HT20 channels when the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

9.5. Bluetooth

Maximum tune-up tolerance limit is 9.5 dBm. This power level qualifies for exclusion of SAR testing.

10. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:

With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

KDB 941225 D01 SAR test for 3G devices:

When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

KDB 941225 D05 SAR for LTE Devices:

SAR test reduction is applied using the following criteria:

- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel.
- When the reported SAR is > 0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel.
- Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg. Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg.
- Testing for 16-QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of QPSK.
- Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.
- For LTE bands that do not support at least three non-overlapping channels in certain channel bandwidths, test the available non-overlapping channels instead. When a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing; therefore, the requirement for H, M and L channels may not fully apply.

KDB 248227 D01 SAR meas for 802.11 v02r02:

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
 - For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
 - The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is ≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the *Maximum Value of SAR (measured)*. The position that produced the highest *Maximum Value of SAR* is considered the worst case position; thus used as the initial test position.

10.1. GSM850

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	190	836.6	33.2	33.2	0.365	0.365	1
			Left Tilt	190	836.6	33.2	33.2	0.229	0.229	
			Right Touch	190	836.6	33.2	33.2	0.459	0.459	
			Right Tilt	190	836.6	33.2	33.2	0.269	0.269	
Head (VoIP)	GPRS 2 Slot	0	Left Touch	190	836.6	31.7	31.7	0.492	0.492	2
			Left Tilt	190	836.6	31.7	31.7	0.265	0.265	
			Right Touch	190	836.6	31.7	31.7	0.578	0.578	
			Right Tilt	190	836.6	31.7	31.7	0.364	0.364	
Body	Voice	10	Rear	190	836.6	33.2	33.2	0.388	0.388	3
			Front	190	836.6	33.2	33.2	0.352	0.352	
Body (VoIP) & Hotspot	GPRS 2 Slot	10	Rear	190	836.6	31.7	31.7	0.558	0.558	4
			Front	190	836.6	31.7	31.7	0.518	0.518	
Hotspot			Edge 2	190	836.6	31.7	31.7	0.425	0.425	
			Edge 3	190	836.6	31.7	31.7	0.423	0.423	
			Edge 4	190	836.6	31.7	31.7	0.281	0.281	
				190	836.6	31.7	31.7	0.281	0.281	

10.2. GSM1900

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	661	1880.0	29.7	29.4	0.292	0.313	5
			Left Tilt	661	1880.0	29.7	29.4	0.150	0.161	
			Right Touch	661	1880.0	29.7	29.4	0.302	0.324	
			Right Tilt	661	1880.0	29.7	29.4	0.101	0.108	
Head (VoIP)	GPRS 2 Slot	0	Left Touch	661	1880.0	28.2	27.7	0.369	0.414	6
			Left Tilt	661	1880.0	28.2	27.7	0.171	0.192	
			Right Touch	661	1880.0	28.2	27.7	0.360	0.404	
			Right Tilt	661	1880.0	28.2	27.7	0.119	0.134	
Body	Voice	10	Rear	661	1880.0	29.7	29.4	0.368	0.394	7
			Front	661	1880.0	29.7	29.4	0.432	0.463	
Body (VoIP) & Hotspot	GPRS 2 Slot	10	Rear	661	1880.0	28.2	27.7	0.466	0.523	8
			Front	661	1880.0	28.2	27.7	0.525	0.589	
Hotspot			Edge 3	661	1880.0	28.2	27.7	0.300	0.337	
			Edge 4	661	1880.0	28.2	27.7	0.350	0.393	
				661	1880.0	28.2	27.7	0.350	0.393	
				661	1880.0	28.2	27.7	0.350	0.393	

10.3. W-CDMA Band II

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC 12.2 kbps	0	Left Touch	9400	1880.0	22.7	22.1	0.545	0.626	9
			Left Tilt	9400	1880.0	22.7	22.1	0.277	0.318	
			Right Touch	9400	1880.0	22.7	22.1	0.511	0.587	
			Right Tilt	9400	1880.0	22.7	22.1	0.182	0.209	
Body & Hotspot	Rel 99 RMC 12.2 kbps	10	Rear	9262	1852.4	22.7	22.1	0.840	0.964	
				9400	1880.0	22.7	22.1	0.831	0.954	
				9538	1907.6	22.7	22.1	0.796	0.914	
			Front	9262	1852.4	22.7	22.1	0.862	0.990	
				9400	1880.0	22.7	22.1	0.882	1.013	
9538	1907.6	22.7	22.1	0.899	1.032	10				
Hotspot	Rel 99 RMC 12.2 kbps	10	Edge 3	9400	1880.0	22.7	22.1	0.488	0.560	
			Edge 4	9400	1880.0	22.7	22.1	0.509	0.584	

10.4. W-CDMA Band IV

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC 12.2 kbps	0	Left Touch	1413	1732.6	22.7	22.1	0.472	0.542	11
			Left Tilt	1413	1732.6	22.7	22.1	0.272	0.312	
			Right Touch	1413	1732.6	22.7	22.1	0.442	0.507	
			Right Tilt	1413	1732.6	22.7	22.1	0.178	0.204	
Body & Hotspot	Rel 99 RMC 12.2 kbps	10	Rear	1312	1712.4	22.7	22.1	0.722	0.829	
				1413	1732.6	22.7	22.1	0.734	0.843	
				1513	1752.6	22.7	22.2	0.789	0.885	12
			Front	1312	1712.4	22.7	22.1	0.688	0.790	
				1413	1732.6	22.7	22.1	0.717	0.823	
1513	1752.6	22.7	22.2	0.730	0.819					
Hotspot	Rel 99 RMC 12.2 kbps	10	Edge 3	1413	1732.6	22.7	22.1	0.403	0.463	
			Edge 4	1413	1732.6	22.7	22.1	0.432	0.496	

10.5. W-CDMA Band V

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC 12.2 kbps	0	Left Touch	4183	836.6	23.7	23.4	0.452	0.484	
			Left Tilt	4183	836.6	23.7	23.4	0.312	0.334	
			Right Touch	4183	836.6	23.7	23.4	0.556	0.596	13
			Right Tilt	4183	836.6	23.7	23.4	0.310	0.332	
Body & Hotspot	Rel 99 RMC 12.2 kbps	10	Rear	4183	836.6	23.7	23.4	0.475	0.509	14
			Front	4183	836.6	23.7	23.4	0.444	0.476	
Hotspot	Rel 99 RMC 12.2 kbps	10	Edge 2	4183	836.6	23.7	23.4	0.365	0.391	
			Edge 3	4183	836.6	23.7	23.4	0.378	0.405	
			Edge 4	4183	836.6	23.7	23.4	0.261	0.280	

10.6. LTE Band 2 (20MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		Plot No.			
								Tune-up limit	Meas.	Meas.	Scaled				
Head	QPSK	0	Left Touch	18900	1880.0	1	49	22.7	22.2	0.500	0.561	15			
						50	0	21.7	21.1	0.382	0.439				
			Left Tilt	18900	1880.0	1	49	22.7	22.2	0.267	0.300				
						50	0	21.7	21.1	0.223	0.256				
			Right Touch	18900	1880.0	1	49	22.7	22.2	0.496	0.557				
						50	0	21.7	21.1	0.400	0.459				
			Right Tilt	18900	1880.0	1	49	22.7	22.2	0.177	0.199				
						50	0	21.7	21.1	0.150	0.172				
			Body & Hotspot	QPSK	10	Rear	18700	1860.0	1	0	22.7	22.2	0.845	0.948	
									18900	1880.0	1	49	22.7	22.2	0.788
50	0	21.7							21.1		0.616	0.707			
Front	18700	1860.0				1	0	22.7	22.2	0.879	0.986				
						50	0	21.7	21.0	0.724	0.851				
						18900	1880.0	1	49	22.7	22.2	0.900	1.010	16	
50	0	21.7				21.1		0.721	0.828						
Hotspot	QPSK	10				Edge 3	18900	1880.0	1	49	22.7	22.2	0.462	0.518	
									50	0	21.7	21.1	0.368	0.423	
									18900	1880.0	1	49	22.7	22.2	0.506
50	0	21.7				21.1	0.394	0.452							

10.7. LTE Band 4 (20MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		Plot No.			
								Tune-up limit	Meas.	Meas.	Scaled				
Head	QPSK	0	Left Touch	20175	1732.5	1	0	23.2	22.4	0.501	0.602	17			
						50	0	22.2	21.3	0.385	0.474				
			Left Tilt	20175	1732.5	1	0	23.2	22.4	0.234	0.281				
						50	0	22.2	21.3	0.193	0.237				
			Right Touch	20175	1732.5	1	0	23.2	22.4	0.408	0.491				
						50	0	22.2	21.3	0.317	0.390				
			Right Tilt	20175	1732.5	1	0	23.2	22.4	0.171	0.206				
						50	0	22.2	21.3	0.140	0.172				
			Body & Hotspot	QPSK	10	Rear	20175	1732.5	1	0	23.2	22.4	0.752	0.904	
									50	0	22.2	21.3	0.577	0.710	
100	0	22.2							21.2	0.576	0.725				
Front	20175	1732.5				1	0	23.2	22.4	0.758	0.911	18			
						50	0	22.2	21.3	0.596	0.733				
						100	0	22.2	21.2	0.592	0.745				
Hotspot	QPSK	10	Edge 3	20175	1732.5	1	0	23.2	22.4	0.439	0.528				
						50	0	22.2	21.3	0.352	0.433				
			Edge 4	20175	1732.5	1	0	23.2	22.4	0.449	0.540				
						50	0	22.2	21.3	0.357	0.439				

10.8. LTE Band 5 (10MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	
Head	QPSK	0	Left Touch	20525	836.5	1	24	24.4	23.9	0.439	0.493	
						25	0	23.4	22.7	0.338	0.397	
			Left Tilt	20525	836.5	1	24	24.4	23.9	0.283	0.318	
						25	0	23.4	22.7	0.215	0.253	
			Right Touch	20525	836.5	1	24	24.4	23.9	0.550	0.617	19
						25	0	23.4	22.7	0.436	0.512	
			Right Tilt	20525	836.5	1	24	24.4	23.9	0.307	0.344	
						25	0	23.4	22.7	0.247	0.290	
Body & Hotspot	QPSK	10	Rear	20525	836.5	1	24	24.4	23.9	0.602	0.675	20
						25	0	23.4	22.7	0.435	0.511	
			Front	20525	836.5	1	24	24.4	23.9	0.513	0.576	
						25	0	23.4	22.7	0.422	0.496	
Hotspot	QPSK	10	Edge 2	20525	836.5	1	24	24.4	23.9	0.455	0.455	
						25	0	23.4	22.7	0.366	0.366	
			Edge 3	20525	836.5	1	24	24.4	23.9	0.436	0.436	
						25	0	23.4	22.7	0.321	0.321	
			Edge 4	20525	836.5	1	24	24.4	23.9	0.340	0.340	
						25	0	23.4	22.7	0.262	0.262	

10.9. LTE Band 12 (10MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	
Head	QPSK	0	Left Touch	23095	707.5	1	0	24.4	23.9	0.280	0.314	
						25	12	23.4	23.1	0.222	0.238	
			Left Tilt	23095	707.5	1	0	24.4	23.9	0.181	0.203	
						25	12	23.4	23.1	0.147	0.158	
			Right Touch	23095	707.5	1	0	24.4	23.9	0.326	0.366	21
						25	12	23.4	23.1	0.245	0.263	
			Right Tilt	23095	707.5	1	0	24.4	23.9	0.171	0.192	
						25	12	23.4	23.1	0.137	0.147	
Body & Hotspot	QPSK	10	Rear	23095	707.5	1	0	24.4	23.9	0.502	0.563	22
						25	12	23.4	23.1	0.378	0.405	
			Front	23095	707.5	1	0	24.4	23.9	0.395	0.443	
						25	12	23.4	23.1	0.298	0.319	
Hotspot	QPSK	10	Edge 2	23095	707.5	1	0	24.4	23.9	0.454	0.509	
						25	12	23.4	23.1	0.346	0.371	
			Edge 3	23095	707.5	1	0	24.4	23.9	0.154	0.173	
						25	12	23.4	23.1	0.125	0.134	
			Edge 4	23095	707.5	1	0	24.4	23.9	0.287	0.322	
						25	12	23.4	23.1	0.227	0.243	

10.10. Wi-Fi (DTS Band)

Frequency Band	Mode	RF Exposure Conditions	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	
2.4GHz	802.11b 1 Mbps	Head	0	Left Touch	6	2437.0	0.586	16.0	16.0	0.476	0.476	23
				Left Tilt	6	2437.0	0.291	16.0	16.0	0.246	0.246	
				Right Touch	6	2437.0	0.269	16.0	16.0			
				Right Tilt	6	2437.0	0.146	16.0	16.0			
		Body & Hotspot/Wi-Fi Direct	10	Rear	6	2437.0	0.159	16.0	16.0	0.118	0.118	24
				Front	6	2437.0	0.134	16.0	16.0			
		Hotspot/Wi-Fi Direct	10	Edge 1	6	2437.0	0.045	16.0	16.0			
				Edge 2	6	2437.0	0.092	16.0	16.0			

10.11. Bluetooth

Standalone SAR Test Exclusion Considerations & Estimated SAR

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}/x}] \text{ W/kg}$ for test separation distances ≤ 50 mm;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Body-worn Accessory Exposure Conditions

Max. tune-up tolerance limit		Min. test separation distance (mm)	Frequency (GHz)	SAR test exclusion Result*	Test Configuration	Estimated 1-g SAR (W/kg)
(dBm)	(mW)					
9.5	9	10	2.480	1.4	Rear/Front	0.189

Conclusion:

*: The computed value is ≤ 3 ; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

11. SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.8 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.8 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or 3 (1-g or 10-g respectively) or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg ($\sim 10\%$ from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 or 3 (1-g or 10-g respectively).

Frequency Band (MHz)	Air Interface	RF Exposure Conditions	Test Position	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	First Repeated	
						Measured SAR (W/kg)	Largest to Smallest SAR Ratio
700	LTE Band 12	Body & Hotspot	Rear	No	0.502	N/A	N/A
850	GSM 850	Head	Right Touch	No	0.578	N/A	N/A
	WCDMA Band V	Head	Right Touch	No	0.556	N/A	N/A
	LTE Band 5	Body & Hotspot	Rear	No	0.602	N/A	N/A
1900	GSM 1900	Body & Hotspot	Front	No	0.525	N/A	N/A
	WCDMA Band II	Body & Hotspot	Front	No	0.899	N/A	N/A
	LTE Band 2	Body & Hotspot	Front	Yes	0.920	0.851	1.08
1700	LTE Band 4	Body & Hotspot	Front	No	0.758	N/A	N/A
	WCDMA Band IV	Body & Hotspot	Rear	No	0.789	N/A	N/A
2400	Wi-Fi 802.11b/g/n	Head	Left Touch	No	0.476	N/A	N/A

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is < 1.20 .

12. Simultaneous Transmission SAR Analysis

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations		
Head	1	GSM(Voice)	+	DTS
	2	GSM(GPRS/EDGE)	+	DTS
	3	W-CDMA	+	DTS
	4	LTE	+	DTS
Body-w orn	5	GSM(Voice)	+	DTS
	6	GSM(Voice)	+	BT
	7	GSM(GPRS/EDGE)	+	DTS
	8	GSM(GPRS/EDGE)	+	BT
	9	W-CDMA	+	DTS
	10	W-CDMA	+	BT
	11	LTE	+	DTS
	12	LTE	+	BT
Hotspot/Wi-Fi Direct	13	GSM(GPRS/EDGE)	+	DTS
	14	W-CDMA	+	DTS
	15	LTE	+	DTS

Notes:

1. DTS supports Hotspot and Wi-Fi Direct.
2. GPRS/EDGE, W-CDMA and LTE support Hotspot.
3. VoIP is supported in GPRS/EDGE, W-CDMA and LTE.
4. DTS Radio cannot transmit simultaneously with Bluetooth Radio.

12.1. Sum of the SAR for WWAN & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DTS	③ BT	① + ② WWAN + DTS		① + ③ WWAN + BT	
				∑ 1-g SAR	SPLSR (Yes/ No)	∑ 1-g SAR	SPLSR (Yes/ No)
Head	0.626	0.476		1.102	No		
Body-Worn & Hotspot/Wi-Fi Direct	1.032	0.118	0.189	1.150	No	1.221	No

Appendixes

Refer to separated files for the following appendixes.

16I22670-S1V1 SAR_App A Photos & Ant. Locations

16I22670-S1V1 SAR_App B System Check Plots

16I22670-S1V1 SAR_App C Highest Test Plots

16I22670-S1V1 SAR_App D Tissue Ingredients

16I22670-S1V1 SAR_App E Probe Cal. Certificates

16I22670-S1V1 SAR_App F Dipole Cal. Certificates

END OF REPORT