

FCC NFC REPORT

FCC Certification

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.

Address:
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue:
February 05, 2016
Test Site/Location:
HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
Report No.: HCT-R-1602-F009
HCT FRN: 0005866421
IC Recognition No.: 5944A-5

FCC ID : ZNFK520

APPLICANT : LG Electronics MobileComm U.S.A., Inc.

Model(s): LG-K520

Additional Model(s): LGK520, K520

EUT Type: GSM/WCDMA/LTE Phone with Bluetooth4.1LE, WIFI802.11 b/g/n(2.4GHz), NFC, VoIP, Hotspot support

RF Output Field Strength: 11.87 dBuV/m @30 m

Frequency of Operation: 13.5600 MHz

Modulation type: ASK

FCC Classification: Low Power Communication Device – Transmitter

FCC Rule Part(s): FCC Part 15.225 Subpart C

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report prepared by
: Seul Ki Lee
Test Engineer of RF Team

Approved by
: Kyoung Houn Seo
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1602-F009	February 05, 2016	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION.....	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
3.5 STANDARDS.....	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS	7
5.1 FACILITIES	7
5.2 EQUIPMENT	7
6. ANTENNA REQUIREMENTS	7
7. TEST SUMMARY	8
8. RADIATED EMISSION MEASUREMENT	9
8.1. RADIATED EMISSION 9 kHz – 30 MHz	10
8.2. RADIATED EMISSION 30 MHz – 1000 MHz	13
9. EMISSION BANDWIDTH PLOT.....	15
10. FREQUENCY TOLERANCE.....	16
11. POWERLINE CONDUCTE EMISSIONS.....	17
12. LIST OF TEST EQUIPMENT	26
12.1 LIST OF TEST EQUIPMENT(Conducted Test)	26
12.2 LIST OF TEST EQUIPMENT(Radiated Test).....	27

1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc.
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFK520
EUT Type: GSM/WCDMA/LTE Phone with Bluetooth4.1LE, WIFI802.11 b/g/n(2.4GHz), NFC, VoIP, Hotspot support
Model name(s): LG-K520
Additional Model name(s): LGK520, K520
Date(s) of Tests: January 26, 2016 ~ February 05, 2016
Place of Tests: HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
(IC Recognition No. : 5944A-5)

2. EUT DESCRIPTION

Model Name	LG-K520
Additional Model name(s):	LGK520, K520
EUT Type	GSM/WCDMA/LTE Phone with Bluetooth4.1LE, WIFI802.11 b/g/n(2.4GHz), NFC, VoIP, Hotspot support
Power Supply	DC 3.85 V
Battery Infomation	Model: BL-45B1F Type: Li-ion Battery
Frequency of Operation	13.5600 MHz
Transmit Power	11.87 dBuV/m @30 m
Modulation Type	ASK
Antenna Specification	Manufacturer: IM-TECH Antenna type: LOOP Antenna

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2013).

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.225 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10. (Version: 2013).

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3.5 STANDARDS

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance With
FCC Part 15.Subpart C

Regulation	Measurement standard	Range
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(a)	ANSI C63.10:2013	13.553MHz to 13.567MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(d)	ANSI C63.10:2013	outside of the 13.110-14.010 MHz band
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2013	9kHz to 30MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2013	30MHz to 1GHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.207	ANSI C63.10:2013	150kHz to 30MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(e)	ANSI C63.10:2013	0.01% of nominal
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.215(c)	ANSI C63.10:2013	-

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

All equipment(spectrum, antenna, accessory, etc.) for measurement is calibrated in accordance with the requirements of ANSI C63.5 (Version: 2006).

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The 10 m semi anechoic chamber used to collect the Conducted and Radiated data is located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4. Detailed description of test facilities was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned loop, dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. TEST SUMMARY

The results in this report apply only to sample tested

Regulation	Test Type	Range	Result
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(a)	Radiated Electric Field Emissions	13.553MHz to 13.567MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(b)	Radiated Electric Field Emissions	13.410MHz to 13.553MHz and 13.567MHz to 13.710MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(c)	Radiated Electric Field Emission	13.110 MHz to 13.410 MHz and 13.710 MHz to 14.010 MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209 (d)	Radiated Electric Field Emissions	9kHz to 30MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	Radiated Electric Field Emissions	30MHz to 1GHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.207	AC power conducted emissions	150kHz to 30MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(e)	Frequency Stability	0.01% of nominal	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.215(c)	20 dB Bandwidth	-	Pass

8. RADIATED EMISSION MEASUREMENT

Requirement(s): 15.209, 15.225

Except as provided elsewhere in this paragraph the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Minimum Standard: FCC Part 15.225 / 15.209

Rule Part	Frequency (MHz)	Limit
Part 15.209	0.009 ~ 0.490	2400/F(kHz) uV/m@300 m
	0.490 ~1.705	24000/F(kHz) uV/m@30 m
	1.705 ~ 30	30 uV/m@30 m
	30 ~ 88	100 ** uV/m@3 m
	88 ~ 216	150 ** uV/m@3 m
	216 ~ 960	200 ** uV/m@3 m
	Above 960	500 uV/m@3 m


** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

15.225 Operation within the band 13.110 – 14.010 MHz.

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter (= 84 dBuV/m) at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter (=50.5dBuV/m) at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter (=40.5 dBuV/m) at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.
- (e) The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.
- (f) In the case of radio frequency powered tags designed to operate with a device authorized under this section, the tag may be approved with the device or be considered as a separate device subject to its own authorization. Powered tags approved with a device under a single application shall be labeled with the same identification number as the device.

8.1. RADIATED EMISSION 9 kHz – 30 MHz

Test Set-up



Test Procedure

The EUT was placed on a non-conductive table located on a large open test site. The loop antenna was placed at a location 3m from the EUT. Radiated emissions were measured with the loop antenna both parallel and perpendicular to the plane of the EUT loop antenna and with x, y, z planes in EUT.

The limit is converted from microvolts/meter to decibel microvolts/meter. Sample Calculation:

Corrected Amplitude = Raw Amplitude(dB μ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor

The spectrum analyzer is set to:

Frequency Range = 9 kHz ~ 1 GHz

RBW = 9 kHz (9 kHz ~ 30 MHz)
= 120 kHz (30 MHz ~ 1 GHz)

Trace Mode = max hold

Detector Mode = peak / Quasi-peak

Sweep time = auto

Test Results
13.553 MHz-13.567 MHz

Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.5600(H)	31.50	20.37	-40.00	11.87	84.00	72.13
13.5593(V)	27.66	20.37	-40.00	8.03	84.00	75.97

13.410 MHz-13.553 MHz and 13.567 MHz-13.710 MHz

Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.553	22.10	19.49	-40.00	1.59	50.47	48.88
13.567	18.71	19.49	-40.00	-1.80	50.47	52.27

13.110 MHz – 13.410 MHz and 13.710 MHz-14.010 MHz

Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.454	19.66	20.37	-40.00	0.03	50.47	50.44
13.567	19.90	20.37	-40.00	0.27	50.47	50.20

9 kHz -30 MHz


Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
10.7518	12.30	20.62	-40.00	-7.08	29.54	36.62
16.3765	12.49	20.34	-40.00	-7.17	29.54	36.71
27.1169	12.59	20.65	-40.00	-6.76	29.54	36.30
27.1237	12.05	20.65	-40.00	-7.30	29.54	36.84

Note :

1. Distance Correction Below 30MHz = $40\log(3m/30m) = -40$ dB
Measurement Distance : 3 m (Below 30 MHz)
2. Factor = Antenna Factor + Cable Loss
3. Result Level = Read Level + Factor + Distance Correction
4. Margin = Limit – Result Level
5. We have done x, y, z planes in EUT
6. Antenna rotated about its vertical/horizontal axis for maximum response at each azimuth position around the EUT.
7. Worst case of operating mode is type A, analog mode and 106 kbps.

□ RESULT PLOTS

Radiated Emissions (9kHz~30MHz) plot




Date: 28.JAN.2016 01:55:57

Note : Only the worst case plots for Radiated Emissions.

8.2. RADIATED EMISSION 30 MHz – 1000 MHz

Test Set-up



Test Procedures: Radiated emissions were measured according to ANSI C63.10.

The EUT was set to transmit at the highest output power.


The EUT was set 3 meter away from the measuring antenna.

■ Test Results

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
35.47	16.13	11.49	0.62	H	28.24	40	11.76
57.65	15.08	12.2	0.74	H	28.02	40	11.98
85.44	15.75	7.96	0.82	V	24.53	40	15.47
100.19	16.10	9.27	0.88	H	26.25	43.5	17.25
*124.82	15.88	11.64	0.98	H	28.5	43.5	15
144.85	15.89	12.84	1.05	V	29.78	43.5	13.72

Remark

1. Result Level = Read Level + (Antenna Factor+ Cable Loss)
2. Margin = Limit – Result Level
3. '*' is the result for restricted band.

□ RESULT PLOTS**Radiated Emissions (30MHz~1000MHz) plot**

Date: 27.JAN.2016 13:18:17

Note : Only the worst case plots for Radiated Emissions.

9. EMISSION BANDWIDTH PLOT.

Requirement(s):

Test Set-up: The EUT was connected to a spectrum analyzer.

Test Procedure: The 20 dB bandwidth was measured by using a spectrum analyzer.

RBW = Auto

VBW = Auto

Span = Adequately in the operating Tx.

Detector = Peak

Trace mode = Max hold

Allow the trace to stabilize

□ Test Results



10. FREQUENCY TOLERANCE

Procedure: Part 15.225, ANSI 63.10

If required, the operating or transmitting frequency of an intentional radiator should be measured in accordance with the following procedure to ensure that the device operates outside certain precluded frequency bands and within the frequency range. No modulation needs to be supplied to the intentional radiator during these tests, unless modulation is required to produce an output, e.g., single-sideband suppressed carrier transmitters.

The frequency stability of the transmitter is measured by:

- a) Temperature: The temperature is varied from -20°C to + 50°C using an environmental chamber.
- b) For battery operated equipment, the equipment tests shall be performed using a new battery.

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

Measurement Result:

OPERATING FREQUENCY:	13.56 MHz
REFERENCE VOLTAGE:	3.85 VDC
DEVIATION LIMIT:	0.01% = 1356 Hz

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (MHz)	Frequency Dev. (Hz)	Frequency Dev (%)
100%	3.85	-20	13.559790	-210.26	-0.0015506
100%		-10	13.559791	-208.81	-0.0015399
100%		0	13.559805	-195.34	-0.0014406
100%		+10	13.559807	-192.64	-0.0014206
100%		+20(Ref.)	13.559812	-187.85	-0.0013853
100%		+30	13.559817	-183.12	-0.0013504
100%		+40	13.559825	-175.26	-0.0012925
100%		+50	13.559832	-167.91	-0.0012383
115%	4.43	+20	13.559815	-184.56	-0.0013611
85%	3.27	+20	13.559820	-180.29	-0.0013296

11. POWERLINE CONDUCTE EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. The EUT is the device operating below 30 MHz.
 - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
 - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

HCT CO.,LTD.

Test Plots

Unterminate the Antenna

Conducted Emissions (Line 1)

EMI Auto Test(15)

1 / 2


HCT TEST Report

Common Information

EUT:
Manufacturer:
Test Site:
Operating Conditions:
Operator Name

LG
SHIELD ROOM
NFC MODE _ UNTERMINATION
SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.158000	38.6	9.000	Off	N	9.6	27.0	65.6
0.370000	20.3	9.000	Off	N	9.6	38.2	58.5
0.470000	41.3	9.000	Off	N	9.6	15.2	56.5
0.474000	44.5	9.000	Off	N	9.6	11.9	56.4
0.496000	32.8	9.000	Off	N	9.6	23.3	56.1
0.502000	29.8	9.000	Off	N	9.6	26.2	56.0
1.082000	35.8	9.000	Off	N	9.7	20.2	56.0
1.110000	31.9	9.000	Off	N	9.7	24.1	56.0
1.142000	33.0	9.000	Off	N	9.7	23.0	56.0
1.166000	35.7	9.000	Off	N	9.7	20.3	56.0
1.170000	33.7	9.000	Off	N	9.7	22.3	56.0
1.882000	34.9	9.000	Off	N	9.7	21.1	56.0
5.238000	31.5	9.000	Off	N	9.8	28.5	60.0
5.242000	31.2	9.000	Off	N	9.8	28.8	60.0
5.248000	30.6	9.000	Off	N	9.8	29.4	60.0
5.298000	29.1	9.000	Off	N	9.8	30.9	60.0

2/3/2016

12:53:10

HCT CO.,LTD.

EMI Auto Test(15)

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
5.452000	26.7	9.000	Off	N	9.8	33.3	60.0
5.484000	26.6	9.000	Off	N	9.8	33.4	60.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.160000	29.3	9.000	Off	N	9.6	26.2	55.5
0.370000	8.5	9.000	Off	N	9.6	40.0	48.5
0.468000	18.8	9.000	Off	N	9.6	27.7	46.5
0.500000	14.9	9.000	Off	N	9.6	31.1	46.0
0.502000	15.5	9.000	Off	N	9.6	30.5	46.0
0.570000	15.6	9.000	Off	N	9.6	30.4	46.0
0.940000	19.0	9.000	Off	N	9.7	27.0	46.0
1.038000	29.6	9.000	Off	N	9.7	16.4	46.0
1.142000	27.3	9.000	Off	N	9.7	18.7	46.0
1.166000	28.7	9.000	Off	N	9.7	17.3	46.0
1.170000	27.3	9.000	Off	N	9.7	18.7	46.0
1.914000	21.3	9.000	Off	N	9.7	24.7	46.0
5.248000	18.4	9.000	Off	N	9.8	31.6	50.0
5.278000	19.8	9.000	Off	N	9.8	30.2	50.0
5.282000	20.2	9.000	Off	N	9.8	29.8	50.0
5.452000	17.4	9.000	Off	N	9.8	32.6	50.0
5.482000	19.3	9.000	Off	N	9.8	30.7	50.0
5.486000	18.9	9.000	Off	N	9.8	31.1	50.0

Conducted Emissions (Line 2)

NFC UNTERM L1 REV1


1 / 2

HCT TEST Report

Common Information

EUT: LG-K520
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE _ UNTERMINATION
 Operator Name: SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.158000	38.1	9.000	Off	L1	9.6	27.5	65.6
0.476000	42.6	9.000	Off	L1	9.7	13.8	56.4
0.582000	41.5	9.000	Off	L1	9.7	14.5	56.0
0.792000	36.4	9.000	Off	L1	9.7	19.6	56.0
0.844000	42.4	9.000	Off	L1	9.7	13.6	56.0
0.896000	35.5	9.000	Off	L1	9.7	20.5	56.0
1.848000	39.1	9.000	Off	L1	9.7	16.9	56.0
1.874000	36.1	9.000	Off	L1	9.7	19.9	56.0
1.902000	38.3	9.000	Off	L1	9.7	17.7	56.0
1.928000	39.7	9.000	Off	L1	9.7	16.3	56.0
1.954000	36.6	9.000	Off	L1	9.7	19.4	56.0
2.008000	39.7	9.000	Off	L1	9.8	16.3	56.0
5.242000	30.0	9.000	Off	L1	9.9	30.0	60.0
5.252000	32.1	9.000	Off	L1	9.9	27.9	60.0
5.288000	30.4	9.000	Off	L1	9.9	29.6	60.0
5.296000	32.2	9.000	Off	L1	9.9	27.8	60.0

2/5/2016

9:42:03

HCT CO.,LTD.

NFC UNTERM L1 REV1

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
5.346000	32.0	9.000	Off	L1	9.9	28.0	60.0
6.024000	32.3	9.000	Off	L1	9.9	27.8	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.158000	28.6	9.000	Off	L1	9.6	27.0	55.6
0.476000	28.8	9.000	Off	L1	9.7	17.6	46.4
0.582000	24.7	9.000	Off	L1	9.7	21.3	46.0
0.792000	22.4	9.000	Off	L1	9.7	23.6	46.0
0.844000	32.1	9.000	Off	L1	9.7	13.9	46.0
0.898000	25.0	9.000	Off	L1	9.7	21.0	46.0
1.794000	22.6	9.000	Off	L1	9.7	23.4	46.0
1.848000	26.9	9.000	Off	L1	9.7	19.1	46.0
1.874000	23.2	9.000	Off	L1	9.7	22.8	46.0
1.900000	28.8	9.000	Off	L1	9.7	17.2	46.0
1.928000	27.7	9.000	Off	L1	9.7	18.3	46.0
2.006000	27.9	9.000	Off	L1	9.8	18.1	46.0
5.248000	20.9	9.000	Off	L1	9.9	29.2	50.0
5.274000	20.8	9.000	Off	L1	9.9	29.2	50.0
5.288000	20.4	9.000	Off	L1	9.9	29.6	50.0
5.296000	22.2	9.000	Off	L1	9.9	27.8	50.0
5.346000	21.7	9.000	Off	L1	9.9	28.3	50.0
6.052000	19.9	9.000	Off	L1	9.9	30.1	50.0

2/5/2016

9:42:03

HCT CO.,LTD.

Terminate the Antenna Conducted Emissions (Line 1)

EMI Auto Test(15)


1 / 2

HCT TEST Report

Common Information

EUT: LG-K520
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE _ TERMINATION
 Operator: SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.474000	38.5	9.000	Off	N	9.6	17.9	56.4
0.486000	47.8	9.000	Off	N	9.6	8.4	56.2
0.490000	43.3	9.000	Off	N	9.6	12.9	56.2
0.496000	46.2	9.000	Off	N	9.6	9.9	56.1
0.500000	43.8	9.000	Off	N	9.6	12.2	56.0
0.598000	38.6	9.000	Off	N	9.6	17.4	56.0
0.928000	39.7	9.000	Off	N	9.7	16.3	56.0
0.970000	40.1	9.000	Off	N	9.7	15.9	56.0
1.248000	36.2	9.000	Off	N	9.7	19.8	56.0
1.716000	33.2	9.000	Off	N	9.7	22.8	56.0
1.736000	39.6	9.000	Off	N	9.7	16.4	56.0
1.740000	39.0	9.000	Off	N	9.7	17.0	56.0
5.292000	31.3	9.000	Off	N	9.8	28.7	60.0
5.398000	27.7	9.000	Off	N	9.8	32.3	60.0
5.610000	29.2	9.000	Off	N	9.9	30.8	60.0
5.614000	30.1	9.000	Off	N	9.9	29.9	60.0

2/3/2016

12:38:22

HCT CO., LTD.

EMI Auto Test(15)

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
5.618000	31.3	9.000	Off	N	9.9	28.7	60.0
6.018000	30.0	9.000	Off	N	9.9	30.0	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.486000	39.8	9.000	Off	N	9.6	6.4	46.2
0.496000	27.9	9.000	Off	N	9.6	18.2	46.1
0.604000	33.5	9.000	Off	N	9.6	12.5	46.0
0.646000	33.1	9.000	Off	N	9.6	12.9	46.0
0.824000	22.8	9.000	Off	N	9.7	23.2	46.0
0.868000	22.6	9.000	Off	N	9.7	23.4	46.0
0.888000	31.7	9.000	Off	N	9.7	14.3	46.0
0.928000	31.3	9.000	Off	N	9.7	14.7	46.0
0.970000	31.1	9.000	Off	N	9.7	14.9	46.0
1.010000	30.9	9.000	Off	N	9.7	15.1	46.0
1.248000	28.3	9.000	Off	N	9.7	17.7	46.0
1.736000	29.8	9.000	Off	N	9.7	16.2	46.0
5.170000	21.4	9.000	Off	N	9.8	28.6	50.0
5.176000	21.1	9.000	Off	N	9.8	28.9	50.0
5.214000	21.1	9.000	Off	N	9.8	28.9	50.0
5.218000	20.3	9.000	Off	N	9.8	29.7	50.0
5.248000	19.0	9.000	Off	N	9.8	31.0	50.0
5.252000	20.3	9.000	Off	N	9.8	29.7	50.0

Conducted Emissions (Line 2)

EMI Auto Test(15)


1 / 2

HCT TEST Report

Common Information

EUT: LG-K520
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE _ TERMINATION
 Operator Name: SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.484000	49.0	9.000	Off	L1	9.7	7.3	56.3
0.494000	49.7	9.000	Off	L1	9.7	6.4	56.1
0.498000	49.0	9.000	Off	L1	9.7	7.0	56.0
0.516000	42.6	9.000	Off	L1	9.7	13.4	56.0
0.602000	39.8	9.000	Off	L1	9.7	16.2	56.0
0.828000	37.4	9.000	Off	L1	9.7	18.6	56.0
0.928000	40.3	9.000	Off	L1	9.7	15.7	56.0
1.632000	40.1	9.000	Off	L1	9.7	15.9	56.0
1.646000	40.3	9.000	Off	L1	9.7	15.7	56.0
1.650000	39.9	9.000	Off	L1	9.7	16.1	56.0
1.684000	41.8	9.000	Off	L1	9.7	14.2	56.0
1.688000	42.9	9.000	Off	L1	9.7	13.1	56.0
5.392000	36.0	9.000	Off	L1	9.9	24.0	60.0
5.948000	33.1	9.000	Off	L1	9.9	26.9	60.0
5.988000	33.2	9.000	Off	L1	9.9	26.8	60.0
5.994000	33.0	9.000	Off	L1	9.9	27.0	60.0

2/5/2016

9:52:18

HCT CO.,LTD.

EMI Auto Test(15)

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
6.004000	33.0	9.000	Off	L1	9.9	27.0	60.0
6.034000	33.4	9.000	Off	L1	9.9	26.6	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.486000	39.3	9.000	Off	L1	9.7	6.9	46.2
0.494000	38.9	9.000	Off	L1	9.7	7.2	46.1
0.500000	36.4	9.000	Off	L1	9.7	9.6	46.0
0.578000	25.4	9.000	Off	L1	9.7	20.6	46.0
0.828000	26.0	9.000	Off	L1	9.7	20.0	46.0
0.868000	26.3	9.000	Off	L1	9.7	19.7	46.0
0.928000	29.7	9.000	Off	L1	9.7	16.3	46.0
1.614000	27.3	9.000	Off	L1	9.7	18.7	46.0
1.648000	29.1	9.000	Off	L1	9.7	16.9	46.0
1.652000	30.3	9.000	Off	L1	9.7	15.7	46.0
1.684000	31.0	9.000	Off	L1	9.7	15.0	46.0
1.688000	33.1	9.000	Off	L1	9.7	12.9	46.0
5.392000	26.5	9.000	Off	L1	9.9	23.5	50.0
5.672000	25.6	9.000	Off	L1	9.9	24.4	50.0
5.944000	24.3	9.000	Off	L1	9.9	25.7	50.0
5.948000	24.2	9.000	Off	L1	9.9	25.8	50.0
6.004000	23.8	9.000	Off	L1	9.9	26.2	50.0
6.034000	24.2	9.000	Off	L1	9.9	25.8	50.0

2/5/2016

9:52:18

HCT CO.,LTD.

12. LIST OF TEST EQUIPMENT

12.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216/ LISN	12/28/2015	Annual	100073
Agilent	E4440A/ Spectrum Analyzer	03/18/2015	Annual	US45303008
Agilent	N9020A / SIGNAL ANALYZER	06/30/2015	Annual	MY51110085
Agilent	N9020A / SIGNAL ANALYZER	07/02/2015	Annual	MY50510304
Agilent	N1911A/Power Meter	07/09/2015	Annual	MY45100523
Agilent	N1921A /POWER SENSOR	07/09/2015	Annual	MY45241059
Agilent	87300B/Directional Coupler	11/30/2015	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/15/2015	Annual	5001
Hewlett Packard	E3632A / DC POWER SUPPLY	03/11/2015	Annual	KR75303962
Agilent	8493C / Attenuator(10 dB)	07/23/2015	Annual	07560

12.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	10/10/2014	Biennial	3368
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
CERNEX	CBL18265035 / POWER AMP	07/27/2015	Annual	22966
Schwarzbeck	BBHA 9120D/ Horn Antenna	05/07/2015	Biennial	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/30/2015	Biennial	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	01/15/2016	Annual	839117/011
Rohde & Schwarz	LOOP ANTENNA	02/18/2014	Biennial	100179
CERNEX	CBL06185030 / POWER AMP	07/21/2015	Annual	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2015	Annual	22964