



HCT CO., LTD.

CERTIFICATE OF COMPLIANCE FCC Certification

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.

Address:
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue:

October 28, 2013

Test Site/Location:

HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon,
Icheon-si, Kyunggi-Do, Korea

Report No.: HCTR1310FR18

HCT FRN: 0005866421

FCC ID : ZNFKS1301

APPLICANT : LG Electronics MobileComm U.S.A., Inc.

FCC Model(s): KS1301

EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC

Max. RF Output Power: 5.55 dBm (3.589 mW)

Frequency Range: 2402 MHz -2480 MHz(BT 4.0_Low Energy Mode)

Modulation type GFSK

FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S.C.853(a)

Report prepared by
: Kwang Il Yoon
Test engineer of RF Team

Approved by
: Chang Seok Choi
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

| | | | | | |
|---------------------------------|------------------------------------|--------------------------|---|----------------------|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC | FCC ID: ZNFKS1301 | |



Version

| TEST REPORT NO. | DATE | DESCRIPTION |
|-----------------|------------------|-------------------------|
| HCTR1310FR18 | October 28, 2013 | - First Approval Report |
| | | |
| | | |
| | | |

| | | | | |
|--|---|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC | | FCC ID: ZNFKS1301 |

Table of Contents

| | |
|--|-----|
| 1. GENERAL INFORMATION | 4 |
| 2. EUT DESCRIPTION | 4 |
| 3. TEST METHODOLOGY | 5 |
| 3.1 EUT CONFIGURATION | 5 |
| 3.2 EUT EXERCISE | 5 |
| 3.3 GENERAL TEST PROCEDURES | 5 |
| 3.4 DESCRIPTION OF TEST MODES | 5 |
| 4. INSTRUMENT CALIBRATION..... | 6 |
| 5. FACILITIES AND ACCREDITATIONS | 6 |
| 5.1 FACILITIES | 6 |
| 5.2 EQUIPMENT | 6 |
| 6. ANTENNA REQUIREMENTS | 6 |
| 7. SUMMARY TEST OF RESULTS | 7 |
| 8. TEST RESULT | 8 |
| 8.1 DUTY CYCLE..... | 8 |
| 8.2 6dB BANDWIDTH MEASUREMENT | 9 |
| 8.3 OUTPUT POWER MEASUREMENT..... | 1 2 |
| 8.4 POWER SPECTRAL DENSITY | 1 9 |
| 8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS ... | 2 3 |
| 8.6 RADIATED MEASUREMENT..... | 3 4 |
| 8.6.1 RADIATED SPURIOUS EMISSIONS..... | 3 4 |
| 8.6.2 RADIATED RESTRICTED BAND EDGES | 4 4 |
| 8.7 POWERLINE CONDUCTED EMISSIONS | 5 1 |
| 9. LIST TEST EQUIPMENT | 5 6 |



1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc.
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFKS1301
EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC
Model name(s): KS1301
Date(s) of Tests: September 26, 2013 ~ October 23, 2013
Place of Tests: HCT Co., Ltd.
 105-1, Jangam-ri , Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, KOREA.
 (IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

| | | |
|------------------------------|--|---------------------|
| EUT Type | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC | |
| FCC Model Name | KS1301 | |
| Power Supply | DC 3.8 V | |
| Battery type | Li-ion Battery(Standard) | |
| Frequency Range | TX: 2402 MHz ~ 2480 MHz RX: 2402 MHz ~ 2480 MHz | |
| Max. RF Output Power | Peak | 5.55 dBm (3.589 mW) |
| | Average | 4.98 dBm (3.148 mW) |
| BT Operating Mode | BT 4.0_Low Energy Mode | |
| Modulation Type | GFSK | |
| Number of Channels | 40 Channels | |
| Antenna Specification | Manufacturer: LS Mtron Co. Ltd. Antenna type: Internal Antenna Peak Gain : -1.13 dBi | |

| | | | | |
|--|---|--|-----------------------------|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC | FCC ID: ZNFKS1301 | |



3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03r01 dated April 09, 2013 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.4-2003) Operating Under §15.247” were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

| | | | | | | |
|---------------------------------|------------------------------------|--------------------------|--------------|------|------------|---|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS | GSM/ | GPRS/EDGE, | Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC |
| | | | | | | FCC ID: ZNFKS1301 |



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 21, 2011 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

| | | | | |
|---------------------------------|------------------------------------|---|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | Cellular GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |

7. SUMMARY TEST OF RESULTS

| Test Description | FCC Part Section(s) | Test Limit | Test Condition | Test Result |
|-------------------------------------|----------------------------|----------------------|----------------|-------------|
| 6 dB Bandwidth | §15.247(a)(2) | > 500 kHz | CONDUCTED | PASS |
| Conducted Maximum Peak Output Power | §15.247(b)(3) | < 1 Watt | | PASS |
| Power Spectral Density | §15.247(e) | < 8 dBm / 3 kHz Band | | PASS |
| Band Edge(Out of Band Emissions) | §15.247(d) | Conducted < 20 dBc | | PASS |
| AC Power line Conducted Emissions | §15.207 | cf. Section 8.6 | | PASS |
| Radiated Spurious Emissions | §15.205, 15.209 | cf. Section 8.5.1 | RADIATED | PASS |
| Radiated Restricted Band Edge | §15.247(d), 15.205, 15.209 | cf. Section 8.5.2 | | PASS |


8. TEST RESULT

8.1 DUTY CYCLE

TEST PROCEDURE

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 04/09/2013)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

| LE Mode | T_{on} (ms) | T_{total} (ms) | Duty Cycle | Duty Cycle Factor |
|---------|------------------|---------------------|------------|-------------------|
| | | 0.3880 | 0.6260 | 0.6198 |


8.2 6dB BANDWIDTH MEASUREMENT

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Page 5 in KDB 558074, issued 04/09/2013)

RBW = 100 kHz

VBW \geq 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |

RESULT PLOTS


6dB Bandwidth plot (Low-CH 0)



6dB Bandwidth plot (Mid-CH 19)



6dB Bandwidth plot (High-CH 39)



| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |


8.3 OUTPUT POWER MEASUREMENT

Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function.

This EUT TX condition is actual operating mode by BT LE mode test program.

The Spectrum Analyzer is set to

- Peak Power (Procedure 9.1.1 in KDB 558074, issued 04/09/2013)
 - RBW ≥ DTS Bandwidth
 - VBW ≥ 3 x RBW
 - SPAN ≥ 3 x RBW
 - Detector Mode = Peak
 - Sweep = auto couple
 - Trace Mode = max hold
 - Allow trace to fully stabilize.
 - Use peak marker function to determine the peak amplitude level

- Average Power (Procedure 9.2.2.4 in KDB 558074, issued 04/09/2013)
 - Measure the duty cycle
 - Set span to at least 1.5 times the OBW
 - RBW = 1-5 % of the OBW, not to exceed 1 MHz.
 - VBW ≥ 3 x RBW.
 - Number of points in sweep ≥ 2 x span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
 - Sweep time = auto.
 - Detector = RMS(i.e., power averaging)
 - Do not use sweep triggering. Allow the sweep to “free run”.
 - Trace average at least 100 traces in power averaging(RMS) mode.
 - Compute power by integrating the spectrum across the OBW of the signal using the instrument's band

| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |



power measurement function with band limits set equal to the OBW band edges.

Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation

Output Power = Reading Value + ATT loss + Cable loss(1 ea) + Duty Cycle Factor

Output Power = 10 dBm + 10 dB + 0.8 dB + 0.2 dB = 21.0 dBm

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 20.2 dB is offset for 2.4 GHz Band.

| | | | | | |
|---------------------------------|------------------------------------|---------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Bluetooth/WLAN/NFC | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | | FCC ID: ZNFKS1301 |



TEST RESULTS-Peak

Conducted Output Power Measurements

| LE Mode | | Measured Power(dBm) | Limit (dBm) |
|----------------|-------------|---------------------|-------------|
| Frequency[MHz] | Channel No. | | |
| 2402 | 0 | 5.550 | 30 |
| 2440 | 19 | 4.611 | 30 |
| 2480 | 39 | 2.799 | 30 |


TEST RESULTS-Average

Conducted Output Power Measurements


| LE Mode | | Measured Power(dBm) | Duty Cycle Factor | Measured Power(dBm) + Duty Cycle Factor | Limit (dBm) |
|----------------|-------------|---------------------|-------------------|---|-------------|
| Frequency[MHz] | Channel No. | | | | |
| 2402 | 0 | 2.90 | 2.08 | 4.98 | 30 |
| 2440 | 19 | 2.07 | 2.08 | 4.15 | 30 |
| 2480 | 39 | 0.26 | 2.08 | 2.34 | 30 |

RESULT PLOTS-Peak


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)




Conducted Output Power (High-CH 39)



| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |

RESULT PLOTS-Average


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)



Conducted Output Power (High-CH 39)



| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |


8.4 POWER SPECTRAL DENSITY

Test Requirements and limit, §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

TEST CONFIGURATION



TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 04/09/2013

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

$$\begin{aligned} \text{PSD} &= \text{Reading Value} + \text{ATT loss} + \text{Cable loss}(1 \text{ ea}) \\ &= -5 \text{ dBm} + 10 \text{ dB} + 0.8 \text{ dB} = 5.8 \text{ dBm} \end{aligned}$$

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 20.2 dB is offset for 2.4 GHz Band.

| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |



TEST RESULTS


Conducted Power Density Measurements

| Frequency (MHz) | Channel No. | Mode | Test Result | | |
|-----------------|-------------|------|-------------|-------------|-----------|
| | | | PSD (dBm) | Limit (dBm) | Pass/Fail |
| 2402 | 0 | LE | -10.836 | 8 | Pass |
| 2440 | 19 | | -9.898 | 8 | Pass |
| 2480 | 39 | | -11.913 | 8 | Pass |


| | | | | | |
|---------------------------------|------------------------------------|--------------------------|---|----------------------|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC | FCC ID: ZNFKS1301 | |

RESULT PLOTS


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)



Power Spectral Density (High-CH 39)



| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |


8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074, issued 04/09/2013)

RBW = 100 kHz

VBW \geq 3 x RBW

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points \geq Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 20.2 dB is

| | | | | | |
|---------------------------------|------------------------------------|--------------------------|--------------|-----------------|---|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS | GSM/ GPRS/EDGE, | Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC |
| | | | | | FCC ID: ZNFKS1301 |



offset for 2.4 GHz Band.

4. In case of conducted spurious emissions test, please check factors blow table.
5. In order to simplify the report, attached plots were only the worst case channel and data rate.

FACTORS FOR FREQUENCY

| Freq(MHz) | Factor(dB) |
|-----------|------------|
| 30 | 19.95 |
| 100 | 20.01 |
| 200 | 20.03 |
| 300 | 20.04 |
| 400 | 20.05 |
| 500 | 20.04 |
| 600 | 20.03 |
| 700 | 20.09 |
| 800 | 20.10 |
| 900 | 20.08 |
| 1000 | 20.11 |
| 2000 | 20.25 |
| 2400* | 20.19 |
| 2500* | 20.26 |
| 3000 | 20.27 |
| 4000 | 20.22 |
| 5000 | 20.48 |
| 5700* | 20.42 |
| 5800* | 20.48 |
| 6000 | 20.48 |
| 7000 | 20.57 |
| 8000 | 20.45 |
| 9000 | 20.50 |
| 10000 | 20.64 |
| 11000 | 20.69 |
| 12000 | 20.75 |
| 13000 | 20.92 |
| 14000 | 21.90 |
| 15000 | 21.00 |
| 16000 | 21.03 |
| 17000 | 20.93 |
| 18000 | 20.96 |




| | |
|-------|-------|
| 19000 | 20.85 |
| 20000 | 22.11 |
| 21000 | 21.17 |
| 22000 | 20.99 |
| 23000 | 21.12 |
| 24000 | 21.10 |
| 25000 | 21.42 |


Note : 1. ** is fundamental frequency range.
2. Factor = Cable loss + Attenuator loss

RESULT PLOTS

BandEdge (Low-CH 0)




BandEdge (High-CH 39)




30 MHz ~ 1 GHz

Conducted Spurious Emission (Low-CH 0)



1 GHz ~ 3 GHz

Conducted Spurious Emission (Low-CH 0)




| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with FCC ID: ZNFKS1301 |




3 GHz ~ 5 GHz

Conducted Spurious Emission (Low-CH 0)



5 GHz ~ 7 GHz

Conducted Spurious Emission (Low-CH 0)




| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with FCC ID: ZNFKS1301 |




7 GHz ~ 9 GHz

Conducted Spurious Emission (Low-CH 0)



9 GHz ~ 11 GHz


Conducted Spurious Emission (Low-CH 0)



| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |


11 GHz ~ 13 GHz

Conducted Spurious Emission (Low-CH 0)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Low-CH 0)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Low-CH 0)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Low-CH 0)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Low-CH 0)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Low-CH 0)



Conducted Spurious Emission (Low-CH 0)



| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |



8.6 RADIATED MEASUREMENT.


8.6.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

ANSI C63.4(2003)

Method 12.2.4 in KDB 558074, issued 04/09/2013 (Peak)

Method 12.2.5.1 in KDB 558074, issued 04/09/2013(Average Case 1)

Method 12.2.5.3 in KDB 558074, issued 04/09/2013(Average Case 2)

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW ≥ 3 x RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

| Frequency | RBW |
|-------------|-------------|
| 9-150 kHz | 200-300 Hz |
| 0.15-30 MHz | 9-10 kHz |
| 30-1000 MHz | 100-120 kHz |
| > 1000 MHz | 1 MHz |



- Average

Case 1

If the EUT can be configured or modified to transmit continuously (duty cycle \geq 98 percent then the average emission levels shall be measured using the following method (with EUT transmitting continuously).

RBW = 1 MHz (unless otherwise specified).

VBW \geq 3 x RBW.

Detector = RMS, if span/(# of points in sweep) \leq (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

- 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
- 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

Sweep time = auto.

Perform a trace average of at least 100 traces.

Case 2

If continuous transmission of the EUT (i.e., duty cycle \geq 98 percent) cannot be achieved and the duty cycle is not constant (i.e., duty cycle variations exceed \pm 2 percent), then the following procedure shall be used:

Set RBW = 1 MHz.

Set VBW \geq 1/T.

Video bandwidth mode or display mode

- 1) The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).
- 2) As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 times (1/duty cycle) traces.

Note :

1. We used the case 2 for BT LE mode to perform the average filed strength measurements for RSE and radiated band edge test.
2. The actual setting value of VBW for BT LE mode.

| | | | | | | |
|---------------------------------|------------------------------------|--------------------------|--------------|------|------------|---|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS | GSM/ | GPRS/EDGE, | Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC |
| | | | | | | FCC ID: ZNFKS1301 |

| BT LE Mode | T _{on} (ms) | T _{total} (ms) | Duty Cycle (%) | VBW(1/T) (Hz) | The actual setting value of VBW (Hz) |
|------------|-------------------------|----------------------------|-------------------|------------------|--|
| | 0.3880 | 0.6260 | 61.98 | 2572.0 | 3000 |



TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

| Frequency | Reading | Ant. factor | Cable loss | Ant. POL | Total | Limit | Margin |
|-------------------------|--------------|-------------|------------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dBm /m | dBm | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | | |

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

| Frequency | Reading | Ant. factor | Cable loss | Ant. POL | Total | Limit | Margin |
|-------------------------|--------------|-------------|------------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dBm /m | dBm | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | | |

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode: CH Low(LE Mode)

| Frequency [MHz] | Reading [dBuV/m] | AN.+CL-AMP G [dBm] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|--------------------|---------------------|-----------------------|-------------------|-------------------|-------------------|----------------|--------|
| 4804 | 52.47 | -4.32 | V | 48.15 | 73.98 | 25.83 | PK |
| 4804 | 41.39 | -4.32 | V | 37.07 | 53.98 | 16.91 | AV |
| 7206 | 52.79 | 5.18 | V | 57.97 | 73.98 | 16.01 | PK |
| 7206 | 41.19 | 5.18 | V | 46.37 | 53.98 | 7.61 | AV |
| 4804 | 52.56 | -4.32 | H | 48.24 | 73.98 | 25.74 | PK |
| 4804 | 41.42 | -4.32 | H | 37.10 | 53.98 | 16.88 | AV |
| 7206 | 52.84 | 5.18 | H | 58.02 | 73.98 | 15.96 | PK |
| 7206 | 41.21 | 5.18 | H | 46.39 | 53.98 | 7.59 | AV |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.



Operation Mode: CH Mid(LE Mode)

| Frequency [MHz] | Reading [dBuV/m] | AN.+CL-AMP G [dBm] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|--------------------|---------------------|-----------------------|-------------------|-------------------|-------------------|----------------|--------|
| 4880 | 51.98 | -3.95 | V | 48.03 | 73.98 | 25.95 | PK |
| 4880 | 39.95 | -3.95 | V | 36.00 | 53.98 | 17.98 | AV |
| 7320 | 52.76 | 5.46 | V | 58.22 | 73.98 | 15.77 | PK |
| 7320 | 41.00 | 5.46 | V | 46.46 | 53.98 | 7.53 | AV |
| 4880 | 52.07 | -3.95 | H | 48.12 | 73.98 | 25.86 | PK |
| 4880 | 40.06 | -3.95 | H | 36.11 | 53.98 | 17.87 | AV |
| 7320 | 52.81 | 5.46 | H | 58.27 | 73.98 | 15.72 | PK |
| 7320 | 41.09 | 5.46 | H | 46.55 | 53.98 | 7.44 | AV |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

| | | | | | | |
|---------------------------------|------------------------------------|--------------------------|--------------|------|------------|---|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS | GSM/ | GPRS/EDGE, | Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC |
| | | | | | | FCC ID: ZNFKS1301 |



Operation Mode: CH High(LE Mode)

| Frequency [MHz] | Reading [dBuV/m] | AN.+CL-AMP G [dBm] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|--------------------|---------------------|-----------------------|-------------------|-------------------|-------------------|----------------|--------|
| 4960 | 51.54 | -3.49 | V | 48.05 | 73.98 | 25.93 | PK |
| 4960 | 39.69 | -3.49 | V | 36.20 | 53.98 | 17.78 | AV |
| 7440 | 51.92 | 5.10 | V | 57.02 | 73.98 | 16.96 | PK |
| 7440 | 40.55 | 5.10 | V | 45.65 | 53.98 | 8.33 | AV |
| 4960 | 51.63 | -3.49 | H | 48.14 | 73.98 | 25.84 | PK |
| 4960 | 39.73 | -3.49 | H | 36.24 | 53.98 | 17.74 | AV |
| 7440 | 51.94 | 5.10 | H | 57.04 | 73.98 | 16.94 | PK |
| 7440 | 40.59 | 5.10 | H | 45.69 | 53.98 | 8.29 | AV |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

| | | | | | | |
|---------------------------------|------------------------------------|--------------------------|--------------|------|------------|---|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS | GSM/ | GPRS/EDGE, | Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC |
| | | | | | | FCC ID: ZNFKS1301 |



8.6.2 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

| | |
|---------------------|-----------|
| Operation Mode | BT 4.0_LE |
| Operating Frequency | 2402 MHz |
| Channel No | 0 Ch |

| Frequency [MHz] | Reading [dBuV/m] | A.F.+CL [dBm] | Ant. Pol. [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|------------------|---------------|-----------------|----------------|----------------|-------------|--------|
| 2390.0 | 24.91 | 33.90 | H | 58.81 | 73.98 | 15.17 | PK |
| 2390.0 | 13.47 | 33.90 | H | 47.37 | 53.98 | 6.61 | AV |
| 2390.0 | 24.87 | 33.90 | V | 58.77 | 73.98 | 15.21 | PK |
| 2390.0 | 13.43 | 33.90 | V | 47.33 | 53.98 | 6.65 | AV |

Notes:

1. Frequency range of measurement = 2310 MHz ~ 2390 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

| | | | | |
|---------------------------------|------------------------------------|--|--|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |



| | |
|---------------------|-----------|
| Operation Mode | BT 4.0_LE |
| Operating Frequency | 2480 MHz |
| Channel No | 39 Ch |

| Frequency [MHz] | *Fund. Reading [dBuV/m] | A.F.+CL [dBm] | Ant. Pol. [H/V] | *Fundamental [dBuV/m] | Delta Value [dB] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|-------------------------|---------------|-----------------|-----------------------|------------------|----------------|----------------|-------------|--------|
| 2483.5 | 64.90 | 33.99 | H | 98.89 | 50.18 | 48.71 | 73.98 | 25.27 | PK |
| 2483.5 | 64.19 | 33.99 | H | 98.18 | 50.18 | 48.00 | 53.98 | 5.98 | AV |
| 2483.5 | 62.78 | 33.99 | V | 96.77 | 47.91 | 48.86 | 73.98 | 25.12 | PK |
| 2483.5 | 62.11 | 33.99 | V | 96.10 | 47.91 | 48.19 | 53.98 | 5.79 | AV |

Notes:

1. Frequency range of measurement = 2483.5 MHz ~ 2485.5 MHz
2. Total = Fundamental Reading Value + Antenna Factor + Cable Loss – Delta Value
2. Radiated Restricted Band Edge measures by marker-delta method according to ANSI C63.10(version : 2009)
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. Marker-Delta Method

In making radiated band-edge measurements, there can be a problem obtaining meaningful data because a measurement instrument that is tuned to a band-edge frequency may also capture some in-band signals when using the resolution bandwidth (RBW). In an effort to compensate for this problem, the following technique for determining band-edge compliance shall be used.

a) Perform an in-band field strength measurement of the fundamental emission using the RBW and detector function specified in 6.3 and 6.4, 6.5, or 6.6, as applicable, and the appropriate regulatory requirements for the frequency being measured. and our Rules for the frequency being measured.

For example, for a device operating in the 902-928 MHz band under 47 CFR 15.249, use a 120 kHz RBW with a CISPR QP detector (a peak detector with 100 kHz RBW may alternatively be used). For unlicensed wireless devices operating above 1 GHz, use a 1 MHz RBW, a 1 MHz VBW, and a peak detector as required by 47 CFR 15.35. Repeat the measurement with an average detector (i.e., 1 MHz RBW with 10 Hz VBW). For pulsed emissions, other factors must be included. For example note that radiated measurements of the fundamental emission of a spread spectrum unlicensed wireless device operating under 47 CFR 15.247 are not normally required, but they are necessary in connection with this procedure.

b) Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to approximately 1% to 5 % of the total span, unless otherwise specified, with a video bandwidth equal to or greater than the RBW. Record the peak levels of the fundamental emission and the relevant band-edge emission (i.e., run several sweeps in

| | | | | | |
|---------------------------------|------------------------------------|---------------------------------|----------------------|------------------------|---|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Bluetooth/WLAN/NFC | Cellular/PCS GSM/ | GPRS/EDGE, Cellular | WCDMA/HSDPA/HSUPA Phone with FCC ID: ZNFKS1301 |




peak hold mode). Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band-edge relative to the highest fundamental emission level.

c) Subtract the delta measured in b) from the field strengths measured in a). The resultant field strengths (CISPR QP, average, or peak, as appropriate) are then used to determine band-edge compliance of the restricted bands, described in 5.9.

| | | | | |
|--|---|---|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with | FCC ID: ZNFKS1301 |




Fund. (Peak_Horizontal_CH 39)



Date: 25.SEP.2013 10:59:31

Fund. (Average_Horizontal_CH 39)




Date: 25.SEP.2013 11:00:14

| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with FCC ID: ZNFKS1301 |




Delta (Horizontal_CH 39)



Date: 25.SEP.2013 11:00:50


Fund. (Peak_Vertical_CH 39)



Date: 25.SEP.2013 11:04:45


| | | | | |
|---------------------------------|------------------------------------|--|---|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Cellular/PCS Bluetooth/WLAN/NFC | GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with FCC ID: ZNFKS1301 |

Fund. (Average_Vertical_CH 39)



Date: 25.SEP.2013 11:05:07

Delta (Vertical_CH 39)



Date: 25.SEP.2013 11:05:36

| | | | | | |
|---------------------------------|------------------------------------|--------------------------|---|-------------------------------|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with Bluetooth/WLAN/NFC | FCC ID: ZNFKS1301 |



| | |
|---------------------|-----------|
| Operation Mode | BT 4.0_LE |
| Operating Frequency | 2480 MHz |
| Channel No | 39 Ch |

| Frequency [MHz] | Reading [dBuV/m] | A.F.+CL [dBm] | Ant. Pol. [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|------------------|---------------|-----------------|----------------|----------------|-------------|--------|
| 2485.5 | 25.34 | 33.99 | H | 59.33 | 73.98 | 14.65 | PK |
| 2485.5 | 14.01 | 33.99 | H | 48.00 | 53.98 | 5.98 | AV |
| 2485.5 | 24.82 | 33.99 | V | 58.81 | 73.98 | 15.17 | PK |
| 2485.5 | 13.47 | 33.99 | V | 47.46 | 53.98 | 6.52 | AV |

Notes:

1. Frequency range of measurement = 2485.5 MHz ~ 2500 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.7 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. We are performed the AC Power Line Conducted Emission test for Ch.0 on BT 4.0 LE mode.
Because Ch.0 on BT 4.0 LE mode is worst case.



RESULT PLOTS

Conducted Emissions (Line 1)


HCT

EMC

EUT: KS1301
 Manufacturer: LG
 Operating Condition: BT LE MODE
 Test Site: SHIELD ROOM
 Operator: JC SHIN
 Test Specification: FCC PART15 B
 Comment: H

SCAN TABLE: "FCC CLASS B(H)"

| Start Frequency | Stop Frequency | Step Width | Short Description | Detector | Meas. Time | IF Bandw. | Transducer |
|-----------------|----------------|------------|-------------------|----------|------------|-----------|------------|
| 150.0 kHz | 500.0 kHz | 4.0 kHz | KN22 CLASS B | MaxPeak | 10.0 ms | 9 kHz | None |
| 500.0 kHz | 5.0 MHz | 4.0 kHz | | Average | | | |
| 5.0 MHz | 30.0 MHz | 4.0 kHz | | MaxPeak | 10.0 ms | 9 kHz | None |
| | | | | Average | | | |
| | | | | MaxPeak | 10.0 ms | 9 kHz | None |
| | | | | Average | | | |



MEASUREMENT RESULT: "PHONE_fin QP"

2013-10-06 8:38오전

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Line | PE |
|---------------|------------|-----------|------------|-----------|------|-----|
| 0.318001 | 37.00 | 9.8 | 60 | 27.8 | --- | --- |
| 0.414001 | 39.00 | 9.8 | 58 | 18.6 | --- | --- |
| 0.498001 | 38.60 | 9.8 | 56 | 17.4 | --- | --- |
| 1.832000 | 42.50 | 9.9 | 56 | 13.5 | --- | --- |
| 1.864000 | 40.00 | 9.9 | 56 | 16.0 | --- | --- |
| 1.876000 | 42.50 | 9.9 | 56 | 13.5 | --- | --- |
| 14.308000 | 41.20 | 10.7 | 60 | 18.8 | --- | --- |
| 14.964000 | 41.30 | 10.8 | 60 | 19.7 | --- | --- |
| 15.224000 | 41.20 | 10.8 | 60 | 18.8 | --- | --- |

MEASUREMENT RESULT: "PHONE_fin AV"

2013-10-06 8:38오전

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Line | PE |
|------------------|---------------|--------------|---------------|--------------|------|-----|
| 0.394001 | 26.60 | 9.8 | 48 | 21.4 | --- | --- |
| 0.438001 | 28.00 | 9.8 | 47 | 19.1 | --- | --- |
| 0.498001 | 25.80 | 9.8 | 46 | 20.2 | --- | --- |
| 0.612000 | 29.60 | 9.8 | 46 | 17.0 | --- | --- |
| 0.920000 | 28.50 | 9.8 | 46 | 17.5 | --- | --- |
| 1.924000 | 31.30 | 9.9 | 46 | 14.7 | --- | --- |
| 8.352000 | 29.20 | 10.4 | 50 | 20.8 | --- | --- |
| 14.352000 | 31.70 | 10.7 | 50 | 18.3 | --- | --- |
| 16.524000 | 30.20 | 10.8 | 50 | 19.8 | --- | --- |

| | | | | | |
|---------------------------------|------------------------------------|---------------------------------|---|------------|--|
| FCC PT.15.247 TEST REPORT | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Bluetooth/WLAN/NFC | Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA | Phone with | FCC ID: ZNFKS1301 |

Conducted Emissions (Line 2)


HCT

EMC

EUI: KS1301
 Manufacturer: LG
 Operating Condition: BT LE MODE
 Test Site: SHIELD ROOM
 Operator: JC SHIN
 Test Specification: FCC PART15 B
 Comment: N

SCAN TABLE: "FCC CLASS B(N)"

| Short Description: | | | KN22 CLASS B | | | |
|--------------------|----------------|------------|--------------|------------|-----------|------------|
| Start Frequency | Stop Frequency | Step Width | Detector | Meas. Time | IF Bandw. | Transducer |
| 150.0 kHz | 500.0 kHz | 4.0 kHz | MaxPeak | 10.0 ms | 9 kHz | None |
| 500.0 kHz | 5.0 MHz | 4.0 kHz | Average | 10.0 ms | 9 kHz | None |
| 5.0 MHz | 30.0 MHz | 4.0 kHz | MaxPeak | 10.0 ms | 9 kHz | None |
| | | | Average | | | |



MEASUREMENT RESULT: "PHONE_fin_QP"

2013-10-06 8:42오전

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Line | PE |
|---------------|------------|-----------|------------|-----------|------|-----|
| 0.178001 | 31.20 | 10.0 | 65 | 33.4 | --- | --- |
| 0.438001 | 31.10 | 10.0 | 57 | 26.0 | --- | --- |
| 0.490001 | 33.30 | 10.0 | 56 | 22.8 | --- | --- |
| 1.400000 | 28.50 | 10.1 | 56 | 27.5 | --- | --- |
| 1.924000 | 34.10 | 10.1 | 56 | 21.9 | --- | --- |
| 4.352000 | 29.60 | 10.3 | 56 | 26.4 | --- | --- |
| 14.072000 | 32.50 | 11.0 | 60 | 27.5 | --- | --- |
| 14.092000 | 32.40 | 11.0 | 60 | 27.6 | --- | --- |
| 14.228000 | 32.70 | 11.0 | 60 | 27.3 | --- | --- |

MEASUREMENT RESULT: "PHONE_fin AV"

2013-10-06 8:42오전

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Line | PE |
|------------------|---------------|--------------|---------------|--------------|------|-----|
| 0.398001 | 19.60 | 10.0 | 48 | 28.3 | --- | --- |
| 0.438001 | 23.70 | 10.0 | 47 | 23.4 | --- | --- |
| 0.486001 | 26.60 | 10.0 | 46 | 19.7 | --- | --- |
| 0.616000 | 24.70 | 10.0 | 46 | 21.8 | --- | --- |
| 0.848000 | 19.50 | 10.0 | 46 | 26.5 | --- | --- |
| 1.932000 | 26.20 | 10.1 | 46 | 19.8 | --- | --- |
| 5.000000 | 22.70 | 10.4 | 46 | 23.8 | --- | --- |
| 15.184000 | 25.20 | 11.0 | 50 | 24.8 | --- | --- |
| 16.688000 | 23.30 | 11.1 | 50 | 26.7 | --- | --- |

| | | | | | | |
|---------------------------------|------------------------------------|---------------------------------|--------------|------|---------------------|--|
| FCC PT.15.247 TEST REPORT | | FCC CERTIFICATION REPORT | | | | www.hct.co.kr |
| Test Report No. HCTR1310FR18 | Date of Issue: October 28, 2013 | EUT Type: Bluetooth/WLAN/NFC | Cellular/PCS | GSM/ | GPRS/EDGE, Cellular | WCDMA/HSDPA/HSUPA Phone with FCC ID: ZNFKS1301 |

9. LIST TEST EQUIPMENT

| Manufacturer | Model / Equipment | Calibration Interval | Calibration Due | Serial No. |
|-----------------------|--|----------------------|-----------------|--------------------|
| Rohde & Schwarz | ENV216/ LISN | Annual | 02/06/2014 | 100073 |
| Schwarzbeck | VULB 9160/ TRILOG Antenna | Biennial | 12/17/2014 | 3150 |
| Rohde & Schwarz | ESI 40 / EMI TEST RECEIVER | Annual | 04/16/2014 | 831564103 |
| Agilent | E4440A/ Spectrum Analyzer | Annual | 04/25/2014 | US45303008 |
| Agilent | N9020A/ SIGNAL ANALYZER | Annual | 05/14/2014 | MY51110063 |
| HD | MA240/ Antenna Position Tower | N/A | N/A | 556 |
| EMCO | 1050/ Turn Table | N/A | N/A | 114 |
| HD GmbH | HD 100/ Controller | N/A | N/A | 13 |
| HD GmbH | KMS 560/ SlideBar | N/A | N/A | 12 |
| Rohde & Schwarz | SCU-18/ Signal Conditioning Unit | Annual | 09/10/2014 | 10094 |
| MITEQ | AMF-6B-180265-35-10P / POWER AMP | Annual | 04/16/2014 | 667624 |
| CERNEX | CBL26405040 / POWER AMP | Annual | 04/16/2014 | 19660 |
| Schwarzbeck | BBHA 9120D/ Horn Antenna | Biennial | 07/05/2015 | 1151 |
| Schwarzbeck | BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz) | Biennial | 10/30/2014 | BBHA9170124 |
| Rohde & Schwarz | FSP / Spectrum Analyzer | Annual | 02/08/2014 | 839117/011 |
| Agilent | E4416A /Power Meter | Annual | 11/07/2013 | GB41291412 |
| Agilent | E9327A /POWER SENSOR | Annual | 04/16/2014 | MY4442009 |
| Wainwright Instrument | WHF3.0/18G-10EF / High Pass Filter | Annual | 02/08/2014 | F6 |
| Wainwright Instrument | WHNX6.0/26.5G-6SS / High Pass Filter | Annual | 04/16/2014 | 1 |
| Wainwright Instrument | WHNX7.0/18G-8SS / High Pass Filter | Annual | 04/16/2014 | 29 |
| Wainwright Instrument | WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter | Annual | 03/19/2014 | 1 |
| Hewlett Packard | 11636B/Power Divider | Annual | 11/07/2013 | 11377 |
| Agilent | 87300B/Directional Coupler | Annual | 12/24/2013 | 3116A03621 |
| Hewlett Packard | 11667B / Power Splitter | Annual | 05/29/2014 | 05001 |
| DIGITAL | EP-3010 /DC POWER SUPPLY | Annual | 11/07/2013 | 3110117 |
| ITECH | IT6720 / DC POWER SUPPLY | Annual | 11/07/2013 | 010002156287001199 |
| TESCOM | TC-3000C / BLUETOOTH TESTER | Annual | 04/24/2014 | 3000C000276 |
| Rohde & Schwarz | CBT / BLUETOOTH TESTER | Annual | 04/25/2014 | 100422 |
| EMCO | 6502.LOOP ANTENNA | Biennial | 01/11/2014 | 9009-2536 |
| CERNEX | CBLU1183540 / POWER AMP | Annual | 07/24/2014 | 21691 |
| Agilent | 8493C / Attenuator(10 dB) | Annual | 07/24/2014 | 76649 |
| WEINSCHTEL | 2-3 / Attenuator(3 dB) | Annual | 11/07/2013 | BR0617 |