

# HCT CO., LTD.

## CERTIFICATE OF COMPLIANCE FCC Certification

<b>Applicant Name:</b> LG Electronics MobileComm U.S.A., Inc.	<b>Date of Issue:</b> November 11, 2013
<b>Address:</b> 1000 Sylvan Avenue, Englewood Cliffs NJ 07632	<b>Test Site/Location:</b> HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, Korea
	<b>Report No.:</b> HCTR1310FR22-1
	<b>HCT FRN:</b> 0005866421

**FCC ID : ZNFKS1301**

**APPLICANT : LG Electronics MobileComm U.S.A., Inc.**

<b>FCC Model(s):</b>	KS1301
<b>EUT Type:</b>	Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC
<b>RF Output Field Strength</b>	6.30 dBuV/m
<b>Frequency of Operation:</b>	13.559508 MHz
<b>Modulation type</b>	ASK
<b>FCC Classification:</b>	Low Power Communication Device – Transmitter
<b>FCC Rule Part(s):</b>	FCC Part 15.225 Subpart C

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



**Report prepared by**  
**: Jong Seok Lee**  
**Test engineer of RF Team**



**Approved by**  
**: Chang Seok Choi**  
**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.225 TEST REPORT		FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	FCC ID: ZNFKS1301	



# Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1310FR22	October 28, 2013	- First Approval Report
HCTR1310FR22-1	November 11, 2013	- Added the frequency tolerance measurements over a variation in primary supply voltage from 85% - 115% of the rated voltage in Section 10



# Table of Contents

1. GENERAL INFORMATION .....	4
2. EUT DESCRIPTION .....	4
3. TEST METHODOLOGY .....	5
3.1 EUT CONFIGURATION .....	5
3.2 EUT EXERCISE .....	5
3.3 GENERAL TEST PROCEDURES .....	5
3.4 DESCRIPTION OF TEST MODES .....	5
3.5 STANDARDS .....	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS .....	7
5.1 FACILITIES .....	7
5.2 EQUIPMENT .....	7
6. ANTENNA REQUIREMENTS .....	7
7. TEST SUMMARY .....	8
8. RADIATED EMISSION MEASUREMENT .....	9
8.1. RADIATED EMISSION 9 kHz – 30 MHz .....	10
8.2. RADIATED EMISSION 30 MHz – 1000 MHz .....	13
9. EMISSION BANDWIDTH PLOT.....	14
10. FREQUENCY TOLERANCE .....	15
11. POWERLINE CONDUCTE EMISSIONS.....	16
12. LIST OF TEST EQUIPMENT .....	25

FCC PT.15.225 TEST REPORT		FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	FCC ID: ZNFKS1301	



## 1. GENERAL INFORMATION

**Applicant:** LG Electronics MobileComm U.S.A., Inc.  
**Address:** 1000 Sylvan Avenue, Englewood Cliffs NJ 07632  
**FCC ID:** ZNFKS1301  
**EUT:** Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC  
**Model name(s):** KS1301  
**Date of Test:** October 02, 2013 ~ November 11, 2013  
**Place of Tests:** HCT Co., Ltd.  
 105-1, Jangam-ri , Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, KOREA.  
 (IC Recognition No. : 5944A-3)

## 2. EUT DESCRIPTION

<b>Product</b>	Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC
<b>FCC Model Name</b>	KS1301
<b>Power Supply</b>	DC 3.8 V
<b>Battery Type</b>	Li-ion Battery(Standard)
<b>Frequency of Operation</b>	6.30 dBuV/m
<b>Transmit Power</b>	13.559508 MHz
<b>Modulation Type</b>	ASK
<b>Antenna Specification</b>	Manufacturer: IMTECH Antenna type: FPCB Antenna

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	<b>FCC ID:</b> ZNFKS1301



### 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.10-2009).

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.225 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2009) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10. (Version: 2009).

#### 3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	<b>FCC ID:</b> ZNFKS1301



### 3.5 STANDARDS

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance With  
FCC Part 15.Subpart C

Regulation	Measurement standard	Range
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(a)	ANSI C63.10:2009	13.553MHz to 13.567MHz
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(d)	ANSI C63.10:2009	outside of the 13.110-14.010 MHz band
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2009	9kHz to 30MHz
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2009	30MHz to 1GHz
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.207	ANSI C63.10:2009	150kHz to 30MHz
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(e)	ANSI C63.10:2009	0.01% of nominal
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.215(c)	ANSI C63.10:2009	-



## 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

The 10 m semi anechoic chamber used to collect the Conducted and Radiated data is located at the 105-1, Jangam-Ri, Majang-Myeon, Icheon-Si, Kyoungki-Do, Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4. Detailed description of test facilities was submitted to the Commission and accepted dated Sep. 03, 2010 (Registration Number: 90661)

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned loop, dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

\* The antennas of this E.U.T are permanently attached.

\*The E.U.T Complies with the requirement of §15.203

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	<b>FCC ID:</b> ZNFKS1301



## 7. TEST SUMMARY

The results in this report apply only to sample tested

Regulation	Test Type	Range	Result
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(a)	Radiated Electric Field Emissions	13.553MHz to 13.567MHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(b)	Radiated Electric Field Emissions	13.410MHz to 13.553MHz and 13.567MHz to 13.710MHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(c)	Radiated Electric Field Emissions	13.110 MHz to 13.410 MHz and 13.710 MHz to 14.010 MHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.209 (d)	Radiated Electric Field Emissions	9kHz to 30MHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.209	Radiated Electric Field Emissions	30MHz to 1GHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.207	AC power conducted emissions	150kHz to 30MHz	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.225(e)	Frequency Stability	0.01% of nominal	Pass
Title 47 of the CFR:2012, Part 15 Subpart (c), Clause 15.215(c)	20 dB Bandwidth	-	Pass

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	<b>FCC ID:</b> ZNFKS1301





## 8. RADIATED EMISSION MEASUREMENT

### Requirement(s): 15.209, 15.225

Except as provided elsewhere in this paragraph the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

#### Minimum Standard: FCC Part 15.225 / 15.209

Rule Part	Frequency (MHz)	Limit
Part 15.209	0.009 ~ 0.490	2400/F(kHz)uV/m@300
	0.490 ~1.705	24000/F(kHz)uV/m@30
	1.705 ~ 30	30 uV/m@30
	30 ~ 88	100 ** uV/m@3m
	88 ~ 216	150 ** uV/m@3m
	216 ~ 960	200 ** uV/m@3m
	Above 960	500 uV/m@3m

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

### 15.225 Operation within the band 13.110 – 14.010 MHz.

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter (= 84 dBuV/m) at 30 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter (=50.5dBuV/m) at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter (=40.5 dBuV/m) at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.


(e) The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

(f) In the case of radio frequency powered tags designed to operate with a device authorized under this section, the tag may be approved with the device or be considered as a separate device subject to its own authorization. Powered tags approved with a device under a single application shall be labeled with the same identification number as the device.

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	FCC ID: ZNFKS1301

## 8.1. RADIATED EMISSION 9 kHz – 30 MHz

### Test Set-up



### Test Procedure

The EUT was placed on a non-conductive table located on a large open test site. The loop antenna was placed at a location 3m from the EUT. Radiated emissions were measured with the loop antenna both parallel and perpendicular to the plane of the EUT loop antenna.

The limit is converted from microvolts/meter to decibel microvolts/meter. Sample Calculation:

Corrected Amplitude = Raw Amplitude(dB $\mu$ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor

The spectrum analyzer is set to:

Frequency Range = 9 kHz ~ 1GHz

RBW = 9 kHz (9 kHz ~ 30MHz)  
= 120 kHz (30 MHz ~ 1 GHz)

Trace Mode = max hold

Detector Mode = peak / Quasi-peak

Sweep time = auto

FCC PT.15.225 TEST REPORT		FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC		FCC ID: ZNFKS1301



## Test Results

13.553 MHz-13.567 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.559508	36.49(H)*	9.81	-40	6.30	84	77.70
13.559508	32.20(V)*	9.81	-40	2.01	84	81.99

13.410 MHz-13.553 MHz and 13.567 MHz-13.710 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.567	26.35	9.81	-40	-3.84	50.47	54.31
13.567	22.53	9.81	-40	-7.66	50.47	58.13

13.110 MHz – 13.410 MHz and 13.710 MHz-14.010 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.1934	29.57	9.81	-40	-0.62	40.51	41.13
13.1280	26.40	9.81	-40	-3.79	40.51	44.30

9 kHz -30 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
10.44540	31.93	9.81	-40	1.74	29.54	27.80
14.55366	25.46	9.81	-40	-4.73	29.54	34.27




Note :

1. Distance Correction Below 30MHz =  $40\log(3m/30m) = - 40 \text{ dB}$   
Measurement Distance : 3 m (Below 30 MHz)
2. Factor = Antenna Factor + Cable Loss
3. Result Level = Read Level + Factor + Distance Correction
4. Margin = Limit – Result Level
5. (H)\* and (V)\* mean antenna polarization.
6. Worst case of operating mode is type A, analog mode and 106 kbps.

<b>FCC PT.15.225 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	<b>FCC ID:</b> ZNFKS1301

## 8.2. RADIATED EMISSION 30 MHz – 1000 MHz

Test Set-up



Test Procedures: Radiated emissions were measured according to ANSI C63.10.

The EUT was set to transmit at the highest output power.

The EUT was set 3 meter away from the measuring antenna.

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
Mhz	dB $\mu$ V	dB /m	dB	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
36.74	21.09	12.5	0.5	V	34.09	40.0	5.91
36.57	23.42	12.5	0.5	H	36.42	40.0	3.58
41.09	20.14	13.1	0.6	H	33.82	40.0	6.18
43.24	21.26	13.3	0.6	V	35.12	40.0	4.88
73.26	23.45	11.0	0.9	H	35.28	40.0	4.72
142.57	24.72	12.7	1.2	H	38.59	43.5	4.91

Remark

1. Result Level = Read Level + (Antenna Factor+ Cable Loss)
2. Margin = Limit – Result Level




## 9. EMISSION BANDWIDTH PLOT.

### Requirement(s):

Test Set-up: The EUT was connected to a spectrum analyzer.

Test Procedure: The 20 dB bandwidth was measured by using a spectrum analyzer.



FCC PT.15.225 TEST REPORT		FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC		FCC ID: ZNFKS1301



## 10. FREQUENCY TOLERANCE

Procedure: Part 15.225, ANSI 63.10

If required, the operating or transmitting frequency of an intentional radiator should be measured in accordance with the following procedure to ensure that the device operates outside certain precluded frequency bands and within the frequency range. No modulation needs to be supplied to the intentional radiator during these tests, unless modulation is required to produce an output, e.g., single-sideband suppressed carrier transmitters.

The frequency stability of the transmitter is measured by:

- a) Temperature: The temperature is varied from -20°C to + 50°C using an environmental chamber.
- b) For battery operated equipment, the equipment tests shall be performed using a new battery.

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

Measurement Result:

VOLTAGE (%)	POWER	Temperature (°C)	Frequency (MHz)	Frequency Error (Hz)
100%	3.8 V	-20	13.560224	716
100%		-10	13.560265	757
100%		0	13.560246	738
100%		10	13.560281	773
100%		20	13.559508	0
100%		30	13.560204	696
100%		40	13.560109	601
100%		50	13.560024	516
115%		4.37	20	13.559518
Batt. Endpoint	3.50	20	13.559510	2

## 11. POWERLINE CONDUCTE EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.





**Test Plots**

**Unterminate the Antenna**

**Conducted Emissions (Line 1)**


HCT

EMC

EUT: KS1301  
 Manufacturer: LG  
 Operating Condition: NFC MODE[Unterminated]  
 Test Site: SHIELD ROOM  
 Operator: JC SHIN  
 Test Specification: FCC PART15 B  
 Comment: H

**SCAN TABLE: "FCC CLASS B(H)"**

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	KN22 CLASS B	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	100.0 ms	9 kHz	None
			Average			



**MEASUREMENT RESULT: "PHONE\_fin QP"**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.282001	30.00	9.8	61	30.8	---	---
0.306001	27.70	9.8	60	32.4	---	---
0.390001	29.10	9.8	58	29.0	---	---
0.406001	32.40	9.8	58	25.4	---	---
0.418001	31.20	9.8	58	26.3	---	---
0.494001	37.00	9.8	56	19.1	---	---
0.960000	31.60	9.8	56	24.4	---	---
1.468000	32.00	9.9	56	24.0	---	---
1.620000	33.60	9.9	56	22.4	---	---
1.912000	32.60	9.9	56	23.4	---	---
4.240000	31.40	10.1	56	24.6	---	---
4.868000	32.70	10.2	56	23.3	---	---
13.356000	40.20	10.7	60	19.8	---	---
13.520000	44.80	10.7	60	15.2	---	---

FCC PT.15.225 TEST REPORT	FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1310FR22-1	Date of Issue: November 11, 2013	EUT Type: Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC	FCC ID: ZNFKS1301

**MEASUREMENT RESULT: "PHONE\_fin QP"**

(continued)

Frequency MHz	Level dB <sub>μV</sub>	Transd dB	Limit dB <sub>μV</sub>	Margin dB	Line	PE
13.556000	68.80	10.7	60	-8.8	---	---
13.564000	70.60	10.7	60	-10.6	---	---
13.596000	42.10	10.7	60	17.9	---	---
13.752000	39.80	10.7	60	20.2	---	---

**MEASUREMENT RESULT: "PHONE\_fin AV"**

2013-10-06 10:15오전

Frequency MHz	Level dB <sub>μV</sub>	Transd dB	Limit dB <sub>μV</sub>	Margin dB	Line	PE
0.278001	19.90	9.8	51	31.0	---	---
0.306001	17.90	9.8	50	32.1	---	---
0.390001	18.00	9.8	48	30.0	---	---
0.418001	22.00	9.8	48	25.5	---	---
0.482001	28.70	9.8	46	17.6	---	---
0.494001	27.90	9.8	46	18.2	---	---
0.504000	22.80	9.8	46	23.2	---	---
0.800000	23.40	9.8	46	22.6	---	---
0.992000	22.30	9.8	46	23.7	---	---
1.580000	23.20	9.9	46	22.8	---	---
1.824000	21.30	9.9	46	24.7	---	---
4.684000	23.50	10.2	46	22.5	---	---
9.044000	26.50	10.4	50	23.5	---	---
12.084000	28.70	10.6	50	21.3	---	---
13.556000	57.40	10.7	50	-7.4	---	---
13.564000	59.40	10.7	50	-9.4	---	---
16.592000	27.00	10.8	50	23.0	---	---
27.124000	24.50	11.2	50	25.5	---	---



## Conducted Emissions (Line 2)


HCT

EMC

EUT: KS1301  
 Manufacturer: LG  
 Operating Condition: NFC MODE[Unterminated]  
 Test Site: SHIELD ROOM  
 Operator: JC SHIN  
 Test Specification: FCC PART15 B  
 Comment: N

### SCAN TABLE: "FCC CLASS B(N)"

Start Frequency	Stop Frequency	Step Width	Short Description:	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	KN22 CLASS B	MaxPeak	10.0 ms	9 kHz	None
				Average			
500.0 kHz	5.0 MHz	4.0 kHz		MaxPeak	10.0 ms	9 kHz	None
				Average			
5.0 MHz	30.0 MHz	4.0 kHz		MaxPeak	100.0 ms	9 kHz	None
				Average			



### MEASUREMENT RESULT: "PHONE\_fin\_QP"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.174001	31.80	10.0	65	33.0	---	---
0.186001	31.20	10.0	64	33.0	---	---
0.490001	31.20	10.0	56	25.0	---	---
1.704000	17.70	10.1	56	38.3	---	---
2.012000	22.20	10.1	56	33.8	---	---
4.692000	28.70	10.4	56	27.3	---	---
13.540000	40.40	10.9	60	19.6	---	---
13.560000	66.20	10.9	60	-6.2	---	---
13.568000	51.70	10.9	60	8.3	---	---

**MEASUREMENT RESULT: "PHONE\_fin AV"**

2013-10-06 10:30오전

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	16.60	10.0	56	39.4	---	---
0.406001	18.50	10.0	48	29.2	---	---
0.486001	23.00	10.0	46	23.3	---	---
0.500000	22.30	10.0	46	23.7	---	---
1.356000	14.70	10.1	46	31.3	---	---
4.684000	21.10	10.4	46	24.9	---	---
13.560000	58.10	10.9	50	-8.1	---	---
13.568000	42.90	10.9	50	7.1	---	---
27.120000	27.90	11.7	50	22.1	---	---

<b>FCC PT.15.225 TEST REPORT</b>		<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC		<b>FCC ID:</b> ZNFKS1301



**Terminate the Antenna  
Conducted Emissions (Line 1)**


HCT

EMC

EUT: KSI301  
 Manufacturer: LG  
 Operating Condition: NFC MODE[Terminated]  
 Test Site: SHIELD ROOM  
 Operator: JC SHIN  
 Test Specification: FCC PART15 B  
 Comment: H

**SCAN TABLE: "FCC CLASS B(H)"**

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



**MEASUREMENT RESULT: "PHONE\_fin QP"**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.422001	39.70	9.8	57	17.7	---	---
0.438001	28.50	9.8	57	28.6	---	---
0.498001	39.70	9.8	56	16.4	---	---
0.884000	39.30	9.8	56	16.7	---	---
1.652000	38.00	9.9	56	18.0	---	---
1.904000	38.60	9.9	56	17.4	---	---
14.840000	40.90	10.8	60	19.1	---	---
16.184000	40.20	10.8	60	19.8	---	---
16.416000	39.50	10.8	60	20.5	---	---

**MEASUREMENT RESULT: "PHONE\_fin AV"**

2013-10-06 8:53오전

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.422001	30.00	9.8	47	17.5	---	---
0.462001	23.80	9.8	47	22.9	---	---
0.500000	32.10	9.8	46	13.9	---	---
0.500000	31.70	9.8	46	14.3	---	---
0.588000	28.90	9.8	46	17.1	---	---
1.796000	29.70	9.9	46	16.3	---	---
9.024000	29.20	10.4	50	20.8	---	---
14.588000	31.00	10.7	50	19.0	---	---
16.992000	28.60	10.8	50	21.4	---	---

<b>FCC PT.15.225 TEST REPORT</b>		<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1310FR22-1	<b>Date of Issue:</b> November 11, 2013	<b>EUT Type:</b> Cellular/PCS GSM/ GPRS/EDGE, Cellular WCDMA/HSDPA/HSUPA Phone with Bluetooth/WLAN/NFC		<b>FCC ID:</b> ZNFKS1301



## Conducted Emissions (Line 2)


HCT

EMC

EUT: KS1301  
 Manufacturer: LG  
 Operating Condition: NFC MODE[Terminated]  
 Test Site: SHIELD ROOM  
 Operator: JC SHIN  
 Test Specification: FCC PART15 B  
 Comment: N

### SCAN TABLE: "FCC CLASS B(N)"

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	KN22 CLASS B	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



### MEASUREMENT RESULT: "PHONE\_fin\_QP"

2013-10-06 8:56오전

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.354001	14.30	10.0	59	44.6	---	---
0.430001	28.60	10.0	57	28.7	---	---
0.498001	32.60	10.0	56	23.4	---	---
1.900000	34.00	10.1	56	22.0	---	---
4.108000	30.00	10.3	56	26.0	---	---
4.908000	28.60	10.4	56	27.4	---	---
11.644000	31.80	10.8	60	28.2	---	---
11.864000	31.60	10.8	60	28.4	---	---
14.696000	32.20	11.0	60	27.8	---	---



MEASUREMENT RESULT: "PHONE\_fin AV"

2013-10-06 8:56오전

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.426001	22.60	10.0	47	24.7	---	---
0.470001	19.50	10.0	47	27.0	---	---
0.494001	22.10	10.0	46	24.0	---	---
0.500000	25.40	10.0	46	20.6	---	---
1.896000	24.80	10.1	46	21.2	---	---
4.968000	22.00	10.4	46	24.0	---	---
5.000000	21.90	10.4	46	24.1	---	---
14.860000	25.00	11.0	50	25.0	---	---
16.608000	22.70	11.1	50	27.3	---	---



## 12. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ENV216/ LISN	Annual	02/06/2014	100073
Schwarzbeck	VULB 9160/ TRILOG Antenna	Biennial	12/17/2014	3150
Rohde & Schwarz	ESI 40 / EMI TEST RECEIVER	Annual	04/16/2014	831564103
Agilent	E4440A/ Spectrum Analyzer	Annual	04/25/2014	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	Annual	05/14/2014	MY51110063
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/10/2014	10094
MITEQ	AMF-6B-180265-35-10P / POWER AMP	Annual	04/16/2014	667624
CERNEX	CBL26405040 / POWER AMP	Annual	04/16/2014	19660
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	07/05/2015	1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	Biennial	10/30/2014	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	02/08/2014	839117/011
Agilent	E4416A /Power Meter	Annual	11/07/2013	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	04/16/2014	MY4442009
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	Annual	02/08/2014	F6
Wainwright Instrument	WHNX6.0/26.5G-6SS / High Pass Filter	Annual	04/16/2014	1
Wainwright Instrument	WHNX7.0/18G-8SS / High Pass Filter	Annual	04/16/2014	29
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	03/19/2014	1
Hewlett Packard	11636B/Power Divider	Annual	11/07/2013	11377
Agilent	87300B/Directional Coupler	Annual	12/24/2013	3116A03621
Hewlett Packard	11667B / Power Splitter	Annual	05/29/2014	05001
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	11/07/2013	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	11/07/2013	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	04/24/2014	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	04/25/2014	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/11/2014	9009-2536
CERNEX	CBLU1183540 / POWER AMP	Annual	07/24/2014	21691
Agilent	8493C / Attenuator(10 dB)	Annual	07/24/2014	76649
WEINSCHTEL	2-3 / Attenuator(3 dB)	Annual	11/07/2013	BR0617