

TEST REPORT

EMI Test for FCC Certification of LG L125DL Model

APPLICANT

LG Electronics USA, Inc.

REPORT NO.

HCT-EM-1911-FC014

DATE OF ISSUE

November 29, 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

EMI Test for
FCC Certification

REPORT NO.
HCT-EM-1911-FC014

DATE OF ISSUE
November 29, 2019

FCC ID
ZNFL125DL

Applicant **LG Electronics USA, Inc.**
1000 Sylvan Avenue, Englewood Cliffs NJ 07632 United States

Product Name CDMA/GSM/WCDMA/LTE Phone with BT & WLAN
Model Name LG L125DL
Series Model Name Refer to the clause 1.1 Description of EUT

Travel Adaptor Information Model name: MCS-V01WH
Manufacturer: PHILHONG

Date of Test November 20, 2019 to November 28, 2019

Test Standard Used FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

Test Results Refer to the present document

Manufacturer LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test results were applied only to the test methods required by the standard.

Tested by
Na-Eun Song

(signature)

Technical Manager
Gu-Cheol Yoon

(signature)

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	November 29, 2019	Initial Release

The above Test Report is not related to the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme) / A2LA(American Association for Laboratory Accreditation), which signed the ILAC-MRA.

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

CONTENTS

1. GENERAL INFORMATION	5
1.1 Description of EUT	5
1.2 Tested System Details	5
1.3 Cable Description	7
1.4 Noise Suppression Parts on Cable. (I/O Cable)	7
1.5 Test Facility	8
1.6 Calibration of Measuring Instrument	8
1.7 Measurement Uncertainty	8
2. DESCRIPTION OF TEST	9
2.1 Measurement of Conducted Emission	9
2.2 Measurement of Radiated Emission	10
2.3 Configuration of Tested System	11
3. PRELIMINARY TEST	12
3.1 Conducted Emission	12
3.2 Radiated Emission	12
4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY	13
4.1 Conducted Emission	13
4.2 Radiated Emission Below 1 GHz	20
4.3 Radiated Emission Above 1 GHz	22
5. CONCLUSION	25
6. APPENDIX A. TEST SETUP PHOTO	26

1. GENERAL INFORMATION

1.1 Description of EUT

FCC ID	ZNFL125DL
Model Name	LG L125DL
Series Model Name	LGL125DL, L125DL, LM-Y120QM, LMY120QM, Y120QM, LM-Y120UM, LMY120UM, Y120UM, LM-Y120QM6, LMY120QM6, Y120QM6
Product Name	CDMA/GSM/WCDMA/LTE Phone with BT & WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 1 710 MHz to 1 780 MHz (LTE B66) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4)

RX Frequency	871.40 MHz to 891.60 MHz (WCDMA B5)
	1 930 MHz to 1 990 MHz (LTE B2)
	2 110 MHz to 2 155 MHz (LTE B4)
	869 MHz to 894 MHz (LTE B5)
	729 MHz to 746 MHz (LTE B12)
	746 MHz to 756 MHz (LTE B13)
	1 925 MHz to 1 990 MHz (LTE B25)
	859 MHz to 894 MHz (LTE B26)
	2 496 MHz to 2 690 MHz (LTE B41)
	2 110 MHz to 2 200 MHz (LTE B66)
	2 402 MHz to 2 480 MHz (Bluetooth)
	2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)

1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	LG L125DL	-	LG
Data Cable	EAD62377928	-	Ningbo Broad
Earphone	EAB64468444	-	CRESYN
Travel Adaptor	MCS-V01WH		PHIHONG
Micro SD Card	Extreme MicroSDHC UHS-I CLASS 10 (32 GB)	-	SANDISK

1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	N/A	(P) 1.0
	Earphone	N/A	N	(D) 1.2

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End

1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Designation No.
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5:2017

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Conducted Emission (0.15 MHz to 30 MHz)	1.8 dB
3 m Radiated Emissions (30 MHz to 1 GHz)	4.8 dB
3 m Radiated Emissions (1 GHz to 18 GHz)	5.4 dB
3 m Radiated Emissions (18 GHz to 40 GHz)	5.7 dB

2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

Conducted Emission Limits

Frequency (MHz)	Resolution Bandwidth (kHz)	Class A		Class B	
		Quasi-Peak (dBμV)	Average (dBμV)	Quasi-Peak (dBμV)	Average (dBμV)
0.15 to 0.5	9	79	66	66 to 56*	56 to 46*
0.5 to 5	9	73	60	56	46
5 to 30	9	73	60	60	50

NOTE. Decreases with the logarithm of the frequency.

2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber.
The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
(1 GHz to 40 GHz)

Radiated Emission Limits


Frequency (MHz)	Class A			Class B		
	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dBμV/m)	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dBμV/m)
30 to 88	10	90	39.0	3	100	40.0
88 to 216	10	150	43.5	3	150	43.5
216 to 960	10	210	46.4	3	200	46.0
Above 960	10	300	49.5	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Class A		Class B		
		Peak (dBμV/m)	Average (dBμV/m)	Peak (dBμV/m)	Average (dBμV/m)	
Above 1 000	3	80	60	74	54	

2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Non-Conductive Table

Power Line: 120 VAC, 60 Hz

3. PRELIMINARY TEST

3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: FRONT CAMERA & MP3 mode

REAR CAMERA & FM RADIO mode

IDLE mode

NOTE. The worst-case emissions are reported.

3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: FRONT CAMERA & MP3 mode

REAR CAMERA & FM RADIO mode

IDLE mode

NOTE. The worst-case emissions are reported.

4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission

4.1.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.18.2019
☒	LISN	Rohde & Schwarz	ENV216	102245	1 year	12.12.2018
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:


Test Standard Used	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	150 kHz to 30 MHz
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Operating Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	Shielded Room
Temperature	22.8 °C
Relative Humidity	41.6 %
Test Date	November 28, 2019

Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

4.1.3 Measuring Data

Figure 1: Conducted Emission (150 kHz to 30 MHz), Line (L1)




QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	45.9	9.000	L1	9.8	20.1	66.0
0.154000	42.7	9.000	L1	9.8	23.1	65.8
0.158000	39.2	9.000	L1	9.8	26.3	65.6
0.194000	38.0	9.000	L1	9.8	25.8	63.9
0.202000	41.4	9.000	L1	9.8	22.1	63.5
0.212000	41.0	9.000	L1	9.8	22.2	63.1
2.694000	31.8	9.000	L1	9.9	24.2	56.0
3.478000	34.6	9.000	L1	9.9	21.4	56.0
3.946000	35.5	9.000	L1	9.9	20.5	56.0
4.026000	35.5	9.000	L1	9.9	20.5	56.0
4.040000	33.8	9.000	L1	9.9	22.2	56.0
4.680000	33.3	9.000	L1	10.0	22.7	56.0
10.800000	36.6	9.000	L1	10.3	23.4	60.0
11.070000	37.2	9.000	L1	10.4	22.8	60.0
11.894000	37.5	9.000	L1	10.4	22.5	60.0
12.150000	37.9	9.000	L1	10.4	22.1	60.0
12.468000	37.8	9.000	L1	10.4	22.2	60.0
13.038000	37.6	9.000	L1	10.4	22.4	60.0

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154000	28.5	9.000	L1	9.8	27.3	55.8
0.198000	26.0	9.000	L1	9.8	27.7	53.7
0.202000	27.3	9.000	L1	9.8	26.3	53.5
0.206000	28.3	9.000	L1	9.8	25.1	53.4
0.212000	27.8	9.000	L1	9.8	25.3	53.1
0.216000	27.3	9.000	L1	9.8	25.7	53.0
2.694000	20.2	9.000	L1	9.9	25.8	46.0
3.262000	22.0	9.000	L1	9.9	24.0	46.0
3.478000	22.9	9.000	L1	9.9	23.1	46.0
3.946000	22.6	9.000	L1	9.9	23.4	46.0
4.040000	22.2	9.000	L1	9.9	23.8	46.0
4.680000	22.0	9.000	L1	10.0	24.0	46.0
10.800000	28.1	9.000	L1	10.3	21.9	50.0
11.070000	28.7	9.000	L1	10.4	21.3	50.0
11.894000	29.4	9.000	L1	10.4	20.6	50.0
11.996000	29.2	9.000	L1	10.4	20.8	50.0
12.150000	29.5	9.000	L1	10.4	20.5	50.0
12.448000	29.4	9.000	L1	10.4	20.6	50.0

Figure 2: Conducted Emission (150 kHz to 30 MHz), Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	42.1	9.000	N	9.8	23.9	66.0
0.160000	35.9	9.000	N	9.8	29.6	65.5
0.200000	37.2	9.000	N	9.8	26.5	63.6
0.206000	38.3	9.000	N	9.8	25.1	63.4
0.210000	38.6	9.000	N	9.8	24.6	63.2
0.218000	36.7	9.000	N	9.8	26.2	62.9
1.066000	34.3	9.000	N	9.9	21.7	56.0
1.908000	30.5	9.000	N	9.9	25.5	56.0
2.146000	30.4	9.000	N	9.9	25.6	56.0
2.214000	30.3	9.000	N	9.9	25.7	56.0
2.236000	28.0	9.000	N	9.9	28.0	56.0
4.442000	28.7	9.000	N	10.0	27.3	56.0
11.620000	31.7	9.000	N	10.4	28.3	60.0
11.770000	32.4	9.000	N	10.4	27.6	60.0
11.946000	32.4	9.000	N	10.4	27.6	60.0
12.080000	31.8	9.000	N	10.4	28.2	60.0
12.630000	32.0	9.000	N	10.5	28.0	60.0
13.384000	32.3	9.000	N	10.5	27.7	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	29.6	9.000	N	9.8	26.4	56.0
0.160000	24.2	9.000	N	9.8	31.2	55.5
0.200000	26.2	9.000	N	9.8	27.4	53.6
0.204000	27.4	9.000	N	9.8	26.0	53.4
0.210000	28.3	9.000	N	9.8	24.9	53.2
0.218000	27.0	9.000	N	9.8	25.9	52.9
1.066000	23.9	9.000	N	9.9	22.1	46.0
1.908000	21.3	9.000	N	9.9	24.7	46.0
2.146000	19.8	9.000	N	9.9	26.2	46.0
2.214000	21.2	9.000	N	9.9	24.8	46.0
2.236000	19.4	9.000	N	9.9	26.6	46.0
4.442000	19.2	9.000	N	10.0	26.8	46.0
10.832000	24.4	9.000	N	10.4	25.6	50.0
11.816000	25.0	9.000	N	10.4	25.0	50.0
11.946000	24.9	9.000	N	10.4	25.1	50.0
12.308000	25.3	9.000	N	10.5	24.7	50.0
13.448000	23.5	9.000	N	10.5	26.5	50.0
14.186000	23.0	9.000	N	10.5	27.0	50.0

4.2 Radiated Emission Below 1 GHz

4.2.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.17.2019
☒	Trilog antenna	Schwarzbeck	VULB 9168	255	2 year	03.26.2019
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
☒	Turn Table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.2.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	30 MHz to 1 000 MHz
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operating Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.4 / 21.3 °C
Relative Humidity	41.7 / 42.5 %
Test Date	November 20, 2019 / November 25, 2019

4.2.3 Measuring Data

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
32.024600	21.4	100.0	V	343.0	18.5	18.6	40.0
60.669600	18.8	225.0	V	8.0	19.3	21.2	40.0
114.532200	20.7	225.3	V	267.0	16.8	22.8	43.5
216.015000	30.6	125.1	H	310.0	17.4	15.4	46.0
687.280200	28.5	192.8	V	0.0	28.6	17.5	46.0
911.803600	31.7	325.0	H	326.0	31.7	14.3	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

4.3 Radiated Emission Above 1 GHz

4.3.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.17.2019
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
☒	Turn table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒	Low Noise amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.04.2019
☒	Horn antenna	Schwarzbeck	BBHA 9120D	01836	1 year	07.19.2019
☐	Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.17.2018
☐	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170 #786	2 year	12.05.2017
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.3.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	2 690 MHz
Tested Frequency Range	1 GHz to 18 GHz
Worst Case of Operating Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.1 / 21.4 °C
Relative Humidity	43.8 / 42.2 %
Test Date	November 27, 2019 / November 28, 2019

4.3.3 Measuring Data

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
3150.290000	34.8	125.8	V	272.0	-20.9	39.2	74.0
4990.130000	39.6	100.0	V	50.0	-15.8	34.4	74.0
7314.260000	44.3	150.0	H	319.0	-9.8	29.7	74.0
9758.050000	47.5	291.6	V	69.0	-5.1	26.5	74.0
11304.510000	47.8	149.7	H	290.0	-2.4	26.2	74.0
14728.490000	49.0	149.5	V	320.0	1.0	25.0	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
3150.290000	22.5	125.8	V	272.0	-20.9	31.5	54.0
4990.130000	26.1	100.0	V	50.0	-15.8	27.9	54.0
7314.260000	31.3	150.0	H	319.0	-9.8	22.7	54.0
9758.050000	34.8	291.6	V	69.0	-5.1	19.2	54.0
11304.510000	35.1	149.7	H	290.0	-2.4	18.9	54.0
14728.490000	36.4	149.5	V	320.0	1.0	17.6	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

5. CONCLUSION

The data collected shows that the **Product Name: CDMA/GSM/WCDMA/LTE Phone with BT & WLAN,**
Model Name: LG L125DL complies with § 15.107 and § 15.109 of the FCC rules.

6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A and test setup photo file no. as follows;

File No.	Date of Issue	Description
HCT-EM-1911-FC014-P	November 29, 2019	Initial Release

End of report