



MEASUREMENT REPORT FCC Part 22 & 90

Applicant Name:
 LG Electronics USA, Inc.
 111 Sylvan Avenue, North Building
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 4/26 - 5/22/2020
Test Site/Location:
 PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
 1M2004220073-06-R1.ZNF

FCC ID:	ZNFL355DL
APPLICANT:	LG Electronics USA, Inc.

Application Type:	Certification
Model:	LM-K300QM
Additional Model(s):	LG-L355DL, LMK300QM, LGL355DL, K300QM, L355DL, LG L355DL
EUT Type:	Portable Handset
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part:	§2.1049, §22(H), §90(S), §90(R)
Test Procedure(s):	ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised test report (S/N: 1M2004220073-06-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President



FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT 	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset
Page 1 of 44		

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS.....	10
7.1	Summary.....	10
7.2	Occupied Bandwidth	11
7.3	Spurious and Harmonic Emissions at Antenna Terminal	21
7.4	Band Edge Emissions at Antenna Terminal	27
7.5	Conducted Power Output Data	33
7.6	Radiated Power (ERP)	34
7.7	Radiated Spurious Emissions Measurements	37
7.8	Frequency Stability / Temperature Variation	41
8.0	CONCLUSION.....	44

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 2 of 44



MEASUREMENT REPORT

FCC Part 22 & 90



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator
LTE Band 26	15 MHz	QPSK	821.5	ERP	0.048	16.84	13M4G7D
		16QAM	821.5	ERP	0.041	16.09	13M5W7D
		64QAM	821.5	ERP	0.032	15.09	13M5W7D
	15 MHz	QPSK	821.5	Conducted	0.297	24.73	13M4G7D
		16QAM	821.5	Conducted	0.219	23.40	13M5W7D
		64QAM	821.5	Conducted	0.172	22.35	13M5W7D
	10 MHz	QPSK	819.0	Conducted	0.327	25.15	8M96G7D
		16QAM	819.0	Conducted	0.224	23.51	8M96W7D
		64QAM	819.0	Conducted	0.172	22.36	8M95W7D
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.328	25.16	4M49G7D
		16QAM	816.5 - 821.5	Conducted	0.237	23.74	4M49W7D
		64QAM	816.5 - 821.5	Conducted	0.186	22.70	4M49W7D
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.321	25.06	2M69G7D
		16QAM	815.5 - 822.5	Conducted	0.232	23.66	2M68W7D
		64QAM	815.5 - 822.5	Conducted	0.182	22.61	2M68W7D
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.321	25.06	1M08G7D
		16QAM	814.7 - 823.3	Conducted	0.220	23.43	1M08W7D
		64QAM	814.7 - 823.3	Conducted	0.182	22.60	1M08W7D
CDMA BC10	N/A	CDMA	817.9 - 823.1	Conducted	0.33	25.16	1M27F9W

EUT Overview

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 3 of 44

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 4 of 44

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFL355DL**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part.

Test Device Serial No.: Error! MergeField was not found in header record of data source.

2.2 Device Capabilities

This device contains the following capabilities:

CDMA, GSM/GPRS/EDGE, WCDMA/HSPA, LTE, WLAN, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFL355DL	 PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	 LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 5 of 44	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBi/dBd]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBi) or an isotropic source (dBd). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 6 of 44

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 7 of 44

© 2020 PCTEST

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

V

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX2	Licensed Transmitter Cable Set	4/9/2020	Annual	4/9/2021	LTX2
Agilent	E5515C	Wireless Communications Test Set	N/A			GB46310798
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	7/17/2020	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	10/10/2021	121034
Espec	ESX-2CA	Environmental Chamber	6/13/2019	Annual	6/13/2020	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	2/22/2019	Biennial	2/22/2021	128338
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	6/5/2019	Annual	6/5/2020	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/11/2019	Annual	7/11/2020	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/8/2019	Annual	7/8/2020	102133
Sunol	DRH-118	Horn Antenna (1-18GHz)	10/3/2019	Annual	10/3/2020	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	5/19/2018	Biennial	5/19/2020	A051107

Table 5-1. Summary of Test Results

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFL355DL		PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 8 of 44	

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission – BC10

Example: Channel 476 CDMA BC10 Mode 3rd Harmonic (2453.70MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 2453.70 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 9 of 44

© 2020 PCTEST

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFL355DL
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA / LTE
 Band: Band Class 10 / Band 26

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	N/A	PASS	Section 7.2
	Conducted Band Edge / Spurious Emissions (LTE Band 26)	2.1051, 90(R).543(a)	> 43 + 10 log10 (P[Watts]) for all out-of-band emissions except > 50 + 10 log10 (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Sections 7.3, 7.4
	Conducted Band Edge / Spurious Emissions (CDMA BC10)			PASS	Sections 7.3, 7.4
	Frequency Stability	2.1055, 90.213	< 2.5 ppm	PASS	Section 7.8
	Conducted Power	2.1046, 90.635	< 100 Watts	PASS	Section 7.5
RADIATED	Effective Radiated Power (LTE Band 26)	22.913(a.2)	< 7 Watts max. ERP	PASS	Section 7.6
	Effective Radiated Power (CDMA BC10)			PASS	Section 7.6
	Radiated Spurious Emissions (LTE Band 26)	2.1053, 90(R).543(e)	> 43 + 10 log10 (P[Watts]) for all out-of-band emissions except > 50 + 10 log10 (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Section 7.7
	Radiated Spurious Emissions (CDMA BC10)			PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST Error! MergeField was not found in header record of data source..

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 10 of 44

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 11 of 44	


© 2020 PCTEST

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

LTE Band 26




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26 - 15MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 12 of 44




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 13 of 44




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 14 of 44




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 15 of 44




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 16 of 44




Plot 7-11. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 17 of 44




Plot 7-13. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-14. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB Configuration)


FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 18 of 44




Plot 7-15. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 19 of 44

CDMA BC10



Plot 7-16. Occupied Bandwidth Plot (CDMA, Ch. 476)



Plot 7-17. Occupied Bandwidth Plot (CDMA, Ch. 684)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 20 of 44

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW $\geq$ 100kHz
3. VBW $\geq$ 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-2. Test Instrument & Measurement Setup

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 21 of 44

LTE Band 26




Plot 7-18. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-19. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 22 of 44



Plot 7-20. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)


FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 23 of 44

© 2020 PCTEST


All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

V

CDMA BC10




Plot 7-31. Conducted Spurious Plot (CDMA Ch. 476- Low Channel)




Plot 7-31. Conducted Spurious Plot (CDMA Ch. 476- Low Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 24 of 44




Plot 7-31. Conducted Spurious Plot (CDMA Ch. 476- Low Channel)




Plot 7-31. Conducted Spurious Plot (CDMA Ch. 684- High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 25 of 44



Plot 7-31. Conducted Spurious Plot (CDMA Ch. 684- High Channel)



Plot 7-31. Conducted Spurious Plot (CDMA Ch. 684- High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 26 of 44

7.4 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


For channel edge emission, the signal analyzer's "ACP" measurement capability is used.

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 27 of 44

LTE Band 26




Plot 7-21. Channel Edge Plot (LTE Band 26 - 15MHz QPSK - Mid Channel)




Plot 7-22. Channel Edge Plot (LTE Band 26 - 10MHz QPSK - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 28 of 44




Plot 7-23. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - Low Channel)




Plot 7-24. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 29 of 44




Plot 7-25. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - Low Channel)




Plot 7-26. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 30 of 44



Plot 7-27. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)



Plot 7-28. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 31 of 44

CDMA BC10



Plot 7-29. Channel Edge Plot (CDMA BC10 – Ch. 476)



Plot 7-30. Channel Edge Plot (CDMA BC10 – Ch. 684)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 32 of 44

7.5 Conducted Power Output Data

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
15 MHz	QPSK	26765	821.5	1 / 0	24.73	0.297	50.00	-25.27
	16-QAM	26765	821.5	1 / 0	23.40	0.219	50.00	-26.60
	64-QAM	26765	821.5	1 / 0	22.35	0.172	50.00	-27.65
10 MHz	QPSK	26740	819.0	1 / 25	25.15	0.327	50.00	-24.85
	16-QAM	26740	819.0	1 / 25	23.51	0.224	50.00	-26.49
	64-QAM	26740	819.0	1 / 25	22.36	0.172	50.00	-27.64
5 MHz	QPSK	26715	816.5	1 / 12	25.16	0.328	50.00	-24.84
		26765	821.5	1 / 12	24.86	0.306	50.00	-25.14
	16-QAM	26715	816.5	1 / 12	23.74	0.237	50.00	-26.26
	64-QAM	26715	816.5	1 / 12	22.70	0.186	50.00	-27.30
3 MHz	QPSK	26705	815.5	1 / 7	25.06	0.321	50.00	-24.94
		26775	822.5	1 / 7	24.91	0.310	50.00	-25.09
	16-QAM	26705	815.5	1 / 7	23.66	0.232	50.00	-26.34
	64-QAM	26705	815.5	1 / 7	22.61	0.182	50.00	-27.39
1.4 MHz	QPSK	26697	814.7	1 / 2	25.06	0.321	50.00	-24.94
		26783	823.3	1 / 2	24.95	0.313	50.00	-25.05
	16-QAM	26697	814.7	1 / 2	23.43	0.220	50.00	-26.57
	64-QAM	26783	823.3	1 / 2	22.60	0.182	50.00	-27.40

Table 7-2. Conducted Power Output Data (LTE-B26)

Frequency [MHz]	Channel	Battery Type	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
817.90	476	Standard	25.16	0.328	50.00	-24.84
823.10	684	Standard	25.14	0.327	50.00	-24.86

Table 7-3. Conducted Power Output Data (CDMA BC10)

NOTES:

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. **Error! MergeField was not found in header record of data source.**

FCC ID: ZNFL355DL		PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 33 of 44

7.6 Radiated Power (ERP)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFL355DL	 PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 34 of 44

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) **Error! MergeField was not found in header record of data source.**

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 35 of 44

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
15 MHz	QPSK	821.5	H	223.0	277.0	6.72	1 / 37	12.27	16.84	0.048	38.45	-21.61
	16-QAM	821.5	H	223.0	277.0	6.72	1 / 37	11.52	16.09	0.041	38.45	-22.36
	64-QAM	821.5	H	223.0	277.0	6.72	1 / 37	10.52	15.09	0.032	38.45	-23.36
	QPSK	821.5	V	186.0	177.0	6.72	1 / 37	10.14	14.71	0.030	38.45	-23.74

Table 7-31. ERP Data (LTE Band 26)

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 36 of 44

7.7 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFL355DL	 PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 37 of 44

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-5. Test Instrument & Measurement Setup

Test Notes

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. **Error! MergeField was not found in header record of data source.**
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
6. Per 90(R)(f), emissions in the 1559 – 1610MHz band are subject to a limit of -40dBm/MHz for wideband signals. These emission measurements are shown in this section below.

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 38 of 44

LTE Band 26



Plot 7-32. Radiated Spurious Plot (LTE Band 26)


Bandwidth (MHz):	15
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 37

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	H	115	44	-71.85	-6.42	28.73	-66.53	-13.00	-53.53
2464.5	H	124	58	-51.52	-2.58	52.90	-42.35	-13.00	-29.35
3286.0	H	-	-	-72.41	1.41	36.00	-59.26	-13.00	-46.26
4107.5	H	400	196	-74.21	2.44	35.23	-60.02	-13.00	-47.02
4929.0	H	-	-	-74.34	4.23	36.89	-58.36	-13.00	-45.36

Table 7-4. Radiated Spurious Data (LTE Band 26)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 39 of 44

CDMA BC10



Plot 7-33. Radiated Spurious Plot (CDMA BC10)

Frequency (MHz):	817.9
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1635.8	H	123	216	-62.70	-6.49	37.81	-57.45	-13.00	-44.45
2453.7	H	400	207	-62.23	-2.32	42.45	-52.81	-13.00	-39.81
3271.6	H	-	-	-62.14	1.27	46.13	-49.12	-13.00	-36.12

Table 7-5. Radiated Spurious Data (CDMA BC10 – Ch. 476)

Frequency (MHz):	823.1
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1646.2	H	114	204	-61.04	-6.40	39.56	-55.69	-13.00	-42.69
2469.3	H	400	356	-62.35	-2.80	41.85	-53.41	-13.00	-40.41
3292.4	H	-	-	-61.89	1.17	46.28	-48.98	-13.00	-35.98

Table 7-6. Radiated Spurious Data (CDMA BC10 – Ch. 684)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1-ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset		Page 40 of 44

7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFL355DL	 PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	 LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 41 of 44	

© 2020 PCTEST

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Frequency Stability / Temperature Variation

LTE Band 26					
		Operating Frequency (Hz):		819,000,000	
		Ref. Voltage (VDC):		3.85	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	- 30	819,000,056	390	0.0000476
		- 20	818,999,721	55	0.0000067
		- 10	819,000,463	797	0.0000973
		0	818,999,992	326	0.0000398
		+ 10	818,999,507	-159	-0.0000194
		+ 20 (Ref)	818,999,666	0	0.0000000
		+ 30	819,000,048	382	0.0000466
		+ 40	819,000,499	833	0.0001017
		+ 50	818,999,981	315	0.0000385
Battery Endpoint	2.80	+ 20	818,999,741	75	0.0000092

Table 7-9. LTE Band 26 Frequency Stability Data




Table 7-9. LTE Band 26 Frequency Stability Chart

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 42 of 44	

Frequency Stability / Temperature Variation

CDMA BC10					
		Operating Frequency (Hz):		817,900,000	
		Ref. Voltage (VDC):		3.85	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	- 30	817,899,688	-255	-0.0000312
		- 20	817,900,427	484	0.0000592
		- 10	817,900,104	161	0.0000197
		0	817,899,881	-62	-0.0000076
		+ 10	817,899,916	-27	-0.0000033
		+ 20 (Ref)	817,899,943	0	0.0000000
		+ 30	817,900,348	405	0.0000495
		+ 40	817,899,559	-384	-0.0000469
		+ 50	817,900,090	147	0.0000180
Battery Endpoint	2.80	+ 20	817,900,107	164	0.0000201

Table 7-9. CDMA BC10 Frequency Stability Data




Table 7-9. CDMA BC10 Frequency Stability Chart

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 90 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 43 of 44	

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset** **FCC ID: ZNFL355DL** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: ZNFL355DL	 PCTEST[®] Proud to be part of element	PART 90 MEASUREMENT REPORT	 LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-06-R1.ZNF	Test Dates: 4/26 - 5/22/2020	EUT Type: Portable Handset	Page 44 of 44	

© 2020 PCTEST

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

V