# PCTEST ENGINEERING LABORATORY, INC.



7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctestlab.com



# MEASUREMENT REPORT FCC Part 22, 24, & 27 LTE

**Applicant Name:** 

LG Electronics MobileComm U.S.A 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States** 

**Date of Testing:** 11/14-11/25/2016 Test Site/Location:

PCTEST Lab., Columbia, MD, USA

**Test Report Serial No.:** 0Y1611151766-R1.ZNF

FCC ID: ZNFL59BL

LG ELECTRONICS MOBILECOMM U.S.A APPLICANT:

**Application Type:** Certification

**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)

§2; §22; §24; §27 FCC Rule Part(s):

**Test Procedure(s):** ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02

**EUT Type:** Portable Handset

Model(s): LGL59BL, LG-L59BL, L59BL, LG-M257, LGM257, M257

**Test Device Serial No.:** identical prototype [S/N: 01395, 01403, 01387]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This test report (S/N: 0Y1611151766-R1.ZNF) supersedes and replaces the previous version of this test report (S/N: 0Y1611151766.ZNF). Please appropriately discard the previous version of this test report.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Domo 1 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 1 of 123



# TABLE OF CONTENTS

FCC P	ART 2	22, 24, & 27 MEASUREMENT REPORT	3
1.0		RODUCTION	
	1.1	Scope	5
	1.2	Testing Facility	5
2.0	PRC	DUCT INFORMATION	6
	2.1	Equipment Description	6
	2.2	Device Capabilities	6
	2.3	Test Configuration	6
	2.4	EMI Suppression Device(s)/Modifications	6
3.0	DES	CRIPTION OF TESTS	7
	3.1	Measurement Procedure	7
	3.2	Block A Frequency Range	7
	3.3	Cellular - Base Frequency Blocks	7
	3.4	Cellular - Mobile Frequency Blocks	7
	3.5	PCS - Base Frequency Blocks	7
	3.6	PCS - Mobile Frequency Blocks	8
	3.7	AWS - Base Frequency Blocks	8
	3.8	AWS - Mobile Frequency Blocks	8
	3.9	Radiated Power and Radiated Spurious Emissions	9
4.0	MEA	SUREMENT UNCERTAINTY	10
5.0	TES	T EQUIPMENT CALIBRATION DATA	11
6.0	SAM	IPLE CALCULATIONS	12
7.0	TES	T RESULTS	13
	7.1	Summary	13
	7.2	Occupied Bandwidth	
	7.3	Spurious and Harmonic Emissions at Antenna Terminal	
	7.4	Band Edge Emissions at Antenna Terminal	
	7.5	Peak-Average Ratio	
	7.6	Radiated Power (ERP/EIRP)	100
	7.7	Radiated Spurious Emissions Measurements	
	7.8	Frequency Stability / Temperature Variation	
8.0	CON	ICLUSION	123

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 2 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 2 01 123





# **MEASUREMENT REPORT**



FCC Part 22, 24, & 27

# §2.1033 General Information

APPLICANT: LG Electronics MobileComm U.S.A

APPLICANT ADDRESS: 1000 Sylvan Avenue

Englewood Cliffs, NJ 07632, United States

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA

**FCC RULE PART(S):** §2; §22; §24; §27

**BASE MODEL**: LGL59BL FCC ID: ZNFL59BL

FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)


**FREQUENCY TOLERANCE**: ±0.00025 % (2.5 ppm)


**Test Device Serial No.:** 01395, 01403, 01387 ☐ Production ☐ Production ☐ Engineering

**DATE(S) OF TEST:** 11/14-11/25/2016 **TEST REPORT S/N:** 0Y1611151766-R1.ZNF

# **Test Facility / Accreditations**


Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.





- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.





FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 2 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 3 of 123
@ 2016 DCTEST Engineering	Laboratory Inc	•		VEC





# **MEASUREMENT REPORT**



FCC Part 22, 24, & 27

			I EDD	TIDD I		1
	FCC Rule		ERP/	EIRP	Emission	
Mode		Tx Frequency (MHz)	Max. Power	Max. Power	Emission	Modulation
	Part	, , ,	(W)	(dBm)	Designator	
LTE Band 12	27	699.7 - 715.3	0.099	19.93	1M15G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.082	19.33	1M14W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.002	20.09	2M76G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.102	19.21	2M73W7D	16QAM
LTE Band 12	27	701.5 - 713.5	0.003	20.76	4M53G7D	QPSK
LTE Band 12	27	701.5 - 713.5	0.093	19.67	4M50W7D	16QAM
LTE Band 12	27	704 - 711	0.033	20.71	8M91G7D	QPSK
LTE Band 12	27	704 - 711	0.110	19.99	8M92W7D	16QAM
LTE Band 5	22H	824.7 - 848.3	0.096	19.82	1M12G7D	QPSK
LTE Band 5	22H	824.7 - 848.3	0.082	19.02	1M12W7D	16QAM
LTE Band 5	22H	825.5 - 847.5	0.002	20.12	2M73G7D	QPSK
LTE Band 5	22H	825.5 - 847.5	0.103	18.85	2M73W7D	16QAM
LTE Band 5	22H	826.5 - 846.5	0.077	21.16	4M54G7D	QPSK
LTE Band 5	22H	826.5 - 846.5	0.103	20.11	4M51W7D	16QAM
LTE Band 5	22H	829 - 844	0.103	21.38	8M96G7D	QPSK
LTE Band 5	22H	829 - 844	0.137	20.28	8M96W7D	16QAM
LTE Band 4	27	1710.7 - 1754.3	0.107	24.07	1M11G7D	QPSK
LTE Band 4	27	1710.7 - 1754.3	0.233	22.94	1M11G7D	16QAM
LTE Band 4	27	1710.7 - 1754.5	0.197	24.14	2M73G7D	QPSK
LTE Band 4	27	1711.5 - 1753.5	0.200	22.91	2M75W7D	16QAM
LTE Band 4	27	1711.5 - 1753.5	0.196	24.83	4M54G7D	QPSK
LTE Band 4	27	1712.5 - 1752.5	0.304	23.84	4M50W7D	16QAM
LTE Band 4	27	1712.5 - 1752.5	0.242	24.55	8M97G7D	QPSK
LTE Band 4	27	1715 - 1750	0.283	22.76	8M97W7D	16QAM
LTE Band 4	27	1715 - 1750	0.169	24.89	13M4G7D	QPSK
LTE Band 4 LTE Band 4	27 27	1717.5 - 1747.5 1720 - 1745	0.228	23.57 24.63	13M4W7D 17M9G7D	16QAM QPSK
LTE Band 4	27	1720 - 1745	0.290 0.210	23.22		16QAM
LTE Band 2	24E	1850.7 - 1909.3		22.98	17M9W7D 1M12G7D	
LTE Band 2	24E	1850.7 - 1909.3	0.199	21.85	1M12W7D	QPSK
LTE Band 2	24E		0.153		2M72G7D	16QAM
		1851.5 - 1908.5	0.236	23.72		QPSK
LTE Band 2	24E	1851.5 - 1908.5	0.203	23.07	2M71W7D	16QAM
LTE Band 2	24E	1852.5 - 1907.5	0.344	25.36	4M54G7D	QPSK
LTE Band 2	24E	1852.5 - 1907.5	0.245	23.89	4M50W7D	16QAM
LTE Band 2	24E	1855 - 1905	0.379	25.79	8M98G7D	QPSK
LTE Band 2	24E	1855 - 1905	0.306	24.86	8M97W7D	16QAM
LTE Band 2	24E	1857.5 - 1902.5	0.357	25.53	13M4G7D	QPSK
LTE Band 2	24E	1857.5 - 1902.5	0.292	24.66	13M4W7D	16QAM
LTE Band 2	24E	1860 - 1900	0.324	25.11	17M9G7D	QPSK
LTE Band 2	24E	1860 - 1900	0.247	23.92	17M9W7D	16QAM

**EUT Overview** 

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 4 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 4 of 123



### 1.0 INTRODUCTION

# 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

# 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Internt'I (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga F of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 5 of 123



# 2.0 PRODUCT INFORMATION

# 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFL59BL**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

# 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

# 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

# 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 6 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 6 01 123



#### **DESCRIPTION OF TESTS** 3.0

#### **Measurement Procedure** 3.1


The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment - Measurements and Performance Standards" (ANSI/TIA-603-D-2010) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

#### 3.2 Block A Frequency Range §27.5(c)

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz; Block B: 704-710 MHz and 734-740 MHz: and Block C: 710-716 MHz and 740-746 MHz.

#### 3.3 **Cellular - Base Frequency Blocks**




BLOCK 1: 869 - 880 MHz (A\* Low + A) BLOCK 3: 890 - 891.5 MHz (A\* High) BLOCK 2: 880 - 890 MHz (B) BLOCK 4: 891.5 - 894 MHz (B\*)

#### 3.4 **Cellular - Mobile Frequency Blocks**



BLOCK 1: 824 - 835 MHz (A\* Low + A) BLOCK 3: 845 - 846.5 MHz (A\* High) BLOCK 4: 846.5 - 849 MHz (B\*) BLOCK 2: 835 - 845 MHz (B)

#### 3.5 **PCS - Base Frequency Blocks**




FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 7 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 7 of 123




BLOCK 1: 1930 - 1945 MHz (A) BLOCK 4: 1965 - 1970 MHz (E) BLOCK 2: 1945 - 1950 MHz (D) BLOCK 5: 1970 - 1975 MHz (F) BLOCK 3: 1950 - 1965 MHz (B) BLOCK 6: 1975 - 1990 MHz (C)

#### **PCS - Mobile Frequency Blocks** 3.6




BLOCK 1: 1850 - 1865 MHz (A) BLOCK 4: 1885 - 1890 MHz (E) BLOCK 5: 1890 - 1895 MHz (F) BLOCK 6: 1895 - 1910 MHz (C) BLOCK 2: 1865 - 1870 MHz (D) BLOCK 3: 1870 - 1885 MHz (B)

#### 3.7 **AWS - Base Frequency Blocks** §27.5(h)



BLOCK 4: 2135 - 2140 MHz (D) BLOCK 1: 2110 - 2120 MHz (A) BLOCK 5: 2140 - 2145 MHz (E) BLOCK 2: 2120 - 2130 MHz (B) BLOCK 3: 2130 - 2135 MHz (C) BLOCK 6: 2145 - 2155 MHz (F)

#### 3.8 **AWS - Mobile Frequency Blocks**



BLOCK 1: 1710 - 1720 MHz (A) BLOCK 4: 1735 - 1740 MHz (D) BLOCK 2: 1720 - 1730 MHz (B) BLOCK 5: 1740 - 1745 MHz (E) BLOCK 3: 1730 - 1735 MHz (C) BLOCK 6: 1745 - 1755 MHz (F)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 8 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 6 01 123



#### 3.9 Radiated Power and Radiated Spurious Emissions §2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(c.10) §27.50(d.4) §27.53(g) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_{d [dBm]} = P_{g [dBm]} - cable loss_{[dB]} + antenna gain_{[dBd/dBi]}$$

Where, Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] - cable loss [dB].

The calculated P<sub>d</sub> levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log<sub>10</sub>(Power <sub>[Watts]</sub>).

FCC ID: ZNFL59BL	PCTEST'	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 9 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Fage 9 01 123



# 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (±dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	⊕ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 10 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 10 of 123



# 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	4/11/2016	Annual	4/11/2017	LTx1
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/11/2016	Annual	7/11/2017	RE1
Agilent	N9020A	MXA Signal Analyzer	12/5/2015	Annual	12/5/2016	US46470561
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	7/20/2016	Annual	7/20/2017	MY49432391
Agilent	N9038A	MXE EMI Receiver	4/21/2016	Annual	4/21/2017	MY51210133
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	7/6/2016	Annual	7/6/2017	441119
Com-Power	PAM-118A	PREAMPLIFIER 500MHZ TO 18GHZ	7/26/2016	Annual	7/26/2017	551079
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
EMCO	3160-09	Small Horn	8/23/2016	Biennial	8/23/2018	135427
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
PCTEST	-	EMC Switch System	7/6/2016	Annual	7/6/2017	NM2
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/16/2016	Annual	5/16/2017	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	7/11/2016	Annual	7/11/2017	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A

Table 5-1. Test Equipment

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 11 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 1101123



# 6.0 SAMPLE CALCULATIONS

### **Emission Designator**

### **QPSK Modulation**

**Emission Designator = 8M62G7D** 

LTE BW = 8.62 MHz G = Phase Modulation 7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### **16QAM Modulation**

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz W = Amplitude/Angle Modulated 7 = Quantized/Digital Info D = Data transmission, telemetry, telecommand

# Spurious Radiated Emission – LTE Band

**Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)** 

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80).

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	<b>⊕</b> LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 10 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 12 of 123



#### **TEST RESULTS** 7.0

#### 7.1 **Summary**

Company Name: LG Electronics MobileComm U.S.A

FCC ID: ZNFL59BL

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
2.1049	Occupied Bandwidth	N/A		PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(g) 27.53(h)	Out of Band Emissions	> 43 + 10log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A	CONDUCTED	PASS	See RF Exposure Report
2.1055. 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power (Band 5)	< 7 Watts max. ERP		PASS	Section 7.6
27.50(c.10)	Effective Radiated Power (Band 12)	< 3 Watts max. ERP		PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	< 2 Watts max. EIRP	RADIATED	PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4 66)	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(g) 27.53(h)	Undesirable Emissions	> 43 + 10log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

### Table 7-1. Summary of Test Results

- Notes: All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the 3) spectrum analyzer through calibrated cables, attenuators, and couplers.
- For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.4.

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	<b>⊕</b> LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 12 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 13 of 123



# 7.2 Occupied Bandwidth §2.1049

### **Test Overview**

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### **Test Procedure Used**

KDB 971168 D01 v02r02 - Section 4.2

### **Test Settings**

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW  $\geq$  3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2-7 were repeated after changing the RBW such that it would be within 1-5% of the 99% occupied bandwidth observed in Step 7

### **Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

### **Test Notes**

None.

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 14 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 14 of 123





Plot 7-1. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - RB Size 6)



Plot 7-2. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogo 15 of 122
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 15 of 123





Plot 7-3. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - RB Size 15)




Plot 7-4. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 16 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 10 01 123





Plot 7-5. Occupied Bandwidth Plot (Band 12 – 5.0MHz QPSK – RB Size 25)



Plot 7-6. Occupied Bandwidth Plot (Band 12 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 17 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 17 01 123






Plot 7-7. Occupied Bandwidth Plot (Band 12 - 10.0MHz QPSK - RB Size 50)




Plot 7-8. Occupied Bandwidth Plot (Band 12 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 18 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 10 01 123






Plot 7-9. Occupied Bandwidth Plot (Band 5 - 1.4MHz QPSK - RB Size 6)



Plot 7-10. Occupied Bandwidth Plot (Band 5 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 10 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 19 of 123






Plot 7-11. Occupied Bandwidth Plot (Band 5 – 3.0MHz QPSK – RB Size 15)



Plot 7-12. Occupied Bandwidth Plot (Band 5 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 20 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 20 01 123





Plot 7-13. Occupied Bandwidth Plot (Band 5 - 5.0MHz QPSK - RB Size 25)




Plot 7-14. Occupied Bandwidth Plot (Band 5 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 21 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 21 01 123






Plot 7-15. Occupied Bandwidth Plot (Band 5 - 10.0MHz QPSK - RB Size 50)




Plot 7-16. Occupied Bandwidth Plot (Band 5 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 22 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 22 01 123






Plot 7-17. Occupied Bandwidth Plot (Band 4 - 1.4MHz QPSK - RB Size 6)



Plot 7-18. Occupied Bandwidth Plot (Band 4 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 23 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 23 01 123





Plot 7-19. Occupied Bandwidth Plot (Band 4 - 3.0MHz QPSK - RB Size 15)



Plot 7-20. Occupied Bandwidth Plot (Band 4 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 24 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 24 01 123





Plot 7-21. Occupied Bandwidth Plot (Band 4 – 5.0MHz QPSK – RB Size 25)



Plot 7-22. Occupied Bandwidth Plot (Band 4 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 25 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 23 01 123






Plot 7-23. Occupied Bandwidth Plot (Band 4 – 10.0MHz QPSK – RB Size 50)



Plot 7-24. Occupied Bandwidth Plot (Band 4 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 26 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 20 01 123






Plot 7-25. Occupied Bandwidth Plot (Band 4 - 15.0MHz QPSK - RB Size 75)



Plot 7-26. Occupied Bandwidth Plot (Band 4 - 15.0MHz 16-QAM - RB Size 75)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 27 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 27 01 123






Plot 7-27. Occupied Bandwidth Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 7-28. Occupied Bandwidth Plot (Band 4 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 28 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 20 01 123





Plot 7-29. Occupied Bandwidth Plot (Band 2 - 1.4MHz QPSK - RB Size 6)




Plot 7-30. Occupied Bandwidth Plot (Band 2 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 29 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 29 01 123





Plot 7-31. Occupied Bandwidth Plot (Band 2 – 3.0MHz QPSK – RB Size 15)



Plot 7-32. Occupied Bandwidth Plot (Band 2 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 30 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 30 01 123






Plot 7-33. Occupied Bandwidth Plot (Band 2 - 5.0MHz QPSK - RB Size 25)



Plot 7-34. Occupied Bandwidth Plot (Band 2 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 31 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Fage 31 01 123





Plot 7-35. Occupied Bandwidth Plot (Band 2 - 10.0MHz QPSK - RB Size 50)



Plot 7-36. Occupied Bandwidth Plot (Band 2 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 32 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Faye 32 01 123






Plot 7-37. Occupied Bandwidth Plot (Band 2 - 15.0MHz QPSK - RB Size 75)



Plot 7-38. Occupied Bandwidth Plot (Band 2 - 15.0MHz 16-QAM - RB Size 75)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 22 of 402
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 33 of 123





Plot 7-39. Occupied Bandwidth Plot (Band 2 - 20.0MHz QPSK - RB Size 100)



Plot 7-40. Occupied Bandwidth Plot (Band 2 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 34 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 34 01 123



## Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)

#### **Test Overview**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is  $43 + log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.

#### **Test Procedure Used**

KDB 971168 D01 v02r02 - Section 6.0

### **Test Settings**

- 1. Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental frequency (separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

### **Test Notes**

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	<b>⊕</b> LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dog 25 of 122
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 35 of 123






Plot 7-41. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-42. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 26 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 36 of 123






Plot 7-43. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-44. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	⊕ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 27 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 37 of 123





Plot 7-45. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-46. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 38 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Faye 30 01 123





Plot 7-47. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-48. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	<b>⊕</b> LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 20 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 39 of 123






Plot 7-49. Conducted Spurious Plot (Band 12 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-50. Conducted Spurious Plot (Band 5 – 10.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	⊕ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 40 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 40 of 123





Plot 7-51. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-52. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 44 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 41 of 123





Plot 7-53. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-54. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 42 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Faye 42 01 123






Plot 7-55. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-56. Conducted Spurious Plot (Band 5 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 42 of 102
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 43 of 123





Plot 7-57. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-58. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL59BL	PCTEST'	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 44 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 44 of 123






Plot 7-59. Conducted Spurious Plot (Band 4 – 3.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-60. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 45 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 40 01 123






Plot 7-61. Conducted Spurious Plot (Band 4 – 3.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-62. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 46 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 40 01 123






Plot 7-63. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-64. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST'	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dog 47 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 47 of 123






Plot 7-65. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-66. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogo 49 of 122
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 48 of 123





Plot 7-67. Conducted Spurious Plot (Band 4 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-68. Conducted Spurious Plot (Band 2 – 3.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	€ LG	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Dags 40 of 102	
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 49 of 123	





Plot 7-69. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-70. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 50 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 50 01 123






Plot 7-71. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-72. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL59BL	PCTEST*	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	<b>⊕</b> LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags E1 of 100
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Page 51 of 123






Plot 7-73. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-74. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 52 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		raye 52 01 123





Plot 7-75. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-76. Conducted Spurious Plot (Band 2 - 3.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL59BL	PCTEST	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 53 of 123
0Y1611151766-R1.ZNF	11/14-11/25/2016	Portable Handset		Fage 53 01 123