



MEASUREMENT REPORT FCC Part 24 & 27 LTE

Applicant Name:
 LG Electronics MobileComm U.S.A
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 01/19-01/29/2016
Test Site/Location:
 PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
 0Y1601180110.ZNF

FCC ID :	ZNFL82VL
APPLICANT:	LG ELECTRONICS MOBILECOMM U.S.A

Application Type: Class II Permissive Change
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §24; §27
Test Procedure(s): ANSI/TIA-603-C-2004, KDB 971168 D01 v02r02
EUT Type: Portable Handset
Model(s): LGL82VL, L82VL, LG-L82VL
Test Device Serial No.: *identical prototype* [S/N: 2BBBH, 2BBBD]
Class II Permissive Change: *Please see FCC change document*
Original Grant Date: 01/27/2016



Mode	Tx Frequency (MHz)	Modulation	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
LTE Band 13	779.5 - 784.5	QPSK	0.069	18.42
LTE Band 13	779.5 - 784.5	16QAM	0.057	17.54
LTE Band 13	782	QPSK	0.062	17.95
LTE Band 13	782	16QAM	0.056	17.45
LTE Band 4	1710.7 - 1754.3	QPSK	0.122	20.86
LTE Band 4	1710.7 - 1754.3	16QAM	0.115	20.60
LTE Band 4	1711.5 - 1753.5	QPSK	0.135	21.31
LTE Band 4	1711.5 - 1753.5	16QAM	0.110	20.43
LTE Band 4	1712.5 - 1752.5	QPSK	0.128	21.06
LTE Band 4	1712.5 - 1752.5	16QAM	0.100	20.01
LTE Band 4	1715 - 1750	QPSK	0.115	20.62
LTE Band 4	1715 - 1750	16QAM	0.097	19.88
LTE Band 4	1717.5 - 1747.5	QPSK	0.117	20.70
LTE Band 4	1717.5 - 1747.5	16QAM	0.098	19.91
LTE Band 4	1720 - 1745	QPSK	0.118	20.71
LTE Band 4	1720 - 1745	16QAM	0.096	19.81
LTE Band 2	1850.7 - 1909.3	QPSK	0.160	22.05
LTE Band 2	1850.7 - 1909.3	16QAM	0.145	21.61
LTE Band 2	1851.5 - 1908.5	QPSK	0.176	22.46
LTE Band 2	1851.5 - 1908.5	16QAM	0.164	22.15
LTE Band 2	1852.5 - 1907.5	QPSK	0.170	22.31
LTE Band 2	1852.5 - 1907.5	16QAM	0.147	21.67
LTE Band 2	1855 - 1905	QPSK	0.177	22.49
LTE Band 2	1855 - 1905	16QAM	0.154	21.88
LTE Band 2	1857.5 - 1902.5	QPSK	0.155	21.91
LTE Band 2	1857.5 - 1902.5	16QAM	0.130	21.14
LTE Band 2	1860 - 1900	QPSK	0.176	22.45
LTE Band 2	1860 - 1900	16QAM	0.133	21.23

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.




 Randy Ortanez
 President




FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 1 of 25	

T A B L E O F C O N T E N T S


FCC PART 24 & 27 MEASUREMENT REPORT		3
1.0 INTRODUCTION		4
1.1 Scope.....		4
1.2 Testing Facility.....		4
2.0 PRODUCT INFORMATION.....		5
2.1 Equipment Description.....		5
2.2 Device Capabilities		5
2.3 Test Configuration.....		5
2.4 EMI Suppression Device(s)/Modifications.....		5
3.0 DESCRIPTION OF TESTS		6
3.1 Measurement Procedure.....		6
3.1 Block C Frequency Range		6
3.2 PCS - Base Frequency Blocks.....		6
3.3 PCS - Mobile Frequency Blocks		6
3.4 AWS - Base Frequency Blocks.....		7
3.5 AWS - Mobile Frequency Blocks.....		7
3.6 Radiated Power and Radiated Spurious Emissions.....		8
4.0 MEASUREMENT UNCERTAINTY		9
5.0 TEST EQUIPMENT CALIBRATION DATA		10
6.0 SAMPLE CALCULATIONS		11
7.0 TEST RESULTS		12
7.1 Summary.....		12
7.2 Radiated Power (ERP/EIRP)		13
7.3 Radiated Spurious Emissions Measurements.....		18
8.0 CONCLUSION.....		25

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 2 of 25	



MEASUREMENT REPORT

FCC Part 24 & 27




§2.1033 General Information



APPLICANT: LG Electronics MobileComm U.S.A
APPLICANT ADDRESS: 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §24; §27
BASE MODEL: LGL82VL, L82VL, LG-L82VL
FCC ID: ZNFL82VL
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: 2BBBH, 2BBBD Production Pre-Production Engineering
DATE(S) OF TEST: 01/19-01/29/2016
TEST REPORT S/N: 0Y1601180110.ZNF

Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 3 of 25	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 4 of 25

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Electronics Portable Handset FCC ID: ZNFL82VL**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

2.2 Device Capabilities

This device contains the following capabilities:



850/1900 CDMA/EvDO Rev0/A (BC0, BC1), Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The LG Electronics Portable Handset FCC ID: ZNFL82VL was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 5 of 25	

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v02r02) were used in the measurement of the **LG Electronics Portable Handset FCC ID: ZNFL82VL**.


3.1 Block C Frequency Range

§27.5(b)(3)

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.


3.2 PCS - Base Frequency Blocks



§24.229



3.3 PCS - Mobile Frequency Blocks


§24.229



FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 6 of 25

3.4 AWS - Base Frequency Blocks

§27.5(h)




BLOCK 1: 2110 – 2120 MHz (A)
 BLOCK 2: 2120 – 2130 MHz (B)
 BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 4: 2135 – 2140 MHz (D)
 BLOCK 5: 2140 – 2145 MHz (E)
 BLOCK 6: 2145 – 2155 MHz (F)



3.5 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)
 BLOCK 2: 1720 – 1730 MHz (B)
 BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 4: 1735 – 1740 MHz (D)
 BLOCK 5: 1740 – 1745 MHz (E)
 BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 7 of 25	

3.6 Radiated Power and Radiated Spurious Emissions

§2.1053 §24.232(c) §24.238(a) §27.50(b.10) §27.50(d.4) §27.53(f) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾” (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.



The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.



The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$.

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 8 of 25	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 9 of 25

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE3	Radiated Emissions Cable Set	4/29/2015	Annual	4/29/2016	RE3
Agilent	8447D	Broadband Amplifier	6/12/2015	Annual	6/12/2016	2443A01900
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	10/22/2014	Biennial	10/22/2016	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/18/2015	Annual	7/18/2016	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/18/2015	Annual	7/18/2016	13SH10-1000/U1000-2
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/11/2015	Annual	3/11/2016	11401010036
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Mini-Circuits	TVA-11-422	RF Power Amp	N/A			QA1303002
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			102060
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/17/2015	Annual	7/17/2016	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2015	Annual	3/5/2016	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/3/2015	Annual	3/3/2016	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	2/21/2014	Biennial	2/21/2016	9105-2404
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107
VWR	62344-734	Thermometer with Clock	2/20/2014	Biennial	2/20/2016	140140420

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.



FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 10 of 25	

6.0 SAMPLE CALCULATIONS

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm $- (-24.80)$.

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 11 of 25	

7.0 TEST RESULTS

7.1 Summary



Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFL82VL
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
<u>TRANSMITTER MODE (TX)</u>					
27.50(b.10)	Effective Radiated Power (Band 13)	< 3 Watts max. ERP	RADIATED	PASS	Section 7.2
24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	< 2 Watts max. EIRP		PASS	Section 7.2
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 7.2
2.1053 24.238(a) 27.53(c) 27.53(h)	Undesirable Emissions	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.3
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz		PASS	Section 7.3

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 12 of 25	

7.2 Radiated Power (ERP/EIRP)

§24.232(c.2) §27.50(b.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 13 of 25	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Radiated Test Setup <1GHz




Figure 7-2. Radiated Test Setup >1GHz



Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 14 of 25	



Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
779.50	5	QPSK	V	146	133	1 / 24	15.95	2.47	18.42	34.77	-16.35
782.00	5	QPSK	V	158	168	1 / 0	15.81	2.51	18.32	34.77	-16.45
784.50	5	QPSK	V	162	189	1 / 0	15.68	2.56	18.24	34.77	-16.53
779.50	5	16QAM	V	146	133	1 / 24	14.97	2.47	17.44	34.77	-17.33
782.00	5	16QAM	V	158	168	1 / 0	15.02	2.51	17.53	34.77	-17.24
784.50	5	16QAM	V	162	189	1 / 0	14.98	2.56	17.54	34.77	-17.23
782.00	10	QPSK	V	159	134	1 / 0	15.44	2.51	17.95	34.77	-16.82
782.00	10	16QAM	V	159	134	1 / 0	14.94	2.51	17.45	34.77	-17.32

Table 7-2. ERP Data (Band 13)

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 15 of 25



Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	V	145	95	1 / 5	10.25	9.28	19.53	30.00	-10.47
1732.50	1.4	QPSK	V	142	88	1 / 0	11.86	9.00	20.86	30.00	-9.14
1754.30	1.4	QPSK	V	151	87	1 / 5	10.96	8.72	19.68	30.00	-10.32
1710.70	1.4	16-QAM	V	145	95	1 / 5	9.53	9.28	18.81	30.00	-11.19
1732.50	1.4	16-QAM	V	142	88	1 / 0	11.60	9.00	20.60	30.00	-9.40
1754.30	1.4	16-QAM	V	151	87	1 / 5	9.97	8.72	18.69	30.00	-11.31
1711.50	3	QPSK	V	146	90	1 / 0	10.60	9.27	19.87	30.00	-10.13
1732.50	3	QPSK	V	147	86	1 / 0	12.31	9.00	21.31	30.00	-8.69
1753.50	3	QPSK	V	150	90	1 / 14	10.98	8.73	19.71	30.00	-10.29
1711.50	3	16-QAM	V	146	90	1 / 0	10.42	9.27	19.69	30.00	-10.31
1732.50	3	16-QAM	V	147	86	1 / 0	11.43	9.00	20.43	30.00	-9.57
1753.50	3	16-QAM	V	150	90	1 / 14	10.46	8.73	19.19	30.00	-10.81
1712.50	5	QPSK	V	144	89	1 / 0	10.70	9.26	19.96	30.00	-10.04
1732.50	5	QPSK	V	143	91	1 / 24	12.06	9.00	21.06	30.00	-8.94
1752.50	5	QPSK	V	150	95	1 / 24	11.29	8.74	20.03	30.00	-9.97
1712.50	5	16-QAM	V	144	89	1 / 0	9.62	9.26	18.88	30.00	-11.12
1732.50	5	16-QAM	V	143	91	1 / 0	11.01	9.00	20.01	30.00	-9.99
1752.50	5	16-QAM	V	150	95	1 / 24	10.55	8.74	19.29	30.00	-10.71
1715.00	10	QPSK	V	144	92	1 / 49	10.94	9.22	20.16	30.00	-9.84
1732.50	10	QPSK	V	145	93	1 / 49	11.62	9.00	20.62	30.00	-9.38
1750.00	10	QPSK	V	145	96	1 / 0	11.00	8.77	19.77	30.00	-10.23
1715.00	10	16-QAM	V	144	92	1 / 49	10.19	9.22	19.41	30.00	-10.59
1732.50	10	16-QAM	V	145	93	1 / 49	10.88	9.00	19.88	30.00	-10.12
1750.00	10	16-QAM	V	145	96	1 / 0	10.24	8.77	19.01	30.00	-10.99
1717.50	15	QPSK	V	148	91	1 / 74	10.98	9.19	20.17	30.00	-9.83
1732.50	15	QPSK	V	142	94	1 / 74	11.70	9.00	20.70	30.00	-9.30
1747.50	15	QPSK	V	142	93	1 / 0	11.42	8.80	20.22	30.00	-9.78
1717.50	15	16-QAM	V	148	91	1 / 74	10.02	9.19	19.21	30.00	-10.79
1732.50	15	16-QAM	V	142	94	1 / 74	10.91	9.00	19.91	30.00	-10.09
1747.50	15	16-QAM	V	142	93	1 / 0	10.38	8.80	19.18	30.00	-10.82
1720.00	20	QPSK	V	149	94	1 / 99	11.55	9.16	20.71	30.00	-9.29
1732.50	20	QPSK	V	146	93	1 / 99	11.26	9.00	20.26	30.00	-9.74
1745.00	20	QPSK	V	145	89	1 / 0	11.69	8.83	20.52	30.00	-9.48
1720.00	20	16-QAM	V	149	94	1 / 99	10.65	9.16	19.81	30.00	-10.19
1732.50	20	16-QAM	V	146	93	1 / 99	10.10	9.00	19.10	30.00	-10.90
1745.00	20	16-QAM	V	145	89	1 / 0	10.97	8.83	19.80	30.00	-10.20

Table 7-3. EIRP Data (Band 4)

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 16 of 25	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	V	144	84	1 / 5	13.66	8.34	22.00	33.01	-11.01
1880.00	1.4	QPSK	V	140	70	1 / 0	13.59	8.46	22.05	33.01	-10.96
1909.30	1.4	QPSK	V	132	82	1 / 0	12.94	8.64	21.58	33.01	-11.43
1850.70	1.4	16-QAM	V	144	84	1 / 5	13.27	8.34	21.61	33.01	-11.40
1880.00	1.4	16-QAM	V	140	70	1 / 0	12.87	8.46	21.33	33.01	-11.68
1909.30	1.4	16-QAM	V	132	82	1 / 0	12.34	8.64	20.98	33.01	-12.03
1851.50	3	QPSK	V	143	81	1 / 14	13.96	8.35	22.31	33.01	-10.70
1880.00	3	QPSK	V	136	69	1 / 0	13.79	8.46	22.25	33.01	-10.76
1908.50	3	QPSK	V	134	79	1 / 0	13.83	8.63	22.46	33.01	-10.55
1851.50	3	16-QAM	V	143	81	1 / 14	13.07	8.35	21.42	33.01	-11.59
1880.00	3	16-QAM	V	136	69	1 / 0	13.17	8.46	21.63	33.01	-11.38
1908.50	3	16-QAM	V	134	79	1 / 0	13.52	8.63	22.15	33.01	-10.86
1852.50	5	QPSK	V	138	83	1 / 0	13.71	8.35	22.06	33.01	-10.95
1880.00	5	QPSK	V	137	74	1 / 0	13.85	8.46	22.31	33.01	-10.70
1907.50	5	QPSK	V	139	79	1 / 0	13.47	8.62	22.09	33.01	-10.92
1852.50	5	16-QAM	V	138	83	1 / 0	12.33	8.35	20.68	33.01	-12.33
1880.00	5	16-QAM	V	137	74	1 / 0	12.71	8.46	21.17	33.01	-11.84
1907.50	5	16-QAM	V	139	79	1 / 0	13.05	8.62	21.67	33.01	-11.34
1855.00	10	QPSK	V	139	84	1 / 49	14.13	8.36	22.49	33.01	-10.52
1880.00	10	QPSK	V	137	75	1 / 49	13.60	8.46	22.06	33.01	-10.95
1905.00	10	QPSK	V	138	74	1 / 0	13.70	8.59	22.29	33.01	-10.72
1855.00	10	16-QAM	V	139	84	1 / 49	13.40	8.36	21.76	33.01	-11.25
1880.00	10	16-QAM	V	137	75	1 / 49	13.42	8.46	21.88	33.01	-11.13
1905.00	10	16-QAM	V	138	74	1 / 0	12.75	8.59	21.34	33.01	-11.67
1857.50	15	QPSK	V	142	82	1 / 0	13.49	8.37	21.86	33.01	-11.15
1880.00	15	QPSK	V	139	75	1 / 74	13.45	8.46	21.91	33.01	-11.10
1902.50	15	QPSK	V	142	78	1 / 0	12.71	8.56	21.27	33.01	-11.74
1857.50	15	16-QAM	V	142	82	1 / 0	12.77	8.37	21.14	33.01	-11.87
1880.00	15	16-QAM	V	139	75	1 / 74	12.62	8.46	21.08	33.01	-11.93
1902.50	15	16-QAM	V	142	78	1 / 0	11.85	8.56	20.41	33.01	-12.60
1860.00	20	QPSK	V	143	83	1 / 99	14.07	8.38	22.45	33.01	-10.56
1880.00	20	QPSK	V	140	79	1 / 0	13.71	8.46	22.17	33.01	-10.84
1900.00	20	QPSK	V	144	78	1 / 99	13.13	8.53	21.66	33.01	-11.35
1860.00	20	16-QAM	V	143	83	1 / 99	12.85	8.38	21.23	33.01	-11.78
1880.00	20	16-QAM	V	140	79	1 / 0	12.44	8.46	20.90	33.01	-12.11
1900.00	20	16-QAM	V	144	78	1 / 99	12.64	8.53	21.17	33.01	-11.84

Table 7-4. EIRP Data (Band 2)

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 17 of 25	

7.3 Radiated Spurious Emissions Measurements

§2.1053 §24.238(a) §27.53(c) §27.53(f) §27.53(h)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 18 of 25	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-3. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 5) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 19 of 25

OPERATING FREQUENCY: 779.50 MHz
 CHANNEL: 23205
 MEASURED OUTPUT POWER: 18.42 dBm = 0.069 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.42 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2338.50	H	123	9	-63.59	7.28	-56.31	74.7
3118.00	H	-	-	-62.93	7.25	-55.68	74.1
3897.50	H	-	-	-58.44	7.10	-51.35	69.8

Table 7-5. Radiated Spurious Data (Band 13 – Low Channel)

OPERATING FREQUENCY: 782.00 MHz
 CHANNEL: 23230
 MEASURED OUTPUT POWER: 18.32 dBm = 0.068 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.32 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2346.00	H	101	367	-61.23	7.26	-53.97	72.3
3128.00	H	-	-	-60.76	7.26	-53.50	71.8
3910.00	H	-	-	-56.41	7.14	-49.27	67.6

Table 7-6. Radiated Spurious Data (Band 13 – Mid Channel)

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 20 of 25	

OPERATING FREQUENCY: 784.50 MHz
 CHANNEL: 23255
 MEASURED OUTPUT POWER: 18.24 dBm = 0.067 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.24 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2353.50	H	101	126	-61.22	7.25	-53.97	72.2
3138.00	H	-	-	-60.78	7.27	-53.51	71.8
3922.50	H	-	-	-56.18	7.20	-48.98	67.2

Table 7-7. Radiated Spurious Data (Band 13 – High Channel)

MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.00 MHz
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1559.00	H	-	-	-65.57	6.42	-59.15	-19.1
1564.00	H	-	-	-66.19	6.44	-59.75	-19.7
1569.00	H	-	-	-65.61	6.46	-59.15	-19.2

Table 7-8. Radiated Spurious Data (Band 13 – 1559-1610MHz Band)

FCC ID: ZNFL82VL		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 21 of 25	

OPERATING FREQUENCY: 1711.50 MHz
 CHANNEL: 19965
 MEASURED OUTPUT POWER: 19.87 dBm = 0.097 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.87 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3423.00	H	111	300	-42.07	9.68	-32.38	52.3
5134.50	H	105	260	-55.45	10.68	-44.76	64.6
6846.00	H	108	335	-50.94	11.74	-39.19	59.1
8557.50	H	109	265	-44.83	11.05	-33.78	53.7

Table 7-9. Radiated Spurious Data (Band 4 – Low Channel)

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 20175
 MEASURED OUTPUT POWER: 21.31 dBm = 0.135 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 34.31 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.00	H	159	218	-45.36	9.71	-35.66	57.0
5197.50	H	102	265	-55.12	10.59	-44.54	65.8
6930.00	H	103	206	-51.10	11.75	-39.35	60.7
8662.50	H	105	281	-47.91	11.06	-36.85	58.2

Table 7-10. Radiated Spurious Data (Band 4 – Mid Channel)

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 22 of 25	

OPERATING FREQUENCY: 1753.50 MHz
 CHANNEL: 20385
 MEASURED OUTPUT POWER: 19.71 dBm = 0.093 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.71 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3507.00	H	107	258	-46.58	9.73	-36.85	56.6
5260.50	H	105	252	-54.97	10.64	-44.33	64.0
7014.00	H	107	9	-50.32	11.75	-38.57	58.3
8767.50	H	109	289	-48.82	11.00	-37.82	57.5

Table 7-11. Radiated Spurious Data (Band 4 – High Channel)

OPERATING FREQUENCY: 1855.00 MHz
 CHANNEL: 18650
 MEASURED OUTPUT POWER: 22.49 dBm = 0.177 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 35.49 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3710.00	H	132	258	-52.84	9.41	-43.42	65.9
5565.00	H	132	231	-54.34	10.82	-43.52	66.0
7420.00	H	128	21	-48.96	10.74	-38.22	60.7
9275.00	H	-	-	-50.95	11.59	-39.36	61.9
11130.00	H	-	-	-50.80	12.78	-38.01	60.5

Table 7-12. Radiated Spurious Data (Band 2 – Low Channel)

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset		Page 23 of 25

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 18900
 MEASURED OUTPUT POWER: 22.06 dBm = 0.161 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 35.06 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	147	252	-48.09	9.28	-38.81	60.9
5640.00	H	101	138	-56.16	11.03	-45.12	67.2
7520.00	H	109	79	-44.43	10.97	-33.46	55.5
9400.00	H	-	-	-51.10	11.53	-39.57	61.6
11280.00	H	109	203	-47.22	12.71	-34.51	56.6

Table 7-13. Radiated Spurious Data (Band 2 – Mid Channel)

OPERATING FREQUENCY: 1905.00 MHz
 CHANNEL: 19150
 MEASURED OUTPUT POWER: 22.29 dBm = 0.170 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 35.29 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3810.00	H	131	284	-48.15	9.19	-38.96	61.3
5715.00	H	139	241	-56.06	11.26	-44.80	67.1
7620.00	H	135	60	-49.13	11.16	-37.97	60.3
9525.00	H	-	-	-51.91	11.76	-40.15	62.4
11430.00	H	128	15	-46.42	12.73	-33.69	56.0

Table 7-14. Radiated Spurious Data (Band 2 – High Channel)

FCC ID: ZNFL82VL			FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset			Page 24 of 25

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Electronics Portable Handset FCC ID: ZNFL82VL** complies with all the requirements of Parts 24 & 27 of the FCC rules for LTE operation only.

FCC ID: ZNFL82VL	 FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180110.ZNF	Test Dates: 01/19-01/29/2016	EUT Type: Portable Handset	Page 25 of 25	