

EMI TEST REPORT FCC CERTIFICATION

Applicant: LG Electronics MobileComm U.S.A., Inc. 1000 Sylvan Avenue, Englewood Cliffs NJ 07632	Date of Receipt: December 19, 2016 Date of Issue: January 05, 2017 Test Report No. HCT-E-1701-F011 HCT FRN: 0005866421
--	---

FCC ID :

ZNFL84VL

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Multi-band CDMA/LTE phone with Bluetooth and WLAN
Model Name: LGL84VL
Additional Model Name: L84VL, LG-L84VL
Date of Test: December 23, 2016 - December 26, 2016

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)
I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.
HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Yeong-Moo Kim
Test Engineer
EMC Team
Certification Division

Reviewed By



Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1701-F011	January 05, 2017	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility	5
1.4 Calibration of Measuring Instrument	5
1.5 Tested System Details.....	6
1.6 Cable Description	7
1.7 Noise Suppression Parts on Cable. (I/O Cable)	7
2. MEASUREMENT UNCERTAINTY	8
3. DESCRIPTION OF TEST	9
3.1 Measurement of Conducted Emission.....	9
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	12
4.1 Conducted Emission Test	12
4. 2 Radiated Emission Test	12
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	13
5.1 Conducted Emission Test	13
5.2 Radiated Emission Test	20
6. LIST OF TEST EQUIPMENT	22
7. CONCLUSION	23

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFL84VL
Model	LGL84VL
Additional Model	L84VL, LG-L84VL
EUT Type	Multi-band CDMA/LTE phone with Bluetooth and WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA 850) 1 851.25 MHz to 1 908.75 MHz (CDMA 1 900) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 777 MHz to 787 MHz (LTE B13) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA 850) 1 931.25 MHz to 1 988.75 MHz (CDMA 1 900) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 746 MHz to 756 MHz (LTE B13) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.

Measurement Facilities	Registration Number
Radiated Field strength measurement facility (3 m)	90661 (July 07, 2015)
Radiated Field strength measurement facility (10 m)	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LGL84VL	LG	ZNFL84VL	Notebook PC, Earphone
USB Cable	EAD62377928	Ningbo Broad	-	EUT, Notebook PC
USB Cable	EAD62377926	LEAGTECH	-	EUT, Notebook PC
USB Cable	EAD62377925	CRESYN	-	EUT, Notebook PC
USB Cable	EAD62377924	KSD	-	EUT, Notebook PC
Earphone	EAB62950102	CRESYN	-	EUT
Notebook PC	ProBook6560b	HP	DoC	Gateway , Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	Series PPP009L-E	LITE-On Technology	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
SD card	256 GB EVO+UHS-I Micro SDXC U1	SAMSUNG	-	EUT



1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.6
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	Both End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.158 MHz to 30 MHz)	± 1.82 dB ($k = 2$)
Radiated Emissions (30 MHz to 1 GHz)	± 5.06 dB ($k = 2$)
Radiated Emissions (1 GHz to 6 GHz)	± 5.0 dB ($k = 2$)
Radiated Emissions (6 GHz to 18 GHz)	± 5.4 dB ($k = 2$)



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

4.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of USB Cable	CRESYN (EAD62377925)
Operation Mode	Data Communication mode
Kind of Test Site	Shielded Room
Temperature	23.2 °C
Relative Humidity	36.2 %
Test Date	December 24, 2016

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	44.8	9.000	L1	9.6	21.2	66.0
0.156000	46.0	9.000	L1	9.6	19.7	65.7
0.164000	45.6	9.000	L1	9.6	19.7	65.3
0.172000	45.0	9.000	L1	9.6	19.9	64.9
0.178000	42.2	9.000	L1	9.6	22.4	64.6
0.182000	41.5	9.000	L1	9.6	22.9	64.4
2.744000	28.4	9.000	L1	9.8	27.6	56.0
2.802000	28.7	9.000	L1	9.8	27.3	56.0
2.842000	28.7	9.000	L1	9.8	27.3	56.0
2.880000	28.8	9.000	L1	9.8	27.2	56.0
2.920000	28.4	9.000	L1	9.8	27.6	56.0
3.118000	28.1	9.000	L1	9.8	27.9	56.0
9.094000	28.9	9.000	L1	10.1	31.1	60.0
9.252000	28.9	9.000	L1	10.1	31.1	60.0
9.294000	28.9	9.000	L1	10.1	31.1	60.0
9.298000	29.0	9.000	L1	10.1	31.0	60.0
9.432000	29.0	9.000	L1	10.1	31.0	60.0
9.436000	31.6	9.000	L1	10.1	28.4	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	31.2	9.000	L1	9.6	24.8	56.0
0.156000	32.2	9.000	L1	9.6	23.5	55.7
0.160000	31.6	9.000	L1	9.6	23.9	55.5
0.172000	32.0	9.000	L1	9.6	22.9	54.9
0.178000	29.1	9.000	L1	9.6	25.5	54.6
0.182000	25.9	9.000	L1	9.6	28.5	54.4
2.744000	21.1	9.000	L1	9.8	24.9	46.0
2.802000	21.3	9.000	L1	9.8	24.7	46.0
2.842000	21.2	9.000	L1	9.8	24.8	46.0
2.880000	20.9	9.000	L1	9.8	25.1	46.0
2.920000	20.9	9.000	L1	9.8	25.1	46.0
3.000000	20.9	9.000	L1	9.8	25.1	46.0
9.106000	22.3	9.000	L1	10.1	27.7	50.0
9.166000	22.4	9.000	L1	10.1	27.6	50.0
9.186000	22.7	9.000	L1	10.1	27.3	50.0
9.282000	22.4	9.000	L1	10.1	27.6	50.0
9.298000	22.6	9.000	L1	10.1	27.4	50.0
9.436000	24.0	9.000	L1	10.1	26.0	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	47.1	9.000	N	9.6	18.9	66.0
0.156000	46.2	9.000	N	9.6	19.5	65.7
0.160000	47.6	9.000	N	9.6	17.8	65.5
0.168000	45.1	9.000	N	9.6	20.0	65.1
0.172000	45.4	9.000	N	9.6	19.4	64.9
0.180000	41.1	9.000	N	9.6	23.4	64.5
4.180000	26.0	9.000	N	9.8	30.0	56.0
4.380000	25.5	9.000	N	9.9	30.5	56.0
4.438000	24.9	9.000	N	9.9	31.1	56.0
4.462000	24.7	9.000	N	9.9	31.3	56.0
4.500000	23.8	9.000	N	9.9	32.2	56.0
4.530000	23.9	9.000	N	9.9	32.1	56.0
9.318000	26.8	9.000	N	10.1	33.2	60.0
9.608000	28.0	9.000	N	10.1	32.0	60.0
9.652000	27.8	9.000	N	10.1	32.2	60.0
9.670000	28.1	9.000	N	10.1	31.9	60.0
9.676000	28.1	9.000	N	10.1	31.9	60.0
9.864000	28.7	9.000	N	10.1	31.3	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	31.3	9.000	N	9.6	24.7	56.0
0.156000	31.8	9.000	N	9.6	23.9	55.7
0.160000	33.7	9.000	N	9.6	21.8	55.5
0.168000	32.3	9.000	N	9.6	22.8	55.1
0.172000	31.0	9.000	N	9.6	23.9	54.9
0.178000	28.6	9.000	N	9.6	26.0	54.6
4.180000	18.7	9.000	N	9.8	27.3	46.0
4.380000	18.2	9.000	N	9.9	27.8	46.0
4.398000	18.3	9.000	N	9.9	27.7	46.0
4.438000	17.8	9.000	N	9.9	28.2	46.0
4.462000	17.7	9.000	N	9.9	28.3	46.0
4.474000	17.4	9.000	N	9.9	28.6	46.0
9.308000	20.1	9.000	N	10.1	29.9	50.0
9.318000	19.2	9.000	N	10.1	30.8	50.0
9.604000	20.6	9.000	N	10.1	29.4	50.0
9.608000	20.9	9.000	N	10.1	29.1	50.0
9.634000	20.8	9.000	N	10.1	29.2	50.0
9.676000	21.0	9.000	N	10.1	29.0	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Worst Case of USB Cable	Ningbo Broad (EAD62377928)
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.7 °C
Relative Humidity	36.3 %
Test Date	December 23, 2016

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
54.056000	28.5	100.0	V	195.0	22.8	11.5	40.0
58.803200	29.5	304.0	V	333.0	22.5	10.5	40.0
63.519200	28.6	125.0	V	168.0	22.0	11.4	40.0
82.326400	31.5	250.0	H	84.0	18.5	8.5	40.0
105.654800	30.0	130.0	V	128.0	18.9	13.5	43.5
265.516000	33.7	150.0	H	240.0	22.6	12.3	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2.48 GHz
Upper Frequency of Measurement Range	1 GHz to 12.4 GHz
Worst Case of USB Cable	Ningbo Broad (EAD62377928)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	25.9 °C
Relative Humidity	38.0 %
Test Date	December 26, 2016

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1000.040000	41.8	367.5	H	0.0	-13.9	32.2	74.0
1400.155000	46.0	328.6	V	53.0	-12.8	28.0	74.0
1800.230000	42.8	100.0	V	26.0	-12.3	31.2	74.0
2063.355000	47.8	100.0	V	211.0	-11.9	26.2	74.0
2665.760000	46.6	150.1	V	165.0	-9.1	27.4	74.0
3599.675000	43.5	344.8	H	195.0	-8.3	30.5	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1000.040000	34.1	367.5	H	0.0	-13.9	19.9	54.0
1400.155000	44.1	328.6	V	53.0	-12.8	9.9	54.0
1800.230000	36.6	100.0	V	26.0	-12.3	17.4	54.0
2063.355000	22.4	100.0	V	211.0	-11.9	31.6	54.0
2665.760000	23.0	150.1	V	165.0	-9.1	31.0	54.0
3599.675000	30.5	344.8	H	195.0	-8.3	23.5	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.23.2016
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	06.09.2016
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	12.23.2016
<input type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESIB26	100298	1 year	02.11.2016
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	255	2 year	04.15.2015
<input checked="" type="checkbox"/> 6dB Attenuator	HP	8491A	24257	2 year	04.15.2015
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESIB26	100298	1 year	02.11.2016
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
<input type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4000-XP-ET	48709515	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.04.2016
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.07.2016
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170541	2 year	09.03.2015
<input type="checkbox"/> Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.11.2016
<input type="checkbox"/> Power Amplifier	CERNEX	CBL26405040	19660	1 year	07.15.2016
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	08.25.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Multi-band CDMA/LTE phone with Bluetooth and WLAN, Model: LGL84VL, FCC ID: ZNFL84VL** complies with §15.107 and §15.109 of the FCC rules.