



FCC CFR47 PART 15 SUBPART C

CERTIFICATION TEST REPORT

FOR

GSM & W-CDMA Phone + BT

MODEL NUMBER: LG440G

FCC ID: ZNFLG440G

REPORT NUMBER: 12U14489

ISSUE DATE: 2012-07-10

Prepared for
LG ELECTRONICS MOBILECOMM U.S.A, INC.
1000 SYLVAN AVE.
EDGEWOOD CLIFFS, NJ, 07632, USA

Prepared by
UNDERWRITERS LABORATORIES INC.
1285 WALT WHITMAN RD.
MELVILLE, NY 11747, U.S.A.
TEL: (631) 271-6200
FAX: (877) 854-3577



NVLAP LAB CODE 100255-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	07/10/12	Initial Issue	M. Antola

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>6</i>
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT</i>	<i>7</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>7</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>7</i>
5.4. <i>SOFTWARE AND FIRMWARE.....</i>	<i>7</i>
5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>8</i>
5.6. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
6. TEST AND MEASUREMENT EQUIPMENT	11
7. ANTENNA PORT TEST RESULTS	13
7.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>13</i>
7.1.1. <i>20 dB BANDWIDTH.....</i>	<i>13</i>
7.1.2. <i>HOPPING FREQUENCY SEPARATION</i>	<i>17</i>
7.1.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>19</i>
7.1.4. <i>AVERAGE TIME OF OCCUPANCY</i>	<i>24</i>
7.1.5. <i>OUTPUT POWER</i>	<i>31</i>
7.1.6. <i>AVERAGE POWER</i>	<i>35</i>
7.1.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>36</i>
7.2. <i>ENHANCED DATA RATE QPSK MODULATION.....</i>	<i>45</i>
7.2.1. <i>20 dB BANDWIDTH.....</i>	<i>45</i>
7.2.2. <i>HOPPING FREQUENCY SEPARATION</i>	<i>49</i>
7.2.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>51</i>
7.2.4. <i>AVERAGE TIME OF OCCUPANCY</i>	<i>56</i>
7.2.5. <i>OUTPUT POWER</i>	<i>63</i>
7.2.6. <i>AVERAGE POWER</i>	<i>67</i>
7.2.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>68</i>
7.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>77</i>
7.3.1. <i>20 dB BANDWIDTH.....</i>	<i>77</i>
7.3.2. <i>HOPPING FREQUENCY SEPARATION</i>	<i>81</i>
7.3.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>83</i>
7.3.4. <i>AVERAGE TIME OF OCCUPANCY</i>	<i>88</i>
7.3.5. <i>OUTPUT POWER</i>	<i>95</i>

7.3.6.	AVERAGE POWER	99
7.3.7.	CONDUCTED SPURIOUS EMISSIONS	100
8.	RADIATED TEST RESULTS	109
8.1.	LIMITS AND PROCEDURE	109
8.2.	TRANSMITTER ABOVE 1 GHz	110
8.2.1.	BASIC DATA RATE GFSK MODULATION	110
8.2.2.	ENHANCED DATA RATE QPSK MODULATION	115
8.2.3.	ENHANCED DATA RATE 8PSK MODULATION	120
8.3.	WORST-CASE BELOW 1 GHz	125
9.	SETUP PHOTOS	127

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A, INC.
1000 SYLVAN AVE.
ENGLEWOOD CLIFFS, NJ, 07632, USA

EUT DESCRIPTION: GSM & W-CDMA Phone + BT

MODEL: LG440G

SERIAL NUMBER: 204KPTM163009 & 204KPLC163008

DATE TESTED: 2012-06-29 to 2012-07-05

APPLICABLE STANDARDS{PRIVATE }	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL LLC based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation, as described by the referenced documents. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL By:



Michael Ferrer
Sr. Project Engineer
UL LLC

Tested By:



Michael Antola
Sr. Project Engineer
UL LLC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 1285 Walt Whitman Rd. Melville, NY 11747, USA.

UL Melville is accredited by NVLAP, Laboratory Code 100255-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/1002550.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	± 3.3 dB
Radiated Disturbance, 30 to 1000 MHz	± 4.00 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM & W-CDMA Phone + BT.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	9.86	9.68
2402 - 2480	DQPSK	10.23	10.54
2402 - 2480	Enhanced 8PSK	10.35	10.84

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIFA antenna, with a maximum gain of 3.65 dBi.

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was KERNAL, Version 3.0.8.

The test utility software used during testing was LA89601R120414A.

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z, it was determined that the X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Testing was performed in all three modulations – GFSK, QPSK and 8PSK. It was determined that the worse-case data rate was DH5, thus all testing was performed in this rate only.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List			
Description	Manufacturer	Model	Serial Number
AC Adapter	LG Electronics	STA-U34WRI	RC22038224
Headphones	LG Electronics	-	-


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC	1	Mini USB	Unshielded	1	None

TEST SETUP

The EUT is a stand-alone device. Test modes were configured via connection to the BT tester.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment Used – Radiated Emissions					
Description	Manufacturer	Model	Identifier	Cal Date	Cal Due Date
30-1000MHz					
EMI Receiver	Rohde & Schwarz	ESIB26	ME5B-081	2012-01-30	2012-01-30
Bicon Antenna	Schaffner	VBA6106A	54	2012-04-10	2013-04-10
Log-P Antenna	Schaffner	UPA6109	44067	2012-05-16	2013-05-16
Switch Driver	HP	11713A	ME7A-627	N/A	N/A
System Controller	Sunol Sciences	SC99V	44396	N/A	N/A
Camera Controller	Panasonic	WV-CU254	44395	N/A	N/A
RF Switch Box	UL	1	44398	N/A	N/A
Measurement Software	UL	Version 9.3	44740	N/A	N/A
Temp/Humidity/Pressure Meter	Cole Parmer	99760-00	4268	2010-12-07	2012-12-07
Multimeter	Fluke	83V	43443	2012-02-01	2013-02-28
Above 1GHz (Band Optimized System)					
EMI Receiver	Rohde & Schwarz	ESIB40	34968	2012-03-06	2013-03-06
Horn Antenna (1-2 GHz)	ETS	3161-01	51442	2008-03-28	See * below
Horn Antenna (2-4 GHz)	ETS	3161-02	48107	2007-09-27	See * below
Horn Antenna (4-8 GHz)	ETS	3161-03	48106	2007-09-27	See * below
Horn Antenna (8-12 GHz)	ETS	3160-07	8933	2008-11-24	See * below
Horn Antenna (12-18 GHz)	ETS	3160-08	8932	2007-09-27	See * below
Horn Antenna (18-26.5 GHz)	ETS	3160-09	8947	2007-09-26	See * below
Signal Path Controller	HP	11713A	50250	N/A	N/A
Gain Controller	HP	11713A	50251	N/A	N/A
RF Switch / Preamp Fixture	UL	BOMS1	50249	N/A	N/A
System Controller	UL	BOMS2	50252	N/A	N/A
Measurement Software	UL	Version 9.3	44740	N/A	N/A
Temp/Humidity/Pressure Meter	Cole Parmer	99760-00	4268	2010-12-07	2012-12-07
Multimeter	Fluke	83V	43443	2012-02-01	2013-02-28
<p>* - Note: As allowed by the calibration standard ANSI C63.4 Section 4.4.2, standard gain horns need only a one-time calibration. Only if physical damage occurs will the horn antenna require re-calibration.</p> <p>* Gain standard horn antennas (sometimes called standard gain horn antennas) need not be calibrated beyond that which is provided by the manufacturer unless they are damaged or deterioration is suspected, or they are used at a distance closer than $2D^2/\lambda$. Gain standard horn antennas have gains that are fixed by their dimensions and dimensional tolerances.</p>					

Test Equipment Used – Antenna Port					
Description	Manufacturer	Model	Identifier	Cal Date	Cal Due Date
Spectrum Analyzer	Agilent	E4446A	72823	2012-01-31	2013-02-28
Power Meter	HP	437B	73872	2012-01-30	2013-02-28
Power Sensor	HP	8481A	71770	2012-01-31	2013-02-28
Temp/Humidity/Pressure Meter	Cole Parmer	99760-00	43733	2012-03-13	2014-03-13
Multimeter	Fluke	83V	43443	2012-02-01	2013-02-28

7. ANTENNA PORT TEST RESULTS

7.1. BASIC DATA RATE GFSK MODULATION

7.1.1. 20 dB BANDWIDTH

LIMIT

None; for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.


RESULTS

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
Low	2402	524.725
Middle	2441	522.673
High	2480	525.549

20 dB BANDWIDTH







7.1.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION



7.1.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS


Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS









7.1.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$.


RESULTS

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
GFSK Normal Mode					
DH1	0.38	32	0.122	0.4	-0.278
DH3	1.625	13	0.211	0.4	-0.189
DH5	2.858	8	0.229	0.4	-0.171


PULSE WIDTH - DH1




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1




PULSE WIDTH – DH3




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



PULSE WIDTH – DH5



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5



7.1.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

RSS-210 Issue 7 Clause A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	9.3	30	-20.70
Middle	2441	9.73	30	-20.27
High	2480	9.82	30	-20.18

OUTPUT POWER







7.1.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB connector) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	7.62
Middle	2441	8
High	2480	8.15

7.1.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS


SPURIOUS EMISSIONS, LOW CHANNEL







SPURIOUS EMISSIONS, MID CHANNEL







SPURIOUS EMISSIONS, HIGH CHANNEL





SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON





7.2. ENHANCED DATA RATE QPSK MODULATION

7.2.1. 20 dB BANDWIDTH

LIMIT

None; for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.


RESULTS

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
Low	2402	796.802
Middle	2441	1011
High	2480	794.533

20 dB BANDWIDTH







7.2.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION



7.2.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS


Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS









7.2.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.


RESULTS

Time Of Occupancy = 10 * xx pulses * yy msec = zz msec


DQPSK Mode

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of (sec)	Limit (sec)	Margin (sec)
DH1	0.385	32	0.123	0.4	-0.277
DH3	1.625	17	0.276	0.4	-0.124
DH5	2.87	8	0.230	0.4	-0.170


PULSE WIDTH - DH1




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



PULSE WIDTH – DH5



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5



7.2.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

RSS-210 Issue 7 Clause A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	9.29	30	-20.71
Middle	2441	9.75	30	-20.25
High	2480	9.83	30	-20.17

OUTPUT POWER







7.2.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB connector) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	6.15
Middle	2441	6.56
High	2480	6.69

7.2.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS


SPURIOUS EMISSIONS, LOW CHANNEL







SPURIOUS EMISSIONS, MID CHANNEL







SPURIOUS EMISSIONS, HIGH CHANNEL





SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON





7.3. ENHANCED DATA RATE 8PSK MODULATION

7.3.1. 20 dB BANDWIDTH

LIMIT

None; for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.


RESULTS

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
Low	2402	999.852
Middle	2441	1004
High	2480	1000

20 dB BANDWIDTH







7.3.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION



7.3.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS


Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS









7.3.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.


RESULTS

Time Of Occupancy = $10 * xx \text{ pulses} * yy \text{ msec} = zz \text{ msec}$


8PSK (EDR) Mode

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of (sec)	Limit (sec)	Margin (sec)
DH1	0.39	32	0.125	0.4	-0.275
DH3	1.617	14	0.226	0.4	-0.174
DH5	2.87	10	0.287	0.4	-0.113


NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1




PULSE WIDTH – DH3




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



PULSE WIDTH – DH5



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5



7.3.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

RSS-210 Issue 7 Clause A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	9.36	30	-20.64
Middle	2441	9.85	30	-20.15
High	2480	9.92	30	-20.08

OUTPUT POWER







7.3.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB connector) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	6.1
Middle	2441	6.45
High	2480	6.64

7.3.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS


SPURIOUS EMISSIONS, LOW CHANNEL







SPURIOUS EMISSIONS, MID CHANNEL







SPURIOUS EMISSIONS, HIGH CHANNEL





SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON





8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


Where necessary, a duty cycle correction factor of -24.44 was applied to the measurements. This was derived from the EUT having a total of two (2) 3ms pulses in a 100ms window:


$$DCF = 20\log (Pulse\ width / Total\ Transmissions\ Time) = 20\log (6 / 100) = -24.44dB$$

8.2. TRANSMITTER ABOVE 1 GHz


8.2.1. BASIC DATA RATE GFSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL)






RESTRICTED BANDEDGE (HIGH CHANNEL)







8.2.2. ENHANCED DATA RATE QPSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL)





RESTRICTED BANDEDGE (HIGH CHANNEL)







HARMONICS AND SPURIOUS EMISSIONS

Manufacturer:LG Electronics														
Device:Cell Phone w/BT QPSK														
Model:LG440G														
Job#:12U14489														
Tested by:BD														
Test Frequency	Meter Reading	Detector	AF-48106 [dB]	BOMS Factor [dB]	dB(uVolts /meter)	DCF [dB]	Corrected Level dB(uVolts /meter)	FCC Part 15 Subpart C	Margin	FCC Part 15 Subpart C	Margin	Azimuth [Degs]	Height [cm]	Polarity
Low Channel														
4804.2255	84.29	PK	27.1	-52.69	58.7	-	-	54	4.7	74	-15.3	179	355	Vert
4804.2255	68.65	Av	27.1	-52.69	43.06	-	-	54	-10.94	74	-30.94	179	355	Vert
4804.2255	85.9	PK	27.1	-52.69	60.31	-	-	54	6.31	74	-13.69	177	346	Horz
4804.2255	69.92	Av	27.1	-52.69	44.33	-	-	54	-9.67	74	-29.67	177	346	Horz
Mid Channel														
4882	87.19	PK	27.2	-52.5	61.89	-	-	54	7.89	74	-12.11	315	309	Vert
4882	70.77	Av	27.2	-52.5	45.47	-	-	54	-8.53	74	-28.53	315	309	Vert
4882	89.42	PK	27.2	-52.5	64.12	-	-	54	10.12	74	-9.88	31	366	Horz
4882	72.7	Av	27.2	-52.5	47.4	-	-	54	-6.6	74	-26.6	31	366	Horz
7323.4248	64.45	PK	28	-51.79	40.66	-	-	54	-13.34	74	-33.34	117	179	Horz
7323.4248	48.02	Av	28	-51.79	24.23	-	-	54	-29.77	74	-49.77	117	179	Horz
7323.4248	67.38	PK	28	-51.79	43.59	-	-	54	-10.41	74	-30.41	158	297	Vert
7323.4248	49.59	Av	28	-51.79	25.8	-	-	54	-28.2	74	-48.2	158	297	Vert
High Channel														
4960.1403	89.66	PK	27.3	-52.34	64.62	-	-	54	10.62	74	-9.38	307	387	Vert
4960.1403	73.19	Av	27.3	-52.34	48.15	-	-	54	-5.85	74	-25.85	307	387	Vert
4960.1403	89.21	PK	27.3	-52.34	64.17	-	-	54	10.17	74	-9.83	45	303	Horz
4960.1403	72.85	Av	27.3	-52.34	47.81	-	-	54	-6.19	74	-26.19	45	303	Horz
7440	67.42	PK	28.1	-51.39	44.13	-	-	54	-9.87	74	-29.87	109	313	Horz
7440	53.28	Av	28.1	-51.39	29.99	-	-	54	-24.01	74	-44.01	109	313	Horz
7440	67.54	PK	28.1	-51.39	44.25	-	-	54	-9.75	74	-29.75	192	269	Vert
7440	52.45	Av	28.1	-51.39	29.16	-	-	54	-24.84	74	-44.84	192	269	Vert
PK - Peak detector														
QP - Quasi-Peak detector														
LnAv - Linear Average detector														
LgAv - Log Average detector														
Av - Average detector														
CAV - CISPR Average detector														
RMS - RMS detection														
CRMS - CISPR RMS detection														
Note: All harmonics were investigated. Only those which were not found to be noise floor were reported.														


8.2.3. ENHANCED DATA RATE 8PSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL)





RESTRICTED BANDEDGE (HIGH CHANNEL)






HARMONICS AND SPURIOUS EMISSIONS

Manufacturer:LG Electronics														
Device:Cell Phone w/BT 8PSK														
Model:LG440G														
Job#:12U14489														
Tested by:BD														
								Corrected	FCC Part		FCC Part			
Test	Meter		AF-48106	BOMS	dB(uVolts/		level	15	15		15			
Frequency	Reading	Detector	[dB]	Factor	meter)	DCF [dB]	dB(uVolts/	Subpart C	Subpart C	Margin	Peak	Margin	Azimuth	
Low							meter)	15.209					Height	
Channel													[Degs]	
													[cm]	
													Polarity	
4804.2255	80.75	PK	27.1	-52.69	55.16	-	-	54	1.16	74	-18.84	321	144	Vert
4804.2255	65.44	Av	27.1	-52.69	39.85	-	-	54	-14.15	74	-34.15	321	144	Vert
4804.2255	86.92	PK	27.1	-52.69	61.33	-	-	54	7.33	74	-12.67	180	301	Horz
4804.2255	70.82	Av	27.1	-52.69	45.23	-	-	54	-8.77	74	-28.77	180	301	Horz
Mid Channel														
4882	89.05	PK	27.2	-52.5	63.75	-	-	54	9.75	74	-10.25	180	293	Horz
4882	72.4	Av	27.2	-52.5	47.1	-	-	54	-6.9	74	-26.9	180	293	Horz
4882	90.78	PK	27.2	-52.5	65.48	-	-	54	11.48	74	-8.52	308	397	Vert
4882	73.81	Av	27.2	-52.5	48.51	-	-	54	-5.49	74	-25.49	308	397	Vert
7323.4248	65.6	PK	28	-51.79	41.81	-	-	54	-12.19	74	-32.19	161	247	Vert
7323.4248	48.96	Av	28	-51.79	25.17	-	-	54	-28.83	74	-48.83	161	247	Vert
7323.4248	64.79	PK	28	-51.79	41	-	-	54	-13	74	-33	75	385	Horz
7323.4248	47.85	Av	28	-51.79	24.06	-	-	54	-29.94	74	-49.94	75	385	Horz
High Channel														
4959.6633	88.02	PK	27.3	-52.35	62.97	-	-	54	8.97	74	-11.03	44	395	Horz
4959.6633	74.7	Av	27.3	-52.35	49.65	-	-	54	-4.35	74	-24.35	44	395	Horz
4959.6633	87.5	PK	27.3	-52.35	62.45	-	-	54	8.45	74	-11.55	356	347	Vert
4959.6633	74.25	Av	27.3	-52.35	49.2	-	-	54	-4.8	74	-24.8	356	347	Vert
7440	67.78	PK	28.1	-51.39	44.49	-	-	54	-9.51	74	-29.51	192	199	Vert
7440	53.52	Av	28.1	-51.39	30.23	-	-	54	-23.77	74	-43.77	192	199	Vert
7440	67.49	PK	28.1	-51.39	44.2	-	-	54	-9.8	74	-29.8	98	262	Horz
7440	53.07	Av	28.1	-51.39	29.78	-	-	54	-24.22	74	-44.22	98	262	Horz
PK - Peak detector														
QP - Quasi-Peak detector														
LnAv - Linear Average detector														
LgAv - Log Average detector														
Av - Average detector														
CAV - CISPR Average detector														
RMS - RMS detection														
CRMS - CISPR RMS detection														
Note: All harmonics were investigated. Only those which were not found to be noise floor were reported.														

8.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZ & VERT)



DATA

Manufacturer:LG Electronics										
Device:Cell Phone w/BT										
Model:LG440G										
Job#:12U14489										
Tested by:BD										
FCC Part 15										
Test	Meter		AF-54	GL-3M	dB(uVolts	Subpart C		Azimuth	Height	
Frequency	Reading	Detector	(dB)	(dB)	/meter)	15.209	Margin	[Degs]	[cm]	Polarity
Horizontal 30 - 200MHz										
117.1271	13.7	PK	13.2	1.1	28	43.5	-15.5	124	100	Horz
167.3273	13.83	PK	14.8	1.3	29.93	43.5	-13.57	99	400	Horz
Vertical 30 - 200MHz										
129.8899	12.15	PK	14	1.2	27.35	43.5	-16.15	94	100	Vert
186.046	11.28	PK	15.4	1.5	28.18	43.5	-15.32	41	100	Vert
Horizontal 200 - 1000MHz										
982.7914	14.11	PK	24.6	3.7	42.41	54	-11.59	117	400	Horz
Vertical 200 - 1000MHz										
979.99	13.67	PK	24.8	3.7	42.17	54	-11.83	301	200	Vert
PK - Peak detector										
QP - Quasi-Peak detector										
LnAv - Linear Average detector										
LgAv - Log Average detector										
Av - Average detector										
CAV - CISPR Average detector										
RMS - RMS detection										
CRMS - CISPR RMS detection										