



FCC 47 CFR PART 15 SUBPART C

C2PC CERTIFICATION TEST REPORT

FOR

CDMA/LTE PHABLET + BLUETOOTH, & DTS/UNII a/b/g/n

MODEL NUMBER: LG-LS770, LS770, LGLS770

FCC ID: ZNFLS770

REPORT NUMBER: 15I20150-E2

ISSUE DATE: MARCH 18, 2015

Prepared for

**LG ELECTRONICS MOBILECOMM U.S.A., INC
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS,
NEW JERSEY, 07632, U.S.A**

Prepared by

**UL VERIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	03/18/15	Initial Issue	D. Corona

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE.....	9
5.5. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. SUMMARY TABLE	13
8. ANTENNA PORT TEST RESULTS	14
8.1. 20 dB AND 99% BANDWIDTH	14
8.1.1. BASIC DATA RATE GFSK MODULATION	14
8.1.2. ENHANCED DATA RATE 8PSK MODULATION	14
8.1.3. 20 dB AND 99% BANDWIDTH PLOTS.....	15
8.2. HOPPING FREQUENCY SEPARATION	27
8.3. NUMBER OF HOPPING CHANNELS.....	29
8.4. AVERAGE TIME OF OCCUPANCY.....	34
8.5. OUTPUT POWER	41
8.5.1. BASIC DATA RATE GFSK MODULATION	41
8.5.2. ENHANCED DATA RATE 8PSK MODULATION	41
8.5.3. OUTPUT POWER PLOTS.....	42
8.6. AVERAGE POWER.....	48
8.6.1. BASIC DATA RATE GFSK MODULATION	49
8.6.2. DATA RATE PI/4-DQPSK MODULATION	49
8.6.3. ENHANCED DATA RATE 8PSK MODULATION	49
8.7. CONDUCTED SPURIOUS EMISSIONS.....	50
8.7.1. BASIC DATA RATE GFSK MODULATION	51

8.7.2. ENHANCED DATA RATE 8PSK MODULATION59

9. RADIATED TEST RESULTS.....67

9.1. LIMITS AND PROCEDURE.....67

9.2. TRANSMITTER ABOVE 1 GHz.....68

9.2.1. BASIC DATA RATE GFSK MODULATION.....68

9.2.2. ENHANCED DATA RATE 8PSK MODULATION81

9.3. TRANSMITTER BELOW 1 GHz.....94

10. SETUP PHOTOS96

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC
EUT DESCRIPTION: CDMA/LTE PHABLET + BLUETOOTH, & DTS/UNII a/b/g/n
MODEL: LG-LS770, LS770, LGLS770
SERIAL NUMBER: 808D2EDE – RADIATED and 80958E37, 80CF45CO – CONDUCTED
DATE TESTED: MARCH 5 & 16, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



DAN CORONIA
CONSUMER TECHNOLOGY DIVISION
WISE PROJECT LEAD
UL VERIFICATION SERVICES INC

Tested By:



STEVEN TRAN
CONSUMER TECHNOLOGY DIVISION
WISE LAB ENGINEER
UL VERIFICATION SERVICES INC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, and FCC CFR 47 Part 15C

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input checked="" type="checkbox"/> Chamber A(IC: 2324B-1)	<input type="checkbox"/> Chamber D(IC: 2324B-4)
<input type="checkbox"/> Chamber B(IC: 2324B-2)	<input type="checkbox"/> Chamber E(IC: 2324B-5)
<input checked="" type="checkbox"/> Chamber C(IC: 2324B-3)	<input type="checkbox"/> Chamber F(IC: 2324B-6)
	<input type="checkbox"/> Chamber G(IC: 2324B-7)
	<input type="checkbox"/> Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable} \\ &\text{Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a CDMA/LTE PHABLET + BLUETOOTH, & DTS/UNII a/b/g/n

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	8.25	6.68
2402 - 2480	Enhanced 8PSK	8.45	7.00

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -3.84dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	MCS-02WR	RA4Y1031433	N/A
Earphone	LG	N/A	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
EUT was set in the Hidden menu mode to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-2 GHz	Sunol Sciences	JB1	C01171	02/18/16
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/04/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/16/16
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Version 9.5, 07/22/14
Conducted Software	UL	UL EMC	Version 9.5, 05/17/14
CLT Software	UL	UL RF	Version 1.0, 02/02/15
Antenna Port Software	UL	UL RF	Version 2.1.1.1, 1/20/15

7. SUMMARY TABLE

C2PC reason: Please see LG FCC Class II Change Description letter for details.

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	RSS-GEN 4.6	Occupied Band width (99%)	N/A	Conducted	Pass	1.189 MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-51.11 dBm
15.247 (b)(1)	RSS-210 A8.4	TX conducted output power	<21dBm		Pass	8.49 dBm
15.247 (a)(1)	RSS-210 A8.1(b)	Hopping frequency separation	> 25KHz		Pass	1 MHz
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79 channels
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Avg Time of Occupancy	< 0.4sec		Pass	0.375 s
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	See original
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	-13.69 dBuV/m

8. ANTENNA PORT TEST RESULTS

8.1. 20 dB AND 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS

8.1.1. BASIC DATA RATE GFSK MODULATION


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	0.9403	0.8968
Middle	2441	0.9403	0.8963
High	2480	0.9384	0.8963
Worst		0.9403	0.8968

8.1.2. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	1.281	1.1882
Middle	2441	1.282	1.1892
High	2480	1.278	1.1869
Worst		1.282	1.1892

8.1.3. 20 dB AND 99% BANDWIDTH PLOTS


GFSK 20 dB BANDWIDTH



MID CHANNEL



HIGH CHANNEL



GFSK 99% BANDWIDTH

LOW CHANNEL

		R L	Measure
Ch Freq 2.402 GHz		Trig Free	
Occupied Bandwidth		Averages: 100	
Ref 20 dBm #Atten 20 dB #Samp Log 10 dB/Offst 11.5 dB 			Meas Off
Center 2.402 000 0 GHz Span 1.766 MHz #Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)			Channel Power
<div style="border: 2px solid green; padding: 5px;"> <p>Occupied Bandwidth 896.8323 kHz</p> <p>Transmit Freq Error 687.058 Hz</p> <p>x dB Bandwidth 893.087 kHz*</p> </div>			Occupied BW
			ACP
			Multi Carrier Power
			Power Stat CCDF
			More 1 of 2
Copyright 2000-2010 Agilent Technologies			

MID CHANNEL


		R L	Measure
Ch Freq 2.441 GHz		Trig Free	Meas Off
Occupied Bandwidth		Averages: 100	Channel Power
Ref 20 dBm #Atten 20 dB #Samp 10 Log dB/Offst 11.5 dB 			Occupied BW
Center 2.441 000 0 GHz Span 1.775 MHz #Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)			ACP
Occupied Bandwidth 896.3141 kHz		Occ BW % Pwr 99.00 % x dB -20.00 dB	Multi Carrier Power
Transmit Freq Error -855.056 Hz x dB Bandwidth 882.298 kHz*			Power Stat CCDF
Copyright 2000-2010 Agilent Technologies			More 1 of 2

HIGH CHANNEL


Agilent	R L	Measure
<p style="text-align: center;">Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth Averages: 100</p>		Meas Off
<p>Ref 20 dBm #Atten 20 dB</p> <p>#Samp Log 10 dB/ Offst 11.5 dB</p> <p style="text-align: center;">Center 2.480 000 0 GHz Span 1.746 MHz</p> <p>#Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)</p>		Channel Power
<p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p style="text-align: center; font-size: 1.2em;">896.3152 kHz x dB -20.00 dB</p> <p>Transmit Freq Error 14.317 kHz</p> <p>x dB Bandwidth 898.687 kHz*</p>		Occupied BW
		ACP
		Multi Carrier Power
		Power Stat CCDF
		More 1 of 2
Copyright 2000-2010 Agilent Technologies		

8PSK 20 dB BANDWIDTH


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8PSK 99% BANDWIDTH

LOW CHANNEL

		R L	Measure
Ch Freq 2.402 GHz		Trig Free	Meas Off
Occupied Bandwidth		Averages: 100	Channel Power
Ref 20 dBm #Atten 20 dB			Occupied BW
			ACP
Center 2.402 000 0 GHz Span 2.344 MHz			Multi Carrier Power
#Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)			Power Stat CCDF
Occupied Bandwidth		Occ BW % Pwr	99.00 %
1.1882 MHz		x dB	-20.00 dB
Transmit Freq Error			
6.062 kHz			
x dB Bandwidth			
1.284 MHz*			
Copyright 2000-2010 Agilent Technologies			More
			1 of 2

MID CHANNEL

		R L	Measure
Ch Freq 2.441 GHz		Trig Free	Meas Off
Occupied Bandwidth		Averages: 100	Channel Power
Ref 20 dBm #Atten 20 dB #Samp Log 10 dB/Offst 11.5 dB 			Occupied BW
Center 2.441 000 0 GHz Span 2.31 MHz #Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)			ACP
Occupied Bandwidth 1.1892 MHz		Occ BW % Pwr 99.00 % x dB -20.00 dB	Multi Carrier Power
Transmit Freq Error 5.407 kHz x dB Bandwidth 1.288 MHz*			Power Stat CCDF
Copyright 2000-2010 Agilent Technologies			More 1 of 2

HIGH CHANNEL

Agilent	R L	Measure								
<p style="text-align: center;">Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth Averages: 100</p>		Meas Off								
<p>Ref 20 dBm #Atten 20 dB</p> <p>#Samp Log 10 dB/ Offst 11.5 dB</p> <p style="text-align: center;">Center 2.480 000 0 GHz Span 2.346 MHz</p> <p>#Res BW 22 kHz #VBW 68 kHz #Sweep 100 ms (1001 pts)</p>		Channel Power								
		Occupied BW								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Occupied Bandwidth</td> <td style="width: 50%;">Occ BW % Pwr 99.00 %</td> </tr> <tr> <td style="text-align: center;">1.1869 MHz</td> <td style="text-align: center;">x dB -20.00 dB</td> </tr> <tr> <td>Transmit Freq Error 6.593 kHz</td> <td></td> </tr> <tr> <td>x dB Bandwidth 1.285 MHz*</td> <td></td> </tr> </table>		Occupied Bandwidth	Occ BW % Pwr 99.00 %	1.1869 MHz	x dB -20.00 dB	Transmit Freq Error 6.593 kHz		x dB Bandwidth 1.285 MHz*		ACP
		Occupied Bandwidth	Occ BW % Pwr 99.00 %							
1.1869 MHz	x dB -20.00 dB									
Transmit Freq Error 6.593 kHz										
x dB Bandwidth 1.285 MHz*										
<p>Copyright 2000-2010 Agilent Technologies</p>		Multi Carrier Power								
		Power Stat CCDF								
		More 1 of 2								

8.2. HOPPING FREQUENCY SEPARATION LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION PLOT



8.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

RESULTS


Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS PLOTS


NUMBER OF HOPPING CHANNELS (100 MHZ SPAN)




NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, FIRST SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, SECOND SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, THIRD SEGMENT)



**8.4. AVERAGE TIME OF OCCUPANCY
 LIMIT**

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to 10 * (# of pulses in 0.8 s) * pulse width.


RESULTS

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
GFSK Normal Mode					
DH1	0.384	28	0.1075	0.4	-0.29248
DH3	1.653	13	0.2149	0.4	-0.18511
DH5	2.883	13	0.3748	0.4	-0.02521
GFSK AFH Mode					
DH Packet	Pulse Width (msec)	Number of Pulses in 0.8 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
DH1	0.384	7.00	0.0269	0.4	-0.37312
DH3	1.653	3.25	0.0537	0.4	-0.34628
DH5	2.883	3.25	0.0937	0.4	-0.3063


PULSE WIDTH - DH1




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH1




PULSE WIDTH - DH3




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH3



PULSE WIDTH - DH5



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH5



8.5. OUTPUT POWER LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

8.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	7.35	21	-13.65
Middle	2441	8.25	21	-12.75
High	2480	7.96	21	-13.04
Worst		8.25		-12.75


8.5.2. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	7.49	21	-13.51
Middle	2441	8.49	21	-12.51
High	2480	8.21	21	-12.79
Worst		8.49		-12.51


8.5.3. OUTPUT POWER PLOTS

GFSK OUTPUT POWER


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




8PSK OUTPUT POWER


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.7 dB (including 10 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

8.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	7.0
Middle	2441	7.9
High	2480	7.3
Worst		7.9

8.6.2. DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	4.5
Middle	2441	5.5
High	2480	4.9
Worst		5.5

8.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	4.5
Middle	2441	5.5
High	2480	4.9
Worst		5.5

8.7. CONDUCTED SPURIOUS EMISSIONS LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

RESULTS


8.7.1. BASIC DATA RATE GFSK MODULATION

SPURIOUS EMISSIONS, LOW CHANNEL


LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS



SPURIOUS EMISSIONS, MID CHANNEL




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON




HIGH BANDEDGE WITH HOPPING ON




8.7.2. ENHANCED DATA RATE 8PSK MODULATION

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL BANDEDGE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON



HIGH BANDEDGE WITH HOPPING ON



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.
 $GFSK = 1/T = 1 / 0.0038S = 460Hz.$

The spectrum from 1GHzHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.339	43.31	PK	31.8	-23.1	52.01	-	-	74	-21.99	273	254	H
4	* 2.378	30.04	VB1T	31.9	-23.1	38.84	54	-15.16	-	-	273	254	H
1	* 2.39	39.95	PK	32	-23.1	48.85	-	-	74	-25.15	273	254	H
3	* 2.39	29.7	VB1T	32	-23.1	38.6	54	-15.4	-	-	273	254	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.321	42.77	PK	31.7	-23.1	51.37	-	-	74	-22.63	197	388	V
4	* 2.387	30.03	VB1T	32	-23.1	38.93	54	-15.07	-	-	197	388	V
1	* 2.39	39.48	PK	32	-23.1	48.38	-	-	74	-25.62	197	388	V
3	* 2.39	29.71	VB1T	32	-23.1	38.61	54	-15.39	-	-	197	388	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Ftr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.88	PK	32.3	-22.8	50.38	-	-	74	-23.62	233	161	H
2	* 2.484	42.62	PK	32.3	-22.8	52.12	-	-	74	-21.88	233	161	H
3	* 2.484	30.72	VB1T	32.3	-22.8	40.22	54	-13.78	-	-	233	161	H
4	* 2.484	30.73	VB1T	32.3	-22.8	40.23	54	-13.77	-	-	233	161	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.3	PK	32.3	-22.8	50.8	-	-	74	-23.2	191	364	V
3	* 2.484	30.69	VB1T	32.3	-22.8	40.19	54	-13.81	-	-	191	364	V
4	* 2.484	30.81	VB1T	32.3	-22.8	40.31	54	-13.69	-	-	191	364	V
2	2.557	42.57	PK	32.4	-22.7	52.27	-	-	74	-21.73	191	364	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	* 4.804	32.51	PK	34	-30.3	36.21	-	-	74	-37.79	0-360	200	H
4	* 4.804	32.17	PK	34	-30.3	35.87	-	-	74	-38.13	0-360	200	V
1	1.96	33.33	PK	31.3	-23.3	41.33	-	-	-	-	0-360	200	H
2	2.187	32.89	PK	31.4	-22.9	41.39	-	-	-	-	0-360	200	V
5	9.607	34.78	PK	36.7	-25.2	46.28	-	-	-	-	0-360	200	H
6	9.608	37.14	PK	36.7	-25.3	48.54	-	-	-	-	0-360	200	V

PK - Peak detector

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	42.09	PK3	34	-30.3	45.79	-	-	74	-28.21	79	266	H
* 4.804	32.55	VB1T	34	-30.3	36.25	54	-17.75	-	-	79	266	H
* 4.804	42.44	PK3	34	-30.3	46.14	-	-	74	-27.86	151	181	V
* 4.804	31.91	VB1T	34	-30.3	35.61	54	-18.39	-	-	151	181	V

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.26	33.47	PK	31.5	-23	41.97	-	-	74	-32.03	0-360	200	V
3	* 4.881	30.26	PK	34	-30.2	34.06	-	-	74	-39.94	0-360	100	H
4	* 4.881	31.29	PK	34	-30.2	35.09	-	-	74	-38.91	0-360	200	V
1	1.932	33.27	PK	31.2	-23.3	41.17	-	-	-	-	0-360	200	H
5	9.764	34.91	PK	36.9	-26	45.81	-	-	-	-	0-360	200	H
6	9.764	35.77	PK	36.9	-26	46.67	-	-	-	-	0-360	200	V

PK - Peak detector

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.882	42.38	PK3	34	-30.2	46.18	-	-	74	-27.82	49	280	H
* 4.882	32.41	VB1T	34	-30.1	36.31	54	-17.69	-	-	49	280	H

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.311	33.04	PK	31.7	-23.1	41.64	-	-	74	-32.36	0-360	100	H
2	* 2.791	33.14	PK	32.6	-22.8	42.94	-	-	74	-31.06	0-360	200	V
3	* 4.96	31.63	PK	34	-31	34.63	-	-	74	-39.37	0-360	200	H
4	* 4.96	32.56	PK	34	-31	35.56	-	-	74	-38.44	0-360	200	V
5	9.919	34.64	PK	36.9	-25.6	45.94	-	-	-	-	0-360	200	H
6	9.919	39.16	PK	36.9	-25.6	50.46	-	-	-	-	0-360	200	V

PK - Peak detector

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96	43.05	PK3	34	-31	46.05	-	-	74	-27.95	64	273	H
* 4.96	33.21	VB1T	34	-31	36.21	54	-17.79	-	-	64	273	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* 2.386	29.99	VB1T	32	-23.1	38.89	54	-15.11	-	-	196	319	V
1	* 2.39	39.6	PK	32	-23.1	48.5	-	-	74	-25.5	196	319	V
2	* 2.39	42.92	PK	32	-23.1	51.82	-	-	74	-22.18	196	319	V
3	* 2.39	29.69	VB1T	32	-23.1	38.59	54	-15.41	-	-	196	319	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.29	PK	32.3	-22.8	50.79	-	-	74	-23.21	198	339	H
3	* 2.484	30.11	VB1T	32.3	-22.8	39.61	54	-14.39	-	-	198	339	H
2	* 2.497	42.97	PK	32.3	-22.7	52.57	-	-	74	-21.43	198	339	H
4	2.531	29.76	VB1T	32.4	-22.6	39.56	54	-14.44	-	-	198	339	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.93	PK	32.3	-22.8	50.43	-	-	74	-23.57	189	361	V
2	* 2.484	43.07	PK	32.3	-22.8	52.57	-	-	74	-21.43	189	361	V
3	* 2.484	30.43	VB1T	32.3	-22.8	39.93	54	-14.07	-	-	189	361	V
4	* 2.484	30.54	VB1T	32.3	-22.8	40.04	54	-13.96	-	-	189	361	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	* 4.804	30.61	PK	34	-30.3	34.31	-	-	74	-39.69	0-360	200	H
4	* 4.804	31.05	PK	34	-30.3	34.75	-	-	74	-39.25	0-360	100	V
1	2.1	33.11	PK	31.5	-23	41.61	-	-	-	-	0-360	100	H
2	2.305	33.8	PK	31.6	-23.1	42.3	-	-	-	-	0-360	100	V
6	9.607	37.59	PK	36.7	-25.2	49.09	-	-	-	-	0-360	200	V
5	9.608	36.29	PK	36.7	-25.3	47.69	-	-	-	-	0-360	200	H

PK - Peak detector

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	41.45	PK3	34	-30.3	45.15	-	-	74	-28.85	80	196	H
* 4.804	29.75	VB1T	34	-30.3	33.45	54	-20.55	-	-	80	196	H

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	* 4.881	29.65	PK	34	-30.2	33.45	-	-	74	-40.55	0-360	100	H
4	* 4.881	30.38	PK	34	-30.2	34.18	-	-	74	-39.82	0-360	100	V
1	1.976	34.86	PK	31.4	-23.3	42.96	-	-	-	-	0-360	100	H
2	2.151	34.01	PK	31.5	-22.9	42.61	-	-	-	-	0-360	200	V
5	9.764	34.77	PK	36.9	-26	45.67	-	-	-	-	0-360	200	H
6	9.764	36.74	PK	36.9	-26	47.64	-	-	-	-	0-360	200	V

PK - Peak detector

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.882	40.39	PK3	34	-30.1	44.29	-	-	74	-29.71	89	237	H
* 4.882	28.98	VB1T	34	-30.1	32.88	54	-21.12	-	-	89	237	H

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.229	33.08	PK	31.5	-23	41.58	-	-	74	-32.42	0-360	200	H
2	* 2.753	33.77	PK	32.4	-22.9	43.27	-	-	74	-30.73	0-360	200	V
3	* 4.957	30.61	PK	34	-30.9	33.71	-	-	74	-40.29	0-360	200	H
4	* 4.957	31.22	PK	34	-30.9	34.32	-	-	74	-39.68	0-360	200	V
6	9.919	38.57	PK	36.9	-25.6	49.87	-	-	-	-	0-360	200	V
5	9.92	35.05	PK	36.9	-25.6	46.35	-	-	-	-	0-360	200	H

PK - Peak detector


RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96	41.75	PK3	34	-31	44.75	-	-	74	-29.25	60	246	H
* 4.96	29.74	VB1T	34	-31	32.74	54	-21.26	-	-	60	246	H


9.3. TRANSMITTER BELOW 1 GHz

GFSK SPOURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AFT130 (dB/m)	Amp/Cbl (dB/m)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	* 170.59	47.15	PK	11.7	-30.1	28.75	43.52	-14.77	0-360	300	H
5	* 130.8525	42.41	PK	14.2	-30.3	26.31	43.52	-17.21	0-360	100	V
6	* 334	39.09	PK	13.9	-29.2	23.79	46.02	-22.23	0-360	100	H
8	* 322.8	35.88	PK	14	-29.3	20.58	46.02	-25.44	0-360	101	V
1	53.375	49.83	PK	7.2	-31	26.03	40	-13.97	0-360	300	H
4	71.99	46.31	PK	8	-30.8	23.51	40	-16.49	0-360	100	V
2	72.7125	48.3	PK	7.9	-30.8	25.4	40	-14.6	0-360	300	H
7	676	36.16	PK	19.8	-28.2	27.76	46.02	-18.26	0-360	400	H
9	676	35.91	PK	19.8	-28.2	27.51	46.02	-18.51	0-360	101	V

PK - Peak detector