



## SAR EVALUATION REPORT

**Applicant Name:**  
 LG Electronics MobileComm U.S.A., Inc.  
 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632  
 United States

**Date of Testing:**  
 12/19/16 - 01/02/17  
**Test Site/Location:**  
 PCTEST Lab, Columbia, MD, USA  
**Document Serial No.:**  
 1M1701030001-01-R1.ZNF

**FCC ID:** ZNFLS777

**APPLICANT:** LG ELECTRONICS MOBILECOMM U.S.A., INC.

**DUT Type:** Portable Handset  
**Application Type:** Class II Permissive Change  
**FCC Rule Part(s):** CFR §2.1093  
**Model(s):** LG-LS777  
**Additional Model(s):** LGLS777, LS777  
**Permissive Change (s):** See FCC Change Document

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)	10 gm Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.29	0.48	0.44	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.26	0.41	0.37	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.36	0.59	0.59	N/A
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.34	1.02	1.02	N/A
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.51	0.81	0.81	N/A
PCE	CDMA/EVDO BC0 (\$22H)	824.70 - 848.31 MHz	0.42	0.67	0.69	N/A
PCE	CDMA/EVDO BC10 (\$90S)	817.90 - 823.10 MHz	0.40	0.68	0.62	N/A
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.59	0.83	0.89	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.28	0.53	0.53	N/A
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.33	0.66	0.66	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.37	0.83	0.83	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.57	0.82	0.82	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.15	1.19	1.27	3.10
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.76	0.22	0.22	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A			
<b>Simultaneous SAR per KDB 690783 D01v01r03:</b>			1.34	1.41	1.49	3.22

Note: This revised Test Report (S/N: 1M1701030001-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez  
 President





The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: [sartick@mmfai.info](mailto:sartick@mmfai.info).

<b>FCC ID:</b> ZNFLS777	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 1 of 70

# TABLE OF CONTENTS

1	DEVICE UNDER TEST .....	3
2	LTE INFORMATION .....	10
3	INTRODUCTION .....	11
4	DOSIMETRIC ASSESSMENT .....	12
5	DEFINITION OF REFERENCE POINTS .....	13
6	TEST CONFIGURATION POSITIONS .....	14
7	RF EXPOSURE LIMITS .....	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS .....	26
10	SYSTEM VERIFICATION.....	45
11	SAR DATA SUMMARY .....	47
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	61
13	SAR MEASUREMENT VARIABILITY .....	65
14	EQUIPMENT LIST.....	66
15	MEASUREMENT UNCERTAINTIES.....	67
16	CONCLUSION.....	68
17	REFERENCES .....	69
APPENDIX A:	SAR TEST PLOTS	
APPENDIX B:	SAR DIPOLE VERIFICATION PLOTS	
APPENDIX C:	PROBE AND DIPOLE CALIBRATION CERTIFICATES	
APPENDIX D:	SAR TISSUE SPECIFICATIONS	
APPENDIX E:	SAR SYSTEM VALIDATION	
APPENDIX F:	DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS	

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 2 of 70



# 1 DEVICE UNDER TEST

## 1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
CDMA/EVDO BC0 (§22H)	Voice/Data	824.70 - 848.31 MHz
CDMA/EVDO BC10 (§90S)	Voice/Data	817.90 - 823.10 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
Bluetooth	Data	2402 - 2480 MHz

## 1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 3 of 70	



### 1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

Mode / Band		Voice (dBm)	Burst Average GSMK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slot	1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GSM/GPRS/EDGE 850	Maximum	<b>33.7</b>	<b>33.7</b>	<b>30.7</b>	<b>27.7</b>	<b>27.7</b>
	Nominal	<b>33.2</b>	<b>33.2</b>	<b>30.2</b>	<b>27.2</b>	<b>27.2</b>
GSM/GPRS/EDGE 1900	Maximum	<b>31.2</b>	<b>31.2</b>	<b>28.2</b>	<b>26.7</b>	<b>26.7</b>
	Nominal	<b>30.7</b>	<b>30.7</b>	<b>27.7</b>	<b>26.2</b>	<b>26.2</b>



Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>
UMTS Band 4 (1750 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>
UMTS Band 2 (1900 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>

Mode / Band		Modulated Average (dBm)
CDMA/EVDO BC10 (§90S)	Maximum	<b>25.2</b>
	Nominal	<b>24.7</b>
CDMA/EVDO BC0 (§22H)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
PCS CDMA/EVDO	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 4 of 70

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 26 (Cell)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 5 (Cell)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 4 (AWS)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 25 (PCS)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 2 (PCS)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 41	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>

Mode / Band		Modulated Average (dBm)		
IEEE 802.11b (2.4 GHz)		Ch. 1-5, 7-8	Ch. 6	Ch. 9-11
	Maximum	<b>17.0</b>		
	Nominal	<b>16.0</b>		
IEEE 802.11g (2.4 GHz)	Maximum	<b>15.5</b>	<b>16.5</b>	<b>15.0</b>
	Nominal	<b>14.5</b>	<b>15.5</b>	<b>14.0</b>
IEEE 802.11n (2.4 GHz)	Maximum	<b>15.0</b>	<b>16.0</b>	<b>14.5</b>
	Nominal	<b>14.0</b>	<b>15.0</b>	<b>13.5</b>
Bluetooth	Maximum	<b>8.5</b>		
	Nominal	<b>7.5</b>		
Bluetooth LE	Maximum	<b>0.0</b>		
	Nominal	<b>-1.0</b>		

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 5 of 70

## 1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”.

**Table 1-1  
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
EVDO BC0 (§22H)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC10 (§90S)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	No	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing.

## 1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



**Figure 1-1  
Simultaneous Transmission Paths**

FCC ID: ZNFLS777	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 6 of 70	

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

**Table 1-2  
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	1x CDMA voice + 2.4 GHz WI-FI	Yes	Yes	N/A	Yes	
2	1x CDMA voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
3	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	Yes	
4	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
5	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
7	LTE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
8	LTE + 2.4 GHz Bluetooth	N/A	Yes*	N/A	Yes	*-Pre-installed VOIP applications are considered.
9	CDMA/EVDO data + 2.4 GHz WI-FI	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
10	CDMA/EVDO data + 2.4 GHz Bluetooth	N/A	Yes*	N/A	Yes	*-Pre-installed VOIP applications are considered.
11	GPRS/EDGE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
12	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	Yes*	N/A	Yes	*-Pre-installed VOIP applications are considered.

- 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Simultaneous transmission scenarios involving WIFI are listed in the above table.
- This device does not support VOLTE.
- This device does support VoWIFI.

## 1.6 Miscellaneous SAR Test Considerations

### (A) WIFI/BT

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:



$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required;  $[(7/10) * \sqrt{2.480}] = 1.1 < 3.0$ . Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet Bluetooth SAR was not required;  $[(7/ 5) * \sqrt{2.480}] = 2.2 < 7.5$ . Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 7 of 70	

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluated for 2.4 GHz WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

**(B) Licensed Transmitter(s)**

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.



This device supports both LTE B26 (Cell) and LTE B5 (Cell). Since the supported frequency span for LTE B5 (Cell) falls completely within the supported frequency span for LTE B26 (Cell), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B26 (Cell).

This device supports both LTE B25 (PCS) and LTE B2 (PCS). Since the supported frequency span for LTE B2 (PCS) falls completely within the supported frequency span for LTE B25 (PCS), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B25 (PCS).

CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01v03r01.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was evaluated for LTE band 41 since wireless router 1g SAR was > 1.2 W/kg for this mode.

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 8 of 70





## 1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

## 1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.



	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number	Phablet Serial Number
GSM/GPRS/EDGE 850	06767	06767	06767	-
GSM/GPRS/EDGE 1900	06767	06767	06767	-
UMTS 850	06767	06767	06767	-
UMTS 1750	06767	06767	06767	-
UMTS 1900	06767	06767	06767	-
CDMA/EVDO BC0 (§22H)	01655	01655	01655	-
CDMA/EVDO BC10 (§90S)	01655	01655	01655	-
PCS CDMA/EVDO	01655	01655	01655	-
LTE Band 12	01653	01653	01653	-
LTE Band 26 (Cell)	01653	01653	01653	-
LTE Band 4 (AWS)	01653	01653	01653	-
LTE Band 25 (PCS)	01653	01653	01653	-
LTE Band 41	01653	01653	01653	01653
2.4 GHz WLAN	01672	01672	01672	-

<b>FCC ID:</b> ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 9 of 70	

# 2

# LTE INFORMATION

LTE Information					
FCC ID	ZNFLS777				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz					
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	821.5 (26765)		831.5 (26865)		841.5 (26965)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	9				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eCIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 10 of 70	

### 3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

#### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1  
SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 11 of 70

# 4 DOSIMETRIC ASSESSMENT

## 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.



**Figure 4-1**  
Sample SAR Area Scan

**Table 4-1**  
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\*

Frequency	Maximum Area Scan Resolution (mm) ( $\Delta x_{area}, \Delta y_{area}$ )	Maximum Zoom Scan Resolution (mm) ( $\Delta x_{zoom}, \Delta y_{zoom}$ )	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22


\*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset			Page 12 of 70

## 5 DEFINITION OF REFERENCE POINTS

### 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view of ERP

### 5.2 HANDSET REFERENCE POINTS



Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom



**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 13 of 70

## 6 TEST CONFIGURATION POSITIONS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).


### 6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:


1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 14 of 70





**Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position**



**Figure 6-3 Side view w/ relevant markings**


## 6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.



## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



**Figure 6-4 Sample Body-Worn Diagram**

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 15 of 70

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations



Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.



When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 16 of 70	



## 6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna  $\leq 25$  mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 17 of 70

# 7 RF EXPOSURE LIMITS

## 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



## 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1  
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
<b>Peak Spatial Average SAR</b> Head	1.6	8.0
<b>Whole Body SAR</b>	0.08	0.4
<b>Peak Spatial Average SAR</b> Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 18 of 70

## 8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

### 8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is  $\leq 0.25$  dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is  $\leq 1.2$  W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

### 8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”



The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

### 8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

#### 8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 19 of 70

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH<sub>0</sub> and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH<sub>0</sub> data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

**Table 8-1**  
**Parameters for Max. Power for RC1**

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

**Table 8-2**  
**Parameters for Max. Power for RC3**

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

## 8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at fullrate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

## 8.4.3 Body-worn SAR Measurements



SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH<sub>n</sub>), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH<sub>n</sub>), with FCH at full rate and SCH<sub>0</sub> enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

## 8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 20 of 70	

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

### 8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For Ev-Do data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with Ev-Do Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

### 8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission LG mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.



## 8.5 SAR Measurement Conditions for UMTS

### 8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

### 8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 21 of 70

### 8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH<sub>n</sub> configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH<sub>n</sub>, for the highest reported SAR configuration in 12.2 kbps RMC.

### 8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

### 8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

## 8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.6.1 Spectrum Plots for RB Configurations



A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 22 of 70



## 8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:



- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg for FDD and  $\leq 0.6$  W/kg for TDD , testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg for FDD and  $< 0.6$  W/kg for TDD.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

## 8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

## 8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 23 of 70

## 8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

### 8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

### 8.7.2 Initial Test Position Procedure



For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 8.7.3 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is  $> 1.2$  W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 24 of 70



### 8.7.4 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.



### 8.7.5 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.4). When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 8.7.6 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is  $\leq 1.2$  W/kg, no additional SAR tests for the subsequent test configurations are required. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 25 of 70

# 9 RF CONDUCTED POWERS



## 9.1 CDMA Conducted Powers

				Loopback			Data			
Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	25.20	25.12	25.18	25.12	25.18	25.17	25.20
Cellular	1013	22H	824.7	24.62	24.58	24.63	24.70	24.54	24.62	24.63
	384	22H	836.52	24.65	24.64	24.59	24.60	24.60	24.64	24.61
	777	22H	848.31	24.62	24.62	24.57	24.60	24.65	24.62	24.67
PCS	25	24E	1851.25	24.68	24.64	24.61	24.63	24.59	24.62	24.61
	600	24E	1880	24.64	24.60	24.64	24.64	24.54	24.58	24.57
	1175	24E	1908.75	24.64	24.70	24.63	24.66	24.70	24.65	24.65

Note: RC1 is only applicable for IS-95 compatibility. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v06 4.1.g), only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.



**Figure 9-1**  
**Power Measurement Setup**



FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 26 of 70	

## 9.2 GSM Conducted Powers

Maximum Burst-Averaged Output Power						
Band	Channel	Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	33.67	33.69	<b>30.61</b>	27.63	27.48
	190	33.65	33.62	<b>30.68</b>	27.70	27.53
	251	33.66	33.65	<b>30.40</b>	27.60	27.50
GSM 1900	512	31.17	31.15	<b>28.00</b>	26.40	26.51
	661	31.15	31.20	<b>28.15</b>	26.65	26.70
	810	31.20	31.17	<b>28.05</b>	26.48	26.60

Calculated Maximum Frame-Averaged Output Power						
Band	Channel	Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	24.64	24.66	<b>24.59</b>	18.60	21.46
	190	24.62	24.59	<b>24.66</b>	18.67	21.51
	251	24.63	24.62	<b>24.38</b>	18.57	21.48
GSM 1900	512	22.14	22.12	<b>21.98</b>	17.37	20.49
	661	22.12	22.17	<b>22.13</b>	17.62	20.68
	810	22.17	22.14	<b>22.03</b>	17.45	20.58

<b>GSM 850</b>	<b>Frame</b>	24.17	24.17	<b>24.18</b>	18.17	21.18
<b>GSM 1900</b>	<b>Avg.Targets:</b>	21.67	21.67	<b>21.68</b>	17.17	20.18

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 27 of 70	



Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

**GSM Class: B**  
**GPRS Multislot class: 10 (Max 2 Tx uplink slots)**  
**EDGE Multislot class: 10 (Max 2 Tx uplink slots)**  
**DTM Multislot Class: N/A**




**Figure 9-2**  
**Power Measurement Setup**

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 28 of 70



### 9.3 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.68	24.65	24.61	24.68	24.69	24.66	24.65	24.66	24.68	-
99		12.2 kbps AMR	24.63	24.66	24.63	24.65	24.70	24.69	24.69	24.62	24.67	-
6	HSDPA	Subtest 1	24.31	24.30	24.28	24.25	24.35	24.16	24.04	23.98	24.08	0
6		Subtest 2	24.32	24.25	24.29	24.17	24.26	24.31	24.03	24.04	24.10	0
6		Subtest 3	24.02	24.08	24.00	23.66	23.77	23.72	23.52	23.48	23.52	0.5
6		Subtest 4	24.09	24.07	24.00	23.67	23.78	23.83	23.66	23.61	23.58	0.5
6	HSUPA	Subtest 1	24.07	24.20	24.09	23.84	23.90	23.97	24.05	23.97	24.01	0
6		Subtest 2	22.47	22.50	22.56	22.26	22.34	22.30	22.18	22.19	22.23	2
6		Subtest 3	23.55	23.47	23.55	23.26	23.30	23.28	23.22	23.19	23.32	1
6		Subtest 4	22.60	22.49	22.53	22.23	22.37	22.26	22.28	22.19	22.34	2
6		Subtest 5	24.16	24.09	24.16	23.99	24.19	24.08	24.02	24.14	24.14	0

This device does not support DC-HSDPA.



**Figure 9-3**  
**Power Measurement Setup**

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 29 of 70

## 9.4 LTE Conducted Powers

### 9.4.1 LTE Band 12



**Table 9-1**  
**LTE Band 12 Conducted Powers - 10 MHz Bandwidth**

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.54	0	0
	1	25	<b>24.70</b>		0
	1	49	24.52		0
	25	0	<b>23.37</b>	0-1	1
	25	12	23.28		1
	25	25	23.36		1
	50	0	23.29		1
16QAM	1	0	23.44	0-1	1
	1	25	23.66		1
	1	49	23.34		1
	25	0	22.22	0-2	2
	25	12	22.20		2
	25	25	22.21		2
	50	0	22.20		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-2**  
**LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.43	24.24	24.22	0	0
	1	12	24.60	24.65	24.60		0
	1	24	24.29	24.18	24.18		0
	12	0	23.41	23.31	23.37	0-1	1
	12	6	23.33	23.44	23.37		1
	12	13	23.23	23.35	23.20		1
	25	0	23.31	23.37	23.37		1
16QAM	1	0	22.93	22.83	22.94	0-1	1
	1	12	22.72	23.17	23.33		1
	1	24	22.73	22.75	23.31		1
	12	0	22.12	22.25	22.16	0-2	2
	12	6	21.90	22.34	22.06		2
	12	13	22.12	22.33	21.84		2
	25	0	22.10	22.37	22.27		2



FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 30 of 70

**Table 9-3  
LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.55	24.45	24.51	0	0
	1	7	24.70	24.69	24.67		0
	1	14	24.39	24.44	24.51		0
	8	0	23.56	23.38	23.42	0-1	1
	8	4	23.36	23.28	23.29		1
	8	7	23.40	23.48	23.31		1
	15	0	23.46	23.39	23.35		1
16QAM	1	0	23.42	23.39	23.46	0-1	1
	1	7	23.33	23.58	23.52		1
	1	14	23.43	23.27	23.00		1
	8	0	22.21	22.12	22.31	0-2	2
	8	4	22.09	22.25	21.89		2
	8	7	22.03	22.35	22.00		2
	15	0	22.11	22.22	22.25		2

**Table 9-4  
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth**

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.31	24.55	24.39	0	0
	1	2	24.58	24.58	24.35		0
	1	5	24.50	24.51	24.43		0
	3	0	24.54	24.38	24.50		0
	3	2	24.67	24.46	24.68		0
	3	3	24.55	24.68	24.36		0
	6	0	23.22	23.58	23.38	0-1	1
16QAM	1	0	23.26	23.41	23.57	0-1	1
	1	2	23.42	23.64	23.69		1
	1	5	22.85	23.69	23.23		1
	3	0	23.25	23.20	23.29		1
	3	2	22.96	23.33	23.10		1
	3	3	23.19	23.10	22.84		1
	6	0	22.12	22.08	22.01	0-2	2

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 31 of 70

9.4.2

LTE Band 26 (Cell)



Table 9-5  
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth						
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26865 (831.5 MHz)			
			Conducted Power [dBm]			
QPSK	1	0	24.61	0	0	
	1	36	<b>24.70</b>		0	
	1	74	24.43		0	
	QPSK	36	0	<b>23.42</b>	0-1	1
		36	18	23.40		1
		36	37	23.32		1
		75	0	23.41		1
16QAM	1	0	23.52	0-1	1	
	1	36	23.55		1	
	1	74	23.69		1	
	16QAM	36	0	22.42	0-2	2
		36	18	22.37		2
		36	37	22.00		2
		75	0	22.21		2

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6  
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)			
QPSK	1	0	24.68	24.50	24.48	0	0	
	1	25	24.64	24.67	24.60		0	
	1	49	24.60	24.52	24.26		0	
	QPSK	25	0	23.38	23.41	23.28	0-1	1
		25	12	23.53	23.44	23.40		1
		25	25	23.53	23.35	23.44		1
		50	0	23.52	23.34	23.42		1
16QAM	1	0	23.52	23.55	23.14	0-1	1	
	1	25	23.30	23.65	23.62		1	
	1	49	23.38	23.22	23.36		1	
	16QAM	25	0	22.27	22.37	22.17	0-2	2
		25	12	22.57	22.34	22.21		2
		25	25	22.29	22.21	22.32		2
		50	0	22.34	22.31	22.17		2

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 32 of 70





**Table 9-7**  
**LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth**

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.11	24.35	24.07	0	0
	1	12	24.48	24.68	24.62		0
	1	24	24.16	24.34	24.25		0
	12	0	23.24	23.33	23.33	0-1	1
	12	6	23.43	23.40	23.37		1
	12	13	23.50	23.35	23.34		1
	25	0	23.44	23.33	23.40		1
16QAM	1	0	23.10	23.17	22.98	0-1	1
	1	12	22.99	23.28	23.22		1
	1	24	23.06	22.94	22.92		1
	12	0	22.21	22.06	22.05	0-2	2
	12	6	22.05	22.23	22.18		2
	12	13	22.20	22.26	22.03		2
	25	0	22.41	22.38	22.27		2



**Table 9-8**  
**LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth**

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.45	24.35	24.49	0	0
	1	7	24.60	24.48	24.47		0
	1	14	24.46	24.32	24.30		0
	8	0	23.26	23.38	23.29	0-1	1
	8	4	23.40	23.42	23.20		1
	8	7	23.43	23.52	23.47		1
	15	0	23.32	23.47	23.31		1
16QAM	1	0	23.52	23.59	23.07	0-1	1
	1	7	23.54	23.04	23.65		1
	1	14	23.57	23.58	23.24		1
	8	0	21.86	22.20	22.49	0-2	2
	8	4	22.04	22.34	21.97		2
	8	7	22.00	22.34	22.15		2
	15	0	22.19	22.48	22.14		2

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 33 of 70

**Table 9-9  
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth**

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.39	24.64	0	0
	1	2	24.37	24.44	24.50		0
	1	5	24.45	24.43	24.45		0
	3	0	24.38	24.48	24.41		0
	3	2	24.39	24.60	24.41		0
	3	3	24.40	24.37	24.59		0
	6	0	23.21	23.38	23.31		0-1
16QAM	1	0	23.33	23.20	23.20	0-1	1
	1	2	23.68	23.20	23.45		1
	1	5	23.14	23.09	23.49		1
	3	0	23.47	23.18	23.32		1
	3	2	23.38	23.01	23.63		1
	3	3	23.11	22.96	23.08		1
	6	0	21.96	22.29	22.07		0-2

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 34 of 70

9.4.3

LTE Band 4 (AWS)



Table 9-10  
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.27	0	0
	1	50	<b>24.59</b>		0
	1	99	24.39		0
	50	0	23.35	0-1	1
	50	25	23.35		1
	50	50	<b>23.42</b>		1
	100	0	23.25		1
16QAM	1	0	23.66	0-1	1
	1	50	23.40		1
	1	99	23.19		1
	50	0	22.53	0-2	2
	50	25	22.54		2
	50	50	22.60		2
	100	0	22.56		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-11  
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.54	24.36	24.68	0	0
	1	36	24.38	24.65	24.66		0
	1	74	24.55	24.52	24.56		0
	36	0	23.64	23.70	23.65	0-1	1
	36	18	23.51	23.60	23.70		1
	36	37	23.63	23.62	23.55		1
	75	0	23.52	23.64	23.58		1
16QAM	1	0	23.59	23.69	23.40	0-1	1
	1	36	23.35	23.66	23.43		1
	1	74	23.48	23.62	23.38		1
	36	0	22.63	22.55	22.41	0-2	2
	36	18	22.38	22.54	22.40		2
	36	37	22.58	22.60	22.33		2
	75	0	22.38	22.59	22.48		2



FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 35 of 70

**Table 9-12**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.37	24.50	0	0
	1	25	24.45	24.45	24.68		0
	1	49	24.29	24.34	24.65		0
	25	0	23.69	23.54	23.53	0-1	1
	25	12	23.57	23.61	23.54		1
	25	25	23.54	23.53	23.54		1
	50	0	23.49	23.62	23.59		1
16QAM	1	0	23.41	23.33	23.69	0-1	1
	1	25	23.23	23.32	23.33		1
	1	49	23.15	23.70	23.41		1
	25	0	22.69	22.57	22.51	0-2	2
	25	12	22.62	22.60	22.43		2
	25	25	22.38	22.42	22.46		2
	50	0	22.45	22.51	22.57		2

**Table 9-13**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.64	24.61	24.22	0	0
	1	12	24.66	24.56	24.64		0
	1	24	24.23	24.45	24.66		0
	12	0	23.59	23.60	23.53	0-1	1
	12	6	23.62	23.53	23.59		1
	12	13	23.54	23.44	23.66		1
	25	0	23.59	23.48	23.44		1
16QAM	1	0	23.40	23.28	23.08	0-1	1
	1	12	23.08	23.30	23.38		1
	1	24	22.95	22.95	22.89		1
	12	0	22.65	22.45	22.23	0-2	2
	12	6	22.37	22.43	22.30		2
	12	13	22.60	22.36	22.14		2
	25	0	22.60	22.55	22.50		2



FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset		Page 36 of 70

**Table 9-14**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

LTE Band 4 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.45	24.52	24.29	0	0
	1	7	24.59	24.70	24.36		0
	1	14	24.52	24.48	24.46		0
	8	0	23.67	23.56	23.38	0-1	1
	8	4	23.45	23.51	23.46		1
	8	7	23.68	23.43	23.52		1
	15	0	23.69	23.57	23.58		1
16QAM	1	0	23.60	23.43	23.32	0-1	1
	1	7	23.51	23.53	23.69		1
	1	14	23.67	23.50	23.24		1
	8	0	22.62	22.37	22.28	0-2	2
	8	4	22.29	22.54	22.19		2
	8	7	22.35	22.55	22.18		2
	15	0	22.39	22.61	22.22		2

**Table 9-15**  
**LTE Band 4 (AWS) Conducted Powers - 1.4 MHz Bandwidth**

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.49	24.45	0	0
	1	2	24.56	24.54	24.42		0
	1	5	24.50	24.47	24.58		0
	3	0	24.49	24.68	24.56		0
	3	2	24.63	24.61	24.61		0
	3	3	24.52	24.48	24.57		0
	6	0	23.66	23.40	23.47	0-1	1
16QAM	1	0	23.53	23.42	23.34	0-1	1
	1	2	23.70	23.27	23.47		1
	1	5	23.00	23.20	23.22		1
	3	0	23.28	23.17	23.13		1
	3	2	23.52	23.15	23.30		1
	3	3	23.23	23.18	23.11		1
	6	0	21.99	22.43	22.35	0-2	2

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 37 of 70

9.4.4



LTE Band 25 (PCS)

**Table 9-16**  
**LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth**

LTE Band 25 (PCS) 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.20	24.40	24.45	0	0	
	1	50	24.45	24.42	24.60		0	
	1	99	24.40	24.23	24.25		0	
	50	0	23.63	23.69	23.66	0-1	1	
	50	25	23.70	23.59	23.55		1	
	50	50	23.69	23.48	23.44		1	
16QAM	100	0	23.59	23.65	23.62	0-1	1	
	1	0	23.32	22.87	22.88		0-1	1
	1	50	22.89	23.08	23.06			1
	1	99	22.90	22.75	22.85	0-2		1
	50	0	22.69	22.63	22.45		2	
	50	25	22.54	22.53	22.53		2	
	50	50	22.53	22.62	22.30	2		
	100	0	22.62	22.60	22.45	2		

**Table 9-17**  
**LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth**

LTE Band 25 (PCS) 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.31	24.65	24.52	0	0	
	1	36	24.59	24.69	24.68		0	
	1	74	24.53	24.61	24.56		0	
	36	0	23.54	23.65	23.69	0-1	1	
	36	18	23.69	23.66	23.48		1	
	36	37	23.67	23.60	23.45		1	
16QAM	75	0	23.59	23.69	23.53	0-1	1	
	1	0	23.68	23.65	22.72		0-1	1
	1	36	23.33	23.51	23.02			1
	1	74	23.67	23.50	23.44	0-2		1
	36	0	22.38	22.70	22.36		2	
	36	18	22.57	22.64	22.45		2	
	36	37	22.59	22.47	22.20	2		
	75	0	22.53	22.59	22.40	2		



FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 38 of 70

**Table 9-18**  
**LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth**

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.64	24.62	24.64	0	0
	1	25	24.65	24.69	24.70		0
	1	49	24.68	24.70	24.65		0
	25	0	23.57	23.70	23.42	0-1	1
	25	12	23.65	23.45	23.41		1
	25	25	23.68	23.39	23.41		1
16QAM	50	0	23.69	23.58	23.46	0-1	1
	1	0	23.45	23.62	23.58		1
	1	25	23.65	23.18	23.61		1
	1	49	23.60	23.21	23.25	0-2	1
	25	0	22.59	22.52	22.23		2
	25	12	22.45	22.57	22.48		2
	25	25	22.66	22.38	22.40		2
50	0	22.56	22.53	22.41	2		

**Table 9-19**  
**LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth**

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.56	24.61	24.42	0	0
	1	12	24.35	24.70	24.68		0
	1	24	24.17	24.41	24.48		0
	12	0	23.65	23.69	23.48	0-1	1
	12	6	23.69	23.67	23.43		1
	12	13	23.53	23.62	23.53		1
16QAM	25	0	23.54	23.62	23.47	0-1	1
	1	0	23.41	23.45	23.27		1
	1	12	23.69	23.61	23.09		1
	1	24	22.84	22.91	22.98	0-2	1
	12	0	22.45	22.57	22.36		2
	12	6	22.43	22.66	22.19		2
	12	13	22.29	22.50	22.21		2
25	0	22.58	22.64	22.43	2		



FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 39 of 70

**Table 9-20**  
**LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth**

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.46	24.66	24.38	0	0
	1	7	24.68	24.59	24.68		0
	1	14	24.60	24.47	24.49		0
	8	0	23.57	23.64	23.34	0-1	1
	8	4	23.68	23.49	23.37		1
	8	7	23.67	23.54	23.45		1
	15	0	23.58	23.54	23.48		1
16QAM	1	0	23.22	23.69	22.85	0-1	1
	1	7	23.69	23.43	23.69		1
	1	14	23.67	23.58	23.17		1
	8	0	22.17	22.50	22.64	0-2	2
	8	4	22.64	22.46	21.99		2
	8	7	22.21	22.41	22.25		2
	15	0	22.27	22.33	22.31		2

**Table 9-21**  
**LTE Band 25 (PCS) Conducted Powers - 1.4 MHz Bandwidth**

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.54	24.53	24.49	0	0
	1	2	24.57	24.56	24.42		0
	1	5	24.70	24.31	24.44		0
	3	0	24.69	24.53	24.50		0
	3	2	24.70	24.56	24.65		0
	3	3	24.67	24.60	24.39		0
16QAM	6	0	23.56	23.57	23.32	0-1	1
	1	0	23.29	23.25	23.52	0-1	1
	1	2	23.69	23.13	23.06		1
	1	5	23.62	22.96	23.16		1
	3	0	23.29	23.11	23.52		1
	3	2	23.50	23.57	22.97		1
3	3	23.22	23.42	23.24	1		
	6	0	22.55	22.12	22.14	0-2	2

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 40 of 70



9.4.5



LTE Band 41

**Table 9-22**  
**LTE Band 41 Conducted Powers - 20 MHz Bandwidth**

LTE Band 41 20 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	24.11	24.53	24.67	24.70	24.63	0	0	
	1	50	24.67	24.42	24.44	24.58	24.58		0	
	1	99	24.41	24.50	24.21	24.42	24.33		0	
	50	0	23.28	23.23	23.59	23.58	23.20	0-1	1	
	50	25	23.33	23.21	23.21	23.41	23.24		1	
	50	50	23.38	23.23	23.17	23.35	23.18		1	
100	0	23.34	23.20	23.19	23.53	23.22	0-1	1		
16QAM	1	0	22.98	22.73	23.30	23.22		23.32	1	
	1	50	23.10	22.85	23.00	23.12		23.00	1	
	1	99	23.31	22.84	22.97	23.14		23.15	1	
	50	0	22.19	22.16	22.53	22.49		22.07	0-2	2
	50	25	22.35	22.04	22.20	22.32		22.21		2
	50	50	22.41	22.08	22.15	22.28	22.14	2		
100	0	22.27	22.08	22.11	22.40	22.09	2			

**Table 9-23**  
**LTE Band 41 Conducted Powers - 15 MHz Bandwidth**

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	24.27	24.32	24.66	24.61	24.68	0	0	
	1	36	24.44	24.24	24.30	24.32	24.40		0	
	1	74	24.57	24.25	24.34	24.32	24.23		0	
	36	0	23.19	23.24	23.56	23.58	23.25	0-1	1	
	36	18	23.37	23.11	23.27	23.48	23.28		1	
	36	37	23.28	23.11	23.04	23.44	23.24		1	
75	0	23.33	23.09	23.21	23.46	23.20	0-1	1		
16QAM	1	0	23.41	23.44	23.67	23.55		23.54	1	
	1	36	23.36	23.33	23.49	23.28		23.44	1	
	1	74	23.29	23.42	23.50	23.22		23.43	1	
	36	0	21.92	22.00	22.19	22.27		21.89	0-2	2
	36	18	22.19	21.88	21.97	22.14		22.04		2
	36	37	22.36	21.87	21.88	22.19	22.08	2		
75	0	22.24	22.19	22.32	22.42	22.12	2			



FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 41 of 70

**Table 9-24**  
**LTE Band 41 Conducted Powers - 10 MHz Bandwidth**

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.55	24.46	24.68	24.60	24.68	0	0
	1	25	24.50	24.40	24.52	24.50	24.67		0
	1	49	24.67	24.36	24.43	24.27	24.41		0
	25	0	23.30	23.26	23.39	23.49	23.31	0-1	1
	25	12	23.26	23.20	23.29	23.45	23.29		1
	25	25	23.44	23.26	23.07	23.34	23.29		1
16QAM	50	0	23.27	23.14	23.23	23.41	23.24	0-1	1
	1	0	23.65	23.28	23.69	23.65	23.53		1
	1	25	23.58	23.62	23.60	23.70	23.65		1
	1	49	23.60	23.18	23.55	23.64	23.36	0-2	1
	25	0	22.18	22.27	22.16	22.23	22.08		2
	25	12	22.16	22.08	22.18	22.19	22.08		2
25	25	22.26	22.11	22.01	22.29	21.99	2		
50	0	22.10	22.15	22.23	22.27	22.16	2		

**Table 9-25**  
**LTE Band 41 Conducted Powers - 5 MHz Bandwidth**

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.32	24.20	24.27	24.30	24.35	0	0
	1	12	24.48	24.60	24.69	24.65	24.50		0
	1	24	24.27	24.15	24.00	24.20	24.26		0
	12	0	23.41	23.13	23.15	23.34	23.27	0-1	1
	12	6	23.26	23.19	23.40	23.37	23.22		1
	12	13	23.27	23.13	23.32	23.36	23.23		1
16QAM	25	0	23.26	23.06	23.15	23.36	23.26	0-1	1
	1	0	22.64	23.42	23.64	23.66	22.92		1
	1	12	22.74	23.68	23.68	23.69	22.95		1
	1	24	22.54	23.46	23.37	23.62	22.86	0-2	1
	12	0	22.01	21.93	22.01	22.08	22.16		2
	12	6	22.26	22.15	22.33	22.05	22.07		2
12	13	21.97	21.89	22.22	22.02	21.91	2		
25	0	22.27	22.03	22.15	22.37	22.03	2		

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset		Page 42 of 70

## 9.4.6 LTE Carrier Aggregation Conducted Powers

Table 9-26  
LTE Carrier Aggregation Conducted Powers



PCC									SCC				Power	
PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Rel 10 Tx.Power (dBm)	LTE Rel. 8 Tx.Power (dBm)
LTE B41	20	41055	2636.5	QPSK	1	0	41055	2636.5	LTE B41	20	40857	2616.7	24.63	24.70

Notes:

1. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.



Figure 9-4  
Power Measurement Setup

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 43 of 70


## 9.5 WLAN Conducted Powers

**Table 9-27**  
**IEEE 802.11b Average RF Power**



Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	16.41	14.75
2437	6	16.45	16.18
2462	11	<b>16.66</b>	14.55

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.



**Figure 9-5**  
**Power Measurement Setup**

FCC ID: ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 44 of 70	



# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1  
Measured Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
12/22/2016	750H	21.5	700	0.854	43.004	0.889	42.201	-3.94%	1.90%
			710	0.864	42.849	0.890	42.149	-2.92%	1.66%
			740	0.895	42.408	0.893	41.994	0.22%	0.99%
			755	0.908	42.202	0.894	41.916	1.57%	0.68%
12/20/2016	835H	22.5	820	0.863	40.061	0.899	41.578	-4.00%	-3.65%
			835	0.874	39.825	0.900	41.500	-2.89%	-4.04%
			850	0.891	39.703	0.916	41.500	-2.73%	-4.33%
12/24/2016	1750H	21.4	1710	1.342	40.865	1.348	40.142	-0.45%	1.80%
			1750	1.379	40.732	1.371	40.079	0.58%	1.63%
			1790	1.421	40.506	1.394	40.016	1.94%	1.22%
12/21/2016	1900H	21.1	1850	1.399	39.488	1.400	40.000	-0.07%	-1.28%
			1880	1.431	39.359	1.400	40.000	2.21%	-1.60%
			1910	1.463	39.232	1.400	40.000	4.50%	-1.92%
12/22/2016	2450H	22.6	2400	1.822	38.295	1.756	39.289	3.76%	-2.53%
			2450	1.873	38.115	1.800	39.200	4.06%	-2.77%
			2500	1.937	37.909	1.855	39.136	4.42%	-3.14%
12/27/2016	2600H	23.0	2500	1.937	37.880	1.855	39.136	4.42%	-3.21%
			2550	1.998	37.700	1.909	39.073	4.66%	-3.51%
			2600	2.053	37.509	1.964	39.009	4.53%	-3.85%
			2650	2.112	37.279	2.018	38.945	4.66%	-4.28%
12/22/2016	750B	21.3	700	0.914	54.762	0.959	55.726	-4.69%	-1.73%
			710	0.924	54.643	0.960	55.687	-3.75%	-1.87%
			740	0.954	54.333	0.963	55.570	-0.93%	-2.23%
			755	0.968	54.165	0.964	55.512	0.41%	-2.43%
12/19/2016	835B	21.4	820	0.991	55.325	0.969	55.258	2.27%	0.12%
			835	1.004	55.173	0.970	55.200	3.51%	-0.05%
			850	1.019	55.035	0.988	55.154	3.14%	-0.22%
12/21/2016	835B	22.2	820	0.983	54.266	0.969	55.258	1.44%	-1.80%
			835	0.998	54.136	0.970	55.200	2.89%	-1.93%
			850	1.013	53.997	0.988	55.154	2.53%	-2.10%
12/19/2016	1750B	21.5	1710	1.460	51.906	1.463	53.537	-0.21%	-3.05%
			1750	1.503	51.815	1.488	53.432	1.01%	-3.03%
			1790	1.543	51.592	1.514	53.326	1.92%	-3.25%
12/26/2016	1750B	21.1	1710	1.467	51.561	1.463	53.537	0.27%	-3.69%
			1750	1.509	51.447	1.488	53.432	1.41%	-3.72%
			1790	1.548	51.209	1.514	53.326	2.25%	-3.97%
12/26/2016	1900B	21.9	1850	1.517	53.274	1.520	53.300	-0.20%	-0.05%
			1880	1.550	53.193	1.520	53.300	1.97%	-0.20%
			1910	1.585	53.133	1.520	53.300	4.28%	-0.31%
12/23/2016	2450B	23.1	2400	1.972	52.228	1.902	52.767	3.68%	-1.02%
			2450	2.032	51.985	1.950	52.700	4.21%	-1.36%
			2500	2.111	51.782	2.021	52.636	4.45%	-1.62%
12/27/2016	2450B-2600B	22.5	2450	1.962	51.891	1.950	52.700	0.62%	-1.54%
			2500	2.024	51.686	2.021	52.636	0.15%	-1.80%
			2550	2.098	51.496	2.092	52.573	0.29%	-2.05%
			2600	2.171	51.333	2.163	52.509	0.37%	-2.24%
			2650	2.236	51.106	2.234	52.445	0.09%	-2.55%
			2700	2.314	50.934	2.305	52.382	0.39%	-2.76%
1/2/2017	2450B - 2600B	23.0	2450	2.001	51.684	1.950	52.700	2.62%	-1.93%
			2500	2.059	51.467	2.021	52.636	1.88%	-2.22%
			2550	2.138	51.298	2.092	52.573	2.20%	-2.43%
			2600	2.198	51.046	2.163	52.509	1.62%	-2.79%
			2650	2.277	50.866	2.234	52.445	1.92%	-3.01%
			2700	2.341	50.701	2.305	52.382	1.56%	-3.21%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 45 of 70

## 10.2 Test System Verification


Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-2  
System Verification Results (1 g)**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR <sub>1g</sub> (W/kg)	1 W Target SAR <sub>1g</sub> (W/kg)	1 W Normalized SAR <sub>1g</sub> (W/kg)	Deviation <sub>1g</sub> (%)
G	750	HEAD	12/22/2016	23.7	21.9	0.200	1054	3287	1.540	8.220	7.700	-6.33%
E	835	HEAD	12/20/2016	23.1	22.5	0.200	4d133	7406	1.740	9.320	8.700	-6.65%
E	1750	HEAD	12/24/2016	23.0	21.6	0.100	1148	7406	3.350	36.200	33.500	-7.46%
G	1900	HEAD	12/21/2016	22.7	21.1	0.100	5d080	3287	4.030	39.300	40.300	2.54%
D	2450	HEAD	12/22/2016	23.4	22.6	0.100	981	3213	5.160	52.800	51.600	-2.27%
E	2600	HEAD	12/27/2016	21.0	22.5	0.100	1071	7406	5.960	56.300	59.600	5.86%
J	750	BODY	12/22/2016	21.1	21.3	0.200	1054	3318	1.710	8.560	8.550	-0.12%
H	835	BODY	12/19/2016	21.8	21.4	0.200	4d047	3319	2.030	9.570	10.150	6.06%
H	835	BODY	12/21/2016	23.1	22.2	0.200	4d047	3319	1.970	9.570	9.850	2.93%
I	1750	BODY	12/19/2016	22.5	21.5	0.100	1008	3209	3.870	37.300	38.700	3.75%
I	1750	BODY	12/26/2016	22.1	21.1	0.100	1148	3209	3.610	37.100	36.100	-2.70%
K	1900	BODY	12/26/2016	21.9	21.9	0.100	5d149	7409	3.960	39.900	39.600	-0.75%
G	2450	BODY	12/23/2016	23.8	22.4	0.100	981	3287	5.280	50.800	52.800	3.94%
E	2450	BODY	12/27/2016	23.5	22.5	0.100	981	7406	5.190	50.800	51.900	2.17%
E	2600	BODY	12/27/2016	23.5	22.5	0.100	1071	7406	5.820	54.200	58.200	7.38%

**Table 10-3  
System Verification Results (10 g)**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR <sub>10g</sub> (W/kg)	1 W Target SAR <sub>10g</sub> (W/kg)	1 W Normalized SAR <sub>10g</sub> (W/kg)	Deviation <sub>10g</sub> (%)
E	2450	BODY	01/02/2017	22.7	22.5	0.100	981	7406	2.380	23.800	23.800	0.00%
E	2600	BODY	01/02/2017	22.7	22.5	0.100	1071	7406	2.480	24.500	24.800	1.22%



**Figure 10-1  
System Verification Setup Diagram**



**Figure 10-2  
System Verification Setup Photo**

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 46 of 70

# 11 SAR DATA SUMMARY



## 11.1 Standalone Head SAR Data

**Table 11-1  
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.7	33.65	-0.05	Right	Cheek	06767	1	1:8.3	0.283	1.012	0.286	A1
836.60	190	GSM 850	GSM	33.7	33.65	0.08	Right	Tilt	06767	1	1:8.3	0.172	1.012	0.174	
836.60	190	GSM 850	GSM	33.7	33.65	0.05	Left	Cheek	06767	1	1:8.3	0.239	1.012	0.242	
836.60	190	GSM 850	GSM	33.7	33.65	0.01	Left	Tilt	06767	1	1:8.3	0.159	1.012	0.161	
836.60	190	GSM 850	GPRS	30.7	30.68	0.09	Right	Cheek	06767	2	1:4.15	0.225	1.005	0.226	
836.60	190	GSM 850	GPRS	30.7	30.68	0.15	Right	Tilt	06767	2	1:4.15	0.150	1.005	0.151	
836.60	190	GSM 850	GPRS	30.7	30.68	-0.01	Left	Cheek	06767	2	1:4.15	0.195	1.005	0.196	
836.60	190	GSM 850	GPRS	30.7	30.68	0.11	Left	Tilt	06767	2	1:4.15	0.132	1.005	0.133	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2  
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	31.2	31.15	0.01	Right	Cheek	06767	1	1:8.3	0.189	1.012	0.191	
1880.00	661	GSM 1900	GSM	31.2	31.15	-0.09	Right	Tilt	06767	1	1:8.3	0.137	1.012	0.139	
1880.00	661	GSM 1900	GSM	31.2	31.15	0.02	Left	Cheek	06767	1	1:8.3	0.255	1.012	0.258	A2
1880.00	661	GSM 1900	GSM	31.2	31.15	0.16	Left	Tilt	06767	1	1:8.3	0.126	1.012	0.128	
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.06	Right	Cheek	06767	2	1:4.15	0.171	1.012	0.173	
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.06	Right	Tilt	06767	2	1:4.15	0.136	1.012	0.138	
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.03	Left	Cheek	06767	2	1:4.15	0.252	1.012	0.255	
1880.00	661	GSM 1900	GPRS	28.2	28.15	-0.02	Left	Tilt	06767	2	1:4.15	0.117	1.012	0.118	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 47 of 70



**Table 11-3  
UMTS 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.08	Right	Cheek	06767	1:1	0.359	1.012	0.363	A3
836.60	4183	UMTS 850	RMC	24.7	24.65	0.08	Right	Tilt	06767	1:1	0.222	1.012	0.225	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.05	Left	Cheek	06767	1:1	0.275	1.012	0.278	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.04	Left	Tilt	06767	1:1	0.181	1.012	0.183	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-4  
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.03	Right	Cheek	06767	1:1	0.282	1.002	0.283	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.02	Right	Tilt	06767	1:1	0.210	1.002	0.210	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.01	Left	Cheek	06767	1:1	0.342	1.002	0.343	A4
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.04	Left	Tilt	06767	1:1	0.224	1.002	0.224	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-5  
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	0.12	Right	Cheek	06767	1:1	0.366	1.009	0.369	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	0.02	Right	Tilt	06767	1:1	0.241	1.009	0.243	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	0.14	Left	Cheek	06767	1:1	0.502	1.009	0.507	A5
1880.00	9400	UMTS 1900	RMC	24.7	24.66	-0.06	Left	Tilt	06767	1:1	0.231	1.009	0.233	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 48 of 70

**Table 11-6  
CDMA BC0 (§22H) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.64	0.01	Right	Cheek	01655	1:1	0.410	1.014	0.416	A6
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.64	0.00	Right	Tilt	01655	1:1	0.260	1.014	0.264	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.64	0.04	Left	Cheek	01655	1:1	0.317	1.014	0.321	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.64	0.02	Left	Tilt	01655	1:1	0.206	1.014	0.209	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.06	Right	Cheek	01655	1:1	0.350	1.021	0.357	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	-0.02	Right	Tilt	01655	1:1	0.199	1.021	0.203	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.02	Left	Cheek	01655	1:1	0.320	1.021	0.327	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.14	Left	Tilt	01655	1:1	0.189	1.021	0.193	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-7  
CDMA BC10 (§90S) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	25.12	0.02	Right	Cheek	01655	1:1	0.392	1.019	0.399	A7
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	25.12	0.08	Right	Tilt	01655	1:1	0.258	1.019	0.263	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	25.12	0.02	Left	Cheek	01655	1:1	0.316	1.019	0.322	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	25.12	0.06	Left	Tilt	01655	1:1	0.209	1.019	0.213	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.20	0.00	Right	Cheek	01655	1:1	0.386	1.000	0.386	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.20	0.05	Right	Tilt	01655	1:1	0.211	1.000	0.211	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.20	0.06	Left	Cheek	01655	1:1	0.349	1.000	0.349	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.20	0.07	Left	Tilt	01655	1:1	0.190	1.000	0.190	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 49 of 70

**Table 11-8  
PCS CDMA Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.60	-0.03	Right	Cheek	01655	1:1	0.428	1.023	0.438	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.60	0.16	Right	Tilt	01655	1:1	0.253	1.023	0.259	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.60	0.02	Left	Cheek	01655	1:1	0.573	1.023	0.586	AB
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.60	0.08	Left	Tilt	01655	1:1	0.287	1.023	0.294	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.57	0.02	Right	Cheek	01655	1:1	0.390	1.030	0.402	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.57	-0.12	Right	Tilt	01655	1:1	0.249	1.030	0.256	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.57	-0.09	Left	Cheek	01655	1:1	0.565	1.030	0.582	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.57	0.17	Left	Tilt	01655	1:1	0.173	1.030	0.178	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-9  
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	0.11	0	Right	Cheek	QPSK	1	25	01653	1:1	0.284	1.000	0.284	AG
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.00	1	Right	Cheek	QPSK	25	0	01653	1:1	0.213	1.079	0.230	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	0.05	0	Right	Tilt	QPSK	1	25	01653	1:1	0.159	1.000	0.159	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.07	1	Right	Tilt	QPSK	25	0	01653	1:1	0.105	1.079	0.113	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.02	0	Left	Cheek	QPSK	1	25	01653	1:1	0.271	1.000	0.271	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	-0.01	1	Left	Cheek	QPSK	25	0	01653	1:1	0.210	1.079	0.227	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.03	0	Left	Tilt	QPSK	1	25	01653	1:1	0.154	1.000	0.154	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.03	1	Left	Tilt	QPSK	25	0	01653	1:1	0.118	1.079	0.127	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-10  
LTE Band 26 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.17	0	Right	Cheek	QPSK	1	36	01653	1:1	0.325	1.000	0.325	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	-0.09	1	Right	Cheek	QPSK	36	0	01653	1:1	0.274	1.067	0.292	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.03	0	Right	Tilt	QPSK	1	36	01653	1:1	0.179	1.000	0.179	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.05	1	Right	Tilt	QPSK	36	0	01653	1:1	0.154	1.067	0.164	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	0.04	0	Left	Cheek	QPSK	1	36	01653	1:1	0.334	1.000	0.334	A10
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.00	1	Left	Cheek	QPSK	36	0	01653	1:1	0.255	1.067	0.272	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.07	0	Left	Tilt	QPSK	1	36	01653	1:1	0.204	1.000	0.204	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.02	1	Left	Tilt	QPSK	36	0	01653	1:1	0.160	1.067	0.171	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 50 of 70	

**Table 11-11  
LTE Band 4 (AWS) Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.16	0	Right	Cheek	QPSK	1	50	01653	1:1	1.026	0.208	0.213	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	0.01	1	Right	Cheek	QPSK	50	50	01653	1:1	1.067	0.136	0.145	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.02	0	Right	Tilt	QPSK	1	50	01653	1:1	1.026	0.187	0.192	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	0.18	1	Right	Tilt	QPSK	50	50	01653	1:1	1.067	0.118	0.126	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	-0.02	0	Left	Cheek	QPSK	1	50	01653	1:1	1.026	0.361	0.370	A11
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	0.00	1	Left	Cheek	QPSK	50	50	01653	1:1	1.067	0.244	0.260	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.16	0	Left	Tilt	QPSK	1	50	01653	1:1	1.026	0.185	0.190	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	0.01	1	Left	Tilt	QPSK	50	50	01653	1:1	1.067	0.128	0.137	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-12  
LTE Band 25 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	0.17	0	Right	Cheek	QPSK	1	50	01653	1:1	1.023	0.347	0.355	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.04	1	Right	Cheek	QPSK	50	25	01653	1:1	1.000	0.280	0.280	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	-0.03	0	Right	Tilt	QPSK	1	50	01653	1:1	1.023	0.219	0.224	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.03	1	Right	Tilt	QPSK	50	25	01653	1:1	1.000	0.193	0.193	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	0.04	0	Left	Cheek	QPSK	1	50	01653	1:1	1.023	0.560	0.573	A12
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.02	1	Left	Cheek	QPSK	50	25	01653	1:1	1.000	0.424	0.424	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	0.06	0	Left	Tilt	QPSK	1	50	01653	1:1	1.023	0.209	0.214	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	0.02	1	Left	Tilt	QPSK	50	25	01653	1:1	1.000	0.201	0.201	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-13  
LTE Band 41 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.05	0	Right	Cheek	QPSK	1	0	01653	1:1.58	1.000	0.056	0.056	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.06	1	Right	Cheek	QPSK	50	0	01653	1:1.58	1.026	0.040	0.041	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.04	0	Right	Tilt	QPSK	1	0	01653	1:1.58	1.000	0.046	0.046	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.11	1	Right	Tilt	QPSK	50	0	01653	1:1.58	1.026	0.031	0.032	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.02	0	Left	Cheek	QPSK	1	0	01653	1:1.58	1.000	0.150	0.150	A13
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.12	1	Left	Cheek	QPSK	50	0	01653	1:1.58	1.026	0.109	0.112	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.03	0	Left	Tilt	QPSK	1	0	01653	1:1.58	1.000	0.031	0.031	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.08	1	Left	Tilt	QPSK	50	0	01653	1:1.58	1.026	0.023	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 51 of 70	

**Table 11-14  
DTS Head SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.04	Right	Cheek	01672	1	99.5	0.369	-	1.081	1.005	-	
2462	11	802.11b	DSSS	22	17.0	16.66	0.01	Right	Tilt	01672	1	99.5	0.350	-	1.081	1.005	-	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.01	Left	Cheek	01672	1	99.5	0.835	0.697	1.081	1.005	0.767	A14
2462	11	802.11b	DSSS	22	17.0	16.66	-0.02	Left	Tilt	01672	1	99.5	0.759	0.633	1.081	1.005	0.688	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

## 11.2 Standalone Body-Worn SAR Data

**Table 11-15  
GSM/UMTS/CDMA Body-Worn SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.7	33.65	0.04	10 mm	06767	1	1:8.3	back	0.475	1.012	0.481	A15
836.60	190	GSM 850	GPRS	30.7	30.68	-0.05	10 mm	06767	2	1:4.15	back	0.397	1.005	0.399	
1880.00	661	GSM 1900	GSM	31.2	31.15	0.05	10 mm	06767	1	1:8.3	back	0.404	1.012	0.409	A17
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.02	10 mm	06767	2	1:4.15	back	0.362	1.012	0.366	
836.60	4183	UMTS 850	RMC	24.7	24.65	-0.04	10 mm	06767	N/A	1:1	back	0.578	1.012	0.585	A19
1712.40	1312	UMTS 1750	RMC	24.7	24.68	-0.03	10 mm	06767	N/A	1:1	back	0.910	1.005	0.915	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.04	10 mm	06767	N/A	1:1	back	0.825	1.002	0.827	
1752.60	1513	UMTS 1750	RMC	24.7	24.66	-0.03	10 mm	06767	N/A	1:1	back	0.604	1.009	0.609	
1712.40	1312	UMTS 1750	RMC	24.7	24.68	-0.03	10 mm	06767	N/A	1:1	back	1.010	1.005	1.015	A20
1852.40	9262	UMTS 1900	RMC	24.7	24.65	0.07	10 mm	06767	N/A	1:1	back	0.667	1.012	0.675	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	-0.03	10 mm	06767	N/A	1:1	back	0.807	1.009	0.814	A21
1907.60	9538	UMTS 1900	RMC	24.7	24.68	0.03	10 mm	06767	N/A	1:1	back	0.730	1.005	0.734	
836.52	384	CDMA BC0 (§22H)	TDSO / SO32	24.7	24.60	0.00	10 mm	01655	N/A	1:1	back	0.652	1.023	0.667	A22
820.10	564	CDMABC10 (§90S)	TDSO / SO32	25.2	25.18	-0.04	10 mm	01655	N/A	1:1	back	0.672	1.005	0.675	A24
1851.25	25	PCS CDMA	TDSO / SO32	24.7	24.59	0.00	10 mm	01655	N/A	1:1	back	0.731	1.026	0.750	
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.54	0.02	10 mm	01655	N/A	1:1	back	0.803	1.038	0.834	
1908.75	1175	PCS CDMA	TDSO / SO32	24.7	24.70	-0.02	10 mm	01655	N/A	1:1	back	0.815	1.000	0.815	A26
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entry represents variability measurement

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 52 of 70	

**Table 11-16  
LTE Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.01	0	01653	QPSK	1	25	10 mm	back	1:1	0.534	1.000	0.534	A28
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	-0.04	1	01653	QPSK	25	0	10 mm	back	1:1	0.380	1.079	0.410	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.14	0	01653	QPSK	1	36	10 mm	back	1:1	0.657	1.000	0.657	A29
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.13	1	01653	QPSK	36	0	10 mm	back	1:1	0.492	1.067	0.525	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.20	0	01653	QPSK	1	50	10 mm	back	1:1	0.810	1.026	0.831	A30
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	-0.07	1	01653	QPSK	50	50	10 mm	back	1:1	0.588	1.067	0.627	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.25	-0.01	1	01653	QPSK	100	0	10 mm	back	1:1	0.574	1.109	0.637	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.45	-0.03	0	01653	QPSK	1	50	10 mm	back	1:1	0.753	1.059	0.797	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.42	-0.19	0	01653	QPSK	1	50	10 mm	back	1:1	0.730	1.067	0.779	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	-0.03	0	01653	QPSK	1	50	10 mm	back	1:1	0.805	1.023	0.824	A31
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.17	1	01653	QPSK	50	25	10 mm	back	1:1	0.652	1.000	0.652	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.65	-0.04	1	01653	QPSK	100	0	10 mm	back	1:1	0.692	1.012	0.700	
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	0.01	0	01653	QPSK	1	50	10 mm	back	1:1.58	0.814	1.007	0.820	
2549.50	40185	Low-Mid	LTE Band 41	20	24.7	24.53	0.20	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.020	1.040	1.061	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	-0.17	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.150	1.007	1.158	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	-0.02	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.190	1.000	1.190	A32
2680.00	41490	High	LTE Band 41	20	24.7	24.63	-0.03	0	01653	QPSK	1	0	10 mm	back	1:1.58	0.783	1.016	0.796	
2506.00	39750	Low	LTE Band 41	20	23.7	23.38	-0.01	1	01653	QPSK	50	50	10 mm	back	1:1.58	0.679	1.076	0.731	
2549.50	40185	Low-Mid	LTE Band 41	20	23.7	23.23	-0.01	1	01653	QPSK	50	50	10 mm	back	1:1.58	0.791	1.114	0.881	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	-0.05	1	01653	QPSK	50	0	10 mm	back	1:1.58	0.888	1.026	0.911	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.58	-0.16	1	01653	QPSK	50	0	10 mm	back	1:1.58	0.714	1.028	0.734	
2680.00	41490	High	LTE Band 41	20	23.7	23.24	0.07	1	01653	QPSK	50	25	10 mm	back	1:1.58	0.576	1.112	0.641	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.53	0.09	1	01653	QPSK	100	0	10 mm	back	1:1.58	0.713	1.040	0.742	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-17  
DTS Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan (W/kg)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.15	10 mm	01672	1	back	99.5	0.218	0.199	1.081	1.005	0.216	A34
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								



FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 53 of 70	

# 11.3 Standalone Hotspot SAR Data

**Table 11-18  
GPRS/UMTS/CDMA Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR [1g]	Scaling Factor	Reported SAR [1g]	Plot #
Mhz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	30.7	30.68	-0.05	10 mm	06767	2	1:4.15	back	0.397	1.005	0.399	
836.60	190	GSM 850	GPRS	30.7	30.68	0.00	10 mm	06767	2	1:4.15	front	0.287	1.005	0.288	
836.60	190	GSM 850	GPRS	30.7	30.68	0.04	10 mm	06767	2	1:4.15	bottom	0.223	1.005	0.224	
836.60	190	GSM 850	GPRS	30.7	30.68	0.03	10 mm	06767	2	1:4.15	right	0.434	1.005	0.436	A16
836.60	190	GSM 850	GPRS	30.7	30.68	-0.07	10 mm	06767	2	1:4.15	left	0.233	1.005	0.234	
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.02	10 mm	06767	2	1:4.15	back	0.362	1.012	0.366	A18
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.02	10 mm	06767	2	1:4.15	front	0.262	1.012	0.265	
1880.00	661	GSM 1900	GPRS	28.2	28.15	-0.03	10 mm	06767	2	1:4.15	bottom	0.210	1.012	0.213	
1880.00	661	GSM 1900	GPRS	28.2	28.15	0.03	10 mm	06767	2	1:4.15	left	0.232	1.012	0.235	
836.60	4183	UMTS 850	RMC	24.7	24.65	-0.04	10 mm	06767	N/A	1:1	back	0.578	1.012	0.585	A19
836.60	4183	UMTS 850	RMC	24.7	24.65	-0.01	10 mm	06767	N/A	1:1	front	0.406	1.012	0.411	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.00	10 mm	06767	N/A	1:1	bottom	0.335	1.012	0.339	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.00	10 mm	06767	N/A	1:1	right	0.566	1.012	0.573	
836.60	4183	UMTS 850	RMC	24.7	24.65	0.00	10 mm	06767	N/A	1:1	left	0.331	1.012	0.335	
1712.40	1312	UMTS 1750	RMC	24.7	24.68	-0.03	10 mm	06767	N/A	1:1	back	0.910	1.005	0.915	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.04	10 mm	06767	N/A	1:1	back	0.825	1.002	0.827	
1752.60	1513	UMTS 1750	RMC	24.7	24.66	-0.03	10 mm	06767	N/A	1:1	back	0.604	1.009	0.609	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.01	10 mm	06767	N/A	1:1	front	0.633	1.002	0.634	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.00	10 mm	06767	N/A	1:1	bottom	0.381	1.002	0.382	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.01	10 mm	06767	N/A	1:1	left	0.488	1.002	0.489	
1712.40	1312	UMTS 1750	RMC	24.7	24.68	-0.03	10 mm	06767	N/A	1:1	back	1.010	1.005	1.015	A20
1852.40	9262	UMTS 1900	RMC	24.7	24.65	0.07	10 mm	06767	N/A	1:1	back	0.667	1.012	0.675	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	-0.03	10 mm	06767	N/A	1:1	back	0.807	1.009	0.814	A21
1907.60	9538	UMTS 1900	RMC	24.7	24.68	0.03	10 mm	06767	N/A	1:1	back	0.730	1.005	0.734	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	0.05	10 mm	06767	N/A	1:1	front	0.584	1.009	0.589	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	0.01	10 mm	06767	N/A	1:1	bottom	0.452	1.009	0.456	
1880.00	9400	UMTS 1900	RMC	24.7	24.66	-0.01	10 mm	06767	N/A	1:1	left	0.473	1.009	0.477	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	24.7	24.64	-0.03	10 mm	01655	N/A	1:1	back	0.680	1.014	0.690	A23
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	24.7	24.64	0.00	10 mm	01655	N/A	1:1	front	0.426	1.014	0.432	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	24.7	24.64	0.07	10 mm	01655	N/A	1:1	bottom	0.352	1.014	0.357	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	24.7	24.64	0.00	10 mm	01655	N/A	1:1	right	0.561	1.014	0.569	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	24.7	24.64	-0.06	10 mm	01655	N/A	1:1	left	0.275	1.014	0.279	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	25.17	-0.07	10 mm	01655	N/A	1:1	back	0.615	1.007	0.619	A25
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	25.17	0.09	10 mm	01655	N/A	1:1	front	0.455	1.007	0.458	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	25.17	0.07	10 mm	01655	N/A	1:1	bottom	0.328	1.007	0.330	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	25.17	-0.04	10 mm	01655	N/A	1:1	right	0.574	1.007	0.578	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	25.17	0.09	10 mm	01655	N/A	1:1	left	0.282	1.007	0.284	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.62	0.06	10 mm	01655	N/A	1:1	back	0.790	1.019	0.805	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.58	0.05	10 mm	01655	N/A	1:1	back	0.847	1.028	0.871	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.65	-0.02	10 mm	01655	N/A	1:1	back	0.870	1.012	0.880	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.58	0.02	10 mm	01655	N/A	1:1	front	0.614	1.028	0.631	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.58	-0.07	10 mm	01655	N/A	1:1	bottom	0.455	1.028	0.468	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.58	-0.01	10 mm	01655	N/A	1:1	left	0.622	1.028	0.639	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.65	-0.04	10 mm	01655	N/A	1:1	back	0.878	1.012	0.889	A27
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entries represent variability measurements



FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 54 of 70	

**Table 11-19  
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.01	0	01653	QPSK	1	25	10 mm	back	1:1	0.534	1.000	0.534	A28
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	-0.04	1	01653	QPSK	25	0	10 mm	back	1:1	0.380	1.079	0.410	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	0.01	0	01653	QPSK	1	25	10 mm	front	1:1	0.348	1.000	0.348	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.01	1	01653	QPSK	25	0	10 mm	front	1:1	0.255	1.079	0.275	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.06	0	01653	QPSK	1	25	10 mm	bottom	1:1	0.176	1.000	0.176	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.05	1	01653	QPSK	25	0	10 mm	bottom	1:1	0.130	1.079	0.140	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.21	0	01653	QPSK	1	25	10 mm	right	1:1	0.460	1.000	0.460	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	0.03	1	01653	QPSK	25	0	10 mm	right	1:1	0.331	1.079	0.357	
707.50	23095	Mid	LTE Band 12	10	24.7	24.70	-0.01	0	01653	QPSK	1	25	10 mm	left	1:1	0.216	1.000	0.216	
707.50	23095	Mid	LTE Band 12	10	23.7	23.37	-0.05	1	00551	QPSK	25	0	10 mm	left	1:1	0.156	1.079	0.168	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-20  
LTE Band 26 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.14	0	01653	QPSK	1	36	10 mm	back	1:1	0.657	1.000	0.657	A29
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.13	1	01653	QPSK	36	0	10 mm	back	1:1	0.492	1.067	0.525	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.06	0	01653	QPSK	1	36	10 mm	front	1:1	0.420	1.000	0.420	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.01	1	01653	QPSK	36	0	10 mm	front	1:1	0.323	1.067	0.345	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.11	0	01653	QPSK	1	36	10 mm	bottom	1:1	0.336	1.000	0.336	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.14	1	01653	QPSK	36	0	10 mm	bottom	1:1	0.247	1.067	0.264	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.08	0	01653	QPSK	1	36	10 mm	right	1:1	0.540	1.000	0.540	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	-0.01	1	01653	QPSK	36	0	10 mm	right	1:1	0.409	1.067	0.436	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.7	24.70	-0.04	0	01653	QPSK	1	36	10 mm	left	1:1	0.251	1.000	0.251	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.7	23.42	0.10	1	01653	QPSK	36	0	10 mm	left	1:1	0.195	1.067	0.208	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 55 of 70	





**Table 11-21  
LTE Band 4 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.20	0	01653	QPSK	1	50	10 mm	back	1:1	0.810	1.026	0.831	A30
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	-0.07	1	01653	QPSK	50	50	10 mm	back	1:1	0.588	1.067	0.627	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.25	-0.01	1	01653	QPSK	100	0	10 mm	back	1:1	0.574	1.109	0.637	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	0.18	0	01653	QPSK	1	50	10 mm	front	1:1	0.601	1.026	0.617	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	0.04	1	01653	QPSK	50	50	10 mm	front	1:1	0.456	1.067	0.487	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	-0.11	0	01653	QPSK	1	50	10 mm	bottom	1:1	0.380	1.026	0.390	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	-0.01	1	01653	QPSK	50	50	10 mm	bottom	1:1	0.267	1.067	0.285	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.59	-0.19	0	01653	QPSK	1	50	10 mm	left	1:1	0.526	1.026	0.540	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.42	-0.08	1	01653	QPSK	50	50	10 mm	left	1:1	0.377	1.067	0.402	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-22  
LTE Band 25 (PCS) Hotspot SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.45	-0.03	0	01653	QPSK	1	50	10 mm	back	1:1	0.753	1.059	0.797	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.42	-0.19	0	01653	QPSK	1	50	10 mm	back	1:1	0.730	1.067	0.779	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	-0.03	0	01653	QPSK	1	50	10 mm	back	1:1	0.805	1.023	0.824	A31
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.17	1	01653	QPSK	50	25	10 mm	back	1:1	0.652	1.000	0.652	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.65	-0.04	1	01653	QPSK	100	0	10 mm	back	1:1	0.692	1.012	0.700	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	0.15	0	01653	QPSK	1	50	10 mm	front	1:1	0.539	1.023	0.551	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.04	1	01653	QPSK	50	25	10 mm	front	1:1	0.459	1.000	0.459	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	0.13	0	01653	QPSK	1	50	10 mm	bottom	1:1	0.396	1.023	0.405	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.12	1	01653	QPSK	50	25	10 mm	bottom	1:1	0.338	1.000	0.338	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.60	-0.04	0	01653	QPSK	1	50	10 mm	left	1:1	0.464	1.023	0.475	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.7	23.70	-0.04	1	01653	QPSK	50	25	10 mm	left	1:1	0.429	1.000	0.429	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 56 of 70	

**Table 11-23  
LTE Band 41 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	0.01	0	01653	QPSK	1	50	10 mm	back	1:1.58	0.814	1.007	0.820	
2549.50	40185	Low-Mid	LTE Band 41	20	24.7	24.53	0.20	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.020	1.040	1.061	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	-0.17	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.150	1.007	1.158	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	-0.02	0	01653	QPSK	1	0	10 mm	back	1:1.58	1.190	1.000	1.190	
2680.00	41490	High	LTE Band 41	20	24.7	24.63	-0.03	0	01653	QPSK	1	0	10 mm	back	1:1.58	0.783	1.016	0.796	
2506.00	39750	Low	LTE Band 41	20	23.7	23.38	-0.01	1	01653	QPSK	50	50	10 mm	back	1:1.58	0.679	1.076	0.731	
2549.50	40185	Low-Mid	LTE Band 41	20	23.7	23.23	-0.01	1	01653	QPSK	50	50	10 mm	back	1:1.58	0.791	1.114	0.881	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	-0.05	1	01653	QPSK	50	0	10 mm	back	1:1.58	0.888	1.026	0.911	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.58	-0.16	1	01653	QPSK	50	0	10 mm	back	1:1.58	0.714	1.028	0.734	
2680.00	41490	High	LTE Band 41	20	23.7	23.24	0.07	1	01653	QPSK	50	25	10 mm	back	1:1.58	0.576	1.112	0.641	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.53	0.09	1	01653	QPSK	100	0	10 mm	back	1:1.58	0.713	1.040	0.742	
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	0.05	0	01653	QPSK	1	50	10 mm	front	1:1.58	0.410	1.007	0.413	
2549.50	40185	Low-Mid	LTE Band 41	20	24.7	24.53	-0.20	0	01653	QPSK	1	0	10 mm	front	1:1.58	0.528	1.040	0.549	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	0.10	0	01653	QPSK	1	0	10 mm	front	1:1.58	0.695	1.007	0.700	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	-0.01	0	01653	QPSK	1	0	10 mm	front	1:1.58	0.656	1.000	0.656	
2680.00	41490	High	LTE Band 41	20	24.7	24.63	-0.01	0	01653	QPSK	1	0	10 mm	front	1:1.58	0.538	1.016	0.547	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.13	1	01653	QPSK	50	0	10 mm	front	1:1.58	0.529	1.026	0.543	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.53	0.02	1	01653	QPSK	100	0	10 mm	front	1:1.58	0.469	1.040	0.488	
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	0.04	0	01653	QPSK	1	50	10 mm	bottom	1:1.58	0.835	1.007	0.841	
2549.50	40185	Low-Mid	LTE Band 41	20	24.7	24.53	0.04	0	01653	QPSK	1	0	10 mm	bottom	1:1.58	1.100	1.040	1.144	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	-0.04	0	01653	QPSK	1	0	10 mm	bottom	1:1.58	1.210	1.007	1.218	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	-0.04	0	01653	QPSK	1	0	10 mm	bottom	1:1.58	1.270	1.000	1.270	A33
2680.00	41490	High	LTE Band 41	20	24.7	24.63	0.01	0	01653	QPSK	1	0	10 mm	bottom	1:1.58	1.010	1.016	1.026	
2506.00	39750	Low	LTE Band 41	20	23.7	23.38	-0.04	1	01653	QPSK	50	50	10 mm	bottom	1:1.58	0.727	1.076	0.782	
2549.50	40185	Low-Mid	LTE Band 41	20	23.7	23.23	-0.08	1	01653	QPSK	50	50	10 mm	bottom	1:1.58	0.930	1.114	1.036	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	-0.02	1	01653	QPSK	50	0	10 mm	bottom	1:1.58	1.120	1.026	1.149	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.58	-0.09	1	01653	QPSK	50	0	10 mm	bottom	1:1.58	1.110	1.028	1.141	
2680.00	41490	High	LTE Band 41	20	23.7	23.24	-0.13	1	01653	QPSK	50	25	10 mm	bottom	1:1.58	0.823	1.112	0.915	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.53	-0.20	1	01653	QPSK	100	0	10 mm	bottom	1:1.58	1.030	1.040	1.071	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.14	0	01653	QPSK	1	0	10 mm	right	1:1.58	0.025	1.000	0.025	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.02	1	01653	QPSK	50	0	10 mm	right	1:1.58	0.020	1.026	0.021	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.01	0	01653	QPSK	1	0	10 mm	left	1:1.58	0.123	1.000	0.123	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	0.12	1	01653	QPSK	50	0	10 mm	left	1:1.58	0.077	1.026	0.079	
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	-0.09	0	01653	QPSK	1	50	10 mm	bottom	1:1.58	0.787	1.007	0.793	
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	0.02	0	01653	QPSK	1	0	10 mm	bottom	1:1.58	1.260	1.000	1.260	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

Note: Blue entries represent variability measurements

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 57 of 70	

**Table 11-24  
WLAN Hotspot SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.15	10 mm	01672	1	back	99.5	0.218	0.199	1.081	1.005	0.216	A34
2462	11	802.11b	DSSS	22	17.0	16.66	-0.07	10 mm	01672	1	front	99.5	0.215	-	1.081	1.005	-	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.10	10 mm	01672	1	top	99.5	0.026	-	1.081	1.005	-	
2462	11	802.11b	DSSS	22	17.0	16.66	-0.02	10 mm	01672	1	right	99.5	0.140	-	1.081	1.005	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

## 11.4 Standalone Phablet SAR Data

**Table 11-25  
LTE Band 41 Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	-0.11	0	01653	QPSK	1	50	0 mm	bottom	1:1.58	2.200	1.007	2.215	
2549.50	40185	Low-Mid	LTE Band 41	20	24.7	24.53	-0.03	0	01653	QPSK	1	0	0 mm	bottom	1:1.58	2.610	1.040	2.714	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	-0.02	0	01653	QPSK	1	0	0 mm	bottom	1:1.58	3.080	1.007	3.102	A35
2636.50	41055	Mid-High	LTE Band 41	20	24.7	24.70	-0.02	0	01653	QPSK	1	0	0 mm	bottom	1:1.58	2.970	1.000	2.970	
2680.00	41490	High	LTE Band 41	20	24.7	24.63	-0.06	0	01653	QPSK	1	0	0 mm	bottom	1:1.58	2.280	1.016	2.316	
2506.00	39750	Low	LTE Band 41	20	23.7	23.38	-0.04	1	01653	QPSK	50	50	0 mm	bottom	1:1.58	1.760	1.076	1.894	
2549.50	40185	Low-Mid	LTE Band 41	20	23.7	23.23	-0.15	1	01653	QPSK	50	50	0 mm	bottom	1:1.58	2.010	1.114	2.239	
2593.00	40620	Mid	LTE Band 41	20	23.7	23.59	-0.02	1	01653	QPSK	50	0	0 mm	bottom	1:1.58	2.400	1.026	2.462	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.58	0.00	1	01653	QPSK	50	0	0 mm	bottom	1:1.58	2.230	1.028	2.292	
2680.00	41490	High	LTE Band 41	20	23.7	23.24	-0.11	1	01653	QPSK	50	25	0 mm	bottom	1:1.58	1.760	1.112	1.957	
2636.50	41055	Mid-High	LTE Band 41	20	23.7	23.53	-0.09	1	01653	QPSK	100	0	0 mm	bottom	1:1.58	2.140	1.040	2.226	
2506.00	39750	Low	LTE Band 41	20	24.7	24.67	-0.02	0	01653	QPSK	1	50	0 mm	bottom	1:1.58	2.160	1.007	2.175	
2593.00	40620	Mid	LTE Band 41	20	24.7	24.67	-0.07	0	01653	QPSK	1	0	0 mm	bottom	1:1.58	3.040	1.007	3.061	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams											

Note: Blue entries represent variability measurements

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 58 of 70	

## 11.5 SAR Test Notes

### General Notes:



1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was  $\leq 1.2$  W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is  $> 160$  mm and  $< 200$  mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR  $> 1.2$  W/kg.

### GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address VoIP scenarios.

### CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 59 of 70	

- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

**UMTS Notes:**



- UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

**LTE Notes:**

- LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
- MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
- A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
- Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was  $> 0.6$  W/kg, testing at the other channels was required for such test configurations.
- TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
- Per KDB Publication 941225 D05Av01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not  $>0.25$  dB higher than the maximum output power when downlink carrier aggregation was inactive.

**WLAN Notes:**

- For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.3 for more information. When the maximum reported 1g averaged SAR is  $\leq 0.8$  W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg or all test channels were measured.
- The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

<b>FCC ID:</b> ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 60 of 70	

# 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

## 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

## 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is  $\leq 1.6$  W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.



$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1  
Estimated SAR**

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)	Separation Distance (Phablet)	Estimated SAR (Phablet)
	[MHz]	[dBm]	[mm]	[W/kg]	[mm]	[W/kg]
Bluetooth	2480	8.50	10	0.147	5	0.118

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 61 of 70

## 12.3 Head SAR Simultaneous Transmission Analysis



**Table 12-2**  
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.286	0.757	1.043
	GSM/GPRS 1900	0.258	0.757	1.015
	UMTS 850	0.363	0.757	1.120
	UMTS 1750	0.343	0.757	1.100
	UMTS 1900	0.507	0.757	1.264
	CDMA/EVDO BC0 (§22H)	0.416	0.757	1.173
	CDMA/EVDO BC10 (§90S)	0.399	0.757	1.156
	PCS CDMA/EVDO	0.586	0.757	<b>1.343</b>
	LTE Band 12	0.284	0.757	1.041
	LTE Band 26 (Cell)	0.334	0.757	1.091
	LTE Band 4 (AWS)	0.370	0.757	1.127
	LTE Band 25 (PCS)	0.573	0.757	1.330
	LTE Band 41	0.150	0.757	0.907

## 12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-3**  
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM/GPRS 850	0.481	0.216	0.697
	GSM/GPRS 1900	0.409	0.216	0.625
	UMTS 850	0.585	0.216	0.801
	UMTS 1750	1.015	0.216	1.231
	UMTS 1900	0.814	0.216	1.030
	CDMA BC0 (§22H)	0.667	0.216	0.883
	CDMA BC10 (§90S)	0.675	0.216	0.891
	PCS CDMA	0.834	0.216	1.050
	LTE Band 12	0.534	0.216	0.750
	LTE Band 26 (Cell)	0.657	0.216	0.873
	LTE Band 4 (AWS)	0.831	0.216	1.047
	LTE Band 25 (PCS)	0.824	0.216	1.040
	LTE Band 41	1.190	0.216	<b>1.406</b>



FCC ID: ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset	Page 62 of 70



**Table 12-4**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM/GPRS 850	0.481	0.147	0.628
	GSM/GPRS 1900	0.409	0.147	0.556
	UMTS 850	0.585	0.147	0.732
	UMTS 1750	1.015	0.147	1.162
	UMTS 1900	0.814	0.147	0.961
	CDMA BC0 (§22H)	0.667	0.147	0.814
	CDMA BC10 (§90S)	0.675	0.147	0.822
	PCS CDMA	0.834	0.147	0.981
	LTE Band 12	0.534	0.147	0.681
	LTE Band 26 (Cell)	0.657	0.147	0.804
	LTE Band 4 (AWS)	0.831	0.147	0.978
	LTE Band 25 (PCS)	0.824	0.147	0.971
	LTE Band 41	1.190	0.147	<b>1.337</b>

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 63 of 70	



## 12.5 Hotspot SAR Simultaneous Transmission Analysis

**Table 12-5**  
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)
Hotspot SAR	GPRS 850	0.436	0.216	0.652
	GPRS 1900	0.366	0.216	0.582
	UMTS 850	0.585	0.216	0.801
	UMTS 1750	1.015	0.216	1.231
	UMTS 1900	0.814	0.216	1.030
	EVDO BC0 (§22H)	0.690	0.216	0.906
	EVDO BC10 (§90S)	0.619	0.216	0.835
	PCS EVDO	0.889	0.216	1.105
	LTE Band 12	0.534	0.216	0.750
	LTE Band 26 (Cell)	0.657	0.216	0.873
	LTE Band 4 (AWS)	0.831	0.216	1.047
	LTE Band 25 (PCS)	0.824	0.216	1.040
	LTE Band 41	1.270	0.216	<b>1.486</b>

## 12.6 Phablet SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis beyond Table 12-6 was required to determine that possible Simultaneous Transmission scenarios would not exceed the SAR limit.



**Table 12-6**  
Simultaneous Transmission Scenario (Bluetooth Phablet)

Exposure Condition	Mode	4G SAR (W/kg)	Bluetooth SAR (W/kg)	$\Sigma$ SAR (W/kg)
Phablet SAR	LTE Band 41	3.102	0.118	<b>3.220</b>

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

## 12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 64 of 70	

# 13 SAR MEASUREMENT VARIABILITY

## 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 4) Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

**Table 13-1  
Body SAR Measurement Variability Results (1 g)**



BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1712.40	1312	UMTS 1750	RMC	back	10 mm	0.910	1.010	1.11	N/A	N/A	N/A	N/A
1900	1908.75	1175	PCS CDMA	EVDO Rev. 0	back	10 mm	0.870	0.878	1.01	N/A	N/A	N/A	N/A
2450	2506.00	39750	LTE Band 41, 20 MHz Bandwidth	QPSK, 1RB, 50 RB Offset	bottom	10 mm	0.835	0.787	1.06	N/A	N/A	N/A	N/A
2600	2636.50	41055	LTE Band 41, 20 MHz Bandwidth	QPSK, 1RB, 0 RB Offset	bottom	10 mm	1.270	1.260	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 13-2  
Body SAR Measurement Variability Results (10 g)**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (10g)	1st Repeated SAR (10g)	Ratio	2nd Repeated SAR (10g)	Ratio	3rd Repeated SAR (10g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
2450	2506.00	39750	LTE Band 41, 20 MHz Bandwidth	QPSK, 1RB, 50 RB Offset	bottom	0 mm	2.200	2.160	1.02	N/A	N/A	N/A	N/A
2600	2593.00	40620	LTE Band 41, 20 MHz Bandwidth	QPSK, 1RB, 0 RB Offset	bottom	0 mm	3.080	3.040	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Phablet 4.0 W/kg (mW/g) averaged over 10 gram							

## 13.2 Measurement Uncertainty



The measured SAR was  $< 1.5$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFLS777		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 65 of 70	

# 14 EQUIPMENT LIST



Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/2/2016	Annual	3/2/2017	JP38020182
Agilent	8753ES	S-Parameter Network Analyzer	3/3/2016	Annual	3/3/2017	US39170122
Agilent	E4432B	ESG-D Series Signal Generator	3/5/2016	Annual	3/5/2017	US40053896
Agilent	E4438C	ESG Vector Signal Generator	3/13/2015	Biennial	3/13/2017	MY42082385
Agilent	E5515C	Wireless Communications Test Set	1/29/2016	Biennial	1/29/2018	GB46310798
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/2/2016	Annual	3/2/2017	MY45470194
Agilent	N5182A	MXG Vector Signal Generator	3/5/2016	Annual	3/5/2017	MY47420800
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA24106A	USB Power Sensor	6/2/2016	Annual	6/2/2017	1231538
Anritsu	MA24106A	USB Power Sensor	6/2/2016	Annual	6/2/2017	1231535
Anritsu	MA2411B	Pulse Power Sensor	10/14/2015	Biennial	10/14/2017	846215
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	5318
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	2400
Anritsu	ML2438A	Power Meter	3/3/2016	Annual	3/3/2017	1070030
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2496A	Power Meter	3/5/2016	Annual	3/5/2017	1351001
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Digital Thermometer	3/15/2015	Biennial	3/15/2017	150194929
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261701
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053081
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	3/25/2016	Annual	3/25/2017	128633
Seekonk	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
SPEAG	D1765V2	1765 MHz SAR Dipole	5/11/2016	Annual	5/11/2017	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Annual	7/8/2017	5d080
SPEAG	D1900V2	1900 MHz SAR Dipole	7/15/2016	Annual	7/15/2017	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	981
SPEAG	D2600V2	2600 MHz SAR Dipole	9/13/2016	Annual	9/13/2017	1071
SPEAG	D750V3	750 MHz Dipole	3/16/2016	Annual	3/16/2017	1054
SPEAG	D835V2	835 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	4d133
SPEAG	D1750V2	SAR Dipole	5/9/2016	Annual	5/9/2017	1148
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Annual	7/13/2017	4d047
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2016	Annual	2/18/2017	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/14/2016	Annual	3/14/2017	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2016	Annual	4/14/2017	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/11/2016	Annual	5/11/2017	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/19/2016	Annual	2/19/2017	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/22/2016	Annual	8/22/2017	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/14/2016	Annual	9/14/2017	1408
SPEAG	DAK-12	Dielectric Assessment Kit (10MHz - 3GHz)	3/1/2016	Annual	3/1/2017	1102
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2016	Annual	5/10/2017	1070
SPEAG	DAKS-3.5	Portable Dielectric Assessment Kit	7/19/2016	Annual	7/19/2017	1039
SPEAG	ES3DV3	SAR Probe	2/19/2016	Annual	2/19/2017	3213
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3319
SPEAG	ES3DV3	SAR Probe	9/19/2016	Annual	9/19/2017	3287
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7406
SPEAG	EX3DV4	SAR Probe	5/17/2016	Annual	5/17/2017	7409
SPEAG	ES3DV3	SAR Probe	2/19/2016	Annual	2/19/2017	3318
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3209

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFLS777		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 1M1701030001-01-R1.ZNF	Test Dates: 12/19/16 - 01/02/17	DUT Type: Portable Handset		Page 66 of 70

# 15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> 1gm	c <sub>i</sub> 10 gms	1gm u <sub>i</sub> (± %)	10gms u <sub>i</sub> (± %)	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
<b>Test Sample Related</b>								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
<b>Phantom &amp; Tissue Parameters</b>								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
<b>Combined Standard Uncertainty (k=1)</b>	RSS					11.5	11.3	60
<b>Expanded Uncertainty</b> (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	



FCC ID: ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset		Page 67 of 70

# 16 CONCLUSION

## 16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



<b>FCC ID:</b> ZNFLS777	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 68 of 70	

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

<b>FCC ID:</b> ZNFLS777		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 69 of 70	

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

<b>FCC ID:</b> ZNFLS777	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 1M1701030001-01-R1.ZNF	<b>Test Dates:</b> 12/19/16 - 01/02/17	<b>DUT Type:</b> Portable Handset	Page 70 of 70

## APPENDIX A: SAR TEST DATA



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium: 835 Head Medium parameters used (interpolated):  
 $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.876 \text{ S/m}$ ;  $\epsilon_r = 39.812$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Right Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (7x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 17.96 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 0.363 W/kg  
**SAR(1 g) = 0.283 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium: 1900 Head Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.431 \text{ S/m}$ ;  $\epsilon_r = 39.359$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-21-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3287; ConvF(5.27, 5.27, 5.27); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Left Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 13.98 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 0.397 W/kg  
**SAR(1 g) = 0.255 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium: 835 Head Medium parameters used (interpolated):  
 $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.876 \text{ S/m}$ ;  $\epsilon_r = 39.812$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Right Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (7x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 19.98 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 0.460 W/kg  
**SAR(1 g) = 0.359 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1  
Medium: 1750 Head Medium parameters used (interpolated):  
 $f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.363 \text{ S/m}$ ;  $\epsilon_r = 40.791$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-24-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Left Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 16.49 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 0.491 W/kg  
**SAR(1 g) = 0.342 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: 1900 Head Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.431 \text{ S/m}$ ;  $\epsilon_r = 39.359$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-21-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3287; ConvF(5.27, 5.27, 5.27); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.36 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.792 W/kg

**SAR(1 g) = 0.502 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1  
Medium: 835 Head Medium parameters used (interpolated):  
 $f = 836.52 \text{ MHz}$ ;  $\sigma = 0.876 \text{ S/m}$ ;  $\epsilon_r = 39.813$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA BC 0, Rule Part 22H, Right Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 21.97 V/m; Power Drift = 0.01 dB  
Peak SAR (extrapolated) = 0.532 W/kg  
**SAR(1 g) = 0.410 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**

Communication System: UID 0, Cellular CDMA (0); Frequency: 820.1 MHz; Duty Cycle: 1:1  
Medium: 835 Head Medium parameters used (interpolated):  
 $f = 820.1 \text{ MHz}$ ;  $\sigma = 0.863 \text{ S/m}$ ;  $\epsilon_r = 40.059$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA BC 10, Rule Part 90S, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.51 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.493 W/kg

**SAR(1 g) = 0.392 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, PCS CDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: 1900 Head Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.431 \text{ S/m}$ ;  $\epsilon_r = 39.359$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-21-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3287; ConvF(5.27, 5.27, 5.27); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASYS2, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: PCS CDMA, Left Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 19.92 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 0.897 W/kg  
**SAR(1 g) = 0.573 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.861 \text{ S/m}$ ;  $\epsilon_r = 42.888$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-22-2016; Ambient Temp: 23.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(6.96, 6.96, 6.96); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.40 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.344 W/kg

**SAR(1 g) = 0.284 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 26 (0); Frequency: 831.5 MHz; Duty Cycle: 1:1  
Medium: 835 Head Medium parameters used (interpolated):  
 $f = 831.5 \text{ MHz}$ ;  $\sigma = 0.871 \text{ S/m}$ ;  $\epsilon_r = 39.88$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Left Head, Cheek, Mid.ch,  
15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 20.56 V/m; Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 0.422 W/kg  
**SAR(1 g) = 0.334 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Head Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.363 \text{ S/m}$ ;  $\epsilon_r = 40.79$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-24-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648  
Measurement SW: DASYS2, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 17.84 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 0.525 W/kg  
**SAR(1 g) = 0.361 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1  
Medium: 1900 Head Medium parameters used (interpolated):  
 $f = 1905 \text{ MHz}$ ;  $\sigma = 1.458 \text{ S/m}$ ;  $\epsilon_r = 39.253$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-21-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3287; ConvF(5.27, 5.27, 5.27); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 20.67 V/m; Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 0.895 W/kg  
**SAR(1 g) = 0.560 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 41 (0); Frequency: 2636.5 MHz; Duty Cycle: 1:1.58  
Medium: 2300 - 2600 Head Medium parameters used (interpolated):  
 $f = 2636.5 \text{ MHz}$ ;  $\sigma = 2.096 \text{ S/m}$ ;  $\epsilon_r = 37.341$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-27-2016; Ambient Temp: 21.0°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(7.08, 7.08, 7.08); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Left Head, Cheek, Mid-High.ch,  
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm  
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 9.294 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 0.282 W/kg  
**SAR(1 g) = 0.150 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01672**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium: 2450 Head Medium parameters used (interpolated):  
 $f = 2462 \text{ MHz}$ ;  $\sigma = 1.888 \text{ S/m}$ ;  $\epsilon_r = 38.066$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 12-22-2016; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3213; ConvF(4.58, 4.58, 4.58); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head, Cheek, Ch 11, 1 Mbps**


**Area Scan (11x18x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 19.84 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.77 W/kg

**SAR(1 g) = 0.697 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 836.6 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 54.121$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Body SAR, Back side, Mid.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 23.04 V/m; Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 0.811 W/kg  
**SAR(1 g) = 0.475 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 54.121$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Body SAR, Right Edge, Mid.ch, 2 Tx Slots**


**Area Scan (10x13x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.81 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.608 W/kg

**SAR(1 g) = 0.434 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium: 1900 Body Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.55 \text{ S/m}$ ;  $\epsilon_r = 53.193$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Body SAR, Back side, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 16.88 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.772 W/kg  
**SAR(1 g) = 0.404 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.55 \text{ S/m}$ ;  $\epsilon_r = 53.193$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 2 Tx Slots**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.11 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.683 W/kg

**SAR(1 g) = 0.362 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 54.121$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.41 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.980 W/kg

**SAR(1 g) = 0.578 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1  
Medium: 1750 Body Medium parameters used (interpolated):  
 $f = 1712.4 \text{ MHz}$ ;  $\sigma = 1.47 \text{ S/m}$ ;  $\epsilon_r = 51.554$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 8/22/2016  
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Body SAR, Back side, Low.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.70 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.46 W/kg  
**SAR(1 g) = 1.01 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 06767**


Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: 1900 Body Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.55 \text{ S/m}$ ;  $\epsilon_r = 53.193$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Back side, Mid.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 23.94 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.54 W/kg  
**SAR(1 g) = 0.807 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 836.52 \text{ MHz}$ ;  $\sigma = 1.006 \text{ S/m}$ ;  $\epsilon_r = 55.159$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 21.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.85 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.08 W/kg

**SAR(1 g) = 0.652 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 836.52$  MHz;  $\sigma = 1.006$  S/m;  $\epsilon_r = 55.159$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 21.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. EVDO, Body SAR, Back side, Mid.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.62 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.13 W/kg  
**SAR(1 g) = 0.680 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 820.1 \text{ MHz}$ ;  $\sigma = 0.991 \text{ S/m}$ ;  $\epsilon_r = 55.324$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 21.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA BC10, Body SAR, Back side, Mid.ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (6x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 26.65 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 0.844 W/kg  
**SAR(1 g) = 0.672 W/kg**



0 dB = 0.754 W/kg = -1.23 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 820.1 \text{ MHz}$ ;  $\sigma = 0.991 \text{ S/m}$ ;  $\epsilon_r = 55.324$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 21.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. EVDO BC10, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.78 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.03 W/kg

**SAR(1 g) = 0.615 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
Medium: 1900 Body Medium parameters used:  
 $f = 1908.75 \text{ MHz}$ ;  $\sigma = 1.584 \text{ S/m}$ ;  $\epsilon_r = 53.136$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: PCS CDMA, Body SAR, Back side, High ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 23.94 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 1.54 W/kg  
**SAR(1 g) = 0.815 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01655**


Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
Medium: 1900 Body Medium parameters used (interpolated):  
 $f = 1908.75 \text{ MHz}$ ;  $\sigma = 1.584 \text{ S/m}$ ;  $\epsilon_r = 53.136$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: PCS EVDO, Body SAR, Back side, High ch**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 24.97 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 1.70 W/kg  
**SAR(1 g) = 0.878 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1  
Medium: 750 Body Medium parameters used (interpolated):  
 $f = 707.5 \text{ MHz}$ ;  $\sigma = 0.921 \text{ S/m}$ ;  $\epsilon_r = 54.673$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-22-2016; Ambient Temp: 21.1°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(6.19, 6.19, 6.19); Calibrated: 2/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800  
Measurement SW: DASYS2, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.52 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.683 W/kg

**SAR(1 g) = 0.534 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**

Communication System: UID 0, LTE Band 26 (0); Frequency: 831.5 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 831.5 \text{ MHz}$ ;  $\sigma = 0.995 \text{ S/m}$ ;  $\epsilon_r = 54.166$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,  
15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.54 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.10 W/kg

**SAR(1 g) = 0.657 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Body Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.484 \text{ S/m}$ ;  $\epsilon_r = 51.855$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 22.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 8/22/2016  
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758  
Measurement SW: DASYS2, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 24.19 V/m; Power Drift = 0.20 dB  
Peak SAR (extrapolated) = 1.18 W/kg  
**SAR(1 g) = 0.810 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1  
Medium: 1900 Body Medium parameters used (interpolated):  
 $f = 1905 \text{ MHz}$ ;  $\sigma = 1.579 \text{ S/m}$ ;  $\epsilon_r = 53.143$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 22.15 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.55 W/kg  
**SAR(1 g) = 0.805 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 41 (0); Frequency: 2636.5 MHz; Duty Cycle: 1:1.58  
Medium: 2400 Body Medium parameters used (interpolated):  
 $f = 2636.5 \text{ MHz}$ ;  $\sigma = 2.218 \text{ S/m}$ ;  $\epsilon_r = 51.167$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-27-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Back side, Mid-High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

**Area Scan (11x16x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$   
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 24.10 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 2.58 W/kg  
**SAR(1 g) = 1.19 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 41 (0); Frequency: 2636.5 MHz; Duty Cycle: 1:1.58  
Medium: 2400 Body Medium parameters used (interpolated):  
 $f = 2636.5 \text{ MHz}$ ;  $\sigma = 2.218 \text{ S/m}$ ;  $\epsilon_r = 51.167$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-27-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Bottom Edge, Mid-High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

**Area Scan (10x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=12\text{mm}$   
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 26.59 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 2.68 W/kg  
**SAR(1 g) = 1.27 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01672**


Communication System: UID 0, IEEE 802.11b (0); Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium: 2400 Body Medium parameters used (interpolated):  
 $f = 2462 \text{ MHz}$ ;  $\sigma = 2.051 \text{ S/m}$ ;  $\epsilon_r = 51.936$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 12-23-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side**

**Area Scan (11x17x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$   
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 10.70 V/m; Power Drift = -0.15 dB  
Peak SAR (extrapolated) = 0.458 W/kg  
**SAR(1 g) = 0.199 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFLS777; Type: Portable Handset; Serial: 01653**


Communication System: UID 0, LTE Band 41 (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium: 2400 Body Medium parameters used (interpolated):  
 $f = 2593 \text{ MHz}$ ;  $\sigma = 2.19 \text{ S/m}$ ;  $\epsilon_r = 51.081$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Space: 0.0 cm

Test Date: 01-02-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Phablet SAR, Bottom Edge, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

**Area Scan (10x9x1):** Measurement grid: dx=5mm, dy=12mm  
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 72.79 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 25.3 W/kg  
**SAR(10 g) = 3.08 W/kg**



0 dB = 18.3 W/kg = 12.62 dBW/kg

## APPENDIX B: SYSTEM VERIFICATION

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.904 \text{ S/m}$ ;  $\epsilon_r = 42.271$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-22-2016; Ambient Temp: 23.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(6.96, 6.96, 6.96); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.29 W/kg

**SAR(1 g) = 1.54 W/kg**

Deviation(1 g) = -6.33%



0 dB = 1.80 W/kg = 2.55 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.874 \text{ S/m}$ ;  $\epsilon_r = 39.825$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-20-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.61 W/kg

**SAR(1 g) = 1.74 W/kg**

Deviation(1 g) = -6.65%



0 dB = 2.33 W/kg = 3.67 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750$  MHz;  $\sigma = 1.379$  S/m;  $\epsilon_r = 40.732$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 5.94 W/kg

**SAR(1 g) = 3.35 W/kg**

Deviation(1 g) = -7.46%



0 dB = 5.01 W/kg = 7.00 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080**


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: 1900 Head Medium parameters used (interpolated):  
 $f = 1900 \text{ MHz}$ ;  $\sigma = 1.452 \text{ S/m}$ ;  $\epsilon_r = 39.274$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3287; ConvF(5.27, 5.27, 5.27); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification at 20.0 dBm (100 mW)

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Peak SAR (extrapolated) = 7.46 W/kg  
**SAR(1 g) = 4.03 W/kg**  
Deviation(1 g) = 2.54%



0 dB = 5.11 W/kg = 7.08 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450$  MHz;  $\sigma = 1.873$  S/m;  $\epsilon_r = 38.115$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-22-2016; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3213; ConvF(4.58, 4.58, 4.58); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.9 W/kg

**SAR(1 g) = 5.16 W/kg**

Deviation(1 g) = -2.27%



0 dB = 6.80 W/kg = 8.33 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Head Medium parameters used:

$f = 2600$  MHz;  $\sigma = 2.053$  S/m;  $\epsilon_r = 37.509$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-27-2016; Ambient Temp: 21.0°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(7.08, 7.08, 7.08); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2600 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.9 W/kg

**SAR(1 g) = 5.96 W/kg**

Deviation(1 g) = 5.86%



0 dB = 10.2 W/kg = 10.09 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.963 \text{ S/m}$ ;  $\epsilon_r = 54.221$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-22-2016; Ambient Temp: 21.1°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(6.19, 6.19, 6.19); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.46 W/kg

**SAR(1 g) = 1.71 W/kg**

Deviation(1 g) = -0.12%



0 dB = 1.98 W/kg = 2.97 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 1.004 \text{ S/m}$ ;  $\epsilon_r = 55.173$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-19-2016; Ambient Temp: 21.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3319; ConvF(6.04, 6.04, 6.04); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.99 W/kg

**SAR(1 g) = 2.03 W/kg**

Deviation(1 g) = 6.06%



0 dB = 2.38 W/kg = 3.77 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$  MHz;  $\sigma = 1.503$  S/m;  $\epsilon_r = 51.815$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 22.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 8/22/2016

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.82 W/kg

**SAR(1 g) = 3.87 W/kg**

Deviation(1 g) = 3.75%



0 dB = 4.78 W/kg = 6.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$  MHz;  $\sigma = 1.509$  S/m;  $\epsilon_r = 51.447$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 8/22/2016

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.31 W/kg

**SAR(1 g) = 3.61 W/kg**

Deviation(1 g) = -2.70%



0 dB = 4.46 W/kg = 6.49 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149**


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: 1900 Body Medium parameters used (interpolated):  
 $f = 1900 \text{ MHz}$ ;  $\sigma = 1.573 \text{ S/m}$ ;  $\epsilon_r = 53.153$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-26-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(7.47, 7.47, 7.47); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification at 20.0 dBm (100 mW)

**Area Scan (7x11x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Peak SAR (extrapolated) = 7.26 W/kg  
**SAR(1 g) = 3.96 W/kg**  
Deviation(1 g) = -0.75%



0 dB = 6.13 W/kg = 7.87 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 2.032$  S/m;  $\epsilon_r = 51.985$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-23-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.3 W/kg

**SAR(1 g) = 5.28 W/kg**

Deviation(1 g) = 3.94%



0 dB = 6.96 W/kg = 8.43 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 1.962$  S/m;  $\epsilon_r = 51.891$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-27-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.6 W/kg

**SAR(1 g) = 5.19 W/kg**

Deviation(1 g) = 2.17%



0 dB = 8.53 W/kg = 9.31 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600$  MHz;  $\sigma = 2.171$  S/m;  $\epsilon_r = 51.333$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-27-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2600 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.6 W/kg

**SAR(1 g) = 5.82 W/kg**

Deviation(1 g) = 7.38%



0 dB = 9.96 W/kg = 9.98 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 2.001$  S/m;  $\epsilon_r = 51.684$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-02-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.9 W/kg

**SAR(10 g) = 2.38 W/kg**

Deviation(10 g) = 0.00%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600$  MHz;  $\sigma = 2.198$  S/m;  $\epsilon_r = 51.046$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-02-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2600 MHz System Verification at 20.0 dBm (100 mW)

**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.7 W/kg

**SAR(10 g) = 2.48 W/kg**

Deviation(10 g) = 1.22%

