



SAR EVALUATION REPORT

Applicant Name:
 LG Electronics MobileComm U.S.A., Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 12/01/14 - 12/15/14
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 0Y1412012171.ZNF

FCC ID: ZNFLS996

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A., INC.

DUT Type: Portable Handset
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §2.1093
Model(s): LS996, LGLS996, LG-LS996
Permissive Change(s): See FCC Change Document
Date of Original Certification: 11/26/2014

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	CDMA/EVDO BC10 (\$90S)	817.90 - 823.10 MHz	0.52	0.70	0.62
PCE	CDMA/EVDO BC0 (\$22H)	824.70 - 848.31 MHz	0.49	0.57	0.57
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.67	0.72	0.90
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.39	0.47	0.61
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.38	0.41	0.48
PCE	UMTS 850	826.40 - 846.60 MHz	0.38	0.45	0.45
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.57	0.54	0.65
PCE	LTE Band 12	699.7 - 715.3 MHz	0.24	0.36	0.36
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.41	0.57	0.57
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.40	0.51	0.51
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.44	0.74	0.74
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.69	0.43	0.70
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.64	< 0.1	0.15
NII	5.2 GHz WLAN	5180 - 5240 MHz	0.67	0.18	
NII	5.3 GHz WLAN	5260 - 5320 MHz	0.63	0.18	
NII	5.5 GHz WLAN	5500 - 5700 MHz	0.75	0.28	
NII	5.8 GHz WLAN	5745 - 5825 MHz	0.72	0.27	0.37
DSS/DTS	Bluetooth	2402 - 2480 MHz		N/A	
Simultaneous SAR per KDB 690783 D01v01r03:			1.42	1.02	1.12

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.9 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
 President





The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: ZNFLS996		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 1 of 77

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	9
3	INTRODUCTION	10
4	DOSIMETRIC ASSESSMENT	11
5	DEFINITION OF REFERENCE POINTS	12
6	TEST CONFIGURATION POSITIONS FOR HANDSETS	13
7	RF EXPOSURE LIMITS	17
8	FCC MEASUREMENT PROCEDURES	18
9	RF CONDUCTED POWERS	25
10	SYSTEM VERIFICATION	47
11	SAR DATA SUMMARY	50
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS	63
13	SAR MEASUREMENT VARIABILITY	71
14	EQUIPMENT LIST	72
15	MEASUREMENT UNCERTAINTIES	73
16	CONCLUSION	75
17	REFERENCES	76
APPENDIX A:	SAR TEST PLOTS	
APPENDIX B:	SAR DIPOLE VERIFICATION PLOTS	
APPENDIX C:	PROBE AND DIPOLE CALIBRATION CERTIFICATES	
APPENDIX D:	SAR TISSUE SPECIFICATIONS	
APPENDIX E:	SAR SYSTEM VALIDATION	
APPENDIX F:	SAR TEST SETUP PHOTOGRAPHS AND ANTENNA LOCATION	

FCC ID: ZNFLS996	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 2 of 77	

1 DEVICE UNDER TEST

1.1 Device Overview



Band & Mode	Operating Modes	Tx Frequency
CDMA/EVDO BC10 (§90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (§22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
5.8 GHz WLAN	Voice/Data	5745 - 5825 MHz
5.2 GHz WLAN	Voice/Data	5180 - 5240 MHz
5.3 GHz WLAN	Voice/Data	5260 - 5320 MHz
5.5 GHz WLAN	Voice/Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

Mode / Band		Modulated Average (dBm)
CDMA/EVDO BC10 (§90S)	Maximum	25.4
	Nominal	24.9
CDMA/EVDO BC0 (§22H)	Maximum	24.7
	Nominal	24.2
PCS CDMA/EVDO	Maximum	24.7
	Nominal	24.2



Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slot	1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.2	33.2	31.2	27.7	27.7
	Nominal	32.7	32.7	30.7	27.2	27.2
GSM/GPRS/EDGE 1900	Maximum	30.7	30.7	28.7	26.7	26.7
	Nominal	30.2	30.2	28.2	26.2	26.2

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 3 of 77

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6
UMTS Band 5 (850 MHz)	Maximum	23.7	23.7	23.7
	Nominal	23.2	23.2	23.2
UMTS Band 2 (1900 MHz)	Maximum	23.7	23.7	23.7
	Nominal	23.2	23.2	23.2

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	23.7
	Nominal	23.2
LTE Band 5 (Cell)	Maximum	23.7
	Nominal	23.2
LTE Band 26 (Cell)	Maximum	24.2
	Nominal	23.7
LTE Band 4 (AWS)	Maximum	24.2
	Nominal	23.7
LTE Band 2 (PCS)	Maximum	23.7
	Nominal	23.2
LTE Band 25 (PCS)	Maximum	24.2
	Nominal	23.7
LTE Band 41	Maximum	24.2
	Nominal	23.7

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	14.5
	Nominal	13.5
IEEE 802.11g (2.4 GHz)	Maximum	13.5
	Nominal	12.5
IEEE 802.11n (2.4 GHz)	Maximum	13.5
	Nominal	12.5
IEEE 802.11ac (2.4 GHz)	Maximum	12.5
	Nominal	11.5
IEEE 802.11a (5 GHz)	Maximum	14.5
	Nominal	13.5
IEEE 802.11n (5 GHz 20 MHz)	Maximum	13.5
	Nominal	12.5
IEEE 802.11n (5 GHz 40 MHz)	Maximum	12.5
	Nominal	11.5
IEEE 802.11ac (5 GHz)	Maximum	12.5
	Nominal	11.5
Bluetooth (1Mbps)	Maximum	8.5
	Nominal	7.5
Bluetooth (2Mbps)	Maximum	5.0
	Nominal	4.0
Bluetooth (3Mbps)	Maximum	5.0
	Nominal	4.0
Bluetooth LE	Maximum	6.0
	Nominal	5.0

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 4 of 77

1.3 DUT Antenna Locations

The overall dimensions of this device are $> 9 \times 5$ cm. The overall diagonal dimension of the device is < 160 mm and the diagonal display is < 150 mm. A diagram showing the location of the device antennas can be found in Appendix F. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filing

**Table 1-1
Mobile Hotspot Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
EVDO BC10 (\$90S)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC0 (\$22H)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	Yes
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 41	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
5.8 GHz WLAN	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, 5.2-5.7 GHz WLAN operations are disabled. Therefore 5.2-5.7 GHz WLAN operations are not considered in this section.

1.4 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device. The NFC antenna location diagram can be found in appendix F.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



**Figure 1-1
Simultaneous Transmission Paths**

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

FCC ID: ZNFLS996	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 5 of 77

**Table 1-2
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router
1	1x CDMA voice + 2.4 GHz WI-FI	Yes	Yes	N/A
2	1x CDMA voice + 5 GHz WI-FI	Yes	Yes	N/A
3	1x CDMA voice + 2.4 GHz Bluetooth	N/A	Yes	N/A
4	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A
5	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A
6	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A
7	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes
8	UMTS + 5 GHz WI-FI	Yes	Yes	Yes
9	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A
10	LTE + 2.4 GHz WI-FI	Yes*	Yes*	Yes
11	LTE + 5 GHz WI-FI	Yes*	Yes*	Yes
12	LTE + 2.4 GHz Bluetooth	N/A	Yes*	N/A
13	CDMA/EVDO data + 2.4 GHz WI-FI	Yes*	Yes*	Yes
14	CDMA/EVDO data + 5 GHz WI-FI	Yes*	Yes*	Yes
15	CDMA/EVDO data + 2.4 GHz Bluetooth	N/A	Yes*	N/A
16	GPRS/EDGE + 2.4 GHz WI-FI	Yes*	Yes*	Yes
17	GPRS/EDGE + 5 GHz WI-FI	Yes*	Yes*	Yes
18	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	Yes*	N/A

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- (*) = for VOIP applications possibly used by the end-user
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- 5 GHz Wireless Router is only supported for the 5.8 GHz Band by S/W, therefore 5.2-5.7 GHz Bands were not evaluated for wireless router conditions.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Simultaneous transmission scenarios involving WIFI direct are specified above.
- 2.4 GHz WIFI supports Hotspot and WIFI-Direct(GO/GC).
- 5.8 GHz WIFI supports Hotspot and WIFI-Direct(GO/GC).

1.6 SAR Test Exclusions Applied



(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using 5.2-5.7 GHz WIFI, only 2.4 GHz and 5.8 GHz WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v01.

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; [(7/8)* √2.480] = 1.4 < 3.0.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 6 of 77

Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 20 MHz and 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only. IEEE 802.11n was not evaluated for SAR since the average output power of 20 MHz and 40 MHz bandwidths was not more than 0.25 dB higher than the average output power of IEEE 802.11a.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 1 Tx antenna output
- d) 256 QAM is supported
- e) No new 5 GHz channels

(B) Licensed Transmitter(s)

CDMA 1X Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg.

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

This Device additionally supports LTE B2. LTE Band 25 and LTE Band 2 share the same transmission path. LTE Band 2 was not evaluated for SAR since the supported frequency range falls within the LTE Band 25 supported frequency range and the Band 2 target power was less than the Band 25 target power.



This Device additionally supports LTE B5. LTE Band 26 and LTE Band 5 share the same transmission path. LTE Band 5 was not evaluated for SAR since the supported frequency range falls within the LTE Band 26 supported frequency range and the Band 5 target power was less than the Band 26 target power.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

This device supports inter-band LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC Guidance, LTE CA SAR was not needed for testing since the data sent by uplink on uplink physical channels does not change between Rel 8 and Rel 10.

1.7 SAR Test Positioning Based on Form Factor

Due to the embowed design of the device, Body SAR was configured per FCC Guidance. For Back side, the device was tested at a distance of 8 mm at the center of the device. For Front side, the device was tested at a distance of 8 mm from the outer ends of the device. The remaining surface or edges within 25 mm of a Tx antenna were tested at a distance of 10 mm.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 7 of 77	

1.8 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.



1.9 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v02, D05v02r03, D05Av01, D06v01r01 (2G/3G/4G, Hotspot, and CDMA 2000 1x Advanced)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- April 2013 TCB Workshop Notes (IEEE 802.11ac)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.10 Device Serial Numbers

Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.



	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
CDMA/EVDO BC10 (\$90S)	089498624600002352	089498624600002352	089498624600002352
CDMA/EVDO BC0 (\$22H)	089498624600002352	089498624600002352	089498624600002352
PCS CDMA/EVDO	089498624600002352	089498624600002352	089498624600002352
GSM/GPRS/EDGE 850	089498624600002354	089498624600002353	089498624600002353
GSM/GPRS/EDGE 1900	089498624600002353	089498624600002353	089498624600002353
UMTS 850	089498624600002354	089498624600002353	089498624600002353
UMTS 1900	089498624600002353	089498624600002353	089498624600002353
LTE Band 12	089498624600002344	089498624600002344	089498624600002344
LTE Band 26 (Cell)	089498624600002344	089498624600002344	089498624600002344
LTE Band 4 (AWS)	089498624600002344	089498624600002344	089498624600002344
LTE Band 25 (PCS)	089498624600002345	089498624600002345	089498624600002345
LTE Band 41	089498624600002345	089498624600002345	089498624600002345
2.4 GHz WLAN	089498624600002355	089498624600002355	089498624600002355
5 GHz WLAN	089498624600002355	089498624600002355	089498624600002355

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 8 of 77

2

LTE INFORMATION

LTE Information						
FCC ID	ZNFLS996					
Form Factor	Portable Handset					
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)					
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)					
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)					
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)					
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)					
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)					
Channel Bandwidths	LTE Band 41 (2498.5 - 2687.5 MHz)					
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz					
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10, MHz					
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz					
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz					
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz					
Channel Numbers and Frequencies (MHz)	Low		Mid		High	
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz					
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)	
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)	
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)	
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)	
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)	
LTE Band 26 (Cell): 15 MHz	831.5 (26865)		836.5 (26915)		841.5 (26965)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)	
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)	
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)	
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	High-Mid	High	
	LTE Band 41: 5 MHz	2498.5 (39675)	2545.8 (40148)	2593 (40620)	2640.3 (41093)	2687.5 (41565)
	LTE Band 41: 10 MHz	2501 (39700)	2547 (40160)	2593 (40620)	2639 (41080)	2685 (41540)
	LTE Band 41: 15 MHz	2503.5 (39725)	2548.3 (40173)	2593 (40620)	2637.8 (41068)	2682.5 (41515)
	LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
	UE Category	6				
Modulations Supported in UL	QPSK, 16QAM					
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES					
A-MPR (Additional MPR) disabled for SAR Testing?	YES					
LTE Carrier Aggregation Possible Combinations	LTE B41 (PCC) + LTE B41 (SCC)					
LTE Carrier Aggregation Additional Information	20MHz (B41) + 20MHz (B41)					
	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink with a total maximum bandwidth of 20 MHz of the spectrum. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WIFI Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.					

FCC ID: ZNFLS996		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 9 of 77

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m^3)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 10 of 77

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASYS manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.





**Figure 4-1
Sample SAR Area
Scan**

**Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01***

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFLS996	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 11 of 77

5

DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom






Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 12 of 77

6 TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 13 of 77




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04_v01. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.






Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 14 of 77

that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.



For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC minitables that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04 v01r01DR04 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 15 of 77	

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFLS996		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 16 of 77	

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 17 of 77

8 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.



8.3 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

8.3.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices" v02, October 2007. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the "All Up" condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 18 of 77

**Table 8-1
Parameters for Max. Power for RC1**

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

**Table 8-2
Parameters for Max. Power for RC3**

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.3.2 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers were measured using SO75 with RC8 on the uplink and RC11 on the downlink per KDB Publication 941225 D02v02. Smart blanking was disabled for all measurements. The EUT was configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers were measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

Based on the maximum output power measured for 1x Advanced, SAR would have to be evaluated for 1x advanced if the maximum output for 1x Advanced is more than 0.25 dB higher than the maximum measured for 1x. Also, if the measured SAR in any 1x mode exposure conditions (head, body etc.) is larger than 1.2 W/kg, the highest of those configurations above 1.2 W/kg for each exposure condition in 1x Advanced has to be repeated. All measured SAR in 1x mode higher than 1.5 W/kg must be repeated for 1x Advanced.

8.3.3 Head SAR Measurements



SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

Head SAR was additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.3.5 for EVDO Rev. A configuration parameters.

8.3.4 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH_n) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCH_n) with FCH at full rate and SCH₀ enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up”

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 19 of 77

8.3.5 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots would be configured in the downlink for both Rev. 0 and Rev. A.

8.3.6 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 per KDB Publication 941225 D01 procedures for “1x Ev-Do data Devices”. SAR for Subtype 2 Physical layer configurations is not required for Rev. A when the maximum average output of each RF channels is less than that measured in Subtype 0/1 Physical layer configurations. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for the RF channels in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

SAR is not required for 1x RTT for Ev-Do devices that also support 1x RTT voice and/or data operations, when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0. Otherwise, CDMA “Body-SAR Measurement” procedures for “CDMA 2000 1x Handsets” were applied.

8.4 SAR Measurement Conditions for UMTS



8.4.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.4.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 20 of 77

3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”.

8.4.4 SAR Measurements for Handsets with Rel 5 HSDPA

Body SAR for HSDPA is not required for handsets with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of $\beta_c=9$ and $\beta_d=15$, and power offset parameters of $\Delta_{ACK} = \Delta_{NACK} = 5$ and $\Delta_{CQI}=2$ is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

Sub-Test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5



Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 8 \Leftrightarrow A_{HS} = \beta_{HS}/\beta_c = 30/15 \Leftrightarrow \beta_{HS} = 30/15 * \beta_c$.
 Note 2: For the HS-DPCCH power mask requirement test in clause 5.2.C, 5.7.A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ ($A_{HS} = 30/15$) with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ ($A_{HS} = 24/15$) with $\beta_{HS} = 24/15 * \beta_c$.
 Note 3: CM = 1 for $\beta_c/\beta_d=12/15$, $\beta_{HS}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Figure 8-1
Table C.10.1.4 of TS 234.121-1

8.4.5 SAR Measurements for Handsets with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under “Release 6 HSPA data devices”

Head SAR for VOIP operations under HSPA is not required when maximum average output of each RF channel with HSPA is less than 0.25 dB higher than as measured using 12.2 kbps RMC. Otherwise SAR is measured using same HSPA configuration as used for body SAR.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 21 of 77

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{d1}: 47/15$ $\beta_{d2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{15} = \beta_{15}/\beta_c = 30/15 \Leftrightarrow \beta_{15} = 30/15 * \beta_c$.
Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{15}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.
Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

8.5 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.



8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 22 of 77

- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

8.5.5 TDD

TDD LTE was tested using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using normal cyclic prefix only and special subframe configuration 6. Due to equipment setup issues with extended cyclic prefix as a result of test samples configured for normal cyclic prefix, SAR tests were performed at maximum output power and worst-case transmission duty factor in normal cyclic prefix. Results were then scaled to the duty factor required for extended cyclic prefix listed in 3GPP TS 36.211 Section 4. The cyclic prefix scaling factor for LTE Band 41 was calculated by dividing the extended cyclic prefix duty factor by the normal cyclic prefix duty factor. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using normal cyclic prefix is 0.629. The duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

8.5.6 Carrier Aggregation



LTE Carrier Aggregation (CA) measurements were made in accordance to 3GPP TS 36.521-1 V10.4.0 (2012-12). The RRC connection is only handled by one cell, the Primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds the Secondary component carrier (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. Additional output powers were measured using two carriers in the downlink for the release 8 configurations with the highest output power among all channels, RB configurations and bandwidths for each uplink band. Per FCC Guidance, no SAR measurements were required.

8.6 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n/ac transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 23 of 77	

8.6.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n/ac modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power than the default channels, these "required channels" were considered instead of the default channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was higher than 0.25 dB or more than the 802.11a mode. 802.11ac SAR was evaluated for highest 802.11a configuration in each 5 GHz band and each exposure condition. 802.11ac modes were additionally evaluated for SAR if the output power for the respective mode was more than 0.25 dB higher than powers of 802.11a modes.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 24 of 77	

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	25.14	25.20	25.23	25.26	25.21	25.21	25.15
Cellular	1013	22H	824.7	24.48	24.47	24.46	24.49	24.45	24.49	24.45
	384	22H	836.52	24.39	24.45	24.40	24.52	24.54	24.62	24.61
	777	22H	848.31	24.59	24.61	24.59	24.58	24.62	24.65	24.62
PCS	25	24E	1851.25	24.41	24.38	24.40	24.50	24.54	24.58	24.53
	600	24E	1880	24.34	24.33	24.36	24.61	24.67	24.57	24.51
	1175	24E	1908.75	24.31	24.34	24.30	24.38	24.38	24.49	24.43

Note:

1. RC1 is only applicable for IS-95 compatibility.
2. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v05 4.1.6, only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.

Per KDB Publication 941225 D01v02:

1. Head SAR was tested with SO55 RC3. SO55 RC1 was not required since the average output power was not more than 0.25 dB than the SO55 RC3 powers. Head SAR was additionally evaluated with EVDO Rev. A to determine compliance for held-to-ear VOIP operations.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. Ev-Do and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers.
3. Hotspot SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. If the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, then Rev. A SAR is not required. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for that RF channel in Rev. 0. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0

Per KDB Publication 941225 D02v02:

1. CDMA 1X Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg. See Section 8.3.2 for 1x Advanced test set up.



Figure 9-1
Power Measurement Setup

FCC ID: ZNFLS996	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 25 of 77

9.2 GSM Conducted Powers

Maximum Burst-Averaged Output Power						
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	32.95	33.03	31.11	27.63	27.51
	190	33.11	33.18	31.19	27.65	27.58
	251	32.81	32.88	30.82	27.53	27.47
GSM 1900	512	30.10	30.15	28.26	26.43	26.36
	661	29.92	30.01	28.15	26.34	26.28
	810	30.37	30.42	28.45	26.40	26.30
Calculated Maximum Frame-Averaged Output Power						
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	23.92	24.00	25.09	18.60	21.49
	190	24.08	24.15	25.17	18.62	21.56
	251	23.78	23.85	24.80	18.50	21.45
GSM 1900	512	21.07	21.12	22.24	17.40	20.34
	661	20.89	20.98	22.13	17.31	20.26
	810	21.34	21.39	22.43	17.37	20.28
GSM 850	Frame	23.67	23.67	24.68	18.17	21.18
GSM 1900	Avg.Targets:	21.17	21.17	22.18	17.17	20.18

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- Per October 2013 TCB Workshop notes the source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B

GPRS Multislot class: 10 (Max 2 Tx uplink slots)

EDGE Multislot class: 10 (Max 2 Tx uplink slots)

DTM Multislot Class: N/A




Figure 9-2
Power Measurement Setup

FCC ID: ZNFLS996	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 26 of 77

9.3 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	23.69	23.67	23.66	23.70	23.66	23.62	-
99		12.2 kbps AMR	23.67	23.66	23.68	23.63	23.60	23.51	-
6	HSDPA	Subtest 1	23.64	23.59	23.67	23.20	23.20	23.21	0
6		Subtest 2	23.65	23.66	23.70	23.31	23.32	23.34	0
6		Subtest 3	23.19	23.10	23.19	22.83	22.71	22.75	0.5
6		Subtest 4	23.19	23.16	23.12	22.75	22.72	22.84	0.5
6	HSPA	Subtest 1	21.53	21.83	22.00	21.70	21.40	21.57	0
6		Subtest 2	21.57	21.53	21.65	21.26	21.27	21.43	2
6		Subtest 3	21.46	21.49	21.66	21.20	21.14	21.19	1
6		Subtest 4	22.62	22.63	22.67	22.30	22.34	22.38	2
6		Subtest 5	23.61	23.55	22.62	23.29	23.26	23.31	0



UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



Figure 9-3
Power Measurement Setup

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 27 of 77	

9.4 LTE Conducted Powers

9.4.1 LTE Band 12



Table 9-1
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	707.5	23095	10	QPSK	1	0	23.61	0	0
	707.5	23095	10	QPSK	1	25	23.49	0	0
	707.5	23095	10	QPSK	1	49	23.32	0	0
	707.5	23095	10	QPSK	25	0	22.50	0-1	1
	707.5	23095	10	QPSK	25	12	22.65	0-1	1
	707.5	23095	10	QPSK	25	25	22.55	0-1	1
	707.5	23095	10	QPSK	50	0	22.56	0-1	1
	707.5	23095	10	16QAM	1	0	22.56	0-1	1
	707.5	23095	10	16QAM	1	25	22.55	0-1	1
	707.5	23095	10	16QAM	1	49	22.61	0-1	1
	707.5	23095	10	16QAM	25	0	21.54	0-2	2
	707.5	23095	10	16QAM	25	12	21.58	0-2	2
	707.5	23095	10	16QAM	25	25	21.47	0-2	2
	707.5	23095	10	16QAM	50	0	21.46	0-2	2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-2
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	701.5	23035	5	QPSK	1	0	23.41	0	0	
	701.5	23035	5	QPSK	1	12	23.32	0	0	
	701.5	23035	5	QPSK	1	24	23.26	0	0	
	701.5	23035	5	QPSK	12	0	22.35	0-1	1	
	701.5	23035	5	QPSK	12	6	22.37	0-1	1	
	701.5	23035	5	QPSK	12	13	22.35	0-1	1	
	701.5	23035	5	QPSK	25	0	22.53	0-1	1	
	701.5	23035	5	16-QAM	1	0	22.30	0-1	1	
	701.5	23035	5	16-QAM	1	12	22.47	0-1	1	
	701.5	23035	5	16-QAM	1	24	22.42	0-1	1	
	701.5	23035	5	16-QAM	12	0	21.48	0-2	2	
	701.5	23035	5	16-QAM	12	6	21.21	0-2	2	
	701.5	23035	5	16-QAM	12	13	21.27	0-2	2	
	701.5	23035	5	16-QAM	25	0	21.10	0-2	2	
	Mid	707.5	23095	5	QPSK	1	0	23.63	0	0
		707.5	23095	5	QPSK	1	12	23.62	0	0
		707.5	23095	5	QPSK	1	24	23.42	0	0
		707.5	23095	5	QPSK	12	0	22.44	0-1	1
707.5		23095	5	QPSK	12	6	22.43	0-1	1	
707.5		23095	5	QPSK	12	13	22.66	0-1	1	
707.5		23095	5	QPSK	25	0	22.44	0-1	1	
707.5		23095	5	16-QAM	1	0	22.46	0-1	1	
707.5		23095	5	16-QAM	1	12	22.48	0-1	1	
707.5		23095	5	16-QAM	1	24	22.49	0-1	1	
707.5		23095	5	16-QAM	12	0	21.45	0-2	2	
707.5		23095	5	16-QAM	12	6	21.60	0-2	2	
707.5		23095	5	16-QAM	12	13	21.57	0-2	2	
707.5		23095	5	16-QAM	25	0	21.42	0-2	2	
High		713.5	23155	5	QPSK	1	0	23.24	0	0
		713.5	23155	5	QPSK	1	12	23.11	0	0
		713.5	23155	5	QPSK	1	24	23.46	0	0
		713.5	23155	5	QPSK	12	0	22.18	0-1	1
	713.5	23155	5	QPSK	12	6	22.36	0-1	1	
	713.5	23155	5	QPSK	12	13	22.29	0-1	1	
	713.5	23155	5	QPSK	25	0	22.28	0-1	1	
	713.5	23155	5	16-QAM	1	0	22.64	0-1	1	
	713.5	23155	5	16-QAM	1	12	22.65	0-1	1	
	713.5	23155	5	16-QAM	1	24	22.64	0-1	1	
	713.5	23155	5	16-QAM	12	0	21.24	0-2	2	
	713.5	23155	5	16-QAM	12	6	21.17	0-2	2	
	713.5	23155	5	16-QAM	12	13	21.26	0-2	2	
	713.5	23155	5	16-QAM	25	0	21.11	0-2	2	

FCC ID: ZNFLS996		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 28 of 77

**Table 9-3
LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	700.5	23025	3	QPSK	1	0	23.21	0	0	
	700.5	23025	3	QPSK	1	7	23.13	0	0	
	700.5	23025	3	QPSK	1	14	22.99	0	0	
	700.5	23025	3	QPSK	8	0	22.25	0-1	1	
	700.5	23025	3	QPSK	8	4	22.08	0-1	1	
	700.5	23025	3	QPSK	8	7	22.06	0-1	1	
	700.5	23025	3	QPSK	15	0	22.15	0-1	1	
	700.5	23025	3	16-QAM	1	0	22.19	0-1	1	
	700.5	23025	3	16-QAM	1	7	22.43	0-1	1	
	700.5	23025	3	16-QAM	1	14	22.11	0-1	1	
	700.5	23025	3	16-QAM	8	0	21.10	0-2	2	
	700.5	23025	3	16-QAM	8	4	21.26	0-2	2	
	700.5	23025	3	16-QAM	8	7	20.99	0-2	2	
	700.5	23025	3	16-QAM	15	0	21.09	0-2	2	
	Mid	707.5	23095	3	QPSK	1	0	23.30	0	0
		707.5	23095	3	QPSK	1	7	23.47	0	0
		707.5	23095	3	QPSK	1	14	23.28	0	0
		707.5	23095	3	QPSK	8	0	22.43	0-1	1
707.5		23095	3	QPSK	8	4	22.33	0-1	1	
707.5		23095	3	QPSK	8	7	22.51	0-1	1	
707.5		23095	3	QPSK	15	0	22.37	0-1	1	
707.5		23095	3	16-QAM	1	0	22.54	0-1	1	
707.5		23095	3	16-QAM	1	7	22.64	0-1	1	
707.5		23095	3	16-QAM	1	14	22.42	0-1	1	
707.5		23095	3	16-QAM	8	0	21.05	0-2	2	
707.5		23095	3	16-QAM	8	4	21.32	0-2	2	
707.5		23095	3	16-QAM	8	7	21.22	0-2	2	
707.5		23095	3	16-QAM	15	0	21.40	0-2	2	
High		714.5	23165	3	QPSK	1	0	22.99	0	0
		714.5	23165	3	QPSK	1	7	23.14	0	0
		714.5	23165	3	QPSK	1	14	23.12	0	0
		714.5	23165	3	QPSK	8	0	22.03	0-1	1
	714.5	23165	3	QPSK	8	4	22.02	0-1	1	
	714.5	23165	3	QPSK	8	7	22.02	0-1	1	
	714.5	23165	3	QPSK	15	0	22.16	0-1	1	
	714.5	23165	3	16-QAM	1	0	21.99	0-1	1	
	714.5	23165	3	16-QAM	1	7	22.00	0-1	1	
	714.5	23165	3	16-QAM	1	14	22.08	0-1	1	
	714.5	23165	3	16-QAM	8	0	20.84	0-2	2	
	714.5	23165	3	16-QAM	8	4	20.85	0-2	2	
	714.5	23165	3	16-QAM	8	7	20.77	0-2	2	
	714.5	23165	3	16-QAM	15	0	20.81	0-2	2	

**Table 9-4
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	699.7	23017	1.4	QPSK	1	0	23.19	0	0	
	699.7	23017	1.4	QPSK	1	2	23.25	0	0	
	699.7	23017	1.4	QPSK	1	5	23.36	0	0	
	699.7	23017	1.4	QPSK	3	0	23.38	0	0	
	699.7	23017	1.4	QPSK	3	2	23.22	0	0	
	699.7	23017	1.4	QPSK	3	3	23.36	0	0	
	699.7	23017	1.4	QPSK	6	0	22.34	0-1	1	
	699.7	23017	1.4	16-QAM	1	0	21.93	0-1	1	
	699.7	23017	1.4	16-QAM	1	2	22.10	0-1	1	
	699.7	23017	1.4	16-QAM	1	5	22.10	0-1	1	
	699.7	23017	1.4	16-QAM	3	0	22.17	0-1	1	
	699.7	23017	1.4	16-QAM	3	2	22.06	0-1	1	
	699.7	23017	1.4	16-QAM	3	3	22.09	0-1	1	
	699.7	23017	1.4	16-QAM	6	0	21.22	0-2	2	
	Mid	707.5	23095	1.4	QPSK	1	0	23.30	0	0
		707.5	23095	1.4	QPSK	1	2	23.41	0	0
		707.5	23095	1.4	QPSK	1	5	23.46	0	0
		707.5	23095	1.4	QPSK	3	0	23.52	0	0
707.5		23095	1.4	QPSK	3	2	23.52	0	0	
707.5		23095	1.4	QPSK	3	3	23.55	0	0	
707.5		23095	1.4	QPSK	6	0	22.68	0-1	1	
707.5		23095	1.4	16-QAM	1	0	22.25	0-1	1	
707.5		23095	1.4	16-QAM	1	2	22.32	0-1	1	
707.5		23095	1.4	16-QAM	1	5	22.41	0-1	1	
707.5		23095	1.4	16-QAM	3	0	22.44	0-1	1	
707.5		23095	1.4	16-QAM	3	2	22.40	0-1	1	
707.5		23095	1.4	16-QAM	3	3	22.46	0-1	1	
707.5		23095	1.4	16-QAM	6	0	21.29	0-2	2	
High		715.3	23173	1.4	QPSK	1	0	23.22	0	0
		715.3	23173	1.4	QPSK	1	2	23.23	0	0
		715.3	23173	1.4	QPSK	1	5	23.02	0	0
		715.3	23173	1.4	QPSK	3	0	23.26	0	0
	715.3	23173	1.4	QPSK	3	2	23.24	0	0	
	715.3	23173	1.4	QPSK	3	3	23.24	0	0	
	715.3	23173	1.4	QPSK	6	0	22.20	0-1	1	
	715.3	23173	1.4	16-QAM	1	0	21.95	0-1	1	
	715.3	23173	1.4	16-QAM	1	2	22.10	0-1	1	
	715.3	23173	1.4	16-QAM	1	5	22.16	0-1	1	
	715.3	23173	1.4	16-QAM	3	0	22.03	0-1	1	
	715.3	23173	1.4	16-QAM	3	2	22.10	0-1	1	
	715.3	23173	1.4	16-QAM	3	3	22.12	0-1	1	
	715.3	23173	1.4	16-QAM	6	0	21.02	0-2	2	

9.4.2 LTE Band 26 (Cell)

Table 9-5
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
N/A	836.5	26915	15	QPSK	1	0	24.18	0	0
	836.5	26915	15	QPSK	1	36	24.16	0	0
	836.5	26915	15	QPSK	1	74	24.17	0	0
	836.5	26915	15	QPSK	36	0	23.13	0-1	1
	836.5	26915	15	QPSK	36	18	23.09	0-1	1
	836.5	26915	15	QPSK	36	37	23.01	0-1	1
	836.5	26915	15	QPSK	75	0	23.05	0-1	1
	836.5	26915	15	16QAM	1	0	23.18	0-1	1
	836.5	26915	15	16QAM	1	36	23.19	0-1	1
	836.5	26915	15	16QAM	1	74	23.17	0-1	1
	836.5	26915	15	16QAM	36	0	22.18	0-2	2
	836.5	26915	15	16QAM	36	18	22.20	0-2	2
	836.5	26915	15	16QAM	36	37	22.09	0-2	2
	836.5	26915	15	16QAM	75	0	22.12	0-2	2

Note: LTE Band 26 at 15 MHz bandwidth is only supported for FCC rule part 22H. There are not three non-overlapping channels within FCC Rule Part 22H. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	819	26740	10	QPSK	1	0	23.93	0	0	
	819	26740	10	QPSK	1	25	24.04	0	0	
	819	26740	10	QPSK	1	49	24.00	0	0	
	819	26740	10	QPSK	25	0	22.95	0-1	1	
	819	26740	10	QPSK	25	12	22.78	0-1	1	
	819	26740	10	QPSK	25	25	22.88	0-1	1	
	819	26740	10	QPSK	50	0	22.86	0-1	1	
	819	26740	10	16QAM	1	0	22.95	0-1	1	
	819	26740	10	16QAM	1	25	22.99	0-1	1	
	819	26740	10	16QAM	1	49	23.04	0-1	1	
	819	26740	10	16QAM	25	0	22.10	0-2	2	
	819	26740	10	16QAM	25	12	22.04	0-2	2	
	819	26740	10	16QAM	25	25	21.79	0-2	2	
	819	26740	10	16QAM	50	0	21.89	0-2	2	
	Mid	831.5	26865	10	QPSK	1	0	24.11	0	0
		831.5	26865	10	QPSK	1	25	24.14	0	0
831.5		26865	10	QPSK	1	49	23.87	0	0	
831.5		26865	10	QPSK	25	0	22.83	0-1	1	
831.5		26865	10	QPSK	25	12	22.88	0-1	1	
831.5		26865	10	QPSK	25	25	22.73	0-1	1	
831.5		26865	10	QPSK	50	0	22.80	0-1	1	
831.5		26865	10	16QAM	1	0	23.00	0-1	1	
831.5		26865	10	16QAM	1	25	23.15	0-1	1	
831.5		26865	10	16QAM	1	49	22.80	0-1	1	
831.5		26865	10	16QAM	25	0	21.97	0-2	2	
831.5		26865	10	16QAM	25	12	22.09	0-2	2	
831.5		26865	10	16QAM	25	25	21.97	0-2	2	
831.5		26865	10	16QAM	50	0	21.94	0-2	2	
High		844	26990	10	QPSK	1	0	23.97	0	0
		844	26990	10	QPSK	1	25	24.12	0	0
	844	26990	10	QPSK	1	49	23.79	0	0	
	844	26990	10	QPSK	25	0	22.93	0-1	1	
	844	26990	10	QPSK	25	12	22.95	0-1	1	
	844	26990	10	QPSK	25	25	22.87	0-1	1	
	844	26990	10	QPSK	50	0	23.00	0-1	1	
	844	26990	10	16QAM	1	0	23.01	0-1	1	
	844	26990	10	16QAM	1	25	22.95	0-1	1	
	844	26990	10	16QAM	1	49	22.99	0-1	1	
	844	26990	10	16QAM	25	0	21.06	0-2	2	
	844	26990	10	16QAM	25	12	22.14	0-2	2	
	844	26990	10	16QAM	25	25	22.12	0-2	2	
	844	26990	10	16QAM	50	0	22.04	0-2	2	



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 30 of 77

Table 9-7
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	816.5	26715	5	QPSK	1	0	23.96	0	0	
	816.5	26715	5	QPSK	1	12	23.76	0	0	
	816.5	26715	5	QPSK	1	24	24.02	0	0	
	816.5	26715	5	QPSK	12	0	22.98	0-1	1	
	816.5	26715	5	QPSK	12	6	22.76	0-1	1	
	816.5	26715	5	QPSK	12	13	22.86	0-1	1	
	816.5	26715	5	QPSK	25	0	22.93	0-1	1	
	816.5	26715	5	16-QAM	1	0	22.83	0-1	1	
	816.5	26715	5	16-QAM	1	12	22.75	0-1	1	
	816.5	26715	5	16-QAM	1	24	22.83	0-1	1	
	816.5	26715	5	16-QAM	12	0	21.72	0-2	2	
	816.5	26715	5	16-QAM	12	6	21.85	0-2	2	
	816.5	26715	5	16-QAM	12	13	21.95	0-2	2	
	816.5	26715	5	16-QAM	25	0	21.74	0-2	2	
	831.5	26865	5	QPSK	1	0	23.77	0	0	
	831.5	26865	5	QPSK	1	12	23.81	0	0	
	831.5	26865	5	QPSK	1	24	24.01	0	0	
	831.5	26865	5	QPSK	12	0	22.99	0-1	1	
831.5	26865	5	QPSK	12	6	23.01	0-1	1		
831.5	26865	5	QPSK	12	13	22.93	0-1	1		
831.5	26865	5	QPSK	25	0	23.03	0-1	1		
831.5	26865	5	16-QAM	1	0	22.93	0-1	1		
831.5	26865	5	16-QAM	1	12	22.74	0-1	1		
831.5	26865	5	16-QAM	1	24	23.10	0-1	1		
831.5	26865	5	16-QAM	12	0	22.03	0-2	2		
831.5	26865	5	16-QAM	12	6	21.93	0-2	2		
831.5	26865	5	16-QAM	12	13	22.05	0-2	2		
831.5	26865	5	16-QAM	25	0	22.12	0-2	2		
Mid	846.5	27015	5	QPSK	1	0	23.89	0	0	
	846.5	27015	5	QPSK	1	12	24.14	0	0	
	846.5	27015	5	QPSK	1	24	23.84	0	0	
	846.5	27015	5	QPSK	12	0	22.90	0-1	1	
	846.5	27015	5	QPSK	12	6	22.89	0-1	1	
	846.5	27015	5	QPSK	12	13	23.02	0-1	1	
	846.5	27015	5	QPSK	25	0	23.07	0-1	1	
	846.5	27015	5	16-QAM	1	0	22.91	0-1	1	
	846.5	27015	5	16-QAM	1	12	22.86	0-1	1	
	846.5	27015	5	16-QAM	1	24	22.89	0-1	1	
	846.5	27015	5	16-QAM	12	0	22.10	0-2	2	
	846.5	27015	5	16-QAM	12	6	22.15	0-2	2	
	846.5	27015	5	16-QAM	12	13	22.16	0-2	2	
	846.5	27015	5	16-QAM	25	0	22.11	0-2	2	
	High	816.5	26715	3	QPSK	1	0	23.88	0	0
		816.5	26705	3	QPSK	1	7	24.03	0	0
		816.5	26705	3	QPSK	1	14	23.87	0	0
		816.5	26705	3	QPSK	8	0	22.98	0-1	1
816.5		26705	3	QPSK	8	4	22.88	0-1	1	
816.5		26705	3	QPSK	8	7	22.79	0-1	1	
816.5		26705	3	QPSK	15	0	23.00	0-1	1	
816.5		26705	3	16-QAM	1	0	22.93	0-1	1	
816.5		26705	3	16-QAM	1	7	22.98	0-1	1	
816.5		26705	3	16-QAM	1	14	22.83	0-1	1	
816.5		26705	3	16-QAM	8	0	21.89	0-2	2	
816.5		26705	3	16-QAM	8	4	21.70	0-2	2	
816.5		26705	3	16-QAM	8	7	21.97	0-2	2	
816.5		26705	3	16-QAM	15	0	22.09	0-2	2	
831.5		26865	3	QPSK	1	0	23.91	0	0	
831.5		26865	3	QPSK	1	7	24.10	0	0	
831.5		26865	3	QPSK	1	14	24.19	0	0	
831.5		26865	3	QPSK	8	0	23.00	0-1	1	
831.5	26865	3	QPSK	8	4	23.12	0-1	1		
831.5	26865	3	QPSK	8	7	23.03	0-1	1		
831.5	26865	3	QPSK	15	0	23.06	0-1	1		
831.5	26865	3	16-QAM	1	0	22.90	0-1	1		
831.5	26865	3	16-QAM	1	7	22.98	0-1	1		
831.5	26865	3	16-QAM	1	14	22.79	0-1	1		
831.5	26865	3	16-QAM	8	0	22.03	0-2	2		
831.5	26865	3	16-QAM	8	4	21.92	0-2	2		
831.5	26865	3	16-QAM	8	7	22.01	0-2	2		
831.5	26865	3	16-QAM	15	0	21.72	0-2	2		
High	847.5	27025	3	QPSK	1	0	24.08	0	0	
	847.5	27025	3	QPSK	1	7	23.84	0	0	
	847.5	27025	3	QPSK	1	14	23.95	0	0	
	847.5	27025	3	QPSK	8	0	23.06	0-1	1	
	847.5	27025	3	QPSK	8	4	22.77	0-1	1	
	847.5	27025	3	QPSK	8	7	23.17	0-1	1	
	847.5	27025	3	QPSK	15	0	23.09	0-1	1	
	847.5	27025	3	16-QAM	1	0	23.18	0-1	1	
	847.5	27025	3	16-QAM	1	7	23.17	0-1	1	
	847.5	27025	3	16-QAM	1	14	22.95	0-1	1	
	847.5	27025	3	16-QAM	8	0	21.78	0-2	2	
	847.5	27025	3	16-QAM	8	4	22.08	0-2	2	
	847.5	27025	3	16-QAM	8	7	21.96	0-2	2	
	847.5	27025	3	16-QAM	15	0	21.99	0-2	2	

Table 9-8
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	816.5	26705	3	QPSK	1	0	23.88	0	0	
	816.5	26705	3	QPSK	1	7	24.03	0	0	
	816.5	26705	3	QPSK	1	14	23.87	0	0	
	816.5	26705	3	QPSK	8	0	22.98	0-1	1	
	816.5	26705	3	QPSK	8	4	22.88	0-1	1	
	816.5	26705	3	QPSK	8	7	22.79	0-1	1	
	816.5	26705	3	QPSK	15	0	23.00	0-1	1	
	816.5	26705	3	16-QAM	1	0	22.93	0-1	1	
	816.5	26705	3	16-QAM	1	7	22.98	0-1	1	
	816.5	26705	3	16-QAM	1	14	22.83	0-1	1	
	816.5	26705	3	16-QAM	8	0	21.89	0-2	2	
	816.5	26705	3	16-QAM	8	4	21.70	0-2	2	
	816.5	26705	3	16-QAM	8	7	21.97	0-2	2	
	816.5	26705	3	16-QAM	15	0	22.09	0-2	2	
	Mid	831.5	26865	3	QPSK	1	0	23.91	0	0
		831.5	26865	3	QPSK	1	7	24.10	0	0
		831.5	26865	3	QPSK	1	14	24.19	0	0
		831.5	26865	3	QPSK	8	0	23.00	0-1	1
831.5		26865	3	QPSK	8	4	23.12	0-1	1	
831.5		26865	3	QPSK	8	7	23.03	0-1	1	
831.5		26865	3	QPSK	15	0	23.06	0-1	1	
831.5		26865	3	16-QAM	1	0	22.90	0-1	1	
831.5		26865	3	16-QAM	1	7	22.98	0-1	1	
831.5		26865	3	16-QAM	1	14	22.79	0-1	1	
831.5		26865	3	16-QAM	8	0	22.03	0-2	2	
831.5		26865	3	16-QAM	8	4	21.92	0-2	2	
831.5		26865	3	16-QAM	8	7	22.01	0-2	2	
831.5		26865	3	16-QAM	15	0	21.72	0-2	2	
High		847.5	27025	3	QPSK	1	0	24.08	0	0
		847.5	27025	3	QPSK	1	7	23.84	0	0
		847.5	27025	3	QPSK	1	14	23.95	0	0
		847.5	27025	3	QPSK	8	0	23.06	0-1	1
	847.5	27025	3	QPSK	8	4	22.77	0-1	1	
	847.5	27025	3	QPSK	8	7	23.17	0-1	1	
	847.5	27025	3	QPSK	15	0	23.09	0-1	1	
	847.5	27025	3	16-QAM	1	0	23.18	0-1	1	
	847.5	27025	3	16-QAM	1	7	23.17	0-1	1	
	847.5	27025	3	16-QAM	1	14	22.95	0-1	1	
	847.5	27025	3	16-QAM	8	0	21.78	0-2	2	
	847.5	27025	3	16-QAM	8	4	22.08	0-2	2	
	847.5	27025	3	16-QAM	8	7	21.96	0-2	2	
	847.5	27025	3	16-QAM	15	0	21.99	0-2	2	

**Table 9-9
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	814.7	26697	1.4	QPSK	1	0	24.08	0	0
	814.7	26697	1.4	QPSK	1	2	23.79	0	0
	814.7	26697	1.4	QPSK	1	5	24.00	0	0
	814.7	26697	1.4	QPSK	3	0	23.86	0	0
	814.7	26697	1.4	QPSK	3	2	23.88	0	0
	814.7	26697	1.4	QPSK	3	3	23.75	0	0
	814.7	26697	1.4	QPSK	6	0	23.03	0-1	1
	814.7	26697	1.4	16-QAM	1	0	22.87	0-1	1
	814.7	26697	1.4	16-QAM	1	2	23.12	0-1	1
	814.7	26697	1.4	16-QAM	1	5	22.89	0-1	1
	814.7	26697	1.4	16-QAM	3	0	23.13	0-1	1
	814.7	26697	1.4	16-QAM	3	2	23.04	0-1	1
	814.7	26697	1.4	16-QAM	3	3	22.86	0-1	1
	814.7	26697	1.4	16-QAM	6	0	22.99	0-2	2
Mid	831.5	26865	1.4	QPSK	1	0	23.73	0	0
	831.5	26865	1.4	QPSK	1	2	23.72	0	0
	831.5	26865	1.4	QPSK	1	5	23.84	0	0
	831.5	26865	1.4	QPSK	3	0	23.88	0	0
	831.5	26865	1.4	QPSK	3	2	24.05	0	0
	831.5	26865	1.4	QPSK	3	3	24.15	0	0
	831.5	26865	1.4	QPSK	6	0	22.85	0-1	1
	831.5	26865	1.4	16-QAM	1	0	23.17	0-1	1
	831.5	26865	1.4	16-QAM	1	2	23.01	0-1	1
	831.5	26865	1.4	16-QAM	1	5	23.12	0-1	1
	831.5	26865	1.4	16-QAM	3	0	23.15	0-1	1
	831.5	26865	1.4	16-QAM	3	2	23.12	0-1	1
	831.5	26865	1.4	16-QAM	3	3	22.99	0-1	1
	831.5	26865	1.4	16-QAM	6	0	22.16	0-2	2
High	848.3	27033	1.4	QPSK	1	0	23.95	0	0
	848.3	27033	1.4	QPSK	1	2	24.00	0	0
	848.3	27033	1.4	QPSK	1	5	24.06	0	0
	848.3	27033	1.4	QPSK	3	0	24.15	0	0
	848.3	27033	1.4	QPSK	3	2	24.17	0	0
	848.3	27033	1.4	QPSK	3	3	24.12	0	0
	848.3	27033	1.4	QPSK	6	0	22.90	0-1	1
	848.3	27033	1.4	16-QAM	1	0	22.79	0-1	1
	848.3	27033	1.4	16-QAM	1	2	22.82	0-1	1
	848.3	27033	1.4	16-QAM	1	5	23.03	0-1	1
	848.3	27033	1.4	16-QAM	3	0	22.81	0-1	1
	848.3	27033	1.4	16-QAM	3	2	23.08	0-1	1
	848.3	27033	1.4	16-QAM	3	3	22.81	0-1	1
	848.3	27033	1.4	16-QAM	6	0	21.92	0-2	2

9.4.3 LTE Band 4 (AWS)

**Table 9-10
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	24.06	0	0
	1732.5	20175	20	QPSK	1	50	24.05	0	0
	1732.5	20175	20	QPSK	1	99	23.90	0	0
	1732.5	20175	20	QPSK	50	0	23.15	0-1	1
	1732.5	20175	20	QPSK	50	25	23.11	0-1	1
	1732.5	20175	20	QPSK	50	50	23.02	0-1	1
	1732.5	20175	20	QPSK	100	0	23.13	0-1	1
	1732.5	20175	20	16QAM	1	0	23.06	0-1	1
	1732.5	20175	20	16QAM	1	50	22.87	0-1	1
	1732.5	20175	20	16QAM	1	99	22.72	0-1	1
	1732.5	20175	20	16QAM	50	0	22.09	0-2	2
	1732.5	20175	20	16QAM	50	25	21.94	0-2	2
	1732.5	20175	20	16QAM	50	50	21.87	0-2	2
	1732.5	20175	20	16QAM	100	0	21.82	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-11
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	23.89	0	0
	1717.5	20025	15	QPSK	1	36	23.93	0	0
	1717.5	20025	15	QPSK	1	74	24.06	0	0
	1717.5	20025	15	QPSK	36	0	23.03	0-1	1
	1717.5	20025	15	QPSK	36	18	23.04	0-1	1
	1717.5	20025	15	QPSK	36	37	22.96	0-1	1
	1717.5	20025	15	QPSK	75	0	23.12	0-1	1
	1717.5	20025	15	16QAM	1	0	22.95	0-1	1
	1717.5	20025	15	16QAM	1	36	22.97	0-1	1
	1717.5	20025	15	16QAM	1	74	23.09	0-1	1
	1717.5	20025	15	16QAM	36	0	21.96	0-2	2
	1717.5	20025	15	16QAM	36	18	21.93	0-2	2
	1717.5	20025	15	16QAM	36	37	21.86	0-2	2
	1717.5	20025	15	16QAM	75	0	21.86	0-2	2
	1717.5	20025	15	16QAM	75	0	21.79	0-2	2
Mid	1732.5	20175	15	QPSK	1	0	24.04	0	0
	1732.5	20175	15	QPSK	1	36	23.86	0	0
	1732.5	20175	15	QPSK	1	74	23.74	0	0
	1732.5	20175	15	QPSK	36	0	23.00	0-1	1
	1732.5	20175	15	QPSK	36	18	22.93	0-1	1
	1732.5	20175	15	QPSK	36	37	22.97	0-1	1
	1732.5	20175	15	QPSK	75	0	22.95	0-1	1
	1732.5	20175	15	16QAM	1	0	22.96	0-1	1
	1732.5	20175	15	16QAM	1	36	22.70	0-1	1
	1732.5	20175	15	16QAM	1	74	22.72	0-1	1
	1732.5	20175	15	16QAM	36	0	21.82	0-2	2
	1732.5	20175	15	16QAM	36	18	21.75	0-2	2
	1732.5	20175	15	16QAM	36	37	21.73	0-2	2
	1732.5	20175	15	16QAM	75	0	21.79	0-2	2
	1732.5	20175	15	16QAM	75	0	21.72	0-2	2
High	1747.5	20325	15	QPSK	1	0	23.84	0	0
	1747.5	20325	15	QPSK	1	36	23.97	0	0
	1747.5	20325	15	QPSK	1	74	24.13	0	0
	1747.5	20325	15	QPSK	36	0	22.88	0-1	1
	1747.5	20325	15	QPSK	36	18	22.93	0-1	1
	1747.5	20325	15	QPSK	36	37	23.04	0-1	1
	1747.5	20325	15	QPSK	75	0	23.02	0-1	1
	1747.5	20325	15	16QAM	1	0	22.76	0-1	1
	1747.5	20325	15	16QAM	1	36	22.77	0-1	1
	1747.5	20325	15	16QAM	1	74	22.86	0-1	1
	1747.5	20325	15	16QAM	36	0	21.78	0-2	2
	1747.5	20325	15	16QAM	36	18	21.91	0-2	2
	1747.5	20325	15	16QAM	36	37	21.87	0-2	2
	1747.5	20325	15	16QAM	75	0	21.82	0-2	2
	1747.5	20325	15	16QAM	75	0	21.75	0-2	2

Table 9-12
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	23.70	0	0
	1715	20000	10	QPSK	1	25	23.81	0	0
	1715	20000	10	QPSK	1	49	23.54	0	0
	1715	20000	10	QPSK	25	0	22.82	0-1	1
	1715	20000	10	QPSK	25	12	22.91	0-1	1
	1715	20000	10	QPSK	25	25	22.87	0-1	1
	1715	20000	10	QPSK	50	0	22.88	0-1	1
	1715	20000	10	16QAM	1	0	22.71	0-1	1
	1715	20000	10	16QAM	1	25	22.83	0-1	1
	1715	20000	10	16QAM	1	49	22.71	0-1	1
	1715	20000	10	16QAM	25	0	21.74	0-2	2
	1715	20000	10	16QAM	25	12	21.84	0-2	2
	1715	20000	10	16QAM	25	25	21.80	0-2	2
	1715	20000	10	16QAM	50	0	21.81	0-2	2
	1715	20000	10	16QAM	50	0	21.74	0-2	2
Mid	1732.5	20175	10	QPSK	1	0	23.74	0	0
	1732.5	20175	10	QPSK	1	25	23.86	0	0
	1732.5	20175	10	QPSK	1	49	23.51	0	0
	1732.5	20175	10	QPSK	25	0	22.84	0-1	1
	1732.5	20175	10	QPSK	25	12	22.96	0-1	1
	1732.5	20175	10	QPSK	25	25	22.88	0-1	1
	1732.5	20175	10	QPSK	50	0	22.86	0-1	1
	1732.5	20175	10	16QAM	1	0	22.50	0-1	1
	1732.5	20175	10	16QAM	1	25	22.79	0-1	1
	1732.5	20175	10	16QAM	1	49	22.40	0-1	1
	1732.5	20175	10	16QAM	25	0	21.73	0-2	2
	1732.5	20175	10	16QAM	25	12	21.87	0-2	2
	1732.5	20175	10	16QAM	25	25	21.85	0-2	2
	1732.5	20175	10	16QAM	50	0	21.75	0-2	2
	1732.5	20175	10	16QAM	50	0	21.68	0-2	2
High	1750	20350	10	QPSK	1	0	23.70	0	0
	1750	20350	10	QPSK	1	25	23.86	0	0
	1750	20350	10	QPSK	1	49	23.73	0	0
	1750	20350	10	QPSK	25	0	22.95	0-1	1
	1750	20350	10	QPSK	25	12	23.01	0-1	1
	1750	20350	10	QPSK	25	25	22.88	0-1	1
	1750	20350	10	QPSK	50	0	22.88	0-1	1
	1750	20350	10	16QAM	1	0	22.42	0-1	1
	1750	20350	10	16QAM	1	25	22.74	0-1	1
	1750	20350	10	16QAM	1	49	22.42	0-1	1
	1750	20350	10	16QAM	25	0	21.77	0-2	2
	1750	20350	10	16QAM	25	12	21.90	0-2	2
	1750	20350	10	16QAM	25	25	21.72	0-2	2
	1750	20350	10	16QAM	50	0	21.85	0-2	2
	1750	20350	10	16QAM	50	0	21.78	0-2	2

Table 9-13
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	23.46	0	0
	1712.5	19975	5	QPSK	1	12	23.54	0	0
	1712.5	19975	5	QPSK	1	24	23.46	0	0
	1712.5	19975	5	QPSK	12	0	22.72	0-1	1
	1712.5	19975	5	QPSK	12	6	22.70	0-1	1
	1712.5	19975	5	QPSK	12	13	22.71	0-1	1
	1712.5	19975	5	QPSK	25	0	22.74	0-1	1
	1712.5	19975	5	16-QAM	1	0	22.30	0-1	1
	1712.5	19975	5	16-QAM	1	12	22.44	0-1	1
	1712.5	19975	5	16-QAM	1	24	22.37	0-1	1
	1712.5	19975	5	16-QAM	12	0	21.75	0-2	2
	1712.5	19975	5	16-QAM	12	6	21.71	0-2	2
	1712.5	19975	5	16-QAM	12	13	21.71	0-2	2
	1712.5	19975	5	16-QAM	25	0	21.72	0-2	2
	1732.5	20175	5	QPSK	1	0	23.71	0	0
1732.5	20175	5	QPSK	1	12	23.70	0	0	
1732.5	20175	5	QPSK	1	24	23.50	0	0	
1732.5	20175	5	QPSK	12	0	22.77	0-1	1	
1732.5	20175	5	QPSK	12	6	22.72	0-1	1	
1732.5	20175	5	QPSK	12	13	22.73	0-1	1	
1732.5	20175	5	QPSK	25	0	22.74	0-1	1	
1732.5	20175	5	16-QAM	1	0	22.24	0-1	1	
1732.5	20175	5	16-QAM	1	12	22.33	0-1	1	
1732.5	20175	5	16-QAM	1	24	22.20	0-1	1	
1732.5	20175	5	16-QAM	12	0	21.57	0-2	2	
1732.5	20175	5	16-QAM	12	6	21.53	0-2	2	
1732.5	20175	5	16-QAM	12	13	21.40	0-2	2	
1732.5	20175	5	16-QAM	25	0	21.53	0-2	2	
1752.5	20375	5	QPSK	1	0	23.46	0	0	
1752.5	20375	5	QPSK	1	12	23.55	0	0	
1752.5	20375	5	QPSK	1	24	23.63	0	0	
1752.5	20375	5	QPSK	12	0	22.60	0-1	1	
1752.5	20375	5	QPSK	12	6	22.62	0-1	1	
1752.5	20375	5	QPSK	12	13	22.64	0-1	1	
1752.5	20375	5	QPSK	25	0	22.61	0-1	1	
1752.5	20375	5	16-QAM	1	0	22.54	0-1	1	
1752.5	20375	5	16-QAM	1	12	22.54	0-1	1	
1752.5	20375	5	16-QAM	1	24	22.61	0-1	1	
1752.5	20375	5	16-QAM	12	0	21.60	0-2	2	
1752.5	20375	5	16-QAM	12	6	21.42	0-2	2	
1752.5	20375	5	16-QAM	12	13	21.45	0-2	2	
1752.5	20375	5	16-QAM	25	0	21.41	0-2	2	

Table 9-14
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	23.55	0	0
	1711.5	19965	3	QPSK	1	7	23.64	0	0
	1711.5	19965	3	QPSK	1	14	23.58	0	0
	1711.5	19965	3	QPSK	8	0	22.70	0-1	1
	1711.5	19965	3	QPSK	8	4	22.78	0-1	1
	1711.5	19965	3	QPSK	8	7	22.73	0-1	1
	1711.5	19965	3	QPSK	15	0	22.76	0-1	1
	1711.5	19965	3	16-QAM	1	0	22.51	0-1	1
	1711.5	19965	3	16-QAM	1	7	22.71	0-1	1
	1711.5	19965	3	16-QAM	1	14	22.56	0-1	1
	1711.5	19965	3	16-QAM	8	0	21.44	0-2	2
	1711.5	19965	3	16-QAM	8	4	21.56	0-2	2
	1711.5	19965	3	16-QAM	8	7	21.55	0-2	2
	1711.5	19965	3	16-QAM	15	0	21.65	0-2	2
	1732.5	20175	3	QPSK	1	0	23.72	0	0
1732.5	20175	3	QPSK	1	7	23.71	0	0	
1732.5	20175	3	QPSK	1	14	23.60	0	0	
1732.5	20175	3	QPSK	8	0	22.70	0-1	1	
1732.5	20175	3	QPSK	8	4	22.65	0-1	1	
1732.5	20175	3	QPSK	8	7	22.56	0-1	1	
1732.5	20175	3	QPSK	15	0	22.61	0-1	1	
1732.5	20175	3	16-QAM	1	0	22.40	0-1	1	
1732.5	20175	3	16-QAM	1	7	22.35	0-1	1	
1732.5	20175	3	16-QAM	1	14	22.22	0-1	1	
1732.5	20175	3	16-QAM	8	0	21.34	0-2	2	
1732.5	20175	3	16-QAM	8	4	21.34	0-2	2	
1732.5	20175	3	16-QAM	8	7	21.31	0-2	2	
1732.5	20175	3	16-QAM	15	0	21.42	0-2	2	
1753.5	20385	3	QPSK	1	0	23.41	0	0	
1753.5	20385	3	QPSK	1	7	23.62	0	0	
1753.5	20385	3	QPSK	1	14	23.64	0	0	
1753.5	20385	3	QPSK	8	0	22.51	0-1	1	
1753.5	20385	3	QPSK	8	4	22.62	0-1	1	
1753.5	20385	3	QPSK	8	7	22.68	0-1	1	
1753.5	20385	3	QPSK	15	0	22.65	0-1	1	
1753.5	20385	3	16-QAM	1	0	22.25	0-1	1	
1753.5	20385	3	16-QAM	1	7	22.47	0-1	1	
1753.5	20385	3	16-QAM	1	14	22.49	0-1	1	
1753.5	20385	3	16-QAM	8	0	21.39	0-2	2	
1753.5	20385	3	16-QAM	8	4	21.51	0-2	2	
1753.5	20385	3	16-QAM	8	7	21.57	0-2	2	
1753.5	20385	3	16-QAM	15	0	21.44	0-2	2	

Table 9-15
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1710.7	19957	1.4	QPSK	1	0	23.62	0	0	
	1710.7	19957	1.4	QPSK	1	2	23.65	0	0	
	1710.7	19957	1.4	QPSK	1	5	23.59	0	0	
	1710.7	19957	1.4	QPSK	3	0	23.53	0	0	
	1710.7	19957	1.4	QPSK	3	2	23.55	0	0	
	1710.7	19957	1.4	QPSK	3	3	23.50	0	0	
	1710.7	19957	1.4	QPSK	6	0	22.63	0-1	1	
	1710.7	19957	1.4	16-QAM	1	0	22.34	0-1	1	
	1710.7	19957	1.4	16-QAM	1	2	22.38	0-1	1	
	1710.7	19957	1.4	16-QAM	1	5	22.33	0-1	1	
	1710.7	19957	1.4	16-QAM	3	0	22.34	0-1	1	
	1710.7	19957	1.4	16-QAM	3	2	22.29	0-1	1	
	1710.7	19957	1.4	16-QAM	3	3	22.33	0-1	1	
	1710.7	19957	1.4	16-QAM	6	0	21.60	0-2	2	
	Mid	1732.5	20175	1.4	QPSK	1	0	23.58	0	0
		1732.5	20175	1.4	QPSK	1	2	23.55	0	0
		1732.5	20175	1.4	QPSK	1	5	23.42	0	0
1732.5		20175	1.4	QPSK	3	0	23.57	0	0	
1732.5		20175	1.4	QPSK	3	2	23.64	0	0	
1732.5		20175	1.4	QPSK	3	3	23.63	0	0	
1732.5		20175	1.4	QPSK	6	0	22.69	0-1	1	
1732.5		20175	1.4	16-QAM	1	0	22.23	0-1	1	
1732.5		20175	1.4	16-QAM	1	2	22.21	0-1	1	
1732.5		20175	1.4	16-QAM	1	5	22.24	0-1	1	
1732.5		20175	1.4	16-QAM	3	0	22.25	0-1	1	
1732.5		20175	1.4	16-QAM	3	2	22.31	0-1	1	
1732.5		20175	1.4	16-QAM	3	3	22.26	0-1	1	
1732.5		20175	1.4	16-QAM	6	0	21.46	0-2	2	
High		1754.3	20393	1.4	QPSK	1	0	23.45	0	0
		1754.3	20393	1.4	QPSK	1	2	23.55	0	0
		1754.3	20393	1.4	QPSK	1	5	23.55	0	0
	1754.3	20393	1.4	QPSK	3	0	23.48	0	0	
	1754.3	20393	1.4	QPSK	3	2	23.60	0	0	
	1754.3	20393	1.4	QPSK	3	3	23.54	0	0	
	1754.3	20393	1.4	QPSK	6	0	22.65	0-1	1	
	1754.3	20393	1.4	16-QAM	1	0	22.21	0-1	1	
	1754.3	20393	1.4	16-QAM	1	2	22.34	0-1	1	
	1754.3	20393	1.4	16-QAM	1	5	22.41	0-1	1	
	1754.3	20393	1.4	16-QAM	3	0	22.20	0-1	1	
	1754.3	20393	1.4	16-QAM	3	2	22.22	0-1	1	
	1754.3	20393	1.4	16-QAM	3	3	22.31	0-1	1	
	1754.3	20393	1.4	16-QAM	6	0	21.47	0-2	2	

9.4.4 LTE Band 25 (PCS)

Table 9-16
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1880	26140	20	QPSK	1	0	23.93	0	0	
	1880	26140	20	QPSK	1	50	24.19	0	0	
	1880	26140	20	QPSK	1	99	23.96	0	0	
	1880	26140	20	QPSK	50	0	23.13	0-1	1	
	1880	26140	20	QPSK	50	25	23.13	0-1	1	
	1880	26140	20	QPSK	50	50	23.16	0-1	1	
	1880	26140	20	QPSK	100	0	23.11	0-1	1	
	1880	26140	20	16QAM	1	0	23.18	0-1	1	
	1880	26140	20	16QAM	1	50	22.99	0-1	1	
	1880	26140	20	16QAM	1	99	22.97	0-1	1	
	1880	26140	20	16QAM	50	0	22.10	0-2	2	
	1880	26140	20	16QAM	50	25	22.16	0-2	2	
	1880	26140	20	16QAM	50	50	22.18	0-2	2	
	1880	26140	20	16QAM	100	0	22.10	0-2	2	
	Mid	1882.5	26365	20	QPSK	1	0	24.08	0	0
		1882.5	26365	20	QPSK	1	50	24.11	0	0
		1882.5	26365	20	QPSK	1	99	24.14	0	0
		1882.5	26365	20	QPSK	50	0	23.02	0-1	1
		1882.5	26365	20	QPSK	50	25	23.18	0-1	1
		1882.5	26365	20	QPSK	50	50	23.17	0-1	1
1882.5		26365	20	QPSK	100	0	23.07	0-1	1	
1882.5		26365	20	16QAM	1	0	23.02	0-1	1	
1882.5		26365	20	16QAM	1	50	23.16	0-1	1	
1882.5		26365	20	16QAM	1	99	23.14	0-1	1	
1882.5		26365	20	16QAM	50	0	22.17	0-2	2	
1882.5		26365	20	16QAM	50	25	22.09	0-2	2	
1882.5		26365	20	16QAM	50	50	22.16	0-2	2	
1882.5		26365	20	16QAM	100	0	22.17	0-2	2	
High	1905	26590	20	QPSK	1	0	23.86	0	0	
	1905	26590	20	QPSK	1	50	24.11	0	0	
	1905	26590	20	QPSK	1	99	23.89	0	0	
	1905	26590	20	QPSK	50	0	22.91	0-1	1	
	1905	26590	20	QPSK	50	25	23.16	0-1	1	
	1905	26590	20	QPSK	50	50	23.19	0-1	1	
	1905	26590	20	QPSK	100	0	23.00	0-1	1	
	1905	26590	20	16QAM	1	0	23.11	0-1	1	
	1905	26590	20	16QAM	1	50	23.18	0-1	1	
	1905	26590	20	16QAM	1	99	23.13	0-1	1	
	1905	26590	20	16QAM	50	0	21.98	0-2	2	
	1905	26590	20	16QAM	50	25	22.10	0-2	2	
	1905	26590	20	16QAM	50	50	22.01	0-2	2	
	1905	26590	20	16QAM	100	0	22.06	0-2	2	

Table 9-17
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	26115	15	QPSK	1	0	24.12	0	0
	1857.5	26115	15	QPSK	1	36	23.91	0	0
	1857.5	26115	15	QPSK	1	74	24.11	0	0
	1857.5	26115	15	QPSK	36	0	22.71	0-1	1
	1857.5	26115	15	QPSK	36	18	22.98	0-1	1
	1857.5	26115	15	QPSK	36	37	22.76	0-1	1
	1857.5	26115	15	QPSK	75	0	22.71	0-1	1
	1857.5	26115	15	16QAM	1	0	22.76	0-1	1
	1857.5	26115	15	16QAM	1	36	22.72	0-1	1
	1857.5	26115	15	16QAM	1	74	22.81	0-1	1
	1857.5	26115	15	16QAM	36	0	21.98	0-2	2
	1857.5	26115	15	16QAM	36	18	21.96	0-2	2
	1857.5	26115	15	16QAM	36	37	21.82	0-2	2
	1857.5	26115	15	16QAM	75	0	21.78	0-2	2
	1882.5	26365	15	QPSK	1	0	24.09	0	0
1882.5	26365	15	QPSK	1	36	24.03	0	0	
1882.5	26365	15	QPSK	1	74	23.87	0	0	
1882.5	26365	15	QPSK	36	0	23.01	0-1	1	
1882.5	26365	15	QPSK	36	18	22.71	0-1	1	
1882.5	26365	15	QPSK	36	37	23.02	0-1	1	
1882.5	26365	15	QPSK	75	0	22.72	0-1	1	
1882.5	26365	15	16QAM	1	0	22.77	0-1	1	
1882.5	26365	15	16QAM	1	36	22.75	0-1	1	
1882.5	26365	15	16QAM	1	74	22.83	0-1	1	
1882.5	26365	15	16QAM	36	0	22.12	0-2	2	
1882.5	26365	15	16QAM	36	18	21.82	0-2	2	
1882.5	26365	15	16QAM	36	37	22.04	0-2	2	
1882.5	26365	15	16QAM	75	0	22.11	0-2	2	
High	1907.5	26615	15	QPSK	1	0	23.95	0	0
	1907.5	26615	15	QPSK	1	36	24.08	0	0
	1907.5	26615	15	QPSK	1	74	24.08	0	0
	1907.5	26615	15	QPSK	36	0	22.75	0-1	1
	1907.5	26615	15	QPSK	36	18	23.07	0-1	1
	1907.5	26615	15	QPSK	36	37	23.00	0-1	1
	1907.5	26615	15	QPSK	75	0	22.87	0-1	1
	1907.5	26615	15	16QAM	1	0	22.80	0-1	1
	1907.5	26615	15	16QAM	1	36	22.82	0-1	1
	1907.5	26615	15	16QAM	1	74	22.95	0-1	1
	1907.5	26615	15	16QAM	36	0	21.77	0-2	2
	1907.5	26615	15	16QAM	36	18	21.79	0-2	2
	1907.5	26615	15	16QAM	36	37	21.78	0-2	2
	1907.5	26615	15	16QAM	75	0	21.86	0-2	2

Table 9-18
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	26090	10	QPSK	1	0	23.89	0	0
	1855	26090	10	QPSK	1	25	23.92	0	0
	1855	26090	10	QPSK	1	49	24.00	0	0
	1855	26090	10	QPSK	25	0	22.76	0-1	1
	1855	26090	10	QPSK	25	12	22.89	0-1	1
	1855	26090	10	QPSK	25	25	22.95	0-1	1
	1855	26090	10	QPSK	50	0	23.00	0-1	1
	1855	26090	10	16QAM	1	0	23.06	0-1	1
	1855	26090	10	16QAM	1	25	22.99	0-1	1
	1855	26090	10	16QAM	1	49	23.18	0-1	1
	1855	26090	10	16QAM	25	0	21.98	0-2	2
	1855	26090	10	16QAM	25	12	22.19	0-2	2
	1855	26090	10	16QAM	25	25	21.86	0-2	2
	1855	26090	10	16QAM	50	0	21.72	0-2	2
	1882.5	26365	10	QPSK	1	0	23.99	0	0
1882.5	26365	10	QPSK	1	25	24.07	0	0	
1882.5	26365	10	QPSK	1	49	24.03	0	0	
1882.5	26365	10	QPSK	25	0	23.09	0-1	1	
1882.5	26365	10	QPSK	25	12	22.99	0-1	1	
1882.5	26365	10	QPSK	25	25	22.73	0-1	1	
1882.5	26365	10	QPSK	50	0	22.82	0-1	1	
1882.5	26365	10	16QAM	1	0	23.13	0-1	1	
1882.5	26365	10	16QAM	1	25	23.17	0-1	1	
1882.5	26365	10	16QAM	1	49	23.03	0-1	1	
1882.5	26365	10	16QAM	25	0	21.70	0-2	2	
1882.5	26365	10	16QAM	25	12	21.96	0-2	2	
1882.5	26365	10	16QAM	25	25	22.00	0-2	2	
1882.5	26365	10	16QAM	50	0	21.86	0-2	2	
High	1910	26640	10	QPSK	1	0	23.92	0	0
	1910	26640	10	QPSK	1	25	24.01	0	0
	1910	26640	10	QPSK	1	49	23.74	0	0
	1910	26640	10	QPSK	25	0	22.86	0-1	1
	1910	26640	10	QPSK	25	12	22.70	0-1	1
	1910	26640	10	QPSK	25	25	22.86	0-1	1
	1910	26640	10	QPSK	50	0	22.93	0-1	1
	1910	26640	10	16QAM	1	0	23.14	0-1	1
	1910	26640	10	16QAM	1	25	23.10	0-1	1
	1910	26640	10	16QAM	1	49	22.78	0-1	1
	1910	26640	10	16QAM	25	0	22.03	0-2	2
	1910	26640	10	16QAM	25	12	22.08	0-2	2
	1910	26640	10	16QAM	25	25	22.18	0-2	2
	1910	26640	10	16QAM	50	0	22.01	0-2	2

Table 9-19
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth



	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1852.5	26065	5	QPSK	1	0	24.16	0	0	
	1852.5	26065	5	QPSK	1	12	24.10	0	0	
	1852.5	26065	5	QPSK	1	24	24.02	0	0	
	1852.5	26065	5	QPSK	12	0	22.85	0-1	1	
	1852.5	26065	5	QPSK	12	6	22.91	0-1	1	
	1852.5	26065	5	QPSK	12	13	22.79	0-1	1	
	1852.5	26065	5	QPSK	25	0	22.95	0-1	1	
	1852.5	26065	5	16-QAM	1	0	23.08	0-1	1	
	1852.5	26065	5	16-QAM	1	12	23.11	0-1	1	
	1852.5	26065	5	16-QAM	1	24	23.15	0-1	1	
	1852.5	26065	5	16-QAM	12	0	22.12	0-2	2	
	1852.5	26065	5	16-QAM	12	6	22.00	0-2	2	
	1852.5	26065	5	16-QAM	12	13	21.78	0-2	2	
	1852.5	26065	5	16-QAM	25	0	22.01	0-2	2	
	Mid	1882.5	26365	5	QPSK	1	0	24.08	0	0
		1882.5	26365	5	QPSK	1	12	24.11	0	0
		1882.5	26365	5	QPSK	1	24	24.16	0	0
		1882.5	26365	5	QPSK	12	0	22.99	0-1	1
1882.5		26365	5	QPSK	12	6	22.87	0-1	1	
1882.5		26365	5	QPSK	12	13	23.16	0-1	1	
1882.5		26365	5	QPSK	25	0	23.07	0-1	1	
1882.5		26365	5	16-QAM	1	0	22.80	0-1	1	
1882.5		26365	5	16-QAM	1	12	22.75	0-1	1	
1882.5		26365	5	16-QAM	1	24	22.71	0-1	1	
1882.5		26365	5	16-QAM	12	0	22.03	0-2	2	
1882.5		26365	5	16-QAM	12	6	21.95	0-2	2	
1882.5		26365	5	16-QAM	12	13	22.13	0-2	2	
1882.5		26365	5	16-QAM	25	0	21.82	0-2	2	
High		1912.5	26665	5	QPSK	1	0	23.89	0	0
		1912.5	26665	5	QPSK	1	12	23.75	0	0
		1912.5	26665	5	QPSK	1	24	23.80	0	0
		1912.5	26665	5	QPSK	12	0	22.91	0-1	1
	1912.5	26665	5	QPSK	12	6	22.74	0-1	1	
	1912.5	26665	5	QPSK	12	13	22.90	0-1	1	
	1912.5	26665	5	QPSK	25	0	23.00	0-1	1	
	1912.5	26665	5	16-QAM	1	0	23.15	0-1	1	
	1912.5	26665	5	16-QAM	1	12	22.99	0-1	1	
	1912.5	26665	5	16-QAM	1	24	23.04	0-1	1	
	1912.5	26665	5	16-QAM	12	0	21.91	0-2	2	
	1912.5	26665	5	16-QAM	12	6	21.87	0-2	2	
	1912.5	26665	5	16-QAM	12	13	21.97	0-2	2	
	1912.5	26665	5	16-QAM	25	0	22.06	0-2	2	

Table 9-20
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1851.5	26055	3	QPSK	1	0	23.95	0	0	
	1851.5	26055	3	QPSK	1	7	23.98	0	0	
	1851.5	26055	3	QPSK	1	14	24.01	0	0	
	1851.5	26055	3	QPSK	8	0	23.12	0-1	1	
	1851.5	26055	3	QPSK	8	4	22.78	0-1	1	
	1851.5	26055	3	QPSK	8	7	22.93	0-1	1	
	1851.5	26055	3	QPSK	15	0	23.18	0-1	1	
	1851.5	26055	3	16-QAM	1	0	23.00	0-1	1	
	1851.5	26055	3	16-QAM	1	7	23.07	0-1	1	
	1851.5	26055	3	16-QAM	1	14	23.12	0-1	1	
	1851.5	26055	3	16-QAM	8	0	21.99	0-2	2	
	1851.5	26055	3	16-QAM	8	4	21.94	0-2	2	
	1851.5	26055	3	16-QAM	8	7	22.17	0-2	2	
	1851.5	26055	3	16-QAM	15	0	22.07	0-2	2	
	Mid	1882.5	26365	3	QPSK	1	0	24.10	0	0
		1882.5	26365	3	QPSK	1	7	23.74	0	0
		1882.5	26365	3	QPSK	1	14	24.10	0	0
		1882.5	26365	3	QPSK	8	0	23.09	0-1	1
		1882.5	26365	3	QPSK	8	4	22.73	0-1	1
		1882.5	26365	3	QPSK	8	7	22.78	0-1	1
		1882.5	26365	3	QPSK	15	0	23.00	0-1	1
		1882.5	26365	3	16-QAM	1	0	23.08	0-1	1
		1882.5	26365	3	16-QAM	1	7	22.74	0-1	1
		1882.5	26365	3	16-QAM	1	14	23.12	0-1	1
1882.5		26365	3	16-QAM	8	0	22.02	0-2	2	
1882.5		26365	3	16-QAM	8	4	21.99	0-2	2	
1882.5		26365	3	16-QAM	8	7	22.03	0-2	2	
1882.5		26365	3	16-QAM	15	0	22.10	0-2	2	
High		1913.5	26675	3	QPSK	1	0	23.99	0	0
		1913.5	26675	3	QPSK	1	7	24.01	0	0
		1913.5	26675	3	QPSK	1	14	24.00	0	0
		1913.5	26675	3	QPSK	8	0	23.01	0-1	1
		1913.5	26675	3	QPSK	8	4	22.85	0-1	1
		1913.5	26675	3	QPSK	8	7	22.92	0-1	1
		1913.5	26675	3	QPSK	15	0	22.94	0-1	1
		1913.5	26675	3	16-QAM	1	0	23.14	0-1	1
		1913.5	26675	3	16-QAM	1	7	22.78	0-1	1
		1913.5	26675	3	16-QAM	1	14	22.82	0-1	1
	1913.5	26675	3	16-QAM	8	0	21.77	0-2	2	
	1913.5	26675	3	16-QAM	8	4	21.97	0-2	2	
	1913.5	26675	3	16-QAM	8	7	21.85	0-2	2	
	1913.5	26675	3	16-QAM	15	0	21.90	0-2	2	

**Table 9-21
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1850.7	26047	1.4	QPSK	1	0	23.77	0	0	
	1850.7	26047	1.4	QPSK	1	2	24.07	0	0	
	1850.7	26047	1.4	QPSK	1	5	24.17	0	0	
	1850.7	26047	1.4	QPSK	3	0	24.05	0	0	
	1850.7	26047	1.4	QPSK	3	2	24.17	0	0	
	1850.7	26047	1.4	QPSK	3	3	23.83	0	0	
	1850.7	26047	1.4	QPSK	6	0	22.74	0-1	1	
	1850.7	26047	1.4	16-QAM	1	0	22.94	0-1	1	
	1850.7	26047	1.4	16-QAM	1	2	23.14	0-1	1	
	1850.7	26047	1.4	16-QAM	1	5	23.12	0-1	1	
	1850.7	26047	1.4	16-QAM	3	0	23.05	0-1	1	
	1850.7	26047	1.4	16-QAM	3	2	23.08	0-1	1	
	1850.7	26047	1.4	16-QAM	3	3	23.19	0-1	1	
	1850.7	26047	1.4	16-QAM	6	0	21.72	0-2	2	
	1882.5	26365	1.4	QPSK	1	0	23.84	0	0	
	1882.5	26365	1.4	QPSK	1	2	24.17	0	0	
	1882.5	26365	1.4	QPSK	1	5	23.71	0	0	
	1882.5	26365	1.4	QPSK	3	0	24.08	0	0	
1882.5	26365	1.4	QPSK	3	2	24.11	0	0		
1882.5	26365	1.4	QPSK	3	3	23.91	0	0		
1882.5	26365	1.4	QPSK	6	0	22.85	0-1	1		
1882.5	26365	1.4	16-QAM	1	0	22.78	0-1	1		
1882.5	26365	1.4	16-QAM	1	2	22.73	0-1	1		
1882.5	26365	1.4	16-QAM	1	5	22.73	0-1	1		
1882.5	26365	1.4	16-QAM	3	0	23.10	0-1	1		
1882.5	26365	1.4	16-QAM	3	2	22.87	0-1	1		
1882.5	26365	1.4	16-QAM	3	3	22.77	0-1	1		
1882.5	26365	1.4	16-QAM	6	0	21.77	0-2	2		
Mid	1914.3	26683	1.4	QPSK	1	0	23.74	0	0	
	1914.3	26683	1.4	QPSK	1	2	23.80	0	0	
	1914.3	26683	1.4	QPSK	1	5	23.96	0	0	
	1914.3	26683	1.4	QPSK	3	0	23.86	0	0	
	1914.3	26683	1.4	QPSK	3	2	23.88	0	0	
	1914.3	26683	1.4	QPSK	3	3	24.00	0	0	
	1914.3	26683	1.4	QPSK	6	0	23.04	0-1	1	
	1914.3	26683	1.4	16-QAM	1	0	23.10	0-1	1	
	1914.3	26683	1.4	16-QAM	1	2	23.05	0-1	1	
	1914.3	26683	1.4	16-QAM	1	5	22.97	0-1	1	
	1914.3	26683	1.4	16-QAM	3	0	23.08	0-1	1	
	1914.3	26683	1.4	16-QAM	3	2	23.08	0-1	1	
	1914.3	26683	1.4	16-QAM	3	3	23.11	0-1	1	
	1914.3	26683	1.4	16-QAM	6	0	21.79	0-2	2	
	High	1914.3	26683	1.4	QPSK	1	0	23.74	0	0
		1914.3	26683	1.4	QPSK	1	2	23.80	0	0
		1914.3	26683	1.4	QPSK	1	5	23.96	0	0
		1914.3	26683	1.4	QPSK	3	0	23.86	0	0
1914.3		26683	1.4	QPSK	3	2	23.88	0	0	
1914.3		26683	1.4	QPSK	3	3	24.00	0	0	
1914.3		26683	1.4	QPSK	6	0	23.04	0-1	1	
1914.3		26683	1.4	16-QAM	1	0	23.10	0-1	1	
1914.3		26683	1.4	16-QAM	1	2	23.05	0-1	1	
1914.3		26683	1.4	16-QAM	1	5	22.97	0-1	1	
1914.3		26683	1.4	16-QAM	3	0	23.08	0-1	1	
1914.3		26683	1.4	16-QAM	3	2	23.08	0-1	1	
1914.3		26683	1.4	16-QAM	3	3	23.11	0-1	1	
1914.3		26683	1.4	16-QAM	6	0	21.79	0-2	2	

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 38 of 77

9.4.5

LTE Band 41

Table 9-22
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	2506	39750	20	QPSK	1	0	24.09	0	0
	2506	39750	20	QPSK	1	50	24.20	0	0
	2506	39750	20	QPSK	1	99	24.05	0	0
	2506	39750	20	QPSK	50	0	23.19	0-1	1
	2506	39750	20	QPSK	50	25	23.20	0-1	1
	2506	39750	20	QPSK	50	50	23.11	0-1	1
	2506	39750	20	QPSK	100	0	23.13	0-1	1
	2506	39750	20	16QAM	1	0	22.98	0-1	1
	2506	39750	20	16QAM	1	50	23.20	0-1	1
	2506	39750	20	16QAM	1	99	22.99	0-1	1
	2506	39750	20	16QAM	50	0	22.08	0-2	2
	2506	39750	20	16QAM	50	25	22.17	0-2	2
	2506	39750	20	16QAM	50	50	22.04	0-2	2
	2506	39750	20	16QAM	100	0	22.06	0-2	2
Low Mid	2549.5	40185	20	QPSK	1	0	24.02	0	0
	2549.5	40185	20	QPSK	1	50	24.11	0	0
	2549.5	40185	20	QPSK	1	99	24.10	0	0
	2549.5	40185	20	QPSK	50	0	23.18	0-1	1
	2549.5	40185	20	QPSK	50	25	23.16	0-1	1
	2549.5	40185	20	QPSK	50	50	23.12	0-1	1
	2549.5	40185	20	QPSK	100	0	23.13	0-1	1
	2549.5	40185	20	16-QAM	1	0	23.03	0-1	1
	2549.5	40185	20	16-QAM	1	50	23.07	0-1	1
	2549.5	40185	20	16-QAM	1	99	23.08	0-1	1
	2549.5	40185	20	16-QAM	50	0	22.15	0-2	2
	2549.5	40185	20	16-QAM	50	25	22.06	0-2	2
	2549.5	40185	20	16-QAM	50	50	22.02	0-2	2
	2549.5	40185	20	16-QAM	100	0	22.05	0-2	2
Mid	2593	40620	20	QPSK	1	0	24.18	0	0
	2593	40620	20	QPSK	1	50	24.18	0	0
	2593	40620	20	QPSK	1	99	24.11	0	0
	2593	40620	20	QPSK	50	0	23.17	0-1	1
	2593	40620	20	QPSK	50	25	23.18	0-1	1
	2593	40620	20	QPSK	50	50	23.04	0-1	1
	2593	40620	20	QPSK	100	0	23.07	0-1	1
	2593	40620	20	16-QAM	1	0	23.20	0-1	1
	2593	40620	20	16-QAM	1	50	23.07	0-1	1
	2593	40620	20	16-QAM	1	99	23.19	0-1	1
	2593	40620	20	16-QAM	50	0	22.12	0-2	2
	2593	40620	20	16-QAM	50	25	22.12	0-2	2
	2593	40620	20	16-QAM	50	50	22.07	0-2	2
	2593	40620	20	16-QAM	100	0	22.01	0-2	2
Mid High	2636.5	41055	20	QPSK	1	0	24.18	0	0
	2636.5	41055	20	QPSK	1	50	24.19	0	0
	2636.5	41055	20	QPSK	1	99	24.19	0	0
	2636.5	41055	20	QPSK	50	0	23.17	0-1	1
	2636.5	41055	20	QPSK	50	25	23.19	0-1	1
	2636.5	41055	20	QPSK	50	50	23.19	0-1	1
	2636.5	41055	20	QPSK	100	0	23.16	0-1	1
	2636.5	41055	20	16-QAM	1	0	23.10	0-1	1
	2636.5	41055	20	16-QAM	1	50	23.09	0-1	1
	2636.5	41055	20	16-QAM	1	99	23.09	0-1	1
	2636.5	41055	20	16-QAM	50	0	22.19	0-2	2
	2636.5	41055	20	16-QAM	50	25	22.14	0-2	2
	2636.5	41055	20	16-QAM	50	50	22.20	0-2	2
	2636.5	41055	20	16-QAM	100	0	22.19	0-2	2
High	2680	41490	20	QPSK	1	0	24.11	0	0
	2680	41490	20	QPSK	1	50	24.19	0	0
	2680	41490	20	QPSK	1	99	24.18	0	0
	2680	41490	20	QPSK	50	0	23.15	0-1	1
	2680	41490	20	QPSK	50	25	23.19	0-1	1
	2680	41490	20	QPSK	50	50	23.17	0-1	1
	2680	41490	20	QPSK	100	0	23.19	0-1	1
	2680	41490	20	16-QAM	1	0	22.89	0-1	1
	2680	41490	20	16-QAM	1	50	23.12	0-1	1
	2680	41490	20	16-QAM	1	99	23.17	0-1	1
	2680	41490	20	16-QAM	50	0	22.16	0-2	2
	2680	41490	20	16-QAM	50	25	22.12	0-2	2
	2680	41490	20	16-QAM	50	50	22.20	0-2	2
	2680	41490	20	16-QAM	100	0	22.10	0-2	2

**Table 9-23
LTE Band 41 Conducted Powers - 15 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	2503.5	39725	15	QPSK	1	0	24.08	0	0
	2503.5	39725	15	QPSK	1	36	24.20	0	0
	2503.5	39725	15	QPSK	1	74	24.14	0	0
	2503.5	39725	15	QPSK	36	0	23.16	0-1	1
	2503.5	39725	15	QPSK	36	18	23.18	0-1	1
	2503.5	39725	15	QPSK	36	37	23.16	0-1	1
	2503.5	39725	15	QPSK	75	0	23.07	0-1	1
	2503.5	39725	15	16QAM	1	0	22.71	0-1	1
	2503.5	39725	15	16QAM	1	36	22.81	0-1	1
	2503.5	39725	15	16QAM	1	74	22.75	0-1	1
	2503.5	39725	15	16QAM	36	0	22.20	0-2	2
	2503.5	39725	15	16QAM	36	18	22.15	0-2	2
	2503.5	39725	15	16QAM	36	37	22.13	0-2	2
	2503.5	39725	15	16QAM	75	0	22.03	0-2	2
	2548.25	40173	15	QPSK	1	0	24.06	0	0
2548.25	40173	15	QPSK	1	36	24.02	0	0	
2548.25	40173	15	QPSK	1	74	24.05	0	0	
2548.25	40173	15	QPSK	36	0	23.11	0-1	1	
2548.25	40173	15	QPSK	36	18	23.12	0-1	1	
2548.25	40173	15	QPSK	36	37	23.00	0-1	1	
2548.25	40173	15	QPSK	75	0	23.04	0-1	1	
2548.25	40173	15	16-QAM	1	0	23.16	0-1	1	
2548.25	40173	15	16-QAM	1	36	22.95	0-1	1	
2548.25	40173	15	16-QAM	1	74	23.03	0-1	1	
2548.25	40173	15	16-QAM	36	0	22.15	0-2	2	
2548.25	40173	15	16-QAM	36	18	21.91	0-2	2	
2548.25	40173	15	16-QAM	36	37	21.85	0-2	2	
2548.25	40173	15	16-QAM	75	0	21.92	0-2	2	
Mid	2593	40620	15	QPSK	1	0	24.19	0	0
	2593	40620	15	QPSK	1	36	24.07	0	0
	2593	40620	15	QPSK	1	74	23.94	0	0
	2593	40620	15	QPSK	36	0	23.20	0-1	1
	2593	40620	15	QPSK	36	18	23.15	0-1	1
	2593	40620	15	QPSK	36	37	23.05	0-1	1
	2593	40620	15	QPSK	75	0	23.03	0-1	1
	2593	40620	15	16-QAM	1	0	23.20	0-1	1
	2593	40620	15	16-QAM	1	36	23.01	0-1	1
	2593	40620	15	16-QAM	1	74	22.90	0-1	1
	2593	40620	15	16-QAM	36	0	22.10	0-2	2
	2593	40620	15	16-QAM	36	18	22.03	0-2	2
	2593	40620	15	16-QAM	36	37	22.00	0-2	2
	2593	40620	15	16-QAM	75	0	21.93	0-2	2
	2637.75	41068	15	QPSK	1	0	24.00	0	0
2637.75	41068	15	QPSK	1	36	24.15	0	0	
2637.75	41068	15	QPSK	1	74	24.15	0	0	
2637.75	41068	15	QPSK	36	0	23.20	0-1	1	
2637.75	41068	15	QPSK	36	18	23.20	0-1	1	
2637.75	41068	15	QPSK	36	37	23.18	0-1	1	
2637.75	41068	15	QPSK	75	0	23.17	0-1	1	
2637.75	41068	15	16-QAM	1	0	23.19	0-1	1	
2637.75	41068	15	16-QAM	1	36	23.07	0-1	1	
2637.75	41068	15	16-QAM	1	74	23.10	0-1	1	
2637.75	41068	15	16-QAM	36	0	22.14	0-2	2	
2637.75	41068	15	16-QAM	36	18	22.10	0-2	2	
2637.75	41068	15	16-QAM	36	37	22.14	0-2	2	
2637.75	41068	15	16-QAM	75	0	22.04	0-2	2	
High	2682.5	41515	15	QPSK	1	0	24.20	0	0
	2682.5	41515	15	QPSK	1	36	24.19	0	0
	2682.5	41515	15	QPSK	1	74	24.20	0	0
	2682.5	41515	15	QPSK	36	0	23.09	0-1	1
	2682.5	41515	15	QPSK	36	18	23.18	0-1	1
	2682.5	41515	15	QPSK	36	37	23.20	0-1	1
	2682.5	41515	15	QPSK	75	0	23.12	0-1	1
	2682.5	41515	15	16-QAM	1	0	23.02	0-1	1
	2682.5	41515	15	16-QAM	1	36	22.88	0-1	1
	2682.5	41515	15	16-QAM	1	74	22.92	0-1	1
	2682.5	41515	15	16-QAM	36	0	22.19	0-2	2
	2682.5	41515	15	16-QAM	36	18	22.18	0-2	2
	2682.5	41515	15	16-QAM	36	37	22.17	0-2	2
	2682.5	41515	15	16-QAM	75	0	22.06	0-2	2

**Table 9-24
LTE Band 41 Conducted Powers - 10 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	2501	39700	10	QPSK	1	0	23.71	0	0
	2501	39700	10	QPSK	1	25	23.95	0	0
	2501	39700	10	QPSK	1	49	23.85	0	0
	2501	39700	10	QPSK	25	0	22.87	0-1	1
	2501	39700	10	QPSK	25	12	22.89	0-1	1
	2501	39700	10	QPSK	25	25	22.99	0-1	1
	2501	39700	10	QPSK	50	0	22.95	0-1	1
	2501	39700	10	16QAM	1	0	22.74	0-1	1
	2501	39700	10	16QAM	1	25	22.86	0-1	1
	2501	39700	10	16QAM	1	49	22.88	0-1	1
	2501	39700	10	16QAM	25	0	21.79	0-2	2
	2501	39700	10	16QAM	25	12	21.93	0-2	2
	2501	39700	10	16QAM	25	25	21.89	0-2	2
	2501	39700	10	16QAM	50	0	21.86	0-2	2
Low Mid	2547	40160	10	QPSK	1	0	23.83	0	0
	2547	40160	10	QPSK	1	25	23.91	0	0
	2547	40160	10	QPSK	1	49	23.73	0	0
	2547	40160	10	QPSK	25	0	22.92	0-1	1
	2547	40160	10	QPSK	25	12	22.89	0-1	1
	2547	40160	10	QPSK	25	25	22.90	0-1	1
	2547	40160	10	QPSK	50	0	22.85	0-1	1
	2547	40160	10	16-QAM	1	0	22.72	0-1	1
	2547	40160	10	16-QAM	1	25	22.75	0-1	1
	2547	40160	10	16-QAM	1	49	22.70	0-1	1
	2547	40160	10	16-QAM	25	0	21.81	0-2	2
	2547	40160	10	16-QAM	25	12	21.83	0-2	2
	2547	40160	10	16-QAM	25	25	21.82	0-2	2
	2547	40160	10	16-QAM	50	0	21.75	0-2	2
Mid	2593	40620	10	QPSK	1	0	23.93	0	0
	2593	40620	10	QPSK	1	25	23.96	0	0
	2593	40620	10	QPSK	1	49	23.76	0	0
	2593	40620	10	QPSK	25	0	23.03	0-1	1
	2593	40620	10	QPSK	25	12	23.02	0-1	1
	2593	40620	10	QPSK	25	25	22.87	0-1	1
	2593	40620	10	QPSK	50	0	22.89	0-1	1
	2593	40620	10	16-QAM	1	0	22.93	0-1	1
	2593	40620	10	16-QAM	1	25	22.97	0-1	1
	2593	40620	10	16-QAM	1	49	22.73	0-1	1
	2593	40620	10	16-QAM	25	0	21.95	0-2	2
	2593	40620	10	16-QAM	25	12	21.93	0-2	2
	2593	40620	10	16-QAM	25	25	21.81	0-2	2
	2593	40620	10	16-QAM	50	0	21.83	0-2	2
Mid High	2639	41080	10	QPSK	1	0	23.90	0	0
	2639	41080	10	QPSK	1	25	24.03	0	0
	2639	41080	10	QPSK	1	49	23.76	0	0
	2639	41080	10	QPSK	25	0	23.10	0-1	1
	2639	41080	10	QPSK	25	12	23.19	0-1	1
	2639	41080	10	QPSK	25	25	23.10	0-1	1
	2639	41080	10	QPSK	50	0	23.10	0-1	1
	2639	41080	10	16-QAM	1	0	22.87	0-1	1
	2639	41080	10	16-QAM	1	25	23.03	0-1	1
	2639	41080	10	16-QAM	1	49	22.83	0-1	1
	2639	41080	10	16-QAM	25	0	21.92	0-2	2
	2639	41080	10	16-QAM	25	12	22.03	0-2	2
	2639	41080	10	16-QAM	25	25	21.95	0-2	2
	2639	41080	10	16-QAM	50	0	21.93	0-2	2
High	2685	41540	10	QPSK	1	0	24.05	0	0
	2685	41540	10	QPSK	1	25	24.18	0	0
	2685	41540	10	QPSK	1	49	24.00	0	0
	2685	41540	10	QPSK	25	0	23.20	0-1	1
	2685	41540	10	QPSK	25	12	23.18	0-1	1
	2685	41540	10	QPSK	25	25	23.20	0-1	1
	2685	41540	10	QPSK	50	0	23.15	0-1	1
	2685	41540	10	16-QAM	1	0	22.83	0-1	1
	2685	41540	10	16-QAM	1	25	22.99	0-1	1
	2685	41540	10	16-QAM	1	49	22.87	0-1	1
	2685	41540	10	16-QAM	25	0	22.18	0-2	2
	2685	41540	10	16-QAM	25	12	22.11	0-2	2
	2685	41540	10	16-QAM	25	25	22.14	0-2	2
	2685	41540	10	16-QAM	50	0	22.05	0-2	2

Table 9-25
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	2498.5	39675	5	QPSK	1	0	23.74	0	0
	2498.5	39675	5	QPSK	1	12	23.77	0	0
	2498.5	39675	5	QPSK	1	24	23.78	0	0
	2498.5	39675	5	QPSK	12	0	22.86	0-1	1
	2498.5	39675	5	QPSK	12	6	22.81	0-1	1
	2498.5	39675	5	QPSK	12	13	22.83	0-1	1
	2498.5	39675	5	QPSK	25	0	22.80	0-1	1
	2498.5	39675	5	16-QAM	1	0	22.78	0-1	1
	2498.5	39675	5	16-QAM	1	12	22.70	0-1	1
	2498.5	39675	5	16-QAM	1	24	22.71	0-1	1
	2498.5	39675	5	16-QAM	12	0	21.73	0-2	2
	2498.5	39675	5	16-QAM	12	6	21.75	0-2	2
	2498.5	39675	5	16-QAM	12	13	21.74	0-2	2
	2498.5	39675	5	16-QAM	25	0	21.75	0-2	2
Low Mid	2545.75	40148	5	QPSK	1	0	23.95	0	0
	2545.75	40148	5	QPSK	1	12	23.99	0	0
	2545.75	40148	5	QPSK	1	24	23.87	0	0
	2545.75	40148	5	QPSK	12	0	22.88	0-1	1
	2545.75	40148	5	QPSK	12	6	22.92	0-1	1
	2545.75	40148	5	QPSK	12	13	22.87	0-1	1
	2545.75	40148	5	QPSK	25	0	22.89	0-1	1
	2545.75	40148	5	16-QAM	1	0	22.70	0-1	1
	2545.75	40148	5	16-QAM	1	12	22.71	0-1	1
	2545.75	40148	5	16-QAM	1	24	22.70	0-1	1
	2545.75	40148	5	16-QAM	12	0	21.84	0-2	2
	2545.75	40148	5	16-QAM	12	6	21.90	0-2	2
	2545.75	40148	5	16-QAM	12	13	21.85	0-2	2
	2545.75	40148	5	16-QAM	25	0	21.85	0-2	2
Mid	2593	40620	5	QPSK	1	0	24.03	0	0
	2593	40620	5	QPSK	1	12	24.02	0	0
	2593	40620	5	QPSK	1	24	24.00	0	0
	2593	40620	5	QPSK	12	0	23.07	0-1	1
	2593	40620	5	QPSK	12	6	22.95	0-1	1
	2593	40620	5	QPSK	12	13	23.02	0-1	1
	2593	40620	5	QPSK	25	0	22.90	0-1	1
	2593	40620	5	16-QAM	1	0	23.05	0-1	1
	2593	40620	5	16-QAM	1	12	23.06	0-1	1
	2593	40620	5	16-QAM	1	24	22.94	0-1	1
	2593	40620	5	16-QAM	12	0	21.93	0-2	2
	2593	40620	5	16-QAM	12	6	21.91	0-2	2
	2593	40620	5	16-QAM	12	13	21.80	0-2	2
	2593	40620	5	16-QAM	25	0	21.86	0-2	2
Mid High	2640.25	41093	5	QPSK	1	0	24.08	0	0
	2640.25	41093	5	QPSK	1	12	24.12	0	0
	2640.25	41093	5	QPSK	1	24	24.05	0	0
	2640.25	41093	5	QPSK	12	0	23.20	0-1	1
	2640.25	41093	5	QPSK	12	6	23.18	0-1	1
	2640.25	41093	5	QPSK	12	13	23.18	0-1	1
	2640.25	41093	5	QPSK	25	0	23.19	0-1	1
	2640.25	41093	5	16-QAM	1	0	22.99	0-1	1
	2640.25	41093	5	16-QAM	1	12	23.03	0-1	1
	2640.25	41093	5	16-QAM	1	24	22.96	0-1	1
	2640.25	41093	5	16-QAM	12	0	22.11	0-2	2
	2640.25	41093	5	16-QAM	12	6	22.11	0-2	2
	2640.25	41093	5	16-QAM	12	13	22.07	0-2	2
	2640.25	41093	5	16-QAM	25	0	22.12	0-2	2
High	2687.5	41565	5	QPSK	1	0	24.03	0	0
	2687.5	41565	5	QPSK	1	12	24.20	0	0
	2687.5	41565	5	QPSK	1	24	24.18	0	0
	2687.5	41565	5	QPSK	12	0	23.20	0-1	1
	2687.5	41565	5	QPSK	12	6	23.19	0-1	1
	2687.5	41565	5	QPSK	12	13	23.20	0-1	1
	2687.5	41565	5	QPSK	25	0	23.18	0-1	1
	2687.5	41565	5	16-QAM	1	0	23.12	0-1	1
	2687.5	41565	5	16-QAM	1	12	23.09	0-1	1
	2687.5	41565	5	16-QAM	1	24	22.95	0-1	1
	2687.5	41565	5	16-QAM	12	0	22.15	0-2	2
	2687.5	41565	5	16-QAM	12	6	22.17	0-2	2
	2687.5	41565	5	16-QAM	12	13	22.19	0-2	2
	2687.5	41565	5	16-QAM	25	0	22.20	0-2	2

9.4.6

LTE Carrier Aggregation Conducted Powers

Table 9-26

LTE Carrier Aggregation Conducted Powers – Band 41 (PCC) + Band 41 (SCC) 20 MHz BW

Band 41 (PCC) + Band 41 (SCC), 20 MHz				
2506.0 MHz / ch.39750 + 2525.8 MHz / ch. 39948	PCC UL	PCC UL	LTE Rel 10 Tx.Power	LTE Rel 8 Tx.Power
	# RB	RB Offset	(dBm)	(dBm)
	1	50	24.19	24.20

Notes:

1. The device does not support all Rel. 10 Carrier Aggregation features due to modem chipset limitation.
2. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. Power measurements were performed with two DL carriers for the Release 8 configuration that had the highest output power (across all bandwidths, channels and RB Configurations) for each band
3. This device only supports intra-band CA with 2 carriers (B41+B41) with a maximum of 20 MHz of spectrum.
4. All control and acknowledge data is sent on uplink channels that operate identical to release 8 specifications.




Figure 9-4
Power Measurement Setup

9.5 WLAN Conducted Powers

Table 9-27

IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	802.11b (2.4 GHz) Conducted Power			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1*	13.23	13.20	13.20	13.16
802.11b	2437	6*	13.24	13.22	13.14	13.24
802.11b	2462	11*	13.57	13.50	13.47	13.45

Table 9-28

IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	802.11g (2.4 GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	12.19	12.10	12.06	12.12	12.44	12.36	12.33	12.23
802.11g	2437	6	12.03	11.94	11.90	11.96	12.28	12.20	12.17	12.07
802.11g	2462	11	12.25	12.16	12.12	12.18	12.50	12.42	12.39	12.29

FCC ID: ZNFLS996	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 43 of 77

**Table 9-29
IEEE 802.11n Average RF Power**

Mode	Freq [MHz]	Channel	802.11n (2.4 GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	6.5		13	20	26	39	52	58	65	
802.11n	2412	1	11.95	11.93	11.92	12.28	12.24	12.26	12.23	12.26
802.11n	2437	6	11.81	11.79	11.78	12.14	12.10	12.12	12.09	12.12
802.11n	2462	11	12.05	12.03	12.02	12.38	12.34	12.36	12.33	12.36

**Table 9-30
IEEE 802.11ac Average RF Power**



802.11ac (2.4GHz) Conducted Power [dBm]			
Mode	Freq [MHz]	Channel	Data Rate
			6.5 Mbps
802.11ac	2412	1	11.06
802.11ac	2437	6	10.85
802.11ac	2462	11	11.20

**Table 9-31
IEEE 802.11a Average RF Power**

Mode	Freq [MHz]	Channel	802.11a (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	6		9	12	18	24	36	48	54	
802.11a	5180	36*	13.20	13.12	13.18	12.81	13.32	13.15	13.31	13.16
802.11a	5200	40	13.05	12.97	13.03	12.66	13.17	13.00	13.16	13.01
802.11a	5220	44	13.12	13.04	13.10	12.73	13.24	13.07	13.23	13.08
802.11a	5240	48*	13.32	13.24	13.30	12.93	13.44	13.27	13.43	13.28
802.11a	5260	52*	13.00	13.06	12.93	12.61	13.27	13.06	13.11	13.02
802.11a	5280	56	13.08	13.14	13.01	12.69	13.35	13.14	13.19	13.10
802.11a	5300	60	13.29	13.35	13.22	12.90	13.56	13.35	13.40	13.31
802.11a	5320	64*	13.34	13.40	13.27	12.95	13.58	13.40	13.45	13.36
802.11a	5500	100	12.83	12.67	12.81	12.43	12.99	12.71	12.93	12.99
802.11a	5520	104*	12.93	12.77	12.91	12.53	13.09	12.81	13.03	13.09
802.11a	5540	108	12.92	12.76	12.90	12.52	13.08	12.80	13.02	13.08
802.11a	5560	112	12.94	12.78	12.92	12.54	13.10	12.82	13.04	13.10
802.11a	5580	116*	12.93	12.77	12.91	12.53	13.09	12.81	13.03	13.09
802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5660	132	13.07	12.91	13.05	12.67	13.23	12.95	13.17	13.23
802.11a	5680	136*	13.03	12.87	13.01	12.63	13.19	12.91	13.13	13.19
802.11a	5700	140	12.93	12.77	12.91	12.53	13.09	12.81	13.03	13.09
802.11a	5720	144	12.95	12.79	12.93	12.55	13.11	12.83	13.05	13.11
802.11a	5745	149*	13.17	13.21	13.14	12.72	13.23	13.16	13.10	13.28
802.11a	5765	153	12.61	12.65	12.58	12.16	12.67	12.60	12.54	12.72
802.11a	5785	157*	12.67	12.71	12.64	12.22	12.73	12.66	12.60	12.78
802.11a	5805	161	12.83	12.87	12.80	12.38	12.89	12.82	12.76	12.94
802.11a	5825	165*	12.80	12.84	12.77	12.35	12.86	12.79	12.73	12.91

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power than the default channels, these “required channels” are considered for SAR testing instead of the default channels.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 44 of 77

**Table 9-32
IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	12.06	12.22	12.25	12.39	12.29	12.40	12.35	12.29
802.11n	5200	40	12.11	12.27	12.30	12.44	12.34	12.45	12.40	12.34
802.11n	5220	44	12.17	12.33	12.36	12.50	12.40	12.51	12.46	12.40
802.11n	5240	48	12.15	12.31	12.34	12.48	12.38	12.49	12.44	12.38
802.11n	5260	52	11.93	11.95	12.15	12.24	12.25	12.31	12.27	12.25
802.11n	5280	56	12.11	12.13	12.33	12.42	12.43	12.49	12.45	12.43
802.11n	5300	60	12.01	12.03	12.23	12.32	12.33	12.39	12.35	12.33
802.11n	5320	64	12.09	12.11	12.31	12.40	12.41	12.47	12.43	12.41
802.11n	5500	100	11.57	11.59	11.67	11.79	11.71	11.97	11.96	11.83
802.11n	5520	104	11.51	11.53	11.61	11.73	11.65	11.91	11.90	11.77
802.11n	5540	108	11.62	11.64	11.72	11.84	11.76	12.02	12.01	11.88
802.11n	5560	112	11.55	11.57	11.65	11.77	11.69	11.95	11.94	11.81
802.11n	5580	116	11.61	11.63	11.71	11.83	11.75	12.01	12.00	11.87
802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5660	132	11.65	11.67	11.75	11.87	11.79	12.05	12.04	11.91
802.11n	5680	136	11.84	11.86	11.94	12.06	11.98	12.24	12.23	12.10
802.11n	5700	140	11.57	11.59	11.67	11.79	11.71	11.97	11.96	11.83
802.11n	5720	144	11.44	11.46	11.54	11.66	11.58	11.84	11.83	11.70
802.11n	5745	149	12.16	12.13	12.21	12.19	12.25	12.44	12.24	12.32
802.11n	5765	153	12.09	12.06	12.14	12.12	12.18	12.37	12.17	12.25
802.11n	5785	157	12.02	11.99	12.07	12.05	12.11	12.30	12.10	12.18
802.11n	5805	161	12.01	11.98	12.06	12.04	12.10	12.29	12.09	12.17
802.11n	5825	165	11.82	11.79	11.87	11.85	11.91	12.10	11.90	11.98

**Table 9-33
IEEE 802.11n Average RF Power – 40 MHz Bandwidth**


Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	11.62	11.82	11.57	11.84	11.86	11.83	11.81	11.85
802.11n	5230	46	11.73	11.93	11.68	11.95	11.97	11.94	11.92	11.96
802.11n	5270	54	11.33	11.35	11.11	11.34	11.59	11.53	11.43	11.55
802.11n	5310	62	11.24	11.26	11.02	11.25	11.50	11.44	11.34	11.46
802.11n	5510	102	11.12	11.09	10.95	11.23	11.25	11.23	11.28	11.21
802.11n	5550	110	11.24	11.21	11.07	11.35	11.37	11.35	11.40	11.33
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	11.21	11.18	11.04	11.32	11.34	11.32	11.37	11.30
802.11n	5710	142	11.19	11.16	11.02	11.30	11.32	11.30	11.35	11.28
802.11n	5755	151	11.95	12.09	11.94	12.07	12.02	12.05	11.88	12.04
802.11n	5795	159	11.79	11.93	11.78	11.91	11.86	11.89	11.72	11.88

**Table 9-34
IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**


Mode	Freq [MHz]	Channel	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
			Data Rate [Mbps]									
			29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac	5210	42	11.01	10.88	10.75	11.10	11.15	11.14	11.14	11.17	11.18	11.19
802.11ac	5290	58	11.15	10.93	10.80	11.24	11.06	11.14	11.12	11.09	11.20	11.21
802.11ac	5530	106	11.30	10.96	10.95	11.29	11.52	11.40	11.37	11.09	11.35	11.11
802.11ac	5690	138	11.47	11.27	11.33	11.43	11.46	11.54	11.49	11.45	11.39	11.54
802.11ac	5775	155	11.76	11.63	11.57	11.81	11.90	11.92	11.93	11.94	11.98	11.88

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:



- For 2.4 GHz operations, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n/ac) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For 5 GHz operations, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- Full SAR tests for all IEEE 802.11ac configurations were not required because the average output power was not more than 0.25 dB higher than IEEE 802.11a mode. IEEE 802.11ac was evaluated for the highest IEEE 802.11a position in each 5 GHz band and exposure condition.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.



**Figure 9-5
Power Measurement Setup for Bandwidths < 50 MHz**



**Figure 9-6
Power Measurement Setup for Bandwidths > 50 MHz**

FCC ID: ZNFLS996	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 46 of 77	



10 SYSTEM VERIFICATION

10.1 Tissue Verification

**Table 10-1
Measured Head Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/1/2014	750H	21.0	695	0.858	41.297	0.889	42.227	-3.49%	-2.20%
			710	0.871	41.095	0.890	42.149	-2.13%	-2.50%
			725	0.886	40.905	0.891	42.071	-0.56%	-2.77%
			740	0.900	40.672	0.893	41.994	0.78%	-3.15%
			755	0.912	40.479	0.894	41.916	2.01%	-3.43%
12/3/2014	835H	22.5	820	0.924	40.398	0.899	41.578	2.78%	-2.84%
			835	0.937	40.218	0.900	41.500	4.11%	-3.09%
			850	0.951	40.013	0.916	41.500	3.82%	-3.58%
12/1/2014	1750H	22.0	1710	1.342	39.128	1.348	40.142	-0.45%	-2.53%
			1750	1.382	38.946	1.371	40.079	0.80%	-2.83%
			1790	1.418	38.758	1.394	40.016	1.72%	-3.14%
12/2/2014	1900H	21.9	1850	1.400	39.561	1.400	40.000	0.00%	-1.10%
			1880	1.430	39.411	1.400	40.000	2.14%	-1.47%
			1910	1.462	39.298	1.400	40.000	4.43%	-1.76%
12/3/2014	2450H	24.7	2401	1.798	40.872	1.756	39.287	2.39%	4.03%
			2450	1.856	40.702	1.800	39.200	3.11%	3.83%
			2499	1.912	40.516	1.853	39.138	3.18%	3.52%
12/15/2014	2450H	21.4	2450	1.853	37.946	1.800	39.200	2.94%	-3.20%
			2500	1.898	37.816	1.855	39.136	2.32%	-3.37%
			2550	1.957	37.515	1.909	39.073	2.51%	-3.99%
			2600	2.015	37.393	1.964	39.009	2.60%	-4.14%
			2650	2.064	37.107	2.018	38.945	2.28%	-4.72%
			2700	2.130	36.942	2.073	38.882	2.75%	-4.99%
12/08/2014	5200H-5800H	20.5	5180	4.561	36.252	4.635	36.009	-1.60%	0.67%
			5200	4.581	36.260	4.655	35.986	-1.59%	0.76%
			5220	4.605	36.166	4.676	35.963	-1.52%	0.56%
			5240	4.625	36.168	4.696	35.940	-1.51%	0.63%
			5280	4.664	36.094	4.737	35.894	-1.54%	0.56%
			5300	4.687	36.091	4.758	35.871	-1.49%	0.61%
			5320	4.709	36.025	4.778	35.849	-1.44%	0.49%
			5500	4.887	35.808	4.963	35.643	-1.53%	0.46%
			5520	4.911	35.767	4.983	35.620	-1.44%	0.41%
			5560	4.957	35.728	5.024	35.574	-1.33%	0.43%
			5600	4.988	35.696	5.065	35.529	-1.52%	0.47%
			5660	5.054	35.603	5.127	35.460	-1.42%	0.40%
			5680	5.080	35.584	5.147	35.437	-1.30%	0.41%
			5700	5.091	35.567	5.168	35.414	-1.49%	0.43%
			5745	5.129	35.489	5.214	35.363	-1.63%	0.36%
			5765	5.158	35.477	5.234	35.340	-1.45%	0.39%
			5785	5.185	35.423	5.255	35.317	-1.33%	0.30%
			5800	5.208	35.420	5.270	35.300	-1.18%	0.34%
			5805	5.212	35.376	5.275	35.294	-1.19%	0.23%
			5825	5.228	35.384	5.296	35.271	-1.28%	0.32%



The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 47 of 77	

**Table 10-2
Measured Body Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/1/2014	750B	21.2	695	0.913	54.289	0.959	55.745	-4.80%	-2.61%
			710	0.928	54.152	0.960	55.687	-3.33%	-2.76%
			725	0.942	53.980	0.961	55.629	-1.98%	-2.96%
			740	0.957	53.798	0.963	55.570	-0.62%	-3.19%
			755	0.971	53.670	0.964	55.512	0.73%	-3.32%
12/6/2014	835B	22.3	820	0.945	53.261	0.969	55.258	-2.48%	-3.61%
			835	0.960	53.096	0.970	55.200	-1.03%	-3.81%
			850	0.975	52.951	0.988	55.154	-1.32%	-3.99%
12/1/2014	1750B	21.4	1710	1.462	51.787	1.463	53.537	-0.07%	-3.27%
			1750	1.508	51.603	1.488	53.432	1.34%	-3.42%
			1790	1.551	51.499	1.514	53.326	2.44%	-3.43%
12/1/2014	1900B	21.5	1850	1.454	52.464	1.520	53.300	-4.34%	-1.57%
			1880	1.486	52.357	1.520	53.300	-2.24%	-1.77%
			1910	1.522	52.255	1.520	53.300	0.13%	-1.96%
12/4/2014	1900B	22.1	1850	1.518	52.108	1.520	53.300	-0.13%	-2.24%
			1880	1.556	52.064	1.520	53.300	2.37%	-2.32%
			1910	1.590	51.991	1.520	53.300	4.61%	-2.46%
12/8/2014	1900B	21.8	1850	1.475	51.137	1.520	53.300	-2.96%	-4.06%
			1880	1.509	51.027	1.520	53.300	-0.72%	-4.26%
			1910	1.544	50.921	1.520	53.300	1.58%	-4.46%
12/4/2014	2450B	24.0	2401	1.960	53.506	1.903	52.765	3.00%	1.40%
			2450	2.027	53.326	1.950	52.700	3.95%	1.19%
			2499	2.096	53.170	2.019	52.638	3.81%	1.01%
12/9/2014	2450B	21.7	2450	2.044	51.143	1.950	52.700	4.82%	-2.95%
			2500	2.113	50.968	2.021	52.636	4.55%	-3.17%
			2550	2.182	50.742	2.092	52.573	4.30%	-3.48%
			2600	2.254	50.583	2.163	52.509	4.21%	-3.67%
			2650	2.324	50.348	2.234	52.445	4.03%	-4.00%
			2700	2.401	50.167	2.305	52.382	4.16%	-4.23%
12/02/2014	5200B-5800B	22.2	5200	5.377	48.110	5.299	49.014	1.47%	-1.84%
			5220	5.409	48.063	5.323	48.987	1.62%	-1.89%
			5240	5.444	48.040	5.346	48.960	1.83%	-1.88%
			5280	5.497	47.947	5.393	48.906	1.93%	-1.96%
			5300	5.512	47.873	5.416	48.879	1.77%	-2.06%
			5320	5.547	47.790	5.439	48.851	1.99%	-2.17%
			5600	5.983	47.092	5.766	48.471	3.76%	-2.85%
			5660	6.077	47.002	5.837	48.390	4.11%	-2.87%
			5680	6.094	46.949	5.860	48.363	3.99%	-2.92%
			5700	6.134	46.858	5.883	48.336	4.27%	-3.06%
			5745	6.212	46.786	5.936	48.275	4.65%	-3.08%
			5765	6.249	46.746	5.959	48.248	4.87%	-3.11%
			5785	6.260	46.710	5.982	48.220	4.65%	-3.13%
5800	6.277	46.667	6.000	48.200	4.62%	-3.18%			

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 48 of 77

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
B	750	HEAD	12/01/2014	22.8	21.0	0.100	1046	3318	0.821	8.270	8.210	-0.73%
E	835	HEAD	12/03/2014	23.6	22.5	0.100	4d119	3332	0.884	9.220	8.840	-4.12%
J	1750	HEAD	12/01/2014	24.0	22.0	0.100	1008	3022	3.480	36.900	34.800	-5.69%
B	1900	HEAD	12/02/2014	22.2	21.9	0.100	5d148	3318	3.780	40.700	37.800	-7.13%
B	2450	HEAD	12/03/2014	24.1	24.7	0.100	882	3318	5.040	52.000	50.400	-3.08%
G	2450	HEAD	12/15/2014	24.5	22.6	0.100	797	3258	5.630	51.800	56.300	8.69%
G	2600	HEAD	12/15/2014	24.5	22.6	0.100	1004	3258	5.870	57.300	58.700	2.44%
A	5200	HEAD	12/08/2014	22.4	20.5	0.100	1120	3914	7.500	79.100	75.000	-5.18%
A	5300	HEAD	12/08/2014	22.4	20.5	0.100	1120	3914	7.850	83.400	78.500	-5.88%
A	5500	HEAD	12/08/2014	22.4	20.5	0.100	1120	3914	8.000	84.900	80.000	-5.77%
A	5600	HEAD	12/08/2014	22.4	20.5	0.100	1120	3914	8.000	82.200	80.000	-2.68%
A	5800	HEAD	12/08/2014	22.4	20.5	0.100	1120	3914	7.600	79.100	76.000	-3.92%
B	750	BODY	12/01/2014	22.9	21.1	0.100	1046	3318	0.902	8.540	9.020	5.62%
C	835	BODY	12/06/2014	21.0	22.3	0.100	4d132	3333	1.030	9.580	10.300	7.52%
J	1750	BODY	12/01/2014	22.9	22.2	0.100	1008	3022	3.640	37.600	36.400	-3.19%
C	1900	BODY	12/01/2014	23.5	21.5	0.100	5d148	3333	4.190	39.300	41.900	6.62%
J	1900	BODY	12/04/2014	22.1	22.1	0.100	5d141	3022	3.900	40.600	39.000	-3.94%
B	1900	BODY	12/08/2014	22.5	21.8	0.100	5d148	3318	3.930	39.300	39.300	0.00%
H	2450	BODY	12/04/2014	24.5	24.0	0.100	797	3319	4.780	49.400	47.800	-3.24%
E	2450	BODY	12/09/2014	24.3	21.9	0.100	797	3332	5.290	49.400	52.900	7.09%
E	2600	BODY	12/09/2014	24.3	21.9	0.100	1004	3332	6.120	56.700	61.200	7.94%
I	5200	BODY	12/02/2014	24.5	22.2	0.100	1191	3589	7.240	77.800	72.400	-6.94%
I	5300	BODY	12/02/2014	24.5	22.1	0.100	1191	3589	7.710	79.900	77.100	-3.50%
I	5600	BODY	12/02/2014	24.2	22.2	0.100	1191	3589	8.100	84.100	81.000	-3.69%
I	5800	BODY	12/02/2014	24.4	22.2	0.100	1191	3589	7.210	78.000	72.100	-7.56%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: ZNFLS996	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 49 of 77

11 SAR DATA SUMMARY



11.1 Standalone Head SAR Data

**Table 11-1
CDMA BC10 (§90S) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.4	25.20	0.00	Right	Cheek	089498624600002352	1:1	0.494	1.047	0.517	A1
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.4	25.20	0.12	Right	Tilt	089498624600002352	1:1	0.336	1.047	0.352	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.4	25.20	0.07	Left	Cheek	089498624600002352	1:1	0.481	1.047	0.504	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.4	25.20	0.09	Left	Tilt	089498624600002352	1:1	0.305	1.047	0.319	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.4	25.15	0.00	Right	Cheek	089498624600002352	1:1	0.407	1.059	0.431	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.4	25.15	0.10	Right	Tilt	089498624600002352	1:1	0.262	1.059	0.277	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.4	25.15	0.11	Left	Cheek	089498624600002352	1:1	0.423	1.059	0.448	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.4	25.15	0.09	Left	Tilt	089498624600002352	1:1	0.268	1.059	0.284	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-2
CDMA BC0 (§22H) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.45	0.06	Right	Cheek	089498624600002352	1:1	0.466	1.059	0.493	A2
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.45	0.10	Right	Tilt	089498624600002352	1:1	0.281	1.059	0.298	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.45	0.09	Left	Cheek	089498624600002352	1:1	0.391	1.059	0.414	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	24.7	24.45	0.14	Left	Tilt	089498624600002352	1:1	0.226	1.059	0.239	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.07	Right	Cheek	089498624600002352	1:1	0.436	1.021	0.445	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.10	Right	Tilt	089498624600002352	1:1	0.248	1.021	0.253	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.12	Left	Cheek	089498624600002352	1:1	0.409	1.021	0.418	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	24.7	24.61	0.09	Left	Tilt	089498624600002352	1:1	0.232	1.021	0.237	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 50 of 77

**Table 11-3
PCS CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.33	0.14	Right	Cheek	089498624600002352	1:1	0.615	1.089	0.670	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.33	0.16	Right	Tilt	089498624600002352	1:1	0.182	1.089	0.198	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.33	-0.03	Left	Cheek	089498624600002352	1:1	0.245	1.089	0.267	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.33	0.19	Left	Tilt	089498624600002352	1:1	0.207	1.089	0.225	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.06	Right	Cheek	089498624600002352	1:1	0.631	1.045	0.659	A3
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	-0.01	Right	Tilt	089498624600002352	1:1	0.185	1.045	0.193	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.04	Left	Cheek	089498624600002352	1:1	0.258	1.045	0.270	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.10	Left	Tilt	089498624600002352	1:1	0.193	1.045	0.202	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-4
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.2	33.11	0.06	Right	Cheek	089498624600002354	1	1:8.3	0.332	1.021	0.339	
836.60	190	GSM 850	GSM	33.2	33.11	0.04	Right	Tilt	089498624600002354	1	1:8.3	0.207	1.021	0.211	
836.60	190	GSM 850	GSM	33.2	33.11	0.09	Left	Cheek	089498624600002354	1	1:8.3	0.305	1.021	0.311	
836.60	190	GSM 850	GSM	33.2	33.11	0.04	Left	Tilt	089498624600002354	1	1:8.3	0.194	1.021	0.198	
836.60	190	GSM 850	GPRS	31.2	31.19	-0.02	Right	Cheek	089498624600002354	2	1:4.15	0.390	1.002	0.391	A4
836.60	190	GSM 850	GPRS	31.2	31.19	0.09	Right	Tilt	089498624600002354	2	1:4.15	0.239	1.002	0.239	
836.60	190	GSM 850	GPRS	31.2	31.19	0.11	Left	Cheek	089498624600002354	2	1:4.15	0.351	1.002	0.352	
836.60	190	GSM 850	GPRS	31.2	31.19	0.11	Left	Tilt	089498624600002354	2	1:4.15	0.234	1.002	0.234	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-5
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.7	29.92	0.18	Right	Cheek	089498624600002353	1	1:8.3	0.235	1.197	0.281	
1880.00	661	GSM 1900	GSM	30.7	29.92	-0.09	Right	Tilt	089498624600002353	1	1:8.3	0.074	1.197	0.089	
1880.00	661	GSM 1900	GSM	30.7	29.92	0.05	Left	Cheek	089498624600002353	1	1:8.3	0.097	1.197	0.116	
1880.00	661	GSM 1900	GSM	30.7	29.92	0.01	Left	Tilt	089498624600002353	1	1:8.3	0.081	1.197	0.097	
1880.00	661	GSM 1900	GPRS	28.7	28.15	0.18	Right	Cheek	089498624600002353	2	1:4.15	0.334	1.135	0.379	A5
1880.00	661	GSM 1900	GPRS	28.7	28.15	-0.11	Right	Tilt	089498624600002353	2	1:4.15	0.087	1.135	0.099	
1880.00	661	GSM 1900	GPRS	28.7	28.15	-0.19	Left	Cheek	089498624600002353	2	1:4.15	0.128	1.135	0.145	
1880.00	661	GSM 1900	GPRS	28.7	28.15	0.04	Left	Tilt	089498624600002353	2	1:4.15	0.092	1.135	0.104	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-6
UMTS 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.02	Right	Cheek	08949862460002354	1:1	0.373	1.007	0.376	A6
836.60	4183	UMTS 850	RMC	23.7	23.67	0.08	Right	Tilt	08949862460002354	1:1	0.211	1.007	0.212	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.06	Left	Cheek	08949862460002354	1:1	0.312	1.007	0.314	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.09	Left	Tilt	08949862460002354	1:1	0.192	1.007	0.193	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-7
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	0.10	Right	Cheek	08949862460002353	1:1	0.565	1.009	0.570	A7
1880.00	9400	UMTS 1900	RMC	23.7	23.66	0.06	Right	Tilt	08949862460002353	1:1	0.170	1.009	0.172	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	-0.08	Left	Cheek	08949862460002353	1:1	0.250	1.009	0.252	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	-0.04	Left	Tilt	08949862460002353	1:1	0.166	1.009	0.167	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-8
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	-0.02	0	Right	Cheek	QPSK	1	0	08949862460002344	1:1	0.226	1.045	0.236	A8
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.05	1	Right	Cheek	QPSK	25	12	08949862460002344	1:1	0.183	1.012	0.185	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	-0.12	0	Right	Tilt	QPSK	1	0	08949862460002344	1:1	0.122	1.045	0.127	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.08	1	Right	Tilt	QPSK	25	12	08949862460002344	1:1	0.116	1.012	0.117	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	0.02	0	Left	Cheek	QPSK	1	0	08949862460002344	1:1	0.152	1.045	0.159	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.04	1	Left	Cheek	QPSK	25	12	08949862460002344	1:1	0.139	1.012	0.141	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	0.03	0	Left	Tilt	QPSK	1	0	08949862460002344	1:1	0.096	1.045	0.100	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.10	1	Left	Tilt	QPSK	25	12	08949862460002344	1:1	0.094	1.012	0.095	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram												

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 52 of 77

**Table 11-9
LTE Band 26 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	-0.03	0	Right	Cheek	QPSK	1	0	089498624600002344	1:1	0.405	1.005	0.407	A9
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.10	1	Right	Cheek	QPSK	36	0	089498624600002344	1:1	0.308	1.016	0.313	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	0.13	0	Right	Tilt	QPSK	1	0	089498624600002344	1:1	0.271	1.005	0.272	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.13	1	Right	Tilt	QPSK	36	0	089498624600002344	1:1	0.197	1.016	0.200	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	0.14	0	Left	Cheek	QPSK	1	0	089498624600002344	1:1	0.377	1.005	0.379	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.08	1	Left	Cheek	QPSK	36	0	089498624600002344	1:1	0.290	1.016	0.295	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	0.03	0	Left	Tilt	QPSK	1	0	089498624600002344	1:1	0.232	1.005	0.233	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.11	1	Left	Tilt	QPSK	36	0	089498624600002344	1:1	0.190	1.016	0.193	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-10
LTE Band 4 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.10	0	Right	Cheek	QPSK	1	0	089498624600002344	1:1	0.391	1.033	0.404	A10
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	-0.01	1	Right	Cheek	QPSK	50	0	089498624600002344	1:1	0.339	1.012	0.343	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	-0.09	0	Right	Tilt	QPSK	1	0	089498624600002344	1:1	0.158	1.033	0.163	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	-0.20	1	Right	Tilt	QPSK	50	0	089498624600002344	1:1	0.146	1.012	0.148	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.05	0	Left	Cheek	QPSK	1	0	089498624600002344	1:1	0.129	1.033	0.133	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	0.09	1	Left	Cheek	QPSK	50	0	089498624600002344	1:1	0.126	1.012	0.128	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.21	0	Left	Tilt	QPSK	1	0	089498624600002344	1:1	0.148	1.033	0.153	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	-0.01	1	Left	Tilt	QPSK	50	0	089498624600002344	1:1	0.137	1.012	0.139	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-11
LTE Band 25 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	-0.07	0	Right	Cheek	QPSK	1	50	089498624600002345	1:1	0.434	1.002	0.435	A11
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.02	1	Right	Cheek	QPSK	50	50	089498624600002345	1:1	0.323	1.002	0.324	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.04	0	Right	Tilt	QPSK	1	50	089498624600002345	1:1	0.166	1.002	0.166	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	-0.10	1	Right	Tilt	QPSK	50	50	089498624600002345	1:1	0.099	1.002	0.099	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.03	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1	0.205	1.002	0.205	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.07	1	Left	Cheek	QPSK	50	50	089498624600002345	1:1	0.104	1.002	0.104	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.03	0	Left	Tilt	QPSK	1	50	089498624600002345	1:1	0.153	1.002	0.153	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.07	1	Left	Tilt	QPSK	50	50	089498624600002345	1:1	0.115	1.002	0.115	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-12
LTE Band 41 Head SAR**



MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor (Cond. Power)	Scaling Factor (CP Duty)	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.														(W/kg)					
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.02	0	Right	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.240	1.000	1.010	0.242	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.06	1	Right	Cheek	QPSK	50	25	089498624600002345	1:1.59	0.185	1.000	1.010	0.187	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.01	0	Right	Tilt	QPSK	1	50	089498624600002345	1:1.59	0.201	1.000	1.010	0.203	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.05	1	Right	Tilt	QPSK	50	25	089498624600002345	1:1.59	0.145	1.000	1.010	0.146	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.05	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.626	1.000	1.010	0.632	
2549.50	40185	Low-Mid	LTE Band 41	20	24.2	24.11	0.00	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.590	1.021	1.010	0.608	
2593.00	40620	Mid	LTE Band 41	20	24.2	24.18	-0.05	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.680	1.005	1.010	0.690	A12
2636.50	41055	Mid-High	LTE Band 41	20	24.2	24.19	-0.04	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.538	1.002	1.010	0.544	
2680.00	41490	High	LTE Band 41	20	24.2	24.19	-0.02	0	Left	Cheek	QPSK	1	50	089498624600002345	1:1.59	0.653	1.002	1.010	0.661	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.15	1	Left	Cheek	QPSK	50	25	089498624600002345	1:1.59	0.506	1.000	1.010	0.511	
2680.00	41490	High	LTE Band 41	20	23.2	23.19	0.02	1	Left	Cheek	QPSK	100	0	089498624600002345	1:1.59	0.527	1.002	1.010	0.533	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.02	0	Left	Tilt	QPSK	1	50	089498624600002345	1:1.59	0.177	1.000	1.010	0.179	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.00	1	Left	Tilt	QPSK	50	25	089498624600002345	1:1.59	0.135	1.000	1.010	0.136	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-13
DTS Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.											(W/kg)			
2462	11	IEEE 802.11b	DSSS	14.5	13.57	0.13	Right	Cheek	089498624600002355	1	1:1	0.516	1.239	0.639	A13
2462	11	IEEE 802.11b	DSSS	14.5	13.57	0.14	Right	Tilt	089498624600002355	1	1:1	0.376	1.239	0.466	
2462	11	IEEE 802.11b	DSSS	14.5	13.57	-0.01	Left	Cheek	089498624600002355	1	1:1	0.202	1.239	0.250	
2462	11	IEEE 802.11b	DSSS	14.5	13.57	-0.09	Left	Tilt	089498624600002355	1	1:1	0.174	1.239	0.216	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram					

**Table 11-14
NII Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5180	36	IEEE 802.11a	OFDM	14.5	13.20	0.18	Right	Cheek	089498624600002355	6	1:1	0.494	1.349	0.666	
5240	48	IEEE 802.11a	OFDM	14.5	13.32	0.19	Right	Cheek	089498624600002355	6	1:1	0.490	1.312	0.643	
5210	42	IEEE 802.11ac	OFDM	12.5	11.01	-0.06	Right	Cheek	089498624600002355	29.3	1:1	0.316	1.409	0.445	
5180	36	IEEE 802.11a	OFDM	14.5	13.20	0.07	Right	Tilt	089498624600002355	6	1:1	0.396	1.349	0.534	
5240	48	IEEE 802.11a	OFDM	14.5	13.32	0.18	Right	Tilt	089498624600002355	6	1:1	0.402	1.312	0.527	
5240	48	IEEE 802.11a	OFDM	14.5	13.32	0.02	Left	Cheek	089498624600002355	6	1:1	0.351	1.312	0.461	
5240	48	IEEE 802.11a	OFDM	14.5	13.32	0.06	Left	Tilt	089498624600002355	6	1:1	0.240	1.312	0.315	
5280	56	IEEE 802.11a	OFDM	14.5	13.08	0.17	Right	Cheek	089498624600002355	6	1:1	0.455	1.387	0.631	
5320	64	IEEE 802.11a	OFDM	14.5	13.34	0.16	Right	Cheek	089498624600002355	6	1:1	0.462	1.306	0.603	
5290	58	IEEE 802.11ac	OFDM	12.5	11.15	-0.02	Right	Cheek	089498624600002355	29.3	1:1	0.275	1.365	0.375	
5280	56	IEEE 802.11a	OFDM	14.5	13.08	0.21	Right	Tilt	089498624600002355	6	1:1	0.375	1.387	0.520	
5320	64	IEEE 802.11a	OFDM	14.5	13.34	0.03	Right	Tilt	089498624600002355	6	1:1	0.383	1.306	0.500	
5320	64	IEEE 802.11a	OFDM	14.5	13.34	0.13	Left	Cheek	089498624600002355	6	1:1	0.322	1.306	0.421	
5320	64	IEEE 802.11a	OFDM	14.5	13.34	-0.12	Left	Tilt	089498624600002355	6	1:1	0.261	1.306	0.341	
5520	104	IEEE 802.11a	OFDM	14.5	12.93	0.11	Right	Cheek	089498624600002355	6	1:1	0.488	1.435	0.700	
5560	112	IEEE 802.11a	OFDM	14.5	12.94	0.04	Right	Cheek	089498624600002355	6	1:1	0.486	1.432	0.696	
5660	132	IEEE 802.11a	OFDM	14.5	13.07	0.16	Right	Cheek	089498624600002355	6	1:1	0.536	1.390	0.745	A14
5690	138	IEEE 802.11ac	OFDM	12.5	11.47	0.18	Right	Cheek	089498624600002355	29.3	1:1	0.282	1.268	0.358	
5520	104	IEEE 802.11a	OFDM	14.5	12.93	0.16	Right	Tilt	089498624600002355	6	1:1	0.392	1.435	0.563	
5560	112	IEEE 802.11a	OFDM	14.5	12.94	0.18	Right	Tilt	089498624600002355	6	1:1	0.455	1.432	0.652	
5660	132	IEEE 802.11a	OFDM	14.5	13.07	0.07	Right	Tilt	089498624600002355	6	1:1	0.469	1.390	0.652	
5520	104	IEEE 802.11a	OFDM	14.5	12.93	0.06	Left	Cheek	089498624600002355	6	1:1	0.388	1.435	0.557	
5560	112	IEEE 802.11a	OFDM	14.5	12.94	0.12	Left	Cheek	089498624600002355	6	1:1	0.377	1.432	0.540	
5660	132	IEEE 802.11a	OFDM	14.5	13.07	-0.01	Left	Cheek	089498624600002355	6	1:1	0.411	1.390	0.571	
5660	132	IEEE 802.11a	OFDM	14.5	13.07	0.12	Left	Tilt	089498624600002355	6	1:1	0.330	1.390	0.459	
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.04	Right	Cheek	089498624600002355	6	1:1	0.505	1.358	0.686	
5805	161	IEEE 802.11a	OFDM	14.5	12.83	0.12	Right	Cheek	089498624600002355	6	1:1	0.490	1.469	0.720	
5825	165	IEEE 802.11a	OFDM	14.5	12.80	0.05	Right	Cheek	089498624600002355	6	1:1	0.445	1.479	0.658	
5775	155	IEEE 802.11ac	OFDM	12.5	11.76	-0.04	Right	Cheek	089498624600002355	29.3	1:1	0.246	1.186	0.292	
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.20	Right	Tilt	089498624600002355	6	1:1	0.426	1.358	0.579	
5805	161	IEEE 802.11a	OFDM	14.5	12.83	0.13	Right	Tilt	089498624600002355	6	1:1	0.408	1.469	0.599	
5825	165	IEEE 802.11a	OFDM	14.5	12.80	0.07	Right	Tilt	089498624600002355	6	1:1	0.433	1.479	0.640	
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.17	Left	Cheek	089498624600002355	6	1:1	0.480	1.358	0.652	
5805	161	IEEE 802.11a	OFDM	14.5	12.83	0.03	Left	Cheek	089498624600002355	6	1:1	0.461	1.469	0.677	
5825	165	IEEE 802.11a	OFDM	14.5	12.80	0.19	Left	Cheek	089498624600002355	6	1:1	0.449	1.479	0.664	
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.14	Left	Tilt	089498624600002355	6	1:1	0.375	1.358	0.509	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 55 of 77

11.2 Standalone Body-Worn SAR Data

**Table 11-15
CDMA/GSM/UMTS Body-Worn SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	TDSO / SO32	25.4	25.21	-0.10	8 mm	089498624600002352	N/A	1:1	back	0.672	1.045	0.702	A15
836.52	384	CDMA BC0 (§22H)	TDSO / SO32	24.7	24.54	0.01	8 mm	089498624600002352	N/A	1:1	back	0.549	1.038	0.570	A17
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.67	0.04	8 mm	089498624600002352	N/A	1:1	back	0.711	1.007	0.716	A19
836.60	190	GSM 850	GSM	33.2	33.11	0.00	8 mm	089498624600002353	1	1:8.3	back	0.383	1.021	0.391	
836.60	190	GSM 850	GPRS	31.2	31.19	0.00	8 mm	089498624600002353	2	1:4.15	back	0.473	1.002	0.474	A21
1880.00	661	GSM 1900	GSM	30.7	29.92	0.07	8 mm	089498624600002353	1	1:8.3	back	0.300	1.197	0.359	
1880.00	661	GSM 1900	GPRS	28.7	28.15	-0.12	8 mm	089498624600002353	2	1:4.15	back	0.365	1.135	0.414	A23
836.60	4183	UMTS 850	RMC	23.7	23.67	0.01	8 mm	089498624600002353	N/A	1:1	back	0.450	1.007	0.453	A25
1880.00	9400	UMTS 1900	RMC	23.7	23.66	-0.02	8 mm	089498624600002353	N/A	1:1	back	0.538	1.009	0.543	A26
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-16
LTE Body-Worn SAR**

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor (Cond. Power)	Scaling Factor (CP Duty)	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)			(W/kg)		
707.50	23095	Md	LTE Band 12	10	23.7	23.51	0.03	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.347	1.045	N/A	0.363	A28
707.50	23095	Md	LTE Band 12	10	22.7	22.65	0.01	1	089498624600002344	QPSK	25	12	8 mm	back	1:1	0.285	1.012	N/A	0.288	
836.50	26915	Md	LTE Band 26 (Cell)	15	24.2	24.18	0.02	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.564	1.005	N/A	0.567	A29
836.50	26915	Md	LTE Band 26 (Cell)	15	23.2	23.13	0.08	1	089498624600002344	QPSK	36	0	8 mm	back	1:1	0.394	1.016	N/A	0.400	
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.2	24.06	0.01	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.491	1.033	N/A	0.507	A30
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.2	23.15	-0.03	1	089498624600002344	QPSK	50	0	8 mm	back	1:1	0.432	1.012	N/A	0.437	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.02	0	089498624600002345	QPSK	1	50	8 mm	back	1:1	0.735	1.002	N/A	0.736	A31
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.02	1	089498624600002345	QPSK	50	50	8 mm	back	1:1	0.562	1.002	N/A	0.563	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.01	0	089498624600002345	QPSK	1	50	8 mm	back	1:1.59	0.421	1.000	1.010	0.425	A32
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.02	1	089498624600002345	QPSK	50	25	8 mm	back	1:1.59	0.352	1.000	1.010	0.356	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram													

**Table 11-17
DTS Body-Worn SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	14.5	13.57	0.17	8 mm	089498624600002355	1	back	1:1	0.070	1.239	0.087	A34
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-18
NII Body-Worn SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.														
5240	48	IEEE 802.11a	OFDM	14.5	13.32	0.01	8 mm	089498624600002355	6	back	1:1	0.125	1.312	0.164	
5210	42	IEEE 802.11ac	OFDM	12.5	11.01	0.18	8 mm	089498624600002355	29.3	back	1:1	0.082	1.409	0.116	
5320	64	IEEE 802.11a	OFDM	14.5	13.34	-0.20	8 mm	089498624600002355	6	back	1:1	0.138	1.306	0.180	
5290	58	IEEE 802.11ac	OFDM	12.5	11.15	0.14	8 mm	089498624600002355	29.3	back	1:1	0.105	1.365	0.143	
5660	132	IEEE 802.11a	OFDM	14.5	13.07	0.16	8 mm	089498624600002355	6	back	1:1	0.204	1.390	0.284	A36
5690	138	IEEE 802.11ac	OFDM	12.5	11.47	0.18	8 mm	089498624600002355	29.3	back	1:1	0.165	1.268	0.209	
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.17	8 mm	089498624600002355	6	back	1:1	0.200	1.358	0.272	
5775	155	IEEE 802.11ac	OFDM	12.5	11.76	0.13	8 mm	089498624600002355	29.3	back	1:1	0.142	1.186	0.168	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

11.3 Standalone Wireless Router SAR Data

**Table 11-19
GPRS/UMTS/CDMA Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.														
820.10	564	CDMABC10 (§90S)	EVDO Rev. 0	25.4	25.21	-0.05	8 mm	089498624600002352	N/A	1:1	back	0.590	1.045	0.617	A16
820.10	564	CDMABC10 (§90S)	EVDO Rev. 0	25.4	25.21	-0.07	8 mm	089498624600002352	N/A	1:1	front	0.465	1.045	0.486	
820.10	564	CDMABC10 (§90S)	EVDO Rev. 0	25.4	25.21	-0.06	10 mm	089498624600002352	N/A	1:1	bottom	0.366	1.045	0.382	
820.10	564	CDMABC10 (§90S)	EVDO Rev. 0	25.4	25.21	0.05	10 mm	089498624600002352	N/A	1:1	right	0.570	1.045	0.596	
820.10	564	CDMABC10 (§90S)	EVDO Rev. 0	25.4	25.21	0.02	10 mm	089498624600002352	N/A	1:1	left	0.482	1.045	0.504	
836.52	384	CDMABC0 (§22H)	EVDO Rev. 0	24.7	24.62	0.00	8 mm	089498624600002352	N/A	1:1	back	0.557	1.019	0.568	A18
836.52	384	CDMABC0 (§22H)	EVDO Rev. 0	24.7	24.62	-0.02	8 mm	089498624600002352	N/A	1:1	front	0.487	1.019	0.496	
836.52	384	CDMABC0 (§22H)	EVDO Rev. 0	24.7	24.62	-0.01	10 mm	089498624600002352	N/A	1:1	bottom	0.395	1.019	0.403	
836.52	384	CDMABC0 (§22H)	EVDO Rev. 0	24.7	24.62	-0.14	10 mm	089498624600002352	N/A	1:1	right	0.532	1.019	0.542	
836.52	384	CDMABC0 (§22H)	EVDO Rev. 0	24.7	24.62	-0.01	10 mm	089498624600002352	N/A	1:1	left	0.441	1.019	0.449	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	-0.02	8 mm	089498624600002352	N/A	1:1	back	0.874	1.030	0.694	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.58	-0.14	8 mm	089498624600002352	N/A	1:1	front	0.586	1.028	0.602	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	0.17	8 mm	089498624600002352	N/A	1:1	front	0.871	1.030	0.897	A20
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.49	-0.02	8 mm	089498624600002352	N/A	1:1	front	0.644	1.050	0.676	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	0.02	10 mm	089498624600002352	N/A	1:1	bottom	0.589	1.030	0.607	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	-0.01	10 mm	089498624600002352	N/A	1:1	right	0.527	1.030	0.543	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	-0.04	10 mm	089498624600002352	N/A	1:1	left	0.134	1.030	0.138	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.57	-0.01	8 mm	089498624600002352	N/A	1:1	front	0.822	1.030	0.847	
836.60	190	GSM 850	GPRS	31.2	31.19	0.00	8 mm	089498624600002353	2	14.15	back	0.473	1.002	0.474	
836.60	190	GSM 850	GPRS	31.2	31.19	0.09	8 mm	089498624600002353	2	14.15	front	0.613	1.002	0.614	A22
836.60	190	GSM 850	GPRS	31.2	31.19	0.08	10 mm	089498624600002353	2	14.15	bottom	0.428	1.002	0.429	
836.60	190	GSM 850	GPRS	31.2	31.19	-0.12	10 mm	089498624600002353	2	14.15	right	0.483	1.002	0.484	
836.60	190	GSM 850	GPRS	31.2	31.19	-0.04	10 mm	089498624600002353	2	14.15	left	0.397	1.002	0.398	
1880.00	661	GSM 1900	GPRS	28.7	28.15	-0.12	8 mm	089498624600002353	2	14.15	back	0.365	1.135	0.414	
1880.00	661	GSM 1900	GPRS	28.7	28.15	0.02	8 mm	089498624600002353	2	14.15	front	0.422	1.135	0.479	A24
1880.00	661	GSM 1900	GPRS	28.7	28.15	0.02	10 mm	089498624600002353	2	14.15	bottom	0.239	1.135	0.271	
1880.00	661	GSM 1900	GPRS	28.7	28.15	0.16	10 mm	089498624600002353	2	14.15	right	0.260	1.135	0.295	
1880.00	661	GSM 1900	GPRS	28.7	28.15	-0.15	10 mm	089498624600002353	2	14.15	left	0.034	1.135	0.039	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.01	8 mm	089498624600002353	N/A	1:1	back	0.450	1.007	0.453	A25
836.60	4183	UMTS 850	RMC	23.7	23.67	-0.06	8 mm	089498624600002353	N/A	1:1	front	0.372	1.007	0.375	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.03	10 mm	089498624600002353	N/A	1:1	bottom	0.315	1.007	0.317	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.02	10 mm	089498624600002353	N/A	1:1	right	0.435	1.007	0.438	
836.60	4183	UMTS 850	RMC	23.7	23.67	0.02	10 mm	089498624600002353	N/A	1:1	left	0.358	1.007	0.361	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	-0.02	8 mm	089498624600002353	N/A	1:1	back	0.538	1.009	0.543	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	0.05	8 mm	089498624600002353	N/A	1:1	front	0.641	1.009	0.647	A27
1880.00	9400	UMTS 1900	RMC	23.7	23.66	0.07	10 mm	089498624600002353	N/A	1:1	bottom	0.492	1.009	0.496	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	-0.03	10 mm	089498624600002353	N/A	1:1	right	0.418	1.009	0.422	
1880.00	9400	UMTS 1900	RMC	23.7	23.66	0.00	10 mm	089498624600002353	N/A	1:1	left	0.147	1.009	0.148	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-20
LTE Band 12 Hotspot SAR Data**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	0.03	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.347	1.045	0.363	A28
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.01	1	089498624600002344	QPSK	25	12	8 mm	back	1:1	0.285	1.012	0.288	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	-0.02	0	089498624600002344	QPSK	1	0	8 mm	front	1:1	0.290	1.045	0.303	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.01	1	089498624600002344	QPSK	25	12	8 mm	front	1:1	0.234	1.012	0.237	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	-0.02	0	089498624600002344	QPSK	1	0	10 mm	bottom	1:1	0.117	1.045	0.122	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.11	1	089498624600002344	QPSK	25	12	10 mm	bottom	1:1	0.087	1.012	0.088	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	0.05	0	089498624600002344	QPSK	1	0	10 mm	right	1:1	0.303	1.045	0.317	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	-0.06	1	089498624600002344	QPSK	25	12	10 mm	right	1:1	0.242	1.012	0.245	
707.50	23095	Mid	LTE Band 12	10	23.7	23.51	-0.18	0	089498624600002344	QPSK	1	0	10 mm	left	1:1	0.148	1.045	0.155	
707.50	23095	Mid	LTE Band 12	10	22.7	22.65	0.13	1	089498624600002344	QPSK	25	12	10 mm	left	1:1	0.123	1.012	0.124	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-21
LTE Band 26 (Cell) Hotspot SAR Data**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	0.02	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.564	1.005	0.567	A29
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.08	1	089498624600002344	QPSK	36	0	8 mm	back	1:1	0.394	1.016	0.400	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	-0.03	0	089498624600002344	QPSK	1	0	8 mm	front	1:1	0.469	1.005	0.471	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	-0.01	1	089498624600002344	QPSK	36	0	8 mm	front	1:1	0.339	1.016	0.344	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	-0.05	0	089498624600002344	QPSK	1	0	10 mm	bottom	1:1	0.388	1.005	0.390	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	-0.01	1	089498624600002344	QPSK	36	0	10 mm	bottom	1:1	0.300	1.016	0.305	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	-0.01	0	089498624600002344	QPSK	1	0	10 mm	right	1:1	0.490	1.005	0.492	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	-0.09	1	089498624600002344	QPSK	36	0	10 mm	right	1:1	0.347	1.016	0.353	
836.50	26915	Mid	LTE Band 26 (Cell)	15	24.2	24.18	-0.01	0	089498624600002344	QPSK	1	0	10 mm	left	1:1	0.378	1.005	0.380	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.2	23.13	0.00	1	089498624600002344	QPSK	36	0	10 mm	left	1:1	0.279	1.016	0.283	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-22
LTE Band 4 (AWS) Hotspot SAR Data**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.01	0	089498624600002344	QPSK	1	0	8 mm	back	1:1	0.491	1.033	0.507	A30
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	-0.03	1	089498624600002344	QPSK	50	0	8 mm	back	1:1	0.432	1.012	0.437	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.01	0	089498624600002344	QPSK	1	0	8 mm	front	1:1	0.354	1.033	0.366	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	0.13	1	089498624600002344	QPSK	50	0	8 mm	front	1:1	0.322	1.012	0.326	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.11	0	089498624600002344	QPSK	1	0	10 mm	bottom	1:1	0.172	1.033	0.178	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	0.06	1	089498624600002344	QPSK	50	0	10 mm	bottom	1:1	0.149	1.012	0.151	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	0.12	0	089498624600002344	QPSK	1	0	10 mm	right	1:1	0.227	1.033	0.234	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	-0.05	1	089498624600002344	QPSK	50	0	10 mm	right	1:1	0.239	1.012	0.242	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.2	24.06	-0.06	0	089498624600002344	QPSK	1	0	10 mm	left	1:1	0.063	1.033	0.065	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.2	23.15	0.07	1	089498624600002344	QPSK	50	0	10 mm	left	1:1	0.046	1.012	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-23
LTE Band 25 (PCS) Hotspot SAR Data**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.02	0	089498624600002345	QPSK	1	50	8 mm	back	1:1	0.735	1.002	0.736	A31
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.02	1	089498624600002345	QPSK	50	50	8 mm	back	1:1	0.562	1.002	0.563	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	-0.03	0	089498624600002345	QPSK	1	50	8 mm	front	1:1	0.602	1.002	0.603	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.05	1	089498624600002345	QPSK	50	50	8 mm	front	1:1	0.434	1.002	0.435	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	-0.02	0	089498624600002345	QPSK	1	50	10 mm	bottom	1:1	0.426	1.002	0.427	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.00	1	089498624600002345	QPSK	50	50	10 mm	bottom	1:1	0.325	1.002	0.326	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	-0.09	0	089498624600002345	QPSK	1	50	10 mm	right	1:1	0.473	1.002	0.474	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.04	1	089498624600002345	QPSK	50	50	10 mm	right	1:1	0.328	1.002	0.329	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.2	24.19	0.03	0	089498624600002345	QPSK	1	50	10 mm	left	1:1	0.115	1.002	0.115	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.2	23.19	0.00	1	089498624600002345	QPSK	50	50	10 mm	left	1:1	0.069	1.002	0.069	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-24
LTE Band 41 Hotspot SAR Data**

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor (Cond. Power)	Scaling Factor (CP Duty)	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																			
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.01	0	089498624600002345	QPSK	1	50	8 mm	back	1:1.59	0.421	1.000	1.010	0.425	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.02	1	089498624600002345	QPSK	50	25	8 mm	back	1:1.59	0.352	1.000	1.010	0.356	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.02	0	089498624600002345	QPSK	1	50	8 mm	front	1:1.59	0.675	1.000	1.010	0.682	
2549.50	40185	Low-Mid	LTE Band 41	20	24.2	24.11	0.02	0	089498624600002345	QPSK	1	50	8 mm	front	1:1.59	0.569	1.021	1.010	0.587	
2593.00	40620	Mid	LTE Band 41	20	24.2	24.18	-0.07	0	089498624600002345	QPSK	1	50	8 mm	front	1:1.59	0.694	1.005	1.010	0.704	A33
2636.50	41055	Mid-High	LTE Band 41	20	24.2	24.19	-0.03	0	089498624600002345	QPSK	1	50	8 mm	front	1:1.59	0.625	1.002	1.010	0.632	
2680.00	41490	High	LTE Band 41	20	24.2	24.19	-0.04	0	089498624600002345	QPSK	1	50	8 mm	front	1:1.59	0.641	1.002	1.010	0.648	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.03	1	089498624600002345	QPSK	50	25	8 mm	front	1:1.59	0.528	1.000	1.010	0.533	
2680.00	41490	High	LTE Band 41	20	23.2	23.19	0.08	1	089498624600002345	QPSK	100	0	8 mm	front	1:1.59	0.486	1.002	1.010	0.492	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.12	0	089498624600002345	QPSK	1	50	10 mm	bottom	1:1.59	0.286	1.000	1.010	0.289	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.08	1	089498624600002345	QPSK	50	25	10 mm	bottom	1:1.59	0.227	1.000	1.010	0.229	
2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.07	0	089498624600002345	QPSK	1	50	10 mm	left	1:1.59	0.359	1.000	1.010	0.363	
2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.02	1	089498624600002345	QPSK	50	25	10 mm	left	1:1.59	0.288	1.000	1.010	0.291	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-25
WIFI Hotspot SAR Data**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.															
2462	11	IEEE 802.11b	DSSS	14.5	13.57	0.17	8 mm	089498624600002355	1	back	1:1	0.070	1.239	0.087		
2462	11	IEEE 802.11b	DSSS	14.5	13.57	-0.01	8 mm	089498624600002355	1	front	1:1	0.117	1.239	0.145	A35	
2462	11	IEEE 802.11b	DSSS	14.5	13.57	0.14	10 mm	089498624600002355	1	top	1:1	0.046	1.239	0.057		
2462	11	IEEE 802.11b	DSSS	14.5	13.57	-0.19	10 mm	089498624600002355	1	left	1:1	0.040	1.239	0.050		
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.17	8 mm	089498624600002355	6	back	1:1	0.200	1.358	0.272		
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.19	8 mm	089498624600002355	6	front	1:1	0.164	1.358	0.223		
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.10	10 mm	089498624600002355	6	top	1:1	0.195	1.358	0.265		
5745	149	IEEE 802.11a	OFDM	14.5	13.17	0.10	10 mm	089498624600002355	6	left	1:1	0.270	1.358	0.367	A37	
5775	155	IEEE 802.11ac	OFDM	12.5	11.76	0.14	10 mm	089498624600002355	29.3	left	1:1	0.145	1.186	0.172		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram						

11.4 SAR Test Notes

General Notes:



1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Due to the embowed design of the device, Body SAR was configured per FCC Guidance. See section 1.7 for more information.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D03v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v02.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers, per FCC KDB Publication 941225 D01v02.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01 procedures for data devices. Since the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, EVDO Rev. A SAR is not required. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 60 of 77

- Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:



- UMTS mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
- Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:



- LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.5.4.
- MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
- A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
- Per FCC KDB Publication 447498 D01v05r01, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
- TDD LTE was tested using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using normal cyclic prefix only and special subframe configuration 6. Due to equipment setup issues with extended cyclic prefix as a result of test samples configured for normal cyclic prefix, SAR tests were performed at maximum output power and worst-case transmission duty factor in normal cyclic prefix. Results were then scaled to the duty factor required for extended cyclic prefix listed in 3GPP TS 36.211 Section 4. The cyclic prefix scaling factor for LTE Band 41 was calculated by dividing the extended cyclic prefix duty factor by the normal cyclic prefix duty factor. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using normal cyclic prefix is 0.629. The duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
- Per FCC Guidance, LTE CA SAR was not needed for testing since the data sent by uplink on the uplink physical channels does not change between Rel. 8 and Rel. 10.

WLAN Notes:

- Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n/ac) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 5 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 61 of 77	

3. Per April 2013 TCB Workshop notes, full SAR tests for all IEEE 802.11ac configurations were not required because the average output power was not more than 0.25 dB higher than IEEE 802.11a mode. IEEE 802.11ac was evaluated for the highest IEEE 802.11a position in each 5 GHz band and exposure condition.
4. When Hotspot is enabled, all 5 GHz bands are disabled. Therefore no 5 GHz WIFI Wireless Router SAR Data was required. When Hotspot is enabled, 5.2-5.7 GHz bands are disabled. Therefore no 5.2 – 5.7 GHz WIFI Wireless Router SAR Data was required.
5. WIFI transmission was verified using an uncalibrated spectrum analyzer.
6. When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is >1.6 W/kg or the reported 1g averaged SAR is >0.8 W/kg, SAR testing on other default channels was required.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 62 of 77	

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n/ac and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1
Estimated SAR**



Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	8.50	8	0.184

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)**

Simult Tx	Configuration	CDMA BC10 (\$90S) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC10 (\$90S) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.517	0.639	1.156	Head SAR	Right Cheek	0.431	0.639	1.070
	Right Tilt	0.352	0.466	0.818		Right Tilt	0.277	0.466	0.743
	Left Cheek	0.504	0.250	0.754		Left Cheek	0.448	0.250	0.698
	Left Tilt	0.319	0.216	0.535		Left Tilt	0.284	0.216	0.500
Simult Tx	Configuration	CDMA BC0 (\$22H) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC0 (\$22H) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.493	0.639	1.132	Head SAR	Right Cheek	0.445	0.639	1.084
	Right Tilt	0.298	0.466	0.764		Right Tilt	0.253	0.466	0.719
	Left Cheek	0.414	0.250	0.664		Left Cheek	0.418	0.250	0.668
	Left Tilt	0.239	0.216	0.455		Left Tilt	0.237	0.216	0.453

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 63 of 77

Simult Tx	Configuration	PCS CDMA SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.670	0.639	1.309	Head SAR	Right Cheek	0.659	0.639	1.298
	Right Tilt	0.198	0.466	0.664		Right Tilt	0.193	0.466	0.659
	Left Cheek	0.267	0.250	0.517		Left Cheek	0.270	0.250	0.520
	Left Tilt	0.225	0.216	0.441		Left Tilt	0.202	0.216	0.418
Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.339	0.639	0.978	Head SAR	Right Cheek	0.391	0.639	1.030
	Right Tilt	0.211	0.466	0.677		Right Tilt	0.239	0.466	0.705
	Left Cheek	0.311	0.250	0.561		Left Cheek	0.352	0.250	0.602
	Left Tilt	0.198	0.216	0.414		Left Tilt	0.234	0.216	0.450
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.281	0.639	0.920	Head SAR	Right Cheek	0.379	0.639	1.018
	Right Tilt	0.089	0.466	0.555		Right Tilt	0.099	0.466	0.565
	Left Cheek	0.116	0.250	0.366		Left Cheek	0.145	0.250	0.395
	Left Tilt	0.097	0.216	0.313		Left Tilt	0.104	0.216	0.320
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.376	0.639	1.015	Head SAR	Right Cheek	0.570	0.639	1.209
	Right Tilt	0.212	0.466	0.678		Right Tilt	0.172	0.466	0.638
	Left Cheek	0.314	0.250	0.564		Left Cheek	0.252	0.250	0.502
	Left Tilt	0.193	0.216	0.409		Left Tilt	0.167	0.216	0.383
Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 26 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.236	0.639	0.875	Head SAR	Right Cheek	0.407	0.639	1.046
	Right Tilt	0.127	0.466	0.593		Right Tilt	0.272	0.466	0.738
	Left Cheek	0.159	0.250	0.409		Left Cheek	0.379	0.250	0.629
	Left Tilt	0.100	0.216	0.316		Left Tilt	0.233	0.216	0.449
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.404	0.639	1.043	Head SAR	Right Cheek	0.435	0.639	1.074
	Right Tilt	0.163	0.466	0.629		Right Tilt	0.166	0.466	0.632
	Left Cheek	0.133	0.250	0.383		Left Cheek	0.205	0.250	0.455
	Left Tilt	0.153	0.216	0.369		Left Tilt	0.153	0.216	0.369
Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)					
Head SAR	Right Cheek	0.242	0.639	0.881					
	Right Tilt	0.203	0.466	0.669					
	Left Cheek	0.690	0.250	0.940					
	Left Tilt	0.179	0.216	0.395					



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 64 of 77

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Simult Tx	Configuration	CDMA BC10 (\$90S) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC10 (\$90S) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.517	0.745	1.262	Head SAR	Right Cheek	0.431	0.745	1.176
	Right Tilt	0.352	0.652	1.004		Right Tilt	0.277	0.652	0.929
	Left Cheek	0.504	0.677	1.181		Left Cheek	0.448	0.677	1.125
	Left Tilt	0.319	0.509	0.828		Left Tilt	0.284	0.509	0.793
Simult Tx	Configuration	CDMA BC0 (\$22H) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC0 (\$22H) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.493	0.745	1.238	Head SAR	Right Cheek	0.445	0.745	1.190
	Right Tilt	0.298	0.652	0.950		Right Tilt	0.253	0.652	0.905
	Left Cheek	0.414	0.677	1.091		Left Cheek	0.418	0.677	1.095
	Left Tilt	0.239	0.509	0.748		Left Tilt	0.237	0.509	0.746
Simult Tx	Configuration	PCS CDMA SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.670	0.745	1.415	Head SAR	Right Cheek	0.659	0.745	1.404
	Right Tilt	0.198	0.652	0.850		Right Tilt	0.193	0.652	0.845
	Left Cheek	0.267	0.677	0.944		Left Cheek	0.270	0.677	0.947
	Left Tilt	0.225	0.509	0.734		Left Tilt	0.202	0.509	0.711
Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.339	0.745	1.084	Head SAR	Right Cheek	0.391	0.745	1.136
	Right Tilt	0.211	0.652	0.863		Right Tilt	0.239	0.652	0.891
	Left Cheek	0.311	0.677	0.988		Left Cheek	0.352	0.677	1.029
	Left Tilt	0.198	0.509	0.707		Left Tilt	0.234	0.509	0.743
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.281	0.745	1.026	Head SAR	Right Cheek	0.379	0.745	1.124
	Right Tilt	0.089	0.652	0.741		Right Tilt	0.099	0.652	0.751
	Left Cheek	0.116	0.677	0.793		Left Cheek	0.145	0.677	0.822
	Left Tilt	0.097	0.509	0.606		Left Tilt	0.104	0.509	0.613
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.376	0.745	1.121	Head SAR	Right Cheek	0.570	0.745	1.315
	Right Tilt	0.212	0.652	0.864		Right Tilt	0.172	0.652	0.824
	Left Cheek	0.314	0.677	0.991		Left Cheek	0.252	0.677	0.929
	Left Tilt	0.193	0.509	0.702		Left Tilt	0.167	0.509	0.676
Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 26 (Cell) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.236	0.745	0.981	Head SAR	Right Cheek	0.407	0.745	1.152
	Right Tilt	0.127	0.652	0.779		Right Tilt	0.272	0.652	0.924
	Left Cheek	0.159	0.677	0.836		Left Cheek	0.379	0.677	1.056
	Left Tilt	0.100	0.509	0.609		Left Tilt	0.233	0.509	0.742

Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.404	0.745	1.149	Head SAR	Right Cheek	0.435	0.745	1.180
	Right Tilt	0.163	0.652	0.815		Right Tilt	0.166	0.652	0.818
	Left Cheek	0.133	0.677	0.810		Left Cheek	0.205	0.677	0.882
	Left Tilt	0.153	0.509	0.662		Left Tilt	0.153	0.509	0.662

Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.242	0.745	0.987
	Right Tilt	0.203	0.652	0.855
	Left Cheek	0.690	0.677	1.367
	Left Tilt	0.179	0.509	0.688

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 0.8 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	CDMA BC10 (§90S)	0.702	0.087	0.789
Back Side	CDMA BC0 (§22H)	0.570	0.087	0.657
Back Side	PCS CDMA	0.716	0.087	0.803
Back Side	GSM 850	0.391	0.087	0.478
Back Side	GPRS 850	0.474	0.087	0.561
Back Side	GSM 1900	0.359	0.087	0.446
Back Side	GPRS 1900	0.414	0.087	0.501
Back Side	UMTS 850	0.453	0.087	0.540
Back Side	UMTS 1900	0.543	0.087	0.630
Back Side	LTE Band 12	0.363	0.087	0.450
Back Side	LTE Band 26 (Cell)	0.567	0.087	0.654
Back Side	LTE Band 4 (AWS)	0.507	0.087	0.594
Back Side	LTE Band 25 (PCS)	0.736	0.087	0.823
Back Side	LTE Band 41	0.425	0.087	0.512



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 66 of 77

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 0.8 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	CDMA BC10 (§90S)	0.702	0.284	0.986
Back Side	CDMA BC0 (§22H)	0.570	0.284	0.854
Back Side	PCS CDMA	0.716	0.284	1.000
Back Side	GSM 850	0.391	0.284	0.675
Back Side	GPRS 850	0.474	0.284	0.758
Back Side	GSM 1900	0.359	0.284	0.643
Back Side	GPRS 1900	0.414	0.284	0.698
Back Side	UMTS 850	0.453	0.284	0.737
Back Side	UMTS 1900	0.543	0.284	0.827
Back Side	LTE Band 12	0.363	0.284	0.647
Back Side	LTE Band 26 (Cell)	0.567	0.284	0.851
Back Side	LTE Band 4 (AWS)	0.507	0.284	0.791
Back Side	LTE Band 25 (PCS)	0.736	0.284	1.020
Back Side	LTE Band 41	0.425	0.284	0.709

The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

Table 12-6
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 0.8 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Back Side	CDMA BC10 (§90S)	0.702	0.184	0.886
Back Side	CDMA BC0 (§22H)	0.570	0.184	0.754
Back Side	PCS CDMA	0.716	0.184	0.900
Back Side	GSM 850	0.391	0.184	0.575
Back Side	GPRS 850	0.474	0.184	0.658
Back Side	GSM 1900	0.359	0.184	0.543
Back Side	GPRS 1900	0.414	0.184	0.598
Back Side	UMTS 850	0.453	0.184	0.637
Back Side	UMTS 1900	0.543	0.184	0.727
Back Side	LTE Band 12	0.363	0.184	0.547
Back Side	LTE Band 26 (Cell)	0.567	0.184	0.751
Back Side	LTE Band 4 (AWS)	0.507	0.184	0.691
Back Side	LTE Band 25 (PCS)	0.736	0.184	0.920
Back Side	LTE Band 41	0.425	0.184	0.609

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

Table 12-7
Simultaneous Transmission Scenario (2.4 GHz Hotspot)

Simult Tx	Configuration	EVDO BC10 (\$90S) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC0 (\$22H) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.617	0.087	0.704	Body SAR	Back	0.568	0.087	0.655
	Front	0.486	0.145	0.631		Front	0.496	0.145	0.641
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.382	-	0.382		Bottom	0.403	-	0.403
	Right	0.596	-	0.596		Right	0.542	-	0.542
	Left	0.504	0.050	0.554		Left	0.449	0.050	0.499
Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.694	0.087	0.781	Body SAR	Back	0.474	0.087	0.561
	Front	0.897	0.145	1.042		Front	0.614	0.145	0.759
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.607	-	0.607		Bottom	0.429	-	0.429
	Right	0.543	-	0.543		Right	0.484	-	0.484
	Left	0.138	0.050	0.188		Left	0.398	0.050	0.448
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.414	0.087	0.501	Body SAR	Back	0.453	0.087	0.540
	Front	0.479	0.145	0.624		Front	0.375	0.145	0.520
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.271	-	0.271		Bottom	0.317	-	0.317
	Right	0.295	-	0.295		Right	0.438	-	0.438
	Left	0.039	0.050	0.089		Left	0.361	0.050	0.411
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.543	0.087	0.630	Body SAR	Back	0.363	0.087	0.450
	Front	0.647	0.145	0.792		Front	0.303	0.145	0.448
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.496	-	0.496		Bottom	0.122	-	0.122
	Right	0.422	-	0.422		Right	0.317	-	0.317
	Left	0.148	0.050	0.198		Left	0.155	0.050	0.205
Simult Tx	Configuration	LTE Band 26 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.567	0.087	0.654	Body SAR	Back	0.507	0.087	0.594
	Front	0.471	0.145	0.616		Front	0.366	0.145	0.511
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.390	-	0.390		Bottom	0.178	-	0.178
	Right	0.492	-	0.492		Right	0.242	-	0.242
	Left	0.380	0.050	0.430		Left	0.065	0.050	0.115

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.736	0.087	0.823	Body SAR	Back	0.425	0.087	0.512
	Front	0.603	0.145	0.748		Front	0.704	0.145	0.849
	Top	-	0.057	0.057		Top	-	0.057	0.057
	Bottom	0.427	-	0.427		Bottom	0.289	-	0.289
	Right	0.474	-	0.474		Right	-	-	0.000
	Left	0.115	0.050	0.165		Left	0.363	0.050	0.413



**Table 12-8
Simultaneous Transmission Scenario (5 GHz WLAN Hotspot)**

Simult Tx	Configuration	EVDO BC10 (§90S) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	EVDO BC0 (§22H) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.617	0.272	0.889	Body SAR	Back	0.568	0.272	0.840
	Front	0.486	0.223	0.709		Front	0.496	0.223	0.719
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.382	-	0.382		Bottom	0.403	-	0.403
	Right	0.596	-	0.596		Right	0.542	-	0.542
	Left	0.504	0.367	0.871		Left	0.449	0.367	0.816
Body SAR	Back	0.694	0.272	0.966	Body SAR	Back	0.474	0.272	0.746
	Front	0.897	0.223	1.120		Front	0.614	0.223	0.837
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.607	-	0.607		Bottom	0.429	-	0.429
	Right	0.543	-	0.543		Right	0.484	-	0.484
	Left	0.138	0.367	0.505		Left	0.398	0.367	0.765
Body SAR	Back	0.414	0.272	0.686	Body SAR	Back	0.453	0.272	0.725
	Front	0.479	0.223	0.702		Front	0.375	0.223	0.598
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.271	-	0.271		Bottom	0.317	-	0.317
	Right	0.295	-	0.295		Right	0.438	-	0.438
	Left	0.039	0.367	0.406		Left	0.361	0.367	0.728
Body SAR	Back	0.543	0.272	0.815	Body SAR	Back	0.363	0.272	0.635
	Front	0.647	0.223	0.870		Front	0.303	0.223	0.526
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.496	-	0.496		Bottom	0.122	-	0.122
	Right	0.422	-	0.422		Right	0.317	-	0.317
	Left	0.148	0.367	0.515		Left	0.155	0.367	0.522

Simult Tx	Configuration	LTE Band 26 (Cell) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.567	0.272	0.839	Body SAR	Back	0.507	0.272	0.779
	Front	0.471	0.223	0.694		Front	0.366	0.223	0.589
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.390	-	0.390		Bottom	0.178	-	0.178
	Right	0.492	-	0.492		Right	0.242	-	0.242
	Left	0.380	0.367	0.747		Left	0.065	0.367	0.432
Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.736	0.272	1.008	Body SAR	Back	0.425	0.272	0.697
	Front	0.603	0.223	0.826		Front	0.704	0.223	0.927
	Top	-	0.265	0.265		Top	-	0.265	0.265
	Bottom	0.427	-	0.427		Bottom	0.289	-	0.289
	Right	0.474	-	0.474		Right	-	-	0.000
	Left	0.115	0.367	0.482		Left	0.363	0.367	0.730

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 70 of 77	

13 SAR MEASUREMENT VARIABILITY

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:



- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

**Table 13-1
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1880.00	600	PCS CDMA	EVDO Rev.0	front	8 mm	0.871	0.822	1.06	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram						

13.1 Measurement Uncertainty



The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 71 of 77	

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629U00687
Agilent	8753ES	S-Parameter Network Analyzer	5/22/2014	Annual	5/22/2015	US39170118
Agilent	E4438C	ESG Vector Signal Generator	4/25/2014	Annual	4/25/2015	MY42082385
Agilent	E5515C	Wireless Communications Test Set	3/28/2014	Annual	3/28/2015	GB42230325
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420651
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1231535
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1231538
Anritsu	MA2411B	Pulse Power Sensor	3/25/2014	Annual	3/25/2015	1207470
Anritsu	MA2411B	Pulse Power Sensor	2/3/2014	Annual	2/3/2015	1339018
Anritsu	ML2469A	Power Meter	3/14/2014	Annual	3/14/2015	1306009
Anritsu	ML2495A	Power Meter	10/31/2013	Biennial	10/31/2015	941001
Anritsu	MA2411B	Pulse Meter	4/8/2014	Biennial	4/8/2016	846215
Anritsu	MT8820C	Radio Communication Analyzer	9/19/2014	Annual	9/19/2015	6201144418
Anritsu	MT8820C	Radio Communication Analyzer	5/6/2014	Annual	5/6/2015	6201144419
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Control Company	4052	Long Stem Thermometer	9/27/2013	Biennial	9/27/2015	130567447
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764551
Fisher Scientific	15-078J	Long Stem Thermometer	1/7/2013	Biennial	1/7/2015	130018204
Fisher Scientific	S97611	Thermometer	4/12/2013	Biennial	4/12/2015	130219303
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	6/6/2014	Annual	6/6/2015	109892
Rohde & Schwarz	CMW500	Radio Communication Tester	10/3/2014	Annual	10/3/2015	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	7/22/2014	Annual	7/22/2015	116743
Rohde & Schwarz	CMW500	Radio Communication Tester	2/20/2014	Annual	2/20/2015	128633
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	22313
SPEAG	D1765V2	1765 MHz SAR Dipole	5/7/2014	Annual	5/7/2015	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	4/9/2014	Annual	4/9/2015	5d141
SPEAG	D1900V2	1900 MHz SAR Dipole	2/27/2014	Annual	2/27/2015	5d148
SPEAG	D2450V2	2450 MHz SAR Dipole	1/21/2014	Annual	1/21/2015	797
SPEAG	D2450V2	2450 MHz SAR Dipole	2/24/2014	Annual	2/24/2015	882
SPEAG	D2600V2	2600 MHz SAR Dipole	4/8/2014	Annual	4/8/2015	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	2/26/2014	Annual	2/26/2015	1120
SPEAG	D5GHzV2	SAR Dipole	9/25/2014	Annual	9/25/2015	1191
SPEAG	D750V3	750 MHz Dipole	2/27/2014	Annual	2/27/2015	1046
SPEAG	D835V2	835 MHz SAR Dipole	4/7/2014	Annual	4/7/2015	4d119
SPEAG	D835V2	835 MHz SAR Dipole	7/10/2014	Annual	7/10/2015	4d132
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/22/2014	Annual	1/22/2015	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/12/2014	Annual	8/12/2015	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2014	Annual	9/17/2015	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/31/2014	Annual	10/31/2015	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2014	Annual	4/11/2015	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/23/2014	Annual	10/23/2015	1408
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/6/2014	Annual	5/6/2015	1070
SPEAG	ES3DV2	SAR Probe	8/19/2014	Annual	8/19/2015	3022
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	ES3DV3	SAR Probe	3/19/2014	Annual	3/19/2015	3318
SPEAG	ES3DV3	SAR Probe	4/17/2014	Annual	4/17/2015	3319
SPEAG	ES3DV3	SAR Probe	9/18/2014	Annual	9/18/2015	3332
SPEAG	ES3DV3	SAR Probe	10/24/2014	Annual	10/24/2015	3333
SPEAG	EX3DV4	SAR Probe	1/29/2014	Annual	1/29/2015	3589
SPEAG	EX3DV4	SAR Probe	10/24/2014	Annual	10/24/2015	3914
VWR	36934-158	Wall-Mounted Thermometer	4/29/2014	Biennial	4/29/2016	111859323

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 72 of 77

15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)				RSS			12.1	11.7	299
Expanded Uncertainty (95% CONFIDENCE LEVEL)				k=2			24.2	23.5	



The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 73 of 77

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k	
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i	
Measurement System										
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞	
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞	
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞	
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞	
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞	
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞	
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞	
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞	
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞	
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞	
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞	
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞	
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞	
Test Sample Related										
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287	
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞	
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞	
Phantom & Tissue Parameters										
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞	
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞	
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6	
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞	
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6	
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0	299
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0	

The above measurement uncertainties are according to IEEE Std. 1528-2003



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 74 of 77

16 CONCLUSION

16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset		Page 75 of 77

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset			Page 76 of 77

- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFLS996	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1412012171.ZNF	Test Dates: 12/01/14 - 12/15/14	DUT Type: Portable Handset	Page 77 of 77	

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA, Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 820.1$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 40.397$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell CDMA BC10, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.97 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.624 W/kg

SAR(1 g) = 0.494 W/kg



0 dB = 0.538 W/kg = -2.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.938 \text{ S/m}$; $\epsilon_r = 40.197$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell CDMA BC0, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.17 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.625 W/kg

SAR(1 g) = 0.466 W/kg



0 dB = 0.517 W/kg = -2.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.43 \text{ S/m}$; $\epsilon_r = 39.411$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-02-2014; Ambient Temp: 22.2°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(5.33, 5.33, 5.33); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS EVDO RevA, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.09 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.631 W/kg



0 dB = 0.741 W/kg = -1.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002354

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.938 \text{ S/m}$; $\epsilon_r = 40.196$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Right Head, Cheek, Mid.ch, 2 Tx slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.29 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.514 W/kg

SAR(1 g) = 0.390 W/kg



0 dB = 0.427 W/kg = -3.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.43 \text{ S/m}$; $\epsilon_r = 39.411$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-02-2014; Ambient Temp: 22.2°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(5.33, 5.33, 5.33); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Right Head, Cheek, Mid.ch, 2 Tx slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.92 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.531 W/kg

SAR(1 g) = 0.334 W/kg



0 dB = 0.384 W/kg = -4.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002354

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.938 \text{ S/m}$; $\epsilon_r = 40.196$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.79 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.494 W/kg

SAR(1 g) = 0.373 W/kg



0 dB = 0.408 W/kg = -3.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.43 \text{ S/m}$; $\epsilon_r = 39.411$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-02-2014; Ambient Temp: 22.2°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(5.33, 5.33, 5.33); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.06 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.929 W/kg

SAR(1 g) = 0.565 W/kg



0 dB = 0.667 W/kg = -1.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.869 \text{ S/m}$; $\epsilon_r = 41.129$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-01-2014; Ambient Temp: 22.8°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3318; ConvF(6.45, 6.45, 6.45); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Right Head, Cheek, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.43 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.294 W/kg

SAR(1 g) = 0.226 W/kg



0 dB = 0.251 W/kg = -6.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.938 \text{ S/m}$; $\epsilon_r = 40.198$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.61 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.513 W/kg

SAR(1 g) = 0.405 W/kg



0 dB = 0.445 W/kg = -3.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5$ MHz; $\sigma = 1.365$ S/m; $\epsilon_r = 39.026$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 12-01-2014; Ambient Temp: 24.0°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(5.04, 5.04, 5.04); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Right Head, Cheek, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.58 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.587 W/kg

SAR(1 g) = 0.391 W/kg



0 dB = 0.456 W/kg = -3.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 08949862460002345

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.41 \text{ S/m}$; $\epsilon_r = 39.511$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-02-2014; Ambient Temp: 22.2°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(5.33, 5.33, 5.33); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 25 (PCS), Right Head, Cheek, Low.ch
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.51 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.679 W/kg

SAR(1 g) = 0.434 W/kg



0 dB = 0.494 W/kg = -3.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002345

Communication System: UID 0, LTE Band 41; Frequency: 2593 MHz; Duty Cycle: 1:1.59

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.007 \text{ S/m}$; $\epsilon_r = 37.41$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-15-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Left Head, Cheek, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (8x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.36 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.680 W/kg



0 dB = 0.832 W/kg = -0.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.87 \text{ S/m}$; $\epsilon_r = 40.656$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-03-2014; Ambient Temp: 24.1°C; Tissue Temp: 24.7°C

Probe: ES3DV3 - SN3318; ConvF(4.69, 4.69, 4.69); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Right Head, Cheek, Ch 11, 1 Mbps


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.83 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.516 W/kg



0 dB = 0.645 W/kg = -1.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11a; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 5.054 \text{ S/m}$; $\epsilon_r = 35.603$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.35, 4.35, 4.35); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.5 GHz, Right Head, Cheek, Ch 132, 6 Mbps


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio:1.4

Reference Value = 10.49 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.71 W/kg

SAR(1 g) = 0.536 W/kg



0 dB = 1.48 W/kg = 1.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1$ MHz; $\sigma = 0.945$ S/m; $\epsilon_r = 53.26$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA BC10, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.39 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.836 W/kg

SAR(1 g) = 0.672 W/kg



0 dB = 0.727 W/kg = -1.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.945 \text{ S/m}$; $\epsilon_r = 53.26$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. BC10, EVDO Rev. 0, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.62 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.741 W/kg

SAR(1 g) = 0.590 W/kg



0 dB = 0.639 W/kg = -1.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52$ MHz; $\sigma = 0.962$ S/m; $\epsilon_r = 53.082$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA BC0, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.54 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.686 W/kg

SAR(1 g) = 0.549 W/kg



0 dB = 0.601 W/kg = -2.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52$ MHz; $\sigma = 0.962$ S/m; $\epsilon_r = 53.082$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. BC0, EVDO Rev. 0, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.63 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.557 W/kg



0 dB = 0.608 W/kg = -2.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.357$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-01-2014; Ambient Temp: 23.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.67, 4.67, 4.67); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS CDMA, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.90 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.711 W/kg



0 dB = 0.828 W/kg = -0.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002352

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.357$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-01-2014; Ambient Temp: 23.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.67, 4.67, 4.67); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS EVDO Rev 0, Body SAR, Front side, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.29 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.871 W/kg



0 dB = 1.03 W/kg = 0.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.962 \text{ S/m}$; $\epsilon_r = 53.081$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.70 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.809 W/kg

SAR(1 g) = 0.473 W/kg



0 dB = 0.512 W/kg = -2.91 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.962 \text{ S/m}$; $\epsilon_r = 53.081$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Front side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.24 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.613 W/kg



0 dB = 0.746 W/kg = -1.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 08949862460002353

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.509 \text{ S/m}$; $\epsilon_r = 51.027$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-08-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.68 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.597 W/kg

SAR(1 g) = 0.365 W/kg



0 dB = 0.435 W/kg = -3.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 08949862460002353

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.509 \text{ S/m}$; $\epsilon_r = 51.027$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-08-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Front side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.11 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.727 W/kg

SAR(1 g) = 0.422 W/kg



0 dB = 0.519 W/kg = -2.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6$ MHz; $\sigma = 0.962$ S/m; $\epsilon_r = 53.081$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.19 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.565 W/kg

SAR(1 g) = 0.450 W/kg



0 dB = 0.490 W/kg = -3.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 08949862460002353

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.556 \text{ S/m}$; $\epsilon_r = 52.064$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-04-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.85 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.886 W/kg

SAR(1 g) = 0.538 W/kg



0 dB = 0.641 W/kg = -1.93 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002353

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.556 \text{ S/m}$; $\epsilon_r = 52.064$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-04-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Front side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.12 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.641 W/kg



0 dB = 0.806 W/kg = -0.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 54.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-01-2014; Ambient Temp: 22.9°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3318; ConvF(6.16, 6.16, 6.16); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Main Twin Sam; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Back side, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.01 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.457 W/kg

SAR(1 g) = 0.347 W/kg



0 dB = 0.381 W/kg = -4.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.961$ S/m; $\epsilon_r = 53.082$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 26, Body SAR, Back side, Mid.ch
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.84 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.711 W/kg

SAR(1 g) = 0.564 W/kg



0 dB = 0.614 W/kg = -2.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002344

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 51.684$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-01-2014; Ambient Temp: 22.9°C; Tissue Temp: 22.2°C

Probe: ES3DV2 - SN3022; ConvF(4.7, 4.7, 4.7); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.12 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.739 W/kg

SAR(1 g) = 0.491 W/kg



0 dB = 0.567 W/kg = -2.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002345

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 51.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-08-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 25 (PCS), Body SAR, Back side, Low.ch
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.56 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.735 W/kg



0 dB = 0.884 W/kg = -0.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002345

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.59

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.121 \text{ S/m}$; $\epsilon_r = 50.941$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-09-2014; Ambient Temp: 24.3°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3332; ConvF(4.31, 4.31, 4.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Body SAR, Back side, Low.ch
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.99 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.833 W/kg

SAR(1 g) = 0.421 W/kg



0 dB = 0.531 W/kg = -2.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002345

Communication System: UID 0, LTE Band 41; Frequency: 2593 MHz; Duty Cycle: 1:1.59

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2593$ MHz; $\sigma = 2.244$ S/m; $\epsilon_r = 50.605$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-09-2014; Ambient Temp: 24.3°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3332; ConvF(4.11, 4.11, 4.11); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Body SAR, Front side, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.24 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.694 W/kg



0 dB = 0.880 W/kg = -0.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462$ MHz; $\sigma = 2.044$ S/m; $\epsilon_r = 53.288$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-04-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.958 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.150 W/kg

SAR(1 g) = 0.070 W/kg



0 dB = 0.0901 W/kg = -10.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.044 \text{ S/m}$; $\epsilon_r = 53.288$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-04-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Front Side


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.547 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.234 W/kg

SAR(1 g) = 0.117 W/kg



0 dB = 0.146 W/kg = -8.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11a; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 6.077 \text{ S/m}$; $\epsilon_r = 47.002$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.8 cm

Test Date: 12-02-2014; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(3.81, 3.81, 3.81); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 132, 6 Mbps, Back Side


Area Scan (12x20x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.327 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.204 W/kg



0 dB = 0.494 W/kg = -3.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFLS996; Type: Portable Handset; Serial: 089498624600002355

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.212 \text{ S/m}$; $\epsilon_r = 46.786$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(3.97, 3.97, 3.97); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 149, 6 Mbps, Left Edge


Area Scan (11x20x1): Measurement grid: dx=5mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.446 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.270 W/kg



0 dB = 0.644 W/kg = -1.91 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.908 \text{ S/m}$; $\epsilon_r = 40.543$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-01-2014; Ambient Temp: 22.8°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3318; ConvF(6.45, 6.45, 6.45); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.821 W/kg

Deviation = -0.73%



0 dB = 0.969 W/kg = -0.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.937 \text{ S/m}$; $\epsilon_r = 40.218$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-03-2014; Ambient Temp: 23.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(6.31, 6.31, 6.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.884 W/kg

Deviation = -4.12%



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.451$ S/m; $\epsilon_r = 39.336$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 22.2°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(5.33, 5.33, 5.33); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.78 W/kg

Deviation = -7.13%



0 dB = 4.83 W/kg = 6.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 882

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.856 \text{ S/m}$; $\epsilon_r = 40.702$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-03-2014; Ambient Temp: 24.1°C; Tissue Temp: 24.7°C

Probe: ES3DV3 - SN3318; ConvF(4.69, 4.69, 4.69); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.04 W/kg

Deviation = -3.08%



0 dB = 6.62 W/kg = 8.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.853 \text{ S/m}$; $\epsilon_r = 37.946$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-15-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.63 W/kg

Deviation = 8.69%



0 dB = 7.44 W/kg = 8.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.015$ S/m; $\epsilon_r = 37.393$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-15-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 12.3 W/kg

SAR(1 g) = 5.87 W/kg

Deviation = 2.44%



0 dB = 7.68 W/kg = 8.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 4.581 \text{ S/m}$; $\epsilon_r = 36.26$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.96, 4.96, 4.96); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5200 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 31.3 W/kg

SAR(1 g) = 7.5 W/kg

Deviation = -5.18%



0 dB = 18.3 W/kg = 12.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 4.687 \text{ S/m}$; $\epsilon_r = 36.091$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.84, 4.84, 4.84); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 33.6 W/kg

SAR(1 g) = 7.85 W/kg

Deviation = -5.88%



0 dB = 18.3 W/kg = 12.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 4.887 \text{ S/m}$; $\epsilon_r = 35.808$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.45, 4.45, 4.45); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.7 W/kg

SAR(1 g) = 8 W/kg

Deviation = -5.77%



0 dB = 19.0 W/kg = 12.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.988 \text{ S/m}$; $\epsilon_r = 35.696$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.35, 4.35, 4.35); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 35.6 W/kg

SAR(1 g) = 8 W/kg

Deviation = -2.68%



0 dB = 19.2 W/kg = 12.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 5.208 \text{ S/m}$; $\epsilon_r = 35.42$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.4°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN3914; ConvF(4.53, 4.53, 4.53); Calibrated: 10/24/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/31/2014

Phantom: SAM Main ; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 35.2 W/kg

SAR(1 g) = 7.6 W/kg

Deviation = -3.92%



0 dB = 18.4 W/kg = 12.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.966 \text{ S/m}$; $\epsilon_r = 53.713$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-01-2014; Ambient Temp: 22.9°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3318; ConvF(6.16, 6.16, 6.16); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Main Twin Sam; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.902 W/kg

Deviation = 5.62%



0 dB = 1.05 W/kg = 0.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.96 \text{ S/m}$; $\epsilon_r = 53.096$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-06-2014; Ambient Temp: 21.0°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 1.03 W/kg

Deviation = 7.52%



0 dB = 1.20 W/kg = 0.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.508$ S/m; $\epsilon_r = 51.603$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-01-2014; Ambient Temp: 22.9°C; Tissue Temp: 22.2°C

Probe: ES3DV2 - SN3022; ConvF(4.7, 4.7, 4.7); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.41 W/kg

SAR(1 g) = 3.64 W/kg

Deviation = -3.19%



0 dB = 4.52 W/kg = 6.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.51 \text{ S/m}$; $\epsilon_r = 52.289$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-01-2014; Ambient Temp: 23.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.67, 4.67, 4.67); Calibrated: 10/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.36 W/kg

SAR(1 g) = 4.19 W/kg

Deviation = 6.62%



0 dB = 5.32 W/kg = 7.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.579$ S/m; $\epsilon_r = 52.015$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-04-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.80 W/kg

SAR(1 g) = 3.9 W/kg

Deviation = -3.94%



0 dB = 4.86 W/kg = 6.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.532 \text{ S/m}$; $\epsilon_r = 50.956$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 6/19/2014

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.04 W/kg

SAR(1 g) = 3.93 W/kg

Deviation = 0.00%



0 dB = 4.96 W/kg = 6.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.027$ S/m; $\epsilon_r = 53.326$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-04-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 10.2 W/kg

SAR(1 g) = 4.78 W/kg

Deviation = -3.24%



0 dB = 6.27 W/kg = 7.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.044$ S/m; $\epsilon_r = 51.143$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-09-2014; Ambient Temp: 24.3°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3332; ConvF(4.31, 4.31, 4.31); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.29 W/kg

Deviation = 7.09%



0 dB = 6.95 W/kg = 8.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.254 \text{ S/m}$; $\epsilon_r = 50.583$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-09-2014; Ambient Temp: 24.3°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3332; ConvF(4.11, 4.11, 4.11); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 13.9 W/kg

SAR(1 g) = 6.12 W/kg

Deviation = 7.94%



0 dB = 8.07 W/kg = 9.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 5.377 \text{ S/m}$; $\epsilon_r = 48.11$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(4.19, 4.19, 4.19); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5200 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 31.5 W/kg

SAR(1 g) = 7.24 W/kg

Deviation = -6.94%



0 dB = 18.6 W/kg = 12.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.512 \text{ S/m}$; $\epsilon_r = 47.873$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3589; ConvF(3.98, 3.98, 3.98); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.6 W/kg

SAR(1 g) = 7.71 W/kg

Deviation = -3.50%



0 dB = 20.0 W/kg = 13.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.983 \text{ S/m}$; $\epsilon_r = 47.092$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(3.81, 3.81, 3.81); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 41.8 W/kg

SAR(1 g) = 8.1 W/kg

Deviation = -3.69%



0 dB = 20.4 W/kg = 13.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.277 \text{ S/m}$; $\epsilon_r = 46.667$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-02-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(3.97, 3.97, 3.97); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.5 W/kg

SAR(1 g) = 7.21 W/kg

Deviation = -7.56%



0 dB = 17.5 W/kg = 12.43 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D750V3-1046_Feb14**

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1046**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

CC✓
3/6/14

Calibration date: **February 27, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Jeton Kastrati** **Function: Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: February 27, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.7 ± 6 %	0.90 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.27 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.42 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.2 ± 6 %	0.98 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.18 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.54 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.43 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.63 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	56.4 Ω + 2.1 j Ω
Return Loss	- 24.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.8 Ω - 2.0 j Ω
Return Loss	- 33.5 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.032 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 02, 2011

DASY5 Validation Report for Head TSL

Date: 21.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1046

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.37, 6.37, 6.37); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.936 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 2.1 W/kg; SAR(10 g) = 1.37 W/kg

Maximum value of SAR (measured) = 2.46 W/kg




0 dB = 2.46 W/kg = 3.91 dBW/kg

Impedance Measurement Plot for Head TSL

21 Feb 2014 09:11:00


CH1 S11 1 U FS 1: 56.385 Δ 2.1367 Δ 453.43 μ H 750.000 000 MHz

*
Del
CA
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -23.975 dB 750.000 000 MHz

Del
CA
Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 27.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1046

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 54.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.13, 6.13, 6.13); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.721 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.20 W/kg

SAR(1 g) = 2.18 W/kg; SAR(10 g) = 1.43 W/kg

Maximum value of SAR (measured) = 2.54 W/kg




0 dB = 2.54 W/kg = 4.05 dBW/kg

Impedance Measurement Plot for Body TSL


27 Feb 2014 10:22:29
[CH1] S11 1 U FS 1: 50.007 Ω -1.9805 Ω 107.15 pF 750.000 000 MHz

*
Del
Cor
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -33.462 dB 750.000 000 MHz

Cor
Avg
16
H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d119_Apr14**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d119**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

*OCV
4/25/14*

Calibration date: **April 07, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
D4E4	SN: 601	25-Apr-13 (No. D4E4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Leif Klysner** Function: **Laboratory Technician**

Signature: *Leif Klysner*

Approved by: **Katja Pokovic** Technical Manager

Katja Pokovic

Issued: April 9, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.6 ± 6 %	0.94 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.22 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.53 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.97 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	53.6 ± 6 %	1.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.44 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.34 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.59 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.15 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.2 Ω - 1.6 j Ω
Return Loss	- 34.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.3 Ω - 4.5 j Ω
Return Loss	- 24.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.386 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	June 29, 2010

DASY5 Validation Report for Head TSL

Date: 07.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.289 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.59 W/kg


SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.53 W/kg

Maximum value of SAR (measured) = 2.80 W/kg



0 dB = 2.80 W/kg = 4.47 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 07.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.02 \text{ S/m}$; $\epsilon_r = 53.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.594 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.61 W/kg

SAR(1 g) = 2.44 W/kg; SAR(10 g) = 1.59 W/kg

Maximum value of SAR (measured) = 2.85 W/kg





0 dB = 2.85 W/kg = 4.55 dBW/kg

Impedance Measurement Plot for Body TSL

7 Apr 2014 11:08:44
 [CH1] S11 1 U FS 1i 46.309 Ω -4.5078 Ω 42.203 pF 835.000 000 MHz

*
 Del
 CA
 Avg
 16
 H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d132_Jul14**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d132**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 10, 2014**

✓
KOK
7/17/14

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	30-Apr-14 (No. DAE4-601_Apr14)	Apr-15
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Michael Weber** Function: **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** Technical Manager

Issued: July 11, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	41.1 \pm 6 %	0.94 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.40 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.27 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.55 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.03 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	53.8 \pm 6 %	1.02 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.50 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.58 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.63 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.30 W/kg \pm 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.0 Ω - 1.6 j Ω
Return Loss	- 31.9 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.7 Ω - 3.4 j Ω
Return Loss	- 27.5 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.386 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 22, 2011

DASY5 Validation Report for Head TSL

Date: 10.07.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d132

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 41.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.43 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.62 W/kg

SAR(1 g) = 2.4 W/kg; SAR(10 g) = 1.55 W/kg

Maximum value of SAR (measured) = 2.83 W/kg




0 dB = 2.83 W/kg = 4.52 dBW/kg

Impedance Measurement Plot for Head TSL

10 Jul 2014 11:02:43

[CH1] S11 1 U FS 1: 52.027 Δ -1.6016 Δ 119.01 pF 835.000 000 MHz

*
De1
C Δ



Avg
16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -31.921 dB 835.000 000 MHz

C Δ

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 09.07.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d132

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 1.02$ S/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/ $P_{in}=250$ mW, $d=15$ mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 55.35 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.5 W/kg; SAR(10 g) = 1.63 W/kg

Maximum value of SAR (measured) = 2.91 W/kg



0 dB = 2.91 W/kg = 4.64 dBW/kg

Impedance Measurement Plot for Body TSL

9 Jul 2014 09:46:12

CH1 S11 1 U FS

1: 47.682 Ω -3.3965 Ω 56.118 pF

835.000 000 MHz


*

De1

CA

Avg
16

H1d



CH2

S11 LOG

5 dB/REF -20 dB


1: -27.522 dB

835.000 000 MHz

CA

Avg
16

H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1765V2-1008_May14**

CALIBRATION CERTIFICATE

Object **D1765V2 - SN: 1008**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

*CCV
6/2/14*

Calibration date: **May 07, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	30-Apr-14 (No. DAE4-601_Apr14)	Apr-15
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Name** Jeton Kastrati **Function** Laboratory Technician **Signature** *[Signature]*

Approved by: **Name** Katja Pokovic **Technical Manager** *[Signature]*

Issued: May 12, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	39.0 \pm 6 %	1.36 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.23 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.9 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	4.87 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.5 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.49 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	52.2 \pm 6 %	1.48 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.41 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	37.6 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.02 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.1 W/kg \pm 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	47.7 Ω - 6.1 j Ω
Return Loss	- 23.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	43.7 Ω - 6.4 j Ω
Return Loss	- 20.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.211 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 06, 2005

DASY5 Validation Report for Head TSL

Date: 07.05.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.23, 5.23, 5.23); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.06 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.23 W/kg; SAR(10 g) = 4.87 W/kg

Maximum value of SAR (measured) = 11.7 W/kg




0 dB = 11.7 W/kg = 10.68 dBW/kg

Impedance Measurement Plot for Head TSL

7 May 2014 09:22:35


CH1 S11 1 U FS 1: 47.709 Ω -6.0566 Ω 15.016 pF 1 750.000 000 MHz

*
De1
C Δ
Avg
16
H1 d



CH2 S11 LOG 5 dB/REF -20 dB 1:-23.588 dB 1 750.000 000 MHz

C Δ
Avg
16
H1 d



DASY5 Validation Report for Body TSL

Date: 07.05.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.48$ S/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.89, 4.89, 4.89); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.01 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 16.3 W/kg

SAR(1 g) = 9.41 W/kg; SAR(10 g) = 5.02 W/kg

Maximum value of SAR (measured) = 11.8 W/kg




0 dB = 11.8 W/kg = 10.72 dBW/kg

Impedance Measurement Plot for Body TSL

7 May 2014 09:21:55


CH1 S11 1 U FS 1: 43.727 Ω -5.3691 Ω 14.279 pF 1 750.000 000 MHz

*
De1
CA
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-20.428 dB 1 750.000 000 MHz

CA
Avg
16
H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1900V2-5d141_Apr14**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d141**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **April 09, 2014**

✓
Kok
5/7/14

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047,2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 801	25-Apr-13 (No. DAE4-801_Apr13)	Apr-14

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Claudio Leubler** Name: Claudio Leubler Function: Laboratory Technician

Approved by: **Katja Pokovic** Name: Katja Pokovic Technical Manager

Signature

Issued: April 9, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	39.1 \pm 6 %	1.36 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.91 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	40.1 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.17 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	20.8 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	52.4 \pm 6 %	1.52 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.2 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	40.6 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.41 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.6 W/kg \pm 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.8 Ω + 5.5 j Ω
Return Loss	- 24.5 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.8 Ω + 6.3 j Ω
Return Loss	- 23.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.199 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 11, 2011

DASY5 Validation Report for Head TSL

Date: 09.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d141

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.06, 5.06, 5.06); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/ $P_{in}=250$ mW, $d=10$ mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 99.080 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.2 W/kg

SAR(1 g) = 9.91 W/kg; SAR(10 g) = 5.17 W/kg

Maximum value of SAR (measured) = 12.5 W/kg




0 dB = 12.5 W/kg = 10.97 dBW/kg

Impedance Measurement Plot for Head TSL

9 Apr 2014 11:03:32

CH1 S11 1 U FS 1: 52.760 n 5.4512 n 456.62 pH 1 900.000 000 MHz

*
Del
CA



AVG
16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -24.525 dB 1 900.000 000 MHz

CA

AVG
16

H1d



START 1 700.000 000 MHz

STOP 2 100.000 000 MHz

DASY5 Validation Report for Body TSL

Date: 09.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d141

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.820 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 17.9 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.41 W/kg

Maximum value of SAR (measured) = 12.9 W/kg




0 dB = 12.9 W/kg = 11.11 dBW/kg

Impedance Measurement Plot for Body TSL

9 Apr 2014 11:02:32


CH1 S11 1 U FS 1: 48.752 Ω 6.3320 Ω 530.41 μ H 1 900.000 000 MHz

*
Del
CA
Avg
16
↑



CH2 S11 LOG 5 dB/REF -20 dB 1: -23.715 dB 1 900.000 000 MHz

CA
Avg
16
↑



START 1 700.000 000 MHz

STOP 2 100.000 000 MHz



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1900V2-5d148_Feb14**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d148**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **February 27, 2014**

*CCV
27/2/2014*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Jeton Kastrati** Name: **Jeton Kastrati** Function: **Laboratory Technician** Signature: *[Signature]*

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Function: **Technical Manager** Signature: *[Signature]*

Issued: February 27, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	38.9 ± 6 %	1.39 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	10.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	40.7 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.2 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.8 ± 6 %	1.49 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.73 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	39.3 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.7 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.5 Ω + 5.5 j Ω
Return Loss	- 24.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.0 Ω + 6.7 j Ω
Return Loss	- 23.0 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.197 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 11, 2011

DASY5 Validation Report for Head TSL

Date: 27.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.06, 5.06, 5.06); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.796 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.31 W/kg

Maximum value of SAR (measured) = 12.8 W/kg



0 dB = 12.8 W/kg = 11.07 dBW/kg

Impedance Measurement Plot for Head TSL

27 Feb 2014 09:42:31


CH1 S11 1 U FS 4: 52.533 Δ 5.5234 Δ 462.67 pH 1 900.000 000 MHz

*
De1

CA

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 4:-24.552 dB 1 900.000 000 MHz

CA

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 27.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.520 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 9.73 W/kg; SAR(10 g) = 5.15 W/kg

Maximum value of SAR (measured) = 12.2 W/kg



0 dB = 12.2 W/kg = 10.86 dBW/kg

Impedance Measurement Plot for Body TSL

27 Feb 2014 09:42:04

CH1 S11 1 U FS


4: 47.971 Ω 6.6777 Ω 559.37 pF 1 900.000 000 MHz

*
De1

CA

Avg
16

H1d



CH2 S11 LOG


5 dB/REF -20 dB

4:-22.970 dB 1 900.000 000 MHz

CA

Avg
16

H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D2450V2-797_Jan14**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 797**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **January 21, 2014**

*CC ✓
2/5/14*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	<i>Israe El-Naouq</i>
Approved by:	Katja Pokovic	Technical Manager	<i>Katja Pokovic</i>

Issued: January 21, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	38.7 ± 6 %	1.86 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.8 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.13 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.3 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	51.3 ± 6 %	2.04 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.7 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.4 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.86 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.1 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.5 \Omega + 3.2 j\Omega$
Return Loss	- 26.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$50.0 \Omega + 4.9 j\Omega$
Return Loss	- 26.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.151 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 24, 2006

DASY5 Validation Report for Head TSL

Date: 21.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.151 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 27.5 W/kg

SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.13 W/kg

Maximum value of SAR (measured) = 16.9 W/kg




0 dB = 16.9 W/kg = 12.28 dBW/kg

Impedance Measurement Plot for Head TSL

21 Jan 2014 11:31:52


CHI S11 1 U FS 2: 53.512 Δ 3.2285 Δ 209.73 pH 2 450.000 000 MHz

*
De1
CA
Avg
1E
H1d



CH2 S11 LOG 5 dB/REF -20 dB 2:-26.730 dB 2 450.000 000 MHz

CA
Avg
1E
H1d



DASY5 Validation Report for Body TSL

Date: 21.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.04$ S/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.35, 4.35, 4.35); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.709 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 26.4 W/kg

SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.86 W/kg

Maximum value of SAR (measured) = 16.8 W/kg




0 dB = 16.8 W/kg = 12.25 dBW/kg

Impedance Measurement Plot for Body TSL

21 Jan 2014 11:31:29

CH1 S11 1 U FS 2: 49.994 Ω 4.9258 Ω 319.98 μH 2 450.000 000 MHz

*
De l
C Δ



Avg
16


H1 d

CH2 S11 LOG 5 dB/REF -20 dB 2:-26.162 dB 2 450.000 000 MHz

C Δ

Avg
16

H1 d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D2450V2-882_Feb14**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 882**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

*CCV
3/16/14*

Calibration date: **February 24, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name Israe El-Naouq	Function Laboratory Technician	Signature <i>Israe El-Naouq</i>
Approved by:	Katja Pokovic	Technical Manager	<i>Katja Pokovic</i>

Issued: February 25, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	38.1 ± 6 %	1.86 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.3 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.0 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.12 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	50.7 ± 6 %	2.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.7 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.87 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.1 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	53.5 Ω - 0.9 j Ω
Return Loss	- 29.1 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.1 Ω + 1.5 j Ω
Return Loss	- 36.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.159 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 06, 2011

DASY5 Validation Report for Head TSL

Date: 24.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 882

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 38.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.531 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 27.8 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.12 W/kg

Maximum value of SAR (measured) = 17.0 W/kg



0 dB = 17.0 W/kg = 12.30 dBW/kg

Impedance Measurement Plot for Head TSL

24 Feb 2014 13:16:01


CH1 S11 1 U FS 2: 53.500 ω -910.16 m ω 71.374 pF 2 450.000 000 MHz

*
De1

C Δ

Avg
16

H1 d




CH2 S11 LOG 5 dB/REF -20 dB 2:-29.134 dB 2 450.000 000 MHz

C Δ

Avg
16

H1 d



DASY5 Validation Report for Body TSL

Date: 24.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 882

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.02$ S/m; $\epsilon_r = 50.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.35, 4.35, 4.35); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scau (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.329 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 26.8 W/kg

SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.87 W/kg

Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.9 W/kg = 12.28 dBW/kg

Impedance Measurement Plot for Body TSL

24 Feb 2014 13:15:34


CH1 S11 1 U FS 2: 50.098 Δ 1.5254 Δ 99.091 pH 2 450.000 000 MHz

*
Del

CA

Avg
16

H1 d




CH2 S11 LOG 5 dB/REF -20 dB 2: -36.332 dB 2 450.000 000 MHz

CA

Avg
16

H1 d



**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D2600V2-1004_Apr14**

CALIBRATION CERTIFICATE

Object **D2600V2 - SN: 1004**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 08, 2014**

*✓ Kok
9/7/14*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292703	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (In house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name Leif Klysner	Function Laboratory Technician	Signature <i>Leif Klysner</i>
Approved by:	Katja Pokovic	Technical Manager	<i>Katja Pokovic</i>

Issued: April 9, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2600 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.0	1.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.7 ± 6 %	1.98 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	14.5 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	57.3 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.44 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	25.6 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.5	2.16 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	50.2 ± 6 %	2.19 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	14.4 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	56.7 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.38 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	25.2 W/kg ± 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.4 Ω - 4.8 j Ω
Return Loss	- 26.3 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.4 Ω - 3.3 j Ω
Return Loss	- 25.9 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.149 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	December 23, 2006

DASY5 Validation Report for Head TSL

Date: 08.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1004

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 37.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEBE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.46, 4.46, 4.46); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 30.7 W/kg

SAR(1 g) = 14.5 W/kg; SAR(10 g) = 6.44 W/kg

Maximum value of SAR (measured) = 19.3 W/kg




0 dB = 19.3 W/kg = 12.86 dBW/kg

Impedance Measurement Plot for Head TSL

8 Apr 2014 11:32:03

CH1 S11 1 U FS 1: 49.363 Ω -4.7871 Ω 12.787 pF 2 600.000 000 MHz

*
De1
CA



Avg
16

H1d


CH2 S11 LOG 5 dB/REF -20 dB 1: -26.275 dB 2 600.000 000 MHz

De1

CA

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 08.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1004

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.19$ S/m; $\epsilon_r = 50.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.24, 4.24, 4.24); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAB4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.472 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 31.1 W/kg

SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.38 W/kg

Maximum value of SAR (measured) = 19.4 W/kg




Impedance Measurement Plot for Body TSL

8 Apr 2014 11:31:17

CH1 S11 1 U FS 1t 46.412 Ω -3.3477 Ω 18.285 pF 2 600.000 000 MHz

*
De1
Ca
Avg
16
H1d



CH2 S11 L00 5 dB/REF -20 dB 1t -25.872 dB 2 600.000 000 MHz

De1
Ca
Avg
16
H1d

