



HCT CO., LTD.

CERTIFICATION DIVISION
105-1, JANGAM-RI, MAJANG-MYEON, ICHEON-SI, KYOUNGKI-DO, REPUBLIC OF KOREA
TEL: +82 31 645 6300 FAX: +82 31 645 6401

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.

10101 Old Grove Road, San Diego, CA 92131

Date of Issue: February 17, 2012

Test Report No.: HCTE1202FE12

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

ZNFP936

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : GSM Phone with Bluetooth and WLAN
Model(s) Name : LG-P936
Port / Connector(s) : USB Port / Headset Port
Date of Issue : February 07, 2012 - February 13, 2012

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Report prepared by
: Jeong-Hyeon Choi
Test Engineer of EMC Team

Approved by
: Sang-Jun Lee
Manager of EMC Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	3
1.1 Product Description.....	3
1.2 Related Submittal(s) / Grant(s).....	3
1.3 Tested System Details.....	4
1.4 Cable Description	5
1.5 Noise Suppression Parts on Cable. (I/O cable)	5
1.6 Test Methodology	6
1.7 Test Facility	6
1.8 Frequency Range of Radiated Measurements	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 Configuration of Test System.....	7
3. PRELIMINARY TEST	8
3.1 Conducted Emission Test	8
3.2 Radiated Emission Test	8
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	9
4.1 Conducted Emission Test	9
4.2 Radiated Emission Test	10
5. FIELD STRENGTH CALCULATION	15
6. TEST EQUIPMENT.....	16
7. CONCLUSION	17

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is **GSM Phone with Bluetooth and WLAN, Model: LG-P936** manufactured by **LG Electronics MobileComm U.S.A., Inc.** Its basic purpose is used for communications.

Model	LG-P936
FCC ID	ZNFP936
E.U.T Type	GSM Phone with Bluetooth and WLAN
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Manufacturer	Model Name	FCC ID / DoC	Connected To
GSM Phone with Bluetooth and WLAN	LG	LG-P936	ZNFP936	Notebook PC
Notebook PC	LG	X140-02	DoC	E.U.T Notebook PC adaptor
Notebook PC adaptor	DELTA (JIANG SU)	ADP-40PH AD	-	Notebook PC
Mouse	PRIMAX ELECTRONICS	MOARUO	DoC	Notebook PC
Micro SD card (2 GB)	SanDisk	-	-	E.U.T
USB cable	-	-	-	E.U.T Notebook PC
Headset	-	-	-	E.U.T
RJ45 cable	-	-	-	Router Notebook PC
Router	-	MW-2100R	-	Notebook PC
Router adaptor	Dee Van Electronics(Shenzhen)Co., Ltd.	DSA-0101F-05KA1	-	Router

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
GSM Phone with Bluetooth and WLAN	Micro USB	Y	Y	(P,D)1.2
	Headset jack	-	N	(D)1.2
Notebook PC	RJ 45	-	N	(D)1.5
	USB (Mouse)	-	Y	(D)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
GSM Phone with Bluetooth and WLAN	Micro USB	N	N/A	Y	Both End
	Headset jack	N	N/A	Y	E.U.T End
Notebook PC	RJ 45	N	N/A	N	Both End
	USB (Mouse)	-	-	Y	Notebook PC End

1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to E.U.T distance of 3 m

1.7 Test Facility

The 3 m semi anechoic chamber used to collect the test data is located at the 105-1, Jangam-Ri, Majang-Myeon, Icheon-Si, Kyoungki-Do, Republic of Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4.

Detailed description of test facilities was submitted to the Commission and accepted dated Mar 02, 2011 (Registration Number: 90661)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower


2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System

Power Line Conducted test : E.U.T was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

Radiated Emission test : Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Frequency Range (Test Limit)	: 0.15 MHz to 0.5 MHz Quasi-Peak(66dB μ V) Average (56 dB μ V) : 0.5 MHz to 5 MHz Quasi-Peak(56dB μ V) Average (46 dB μ V) : 5 MHz to 30 MHz Quasi-Peak(60dB μ V) Average (50 dB μ V)
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
Temperature	: 24.3 °C
Humidity Level	: 50.3 %
Test Date	: February 13, 2012

※ **NOTE:** Refer to page 10 to page 13 for details.


HCT

EMC

EUT: P936
 Manufacturer: LG
 Operating Condition: DATA MODE
 Test Site: SHIELD ROOM
 Operator: JH CHOI
 Test Specification: FCC PART15 CLASS B
 Comment: H

SCAN TABLE: "FCC PART 15 B(H)"

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin_QP"

2/13/2012 10:50AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.150010	51.20	10.1	66	14.8	---	---
0.228010	42.20	10.1	63	20.3	---	---
0.335010	34.20	10.1	59	25.1	---	---
3.404000	35.20	10.3	56	20.8	---	---
3.488000	36.40	10.3	56	19.6	---	---
3.600000	35.20	10.4	56	20.8	---	---
20.464000	51.20	11.9	60	8.8	---	---
20.632000	51.60	11.9	60	8.4	---	---
20.700000	51.60	11.9	60	8.4	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2/13/2012 10:50AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.188010	26.00	10.1	54	28.1	---	---
0.252010	18.40	10.1	52	33.3	---	---
0.265010	17.00	10.1	51	34.2	---	---
1.940000	28.30	10.2	46	17.7	---	---
2.004000	28.70	10.2	46	17.3	---	---
2.068000	28.10	10.2	46	17.9	---	---
19.200000	38.80	11.8	50	11.2	---	---
20.712000	43.90	11.9	50	6.1	---	---
22.232000	37.40	12.0	50	12.6	---	---


HCT

EMC

EUT: P936
 Manufacturer: LG
 Operating Condition: DATA MODE
 Test Site: SHIELD ROOM
 Operator: JH CHOI
 Test Specification: FCC PART15 CLASS B
 Comment: N

SCAN TABLE: "FCC PART 15 B(N)"

Short Description:			FCC PART 15 CLASS B			
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average	10.0 ms	9 kHz	None



MEASUREMENT RESULT: "PHONE_fin_QP"

2/13/2012 10:38AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.150010	50.80	10.3	66	15.2	---	---
0.226010	42.40	10.3	63	20.2	---	---
0.338010	34.60	10.3	59	24.7	---	---
2.948000	31.70	10.5	56	24.3	---	---
3.452000	33.70	10.6	56	22.3	---	---
3.468000	35.10	10.6	56	20.9	---	---
18.820000	47.10	11.6	60	12.9	---	---
20.236000	48.60	11.7	60	11.4	---	---
20.448000	51.50	11.7	60	8.5	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2/13/2012 10:38AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.186010	27.20	10.3	54	27.0	---	---
0.250010	23.40	10.3	52	28.3	---	---
0.500000	15.80	10.3	46	30.2	---	---
2.008000	28.70	10.4	46	17.3	---	---
2.072000	27.90	10.4	46	18.1	---	---
3.692000	27.30	10.6	46	18.7	---	---
17.520000	32.90	11.5	50	17.1	---	---
18.812000	39.60	11.6	50	10.4	---	---
20.448000	44.50	11.7	50	5.5	---	---

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Limit Apply to : FCC PART 15 Subpart B Class B

-For measurement below 1 GHz

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

Operation Mode : Data Communication mode

-For measurement above 1 GHz

Detector : Peak mode: Peak (RBW: 1 MHz / VBW: 1 MHz)

: Average mode: Peak (RBW: 1 MHz / VBW: 10 Hz)

Operation Mode : Data Communication mode

Temperature : 22.3 °C

Humidity Level : 50.0 %

Test Date : February 07, 2012

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
64.900	15.16	V	1.0	11.19	3.65	40.0	30.0	10.0
105.800	19.59	H	1.2	10.06	3.86	43.5	33.5	10.0
119.400	17.62	V	1.0	11.78	3.99	43.5	33.4	10.1
240.000	19.34	V	1.0	11.40	4.46	46.0	35.2	10.8
376.000	16.51	H	1.2	15.08	4.90	46.0	36.5	9.5
755.300	5.20	H	1.0	21.80	5.70	46.0	32.7	13.3

※ NOTE:

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. The highest fundamental frequency is GSM 1 900 center frequency.
2. For measurement above 1 GHz, Emission noise was not founded over the ambient noise.

5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
 The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Number</u>	<u>Serial Number</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>				
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	2012.05.03
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	2013.02.03
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	2012.04.01
<input checked="" type="checkbox"/> Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	2012.08.01
<u>Radiated Emission</u>				
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	2012.05.26
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	2012.08.02
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3125	2013.05.03
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2012.09.13
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	-
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD100	100/637BJ:00	-
<input checked="" type="checkbox"/> Turn Table	HD GmbH	2090	9702/1224	-
<input checked="" type="checkbox"/> Power Amplifier	Rohde & Schwarz	SCU-18	10094	2012.09.19
<input type="checkbox"/> Communication Antenna	Schwarzbeck	USLP9142	9142-248	-
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	-	2012.04.13
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	937	2013.10.17

7. CONCLUSION

The data collected shows that the **GSM Phone with Bluetooth and WLAN, FCC ID: ZNFP936, Model: LG-P936** complies with §15.107 and §15.109 of the FCC rules.