


## Band 66/4



**Plot 7-344. Radiated Spurious Plot above 1GHz (Band 66/4)**

OPERATING FREQUENCY: 1710.70 MHz

MODULATION SIGNAL: QPSK

BANDWIDTH: 1.4 MHz

DISTANCE: 3 meters

LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3421.40	H	108	55	-64.53	6.22	-58.31	-45.3
5132.10	H	-	-	-70.00	8.68	-61.32	-48.3
6842.80	H	102	42	-58.57	8.76	-49.81	-36.8
8553.50	H	-	-	-65.79	9.17	-56.62	-43.6
10264.20	H	-	-	-64.49	9.64	-54.86	-41.9

**Table 7-27. Radiated Spurious Data (Band 66/4 – Low Channel)**

FCC ID: ZNFQ620WA	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset			Page 217 of 244

OPERATING FREQUENCY: 1745.00 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 1.4 MHz  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3490.00	H	201	18	-66.80	6.32	-60.47	-47.5
5235.00	H	-	-	-69.57	8.71	-60.85	-47.9
6980.00	H	108	48	-60.40	8.74	-51.67	-38.7
8725.00	H	-	-	-65.87	9.42	-56.46	-43.5
10470.00	H	-	-	-64.22	9.62	-54.60	-41.6

Table 7-28. Radiated Spurious Data (Band 66/4 – Mid Channel)


OPERATING FREQUENCY: 1779.30 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 1.4 MHz  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3558.60	H	365	5	-67.02	6.31	-60.72	-47.7
5337.90	H	-	-	-69.44	8.74	-60.70	-47.7
7117.20	H	377	356	-64.90	8.66	-56.24	-43.2
8896.50	H	-	-	-66.26	9.53	-56.73	-43.7
10675.80	H	-	-	-63.76	9.50	-54.26	-41.3

Table 7-29. Radiated Spurious Data (Band 66/4 – High Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 218 of 244

## Band 25/2



**Plot 7-345. Radiated Spurious Plot above 1GHz (Band 25/2)**

OPERATING FREQUENCY: 1855.00 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3710.00	V	-	-	-67.75	6.58	-61.17	-48.2
5565.00	V	-	-	-69.38	8.74	-60.64	-47.6

**Table 7-30. Radiated Spurious Data (Band 25/2 – Low Channel)**

FCC ID: ZNFQ620WA	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 219 of 244

OPERATING FREQUENCY: 1882.50 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3765.00	V	-	-	-68.07	6.70	-61.38	-48.4
5647.50	V	-	-	-68.69	8.83	-59.86	-46.9

Table 7-31. Radiated Spurious Data (Band 25/2 – Mid Channel)


OPERATING FREQUENCY: 1910.00 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3820.00	V	-	-	-67.74	6.94	-60.81	-47.8
5730.00	V	-	-	-67.77	8.77	-59.01	-46.0


Table 7-32. Radiated Spurious Data (Band 25/2 – High Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 220 of 244

## Band 7



**Plot 7-346. Radiated Spurious Plot above 1GHz – 18GHz (Band 7)**



**Plot 7-347. Radiated Spurious Plot above 18GHz – 26.5GHz (Band 7)**

FCC ID: ZNFQ620WA	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>MEASUREMENT REPORT (CERTIFICATION)</b>	LG	Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 221 of 244

OPERATING FREQUENCY: 2502.50 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5005.00	H	158	344	-54.34	8.56	-45.78	-20.8
7507.50	H	237	26	-64.63	8.52	-56.12	-31.1
10010.00	H	105	364	-63.52	9.85	-53.67	-28.7
12512.50	H	-	-	-61.43	9.08	-52.35	-27.4
15015.00	H	-	-	-58.72	8.79	-49.93	-24.9

Table 7-33. Radiated Spurious Data (Band 7 – Low Channel)

OPERATING FREQUENCY: 2535.00 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5070.00	H	130	15	-54.42	8.60	-45.82	-20.8
7605.00	H	249	28	-63.33	8.48	-54.85	-29.8
10140.00	H	113	1	-62.96	9.78	-53.17	-28.2
12675.00	H	-	-	-60.58	9.08	-51.50	-26.5
15210.00	H	-	-	-57.81	8.47	-49.35	-24.3

Table 7-34. Radiated Spurious Data (Band 7 – Mid Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 222 of 244


OPERATING FREQUENCY: 2567.50 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5135.00	H	108	14	-52.45	8.66	-43.78	-18.8
7702.50	H	277	20	-64.10	8.59	-55.51	-30.5
10270.00	H	121	1	-64.21	9.64	-54.58	-29.6
12837.50	H	-	-	-61.18	9.13	-52.05	-27.0
15405.00	H	-	-	-57.70	8.47	-49.23	-24.2


Table 7-35. Radiated Spurious Data (Band 7 – High Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 223 of 244

## Band 41



**Plot 7-348. Radiated Spurious Plot above 1GHz – 18GHz (Band 41)**



**Plot 7-349. Radiated Spurious Plot above 18GHz – 26.5GHz (Band 41)**

FCC ID: ZNFQ620WA	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>MEASUREMENT REPORT (CERTIFICATION)</b>	LG	Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 224 of 244



OPERATING FREQUENCY: 2507.50 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5015.00	H	100	10	-48.40	8.76	-39.63	-14.6
7522.50	H	285	364	-64.25	9.31	-54.93	-29.9
10030.00	H	-	-	-62.26	9.80	-52.47	-27.5
12537.50	H	-	-	-58.58	8.84	-49.74	-24.7

Table 7-36. Radiated Spurious Data (Band 41 – Low Channel)

OPERATING FREQUENCY: 2593.00 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5186.00	H	100	4	-46.82	9.03	-37.80	-12.8
7779.00	H	299	13	-60.99	9.29	-51.70	-26.7
10372.00	H	-	-	-62.69	9.50	-53.19	-28.2
12965.00	H	-	-	-58.02	8.75	-49.26	-24.3

Table 7-37. Radiated Spurious Data (Band 41 – Mid Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 225 of 244

OPERATING FREQUENCY: 2682.50 MHz  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT: -25 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
5365.00	H	100	2	-53.95	8.99	-44.96	-20.0
8047.50	H	301	5	-62.72	9.35	-53.38	-28.4
10730.00	H	-	-	-61.26	9.38	-51.88	-26.9
13412.50	H	-	-	-57.77	8.65	-49.12	-24.1

Table 7-38. Radiated Spurious Data (Band 41 – High Channel)

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 226 of 244

## 7.8 Frequency Stability / Temperature Variation

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 24, Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-E-2016

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 227 of 244

## Band 71 Frequency Stability Measurements

OPERATING FREQUENCY: 680,500,000 Hz  
 CHANNEL: 133372  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	680,500,061	61	0.0000090
100 %		- 20	680,500,166	166	0.0000244
100 %		- 10	680,499,977	-23	-0.0000034
100 %		0	680,500,215	215	0.0000316
100 %		+ 10	680,499,959	-41	-0.0000060
100 %		+ 20	680,499,881	-119	-0.0000175
100 %		+ 30	680,499,806	-194	-0.0000285
100 %		+ 40	680,500,096	96	0.0000141
100 %		+ 50	680,500,196	196	0.0000288
BATT. ENDPOINT	2.93	+ 20	680,499,811	-189	-0.0000278


**Table 7-39. Frequency Stability Data (Band 71)**

### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 228 of 244	

## Band 71 Frequency Stability Measurements



**Figure 7-8. Frequency Stability Graph (Band 71)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 229 of 244

## Band 12/17 Frequency Stability Measurements

OPERATING FREQUENCY: 707,500,000 Hz  
 CHANNEL: 23790  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	707,499,963	-37	-0.0000052
100 %		- 20	707,500,319	319	0.0000451
100 %		- 10	707,499,918	-82	-0.0000116
100 %		0	707,499,807	-193	-0.0000273
100 %		+ 10	707,500,112	112	0.0000158
100 %		+ 20	707,499,788	-212	-0.0000300
100 %		+ 30	707,500,198	198	0.0000280
100 %		+ 40	707,500,106	106	0.0000150
100 %		+ 50	707,499,805	-195	-0.0000276
BATT. ENDPOINT	2.93	+ 20	707,500,125	125	0.0000177


**Table 7-40. Frequency Stability Data (Band 12/17)**

### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 230 of 244

## Band 12/17 Frequency Stability Measurements



**Figure 7-9. Frequency Stability Graph (Band 12/17)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 231 of 244

## Band 13 Frequency Stability Measurements

OPERATING FREQUENCY: 782,000,000 Hz  
 CHANNEL: 23230  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	782,000,101	101	0.0000129
100 %		- 20	782,000,332	332	0.0000425
100 %		- 10	782,000,028	28	0.0000036
100 %		0	782,000,125	125	0.0000160
100 %		+ 10	781,999,928	-72	-0.0000092
100 %		+ 20	781,999,517	-483	-0.0000618
100 %		+ 30	781,999,894	-106	-0.0000136
100 %		+ 40	782,000,022	22	0.0000028
100 %		+ 50	782,000,005	5	0.0000006
BATT. ENDPOINT	2.93	+ 20	781,999,866	-134	-0.0000171

**Table 7-41. Frequency Stability Data (Band 13)**


### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 232 of 244	



## Band 13 Frequency Stability Measurements



**Figure 7-10. Frequency Stability Graph (Band 13)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 233 of 244

## Band 26/5 Frequency Stability Measurements


OPERATING FREQUENCY: 831,500,000 Hz  
 CHANNEL: 26865  
 REFERENCE VOLTAGE: 4.33 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	831,499,788	-212	-0.0000255
100 %		- 20	831,499,963	-37	-0.0000044
100 %		- 10	831,500,044	44	0.0000053
100 %		0	831,499,722	-278	-0.0000334
100 %		+ 10	831,499,954	-46	-0.0000055
100 %		+ 20	831,499,840	-160	-0.0000192
100 %		+ 30	831,499,992	-8	-0.0000010
100 %		+ 40	831,500,033	33	0.0000040
100 %		+ 50	831,499,857	-143	-0.0000172
BATT. ENDPOINT	2.93	+ 20	831,500,218	218	0.0000262

**Table 7-42. Frequency Stability Data (Band 26/5)**

FCC ID: ZNFQ620WA	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 234 of 244

## Band 26/5 Frequency Stability Measurements



**Figure 7-11. Frequency Stability Graph (Band 26/5)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 235 of 244

## Band 66/4 Frequency Stability Measurements

OPERATING FREQUENCY: 1,745,000,000 Hz  
 CHANNEL: 132322  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	1,744,999,968	-32	-0.0000018
100 %		- 20	1,744,999,959	-41	-0.0000023
100 %		- 10	1,744,999,962	-38	-0.0000022
100 %		0	1,745,000,099	99	0.0000057
100 %		+ 10	1,744,999,954	-46	-0.0000026
100 %		+ 20	1,744,999,947	-53	-0.0000030
100 %		+ 30	1,744,999,768	-232	-0.0000133
100 %		+ 40	1,745,000,015	15	0.0000009
100 %		+ 50	1,744,999,911	-89	-0.0000051
BATT. ENDPOINT	2.93	+ 20	1,744,999,789	-211	-0.0000121


**Table 7-43. Frequency Stability Data (Band 66/4)**

### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 236 of 244	

## Band 66/4 Frequency Stability Measurements



**Figure 7-12. Frequency Stability Graph (Band 66/4)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 237 of 244

## Band 25/2 Frequency Stability Measurements

OPERATING FREQUENCY: 1,882,500,000 Hz  
 CHANNEL: 26365  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	1,882,500,085	85	0.0000045
100 %		- 20	1,882,500,110	110	0.0000058
100 %		- 10	1,882,499,807	-193	-0.0000103
100 %		0	1,882,500,024	24	0.0000013
100 %		+ 10	1,882,499,959	-41	-0.0000022
100 %		+ 20	1,882,500,133	133	0.0000071
100 %		+ 30	1,882,500,190	190	0.0000101
100 %		+ 40	1,882,499,807	-193	-0.0000103
100 %		+ 50	1,882,500,087	87	0.0000046
BATT. ENDPOINT	2.93	+ 20	1,882,499,661	-339	-0.0000180


Table 7-44. Frequency Stability Data (Band 25/2)

### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 238 of 244

## Band 25/2 Frequency Stability Measurements



**Figure 7-13. Frequency Stability Graph (Band 25/2)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 239 of 244

## Band 7 Frequency Stability Measurements

OPERATING FREQUENCY: 2,535,000,000 Hz  
 CHANNEL: 21100  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	2,535,000,258	258	0.0000102
100 %		- 20	2,535,000,363	363	0.0000143
100 %		- 10	2,534,999,790	-210	-0.0000083
100 %		0	2,535,000,183	183	0.0000072
100 %		+ 10	2,535,000,138	138	0.0000054
100 %		+ 20	2,534,999,822	-178	-0.0000070
100 %		+ 30	2,534,999,726	-274	-0.0000108
100 %		+ 40	2,534,999,712	-288	-0.0000114
100 %		+ 50	2,535,000,096	96	0.0000038
BATT. ENDPOINT	2.93	+ 20	2,534,999,720	-280	-0.0000110

**Table 7-45. Frequency Stability Data (Band 7)**


### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset	Page 240 of 244



## Band 7 Frequency Stability Measurements



**Figure 7-14. Frequency Stability Graph (Band 7)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 241 of 244

## Band 41 Frequency Stability Measurements

OPERATING FREQUENCY: 2,593,000,000 Hz  
 CHANNEL: 40620  
 REFERENCE VOLTAGE: 4.33 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.33	- 30	2,592,999,771	-229	-0.0000088
100 %		- 20	2,592,999,989	-11	-0.0000004
100 %		- 10	2,592,999,939	-61	-0.0000024
100 %		0	2,593,000,003	3	0.0000001
100 %		+ 10	2,593,000,297	297	0.0000115
100 %		+ 20	2,593,000,401	401	0.0000155
100 %		+ 30	2,592,999,859	-141	-0.0000054
100 %		+ 40	2,592,999,611	-389	-0.0000150
100 %		+ 50	2,592,999,902	-98	-0.0000038
BATT. ENDPOINT	2.93	+ 20	2,593,000,124	124	0.0000048


**Table 7-46. Frequency Stability Data (Band 41)**

### Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 242 of 244

## Band 41 Frequency Stability Measurements



**Figure 7-15. Frequency Stability Graph (Band 41)**

<b>FCC ID:</b> ZNFQ620WA		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1909120153-03-R1.ZNF	<b>Test Dates:</b> 9/12 – 10/14/2019	<b>EUT Type:</b> Portable Handset		Page 243 of 244

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFQ620WA** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules for LTE operation only.

FCC ID: ZNFQ620WA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909120153-03-R1.ZNF	Test Dates: 9/12 – 10/14/2019	EUT Type: Portable Handset		Page 244 of 244