

EMI TEST REPORT

FCC CERTIFICATION

Applicant:

LG Electronics USA, Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632
United States

Date of Issue: April 30, 2019**Test Report No. HCT-EM-1904-FC034****Test Site: HCT CO., LTD.****FCC ID :****ZNFQ720TS**

Rule Part(s) / Standard(s) : 47 CFR PART 15 Subpart B Class B
ANSI C63.4-2014

EUT Type : Multi-band GSM/WCDMA/LTE Phone with BT, WLAN and
NFC

Model Name : LM-Q720TS

Additional Model Name : LMQ720TS, Q720TS, LM-Q720MS, LMQ720MS, Q720MS


Travel Adaptor Information : Model Name: MCS-H06WP / Manufacturer: PNTELECOM

Date of Test : April 21, 2019 to April 28, 2019

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Na-Eun Song
Test Engineer
EMC Team
Certification Division

Reviewed

Jeong-Hyun Choi
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



REVISION HISTORY

The revision history for this document is shown in table.

Report No.	Issue Date	Information About Changes
HCT-EM-1904-FC034	April 30, 2019	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Tested System Details	4
1.3 Cable Description.....	5
1.4 Noise Suppression Parts on Cable. (I/O Cable)	6
1.5 Test Facility	6
1.6 Calibration of Measuring Instrument	6
1.7 Measurement Uncertainty	6
2. LIST OF TEST EQUIPMENT.....	7
3. DESCRIPTION OF TEST	8
3.1 Measurement of Conducted Emission.....	8
3.2 Measurement of Radiated Emission.....	9
4. OPERATING MODES	11
4.1 Conducted Emission.....	11
4.2 Radiated Emission.....	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
5.1 Conducted Emission.....	12
5.2 Radiated Emission.....	19
6. CONCLUSION.....	21
7. APPENDIX A. TEST SETUP PHOTOGRAPHS	22



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFQ720TS
Model	LM-Q720TS
Additional Model	LMQ720TS, Q720TS, LM-Q720MS, LMQ720MS, Q720MS
EUT Type	Multi-band GSM/WCDMA/LTE Phone with BT, WLAN and NFC
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 824.2 MHz to 848.8 MHz (GSM 850) 1 850.2 MHz to 1 909.8 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.4 MHz to 846.6 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 2 496 MHz to 2570 MHz (LTE B7) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 704 MHz to 716 MHz (LTE B17) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 1 710 MHz to 1 780 MHz (LTE B66) 663 MHz to 698 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (NFC)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10) 869.2 MHz to 893.8 MHz (GSM 850) 1 930.2 MHz to 1 989.8 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.4 MHz to 891.6 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 2 516 MHz to 2690 MHz (LTE B7) 729 MHz to 746 MHz (LTE B12)



RX Frequency	746 MHz to 756 MHz (LTE B13) 734 MHz to 746 MHz (LTE B17) 1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 2 110 MHz to 2 200 MHz (LTE B66) 617 MHz to 652 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (NFC)
--------------	--

1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer	FCC ID / DoC
EUT	LM-Q720TS	-	LG	ZNFQ720TS
Data Cable	EAD64746102	-	Luxshare	-
Earphone	EAB64468444	-	CRESYN	-
Micro SD card	SAMSUNG EVO +microSDXC CLASS10 UHS-1 (256 GB)	-	SAMSUNG	-
TA	MCS-H06WP	-	PNTELECOM	-

1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C	Y	N/A	(P) 1.0
	Earphone	N/A	N	(D) 1.2

* The marked "(D)" means the data cable and "(P)" means the power cable.



1.4 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End

1.5 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB
Radiated Emissions (30 MHz to 1 GHz)	5.20 dB
Radiated Emissions (1 GHz to 18 GHz)	5.24 dB
Radiated Emissions (18 GHz to 40 GHz)	5.40 dB



2. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.25.2018
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.27.2018
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	102245	1 year	12.12.2018
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	07.27.2018
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	10.31.2018
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB 9168	255	2 year	03.26.2019
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	03.22.2019
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.14.2018
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	ESU 40	Rohde & Schwarz	100361	1 year	10.11.2018
<input checked="" type="checkbox"/> Antenna master	MA4640/800-XP-ET	NNCO System	-	-	-
<input checked="" type="checkbox"/> Antenna controller	master CO3000	INNCO SYSTEM	CO3000/951/3859 0616/L	-	-
<input checked="" type="checkbox"/> Turn Table	DT3000-3t	INNCO systems	-	-	-
<input checked="" type="checkbox"/> Turn Table controller	CO3000	INNCO SYSTEM	CO3000/999/4024 0317/G	-	-
<input checked="" type="checkbox"/> Power Amplifier	TK-PA18H	TESTEK	170012-L	1 year	03.11.2019
<input checked="" type="checkbox"/> Horn Antenna	BBHA 9120D	Schwarzbeck	1152	2 year	11.29.2017
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 18 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	07.27.2018
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Low Noise Amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.04.2019
<input checked="" type="checkbox"/> Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.17.2018
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V}/\text{m})$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V}/\text{m})$)	Average ($\text{dB}(\mu\text{V}/\text{m})$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Non-Conductive Table
 Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes:

- FRONT CAMERA & MP3 mode
- REAR CAMERA & FM RADIO mode
- IDLE mode

NOTE. The worst-case emissions are reported.

4.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes:

- FRONT CAMERA & MP3 mode
- REAR CAMERA & FM RADIO mode
- IDLE mode

NOTE. The worst-case emissions are reported.



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operating Mode	REAR CAMERA & FM RADIO mode
Kind of Test Site	Shielded Room
Temperature	23.6 °C
Relative Humidity	43.8 %
Test Date	April 21, 2019

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	31.4	9.000	L1	9.7	34.6	66.0
0.158000	31.3	9.000	L1	9.7	34.3	65.6
0.164000	32.0	9.000	L1	9.7	33.2	65.3
0.170000	31.5	9.000	L1	9.7	33.4	65.0
0.176000	31.9	9.000	L1	9.7	32.8	64.7
0.672000	32.6	9.000	L1	9.8	23.4	56.0
1.102000	30.1	9.000	L1	9.8	25.9	56.0
2.436000	33.3	9.000	L1	9.9	22.7	56.0
3.780000	28.1	9.000	L1	10.0	27.9	56.0
4.152000	27.5	9.000	L1	10.0	28.5	56.0
4.342000	27.6	9.000	L1	10.0	28.4	56.0
4.346000	27.0	9.000	L1	10.0	29.0	56.0
9.762000	29.3	9.000	L1	10.2	30.7	60.0
9.884000	28.8	9.000	L1	10.2	31.2	60.0
10.042000	28.4	9.000	L1	10.2	31.6	60.0
10.280000	28.6	9.000	L1	10.2	31.4	60.0
10.304000	29.0	9.000	L1	10.2	31.0	60.0
10.658000	27.5	9.000	L1	10.3	32.5	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	22.6	9.000	L1	9.7	33.4	56.0
0.156000	22.2	9.000	L1	9.7	33.4	55.7
0.166000	26.1	9.000	L1	9.7	29.1	55.2
0.178000	21.1	9.000	L1	9.7	33.5	54.6
0.182000	21.4	9.000	L1	9.7	33.0	54.4
0.670000	19.8	9.000	L1	9.8	26.2	46.0
1.102000	18.0	9.000	L1	9.8	28.0	46.0
2.436000	19.8	9.000	L1	9.9	26.2	46.0
2.442000	17.4	9.000	L1	9.9	28.6	46.0
3.778000	17.3	9.000	L1	10.0	28.7	46.0
4.156000	16.0	9.000	L1	10.0	30.0	46.0
4.342000	17.2	9.000	L1	10.0	28.8	46.0
9.762000	20.4	9.000	L1	10.2	29.6	50.0
9.884000	20.5	9.000	L1	10.2	29.5	50.0
10.042000	20.7	9.000	L1	10.2	29.3	50.0
10.060000	20.5	9.000	L1	10.2	29.5	50.0
10.194000	20.7	9.000	L1	10.2	29.3	50.0
10.304000	20.5	9.000	L1	10.2	29.5	50.0



Figure 2: Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	31.1	9.000	N	9.8	34.7	65.8
0.164000	32.7	9.000	N	9.8	32.6	65.3
0.168000	32.9	9.000	N	9.8	32.2	65.1
0.176000	31.7	9.000	N	9.8	32.9	64.7
0.182000	31.5	9.000	N	9.8	32.9	64.4
0.192000	27.7	9.000	N	9.8	36.3	63.9
1.104000	28.6	9.000	N	10.0	27.4	56.0
2.872000	26.2	9.000	N	10.1	29.8	56.0
4.204000	24.7	9.000	N	10.2	31.3	56.0
4.210000	26.5	9.000	N	10.2	29.5	56.0
4.216000	24.6	9.000	N	10.2	31.4	56.0
4.336000	26.3	9.000	N	10.2	29.7	56.0
27.936000	29.7	9.000	N	11.1	30.3	60.0
28.528000	31.1	9.000	N	11.1	28.9	60.0
28.532000	31.0	9.000	N	11.1	29.0	60.0
28.904000	30.5	9.000	N	11.1	29.6	60.0
29.082000	30.4	9.000	N	11.1	29.6	60.0
29.196000	30.3	9.000	N	11.1	29.7	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.156000	22.3	9.000	N	9.8	33.4	55.7
0.168000	25.3	9.000	N	9.8	29.7	55.1
0.176000	20.9	9.000	N	9.8	33.8	54.7
0.184000	21.2	9.000	N	9.8	33.2	54.3
0.192000	19.5	9.000	N	9.8	34.4	53.9
0.440000	21.8	9.000	N	9.9	25.2	47.1
1.106000	16.8	9.000	N	10.0	29.2	46.0
2.866000	14.5	9.000	N	10.1	31.5	46.0
2.872000	14.5	9.000	N	10.1	31.5	46.0
4.204000	13.9	9.000	N	10.2	32.1	46.0
4.210000	14.5	9.000	N	10.2	31.5	46.0
4.214000	14.2	9.000	N	10.2	31.8	46.0
27.936000	15.8	9.000	N	11.1	34.2	50.0
28.108000	16.3	9.000	N	11.1	33.7	50.0
28.460000	16.5	9.000	N	11.1	33.5	50.0
28.528000	16.6	9.000	N	11.1	33.4	50.0
29.082000	16.3	9.000	N	11.1	33.7	50.0
29.196000	16.1	9.000	N	11.1	33.9	50.0



5.2 Radiated Emission

The test results of radiated emission provide the following information:

For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operating Mode	REAR CAMERA & FM RADIO mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.3 °C
Relative Humidity	43.5 %
Test Date	April 28, 2019

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
30.422846	22.5	100.0	V	36.0	18.3	17.5	40.0
43.476953	21.2	100.0	V	56.0	19.2	18.8	40.0
85.921843	20.7	225.0	H	319.0	14.8	19.3	40.0
125.312625	23.4	100.0	V	246.0	17.8	20.1	43.5
150.346693	22.8	125.1	H	89.0	19.4	20.7	43.5
617.276553	26.4	125.0	H	69.0	27.5	19.6	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	5 825 MHz
Tested Frequency Range	1 GHz to 30 GHz
Operating Mode	REAR CAMERA & FM RADIO mode
Kind of Test Site	10 m semi anechoic chamber
Temperature	22.9 - 23.6 °C
Relative Humidity	42.4 - 43.1 %
Test Date	April 21, 2019

Frequency (MHz)	Peak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)
4717.445300	35.24	70.00	34.76	184.6	H	-4.0	-10.2
5724.446900	36.82	70.00	33.18	202.3	V	352.0	-6.6
6624.943300	40.33	70.00	29.67	124.8	H	140.0	-3.3
8425.197300	42.38	70.00	27.62	124.7	H	172.0	-0.4
10333.461100	47.06	70.00	22.94	99.6	H	140.0	3.6
10612.077500	47.46	70.00	22.54	124.8	V	-15.0	4.7

Frequency (MHz)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)
4717.445300	22.47	50.00	27.53	184.6	H	-4.0	-10.2
5724.446900	24.25	50.00	25.75	202.3	V	352.0	-6.6
6624.943300	27.09	50.00	22.91	124.8	H	140.0	-3.3
8425.197300	29.92	50.00	20.08	124.7	H	172.0	-0.4
10333.461100	33.78	50.00	16.22	99.6	H	140.0	3.6
10612.077500	34.76	50.00	15.24	124.8	V	-15.0	4.7

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. CONCLUSION

The data collected shows that the **EUT Type: Multi-band GSM/WCDMA/LTE Phone with BT, WLAN and NFC, FCC ID: ZNFQ720TS, Model: LM-Q720TS** complies with §15.107 and §15.109 of the FCC rules.



7. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Annex A