

HEARING AID COMPATIBILITY

Applicant Name:
 LG Electronics U.S.A, Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 3/2/2020 - 3/5/2020
Test Site/Location:
 PCTEST, Columbia, MD, USA
Test Report Serial No.:
 1M2002170022-12-R1.ZNF
Date of Issue:
 03/31/2020

FCC ID:	ZNFQ730TM
APPLICANT:	LG ELECTRONICS U.S.A, INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011
 285076 D01 HAC Guidance v05
 285076 D02 T-Coil testing for CMRS IP v03
DUT Type: Portable Handset
Model: LM-Q730TM
Additional Model(s): LM-Q730MM, LMQ730TM, LMQ730MM, Q730TM, Q730MM
Test Device Serial No.: Pre-Production Sample [S/N: 04906]
Class II Permissive Change(s): See FCC Change Document

C63.19-2011 HAC Category:	T3 (SIGNAL TO NOISE CATEGORY)
----------------------------------	--------------------------------------

Note: This revised Test Report (S/N: 1M2002170022-12-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President







FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 1 of 84

TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION.....	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	5
4.	METHOD OF MEASUREMENT	7
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	17
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	21
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	24
8.	FCC 3G MEASUREMENTS	27
9.	T-COIL TEST SUMMARY	29
10.	MEASUREMENT UNCERTAINTY	41
11.	EQUIPMENT LIST	42
12.	TEST DATA	43
13.	CALIBRATION CERTIFICATES.....	72
14.	CONCLUSION.....	79
15.	REFERENCES	80
16.	TEST SETUP PHOTOGRAPHS	82

FCC ID: ZNFQ730TM	 <small>Head to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 2 of 84	

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.






Figure 1-1 Hearing Aid *in-vitu*

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 3 of 84

2. DUT DESCRIPTION



FCC ID: ZNFQ730TM
 Applicant: LG Electronics U.S.A, Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States
 Model: LM-Q730TM
 Additional Model(s): LM-Q730MM, LMQ730TM, LMQ730MM, Q730TM, Q730MM
 Serial Number: 04906
 HW Version: Rev.1.0
 SW Version: Q730TM08u4
 Antenna: Internal Antenna
 DUT Type: Portable Handset

I. LTE Band Selection

This device supports the following pairs of LTE bands with similar frequencies: LTE B26 & B5, B25 & B2, and B66 & B4. These pairs of LTE bands have the same target powers and share the same transmission paths. Since the supported frequency span for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B26, B25, & B66) were evaluated for hearing-aid compliance.

Table 2-1
 ZNFQ730TM HAC Air Interfaces

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	Audio Codec Evaluated
CDMA	835	VO	Yes	Yes: WiFi or BT	CMRS Voice ¹	EVRC
	1900		Yes			
GSM	850	VO	Yes	Yes: WiFi or BT	CMRS Voice ¹	EFR
	1900		Yes			
UMTS	850	VD	Yes	Yes: WiFi or BT	CMRS Voice ¹	NB AMR
	1700		Yes			
LTE (FDD)	680 (B71)	VD	Yes ²	Yes: WiFi or BT	VoLTE ¹ , Google Duo ²	VoLTE: NB AMR, WB AMR, EVS Google Duo: OPUS
	700 (B12)		Yes			
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WiFi or BT	VoLTE ¹ , Google Duo ²	VoLTE: NB AMR, WB AMR, EVS Google Duo: OPUS
	2450		Yes			
WIFI	5300 (U-NII 1)	VD	Yes	Yes: CDMA, GSM, UMTS, or LTE	VoWiFi ³ , Google Duo ²	VoWiFi: NB AMR, WB AMR, EVS Google Duo: OPUS
	5800 (U-NII 3)		Yes			
BT	2450	DT	No	Yes: CDMA, GSM, UMTS, or LTE	N/A	N/A

Type Transport
 VO = Voice Only
 DT = Digital Data - Not Intended for Voice Services
 VD = CMRS and/or IP Voice over Data Transport

Notes:
 1. Reference level in accordance with 7.4.2.1 of ANSI C63.19-2011 and July 2012 C63 VoLTE Interpretation.
 2. Reference level is -20dBm0 in accordance with FCC KDB 285076 D02
 3. LTE B71, while outside the scope of ANSI C63.19 and FCC HAC regulations, was additionally tested according to the existing HAC procedures with currently available test equipment.

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 4 of 84

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be ≥ -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤ -15 dB(A/m) at 1 kHz






Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds -15 dB(A/m) at 1 kHz

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 5 of 84

Signal Quality



The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Category	Telephone RF Parameters
	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]
T1	0 to 10 dB
T2	10 to 20 dB
T3	20 to 30 dB
T4	> 30 dB

Table 3-1
Magnetic Coupling Parameters

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of </small>	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 6 of 84

4. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil






Figure 4-2
T-Coil Test Setup

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 7 of 84

II. Scanning Mechanism

Manufacturer:	TEM
Accuracy:	± 0.83 cm/meter
Minimum Step Size:	0.1 mm
Maximum speed	6.1 cm/sec
Line Voltage:	115 VAC
Line Frequency:	60 Hz
Material Composite:	Delrin (Acetal)
Data Control:	Parallel Port
Dynamic Range (X-Y-Z):	45 x 31.75 x 47 cm
Dimensions:	36" x 25" x 38"
Operating Area:	36" x 49" x 55"
Reflections:	< -20 dB (in anechoic chamber)




Figure 4-3
RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer:	ITU-T
Active Frequency Range:	100 Hz – 8 kHz
Stimulus Type:	Male and Female, no spaces
Single Sample Duration:	20.96 seconds
Activity Level:	100%




Figure 4-4
Spectral Characteristic of full P.50







Figure 4-5
Temporal Characteristic of full P.50

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 8 of 84

ABM1 Measurement Block Diagram:



ABM2 Measurement Block Diagram:




Figure 4-6 Magnetic Measurement Processing Steps

IV. Test Procedure

1. Ambient Noise Check per C63.19 §7.3.1
 - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. “A-weighting” and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:



$$-18 - 30 - 10 = -58 \text{ dBA/m}$$
2. Measurement System Validation (See Figure 4-1)
 - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation
 The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N\left(\frac{V}{R}\right)}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter
 N = number of turns per coil
 For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot \left(\frac{0.018}{10.2}\right)}{0.08 \cdot \sqrt{1.25^3}} = 0.316 \text{ A/m} \approx -10 \text{ dB(A/m)}$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within ± 0.5 dB of the -10dB(A/m) value (see Page 39).

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 9 of 84

c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:





Figure 4-7 Frequency Response Validation

d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

f (Hz)	HBI, A - Measured (dB re 1kHz)	HBI, A - Theoretical (dB re 1kHz)	dB Var.
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 10 of 84




Figure 4-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:






Figure 4-9
ABM2 Validation Block Diagram

The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 11 of 84




Figure 4-10
ABM2 Power Sum Validation

3. Measurement Test Setup

a. Fine scan above the WD (TEM)

- i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):




Figure 4-11
Measurement Distance






Figure 4-12
Measurement Grid

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
 - iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-14 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
- i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
IDEN™	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 12 of 84

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
 - iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.
 - c. Real-Time Analyzer (RTA)
 - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
 - d. WD Radio Configuration Selection
 - i. The device was chosen to be tested in the worst-case ABM2 condition (See Section 8 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5 and 7. WIFI configuration information can be found in Section 6 and 7.)
 - ii. Supported GSM vocoders were investigated for the worst-case ABM2 condition. GSM-EFR was deemed the worst-case condition for the GSM air interface.
- 4. Signal Quality Data Analysis
 - a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
 - b. Frequency Response
 - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 – 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
 - ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
 - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.
 - c. Signal Quality Index
 - i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz – 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
 - ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
 - iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of </small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 13 of 84	

V. Test Setup




Figure 4-13
Audio Magnetic Field Test Setup



Environmental conditions such as temperature and relative humidity are monitored to ensure there are no impacts on system specifications. Proper voltage and power line frequency conditions are maintained with three phase power sources. Environmental noise and reflections are monitored through system checks.

VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 14 of 84

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes.

**Table 4-3
Center Channels and Frequencies**



Test frequencies & associated channels	
Channel	Frequency (MHz)
Secondary Cellular 820	
564 (CDMA)	820.10
Cellular 850	
384 (CDMA)	836.52
190 (GSM)	836.60
4183 (UMTS)	836.60
AWS 1750	
1412 (UMTS)	1730.40
PCS 1900	
600 (CDMA)	1880
661 (GSM)	1880
9400 (UMTS)	1880

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case bands according to Tables 7-6 and 7-7 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-5 to 9-12 and Tables 9-20 to 9-21 for LTE bandwidths and channels.

3. WIFI

The middle channel for each IEEE 802.11 standard was tested for each probe orientation. The 2.4GHz IEEE 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz IEEE 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-13 to 9-16 and Tables 9-22 to 9-25 for WIFI standards and channels.

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 15 of 84

IX. Test Flow

The flow diagram below was followed (From C63.19):






Figure 4-14
C63.19 T-Coil Signal Test Process

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of</small>	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 16 of 84

5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.






Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 17 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

II. DUT Configuration for VoLTE over IMS T-coil Testing

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. The effects of modulation and RB configuration were found to be independent of band and bandwidth; therefore, only one band and bandwidth were used for this investigation. 16QAM, 1RB, 50%RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

Table 5-1
VoLTE over IMS SNNR by Radio Configuration

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
66	1745.0	132322	20	QPSK	1	0	8.91	-48.12	57.03
66	1745.0	132322	20	QPSK	1	50	9.37	-46.04	55.41
66	1745.0	132322	20	QPSK	1	99	8.90	-47.42	56.32
66	1745.0	132322	20	QPSK	50	0	9.44	-50.22	59.66
66	1745.0	132322	20	QPSK	50	25	8.81	-50.16	58.97
66	1745.0	132322	20	QPSK	50	50	8.82	-49.86	58.68
66	1745.0	132322	20	QPSK	100	0	8.75	-48.88	57.63
66	1745.0	132322	20	16QAM	1	0	9.08	-41.20	50.28
66	1745.0	132322	20	16QAM	1	50	9.12	-39.66	48.78
66	1745.0	132322	20	16QAM	1	99	8.73	-40.72	49.45
66	1745.0	132322	20	16QAM	50	0	9.43	-47.69	57.12
66	1745.0	132322	20	16QAM	50	25	8.91	-48.71	57.62
66	1745.0	132322	20	16QAM	50	50	9.29	-48.60	57.89
66	1745.0	132322	20	16QAM	100	0	9.24	-48.28	57.52
66	1745.0	132322	20	64QAM	1	0	9.05	-41.45	50.50
66	1745.0	132322	20	64QAM	1	50	8.91	-39.93	48.84
66	1745.0	132322	20	64QAM	1	99	9.10	-40.93	50.03
66	1745.0	132322	20	64QAM	50	0	9.17	-48.76	57.93
66	1745.0	132322	20	64QAM	50	25	9.15	-48.52	57.67
66	1745.0	132322	20	64QAM	50	50	9.37	-49.11	58.48
66	1745.0	132322	20	64QAM	100	0	8.82	-49.65	58.47

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The WB AMR 23.85kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 5-2
AMR Codec Investigation – VoLTE over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	9.02	9.43	10.20	10.20	Axial	Band 66 20MHz BW	132322
ABM2 (dBA/m)	-41.47	-41.91	-41.94	-41.91			
Frequency Response	Pass	Pass	Pass	Pass			
S+N/N (dB)	50.49	51.34	52.14	52.11			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = “Max Power”



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 18 of 84

Table 5-3
EVS Codec Investigation - VoLTE over IMS

Codec Setting:	EVS Primary WB 13.2kbps	EVS Primary WB 5.9kbps	EVS Primary NB 13.2kbps	EVS Primary NB 5.9kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	10.23	10.19	11.38	9.76	Axial	Band 66 20MHz BW	132322
ABM2 (dBA/m)	-40.87	-41.12	-41.03	-41.39			
Frequency Response	Pass	Pass	Pass	Pass			
S+N/N (dB)	51.10	51.31	52.41	51.15			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"




Figure 5-2
Audio Band Magnetic Curve Measurement Block Diagram

3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS



An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length $T_f = 307200 \cdot T_s = 10$ ms, where T_s is a number of time units equal to $1/(15000 \times 2048)$ seconds. Additionally, each radio frame consists of 10 subframes, each of length $30720 \cdot T_s = 1$ ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is $2192 \cdot T_s$ which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

Table 5-4
Uplink-Downlink Configurations for Type 2 Frame Structures

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number										Calculated Transmission Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 19 of 84

a. Power Class 3 Uplink-Downlink Configuration Investigation

Power class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 0RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 2 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

**Table 5-5
Power Class 3 VoLTE over IMS SNNR by UL-DL Configuration**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	0	0	8.98	-26.82	35.80
2593.0	40620	20	16QAM	1	0	1	9.10	-26.71	35.81
2593.0	40620	20	16QAM	1	0	2	9.16	-26.51	35.67
2593.0	40620	20	16QAM	1	0	3	8.69	-29.87	38.56
2593.0	40620	20	16QAM	1	0	4	8.86	-29.85	38.71
2593.0	40620	20	16QAM	1	0	5	9.21	-29.28	38.49
2593.0	40620	20	16QAM	1	0	6	9.12	-26.66	35.78

b. Power Class 2 Uplink-Downlink Configuration Investigation

Power Class 2 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 0RB Offset. For Power Class 2, configurations 1-5 are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 2 was used as the worst-case configuration for Power Class 2 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:



**Table 5-6
Power Class 2 VoLTE over IMS SNNR by UL-DL Configuration**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	0	1	8.77	-25.00	33.77
2593.0	40620	20	16QAM	1	0	2	8.74	-24.75	33.49
2593.0	40620	20	16QAM	1	0	3	8.94	-28.13	37.07
2593.0	40620	20	16QAM	1	0	4	9.27	-27.90	37.17
2593.0	40620	20	16QAM	1	0	5	8.64	-27.40	36.04

Note: LTE TDD B41 Power Class 2 only supports UL-DL configurations 1-5, not 0 or 6.

c. Conclusion

Per the investigations above, UL-DL Configuration 2 was used to evaluate both Power Class 3 and Power class 2 VoLTE over IMS.

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 20 of 84

6. VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoWIFI over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.






Figure 6-1
Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level². The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 21 of 84

II. DUT Configuration for VoWiFi over IMS T-coil Testing

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each IEEE 802.11 standard:

**Table 6-1
IEEE 802.11b SNNR by Radio Configuration**

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11b	6	DSSS	1	5.03	-47.33	52.36
IEEE 802.11b	6	DSSS	2	5.58	-46.51	52.09
IEEE 802.11b	6	CCK	5.5	4.99	-46.85	51.84
IEEE 802.11b	6	CCK	11	5.47	-46.68	52.15

**Table 6-2
IEEE 802.11g/a SNNR by Radio Configuration**

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11g	6	BPSK	6	5.42	-49.64	55.06
IEEE 802.11g	6	BPSK	9	5.59	-51.11	56.70
IEEE 802.11g	6	QPSK	12	5.47	-50.18	55.65
IEEE 802.11g	6	QPSK	18	4.96	-51.99	56.95
IEEE 802.11g	6	16QAM	24	5.60	-53.19	58.79
IEEE 802.11g	6	16QAM	36	4.96	-53.11	58.07
IEEE 802.11g	6	64QAM	48	5.43	-54.62	60.05
IEEE 802.11g	6	64QAM	54	5.69	-53.88	59.57

**Table 6-3
IEEE 802.11n/ac 20MHz BW SNNR by Radio Configuration**

Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11n	20	40	BPSK	0	5.43	-46.65	52.08
IEEE 802.11n	20	40	QPSK	1	5.57	-46.94	52.51
IEEE 802.11n	20	40	QPSK	2	5.70	-47.55	53.25
IEEE 802.11n	20	40	16QAM	3	5.67	-47.29	52.96
IEEE 802.11n	20	40	16QAM	4	5.74	-47.62	53.36
IEEE 802.11n	20	40	64QAM	5	5.30	-47.89	53.19
IEEE 802.11n	20	40	64QAM	6	5.37	-47.67	53.04
IEEE 802.11n	20	40	64QAM	7	5.17	-47.64	52.81
IEEE 802.11ac	20	40	256QAM	8	5.53	-47.51	53.04



FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 22 of 84

Table 6-4
IEEE 802.11n/ac 40MHz BW SNNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11n	40	38	BPSK	0	5.54	-46.56	52.10
IEEE 802.11n	40	38	QPSK	1	5.58	-46.77	52.35
IEEE 802.11n	40	38	QPSK	2	5.60	-47.19	52.79
IEEE 802.11n	40	38	16QAM	3	5.51	-48.09	53.60
IEEE 802.11n	40	38	16QAM	4	4.93	-47.76	52.69
IEEE 802.11n	40	38	64QAM	5	5.35	-47.18	52.53
IEEE 802.11n	40	38	64QAM	6	5.17	-48.12	53.29
IEEE 802.11n	40	38	64QAM	7	5.20	-48.49	53.69
IEEE 802.11ac	40	38	256QAM	8	5.39	-46.75	52.14
IEEE 802.11ac	40	38	256QAM	9	5.49	-47.30	52.79

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The WB AMR 23.85kbps setting was used for the audio codec on the CMW500 for VoWiFi over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 6-5
AMR Codec Investigation – VoWiFi over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	4.67	5.20	6.08	6.13	Axial	2.4GHz	IEEE 802.11b	6
ABM2 (dBA/m)	-47.16	-47.03	-47.71	-47.63				
Frequency Response	Pass	Pass	Pass	Pass				
S+N/N (dB)	51.83	52.23	53.79	53.76				

Table 6-6
EVS Codec Investigation – VoWiFi over IMS

Codec Setting:	EVS Primary WB 13.2kbps	EVS Primary WB 5.9kbps	EVS Primary NB 13.2kbps	EVS Primary NB 5.9kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	6.07	4.98	7.23	6.57	Axial	2.4GHz	IEEE 802.11b	6
ABM2 (dBA/m)	-47.72	-48.11	-48.11	-48.20				
Frequency Response	Pass	Pass	Pass	Pass				
S+N/N (dB)	53.79	53.09	55.34	54.77				

- Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 23 of 84

7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

I. Test System Setup for OTT VoIP T-Coil Testing

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 75kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

3. Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation³. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

Note: The green highlighted text is approved by FCC under the TCB PAG Re-Use Policy 388624 D01 IV. D. for T-Coil Testing for WI-FI calling and Google Duo.

II. DUT Configuration for OTT VoIP T-Coil Testing



1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration for each applicable data mode was used for these investigations. The 75kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

**Table 7-1
Codec Investigation – OTT VoIP (EvDO)**

Codec Setting:	75kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	21.76	22.00	Axial	600
ABM2 (dBA/m)	-53.82	-54.31		
Frequency Response	Pass	Pass		
S+N/N (dB)	75.58	76.31		

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 24 of 84

**Table 7-2
Codec Investigation – OTT VoIP (EDGE)**

Codec Setting:	75kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	21.53	21.76	Axial	661
ABM2 (dBA/m)	-26.75	-27.34		
Frequency Response	Pass	Pass		
S+N/N (dB)	48.28	49.10		

**Table 7-3
Codec Investigation – OTT VoIP (HSPA)**

Codec Setting:	75kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	22.37	22.15	Axial	9400
ABM2 (dBA/m)	-53.92	-54.28		
Frequency Response	Pass	Pass		
S+N/N (dB)	76.29	76.43		


**Table 7-4
Codec Investigation – OTT VoIP (LTE)**

Codec Setting:	75kbps	6kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	22.16	22.01	Axial	Band 66 20MHz BW	132322
ABM2 (dBA/m)	-40.60	-41.05			
Frequency Response	Pass	Pass			
S+N/N (dB)	62.76	63.06			




**Table 7-5
Codec Investigation – OTT VoIP (WIFI)**

Codec Setting:	75kbps	6kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	22.10	21.96	Axial	2.4GHz	IEEE 802.11b	6
ABM2 (dBA/m)	-43.79	-44.13				
Frequency Response	Pass	Pass				
S+N/N (dB)	65.89	66.09				

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.H



**Figure 7-1
Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of 	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 25 of 84

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE FDD band to be used for OTT VoIP testing. LTE FDD Band 25 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE FDD bands:

Table 7-6
OTT VoIP (LTE FDD) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
71	680.5	133297	20	16QAM	1	0	22.64	-42.60	65.24
12	707.5	23095	10	16QAM	1	0	22.39	-42.30	64.69
13	782.0	23230	10	16QAM	1	0	22.83	-40.67	63.50
26	831.5	26865	15	16QAM	1	0	22.53	-41.54	64.07
66	1745.0	132322	20	16QAM	1	0	22.40	-40.44	62.84
25	1882.5	26365	20	16QAM	1	0	22.40	-40.38	62.78

An investigation was performed to determine the worst-case LTE TDD band to be used for OTT VoIP testing. LTE TDD Band 41 Power Class 2 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE TDD bands:

Table 7-7
OTT VoIP (LTE TDD) SNNR by LTE Band



Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
41 (PC3)	2593.0	40620	20	16QAM	1	0	22.31	-25.35	47.66
41 (PC2)	2593.0	40620	20	16QAM	1	0	22.40	-23.86	46.26

3. LTE TDD Uplink Carrier Aggregation for OTT VoIP

LTE TDD ULCA was evaluated to ensure LTE TDD standalone was the worst-case scenario. The configurations in Table 7-8 were determined from Table 7-7 and satisfy the configuration requirements as defined in 3GPP 36.101.

Table 7-8
LTE TDD SNNR for OTT VoIP Uplink Carrier Aggregation

Combination	PCC		PCC		Modulation	PCC UL# RB		SCC		SCC		Modulation	SCC UL# RB		ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]		PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]		SCC UL# RB	SCC UL RB Offset			
CA_41C (PC3)	LTE B41	20	40620	2593.0	16QAM	1	0	LTE B41	20	40422	2573.2	16QAM	1	99	22.01	-27.77	49.78
CA_41C (PC2)	LTE B41	20	40620	2593.0	16QAM	1	0	LTE B41	20	40422	2573.2	16QAM	1	99	22.21	-25.80	48.01

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 26 of 84

8. FCC 3G MEASUREMENTS

I. CDMA Test Configurations

Radio Configuration 1, Service Option 3 (thick, green data curve) was used for the testing as the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:




Figure 8-1
CDMA Audio Band Magnetic Noise

Table 8-1
FCC 3G ABM Measurements for ZNFQ730TM (CDMA)

Configuration:	RC1/SO3	RC3/SO3	RC4/SO3	Orientation	Channel
ABM1 (dBA/m)	12.35	12.65	12.30	Axial	600
ABM2 (dBA/m)	-35.11	-54.92	-55.16		
Frequency Response	Pass	Pass	Pass		
S+N/N (dB)	47.46	67.57	67.46		

- Mute on; Backlight off; Max Volume; Max Contrast
- Power Control Bits = "All Up"




Figure 8-2
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 27 of 84

II. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB (thick, purple data curve) was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:




Figure 8-3
UMTS Audio Band Magnetic Noise

Table 8-2
Codec Investigation - UMTS

Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel
ABM1 (dBA/m)	13.21	13.25	13.33	Axial	9400
ABM2 (dBA/m)	-55.77	-55.94	-56.38		
Frequency Response	Pass	Pass	Pass		
S+N/N (dB)	68.98	69.19	69.71		

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC="All 1s"







Figure 8-4
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 28 of 84

9. T-COIL TEST SUMMARY

**Table 9-1
Consolidated Tabled Results**

C63.19 Section		Freq. Response Margin		Magnetic Intensity Verdict		FCC SNNR Verdict		Margin from FCC Limit (dB)	C63.19-2011 Rating
		8.3.2		8.3.1		8.3.4			
		Axial	Radial	Axial	Radial	Axial	Radial		
CDMA	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS	-25.97	T4
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
EvDO (OTT VoIP)	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS	-43.82	T4
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-7.09	T3
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
EDGE (OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-25.21	T4
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
UMTS	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-38.27	T4
	AWS	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
HSPA (OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-50.53	T4
	AWS	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B71	PASS	NA	PASS	PASS	PASS	PASS	-22.63	T4
	B12	PASS	NA	PASS	PASS	PASS	PASS		
	B13	PASS	NA	PASS	PASS	PASS	PASS		
	B26	PASS	NA	PASS	PASS	PASS	PASS		
	B66	PASS	NA	PASS	PASS	PASS	PASS		
	B25	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD (OTT VoIP)	B25	PASS	NA	PASS	PASS	PASS	PASS	-39.05	T4
LTE TDD	B41 (PC3)	PASS	NA	PASS	PASS	PASS	PASS	-12.48	T4
	B41 (PC2)	PASS	NA	PASS	PASS	PASS	PASS		
LTE TDD (OTT VoIP)	B41 (PC2)	PASS	NA	PASS	PASS	PASS	PASS	-26.34	T4
WLAN	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS	-24.76	T4
	IEEE 802.11g	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS		
WLAN (OTT VoIP)	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS	-39.29	T4
	IEEE 802.11g	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS		
U-NII	IEEE 802.11a	PASS	NA	PASS	PASS	PASS	PASS	-24.62	T4
	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11ac	PASS	NA	PASS	PASS	PASS	PASS		
U-NII (OTT VoIP)	IEEE 802.11a	PASS	NA	PASS	PASS	PASS	PASS	-38.54	T4
	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11ac	PASS	NA	PASS	PASS	PASS	PASS		

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of  amsol</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 29 of 84

I. Raw Handset Data

Table 9-2
Raw Data Results for CDMA



Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
Secondary Cellular	Axial	476	12.36	-36.14	-64.57	1.68	48.50	20.00	-28.50	T4	2.0, 4.0
		564	12.45	-35.45		1.42	47.90	20.00	-27.90	T4	
		684	12.14	-35.19		1.35	47.33	20.00	-27.33	T4	
	Radial	476	5.22	-42.22	-63.63	N/A	47.44	20.00	-27.44	T4	2.0, 4.8
		564	5.01	-42.03			47.04	20.00	-27.04	T4	
		684	4.95	-41.56			46.51	20.00	-26.51	T4	
Cellular	Axial	1013	12.40	-35.24	-64.57	1.37	47.64	20.00	-27.64	T4	2.0, 4.0
		384	12.31	-36.24		1.51	48.55	20.00	-28.55	T4	
		777	12.22	-35.06		1.69	47.28	20.00	-27.28	T4	
	Radial	1013	4.75	-41.55	-63.63	N/A	46.30	20.00	-26.30	T4	2.0, 4.8
		384	5.08	-42.53			47.61	20.00	-27.61	T4	
		777	4.74	-41.23			45.97	20.00	-25.97	T4	
PCS	Axial	25	12.55	-35.92	-64.57	1.62	48.47	20.00	-28.47	T4	2.0, 4.0
		600	12.23	-35.45		1.65	47.68	20.00	-27.68	T4	
		1175	12.16	-35.76		1.37	47.92	20.00	-27.92	T4	
	Radial	25	5.01	-42.65	-63.63	N/A	47.66	20.00	-27.66	T4	2.0, 4.8
		600	5.33	-41.91			47.24	20.00	-27.24	T4	
		1175	4.91	-42.12			47.03	20.00	-27.03	T4	

Table 9-3
Raw Data Results for GSM

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
GSM850	Axial	128	10.97	-16.12	-64.57	1.67	27.09	20.00	-7.09	T3	1.4, 4.0
		190	10.66	-16.93		1.47	27.59	20.00	-7.59	T3	
		251	10.94	-17.55		1.68	28.49	20.00	-8.49	T3	
	Radial	128	5.79	-25.85	-63.63	N/A	31.64	20.00	-11.64	T4	2.0, 4.8
		190	5.82	-26.60			32.42	20.00	-12.42	T4	
		251	5.80	-27.34			33.14	20.00	-13.14	T4	
GSM1900	Axial	512	12.62	-24.61	-64.57	1.75	37.23	20.00	-17.23	T4	2.0, 4.0
		661	12.62	-24.04		1.47	36.66	20.00	-16.66	T4	
		810	12.63	-23.29		1.61	35.92	20.00	-15.92	T4	
	Radial	512	5.81	-31.88	-63.63	N/A	37.69	20.00	-17.69	T4	2.0, 4.8
		661	5.81	-31.24			37.05	20.00	-17.05	T4	
		810	5.80	-30.68			36.48	20.00	-16.48	T4	

Table 9-4
Raw Data Results for UMTS

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
UMTS V	Axial	4132	13.30	-52.16	-64.57	1.79	65.46	20.00	-45.46	T4	2.0, 4.0
		4183	13.30	-52.33		1.89	65.63	20.00	-45.63	T4	
		4233	13.29	-51.45		1.63	64.74	20.00	-44.74	T4	
	Radial	4132	6.60	-54.99	-63.63	N/A	61.59	20.00	-41.59	T4	2.0, 4.8
		4183	6.60	-54.82			61.42	20.00	-41.42	T4	
		4233	6.63	-54.63			61.26	20.00	-41.26	T4	
UMTS IV	Axial	1312	13.26	-53.98	-64.57	1.83	67.24	20.00	-47.24	T4	2.0, 4.0
		1412	13.27	-54.71		1.85	67.98	20.00	-47.98	T4	
		1513	13.27	-54.79		1.88	68.06	20.00	-48.06	T4	
	Radial	1312	6.62	-56.52	-63.63	N/A	63.14	20.00	-43.14	T4	2.0, 4.8
		1412	6.59	-56.28			62.87	20.00	-42.87	T4	
		1513	6.64	-56.66			63.30	20.00	-43.30	T4	
UMTS II	Axial	9262	13.27	-54.48	-64.57	1.90	67.75	20.00	-47.75	T4	2.0, 4.0
		9400	13.75	-55.60		1.60	69.35	20.00	-49.35	T4	
		9538	13.32	-56.10		1.60	69.42	20.00	-49.42	T4	
	Radial	9262	6.60	-57.00	-63.63	N/A	63.60	20.00	-43.60	T4	2.0, 4.8
		9400	6.66	-51.61			58.27	20.00	-38.27	T4	
		9538	6.66	-54.31			60.97	20.00	-40.97	T4	

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 30 of 84

**Table 9-5
Raw Data Results for LTE B71**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 71	Axial	20MHz	133297	9.18	-43.07	-64.57	1.50	52.25	20.00	-32.25	T4	2.0, 4.0
		15MHz	133297	9.12	-41.65		1.51	50.77	20.00	-30.77	T4	
		10MHz	133297	8.92	-41.40		1.47	50.32	20.00	-30.32	T4	
		5MHz	133297	8.96	-42.17		1.59	51.13	20.00	-31.13	T4	
	Radial	20MHz	133297	2.27	-43.97	-63.63	N/A	46.24	20.00	-26.24	T4	2.0, 4.8
		15MHz	133297	1.95	-43.30			45.25	20.00	-25.25	T4	
		10MHz	133297	2.24	-43.67			45.91	20.00	-25.91	T4	
		5MHz	133297	2.13	-44.08			46.21	20.00	-26.21	T4	

**Table 9-6
Raw Data Results for LTE B12**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 12	Axial	10MHz	23095	9.05	-44.45	-64.57	1.49	53.50	20.00	-33.50	T4	2.0, 4.0
		5MHz	23095	9.15	-44.44		1.49	53.59	20.00	-33.59	T4	
		3MHz	23095	8.92	-44.54		1.41	53.46	20.00	-33.46	T4	
		1.4MHz	23095	9.10	-44.84		1.47	53.94	20.00	-33.94	T4	
	Radial	10MHz	23095	2.30	-46.32	-63.63	N/A	48.62	20.00	-28.62	T4	2.0, 4.8
		5MHz	23095	1.96	-46.35			48.31	20.00	-28.31	T4	
		3MHz	23095	2.21	-46.68			48.89	20.00	-28.89	T4	
		1.4MHz	23095	2.14	-47.03			49.17	20.00	-29.17	T4	

**Table 9-7
Raw Data Results for LTE B13**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 13	Axial	10MHz	23230	8.99	-43.77	-64.57	1.42	52.76	20.00	-32.76	T4	2.0, 4.0
		5MHz	23230	8.95	-44.90		1.43	53.85	20.00	-33.85	T4	
	Radial	10MHz	23230	2.26	-46.51	-63.63	N/A	48.77	20.00	-28.77	T4	2.0, 4.8
		5MHz	23230	2.03	-46.64			48.67	20.00	-28.67	T4	

**Table 9-8
Raw Data Results for LTE B26**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 26	Axial	15MHz	26865	9.02	-44.56	-64.57	1.53	53.58	20.00	-33.58	T4	2.0, 4.0
		10MHz	26865	8.82	-42.98		1.51	51.80	20.00	-31.80	T4	
		5MHz	26865	9.43	-43.37		1.53	52.80	20.00	-32.80	T4	
		3MHz	26865	9.23	-42.84		1.53	52.07	20.00	-32.07	T4	
		1.4MHz	26865	9.29	-43.92		1.49	53.21	20.00	-33.21	T4	
	Radial	15MHz	26865	1.96	-47.21	-63.63	N/A	49.17	20.00	-29.17	T4	2.0, 4.8
		10MHz	26865	1.99	-45.43			47.42	20.00	-27.42	T4	
		5MHz	26865	2.06	-46.20			48.26	20.00	-28.26	T4	
		3MHz	26865	1.93	-45.43			47.36	20.00	-27.36	T4	
		1.4MHz	26865	1.99	-46.32			48.31	20.00	-28.31	T4	

**Table 9-9
Raw Data Results for LTE B66**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
LTE Band 66	Axial	20MHz	132322	9.38	-39.33	-64.57	1.48	48.71	20.00	-28.71	T4	2.0, 4.0			
		15MHz	132597	9.13	-38.65		1.52	47.78	20.00	-27.78	T4				
		15MHz	132322	9.06	-38.98		1.51	48.04	20.00	-28.04	T4				
		15MHz	132047	9.13	-38.96		1.49	48.09	20.00	-28.09	T4				
		10MHz	132322	9.28	-38.79		1.50	48.07	20.00	-28.07	T4				
		5MHz	132322	9.35	-39.50		1.44	48.85	20.00	-28.85	T4				
		3MHz	132322	9.05	-39.08		1.47	48.13	20.00	-28.13	T4				
		1.4MHz	132322	9.37	-39.61		1.49	48.98	20.00	-28.98	T4				
		Radial	20MHz	132322	1.97		-41.45	-63.63	N/A	43.42	20.00		-23.42	T4	2.0, 4.8
			15MHz	132322	2.21		-40.69			42.90	20.00		-22.90	T4	
	10MHz		132622	1.99	-41.05	43.04	20.00			-23.04	T4				
	10MHz		132322	1.90	-40.73	42.63	20.00			-22.63	T4				
	10MHz		132022	2.08	-40.71	42.79	20.00			-22.79	T4				
	5MHz		132322	1.82	-41.89	43.71	20.00			-23.71	T4				
	3MHz		132322	2.13	-40.86	42.99	20.00			-22.99	T4				
	1.4MHz		132322	2.00	-40.78	42.78	20.00			-22.78	T4				



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 31 of 84

Table 9-10
Raw Data Results for LTE B25

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 25	Axial	20MHz	26365	9.01	-43.54	-64.57	1.47	52.55	20.00	-32.55	T4	2.0, 4.0
		15MHz	26365	9.40	-42.73		1.54	52.13	20.00	-32.13	T4	
		10MHz	26365	9.02	-42.90		1.47	51.92	20.00	-31.92	T4	
		5MHz	26365	8.93	-42.79		1.48	51.72	20.00	-31.72	T4	
		3MHz	26365	9.32	-41.67		1.45	50.99	20.00	-30.99	T4	
	1.4MHz	26365	9.18	-42.21	1.48	51.39	20.00	-31.39	T4			
	Radial	20MHz	26365	2.02	-44.72	-63.63	N/A	46.74	20.00	-26.74	T4	2.0, 4.8
		15MHz	26365	2.19	-45.03			47.22	20.00	-27.22	T4	
		10MHz	26365	1.84	-45.15			46.99	20.00	-26.99	T4	
		5MHz	26365	1.75	-45.91			47.66	20.00	-27.66	T4	
3MHz		26365	2.21	-45.00	47.21			20.00	-27.21	T4		
1.4MHz	26365	2.13	-46.19	48.32	20.00	-28.32	T4					

Table 9-11
Raw Data Results for LTE B41 Power Class 3

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 41	Axial	20MHz	40620	8.92	-26.45	-64.57	1.49	35.37	20.00	-15.37	T4	2.0, 4.0
		15MHz	40620	9.02	-26.64		1.45	35.66	20.00	-15.66	T4	
		10MHz	40620	8.60	-26.02		1.52	34.62	20.00	-14.62	T4	
		5MHz	40620	9.08	-26.21		1.52	35.29	20.00	-15.29	T4	
	Radial	20MHz	40620	1.82	-32.96	-63.63	N/A	34.78	20.00	-14.78	T4	2.0, 4.8
		15MHz	40620	1.85	-33.26			35.11	20.00	-15.11	T4	
		10MHz	40620	2.12	-33.08			35.20	20.00	-15.20	T4	
		5MHz	40620	2.23	-33.33			35.56	20.00	-15.56	T4	

Table 9-12
Raw Data Results for LTE B41 Power Class 2

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 41	Axial	20MHz	41490	9.20	-25.57	-64.57	1.51	34.77	20.00	-14.77	T4	2.0, 4.0
		20MHz	41055	9.32	-25.69		1.48	35.01	20.00	-15.01	T4	
		20MHz	40620	8.73	-24.73		1.53	33.46	20.00	-13.46	T4	
		20MHz	40185	9.19	-25.05		1.53	34.24	20.00	-14.24	T4	
		20MHz	39750	9.59	-29.59		1.49	39.18	20.00	-19.18	T4	
		15MHz	40620	9.33	-24.86		1.48	34.19	20.00	-14.19	T4	
		10MHz	40620	9.33	-24.59		1.52	33.92	20.00	-13.92	T4	
		5MHz	40620	9.38	-24.97		1.49	34.35	20.00	-14.35	T4	
	Radial	20MHz	41490	2.34	-31.64	-63.63	N/A	33.98	20.00	-13.98	T4	2.0, 4.8
		20MHz	41055	1.79	-31.89			33.68	20.00	-13.68	T4	
		20MHz	40620	2.01	-30.94			32.95	20.00	-12.95	T4	
		20MHz	40185	1.75	-30.73			32.48	20.00	-12.48	T4	
		20MHz	39750	2.20	-32.43			34.63	20.00	-14.63	T4	
		15MHz	40620	1.88	-31.22			33.10	20.00	-13.10	T4	
		10MHz	40620	1.94	-31.18			33.12	20.00	-13.12	T4	
		5MHz	40620	2.26	-31.39			33.65	20.00	-13.65	T4	

Table 9-13
Raw Data Results for 2.4GHz WIFI

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11b	Axial	1	5.31	-46.23	-64.57	1.57	51.54	20.00	-31.54	T4	2.0, 4.0
		6	5.47	-46.62		1.53	52.09	20.00	-32.09	T4	
		11	5.51	-47.20		1.52	52.71	20.00	-32.71	T4	
	Radial	1	-1.96	-50.01	-63.63	N/A	48.05	20.00	-28.05	T4	2.0, 4.8
		6	-1.62	-47.54			45.92	20.00	-25.92	T4	
		11	-1.56	-46.32			44.76	20.00	-24.76	T4	
IEEE 802.11g	Axial	6	5.26	-49.08	-64.57	1.53	54.34	20.00	-34.34	T4	2.0, 4.0
	Radial	6	-1.67	-51.94	-63.63	N/A	50.27	20.00	-30.27	T4	2.0, 4.8
IEEE 802.11n	Axial	6	5.38	-49.23	-64.57	1.51	54.61	20.00	-34.61	T4	2.0, 4.0
	Radial	6	-1.52	-52.72	-63.63	N/A	51.20	20.00	-31.20	T4	2.0, 4.8



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 32 of 84

Table 9-14
Raw Data Results for 5GHz WIFI IEEE 802.11a

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11a	Axial	20MHz	1	40	5.42	-45.64	-64.57	1.51	51.06	20.00	-31.06	T4	2.0, 4.0
		20MHz	2A	52	5.49	-47.12		1.51	52.61	20.00	-32.61	T4	
		20MHz	2A	56	5.33	-45.69		1.51	51.02	20.00	-31.02	T4	
		20MHz	2A	64	5.33	-46.12		1.54	51.45	20.00	-31.45	T4	
		20MHz	2C	120	5.19	-46.00		1.52	51.19	20.00	-31.19	T4	
		20MHz	3	157	5.58	-46.28		1.56	51.86	20.00	-31.86	T4	
	Radial	20MHz	1	40	-1.52	-49.16	-63.63	N/A	47.64	20.00	-27.64	T4	2.0, 4.8

Table 9-15
Raw Data Results for 5GHz WIFI IEEE 802.11n

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11n	Axial	40MHz	1	38	5.47	-46.36	-64.57	1.53	51.83	20.00	-31.83	T4	2.0, 4.0
		20MHz	1	40	5.05	-47.09		1.55	52.14	20.00	-32.14	T4	
	Radial	40MHz	1	38	-1.82	-48.81	-63.63	N/A	46.99	20.00	-26.99	T4	2.0, 4.8
		20MHz	1	40	-1.74	-48.24			46.50	20.00	-26.50	T4	
		40MHz	2A	54	-1.79	-49.16			47.37	20.00	-27.37	T4	
		20MHz	2A	56	-1.55	-48.81			47.26	20.00	-27.26	T4	
		40MHz	2C	118	-1.70	-50.20			48.50	20.00	-28.50	T4	
		20MHz	2C	100	-1.70	-48.23			46.53	20.00	-26.53	T4	
		20MHz	2C	120	-1.77	-47.71			45.94	20.00	-25.94	T4	
		20MHz	2C	144	-1.59	-46.21			44.62	20.00	-24.62	T4	
		40MHz	3	151	-1.72	-49.59			47.87	20.00	-27.87	T4	
		20MHz	3	157	-1.60	-48.78			47.18	20.00	-27.18	T4	

Table 9-16
Raw Data Results for 5GHz WIFI IEEE 802.11ac

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11ac	Axial	40MHz	1	38	5.30	-47.30	-64.57	1.51	52.60	20.00	-32.60	T4	2.0, 4.0
		20MHz	1	40	5.05	-47.32		1.52	52.37	20.00	-32.37	T4	
	Radial	40MHz	1	38	-1.62	-50.15	-63.63	N/A	48.53	20.00	-28.53	T4	2.0, 4.8
		20MHz	1	40	-1.65	-50.10			48.45	20.00	-28.45	T4	

Table 9-17
Raw Data Results for EvDO (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
Secondary Cellular EvDO	Axial	564	21.80	-53.46	-64.57	2.00	75.26	20.00	-55.26	T4	2.0, 4.0
	Radial	564	15.16	-50.19	-63.63	N/A	65.35	20.00	-45.35	T4	2.0, 4.8
Cellular EvDO	Axial	384	21.72	-53.53	-64.57	2.00	75.25	20.00	-55.25	T4	2.0, 4.0
	Radial	384	15.11	-50.41	-63.63	N/A	65.52	20.00	-45.52	T4	2.0, 4.8
PCS EvDO	Axial	600	21.69	-53.58	-64.57	2.00	75.27	20.00	-55.27	T4	2.0, 4.0
	Radial	600	15.13	-48.69	-63.63	N/A	63.82	20.00	-43.82	T4	2.0, 4.8

Table 9-18
Raw Data Results for EDGE (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
EDGE850	Axial	190	22.01	-24.08	-64.57	2.00	46.09	20.00	-26.09	T4	2.0, 4.0
	Radial	190	14.75	-30.46	-63.63	N/A	45.21	20.00	-25.21	T4	2.0, 4.8
EDGE1900	Axial	661	21.64	-26.35	-64.57	2.00	47.99	20.00	-27.99	T4	2.0, 4.0
	Radial	661	14.70	-34.79	-63.63	N/A	49.49	20.00	-29.49	T4	2.0, 4.8



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 33 of 84

Table 9-19
Raw Data Results for HSPA (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
HSPA V	Axial	4183	22.39	-54.18	-64.57	2.00	76.57	20.00	-56.57	T4	2.0, 4.0
	Radial	4183	15.11	-55.42	-63.63	N/A	70.53	20.00	-50.53	T4	2.0, 4.8
HSPA IV	Axial	1412	22.37	-53.84	-64.57	2.00	76.21	20.00	-56.21	T4	2.0, 4.0
	Radial	1412	15.18	-55.74	-63.63	N/A	70.92	20.00	-50.92	T4	2.0, 4.8
HSPA II	Axial	9400	22.35	-53.94	-64.57	2.00	76.29	20.00	-56.29	T4	2.0, 4.0
	Radial	9400	15.16	-55.79	-63.63	N/A	70.95	20.00	-50.95	T4	2.0, 4.8

Table 9-20
Raw Data Results for LTE B25 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 25	Axial	20MHz	26365	22.40	-40.96	-64.57	2.00	63.36	20.00	-43.36	T4	2.0, 4.0
		15MHz	26365	22.39	-40.28		2.00	62.67	20.00	-42.67	T4	
		10MHz	26640	22.45	-40.73		2.00	63.18	20.00	-43.18	T4	
		10MHz	26365	22.45	-39.83		2.00	62.28	20.00	-42.28	T4	
		10MHz	26090	22.48	-42.67		2.00	65.15	20.00	-45.15	T4	
		5MHz	26365	22.47	-42.25		2.00	64.72	20.00	-44.72	T4	
		3MHz	26365	22.41	-41.70		2.00	64.11	20.00	-44.11	T4	
	1.4MHz	26365	22.32	-43.11	2.00	65.43	20.00	-45.43	T4			
	Radial	20MHz	26365	14.96	-45.44	-63.63	N/A	60.40	20.00	-40.40	T4	2.0, 4.8
		15MHz	26365	14.97	-45.75			60.72	20.00	-40.72	T4	
		10MHz	26365	14.95	-45.57			60.52	20.00	-40.52	T4	
		5MHz	26665	14.89	-44.16			59.05	20.00	-39.05	T4	
		5MHz	26365	14.90	-45.15			60.05	20.00	-40.05	T4	
		5MHz	26065	14.82	-46.54			61.36	20.00	-41.36	T4	
3MHz		26365	14.94	-45.83	60.77			20.00	-40.77	T4		
1.4MHz	26365	14.87	-45.56	60.43	20.00	-40.43	T4					

Table 9-21
Raw Data Results for LTE B41 Power Class 2 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 41	Axial	20MHz	41490	22.63	-24.76	-64.57	2.00	47.39	20.00	-27.39	T4	2.0, 4.0
		20MHz	41055	22.26	-25.20		2.00	47.46	20.00	-27.46	T4	
		20MHz	40620	22.33	-24.01		2.00	46.34	20.00	-26.34	T4	
		20MHz	40185	22.70	-24.51		2.00	47.21	20.00	-27.21	T4	
		20MHz	39750	22.08	-24.76		2.00	46.84	20.00	-26.84	T4	
		15MHz	40620	22.65	-24.19		2.00	46.84	20.00	-26.84	T4	
		10MHz	40620	22.44	-24.02		2.00	46.46	20.00	-26.46	T4	
		5MHz	40620	22.41	-24.25		2.00	46.66	20.00	-26.66	T4	
		Radial	20MHz	41490	14.90		-32.39	-63.63	N/A	47.29	20.00	
	20MHz		41055	14.94	-32.86	47.80	20.00			-27.80	T4	
	20MHz		40620	15.02	-31.61	46.63	20.00			-26.63	T4	
	20MHz		40185	14.94	-31.46	46.40	20.00			-26.40	T4	
	20MHz		39750	14.98	-32.98	47.96	20.00			-27.96	T4	
	15MHz		40620	14.95	-31.87	46.82	20.00			-26.82	T4	
	10MHz		40620	14.95	-31.69	46.64	20.00			-26.64	T4	
	5MHz		40620	14.93	-31.79	46.72	20.00			-26.72	T4	



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 34 of 84

Table 9-22
Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11b	Axial	1	22.32	-44.66	-64.57	2.00	66.98	20.00	-46.98	T4	2.0, 4.0
		6	21.95	-43.92		2.00	65.87	20.00	-45.87	T4	
		11	22.26	-43.51		2.00	65.77	20.00	-45.77	T4	
	Radial	1	15.00	-44.29	-63.63	N/A	59.29	20.00	-39.29	T4	2.0, 4.8
		6	14.93	-45.48			60.41	20.00	-40.41	T4	
		11	14.91	-46.15			61.06	20.00	-41.06	T4	
IEEE 802.11g	Axial	6	22.09	-46.64	-64.57	2.00	68.73	20.00	-48.73	T4	2.0, 4.0
	Radial	6	15.04	-46.61	-63.63	N/A	61.65	20.00	-41.65	T4	2.0, 4.8
IEEE 802.11n	Axial	6	22.34	-45.30	-64.57	2.00	67.64	20.00	-47.64	T4	2.0, 4.0
	Radial	6	14.93	-48.03	-63.63	N/A	62.96	20.00	-42.96	T4	2.0, 4.8

Table 9-23
Raw Data Results for 5GHz WIFI IEEE 802.11a (OTT VoIP)

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11a	Axial	20MHz	1	40	22.18	-43.48	-64.57	2.00	65.66	20.00	-45.66	T4	2.0, 4.0
	Radial	20MHz	1	40	14.99	-44.69	-63.63	N/A	59.68	20.00	-39.68	T4	2.0, 4.8

Table 9-24
Raw Data Results for 5GHz WIFI IEEE 802.11n (OTT VoIP)

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11n	Axial	40MHz	1	38	22.29	-44.10	-64.57	2.00	66.39	20.00	-46.39	T4	2.0, 4.0
		20MHz	1	40	22.23	-42.87		2.00	65.10	20.00	-45.10	T4	
		40MHz	2A	54	22.32	-43.33		2.00	65.65	20.00	-45.65	T4	
		20MHz	2A	56	22.42	-42.76		2.00	65.18	20.00	-45.18	T4	
		40MHz	2C	118	22.27	-42.91		2.00	65.18	20.00	-45.18	T4	
		20MHz	2C	120	22.32	-43.04		2.00	65.36	20.00	-45.36	T4	
		40MHz	3	151	22.26	-43.79		2.00	66.05	20.00	-46.05	T4	
		20MHz	3	149	22.15	-42.71		2.00	64.86	20.00	-44.86	T4	
		20MHz	3	157	22.28	-41.94		2.00	64.22	20.00	-44.22	T4	
		20MHz	3	165	22.23	-42.64		2.00	64.87	20.00	-44.87	T4	
	Radial	40MHz	1	38	14.92	-46.97	-63.63	N/A	61.89	20.00	-41.89	T4	2.0, 4.8
		20MHz	1	36	14.90	-45.87			60.77	20.00	-40.77	T4	
		20MHz	1	40	15.04	-43.50			58.54	20.00	-38.54	T4	
		20MHz	1	48	15.01	-45.27			60.28	20.00	-40.28	T4	
		40MHz	2A	54	14.98	-45.75			60.73	20.00	-40.73	T4	
		20MHz	2A	56	15.02	-44.88			59.90	20.00	-39.90	T4	
		40MHz	2C	118	14.86	-46.53			61.39	20.00	-41.39	T4	
		20MHz	2C	120	14.91	-45.68			60.59	20.00	-40.59	T4	
		40MHz	3	151	14.89	-45.79			60.68	20.00	-40.68	T4	
		20MHz	3	157	15.00	-44.63			59.63	20.00	-39.63	T4	



Table 9-25
Raw Data Results for 5GHz WIFI IEEE 802.11ac (OTT VoIP)

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE 802.11ac	Axial	40MHz	1	38	22.25	-44.06	-64.57	2.00	66.31	20.00	-46.31	T4	2.0, 4.0
		20MHz	1	40	21.76	-43.52		2.00	65.28	20.00	-45.28	T4	
	Radial	40MHz	1	38	15.09	-46.40	-63.63	N/A	61.49	20.00	-41.49	T4	2.0, 4.8
		20MHz	1	40	14.95	-45.75			60.70	20.00	-40.70	T4	

II. Test Notes

A. General

1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
2. 'Radial' orientation refers to radial transverse.
3. Hearing Aid Mode (**Phone→Call Settings→Additional Settings→Hearing aids**) was set to ON for Frequency Response compliance

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 35 of 84

4. Speech Signal: ITU-T P.50 Artificial Voice
5. Bluetooth and WIFI were disabled while testing 2G/3G/4G modes.
6. Licensed data modes and Bluetooth were disabled while testing WIFI modes.
7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. CDMA

1. Power Configuration: Power Control Bits = "All Up"
2. Vocoder Configuration: RC1/SO3 (CDMA – EVRC)

C. GSM

1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
2. Vocoder Configuration: EFR (GSM);

D. UMTS

1. Power Configuration: TPC= "All 1s";
2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

E. LTE FDD



1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 50%RB offset
3. Vocoder Configuration: WB AMR 23.85kbps
4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 66 at 15MHz is the worst-case for the Axial probe orientation. LTE Band 66 at 10MHz bandwidth is the worst-case for the Radial probe orientation.

F. LTE TDD

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 50%RB offset
3. Power Class 3 Uplink-Downlink configuration: 2
4. Power Class 2 Uplink-Downlink configuration: 2
5. Vocoder Configuration: WB AMR 23.85kbps
6. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Power Class 2) at 20MHz is the worst-case for both the Axial and Radial probe orientations.

G. WIFI



1. Radio Configuration
 - a. IEEE 802.11b: CCK, 5.5Mbps
 - b. IEEE 802.11g/a: BPSK, 6Mbps
 - c. IEEE 802.11n/ac 20MHz: BPSK, MCS 0
 - d. IEEE 802.11n/ac 40MHz: BPSK, MCS 0
2. Vocoder Configuration: WB AMR 23.85kbps
3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11b is the worst-case for both the Axial and Radial probe orientations.

FCC ID: ZNFQ730TM	 PCTEST <small>Practical to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 36 of 84	


4. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. IEEE 802.11a (U-NII 2A) is the worst-case for the Axial probe orientation. IEEE 802.11n 20MHz (U-NII 2C) is the worst-case for the Radial probe orientation.

H. OTT VoIP




1. Vocoder Configuration: 75kbps
2. EvDO Configuration
 - a. Revision: A
3. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
4. HSPA Configuration:
 - a. Release: 6
 - b. 3GPP 34.121 Subtest 1
5. LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 50%RB offset
 - c. LTE Band 25 was the worst-case band from Table 7-6 and was used to test both Axial and Radial probe orientations.
 - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 25 at 10MHz is the worst-case for the Axial probe orientation. LTE Band 25 at 5MHz bandwidth is the worst-case for the Radial probe orientation.
6. LTE TDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 50%RB offset
 - c. Power Class 2 Uplink-Downlink configuration: 2
 - d. LTE Band 41 Power Class 2 was the worst-case band from Table 7-7 and was used to test both Axial and Radial probe orientations.
 - e. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Power Class 2) at 20MHz is the worst-case for both the Axial and Radial probe orientations.
7. WIFI Configuration:
 - a. Radio Configuration
 - i. IEEE 802.11b: CCK, 5.5Mbps
 - ii. IEEE 802.11g/a: BPSK, 6Mbps
 - iii. IEEE 802.11n/ac 20MHz: BPSK, MCS 0
 - iv. IEEE 802.11n/ac 40MHz: BPSK, MCS 0
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11b is the worst-case for both the Axial and Radial probe orientations.
 - c. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. IEEE 802.11n 20MHz (U-NII 3) is the worst-case for the Axial probe orientation. IEEE 802.11n 20MHz (U-NII 1) is the worst-case for the Radial probe orientation.

FCC ID: ZNFQ730TM	 PCTEST <small>Prized to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 37 of 84	



III. 1 kHz Vocoder Application Check





This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.





This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWiFi over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 38 of 84


IV. T-Coil Validation Test Results

**Table 9-26
Helmholtz Coil Validation Table of Results**

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	$-10 \pm 0.5 \text{ dB}$	-10.289	PASS
Environmental Noise	< -58 dBA/m	-64.57	PASS
Frequency Response, from limits	$> 0 \text{ dB}$	0.80	PASS
Radial			
Magnetic Intensity, -10 dBA/m	$-10 \pm 0.5 \text{ dB}$	-10.336	PASS
Environmental Noise	< -58 dBA/m	-63.63	PASS
Frequency Response, from limits	$> 0 \text{ dB}$	0.80	PASS

FCC ID: ZNFQ730TM	 PCTEST <small>Head to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 39 of 84

V. ABM1 Magnetic Field Distribution Scan Overlays





Axial

Radial (Transverse)

**Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions**

Notes:

1. Final measurement locations are indicated by a cursor on the contour plots. The GSM 850 Axial Measurement location is indicated by a blue cursor.
2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFQ730TM	 PCTEST <small>Probed to be part of</small>	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 40 of 84	

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

10. MEASUREMENT UNCERTAINTY



**Table 10-1
Uncertainty Estimation Table**

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

Notes:

1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
2. All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.



Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFQ730TM	 PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	 LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 41 of 84



11. EQUIPMENT LIST

**Table 11-1
Equipment List**

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Control Company	4040	Therm./Clock/Humidity Monitor	6/29/2019	Biennial	6/29/2021	192291463
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/24/2019	Biennial	4/24/2021	7BFNM32
Listen	SoundConnect	Microphone Power Supply	4/22/2019	Biennial	4/22/2021	PS2612
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/24/2019	Biennial	4/24/2021	23528889
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/4/2020	Annual	2/4/2021	162125
Rohde & Schwarz	CMW500	Radio Communication tester	8/14/2019	Annual	8/14/2020	140144
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	6/6/2019	Annual	6/6/2020	161662
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM		HAC Positioner	N/A		N/A	N/A
TEM	Axial T-Coil Probe	Axial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1124
TEM	Radial T-Coil Probe	Radial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1130
TEM	C63.19	Helmholtz Coil	5/20/2019	Biennial	5/20/2021	925

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 42 of 84

12. TEST DATA

FCC ID: ZNFQ730TM	 PCTEST <small>Head to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 43 of 84	

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



PCTEST Hearing-Aid Compatibility Facility

DUT: HH Coil – SN: 925


Type: HH Coil
Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019
- Helmholtz Coil – SN: 925; Calibrated: 05/20/2019

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.289 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-64.57 dB	✓	Maximum	-58.0
Frequency Response Margin	800m dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM	PCTEST Proud to be part of element	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 44 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: HH Coil – SN: 925


Type: HH Coil
Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019
- Helmholtz Coil – SN: 925; Calibrated: 05/20/2019

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.336 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-63.63 dB	✓	Maximum	-58.0
Frequency Response Margin	800m dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 45 of 84



PCTEST

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: CDMA Secondary Cellular
- Channel: 684
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	12.14 dB	✓	Minimum	-18.0
ABM2	-35.19 dB	✓	Maximum	0.0
SNNR	47.33 dB	✓	Minimum	20.0
Aligned Response - P.50	1.35 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 46 of 84



PCTEST

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: CDMA Cellular
- Channel: 777
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	12.22 dB	✓	Minimum	-18.0
ABM2	-35.06 dB	✓	Maximum	0.0
SNNR	47.28 dB	✓	Minimum	20.0
Aligned Response - P.50	1.69 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 47 of 84	



PCTEST

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: CDMA PCS
- Channel: 600
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	12.23 dB	✓	Minimum	-18.0
ABM2	-35.44 dB	✓	Maximum	0.0
SNNR	47.68 dB	✓	Minimum	20.0
Aligned Response - P.50	1.65 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 48 of 84



PCTEST®

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: GSM 850
- Channel: 128
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	10.97 dB	✓	Minimum	-18.0
ABM2	-16.11 dB	✓	Maximum	0.0
SNNR	27.09 dB	✓	Minimum	20.0
Aligned Response - P.50	1.67 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 49 of 84



PCTEST®

 Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: GSM 1900
- Channel: 810
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	12.63 dB	✓	Minimum	-18.0
ABM2	-23.29 dB	✓	Maximum	0.0
SNNR	35.92 dB	✓	Minimum	20.0
Aligned Response - P.50	1.61 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 50 of 84



PCTEST[®]

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: UMTS Band V
- Channel: 4233
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	13.29 dB	✓	Minimum	-18.0
ABM2	-51.45 dB	✓	Maximum	0
SNNR	64.74 dB	✓	Minimum	20
Aligned Response - P.50	1.63 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 51 of 84	



PCTEST®

 Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: UMTS Band IV
- Channel: 1312
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	13.26 dB	✓	Minimum	-18.0
ABM2	-53.99 dB	✓	Maximum	0.0
SNNR	67.24 dB	✓	Minimum	20.0
Aligned Response - P.50	1.83 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 52 of 84



PCTEST

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: UMTS Band II
- Channel: 9262
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	13.27 dB	✓	Minimum	-18.0
ABM2	-54.48 dB	✓	Maximum	0.0
SNNR	67.75 dB	✓	Minimum	20.0
Aligned Response - P.50	1.9 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 53 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020



PCTEST[®]

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: LTE FDD Band 66
- Bandwidth: 15MHz
- Channel: 132597
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	9.13 dB	✓	Minimum	-18.0
ABM2	-38.66 dB	✓	Maximum	0
SNNR	47.78 dB	✓	Minimum	20
Aligned Response - P.50	1.52 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 54 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020



PCTEST®

 Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: LTE TDD Band 41 (Power Class 2)
- Bandwidth: 20MHz
- Channel: 40620
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	8.73 dB	✓	Minimum	-18.0
ABM2	-24.73 dB	✓	Maximum	0.0
SNNR	33.46 dB	✓	Minimum	20.0
Aligned Response - P.50	1.53 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 55 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020



PCTEST®

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: 2.4GHz WiFi
- Standard: IEEE 802.11b
- Channel: 1
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	5.31 dB	✓	Minimum	-18.0
ABM2	-46.23 dB	✓	Maximum	0
SNNR	51.54 dB	✓	Minimum	20
Aligned Response - P.50	1.57 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 56 of 84



DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- Mode: 5GHz WIFI
- Standard: IEEE 802.11a (U-NII 2A)
- Bandwidth: 20MHz
- Channel: 56
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

ABM1	5.33 dB	✓	Minimum	-18.0
ABM2	-45.69 dB	✓	Maximum	0.0
SNNR	51.02 dB	✓	Minimum	20.0
Aligned Response - P.50	1.51 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 57 of 84



PCTEST

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM
 Type: Portable Handset
 Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 5/17/2019


Test Configuration:

- VoIP Application: Google Duo
- Mode: EDGE 850
- Channel: 190
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum





Frequency Response



Results

ABM1	22.01 dB	✓	Minimum	-18.0
ABM2	-24.08 dB	✓	Maximum	0
SNNR	46.09 dB	✓	Minimum	20
Aligned Response - P.50	2 dB	✓	Tolerance curves	Aligned Data

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 58 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: CDMA Secondary Cellular
- Channel: 684

Noise Spectrum



Results

ABM1	4.95 dB	✓	Minimum	-18.0
ABM2	-41.57 dB	✓	Maximum	0.0
SNNR	46.51 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 59 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: CDMA Cellular
- Channel: 777

Noise Spectrum



Results

ABM1	4.74 dB	✓	Minimum	-18.0
ABM2	-41.23 dB	✓	Maximum	0.0
SNNR	45.97 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM	PCTEST Proud to be part of element	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 60 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: CDMA PCS
- Channel: 1175

Noise Spectrum



Results

ABM1	4.91 dB	✓	Minimum	-18.0
ABM2	-42.12 dB	✓	Maximum	0.0
SNNR	47.03 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM	PCTEST Proud to be part of element	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 61 of 84



PCTEST[®]

Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: GSM 850
- Channel: 128



Noise Spectrum



Results

ABM1	5.79 dB	✓	Minimum	-18.0
ABM2	-25.84 dB	✓	Maximum	0.0
SNNR	31.64 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 62 of 84



PCTEST[®]

 Proud to be part of 

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: GSM 1900
- Channel: 810



Noise Spectrum



Results

ABM1	5.8 dB	✓	Minimum	-18.0
ABM2	-30.68 dB	✓	Maximum	0.0
SNNR	36.48 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 63 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: UMTS Band V
- Channel: 4233

Noise Spectrum



Results

ABM1	6.63 dB	✓	Minimum	-18.0
ABM2	-54.64 dB	✓	Maximum	0.0
SNNR	61.26 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 64 of 84



PCTEST[®]

Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: UMTS Band IV
- Channel: 1412



Noise Spectrum



Results

ABM1	6.59 dB	✓	Minimum	-18.0
ABM2	-56.28 dB	✓	Maximum	0.0
SNNR	62.87 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 65 of 84	



PCTEST[®]

 Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: UMTS Band II
- Channel: 9400



Noise Spectrum



Results

ABM1	6.66 dB	✓	Minimum	-18.0
ABM2	-51.62 dB	✓	Maximum	0.0
SNNR	58.27 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 66 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: LTE FDD Band 66
- Bandwidth: 10MHz
- Channel: 132322



Noise Spectrum



Results

ABM1	1.9 dB	✓	Minimum	-18.0
ABM2	-40.73 dB	✓	Maximum	0.0
SNNR	42.63 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 67 of 84	



PCTEST[®]

 Proud to be part of  element

PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: LTE TDD Band 41 (Power Class 2)
- Bandwidth: 20MHz
- Channel: 40185



Noise Spectrum



Results

ABM1	1.75 dB	✓	Minimum	-18.0
ABM2	-30.73 dB	✓	Maximum	0.0
SNNR	32.48 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 68 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: 2.4GHz WIFI
- Standard: IEEE 802.11b
- Channel: 11

Noise Spectrum



Results

ABM1	-1.56 dB	✓	Minimum	-18.0
ABM2	-46.32 dB	✓	Maximum	0.0
SNNR	44.76 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 69 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- Mode: 5GHz WIFI
- Standard: IEEE 802.11n (U-NII 2C)
- Bandwidth: 20MHz
- Channel: 144

Noise Spectrum



Results

ABM1	-1.59 dB	✓	Minimum	-18.0
ABM2	-46.22 dB	✓	Maximum	0.0
SNNR	44.62 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 70 of 84



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFQ730TM

Type: Portable Handset
Serial: 04906

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 5/17/2019

Test Configuration:

- VoIP Application: Google Duo
- Mode: EDGE 850
- Channel: 190

Noise Spectrum





Results

ABM1	14.75 dB	✓	Minimum	-18.0
ABM2	-30.46 dB	✓	Maximum	0.0
SNNR	45.21 dB	✓	Minimum	20.0

PCTEST 2020

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 71 of 84

13. CALIBRATION CERTIFICATES

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 72 of 84	

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

West Caldwell Calibration Laboratories Inc.

Certificate of Calibration

for

AXIAL T COIL PROBE

Manufactured by: TEM CONSULTING
Model No: AXIAL T COIL PROBE
Serial No: TEM-1124
Calibration Recall No: 29973

Submitted By:

Customer: ANDREW HARWELL
Company: PCTEST ENGINEERING LAB
Address: 6660-B DOBBIN ROAD
COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. AXIAL T C TEM C

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.
The information supplied relates to the calibrated item listed above.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

James Zhu

Calibration Date: 17-May-19

Certificate No: 29973 -1

Quality Manager
ISO/IEC 17025:2005



QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

West Caldwell Calibration Laboratories, Inc.
uncompromised calibration
1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 73 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



ISO/IEC 17025: 2005



Calibration Lab. Cert. # 1533.01

REPORT OF CALIBRATION

for

TEM Consulting LP Axial T Coil Probe
Company: PCTest Engineering Labs

Model No.: Axial T Coil Probe

Serial No.: TEM-1124
I. D. No.: XXXX


Calibration results:			
Probe Sensitivity measured with Helmholtz Coil			
<i>Helmholtz Coil;</i>			
the number of turns on each coil;	10	No.	Before & after data same: ...X...
the radius of each coil, in meters;	0.204	m	
the current in the coils, in amperes.;	0.09	A	
<i>Helmholtz Coil Constant;</i>	7.09	A/m/V	Laboratory Environment:
<i>Helmholtz Coil magnetic field;</i>	5.96	A/m	Ambient Temperature: 20.7 °C
			Ambient Humidity: 42.7 % RH
			Ambient Pressure: 98.256 kPa
			Calibration Date: 17-May-2019
			Calibration Due: 17-May-2020
			Report Number: 29973 -1
			Control Number: 29973
Probe Sensitivity at	1000	Hz.	
was	-60.41	dBV/A/m	
	0.954	mV/A/m	
Probe resistance	903	Ohms	

The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers: 683/290345-18

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019

Measurements performed by: *James Zhu*

Calibrated on WCCL system type 9700

James Zhu

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 74 of 84

HCATEMC_TEM-1124_May-17-2019

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564
Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe
Company: PCTest Engineering Labs

for
Model No.: Axial T Coil Probe

Serial No.: TEM-1124

Test	Function	Tolerance	Measured values		
			Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz. dBV/A/m	-60.41		
2.0	Probe Level Linearity	Ref. (0 dB)	dB		
			6	6.10	
			0	0.00	
			-6	-6.00	
			-12	-12.00	
3.0	Probe Frequency Response	Ref. (0 dB)	Hz		
			100	-19.9	
			126	-17.9	
			158	-16.0	
			200	-14.0	
			251	-12.0	
			316	-10.0	
			398	-8.0	
			501	-6.0	
			631	-3.9	
			794	-2.0	
			1000	0.0	
			1259	2.0	
			1585	4.0	
			1995	5.9	
			2512	7.9	
			3162	9.9	
3981	11.9				
5012	13.9				
6310	15.9				
7943	18.0				
10000	20.2				

Instruments used for calibration:			Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019



Cal. Date: 17-May-2019

Tested by: James Zhu

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 75 of 84

West Caldwell Calibration Laboratories Inc.

Certificate of Calibration

for

RADIAL T COIL PROBE

Manufactured by: TEM CONSULTING
Model No: RADIAL T COIL PROBE
Serial No: TEM-1130
Calibration Recall No: 29973

Submitted By:

Customer: ANDREW HARWELL
Company: PCTEST ENGINEERING LAB
Address: 6660-B DOBBIN ROAD
COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. RADIAL T TEM C

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.

The information supplied relates to the calibrated item listed above.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

James Zhu

Calibration Date: 17-May-19

Certificate No: 29973 -2

Quality Manager
ISO/IEC 17025:2005



QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

West Caldwell Calibration Laboratories, Inc.
uncompromised calibration
1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 76 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



REPORT OF CALIBRATION

for


TEM Consulting LP Radial T Coil Probe
Company: PCTest Engineering Labs

Model No.: Radial T Coil Probe

Serial No.: TEM-1130
I. D. No.: XXXX

Calibration results:			
Probe Sensitivity measured with Helmholtz Coil			
<i>Helmholtz Coil;</i>			
the number of turns on each coil;	10	No.	Before & after data same: ...X...
the radius of each coil, in meters;	0.204	m	
the current in the coils, in amperes.;	0.08	A	
<i>Helmholtz Coil Constant;</i>	7.09	A/m/V	Laboratory Environment:
<i>Helmholtz Coil magnetic field;</i>	5.94	A/m	Ambient Temperature: 20.7 °C
			Ambient Humidity: 42.7 % RH
			Ambient Pressure: 98.256 kPa
			Calibration Date: 17-May-2019
			Calibration Due: 17-May-2020
Probe Sensitivity at 1000 Hz.			Report Number: 29973 -2
was -60.37 dBV/A/m			Control Number: 29973
0.958 mV/A/m			
Probe resistance 895 Ohms			

The above listed instrument meets or exceeds the tested manufacturer's specifications.
This Calibration is traceable through NIST test numbers: 683/290345-18
The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.
Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC
Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NC SL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019
Calibrated on WCCL system type 9700

Measurements performed by: *James Zhu*
James Zhu

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

FCC ID: ZNFQ730TM	PCTEST Proud to be part of	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 77 of 84

HCRTEMC_TEM-1130_May-17-2019

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564
Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe for Model No.: Radial T Coil Probe Serial No.: TEM-1130
Company: PCTest Engineering Labs

Test	Function	Tolerance	Measured values		
			Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz. dBV/A/m	-60.37		
2.0	Probe Level Linearity	Ref. (0 dB)	dB		
			6	6.00	
			0	0.00	
			-6	-6.10	
			-12	-12.10	
3.0	Probe Frequency Response	Ref. (0 dB)	Hz		
			100	-20.0	
			126	-17.9	
			158	-16.0	
			200	-14.0	
			251	-12.0	
			316	-10.0	
			398	-8.0	
			501	-6.0	
			631	-4.0	
			794	-2.0	
			1000	0.0	
			1259	1.9	
			1585	3.9	
			1995	5.9	
			2512	7.9	
			3162	9.9	
			3981	11.9	
5012	13.9				
6310	15.9				
7943	18.0				
10000	20.1				



Instruments used for calibration:			Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019

Cal. Date: 17-May-2019
Calibrated on WCCL system type 9700

Tested by: James Zhu

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.



Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 78 of 84

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFQ730TM	 PCTEST <small>Head to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 79 of 84	



© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

15. REFERENCES

1. ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids., New York, NY, IEEE, May 2011
2. FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
3. FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017
4. FCC Public Notice DA 06-1215, *Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard*, June 6, 2006
5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
6. Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
7. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," *Wireless Telephones and Hearing Aids: New Challenges for Audiology*, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices," IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
9. Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
10. Byrne, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
11. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells," U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
13. EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
19. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
20. Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Construction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.
22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.



FCC ID: ZNFQ730TM		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset		Page 80 of 84

© 2020 PCTEST

REV 3.5.M
3/2/2020

© 2020 PCTEST All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
25. Ma, M. A., Sreenivashiah, I. , and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFQ730TM	 PCTEST <small> proud to be part of</small>	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M2002170022-12-R1.ZNF	Test Dates: 3/2/2020 - 3/5/2020	DUT Type: Portable Handset	Page 81 of 84	