



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 22 & 90

Applicant:

LG Electronics MobileComm U.S.A
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

6/28-7/21/2017

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

1M1706280211-04-R1.ZNF

FCC ID:

ZNFSP320

APPLICANT:

LG ELECTRONICS MOBILECOMM U.S.A

Applicant Type:

Certification

Model:

LG-SP320

Additional Model(s):

LGSP320, SP320, LG-US601, LGUS601, US601

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part:

§2.1049, §22(H), §90.691

Test Procedure(s):

ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02


Test Device Serial No.:

identical prototype [S/N: 04867, 04866, 34QZL, 34QZK, 34QZJ]



This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1706280211-04-R1.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1706280211-04.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 1 of 42



© 2017 PCTEST Engineering Laboratory, Inc.


V 6.7
06/23/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

TABLE OF CONTENTS


FCC PART 22(H) & 90 MEASUREMENT REPORT	3
1.0 INTRODUCTION	5
1.1 Scope.....	5
1.2 Testing Facility	5
2.0 PRODUCT INFORMATION.....	6
2.1 Equipment Description	6
2.2 Device Capabilities	6
2.3 Test Configuration.....	6
2.4 EMI Suppression Device(s)/Modifications.....	6
3.0 DESCRIPTION OF TESTS	7
3.1 Evaluation Procedure.....	7
3.2 Radiated Power and Radiated Spurious Emissions.....	7
4.0 MEASUREMENT UNCERTAINTY	8
5.0 TEST EQUIPMENT CALIBRATION DATA	9
6.0 SAMPLE CALCULATIONS	10
7.0 TEST RESULTS.....	11
7.1 Summary.....	11
7.2 Occupied Bandwidth	12
7.3 Spurious and Harmonic Emissions at Antenna Terminal	19
7.4 Band Edge Emissions at Antenna Terminal.....	24
7.5 Conducted Power Output Data	30
7.6 Radiated Power (ERP).....	31
7.7 Radiated Spurious Emissions Measurements.....	33
7.8 Frequency Stability / Temperature Variation	37
8.0 CONCLUSION.....	42

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 2 of 42	



MEASUREMENT REPORT

FCC Part 22(H) & 90



§2.1033 General Information



APPLICANT: LG Electronics MobileComm U.S.A
APPLICANT ADDRESS: 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
BASE MODEL: LG-SP320
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
MODE: CDMA / EvDO / LTE
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: 04867, 04866, 34QZL, ☐ Production ☒ Pre-Production ☐ Engineering
 34QZK, 34QZJ
DATE(S) OF TEST: 6/28-7/21/2017
TEST REPORT S/N: 1M1706280211-04-R1.ZNF


Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 3 of 42	





MEASUREMENT REPORT

FCC Part 22(H) & 90



Mode	Tx Frequency (MHz)	Emission Designator	Measurement	Max. Power (W)	Max. Power (dBm)
CDMA800 (BC10)	817.9 - 823.1	1M27F9W	Conducted	0.282	24.50
LTE Band 26	814.7 - 823.3	1M08G7D	Conducted	0.220	23.42
LTE Band 26	814.7 - 823.3	1M08W7D	Conducted	0.214	23.31
LTE Band 26	815.5 - 822.5	2M69G7D	Conducted	0.221	23.44
LTE Band 26	815.5 - 822.5	2M69W7D	Conducted	0.181	22.57
LTE Band 26	816.5 - 821.5	4M51G7D	Conducted	0.221	23.45
LTE Band 26	816.5 - 821.5	4M51W7D	Conducted	0.183	22.62
LTE Band 26	819	8M99G7D	Conducted	0.223	23.48
LTE Band 26	819	8M99W7D	Conducted	0.184	22.64
LTE Band 26	821.5	13M5G7D	ERP	0.127	21.04
LTE Band 26	821.5	13M5W7D	ERP	0.106	20.26

EUT Overview

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 4 of 42	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.






Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 5 of 42

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFSP320**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22(H) and 90.691.

2.2 Device Capabilities

This device contains the following capabilities:



850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 6 of 42	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions

\$2.1053, \$90.635, \$90.691

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3” (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.



Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$ specified in 90.691.



For fundamental radiated power measurements, the guidance of KDB 971168 D01 v02r02 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-D-2010.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 7 of 42

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09



FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 8 of 42

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX2	Licensed Transmitter Cable Set	5/3/2017	Annual	5/3/2018	LTX2
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Agilent	N9038A	MXE EMI Receiver	4/26/2017	Annual	4/26/2018	MY51210133
Agilent	E5515C	Wireless Communications Test Set	1/29/2016	Biennial	1/29/2018	GB46310798
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	6/21/2017	Annual	6/21/2018	441119
Com-Power	PAM-118A	PREAMPLIFIER 500MHZ TO 18GHZ	8/9/2016	Annual	8/9/2017	551079
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	12/5/2016	Biennial	12/5/2018	128338
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11401010036
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM2
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	11/18/2015	Biennial	11/18/2017	91052522TX
Schwarzbeck	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 9 of 42	

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission – BC10

Example: Channel 476 CDMA BC10 Mode 3rd Harmonic (2453.70MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 2453.70 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated



7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 10 of 42	

7.0 TEST RESULTS

7.1 Summary



Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFSP320
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA / EvDO / LTE
 Band: Band Class 10 / Band 26

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90.691	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except $> 50 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Sections 7.3, 7.4
2.1055 90.213	Frequency Stability	< 2.5 ppm		PASS	Section 7.8
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
22.913(a.2)	Effective Radiated Power (Band 26)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
2.1053 90.691	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except $> 50 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 11 of 42	

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.







Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 12 of 42	




Plot 7-1. Occupied Bandwidth Plot (Ch. 476)




Plot 7-2. Occupied Bandwidth Plot (Ch. 684)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 13 of 42




Plot 7-3. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6– Low Channel)




Plot 7-4. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6– Low Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 14 of 42




Plot 7-5. Occupied Bandwidth Plot (3MHz QPSK – RB Size 15– Low Channel)




Plot 7-6. Occupied Bandwidth Plot (3MHz 16-QAM – RB Size 15– Low Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 15 of 42




Plot 7-7. Occupied Bandwidth Plot (5MHz QPSK – RB Size 25– Low Channel)




Plot 7-8. Occupied Bandwidth Plot (5MHz 16-QAM – RB Size 25– Low Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 16 of 42




Plot 7-9. Occupied Bandwidth Plot (10MHz QPSK – RB Size 50)




Plot 7-10. Occupied Bandwidth Plot (10MHz 16-QAM – RB Size 50)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EVDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 17 of 42



Plot 7-11. Occupied Bandwidth Plot (15MHz QPSK – RB Size 75)



Plot 7-12. Occupied Bandwidth Plot (15MHz 16-QAM – RB Size 75)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 18 of 42

7.3 Spurious and Harmonic Emissions at Antenna Terminal

\$2.1051 \$90.691

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW \geq 1MHz
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 19 of 42




Plot 7-13. Conducted Spurious Plot (Ch. 476)




Plot 7-14. Conducted Spurious Plot (Ch. 476)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 20 of 42




Plot 7-15. Conducted Spurious Plot (Ch. 684)




Plot 7-16. Conducted Spurious Plot (Ch. 684)


FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 21 of 42




Plot 7-17. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-18. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)



FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 22 of 42



Plot 7-19. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-20. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 23 of 42

7.4 Band Edge Emissions at Antenna Terminal

\$2.1051 \$90.691

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + \log_{10}(P_{\text{Watts}}) = -13\text{dBm}$, where P is the transmitter power in Watts.

The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10 \log_{10}(P_{\text{Watts}}) = -20\text{dBm}$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


For channel edge emission, the signal analyzer's "ACP" measurement capability is used.

Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 24 of 42	




Plot 7-21. Channel Edge Plot (Ch. 476)




Plot 7-22. Channel Edge Plot (Ch. 684)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 25 of 42




Plot 7-23. Channel Edge Plot (1.4MHz QPSK – RB Size 6 – Low Channel)




Plot 7-24. Channel Edge Plot (1.4MHz QPSK – RB Size 6 – High Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 26 of 42




Plot 7-25. Channel Edge Plot (3MHz QPSK – RB Size 15– Low Channel)




Plot 7-26. Channel Edge Plot (3MHz QPSK – RB Size 15 – High Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 27 of 42




Plot 7-27. Channel Edge Plot (5MHz QPSK – RB Size 25– Low Channel)




Plot 7-28. Channel Edge Plot (5MHz QPSK – RB Size 25 – High Channel)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 28 of 42



Plot 7-29. Channel Edge Plot (10MHz QPSK – RB Size 50)



Plot 7-30. Channel Edge Plot (15MHz QPSK – RB Size 75)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION	LG	Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1-ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 29 of 42

7.5 Conducted Power Output Data

\$90.635

Frequency [MHz]	BC10 [Channel]	Battery Type	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
817.90	476	Standard	24.41	0.276	50.00	-25.59
823.10	684	Standard	24.50	0.282	50.00	-25.50



Table 7-2. CDMA BC10 Conducted Power Output Data

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
814.70	1.4	QPSK	23.42	0.220	50.00	-26.58
823.30	1.4	QPSK	23.31	0.214	50.00	-26.69
814.70	1.4	16-QAM	22.56	0.180	50.00	-27.44
823.30	1.4	16-QAM	23.31	0.214	50.00	-26.69
815.50	3	QPSK	23.40	0.219	50.00	-26.60
822.50	3	QPSK	23.44	0.221	50.00	-26.56
815.50	3	16-QAM	22.57	0.181	50.00	-27.43
822.50	3	16-QAM	22.40	0.174	50.00	-27.60
816.50	5	QPSK	23.45	0.221	50.00	-26.55
821.50	5	QPSK	23.40	0.219	50.00	-26.60
816.50	5	16-QAM	22.62	0.183	50.00	-27.38
821.50	5	16-QAM	22.21	0.166	50.00	-27.79
819.00	10	QPSK	23.48	0.223	50.00	-26.52
819.00	10	16-QAM	22.64	0.184	50.00	-27.36
821.50	15	QPSK	23.30	0.214	50.00	-26.70
821.50	15	16-QAM	22.40	0.174	50.00	-27.60

Table 7-3. LTE Band 26 Conducted Power Output Data

NOTES:

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 30 of 42

7.6 Radiated Power (ERP)

§22.913(a.2)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 31 of 42	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
821.50	15	QPSK	H	150	345	1 / 74	21.70	-0.66	21.04	38.45	-17.41
821.50	15	16-QAM	H	150	345	1 / 74	20.92	-0.66	20.26	38.45	-18.19
821.50	15	QPSK	V	13	170	1 / 74	19.69	-0.65	19.04	38.45	-19.41

Table 7-31. ERP Data (Band 26)

FCC ID: ZNFSP320	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION							Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset							Page 32 of 42

7.7 Radiated Spurious Emissions Measurements

\$2.1053 \$90.691

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 33 of 42	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-5. Test Instrument & Measurement Setup

Test Notes

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 34 of 42

OPERATING FREQUENCY: 817.90 MHz
CHANNEL: 476
MODULATION SIGNAL: CDMA
DISTANCE: 3 meters
LIMIT: -13.00 dBm



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1635.80	H	121	39	-69.67	6.35	-63.32	-50.3
2453.70	H	108	141	-70.10	6.86	-63.24	-50.2
3271.60	H	-	-	-68.44	7.12	-61.33	-48.3

Table 7-4. CDMA BC10 Radiated Spurious Data (Ch. 476)

OPERATING FREQUENCY: 823.10 MHz
CHANNEL: 684
MODULATION SIGNAL: CDMA
DISTANCE: 3 meters
LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1646.20	H	115	34	-66.77	6.31	-60.46	-47.5
2469.30	H	100	134	-70.15	6.85	-63.30	-50.3
3292.40	H	-	-	-68.16	7.12	-61.04	-48.0



Table 7-5. CDMA BC10 Radiated Spurious Data (Ch. 684)

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset		Page 35 of 42

OPERATING FREQUENCY: 819.00 MHz
 CHANNEL: 26740
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1638.00	H	121	52	-66.79	6.34	-60.45	-47.4
2457.00	H	-	-	-71.13	6.86	-64.27	-51.3

Table 7-6. Radiated Spurious Data (Ch. 26740)

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 36 of 42

7.8 Frequency Stability / Temperature Variation

\$2.1055 \$90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 37 of 42	

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.7
06/23/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



Frequency Stability / Temperature Variation

\$2.1055, \$90.213

OPERATING FREQUENCY: 817,900,000 Hz
 CHANNEL: 476
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	817,900,077	77	0.0000094
100 %		- 30	817,900,082	82	0.0000100
100 %		- 20	817,900,177	177	0.0000216
100 %		- 10	817,900,015	15	0.0000018
100 %		0	817,900,122	122	0.0000149
100 %		+ 10	817,899,826	-174	-0.0000213
100 %		+ 20	817,899,864	-136	-0.0000166
100 %		+ 30	817,899,857	-143	-0.0000175
100 %		+ 40	817,900,026	26	0.0000032
100 %		+ 50	817,900,112	112	0.0000137
BATT. ENDPOINT	3.45	+ 20	817,900,076	76	0.0000093

Table 7-7. CDMA BC10 Frequency Stability Data (Ch. 476)

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 38 of 42

Frequency Stability / Temperature Variation

§2.1055, §90.213






Figure 7-6. CDMA BC10 Frequency Stability Graph (Ch. 476)

FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 39 of 42



Frequency Stability / Temperature Variation

\$2.1055, \$90.213

OPERATING FREQUENCY: 819,000,000 Hz
 CHANNEL: 26740
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	817,900,000	-17	-0.0000021
100 %		- 30	817,900,000	59	0.0000072
100 %		- 20	817,900,000	8	0.0000010
100 %		- 10	817,900,000	-120	-0.0000147
100 %		0	817,900,000	179	0.0000219
100 %		+ 10	817,900,000	191	0.0000233
100 %		+ 20	817,900,000	199	0.0000243
100 %		+ 30	817,900,000	273	0.0000333
100 %		+ 40	817,900,000	-177	-0.0000216
100 %		+ 50	817,900,000	312	0.0000381
BATT. ENDPOINT		+ 20	817,900,000	-12	-0.0000015

Table 7-8. LTE Band 26 Frequency Stability Data (Ch. 26740)

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset			Page 40 of 42

Frequency Stability / Temperature Variation

§2.1055, §90.213








Table 7-9. LTE Band 26 Frequency Stability Data (Ch. 26740)

FCC ID: ZNFSP320	 Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 41 of 42

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFSP320** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: ZNFSP320		Part 22(H) & 90 CDMA / EvDO / LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1706280211-04-R1.ZNF	Test Dates: 6/28-7/21/2017	EUT Type: Portable Handset	Page 42 of 42	