



## SAR EVALUATION REPORT

**Applicant Name:**  
 LG Electronics MobileComm U.S.A., Inc.  
 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632  
 United States

**Date of Testing:**  
 11/07/16 – 12/19/16  
**Test Site/Location:**  
 PCTEST Lab, Columbia, MD, USA  
**Document Serial No.:**  
 0Y1611071720-R5.ZNF

**FCC ID:** ZNFTP260  
**APPLICANT:** LG ELECTRONICS MOBILECOMM U.S.A., INC.

**DUT Type:** Portable Handset  
**Application Type:** Certification  
**FCC Rule Part(s):** CFR §2.1093  
**Model(s):** LG-TP260, LGTP260, TP260, LG-MP260, LGMP260, MP260, LG-TP260BK, LGTP260BK, TP260BK

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.46	0.64	0.64
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.33	0.61	0.61
PCE	UMTS 850	826.40 - 846.60 MHz	0.49	0.78	0.78
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.51	0.98	0.98
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.67	1.18	1.18
PCE	LTE Band 12	699.7 - 715.3 MHz	0.35	0.54	0.54
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.52	0.90	0.90
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.44	1.09	1.09
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.66	1.19	1.19
DTS	2.4 GHz WLAN	2412 - 2462 MHz	1.04	0.54	0.54
NII	U-NII-1	5180 - 5240 MHz	N/A		
NII	U-NII-2A	5260 - 5320 MHz	0.95	0.18	N/A
NII	U-NII-2C	5500 - 5700 MHz	0.87	0.11	N/A
NII	U-NII-3	5745 - 5825 MHz	1.19	0.17	0.39
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A	< 0.1	N/A
<b>Simultaneous SAR per KDB 690783 D01v01r03:</b>			1.58	1.52	1.58

Note: This revised Test Report (S/N: 0Y1611071720-R5.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez  
 President





The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: [sartick@mmfai.info](mailto:sartick@mmfai.info).

<b>FCC ID:</b> ZNFTP260	<b>SAR EVALUATION REPORT</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset
		Page 1 of 67

# TABLE OF CONTENTS

1	DEVICE UNDER TEST .....	3
2	LTE INFORMATION .....	9
3	INTRODUCTION .....	10
4	DOSIMETRIC ASSESSMENT .....	11
5	DEFINITION OF REFERENCE POINTS.....	12
6	TEST CONFIGURATION POSITIONS.....	13
7	RF EXPOSURE LIMITS .....	16
8	FCC MEASUREMENT PROCEDURES.....	17
9	RF CONDUCTED POWERS .....	22
10	SYSTEM VERIFICATION.....	41
11	SAR DATA SUMMARY .....	43
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	54
13	SAR MEASUREMENT VARIABILITY .....	62
14	EQUIPMENT LIST.....	63
15	MEASUREMENT UNCERTAINTIES.....	64
16	CONCLUSION.....	65
17	REFERENCES .....	66
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: WIFI POWER REDUCTION VERIFICATION		

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 2 of 67	

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5700 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

## 1.2 Power Reduction for SAR



This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

## 1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

### 1.3.1 Maximum Output Powers

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
			1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots
GSM/GPRS/EDGE 850	Maximum	32.7	32.7	31.7	29.7	28.7	27.7	26.7	24.7	23.7
	Nominal	32.2	32.2	31.2	29.2	28.2	27.2	26.2	24.2	23.2
GSM/GPRS/EDGE 1900	Maximum	30.7	30.7	28.7	26.7	25.7	26.7	25.7	23.7	22.7
	Nominal	30.2	30.2	28.2	26.2	25.2	26.2	25.2	23.2	22.2



FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 3 of 67

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>
UMTS Band 4 (1750 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>
UMTS Band 2 (1900 MHz)	Maximum	<b>24.7</b>	<b>24.7</b>	<b>24.7</b>
	Nominal	<b>24.2</b>	<b>24.2</b>	<b>24.2</b>

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	<b>25.2</b>
	Nominal	<b>24.7</b>
LTE Band 5 (Cell)	Maximum	<b>25.2</b>
	Nominal	<b>24.7</b>
LTE Band 4 (AWS)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>
LTE Band 2 (PCS)	Maximum	<b>24.7</b>
	Nominal	<b>24.2</b>

Mode / Band		Modulated Average (dBm)		
		Ch. 1	Ch. 2-10	Ch. 11
IEEE 802.11b (2.4 GHz)	Maximum	<b>21.0</b>		
	Nominal	<b>20.0</b>		
IEEE 802.11g (2.4 GHz)	Maximum	<b>17.0</b>	<b>20.0</b>	<b>17.0</b>
	Nominal	<b>16.0</b>	<b>19.0</b>	<b>16.0</b>
IEEE 802.11n (2.4 GHz)	Maximum	<b>16.0</b>	<b>19.0</b>	<b>16.0</b>
	Nominal	<b>15.0</b>	<b>18.0</b>	<b>15.0</b>

Mode / Band		Modulated Average (dBm)			
		20 MHz Bandwidth			40 MHz Bandwidth
		Ch. 36	Ch. 40, 56, 157	Ch. 44-52, 60-153, 161-165	
IEEE 802.11a (5 GHz)	Maximum	<b>18.0</b>	<b>20.0</b>	<b>19.0</b>	
	Nominal	<b>17.0</b>	<b>19.0</b>	<b>18.0</b>	
IEEE 802.11n (5 GHz)	Maximum	<b>17.0</b>	<b>19.0</b>	<b>18.0</b>	<b>14.0</b>
	Nominal	<b>16.0</b>	<b>18.0</b>	<b>17.0</b>	<b>13.0</b>



FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>			<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 4 of 67	

Mode / Band		Modulated Average (dBm)
Bluetooth (1 Mbps)	Maximum	<b>11.0</b>
	Nominal	<b>10.0</b>
Bluetooth (2 Mbps)	Maximum	<b>10.0</b>
	Nominal	<b>9.0</b>
Bluetooth (3 Mbps)	Maximum	<b>10.0</b>
	Nominal	<b>9.0</b>
Bluetooth LE	Maximum	<b>1.0</b>
	Nominal	<b>0.0</b>

### 1.3.2 Reduced Output Powers

Mode / Band		Modulated Average (dBm)		
		Ch. 1	Ch. 2-10	Ch. 11
IEEE 802.11b (2.4 GHz)	Maximum	<b>17.0</b>		
	Nominal	<b>16.0</b>		
IEEE 802.11g (2.4 GHz)	Maximum	<b>14.0</b>	<b>17.0</b>	<b>14.0</b>
	Nominal	<b>13.0</b>	<b>16.0</b>	<b>13.0</b>
IEEE 802.11n (2.4 GHz)	Maximum	<b>14.0</b>	<b>17.0</b>	<b>14.0</b>
	Nominal	<b>13.0</b>	<b>16.0</b>	<b>13.0</b>

Mode / Band		Modulated Average (dBm)			
		20 MHz Bandwidth			40 MHz Bandwidth
		Ch. 36	Ch. 40, 56, 157	Ch. 44-52, 60-153, 161-165	
IEEE 802.11a (5 GHz)	Maximum	<b>14.0</b>	<b>16.0</b>	<b>15.0</b>	
	Nominal	<b>13.0</b>	<b>15.0</b>	<b>14.0</b>	
IEEE 802.11n (5 GHz)	Maximum	<b>14.0</b>	<b>16.0</b>	<b>15.0</b>	<b>14.0</b>
	Nominal	<b>13.0</b>	<b>15.0</b>	<b>14.0</b>	<b>13.0</b>

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 5 of 67	

## 1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.


**Table 1-1  
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No
5 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.



## 1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



**Figure 1-1  
Simultaneous Transmission Paths**

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 6 of 67

**Table 1-2  
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	
5	UMTS + 5 GHz WI-FI	Yes	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
7	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	
8	LTE + 5 GHz WI-FI	Yes	Yes	Yes	
9	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
10	GPRS/EDGE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
11	GPRS/EDGE + 5 GHz WI-FI	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
12	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	Yes*	N/A	*-Pre-installed VOIP applications are considered.
13	GSM voice + 2.4 GHz Bluetooth + 5 GHz WI-FI	N/A	Yes	N/A	
14	UMTS + 2.4 GHz Bluetooth + 5 GHz WI-FI	N/A	Yes	N/A	
15	LTE + 2.4 GHz Bluetooth + 5 GHz WI-FI	N/A	Yes	N/A	
16	GPRS/EDGE + 2.4 GHz Bluetooth + 5 GHz WI-FI	N/A	Yes*	N/A	*-Pre-installed VOIP applications are considered.

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Simultaneous transmission scenarios involving WIFI direct are included in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports VOLTE.
6. This device supports VOWIFI.

## 1.6 Miscellaneous SAR Test Considerations

### (A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.



Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

### (B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest

FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 7 of 67	

bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.



## 1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- October 2016 TCB Workshop Notes (Bluetooth Testing Considerations)

## 1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	00191	00191	00191
GSM/GPRS/EDGE 1900	00167	00167	00167
UMTS 850	00167	00209	00209
UMTS 1750	00175	00175	00175
UMTS 1900	00167	00167	00167
LTE Band 12	00167	00167	00167
LTE Band 5 (Cell)	00167	00191	00191
LTE Band 4 (AWS)	00175	00175	00175
LTE Band 2 (PCS)	00167	00167	00167
2.4 GHz WLAN	2SJR0	2SJR0	2SJR0
5 GHz WLAN	2SJR0	2SJR0	2SJR0
Bluetooth	-	2SJR0	-



FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 8 of 67



## 2

## LTE INFORMATION

LTE Information			
<b>FCC ID</b>	<b>ZNFTP260</b>		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	4		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations		
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, WIFI Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.		

<b>FCC ID:</b> ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 9 of 67

### 3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

#### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1  
SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 10 of 67

# 4 DOSIMETRIC ASSESSMENT

## 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.





**Figure 4-1**  
Sample SAR Area Scan

**Table 4-1**  
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\*

Frequency	Maximum Area Scan Resolution (mm) ( $\Delta x_{area}, \Delta y_{area}$ )	Maximum Zoom Scan Resolution (mm) ( $\Delta x_{zoom}, \Delta y_{zoom}$ )	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22


\*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 11 of 67

# 5 DEFINITION OF REFERENCE POINTS

## 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view of ERP

## 5.2 HANDSET REFERENCE POINTS



Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom



**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 12 of 67

## 6 TEST CONFIGURATION POSITIONS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position


2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

### 6.3 Positioning for Ear / 15° Tilt


With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 13 of 67



**Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position**



**Figure 6-3 Side view w/ relevant markings**


## 6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.



## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



**Figure 6-4 Sample Body-Worn Diagram**

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 14 of 67

dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person’s face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations



Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user’s body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 15 of 67

# 7 RF EXPOSURE LIMITS

## 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



## 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1  
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
<b>Peak Spatial Average SAR</b> Head	1.6	8.0
<b>Whole Body SAR</b>	0.08	0.4
<b>Peak Spatial Average SAR</b> Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 16 of 67	



## 8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

### 8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is  $\leq 0.25$  dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is  $\leq 1.2$  W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

### 8.3 Procedures Used to Establish RF Signal for SAR



The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

### 8.4 SAR Measurement Conditions for UMTS

#### 8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 17 of 67

## 8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

## 8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH<sub>n</sub> configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH<sub>n</sub>, for the highest reported SAR configuration in 12.2 kbps RMC.

## 8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

## 8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

## 8.5 SAR Measurement Conditions for LTE



LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 18 of 67

### 8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### 8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:



- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

### 8.5.5 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

## 8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 19 of 67	

## 8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

## 8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is  $> 1.2$  W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is  $> 1.2$  W/kg.

## 8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.



## 8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.

## 8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 20 of 67

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

### 8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.



### 8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

### 8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is  $\leq 1.2$  W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 21 of 67



## 9 RF CONDUCTED POWERS

### 9.1 GSM Conducted Powers

Maximum Burst-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.57	32.58	31.66	29.66	<b>28.26</b>	27.50	26.40	24.50	23.44
	190	32.42	32.43	31.64	29.61	<b>28.51</b>	27.44	26.56	24.51	23.40
	251	32.41	32.38	31.59	29.55	<b>28.55</b>	27.56	26.33	24.44	23.28
GSM 1900	512	30.36	30.53	28.48	26.50	<b>25.50</b>	26.51	25.40	23.44	22.40
	661	30.48	30.58	28.70	26.62	<b>25.61</b>	26.45	25.33	23.45	22.45
	810	30.40	30.50	28.52	26.57	<b>25.55</b>	26.26	25.60	23.51	22.55

Calculated Maximum Frame-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.54	23.55	25.64	25.40	<b>25.25</b>	18.47	20.38	20.24	20.43
	190	23.39	23.40	25.62	25.35	<b>25.50</b>	18.41	20.54	20.25	20.39
	251	23.38	23.35	25.57	25.29	<b>25.54</b>	18.53	20.31	20.18	20.27
GSM 1900	512	21.33	21.50	22.46	22.24	<b>22.49</b>	17.48	19.38	19.18	19.39
	661	21.45	21.55	22.68	22.36	<b>22.60</b>	17.42	19.31	19.19	19.44
	810	21.37	21.47	22.50	22.31	<b>22.54</b>	17.23	19.58	19.25	19.54

<b>GSM 850</b>	<b>Frame Avg. Targets:</b>	23.17	23.17	25.18	24.94	<b>25.19</b>	18.17	20.18	19.94	20.19
<b>GSM 1900</b>		21.17	21.17	22.18	21.94	<b>22.19</b>	17.17	19.18	18.94	19.19

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT					Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset				Page 22 of 67	

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

**GSM Class: B**  
**GPRS Multislot class: 12 (Max 4 Tx uplink slots)**  
**EDGE Multislot class: 12 (Max 4 Tx uplink slots)**  
**DTM Multislot Class: N/A**



**Figure 9-1**  
**Power Measurement Setup**

<b>FCC ID:</b> ZNFTP260	<b>PCTEST</b> <small>ENGINEERING LABORATORY, INC.</small>	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 23 of 67	



## 9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.57	24.64	24.59	24.54	24.69	24.65	24.58	24.68	24.58	-
99		12.2 kbps AMR	24.60	24.61	24.61	24.50	24.70	24.66	24.55	24.59	24.51	-
6	HSDPA	Subtest 1	24.62	24.70	24.66	24.54	24.66	24.42	24.46	24.49	24.52	0
6		Subtest 2	24.61	24.60	24.61	24.60	24.68	24.48	24.50	24.47	24.46	0
6		Subtest 3	24.11	24.15	24.15	24.01	24.07	23.96	23.94	23.88	23.93	0.5
6		Subtest 4	24.13	24.10	24.20	24.02	24.03	23.98	24.08	23.81	23.86	0.5
6	HSUPA	Subtest 1	24.07	24.49	23.94	24.62	24.43	24.04	24.43	23.82	24.38	0
6		Subtest 2	22.59	22.17	22.14	22.59	22.24	22.54	22.46	22.26	22.45	2
6		Subtest 3	23.22	23.46	23.69	23.61	23.65	23.57	23.53	23.34	23.56	1
6		Subtest 4	22.61	22.21	22.17	22.49	22.21	22.58	22.49	22.31	22.48	2
6		Subtest 5	24.46	24.51	24.33	24.41	24.36	24.30	24.15	24.20	24.12	0

This device does not support DC-HSDPA.



**Figure 9-2**  
Power Measurement Setup

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 24 of 67



### 9.3 LTE Conducted Powers

#### 9.3.1 LTE Band 12



**Table 9-1  
LTE Band 12 Conducted Powers - 10 MHz Bandwidth**

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.01	0	0
	1	25	<b>25.20</b>		0
	1	49	25.08		0
	25	0	<b>24.12</b>	0-1	1
	25	12	23.87		1
	25	25	23.99		1
16QAM	50	0	23.96	0-1	1
	1	0	24.20		1
	1	25	24.13		1
	1	49	23.61	0-2	1
	25	0	23.17		2
	25	12	22.90		2
	25	25	22.94	2	
	50	0	22.90	2	

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-2  
LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.94	25.00	24.99	0	0
	1	12	25.13	25.01	25.19		0
	1	24	25.08	25.00	24.73		0
	12	0	23.99	24.07	23.96	0-1	1
	12	6	24.18	24.06	24.07		1
	12	13	24.02	24.04	23.94		1
16QAM	25	0	24.01	23.94	23.87	0-1	1
	1	0	23.93	23.84	23.81		1
	1	12	24.03	23.87	24.17		1
	1	24	24.11	23.76	24.00	0-2	1
	12	0	23.01	22.99	22.87		2
	12	6	23.11	22.99	23.00		2
	12	13	23.07	22.90	22.98	2	
	25	0	22.94	22.92	23.00	2	



FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 25 of 67

**Table 9-3  
LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.81	24.90	25.05	0	0
	1	7	24.87	24.91	25.00		0
	1	14	25.20	24.96	24.75		0
	8	0	23.94	23.98	23.98	0-1	1
	8	4	23.86	24.01	24.09		1
	8	7	24.05	24.01	23.95		1
16QAM	15	0	23.84	23.99	24.04	0-1	1
	1	0	23.67	24.18	24.06		1
	1	7	23.98	24.20	24.20		1
	1	14	24.05	23.56	23.92	0-2	1
	8	0	23.00	22.98	23.02		2
	8	4	22.89	22.93	22.83		2
	8	7	23.13	22.89	22.82	2	
	15	0	22.86	22.99	22.89	2	

**Table 9-4  
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth**

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.01	24.80	24.84	0	0
	1	2	25.11	24.91	24.91		0
	1	5	25.05	24.85	24.85		0
	3	0	24.93	24.92	24.89		0
	3	2	25.00	24.99	24.85		0
	3	3	24.95	25.01	24.93	0	
16QAM	6	0	23.89	24.09	23.95	0-1	1
	1	0	24.18	23.87	23.97	0-1	1
	1	2	24.20	24.01	24.15		1
	1	5	24.20	24.09	24.04		1
	3	0	24.00	24.14	23.99		1
	3	2	24.04	24.20	24.02		1
	3	3	23.99	24.18	23.99	1	
	6	0	22.64	22.96	23.06	0-2	2

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 26 of 67

### 9.3.2 LTE Band 5 (Cell)



**Table 9-5**  
**LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth**

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.83	0	0
	1	25	<b>25.10</b>		0
	1	49	25.02		0
	25	0	24.08	0-1	1
	25	12	<b>24.14</b>		1
	25	25	24.04		1
16QAM	50	0	24.07	0-1	1
	1	0	24.16		1
	1	25	24.18		1
	1	49	24.15	0-2	1
	25	0	23.14		2
	25	12	23.14		2
	25	25	22.94	2	
	50	0	23.04	2	

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-6**  
**LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth**

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.89	24.90	24.96	0	0
	1	12	25.04	25.01	24.94		0
	1	24	24.89	24.81	24.83		0
	12	0	23.95	24.18	24.02	0-1	1
	12	6	24.10	24.10	24.03		1
	12	13	24.05	23.99	24.02		1
16QAM	25	0	24.05	24.01	24.08	0-1	1
	1	0	24.02	24.20	23.77		1
	1	12	24.02	24.15	23.89		1
	1	24	23.96	23.81	23.79	0-2	1
	12	0	22.88	22.80	22.73		2
	12	6	22.89	22.82	22.78		2
	12	13	22.83	22.73	22.95	2	
	25	0	22.99	22.91	22.96	2	



FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 27 of 67

**Table 9-7**  
**LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth**

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.90	25.00	24.98	0	0
	1	7	25.05	25.20	24.94		0
	1	14	24.98	24.98	24.98		0
	8	0	24.04	24.07	24.05	0-1	1
	8	4	24.09	24.06	24.08		1
	8	7	24.03	24.05	24.05		1
	15	0	24.15	24.11	24.08		1
16QAM	1	0	24.18	23.78	24.09	0-1	1
	1	7	24.13	23.82	24.20		1
	1	14	24.12	23.53	24.07		1
	8	0	23.16	23.04	23.11	0-2	2
	8	4	23.13	23.05	23.20		2
	8	7	23.08	22.94	22.90		2
	15	0	23.20	23.00	22.97		2

**Table 9-8**  
**LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth**

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.92	25.01	24.88	0	0
	1	2	24.91	25.03	25.10		0
	1	5	24.89	24.95	25.01		0
	3	0	24.94	25.03	25.03		0
	3	2	24.99	25.13	25.03		0
	3	3	24.95	25.08	25.06		0
	6	0	24.01	24.10	23.87	0-1	1
16QAM	1	0	24.20	24.07	24.10	0-1	1
	1	2	24.13	24.19	24.20		1
	1	5	24.18	24.16	24.16		1
	3	0	24.02	24.12	24.05		1
	3	2	24.05	24.20	23.82		1
	3	3	24.00	24.12	24.15		1
	6	0	22.69	23.09	22.93	0-2	2

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 28 of 67

### 9.3.3 LTE Band 4 (AWS)



**Table 9-9**  
**LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.23	0	0
	1	50	24.57		0
	1	99	24.22		0
	50	0	23.59	0-1	1
	50	25	23.53		1
	50	50	23.38		1
16QAM	100	0	23.49	0-1	1
	1	0	23.10		1
	1	50	23.11		1
	1	99	22.79	0-2	1
	50	0	22.66		2
	50	25	22.60		2
	50	50	22.30		2
100	0	22.43	2		

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-10**  
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.42	24.46	24.49	0	0
	1	36	24.34	24.46	24.28		0
	1	74	24.58	24.25	24.46		0
	36	0	23.37	23.44	23.35	0-1	1
	36	18	23.35	23.45	23.22		1
	36	37	23.33	23.54	23.43		1
	75	0	23.31	23.20	23.32		1
16QAM	1	0	23.31	23.33	23.64	0-1	1
	1	36	23.70	23.50	23.48		1
	1	74	23.27	23.56	23.66		1
	36	0	22.48	22.70	22.28	0-2	2
	36	18	22.50	22.54	22.25		2
	36	37	22.37	22.36	22.36		2
	75	0	22.25	22.39	22.38		2



FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 29 of 67

**Table 9-11**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.38	24.34	24.51	0	0
	1	25	24.52	24.60	24.70		0
	1	49	24.32	24.43	24.66		0
	25	0	23.39	23.42	23.38	0-1	1
	25	12	23.29	23.60	23.35		1
	25	25	23.27	23.48	23.44		1
16QAM	50	0	23.48	23.38	23.37	0-1	1
	1	0	23.20	23.41	22.80		1
	1	25	23.24	23.47	23.70		1
	1	49	22.98	23.37	23.66	0-2	1
	25	0	22.56	22.56	22.34		2
	25	12	22.38	22.62	22.30		2
	25	25	22.48	22.46	22.36	2	
	50	0	22.25	22.47	22.33	2	

**Table 9-12**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.41	24.53	24.39	0	0
	1	12	24.34	24.70	24.55		0
	1	24	24.27	24.40	24.60		0
	12	0	23.48	23.54	23.63	0-1	1
	12	6	23.42	23.55	23.56		1
	12	13	23.41	23.49	23.49		1
16QAM	25	0	23.52	23.51	23.51	0-1	1
	1	0	23.52	23.50	23.45		1
	1	12	23.36	23.64	23.54		1
	1	24	23.19	23.58	23.65	0-2	1
	12	0	22.39	22.70	22.62		2
	12	6	22.34	22.65	22.66		2
	12	13	22.33	22.63	22.58	2	
	25	0	22.37	22.57	22.61	2	



FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 30 of 67

**Table 9-13**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

LTE Band 4 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.49	24.60	24.48	0	0
	1	7	24.36	24.70	24.51		0
	1	14	24.28	24.60	24.43		0
	8	0	23.48	23.55	23.47	0-1	1
	8	4	23.59	23.56	23.49		1
	8	7	23.27	23.53	23.43		1
	15	0	23.40	23.54	23.32		1
16QAM	1	0	23.40	23.23	23.47	0-1	1
	1	7	23.40	23.29	23.47		1
	1	14	23.44	23.19	23.44		1
	8	0	22.35	22.69	22.14	0-2	2
	8	4	22.30	22.59	22.10		2
	8	7	22.21	22.55	22.25		2
	15	0	22.50	22.54	22.31		2

**Table 9-14**  
**LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth**

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.62	24.25	0	0
	1	2	24.52	24.61	24.60		0
	1	5	24.50	24.47	24.53		0
	3	0	24.43	24.47	24.43		0
	3	2	24.50	24.52	24.47		0
	3	3	24.54	24.49	24.41		0
	6	0	23.16	23.50	23.44	0-1	1
16QAM	1	0	23.66	23.46	23.70	0-1	1
	1	2	23.65	23.60	23.66		1
	1	5	23.08	23.49	23.65		1
	3	0	23.42	23.70	23.45		1
	3	2	23.48	23.65	23.46		1
	3	3	23.37	23.69	23.39		1
	6	0	22.41	22.70	22.12	0-2	2

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 31 of 67	



### 9.3.4 LTE Band 2 (PCS)

**Table 9-15**  
**LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth**

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.33	24.63	24.28	0	0
	1	50	24.55	24.68	24.65		0
	1	99	24.22	24.61	24.21		0
	50	0	23.47	23.51	23.41	0-1	1
	50	25	23.56	23.40	23.35		1
	50	50	23.55	23.32	23.27		1
16QAM	100	0	23.52	23.37	23.35	0-1	1
	1	0	23.28	23.08	23.36		1
	1	50	23.39	23.46	23.44		1
	1	99	23.18	22.86	23.24	0-2	1
	50	0	22.62	22.43	22.48		2
	50	25	22.59	22.43	22.33		2
	50	50	22.47	22.25	22.06	2	
	100	0	22.47	22.30	22.30	2	

**Table 9-16**  
**LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth**

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.70	24.33	24.40	0	0
	1	36	24.66	24.57	24.35		0
	1	74	24.62	24.30	24.24		0
	36	0	23.48	23.40	23.47	0-1	1
	36	18	23.52	23.36	23.34		1
	36	37	23.41	23.28	23.19		1
16QAM	75	0	23.43	23.26	23.25	0-1	1
	1	0	23.39	23.65	23.64		1
	1	36	23.70	23.70	23.69		1
	1	74	23.64	23.66	23.30	0-2	1
	36	0	22.47	22.46	22.54		2
	36	18	22.60	22.53	22.32		2
	36	37	22.49	22.32	22.10	2	
	75	0	22.44	22.30	22.30	2	

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 32 of 67





**Table 9-17**  
**LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth**

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.55	24.41	24.43	0	0
	1	25	24.58	24.66	24.55		0
	1	49	24.48	24.36	24.35		0
	25	0	23.41	23.38	23.34	0-1	1
	25	12	23.49	23.40	23.27		1
	25	25	23.33	23.33	23.23		1
	50	0	23.35	23.36	23.26		1
16QAM	1	0	22.83	23.70	23.38	0-1	1
	1	25	23.55	23.18	23.41		1
	1	49	23.60	23.67	23.08		1
	25	0	22.49	22.52	22.47	0-2	2
	25	12	22.47	22.54	22.59		2
	25	25	22.39	22.32	22.23		2
	50	0	22.43	22.26	22.29		2

**Table 9-18**  
**LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.45	24.38	0	0
	1	12	24.40	24.52	24.40		0
	1	24	24.33	24.40	24.35		0
	12	0	23.46	23.41	23.38	0-1	1
	12	6	23.53	23.44	23.28		1
	12	13	23.47	23.37	23.19		1
	25	0	23.48	23.39	23.41		1
16QAM	1	0	23.55	23.38	23.37	0-1	1
	1	12	23.60	23.06	23.53		1
	1	24	23.52	22.85	23.35		1
	12	0	22.39	22.52	22.57	0-2	2
	12	6	22.46	22.66	22.57		2
	12	13	22.50	22.59	22.37		2
	25	0	22.57	22.40	22.47		2



FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 33 of 67

**Table 9-19**  
**LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.37	24.33	24.35	0	0
	1	7	24.47	24.38	24.34		0
	1	14	24.35	24.26	24.28		0
	8	0	23.52	23.44	23.49	0-1	1
	8	4	23.58	23.35	23.29		1
	8	7	23.53	23.31	23.24		1
	15	0	23.51	23.31	23.37		1
16QAM	1	0	23.55	23.66	23.48	0-1	1
	1	7	23.65	23.70	23.47		1
	1	14	23.54	23.66	23.26		1
	8	0	22.63	22.45	22.26	0-2	2
	8	4	22.58	22.46	22.06		2
	8	7	22.47	22.41	21.94		2
	15	0	22.56	22.40	22.07		2

**Table 9-20**  
**LTE Band 2 (PCS) Conducted Powers - 1.4 MHz Bandwidth**

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.49	24.30	24.34	0	0
	1	2	24.44	24.33	24.37		0
	1	5	24.38	24.47	24.28		0
	3	0	24.31	24.22	24.29		0
	3	2	24.45	24.27	24.35		0
	3	3	24.40	24.32	24.37		0
	6	0	23.54	23.41	23.26	0-1	1
16QAM	1	0	23.50	23.24	23.62	0-1	1
	1	2	23.08	23.27	23.43		1
	1	5	23.24	23.15	23.28		1
	3	0	23.52	23.64	23.30		1
	3	2	23.66	23.63	23.28		1
	3	3	23.29	23.58	23.22		1
	6	0	22.21	22.62	22.61	0-2	2

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 34 of 67

### 9.3.5 LTE Carrier Aggregation Conducted Powers

Table 9-21  
LTE Carrier Aggregation Conducted Powers



PCC									SCC				Power	
PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Rel. 10 Tx.Power (dBm)	LTE Rel. 8 Tx.Power (dBm)
LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	10	900	1960	25.13	25.20
LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B4	10	2175	2132.5	25.16	25.20
LTE B2	10	18900	1880	QPSK	1	25	900	1960	LTE B12	10	5095	737.5	24.62	24.66
LTE B4	10	20350	1750	QPSK	1	25	2350	2150	LTE B12	10	5095	737.5	24.60	24.70

Notes:

1. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.



Figure 9-3  
Power Measurement Setup

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 35 of 67



## 9.4 WLAN Conducted Powers

**Table 9-22**  
**2.4 GHz WLAN Maximum Average RF Power**

2.4GHz Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11b	802.11g
2412	1	20.02	16.07
2417	2	N/A	19.07
2437	6	20.03	19.08
2457	10	N/A	19.09
2462	11	20.06	16.06

**Table 9-23**  
**2.4 GHz WLAN Reduced Average RF Power**

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	16.13	13.24	13.18
2417	2	N/A	16.09	16.15
2437	6	16.21	16.11	16.26
2457	10	N/A	16.10	16.22
2462	11	16.25	13.19	13.21



FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 36 of 67

**Table 9-24**  
**5 GHz WLAN Maximum Average RF Power**

5GHz (20MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11a
5180	36	17.93
5200	40	19.21
5220	44	18.41
5240	48	18.37
5260	52	18.30
5280	56	19.27
5300	60	18.29
5320	64	18.27
5500	100	18.42
5580	116	18.42
5660	132	18.29
5700	140	18.37
5745	149	18.25
5785	157	19.26
5825	165	18.30


**Table 9-25**  
**5 GHz WLAN Reduced Average RF Power**

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11a	802.11n
5180	36	13.97	13.93
5200	40	15.47	15.11
5220	44	14.49	14.08
5240	48	14.62	14.44
5260	52	14.43	14.20
5280	56	15.54	15.08
5300	60	14.64	14.32
5320	64	14.81	14.50
5500	100	14.62	14.35
5580	116	14.65	14.31
5660	132	14.40	14.05
5700	140	14.47	14.11
5745	149	14.52	14.19
5785	157	15.80	15.36
5825	165	14.53	14.34



FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 37 of 67

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




**Figure 9-4**  
**Power Measurement Setup**

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 38 of 67



## 9.5 Bluetooth Conducted Powers

**Table 9-26**  
**Bluetooth Average RF Power**

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	9.15	8.231
2441	1.0	39	<b>10.58</b>	11.429
2480	1.0	78	8.55	7.166
2402	2.0	0	8.50	7.074
2441	2.0	39	9.93	9.841
2480	2.0	78	7.89	6.146
2402	3.0	0	8.56	7.175
2441	3.0	39	9.99	9.985
2480	3.0	78	7.95	6.240



**Figure 9-5**  
**Power Measurement Setup**

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 39 of 67






Figure 9-6  
Bluetooth Transmission Plot

Equation 9-1  
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.889\ ms}{3.749\ ms} * 100\% = 77.1\%$$

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 40 of 67





# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1  
Measured Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
11/8/2016	750H	20.9	700	0.859	42.640	0.889	42.201	-3.37%	1.04%
			710	0.868	42.495	0.890	42.149	-2.47%	0.82%
			740	0.894	42.045	0.893	41.994	0.11%	0.12%
			755	0.908	41.828	0.894	41.916	1.57%	-0.21%
			820	0.911	42.608	0.899	41.578	1.33%	2.48%
11/7/2016	835H	20.1	835	0.927	42.457	0.900	41.500	3.00%	2.31%
			850	0.940	42.265	0.916	41.500	2.62%	1.84%
			1710	1.329	40.099	1.348	40.142	-1.41%	-0.11%
11/7/2016	1750H	20.8	1750	1.370	39.889	1.371	40.079	-0.07%	-0.47%
			1790	1.413	39.730	1.394	40.016	1.36%	-0.71%
			1850	1.359	40.032	1.400	40.000	-2.93%	0.08%
11/8/2016	1900H	23.0	1880	1.388	39.899	1.400	40.000	-0.86%	-0.25%
			1910	1.419	39.770	1.400	40.000	1.36%	-0.57%
			2400	1.814	38.457	1.756	39.289	3.30%	-2.12%
11/10/2016	2450H	22.2	2450	1.869	38.283	1.800	39.200	3.83%	-2.34%
			2500	1.924	38.087	1.855	39.136	3.72%	-2.68%
12/19/2016	2450H	22.0	2400	1.824	39.163	1.756	39.289	3.87%	-0.32%
			2450	1.872	38.889	1.800	39.200	4.00%	-0.79%
			2500	1.937	38.684	1.855	39.136	4.42%	-1.15%
			5240	4.637	34.828	4.696	35.940	-1.26%	-3.09%
			5260	4.658	34.789	4.717	35.917	-1.25%	-3.14%
11/07/2016	5200H-5800H	19.6	5280	4.682	34.779	4.737	35.894	-1.16%	-3.11%
			5320	4.712	34.704	4.778	35.849	-1.38%	-3.19%
			5500	4.895	34.430	4.963	35.643	-1.37%	-3.40%
			5580	4.974	34.294	5.045	35.551	-1.41%	-3.54%
			5600	4.996	34.274	5.065	35.529	-1.36%	-3.53%
			5745	5.154	34.035	5.214	35.363	-1.15%	-3.76%
			5765	5.178	34.040	5.234	35.340	-1.07%	-3.68%
			5785	5.193	34.003	5.255	35.317	-1.18%	-3.72%
			5825	5.232	33.928	5.296	35.271	-1.21%	-3.81%
			700	0.919	55.868	0.959	55.726	-4.17%	0.25%
			710	0.928	55.757	0.960	55.687	-3.33%	0.13%
			11/7/2016	750B	22.0	740	0.957	55.419	0.963
755	0.971	55.256				0.964	55.512	0.73%	-0.46%
820	0.984	54.051				0.969	55.258	1.55%	-2.18%
835	0.999	53.912				0.970	55.200	2.99%	-2.33%
850	1.014	53.778				0.988	55.154	2.63%	-2.49%
11/9/2016	835B	21.3	820	0.978	53.527	0.969	55.258	0.93%	-3.13%
			835	0.993	53.388	0.970	55.200	2.37%	-3.28%
			850	1.008	53.248	0.988	55.154	2.02%	-3.46%
11/15/2016	835B	20.7	820	0.984	54.475	0.969	55.258	1.55%	-1.42%
			835	0.999	54.345	0.970	55.200	2.99%	-1.55%
			850	1.014	54.215	0.988	55.154	2.63%	-1.70%
			1710	1.420	51.768	1.463	53.537	-2.94%	-3.30%
			1750	1.462	51.589	1.488	53.432	-1.75%	-3.45%
11/7/2016	1750B	22.7	1790	1.506	51.458	1.514	53.326	-0.53%	-3.50%
			1850	1.521	53.777	1.520	53.300	0.07%	0.89%
			1880	1.556	53.680	1.520	53.300	2.37%	0.71%
			1910	1.591	53.590	1.520	53.300	4.67%	0.54%
			2400	1.923	51.859	1.902	52.767	1.10%	-1.72%
11/9/2016	2450B	22.9	2450	1.988	51.680	1.950	52.700	1.95%	-1.94%
			2500	2.053	51.478	2.021	52.636	1.58%	-2.20%
			2400	1.899	52.400	1.902	52.767	-0.16%	-0.70%
12/19/2016	2450B	22.9	2450	1.964	52.185	1.950	52.700	0.72%	-0.98%
			2500	2.033	52.006	2.021	52.636	0.59%	-1.20%
			5240	5.489	47.948	5.346	48.960	2.67%	-2.07%
			5260	5.515	47.896	5.369	48.933	2.72%	-2.12%
			5280	5.546	47.883	5.393	48.906	2.84%	-2.09%
11/07/2016	5200B-5800B	22.2	5580	5.942	47.352	5.743	48.499	3.47%	-2.36%
			5600	5.968	47.329	5.766	48.471	3.50%	-2.36%
			5745	6.173	47.071	5.936	48.275	3.99%	-2.49%
			5765	6.203	47.059	5.959	48.248	4.09%	-2.46%
			5785	6.227	47.022	5.982	48.220	4.10%	-2.48%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 41 of 67

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-2  
System Verification Results**



System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR <sub>1g</sub> (W/kg)	1 W Target SAR <sub>1g</sub> (W/kg)	1 W Normalized SAR <sub>1g</sub> (W/kg)	Deviation <sub>1g</sub> (%)
I	750	HEAD	11/08/2016	20.5	20.7	0.200	1054	3288	1.600	8.220	8.000	-2.68%
H	835	HEAD	11/07/2016	20.1	20.1	0.200	4d047	3319	1.950	9.130	9.750	6.79%
A	1750	HEAD	11/07/2016	20.7	20.8	0.100	1150	3022	3.590	36.100	35.900	-0.55%
K	1900	HEAD	11/08/2016	23.7	22.4	0.100	5d149	7409	4.060	40.100	40.600	1.25%
I	2450	HEAD	11/10/2016	20.7	20.7	0.100	981	3288	5.310	52.800	53.100	0.57%
G	2450	HEAD	12/19/2016	23.4	21.8	0.100	981	3287	5.570	52.800	55.700	5.49%
J	5250	HEAD	11/07/2016	20.9	19.6	0.050	1237	7357	3.710	79.200	74.200	-6.31%
J	5600	HEAD	11/07/2016	20.9	19.6	0.050	1237	7357	3.840	83.300	76.800	-7.80%
J	5750	HEAD	11/07/2016	20.9	19.6	0.050	1237	7357	3.880	81.500	77.600	-4.79%
K	750	BODY	11/07/2016	22.5	21.1	0.200	1161	7409	1.700	8.430	8.500	0.83%
D	835	BODY	11/09/2016	22.6	21.5	0.200	4d133	3213	2.050	9.500	10.250	7.89%
D	835	BODY	11/12/2016	20.9	21.1	0.200	4d133	3213	2.040	9.500	10.200	7.37%
D	835	BODY	11/15/2016	22.6	20.9	0.200	4d133	3213	2.050	9.500	10.250	7.89%
C	1750	BODY	11/07/2016	24.1	22.3	0.100	1150	7410	3.650	36.500	36.500	0.00%
G	1900	BODY	11/09/2016	22.7	21.9	0.100	5d080	3287	3.860	39.100	38.600	-1.28%
E	2450	BODY	11/09/2016	22.1	21.9	0.100	797	7406	5.070	50.700	50.700	0.00%
E	2450	BODY	12/19/2016	22.7	22.3	0.100	797	7406	4.850	50.700	48.500	-4.34%
D	5250	BODY	11/07/2016	21.6	22.3	0.050	1191	3914	3.600	77.000	72.000	-6.49%
D	5600	BODY	11/07/2016	21.6	22.3	0.050	1191	3914	3.950	79.200	79.000	-0.25%
D	5750	BODY	11/07/2016	21.6	22.3	0.050	1191	3914	3.470	76.100	69.400	-8.80%



**Figure 10-1  
System Verification Setup Diagram**



**Figure 10-2  
System Verification Setup Photo**

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 42 of 67	

# 11 SAR DATA SUMMARY



## 11.1 Standalone Head SAR Data

**Table 11-1  
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.42	-0.01	Right	Cheek	00191	1	1:8.3	0.416	1.067	0.444	
836.60	190	GSM 850	GSM	32.7	32.42	0.06	Right	Tilt	00191	1	1:8.3	0.221	1.067	0.236	
836.60	190	GSM 850	GSM	32.7	32.42	0.04	Left	Cheek	00191	1	1:8.3	0.308	1.067	0.329	
836.60	190	GSM 850	GSM	32.7	32.42	0.01	Left	Tilt	00191	1	1:8.3	0.200	1.067	0.213	
836.60	190	GSM 850	GPRS	28.7	28.51	0.04	Right	Cheek	00191	4	1:2.076	0.444	1.045	0.464	A1
836.60	190	GSM 850	GPRS	28.7	28.51	0.04	Right	Tilt	00191	4	1:2.076	0.244	1.045	0.255	
836.60	190	GSM 850	GPRS	28.7	28.51	0.01	Left	Cheek	00191	4	1:2.076	0.371	1.045	0.388	
836.60	190	GSM 850	GPRS	28.7	28.51	0.07	Left	Tilt	00191	4	1:2.076	0.254	1.045	0.265	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-2  
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.7	30.48	-0.03	Right	Cheek	00167	1	1:8.3	0.172	1.052	0.181	
1880.00	661	GSM 1900	GSM	30.7	30.48	0.09	Right	Tilt	00167	1	1:8.3	0.097	1.052	0.102	
1880.00	661	GSM 1900	GSM	30.7	30.48	0.04	Left	Cheek	00167	1	1:8.3	0.210	1.052	0.221	
1880.00	661	GSM 1900	GSM	30.7	30.48	0.04	Left	Tilt	00167	1	1:8.3	0.113	1.052	0.119	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.01	Right	Cheek	00167	4	1:2.076	0.292	1.021	0.298	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.02	Right	Tilt	00167	4	1:2.076	0.142	1.021	0.145	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.05	Left	Cheek	00167	4	1:2.076	0.318	1.021	0.325	A2
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.08	Left	Tilt	00167	4	1:2.076	0.163	1.021	0.166	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 43 of 67

**Table 11-3  
UMTS 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.03	Right	Cheek	00167	1:1	0.484	1.014	0.491	A3
836.60	4183	UMTS 850	RMC	24.7	24.64	-0.02	Right	Tilt	00167	1:1	0.259	1.014	0.263	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.04	Left	Cheek	00167	1:1	0.402	1.014	0.408	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.04	Left	Tilt	00167	1:1	0.248	1.014	0.251	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-4  
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.03	Right	Cheek	00175	1:1	0.364	1.002	0.365	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.03	Right	Tilt	00175	1:1	0.312	1.002	0.313	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.00	Left	Cheek	00175	1:1	0.511	1.002	0.512	A4
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.02	Left	Tilt	00175	1:1	0.320	1.002	0.321	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-5  
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	-0.04	Right	Cheek	00167	1:1	0.545	1.005	0.548	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	-0.13	Right	Tilt	00167	1:1	0.280	1.005	0.281	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.09	Left	Cheek	00167	1:1	0.662	1.005	0.665	A5
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.02	Left	Tilt	00167	1:1	0.315	1.005	0.317	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 44 of 67

**Table 11-6  
LTE Band 12 Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.07	0	Right	Cheek	QPSK	1	25	00167	1:1	0.345	1.000	0.345	A6
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	0.01	1	Right	Cheek	QPSK	25	0	00167	1:1	0.269	1.019	0.274	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	0.03	0	Right	Tilt	QPSK	1	25	00167	1:1	0.201	1.000	0.201	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	0.03	1	Right	Tilt	QPSK	25	0	00167	1:1	0.161	1.019	0.164	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.11	0	Left	Cheek	QPSK	1	25	00167	1:1	0.286	1.000	0.286	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	-0.01	1	Left	Cheek	QPSK	25	0	00167	1:1	0.218	1.019	0.222	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	0.14	0	Left	Tilt	QPSK	1	25	00167	1:1	0.216	1.000	0.216	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	-0.02	1	Left	Tilt	QPSK	25	0	00167	1:1	0.158	1.019	0.161	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-7  
LTE Band 5 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.04	0	Right	Cheek	QPSK	1	25	00167	1:1	0.509	1.024	0.521	A7
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.05	1	Right	Cheek	QPSK	25	12	00167	1:1	0.384	1.014	0.389	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.15	0	Right	Tilt	QPSK	1	25	00167	1:1	0.290	1.024	0.297	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.06	1	Right	Tilt	QPSK	25	12	00167	1:1	0.212	1.014	0.215	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.08	0	Left	Cheek	QPSK	1	25	00167	1:1	0.408	1.024	0.418	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	0.00	1	Left	Cheek	QPSK	25	12	00167	1:1	0.318	1.014	0.322	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.02	0	Left	Tilt	QPSK	1	25	00167	1:1	0.251	1.024	0.257	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.05	1	Left	Tilt	QPSK	25	12	00167	1:1	0.194	1.014	0.197	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-8  
LTE Band 4 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	0.05	0	Right	Cheek	QPSK	1	50	00175	1:1	0.323	1.031	0.333	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.59	-0.01	1	Right	Cheek	QPSK	50	0	00175	1:1	0.258	1.025	0.264	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	0.09	0	Right	Tilt	QPSK	1	50	00175	1:1	0.275	1.031	0.284	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.59	-0.12	1	Right	Tilt	QPSK	50	0	00175	1:1	0.218	1.025	0.223	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	-0.01	0	Left	Cheek	QPSK	1	50	00175	1:1	0.422	1.031	0.435	A8
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.59	0.03	1	Left	Cheek	QPSK	50	0	00175	1:1	0.347	1.025	0.356	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	0.17	0	Left	Tilt	QPSK	1	50	00175	1:1	0.289	1.031	0.298	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.59	0.02	1	Left	Tilt	QPSK	50	0	00175	1:1	0.231	1.025	0.237	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 45 of 67	



**Table 11-9  
LTE Band 2 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.7	24.68	-0.20	0	Right	Cheek	QPSK	1	50	00167	1:1	0.490	1.004	0.492	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	0.04	1	Right	Cheek	QPSK	50	25	00167	1:1	0.383	1.033	0.396	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.7	24.68	0.19	0	Right	Tilt	QPSK	1	50	00167	1:1	0.302	1.004	0.303	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	0.01	1	Right	Tilt	QPSK	50	25	00167	1:1	0.217	1.033	0.224	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.7	24.68	-0.07	0	Left	Cheek	QPSK	1	50	00167	1:1	0.655	1.004	0.658	A9
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	0.01	1	Left	Cheek	QPSK	50	25	00167	1:1	0.497	1.033	0.513	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.7	24.68	-0.14	0	Left	Tilt	QPSK	1	50	00167	1:1	0.298	1.004	0.299	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	0.10	1	Left	Tilt	QPSK	50	25	00167	1:1	0.218	1.033	0.225	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-10  
DTS Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	17.0	16.25	0.10	Right	Cheek	2SJR0	1	99.9	0.421	0.344	1.189	1.001	0.409	
2462	11	802.11b	DSSS	22	17.0	16.25	-0.03	Right	Tilt	2SJR0	1	99.9	0.320	-	1.189	1.001	-	
2437	6	802.11b	DSSS	22	17.0	16.21	0.18	Left	Cheek	2SJR0	1	99.9	1.046	0.865	1.199	1.001	1.038	
2462	11	802.11b	DSSS	22	17.0	16.25	0.13	Left	Cheek	2SJR0	1	99.9	1.101	0.874	1.189	1.001	1.040	A10
2462	11	802.11b	DSSS	22	17.0	16.25	-0.15	Left	Tilt	2SJR0	1	99.9	0.784	0.566	1.189	1.001	0.674	
2462	11	802.11b	DSSS	22	17.0	16.25	0.04	Left	Cheek	2SJR0	1	99.9	0.996	0.824	1.189	1.001	0.981	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entry represents variability measurement

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 46 of 67

**Table 11-11  
NII Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)	(W/kg)	(W/kg)		
5280	56	802.11a	OFDM	20	16.0	15.54	0.17	Right	Cheek	2SJR0	6	99.2	0.758	-	1.112	1.008	-	
5280	56	802.11a	OFDM	20	16.0	15.54	0.19	Right	Tilt	2SJR0	6	99.2	0.848	0.405	1.112	1.008	0.454	
5280	56	802.11a	OFDM	20	16.0	15.54	0.12	Left	Cheek	2SJR0	6	99.2	1.633	0.849	1.112	1.008	0.952	
5320	64	802.11a	OFDM	20	15.0	14.81	0.12	Left	Cheek	2SJR0	6	99.2	1.354	0.693	1.045	1.008	0.730	
5280	56	802.11a	OFDM	20	16.0	15.54	-0.07	Left	Tilt	2SJR0	6	99.2	1.549	0.776	1.112	1.008	0.870	
5320	64	802.11a	OFDM	20	15.0	14.81	-0.19	Left	Tilt	2SJR0	6	99.2	1.235	0.578	1.045	1.008	0.609	
5280	56	802.11a	OFDM	20	16.0	15.54	0.14	Left	Cheek	2SJR0	6	99.2	1.682	0.839	1.112	1.008	0.940	
5580	116	802.11a	OFDM	20	15.0	14.65	0.13	Right	Cheek	2SJR0	6	99.2	0.788	-	1.084	1.008	-	
5580	116	802.11a	OFDM	20	15.0	14.65	0.14	Right	Tilt	2SJR0	6	99.2	0.842	-	1.084	1.008	-	
5500	100	802.11a	OFDM	20	15.0	14.62	-0.17	Left	Cheek	2SJR0	6	99.2	1.605	0.720	1.091	1.008	0.792	
5580	116	802.11a	OFDM	20	15.0	14.65	-0.17	Left	Cheek	2SJR0	6	99.2	1.572	0.795	1.084	1.008	0.869	
5580	116	802.11a	OFDM	20	15.0	14.65	0.00	Left	Tilt	2SJR0	6	99.2	1.442	0.699	1.084	1.008	0.764	
5785	157	802.11a	OFDM	20	16.0	15.80	-0.13	Right	Cheek	2SJR0	6	99.2	1.163	0.584	1.047	1.008	0.616	
5785	157	802.11a	OFDM	20	16.0	15.80	-0.16	Right	Tilt	2SJR0	6	99.2	0.494	-	1.047	1.008	-	
5785	157	802.11a	OFDM	20	16.0	15.80	-0.01	Left	Cheek	2SJR0	6	99.2	2.160	1.060	1.047	1.008	1.119	
5825	165	802.11a	OFDM	20	15.0	14.53	0.13	Left	Cheek	2SJR0	6	99.2	1.966	0.983	1.114	1.008	1.104	
5785	157	802.11a	OFDM	20	16.0	15.80	-0.09	Left	Tilt	2SJR0	6	99.2	1.954	0.896	1.047	1.008	0.946	
5825	165	802.11a	OFDM	20	15.0	14.53	0.13	Left	Tilt	2SJR0	6	99.2	1.922	0.865	1.114	1.008	0.971	
5785	157	802.11a	OFDM	20	16.0	15.80	0.17	Left	Cheek	2SJR0	6	99.2	2.721	1.130	1.047	1.008	1.193	A11
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram										



Note: Blue entries represent variability measurements

## 11.2 Standalone Body-Worn SAR Data

**Table 11-12  
GSM/UMTS Body-Worn SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.42	-0.09	10 mm	00191	1	1:8.3	back	0.547	1.067	0.584	
836.60	190	GSM 850	GPRS	28.7	28.51	0.10	10 mm	00191	4	1:2.076	back	0.612	1.045	0.640	A12
1880.00	661	GSM 1900	GSM	30.7	30.48	-0.05	10 mm	00167	1	1:8.3	back	0.384	1.052	0.404	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.05	10 mm	00167	4	1:2.076	back	0.595	1.021	0.607	A13
836.60	4183	UMTS 850	RMC	24.7	24.64	0.01	10 mm	00209	N/A	1:1	back	0.764	1.014	0.775	A14
1712.40	1312	UMTS 1750	RMC	24.7	24.54	-0.01	10 mm	00175	N/A	1:1	back	0.945	1.038	0.981	A15
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.05	10 mm	00175	N/A	1:1	back	0.922	1.002	0.924	
1752.60	1513	UMTS 1750	RMC	24.7	24.65	-0.01	10 mm	00175	N/A	1:1	back	0.917	1.012	0.928	
1852.40	9262	UMTS 1900	RMC	24.7	24.58	0.00	10 mm	00167	N/A	1:1	back	1.060	1.028	1.090	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.00	10 mm	00167	N/A	1:1	back	1.170	1.005	1.176	A16
1907.60	9538	UMTS 1900	RMC	24.7	24.58	0.04	10 mm	00167	N/A	1:1	back	1.090	1.028	1.121	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.00	10 mm	00167	N/A	1:1	back	1.040	1.005	1.045	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entry represents variability measurement

FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 47 of 67	

**Table 11-13  
LTE Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.02	0	00167	QPSK	1	25	10 mm	back	1:1	0.538	1.000	0.538	A17
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	-0.07	1	00167	QPSK	25	0	10 mm	back	1:1	0.410	1.019	0.418	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.13	0	00191	QPSK	1	25	10 mm	back	1:1	0.880	1.024	0.901	A18
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.07	1	00191	QPSK	25	12	10 mm	back	1:1	0.678	1.014	0.687	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.07	-0.01	1	00191	QPSK	50	0	10 mm	back	1:1	0.677	1.031	0.698	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.08	0	00191	QPSK	1	25	10 mm	back	1:1	0.855	1.024	0.876	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	0.18	0	00175	QPSK	1	50	10 mm	back	1:1	1.060	1.031	1.093	A19
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.59	0.11	1	00175	QPSK	50	0	10 mm	back	1:1	0.849	1.025	0.870	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.7	23.49	-0.12	1	00175	QPSK	100	0	10 mm	back	1:1	0.827	1.049	0.868	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.7	24.57	0.01	0	00175	QPSK	1	50	10 mm	back	1:1	1.010	1.031	1.041	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.7	24.55	0.02	0	00167	QPSK	1	50	10 mm	back	1:1	1.150	1.035	1.190	A20
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.7	24.68	0.07	0	00167	QPSK	1	50	10 mm	back	1:1	1.150	1.004	1.155	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.7	24.65	0.02	0	00167	QPSK	1	50	10 mm	back	1:1	1.120	1.012	1.133	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	-0.14	1	00167	QPSK	50	25	10 mm	back	1:1	0.894	1.033	0.924	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.7	23.51	0.11	1	00167	QPSK	50	0	10 mm	back	1:1	0.903	1.045	0.944	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.7	23.41	0.00	1	00167	QPSK	50	0	10 mm	back	1:1	0.858	1.070	0.918	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.52	-0.03	1	00167	QPSK	100	0	10 mm	back	1:1	0.907	1.043	0.946	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entries represent variability measurements

**Table 11-14  
DTS Body-Worn SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan (W/kg)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
2462	11	802.11b	DSSS	22	21.0	20.06	-0.01	10 mm	2SJR0	1	back	99.9	0.655	0.430	1.242	1.001	0.535	A21
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-15  
NII Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan (W/kg)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
5280	56	802.11a	OFDM	20	20.0	19.27	0.03	10 mm	2SJR0	6	back	99.2	0.622	0.149	1.183	1.008	0.178	A22
5580	116	802.11a	OFDM	20	19.0	18.42	0.14	10 mm	2SJR0	6	back	99.2	0.167	0.093	1.143	1.008	0.107	
5785	157	802.11a	OFDM	20	20.0	19.26	0.17	10 mm	2SJR0	6	back	99.2	0.289	0.141	1.186	1.008	0.169	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-16  
Bluetooth Body-Worn SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																
2441	39	Bluetooth	FHSS	11.0	10.58	0.15	10 mm	2SJR0	1	back	77.1	0.025	1.102	1.298	0.036	A24	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 48 of 67	





# 11.3 Standalone Hotspot SAR Data

**Table 11-17  
GPRS/UMTS Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	28.7	28.51	0.10	10 mm	00191	4	1:2.076	back	0.612	1.045	0.640	A12
836.60	190	GSM 850	GPRS	28.7	28.51	0.08	10 mm	00191	4	1:2.076	front	0.481	1.045	0.503	
836.60	190	GSM 850	GPRS	28.7	28.51	0.05	10 mm	00191	4	1:2.076	bottom	0.389	1.045	0.407	
836.60	190	GSM 850	GPRS	28.7	28.51	0.00	10 mm	00191	4	1:2.076	right	0.455	1.045	0.475	
836.60	190	GSM 850	GPRS	28.7	28.51	0.06	10 mm	00191	4	1:2.076	left	0.294	1.045	0.307	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.05	10 mm	00167	4	1:2.076	back	0.595	1.021	0.607	A13
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.02	10 mm	00167	4	1:2.076	front	0.579	1.021	0.591	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.10	10 mm	00167	4	1:2.076	bottom	0.338	1.021	0.345	
1880.00	661	GSM 1900	GPRS	25.7	25.61	0.07	10 mm	00167	4	1:2.076	left	0.345	1.021	0.352	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.01	10 mm	00209	N/A	1:1	back	0.764	1.014	0.775	A14
836.60	4183	UMTS 850	RMC	24.7	24.64	-0.01	10 mm	00209	N/A	1:1	front	0.532	1.014	0.539	
836.60	4183	UMTS 850	RMC	24.7	24.64	-0.02	10 mm	00209	N/A	1:1	bottom	0.453	1.014	0.459	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.04	10 mm	00209	N/A	1:1	right	0.456	1.014	0.462	
836.60	4183	UMTS 850	RMC	24.7	24.64	0.03	10 mm	00209	N/A	1:1	left	0.365	1.014	0.370	
1712.40	1312	UMTS 1750	RMC	24.7	24.54	-0.01	10 mm	00175	N/A	1:1	back	0.945	1.038	0.981	A15
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.05	10 mm	00175	N/A	1:1	back	0.922	1.002	0.924	
1752.60	1513	UMTS 1750	RMC	24.7	24.65	-0.01	10 mm	00175	N/A	1:1	back	0.917	1.012	0.928	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.15	10 mm	00175	N/A	1:1	front	0.731	1.002	0.732	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	-0.04	10 mm	00175	N/A	1:1	bottom	0.476	1.002	0.477	
1732.40	1412	UMTS 1750	RMC	24.7	24.69	0.08	10 mm	00175	N/A	1:1	left	0.389	1.002	0.390	
1852.40	9262	UMTS 1900	RMC	24.7	24.58	0.00	10 mm	00167	N/A	1:1	back	1.060	1.028	1.090	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.00	10 mm	00167	N/A	1:1	back	1.170	1.005	1.176	A16
1907.60	9538	UMTS 1900	RMC	24.7	24.58	0.04	10 mm	00167	N/A	1:1	back	1.090	1.028	1.121	
1852.40	9262	UMTS 1900	RMC	24.7	24.58	0.09	10 mm	00167	N/A	1:1	front	0.992	1.028	1.020	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	-0.01	10 mm	00167	N/A	1:1	front	1.170	1.005	1.176	
1907.60	9538	UMTS 1900	RMC	24.7	24.58	-0.12	10 mm	00167	N/A	1:1	front	1.040	1.028	1.069	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.04	10 mm	00167	N/A	1:1	bottom	0.708	1.005	0.712	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	-0.01	10 mm	00167	N/A	1:1	left	0.710	1.005	0.714	
1880.00	9400	UMTS 1900	RMC	24.7	24.68	0.00	10 mm	00167	N/A	1:1	back	1.040	1.005	1.045	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak							Body 1.6 W/kg (mW/g) averaged over 1 gram								
Uncontrolled Exposure/General Population															

Note: Blue entry represents variability measurement

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 49 of 67



**Table 11-18  
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.02	0	00167	QPSK	1	25	10 mm	back	1:1	0.538	1.000	0.538	A17
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	-0.07	1	00167	QPSK	25	0	10 mm	back	1:1	0.410	1.019	0.418	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	0.03	0	00167	QPSK	1	25	10 mm	front	1:1	0.380	1.000	0.380	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	0.07	1	00167	QPSK	25	0	10 mm	front	1:1	0.288	1.019	0.293	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.08	0	00167	QPSK	1	25	10 mm	bottom	1:1	0.239	1.000	0.239	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	0.01	1	00167	QPSK	25	0	10 mm	bottom	1:1	0.176	1.019	0.179	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.03	0	00167	QPSK	1	25	10 mm	right	1:1	0.346	1.000	0.346	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	0.00	1	00167	QPSK	25	0	10 mm	right	1:1	0.281	1.019	0.286	
707.50	23095	Mid	LTE Band 12	10	25.2	25.20	-0.02	0	00167	QPSK	1	25	10 mm	left	1:1	0.225	1.000	0.225	
707.50	23095	Mid	LTE Band 12	10	24.2	24.12	-0.15	1	00167	QPSK	25	0	10 mm	left	1:1	0.173	1.019	0.176	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-19  
LTE Band 5 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.13	0	00191	QPSK	1	25	10 mm	back	1:1	0.880	1.024	0.901	A18
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.07	1	00191	QPSK	25	12	10 mm	back	1:1	0.678	1.014	0.687	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.07	-0.01	1	00191	QPSK	50	0	10 mm	back	1:1	0.677	1.031	0.698	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.01	0	00191	QPSK	1	25	10 mm	front	1:1	0.532	1.024	0.545	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	0.05	1	00191	QPSK	25	12	10 mm	front	1:1	0.423	1.014	0.429	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.10	0	00191	QPSK	1	25	10 mm	bottom	1:1	0.450	1.024	0.461	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	-0.05	1	00191	QPSK	25	12	10 mm	bottom	1:1	0.354	1.014	0.359	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	-0.13	0	00191	QPSK	1	25	10 mm	right	1:1	0.411	1.024	0.421	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	0.04	1	00191	QPSK	25	12	10 mm	right	1:1	0.323	1.014	0.328	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.05	0	00191	QPSK	1	25	10 mm	left	1:1	0.333	1.024	0.341	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.14	0.06	1	00191	QPSK	25	12	10 mm	left	1:1	0.267	1.014	0.271	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.10	0.08	0	00191	QPSK	1	25	10 mm	back	1:1	0.855	1.024	0.876	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 50 of 67

**Table 11-20  
LTE Band 4 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.7	24.57	0.18	0	00175	QPSK	1	50	10 mm	back	1:1	1.060	1.031	1.093	A19
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.7	23.59	0.11	1	00175	QPSK	50	0	10 mm	back	1:1	0.849	1.025	0.870	
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.7	23.49	-0.12	1	00175	QPSK	100	0	10 mm	back	1:1	0.827	1.049	0.868	
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.7	24.57	0.16	0	00175	QPSK	1	50	10 mm	front	1:1	0.766	1.031	0.790	
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.7	23.59	0.06	1	00175	QPSK	50	0	10 mm	front	1:1	0.614	1.025	0.629	
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.7	24.57	-0.04	0	00175	QPSK	1	50	10 mm	bottom	1:1	0.452	1.031	0.466	
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.7	23.59	-0.06	1	00175	QPSK	50	0	10 mm	bottom	1:1	0.325	1.025	0.333	
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.7	24.57	0.00	0	00175	QPSK	1	50	10 mm	left	1:1	0.391	1.031	0.403	
1732.50	20175	Md	LTE Band 4 (AWS)	20	23.7	23.59	0.01	1	00175	QPSK	50	0	10 mm	left	1:1	0.279	1.025	0.286	
1732.50	20175	Md	LTE Band 4 (AWS)	20	24.7	24.57	0.01	0	00175	QPSK	1	50	10 mm	back	1:1	1.010	1.031	1.041	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population												Body 1.6 W/kg (mW/g) averaged over 1 gram							



Note: Blue entry represents variability measurement

**Table 11-21  
LTE Band 2 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.7	24.55	0.02	0	00167	QPSK	1	50	10 mm	back	1:1	1.150	1.035	1.190	A20
1880.00	18900	Md	LTE Band 2 (PCS)	20	24.7	24.68	0.07	0	00167	QPSK	1	50	10 mm	back	1:1	1.150	1.004	1.155	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.7	24.65	0.02	0	00167	QPSK	1	50	10 mm	back	1:1	1.120	1.012	1.133	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	-0.14	1	00167	QPSK	50	25	10 mm	back	1:1	0.894	1.033	0.924	
1880.00	18900	Md	LTE Band 2 (PCS)	20	23.7	23.51	0.11	1	00167	QPSK	50	0	10 mm	back	1:1	0.903	1.045	0.944	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.7	23.41	0.00	1	00167	QPSK	50	0	10 mm	back	1:1	0.858	1.070	0.918	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.52	-0.03	1	00167	QPSK	100	0	10 mm	back	1:1	0.907	1.043	0.946	
1880.00	18900	Md	LTE Band 2 (PCS)	20	24.7	24.68	0.02	0	00167	QPSK	1	50	10 mm	front	1:1	0.790	1.004	0.793	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	-0.09	1	00167	QPSK	50	25	10 mm	front	1:1	0.741	1.033	0.765	
1880.00	18900	Md	LTE Band 2 (PCS)	20	24.7	24.68	0.13	0	00167	QPSK	1	50	10 mm	bottom	1:1	0.619	1.004	0.621	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	-0.10	1	00167	QPSK	50	25	10 mm	bottom	1:1	0.441	1.033	0.456	
1880.00	18900	Md	LTE Band 2 (PCS)	20	24.7	24.68	0.15	0	00167	QPSK	1	50	10 mm	left	1:1	0.616	1.004	0.618	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.7	23.56	-0.07	1	00167	QPSK	50	25	10 mm	left	1:1	0.439	1.033	0.453	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population												Body 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-22  
WLAN Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)				
2462	11	802.11b	DSSS	22	21.0	20.06	-0.01	10 mm	2SJR0	1	back	99.9	0.655	0.430	1.242	1.001	0.535	A21
2462	11	802.11b	DSSS	22	21.0	20.06	0.00	10 mm	2SJR0	1	front	99.9	0.388	0.218	1.242	1.001	0.271	
2462	11	802.11b	DSSS	22	21.0	20.06	0.09	10 mm	2SJR0	1	top	99.9	0.241	-	1.242	1.001	-	
2462	11	802.11b	DSSS	22	21.0	20.06	0.05	10 mm	2SJR0	1	right	99.9	0.330	-	1.242	1.001	-	
5785	157	802.11a	OFDM	20	20.0	19.26	0.17	10 mm	2SJR0	6	back	99.2	0.289	-	1.186	1.008	-	
5785	157	802.11a	OFDM	20	20.0	19.26	-0.16	10 mm	2SJR0	6	front	99.2	0.195	-	1.186	1.008	-	
5785	157	802.11a	OFDM	20	20.0	19.26	0.16	10 mm	2SJR0	6	top	99.2	0.515	-	1.186	1.008	-	
5785	157	802.11a	OFDM	20	20.0	19.26	-0.15	10 mm	2SJR0	6	right	99.2	0.657	0.328	1.186	1.008	0.392	A23
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population												Body 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 51 of 67	

## 11.4 SAR Test Notes

### General Notes:



1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was  $\leq 1.2$  W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

### GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

### UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 52 of 67

**LTE Notes:**



1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

**WLAN Notes:**

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. When the maximum reported 1g averaged SAR is  $\leq 0.8$  W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

**Bluetooth Notes:**

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.5 for the time-domain plot and calculation for the duty factor of the device.

FCC ID: ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset	Page 53 of 67

# 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

## 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

## 12.2 Simultaneous Transmission Procedures



This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is  $\leq 1.6$  W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g SAR.

## 12.3 Head SAR Simultaneous Transmission Analysis

(\*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN head SAR result was used for simultaneous transmission analysis.

**Table 12-1**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.444	0.409	0.853	N/A	Head SAR	Right Cheek	0.464	0.409	0.873	N/A
	Right Tilt	0.236	1.040*	1.276	N/A		Right Tilt	0.255	1.040*	1.295	N/A
	Left Cheek	0.329	1.040	1.369	N/A		Left Cheek	0.388	1.040	1.428	N/A
	Left Tilt	0.213	0.674	0.887	N/A		Left Tilt	0.265	0.674	0.939	N/A
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.181	0.409	0.590	N/A	Head SAR	Right Cheek	0.298	0.409	0.707	N/A
	Right Tilt	0.102	1.040*	1.142	N/A		Right Tilt	0.145	1.040*	1.185	N/A
	Left Cheek	0.221	1.040	1.261	N/A		Left Cheek	0.325	1.040	1.365	N/A
	Left Tilt	0.119	0.674	0.793	N/A		Left Tilt	0.166	0.674	0.840	N/A
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.491	0.409	0.900	N/A	Head SAR	Right Cheek	0.365	0.409	0.774	N/A
	Right Tilt	0.263	1.040*	1.303	N/A		Right Tilt	0.313	1.040*	1.353	N/A
	Left Cheek	0.408	1.040	1.448	N/A		Left Cheek	0.512	1.040	1.552	N/A
	Left Tilt	0.251	0.674	0.925	N/A		Left Tilt	0.321	0.674	0.995	N/A
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.548	0.409	0.957	N/A	Head SAR	Right Cheek	0.345	0.409	0.754	N/A
	Right Tilt	0.281	1.040*	1.321	N/A		Right Tilt	0.201	1.040*	1.241	N/A
	Left Cheek	0.665	1.040	See Note 1	0.03		Left Cheek	0.286	1.040	1.326	N/A
	Left Tilt	0.317	0.674	0.991	N/A		Left Tilt	0.216	0.674	0.890	N/A

FCC ID: ZNFTP260	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 54 of 67



Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.521	0.409	0.930	N/A	Head SAR	Right Cheek	0.333	0.409	0.742	N/A
	Right Tilt	0.297	1.040*	1.337	N/A		Right Tilt	0.284	1.040*	1.324	N/A
	Left Cheek	0.418	1.040	1.458	N/A		Left Cheek	0.435	1.040	1.475	N/A
	Left Tilt	0.257	0.674	0.931	N/A		Left Tilt	0.298	0.674	0.972	N/A

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.492	0.409	0.901	N/A
	Right Tilt	0.303	1.040*	1.343	N/A
	Left Cheek	0.658	1.040	See Note 1	0.03
	Left Tilt	0.299	0.674	0.973	N/A

**Table 12-2  
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.444	0.616	1.060	N/A	Head SAR	Right Cheek	0.464	0.616	1.080	N/A
	Right Tilt	0.236	0.454	0.690	N/A		Right Tilt	0.255	0.454	0.709	N/A
	Left Cheek	0.329	1.193	1.522	N/A		Left Cheek	0.388	1.193	1.581	N/A
	Left Tilt	0.213	0.971	1.184	N/A		Left Tilt	0.265	0.971	1.236	N/A
Head SAR	Right Cheek	0.181	0.616	0.797	N/A	Head SAR	Right Cheek	0.298	0.616	0.914	N/A
	Right Tilt	0.102	0.454	0.556	N/A		Right Tilt	0.145	0.454	0.599	N/A
	Left Cheek	0.221	1.193	1.414	N/A		Left Cheek	0.325	1.193	1.518	N/A
	Left Tilt	0.119	0.971	1.090	N/A		Left Tilt	0.166	0.971	1.137	N/A
Head SAR	Right Cheek	0.491	0.616	1.107	N/A	Head SAR	Right Cheek	0.365	0.616	0.981	N/A
	Right Tilt	0.263	0.454	0.717	N/A		Right Tilt	0.313	0.454	0.767	N/A
	Left Cheek	0.408	1.193	See Note 1	0.03		Left Cheek	0.512	1.193	See Note 1	0.03
	Left Tilt	0.251	0.971	1.222	N/A		Left Tilt	0.321	0.971	1.292	N/A
Head SAR	Right Cheek	0.548	0.616	1.164	N/A	Head SAR	Right Cheek	0.345	0.616	0.961	N/A
	Right Tilt	0.281	0.454	0.735	N/A		Right Tilt	0.201	0.454	0.655	N/A
	Left Cheek	0.665	1.193	See Note 1	0.03		Left Cheek	0.286	1.193	1.479	N/A
	Left Tilt	0.317	0.971	1.288	N/A		Left Tilt	0.216	0.971	1.187	N/A
Head SAR	Right Cheek	0.521	0.616	1.137	N/A	Head SAR	Right Cheek	0.333	0.616	0.949	N/A
	Right Tilt	0.297	0.454	0.751	N/A		Right Tilt	0.284	0.454	0.738	N/A
	Left Cheek	0.418	1.193	See Note 1	0.03		Left Cheek	0.435	1.193	See Note 1	0.03
	Left Tilt	0.257	0.971	1.228	N/A		Left Tilt	0.298	0.971	1.269	N/A

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.492	0.616	1.108	N/A
	Right Tilt	0.303	0.454	0.757	N/A
	Left Cheek	0.658	1.193	See Note 1	0.03
	Left Tilt	0.299	0.971	1.270	N/A

<b>FCC ID:</b> ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 55 of 67	

## 12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-3**  
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)



Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)	SPLSR
Body-Worn	GSM/GPRS 850	0.640	0.535	1.175	N/A
	GSM/GPRS 1900	0.607	0.535	1.142	N/A
	UMTS 850	0.775	0.535	1.310	N/A
	UMTS 1750	0.981	0.535	<b>1.516</b>	N/A
	UMTS 1900	1.176	0.535	See Note 1	0.02
	LTE Band 12	0.538	0.535	1.073	N/A
	LTE Band 5 (Cell)	0.901	0.535	1.436	N/A
	LTE Band 4 (AWS)	1.093	0.535	See Note 1	0.02
	LTE Band 2 (PCS)	1.190	0.535	See Note 1	0.02

**Table 12-4**  
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	$\Sigma$ SAR (W/kg)
Body-Worn	GSM/GPRS 850	0.640	0.178	0.818
	GSM/GPRS 1900	0.607	0.178	0.785
	UMTS 850	0.775	0.178	0.953
	UMTS 1750	0.981	0.178	<b>1.159</b>
	UMTS 1900	1.176	0.178	1.354
	LTE Band 12	0.538	0.178	0.716
	LTE Band 5 (Cell)	0.901	0.178	1.079
	LTE Band 4 (AWS)	1.093	0.178	1.271
	LTE Band 2 (PCS)	1.190	0.178	1.368

**Table 12-5**  
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	$\Sigma$ SAR (W/kg)
Body-Worn	GSM/GPRS 850	0.640	0.036	0.676
	GSM/GPRS 1900	0.607	0.036	0.643
	UMTS 850	0.775	0.036	0.811
	UMTS 1750	0.981	0.036	<b>1.017</b>
	UMTS 1900	1.176	0.036	1.212
	LTE Band 12	0.538	0.036	0.574
	LTE Band 5 (Cell)	0.901	0.036	0.937
	LTE Band 4 (AWS)	1.093	0.036	1.129
	LTE Band 2 (PCS)	1.190	0.036	1.226

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>			<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 56 of 67	



**Table 12-6**  
**Simultaneous Transmission Scenario with 5 GHz WLAN and Bluetooth (Body-Worn at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM/GPRS 850	0.640	0.178	0.036	0.854
	GSM/GPRS 1900	0.607	0.178	0.036	0.821
	UMTS 850	0.775	0.178	0.036	0.989
	UMTS 1750	0.981	0.178	0.036	1.195
	UMTS 1900	1.176	0.178	0.036	1.390
	LTE Band 12	0.538	0.178	0.036	0.752
	LTE Band 5 (Cell)	0.901	0.178	0.036	1.115
	LTE Band 4 (AWS)	1.093	0.178	0.036	1.307
	LTE Band 2 (PCS)	1.190	0.178	0.036	<b>1.404</b>



## 12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-“).

(\*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN hotspot SAR result was used for simultaneous transmission analysis.

**Table 12-7**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)**

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Hotspot SAR	Back	0.640	0.535	1.175	N/A	Hotspot SAR	Back	0.607	0.535	1.142	N/A
	Front	0.503	0.271	0.774	N/A		Front	0.591	0.271	0.862	N/A
	Top	-	0.535*	0.535	N/A		Top	-	0.535*	0.535	N/A
	Bottom	0.407	-	0.407	N/A		Bottom	0.345	-	0.345	N/A
	Right	0.475	0.535*	1.010	N/A		Right	-	0.535*	0.535	N/A
	Left	0.307	-	0.307	N/A		Left	0.352	-	0.352	N/A
Hotspot SAR	Back	0.775	0.535	1.310	N/A	Hotspot SAR	Back	0.981	0.535	1.516	N/A
	Front	0.539	0.271	0.810	N/A		Front	0.732	0.271	1.003	N/A
	Top	-	0.535*	0.535	N/A		Top	-	0.535*	0.535	N/A
	Bottom	0.459	-	0.459	N/A		Bottom	0.477	-	0.477	N/A
	Right	0.462	0.535*	0.997	N/A		Right	-	0.535*	0.535	N/A
	Left	0.370	-	0.370	N/A		Left	0.390	-	0.390	N/A
Hotspot SAR	Back	1.176	0.535	See Note 1	0.02	Hotspot SAR	Back	0.538	0.535	1.073	N/A
	Front	1.176	0.271	1.447	N/A		Front	0.380	0.271	0.651	N/A
	Top	-	0.535*	0.535	N/A		Top	-	0.535*	0.535	N/A
	Bottom	0.712	-	0.712	N/A		Bottom	0.239	-	0.239	N/A
	Right	-	0.535*	0.535	N/A		Right	0.346	0.535*	0.881	N/A
	Left	0.714	-	0.714	N/A		Left	0.225	-	0.225	N/A

FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 57 of 67

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Hotspot SAR	Back	0.901	0.535	1.436	N/A	Hotspot SAR	Back	1.093	0.535	See Note 1	0.02
	Front	0.545	0.271	0.816	N/A		Front	0.790	0.271	1.061	N/A
	Top	-	0.535*	0.535	N/A		Top	-	0.535*	0.535	N/A
	Bottom	0.461	-	0.461	N/A		Bottom	0.466	-	0.466	N/A
	Right	0.421	0.535*	0.956	N/A		Right	-	0.535*	0.535	N/A
	Left	0.341	-	0.341	N/A		Left	0.403	-	0.403	N/A



Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Hotspot SAR	Back	1.190	0.535	See Note 1	0.02
	Front	0.793	0.271	1.064	N/A
	Top	-	0.535*	0.535	N/A
	Bottom	0.621	-	0.621	N/A
	Right	-	0.535*	0.535	N/A
	Left	0.618	-	0.618	N/A

**Table 12-8  
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.640	0.392	1.032
	GPRS 1900	0.607	0.392	0.999
	UMTS 850	0.775	0.392	1.167
	UMTS 1750	0.981	0.392	1.373
	UMTS 1900	1.176	0.392	1.568
	LTE Band 12	0.538	0.392	0.930
	LTE Band 5 (Cell)	0.901	0.392	1.293
	LTE Band 4 (AWS)	1.093	0.392	1.485
	LTE Band 2 (PCS)	1.190	0.392	1.582

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.6 for detailed SPLS ratio analysis.

FCC ID: ZNFTP260		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 58 of 67

## 12.6 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is  $\leq 0.04$  for 1g simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Head: Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

$$\text{Body: Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$



### 12.6.1 Left Cheek SPLSR Evaluation and Analysis

**Table 12-9**  
**Peak SAR Locations for Left Cheek**


Mode/Band	x (mm)	y (mm)	z (mm)	Reported SAR (W/kg)
2.4 GHz WLAN	8.58	330.38	-171.01	1.04
5 GHz WLAN	2.73	325.66	-173.07	1.193
UMTS 850	50.69	277.79	-172.82	0.408
UMTS 1750	46.30	254.65	-171.83	0.512
UMTS 1900	44.66	252.14	-172.99	0.665
LTE Band 5 (Cell)	51.69	280.66	-172.63	0.418
LTE Band 4 (AWS)	47.48	255.74	-171.81	0.435
LTE Band 2 (PCS)	44.02	254.21	-173.30	0.658



**Table 12-10**  
**Left Cheek SAR to Peak Location Separation Ratio Calculations**

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D <sub>a-b</sub>	(a+b) <sup>1.5</sup> /D <sub>a-b</sub>	
2.4 GHz WLAN	UMTS 1900	1.04	0.665	1.705	86.18	0.03	1
2.4 GHz WLAN	LTE Band 2 (PCS)	1.04	0.658	1.698	84.04	0.03	2
5 GHz WLAN	UMTS 850	1.193	0.408	1.601	67.76	0.03	3
5 GHz WLAN	UMTS 1750	1.193	0.512	1.705	83.32	0.03	4
5 GHz WLAN	UMTS 1900	1.193	0.665	1.858	84.64	0.03	5
5 GHz WLAN	LTE Band 5 (Cell)	1.193	0.418	1.611	66.50	0.03	6
5 GHz WLAN	LTE Band 4 (AWS)	1.193	0.435	1.628	83.02	0.03	7
5 GHz WLAN	LTE Band 2 (PCS)	1.193	0.658	1.851	82.52	0.03	8

FCC ID: ZNFTP260			SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 59 of 67		

**Table 12-11**  
**Left Cheek SAR to Peak Location Separation Ratio Plots**



<b>FCC ID:</b> ZNFTP260	 <small>PCTEST ENGINEERING LABORATORY, INC.</small>	<b>SAR EVALUATION REPORT</b>	 <b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 60 of 67

## 12.6.2 Back Side SPLSR Evaluation and Analysis


**Table 12-12**  
**Peak SAR Locations for Body Back Side**

Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
2.4 GHz WLAN	-38.60	66.00	0.535
UMTS 1900	-26.00	-52.50	1.176
LTE Band 4 (AWS)	-13.98	-41.98	1.093
LTE Band 2 (PCS)	-24.50	-43.50	1.19

**Table 12-13**  
**Back Side SAR to Peak Location Separation Ratio Calculations**

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D <sub>a-b</sub>	$(a+b)^{1.5}/D_{a-b}$	
2.4 GHz WLAN	UMTS 1900	0.535	1.176	1.711	119.17	0.02	1
2.4 GHz WLAN	LTE Band 4 (AWS)	0.535	1.093	1.628	110.75	0.02	2
2.4 GHz WLAN	LTE Band 2 (PCS)	0.535	1.19	1.725	110.40	0.02	3

**Table 12-14**  
**Back Side SAR to Peak Location Separation Ratio Plots**



## 12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: ZNFTP260	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 61 of 67

# 13 SAR MEASUREMENT VARIABILITY

## 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 4) Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg

**Table 13-1  
Head SAR Measurement Variability Results**



HEAD VARIABILITY RESULTS														
Band	FREQUENCY		Mode/Band	Service	Side	Test Position	Data Rate (Mbps)	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
2450	2462.00	11	802.11b, 22 MHz Bandwidth	DSSS	Left	Cheek	1	0.874	0.824	1.06	N/A	N/A	N/A	N/A
5250	5280.00	56	802.11a, 20 MHz Bandwidth	OFDM	Left	Cheek	6	0.849	0.839	1.01	N/A	N/A	N/A	N/A
5750	5785.00	157	802.11a, 20 MHz Bandwidth	OFDM	Left	Cheek	6	1.060	1.130	1.07	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 13-2  
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1880.00	9400	UMTS 1900	RMC	back	10 mm	1.170	1.040	1.13	N/A	N/A	N/A	N/A
835	836.50	20525	LTE Band 5 (Cell), 10 MHz Bandwidth	QPSK, 1 RB, 25 RB Offset	back	10 mm	0.880	0.855	1.03	N/A	N/A	N/A	N/A
1750	1732.50	20175	LTE Band 4 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	back	10 mm	1.060	1.010	1.05	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

## 13.2 Measurement Uncertainty



The measured SAR was  $< 1.5$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFTP260		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 62 of 67	

# 14 EQUIPMENT LIST



Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/2/2016	Annual	3/2/2017	JP38020182
Agilent	8753ES	S-Parameter Network Analyzer	3/3/2016	Annual	3/3/2017	US39170122
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/19/2016	Annual	8/19/2017	MY40003841
Agilent	E4432B	ESG-D Series Signal Generator	3/5/2016	Annual	3/5/2017	US40053896
Agilent	E4438C	ESG Vector Signal Generator	2/27/2016	Annual	2/27/2017	MY45091346
Agilent	E5515C	Wireless Communications Test Set	5/16/2015	Biennial	5/16/2017	GB43304447
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	10/5/2016	Annual	10/5/2017	GB42320325
Agilent	E5515C	Wireless Communications Test Set	11/30/2015	Biennial	11/30/2017	GB42361078
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/2/2016	Annual	3/2/2017	MY45470194
Agilent	N4010A	Wireless Connectivity Test Set	CBT	N/A	CBT	GB46170464
Agilent	N5182A	MXG Vector Signal Generator	2/27/2016	Annual	2/27/2017	MY47420651
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA24106A	USB Power Sensor	2/27/2016	Annual	2/27/2017	1344559
Anritsu	MA24106A	USB Power Sensor	2/27/2016	Annual	2/27/2017	1349503
Anritsu	MA2411B	Pulse Power Sensor	8/18/2016	Annual	8/18/2017	1126066
Anritsu	MA2411B	Pulse Power Sensor	8/18/2016	Annual	8/18/2017	1207470
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	5318
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	2400
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2496A	Power Meter	3/5/2016	Annual	3/5/2017	1351001
Anritsu	MT8820C	Radio Communication Analyzer	9/15/2016	Annual	9/15/2017	6200901190
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Digital Thermometer	3/15/2015	Biennial	3/15/2017	150194929
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261728
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053081
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6°CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	3/25/2016	Annual	3/25/2017	128633
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
SPEAG	D1750V2	1750 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	1150
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Annual	7/8/2017	50800
SPEAG	D1900V2	1900 MHz SAR Dipole	7/15/2016	Annual	7/15/2017	58149
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	981
SPEAG	D2450V2	2450 MHz SAR Dipole	9/13/2016	Annual	9/13/2017	797
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/2/2016	Annual	8/2/2017	1237
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/21/2016	Annual	9/21/2017	1191
SPEAG	D750V3	750 MHz Dipole	3/16/2016	Annual	3/16/2017	1054
SPEAG	D750V3	750 MHz SAR Dipole	7/13/2016	Annual	7/13/2017	1161
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Annual	7/13/2017	46047
SPEAG	D835V2	835 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	46133
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2016	Annual	1/15/2017	1466
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2016	Annual	2/18/2017	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/19/2016	Annual	2/19/2017	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/14/2016	Annual	3/14/2017	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2016	Annual	4/14/2017	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/11/2016	Annual	5/11/2017	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/12/2016	Annual	7/12/2017	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/22/2016	Annual	8/22/2017	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/14/2016	Annual	9/14/2017	1408
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/13/2016	Annual	9/13/2017	1091
SPEAG	ES3DV2	SAR Probe	7/19/2016	Annual	7/19/2017	3022
SPEAG	ES3DV3	SAR Probe	2/19/2016	Annual	2/19/2017	3213
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3319
SPEAG	ES3DV3	SAR Probe	8/24/2016	Annual	8/24/2017	3288
SPEAG	ES3DV3	SAR Probe	9/19/2016	Annual	9/19/2017	3287
SPEAG	EX3DV4	SAR Probe	2/22/2016	Annual	2/22/2017	3914
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7357
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7406
SPEAG	EX3DV4	SAR Probe	5/17/2016	Annual	5/17/2017	7409
SPEAG	EX3DV4	SAR Probe	7/25/2016	Annual	7/25/2017	7410

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFTP260		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1611071720-R5.ZNF	Test Dates: 11/07/16 – 12/19/16	DUT Type: Portable Handset		Page 63 of 67

# 15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> 1gm	c <sub>i</sub> 10 gms	1gm u <sub>i</sub> (± %)	10gms u <sub>i</sub> (± %)	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
<b>Test Sample Related</b>								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
<b>Phantom &amp; Tissue Parameters</b>								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
<b>Combined Standard Uncertainty (k=1)</b>	RSS					11.5	11.3	60
<b>Expanded Uncertainty</b> (95% CONFIDENCELEVEL)	k=2					23.0	22.6	

FCC ID: ZNFTP260	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 64 of 67





# 16 CONCLUSION

## 16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



<b>FCC ID:</b> ZNFTP260		<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset		Page 65 of 67

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

<b>FCC ID:</b> ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 66 of 67

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

<b>FCC ID:</b> ZNFTP260	 <b>SAR EVALUATION REPORT</b> 		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1611071720-R5.ZNF	<b>Test Dates:</b> 11/07/16 – 12/19/16	<b>DUT Type:</b> Portable Handset	Page 67 of 67

## APPENDIX A: SAR TEST DATA

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00191**

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.076  
Medium: 835 Head; Medium parameters used (interpolated):  
 $f = 836.6$  MHz;  $\sigma = 0.928$  S/m;  $\epsilon_r = 42.437$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section

Test Date: 11-07-2016; Ambient Temp: 20.1°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(6.16, 6.16, 6.16); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Right Head, Cheek, Mid.ch, 4 Tx slots**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.85 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.538 W/kg

**SAR(1 g) = 0.444 W/kg**



0 dB = 0.485 W/kg = -3.14 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076  
Medium: 1900 Head; Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.388 \text{ S/m}$ ;  $\epsilon_r = 39.899$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-08-2016; Ambient Temp: 23.7°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(7.69, 7.69, 7.69); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Left Head, Cheek, Mid.ch, 4 Tx slots**

**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 15.67 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.486 W/kg  
**SAR(1 g) = 0.318 W/kg**



0 dB = 0.424 W/kg = -3.73 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium: 835 Head; Medium parameters used (interpolated):  
 $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.928 \text{ S/m}$ ;  $\epsilon_r = 42.437$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 11-07-2016; Ambient Temp: 20.1°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(6.16, 6.16, 6.16); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Right Head, Cheek, Mid.ch**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.05 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.612 W/kg

**SAR(1 g) = 0.484 W/kg**



0 dB = 0.536 W/kg = -2.71 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00175**

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1  
Medium: 1750 Head; Medium parameters used (interpolated):  
 $f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.352 \text{ S/m}$ ;  $\epsilon_r = 39.981$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-07-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.8°C

Probe: ES3DV2 - SN3022; ConvF(5.15, 5.15, 5.15); Calibrated: 7/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1466; Calibrated: 1/15/2016  
Phantom: SAM Main; Type: QD000P40CC; Serial: TP 1114  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.52 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.764 W/kg

**SAR(1 g) = 0.511 W/kg**



0 dB = 0.599 W/kg = -2.23 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: 1900 Head; Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.388 \text{ S/m}$ ;  $\epsilon_r = 39.899$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-08-2016; Ambient Temp: 23.7°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(7.69, 7.69, 7.69); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.05 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.01 W/kg

**SAR(1 g) = 0.662 W/kg**



0 dB = 0.880 W/kg = -0.56 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1  
Medium: 750 Head; Medium parameters used (interpolated):  
 $f = 707.5 \text{ MHz}$ ;  $\sigma = 0.866 \text{ S/m}$ ;  $\epsilon_r = 42.531$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 11-08-2016; Ambient Temp: 20.5°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3288; ConvF(7, 7, 7); Calibrated: 8/24/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 8/22/2016  
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (6x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 21.28 V/m; Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 0.424 W/kg  
**SAR(1 g) = 0.345 W/kg**



0 dB = 0.374 W/kg = -4.27 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: 835 Head; Medium parameters used (interpolated):  
 $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.928 \text{ S/m}$ ;  $\epsilon_r = 42.438$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 11-07-2016; Ambient Temp: 20.1°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(6.16, 6.16, 6.16); Calibrated: 3/18/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016  
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 25.83 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 0.627 W/kg  
**SAR(1 g) = 0.509 W/kg**



0 dB = 0.561 W/kg = -2.51 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00175**


Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Head; Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.352 \text{ S/m}$ ;  $\epsilon_r = 39.981$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-07-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.8°C

Probe: ES3DV2 - SN3022; ConvF(5.15, 5.15, 5.15); Calibrated: 7/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1466; Calibrated: 1/15/2016  
Phantom: SAM Main; Type: QD000P40CC; Serial: TP 1114  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch**  
**20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 19.61 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 0.631 W/kg  
**SAR(1 g) = 0.422 W/kg**



0 dB = 0.496 W/kg = -3.05 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.388 \text{ S/m}$ ;  $\epsilon_r = 39.899$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 11-08-2016; Ambient Temp: 23.7°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(7.69, 7.69, 7.69); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, Mid.ch**

**20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.77 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.01 W/kg

**SAR(1 g) = 0.655 W/kg**



0 dB = 0.864 W/kg = -0.63 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium: 2450 Head; Medium parameters used (interpolated):  
 $f = 2462 \text{ MHz}$ ;  $\sigma = 1.882 \text{ S/m}$ ;  $\epsilon_r = 38.236$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-10-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3288; ConvF(4.76, 4.76, 4.76); Calibrated: 8/24/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 8/22/2016  
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head, Cheek, Ch 11, 1 Mbps**


**Area Scan (11x18x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.16 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 0.874 W/kg**



0 dB = 1.13 W/kg = 0.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5785 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Head; Medium parameters used:  
 $f = 5785 \text{ MHz}$ ;  $\sigma = 5.193 \text{ S/m}$ ;  $\epsilon_r = 34.003$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

Test Date: 11-07-2016; Ambient Temp: 20.9°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7357; ConvF(4.65, 4.65, 4.65); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn665; Calibrated: 2/19/2016  
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Left Head, Cheek, Ch 157, 6 Mbps**


**Area Scan (11x19x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 7.416 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 5.19 W/kg

**SAR(1 g) = 1.13 W/kg**



0 dB = 3.03 W/kg = 4.81 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00191**

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.076  
Medium: 835 Body Medium parameters used (interpolated):  
 $f = 836.6$  MHz;  $\sigma = 1.001$  S/m;  $\epsilon_r = 54.331$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3213; ConvF(6, 6, 6); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Body SAR, Back side, Mid.ch, 4 Tx Slots**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.86 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.09 W/kg

**SAR(1 g) = 0.612 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076  
Medium: 1900 Body; Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.556 \text{ S/m}$ ;  $\epsilon_r = 53.68$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 4 Tx Slots**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 20.41 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.879 W/kg  
**SAR(1 g) = 0.595 W/kg**



0 dB = 0.689 W/kg = -1.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00209**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium: 835 Body; Medium parameters used (interpolated):  
 $f = 836.6 \text{ MHz}$ ;  $\sigma = 1.001 \text{ S/m}$ ;  $\epsilon_r = 53.898$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(6, 6, 6); Calibrated: 2/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.89 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.986 W/kg

**SAR(1 g) = 0.764 W/kg**



0 dB = 0.837 W/kg = -0.77 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00175**

Communication System: UID 0, UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1  
Medium: 1750 Body; Medium parameters used (interpolated):  
 $f = 1712.4 \text{ MHz}$ ;  $\sigma = 1.423 \text{ S/m}$ ;  $\epsilon_r = 51.757$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 24.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7410; ConvF(7.95, 7.95, 7.95); Calibrated: 7/25/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1322; Calibrated: 7/12/2016  
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Body SAR, Back side, Low.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.39 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.43 W/kg

**SAR(1 g) = 0.945 W/kg**



0 dB = 1.26 W/kg = 1.00 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: 1900 Body; Medium parameters used:  
 $f = 1880 \text{ MHz}$ ;  $\sigma = 1.556 \text{ S/m}$ ;  $\epsilon_r = 53.68$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 28.76 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.73 W/kg

**SAR(1 g) = 1.17 W/kg**



0 dB = 1.35 W/kg = 1.30 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1  
Medium: 750 Body; Medium parameters used (interpolated):  
 $f = 707.5$  MHz;  $\sigma = 0.926$  S/m;  $\epsilon_r = 55.785$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 22.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(9.46, 9.46, 9.46); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 23.90 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 0.983 W/kg  
**SAR(1 g) = 0.538 W/kg**



0 dB = 0.809 W/kg = -0.92 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00191**

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: 835 Body; Medium parameters used (interpolated):  
 $f = 836.5$  MHz;  $\sigma = 0.995$  S/m;  $\epsilon_r = 53.374$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section; Space: 1.0 cm


Test Date: 11-12-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6, 6, 6); Calibrated: 2/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 31.26 V/m; Power Drift = -0.13 dB  
Peak SAR (extrapolated) = 1.65 W/kg  
**SAR(1 g) = 0.880 W/kg**



0 dB = 1.07 W/kg = 0.29 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00175**


Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Body; Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.444 \text{ S/m}$ ;  $\epsilon_r = 51.667$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 24.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7410; ConvF(7.95, 7.95, 7.95); Calibrated: 7/25/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1322; Calibrated: 7/12/2016  
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch**  
**20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.72 V/m; Power Drift = 0.18 dB  
Peak SAR (extrapolated) = 1.58 W/kg  
**SAR(1 g) = 1.06 W/kg**



0 dB = 1.39 W/kg = 1.43 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 00167**


Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1  
Medium: 1900 Body; Medium parameters used (interpolated):  
 $f = 1860 \text{ MHz}$ ;  $\sigma = 1.533 \text{ S/m}$ ;  $\epsilon_r = 53.745$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 9/14/2016  
Phantom: SAM Front; Type: SAM; Serial: 1686  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch**  
**20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 28.68 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 1.69 W/kg  
**SAR(1 g) = 1.15 W/kg**



0 dB = 1.33 W/kg = 1.24 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium: 2450 Body; Medium parameters used (interpolated):  
 $f = 2462 \text{ MHz}$ ;  $\sigma = 2.004 \text{ S/m}$ ;  $\epsilon_r = 51.632$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side**


**Area Scan (11x17x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.36 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.945 W/kg

**SAR(1 g) = 0.430 W/kg**



0 dB = 0.728 W/kg = -1.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5280 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Body; Medium parameters used:  
 $f = 5280 \text{ MHz}$ ;  $\sigma = 5.546 \text{ S/m}$ ;  $\epsilon_r = 47.883$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth, Body SAR, Ch 56, 6 Mbps, Back Side**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 4.920 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.856 W/kg

**SAR(1 g) = 0.149 W/kg**



0 dB = 0.459 W/kg = -3.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5785 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Body; Medium parameters used:  
 $f = 5785 \text{ MHz}$ ;  $\sigma = 6.227 \text{ S/m}$ ;  $\epsilon_r = 47.022$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR, Ch 157, 6 Mbps, Right Edge**


**Area Scan (10x22x1):** Measurement grid: dx=5mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 4.258 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.29 W/kg

**SAR(1 g) = 0.328 W/kg**



0 dB = 0.788 W/kg = -1.03 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: ZNFTP260; Type: Portable Handset; Serial: 2SJR0**

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.298

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2441$  MHz;  $\sigma = 1.952$  S/m;  $\epsilon_r = 52.224$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side**


**Area Scan (11x18x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.660 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.0540 W/kg

**SAR(1 g) = 0.025 W/kg**



## APPENDIX B: SYSTEM VERIFICATION

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.903 \text{ S/m}$ ;  $\epsilon_r = 41.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-08-2016; Ambient Temp: 20.5°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3288; ConvF(7, 7, 7); Calibrated: 8/24/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 8/22/2016

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.35 W/kg

**SAR(1 g) = 1.60 W/kg**

Deviation(1 g) = -2.68%



0 dB = 1.87 W/kg = 2.72 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.927 \text{ S/m}$ ;  $\epsilon_r = 42.457$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-07-2016; Ambient Temp: 20.1°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(6.16, 6.16, 6.16); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.76 W/kg

**SAR(1 g) = 1.95 W/kg**

Deviation(1 g) = 6.79%



0 dB = 2.27 W/kg = 3.56 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.37 \text{ S/m}$ ;  $\epsilon_r = 39.889$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.8°C

Probe: ES3DV2 - SN3022; ConvF(5.15, 5.15, 5.15); Calibrated: 7/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Main; Type: QD000P40CC; Serial: TP 1114

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.51 W/kg

**SAR(1 g) = 3.59 W/kg**

Deviation(1 g) = -0.55%



0 dB = 4.50 W/kg = 6.53 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149**


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: 1900 Head; Medium parameters used (interpolated):  
 $f = 1900 \text{ MHz}$ ;  $\sigma = 1.409 \text{ S/m}$ ;  $\epsilon_r = 39.813$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-08-2016; Ambient Temp: 23.7°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(7.69, 7.69, 7.69); Calibrated: 5/17/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn859; Calibrated: 5/11/2016  
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification at 20.0 dBm (100 mW)

**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Peak SAR (extrapolated) = 7.73 W/kg  
**SAR(1 g) = 4.06 W/kg**  
Deviation(1 g) = 1.25%



0 dB = 6.43 W/kg = 8.08 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.869 \text{ S/m}$ ;  $\epsilon_r = 38.283$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-10-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3288; ConvF(4.76, 4.76, 4.76); Calibrated: 8/24/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 8/22/2016

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.4 W/kg

**SAR(1 g) = 5.31 W/kg**

Deviation(1 g) = 0.57%



0 dB = 7.01 W/kg = 8.46 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.872 \text{ S/m}$ ;  $\epsilon_r = 38.889$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 23.4°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3287; ConvF(4.54, 4.54, 4.54); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.7 W/kg

**SAR(1 g) = 5.57 W/kg**

Deviation(1 g) = 5.49%



0 dB = 7.31 W/kg = 8.64 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1  
Medium: 5GHz Head; Medium parameters used (interpolated):  
 $f = 5250 \text{ MHz}$ ;  $\sigma = 4.648 \text{ S/m}$ ;  $\epsilon_r = 34.809$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 20.9°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7357; ConvF(5.1, 5.1, 5.1); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5250 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.5 W/kg

**SAR(1 g) = 3.71 W/kg**

Deviation(1 g) = -6.31%



0 dB = 8.81 W/kg = 9.45 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 4.996 \text{ S/m}$ ;  $\epsilon_r = 34.274$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 20.9°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7357; ConvF(4.41, 4.41, 4.41); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5600 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.4 W/kg

**SAR(1 g) = 3.84 W/kg**

Deviation(1 g) = -7.80%



0 dB = 9.27 W/kg = 9.67 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1  
Medium: 5GHz Head; Medium parameters used (interpolated):  
 $f = 5750 \text{ MHz}$ ;  $\sigma = 5.16 \text{ S/m}$ ;  $\epsilon_r = 34.036$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 20.9°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7357; ConvF(4.65, 4.65, 4.65); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn665; Calibrated: 2/19/2016  
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800  
Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5750 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.5 W/kg

**SAR(1 g) = 3.88 W/kg**

Deviation(1 g) = -4.79%



0 dB = 9.31 W/kg = 9.69 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.966 \text{ S/m}$ ;  $\epsilon_r = 55.31$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-07-2016; Ambient Temp: 22.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(9.46, 9.46, 9.46); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.54 W/kg

**SAR(1 g) = 1.70 W/kg**

Deviation(1 g) = 0.83%



0 dB = 2.26 W/kg = 3.54 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.999 \text{ S/m}$ ;  $\epsilon_r = 53.912$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-09-2016; Ambient Temp: 22.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(6, 6, 6); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.04 W/kg

**SAR(1 g) = 2.05 W/kg**

Deviation(1 g) = 7.89%



0 dB = 2.40 W/kg = 3.80 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750$  MHz;  $\sigma = 1.462$  S/m;  $\epsilon_r = 51.589$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 24.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7410; ConvF(7.95, 7.95, 7.95); Calibrated: 7/25/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/12/2016

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.29 W/kg

**SAR(1 g) = 3.65 W/kg**

Deviation(1 g) = 0.00%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.579 \text{ S/m}$ ;  $\epsilon_r = 53.62$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-09-2016; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.86 W/kg

**SAR(1 g) = 3.86 W/kg**

Deviation(1 g) = -1.28%



0 dB = 4.90 W/kg = 6.90 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.964 \text{ S/m}$ ;  $\epsilon_r = 52.185$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.0 W/kg

**SAR(1 g) = 4.85 W/kg**

Deviation(1 g) = -4.34%



0 dB = 8.43 W/kg = 9.26 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191**

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Body; Medium parameters used (interpolated):  
 $f = 5250 \text{ MHz}$ ;  $\sigma = 5.502 \text{ S/m}$ ;  $\epsilon_r = 47.922$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016  
Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5250 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.4 W/kg

**SAR(1 g) = 3.60 W/kg**

Deviation(1 g) = -6.49%



0 dB = 8.55 W/kg = 9.32 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 5.968 \text{ S/m}$ ;  $\epsilon_r = 47.329$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.63, 3.63, 3.63); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5600 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.0 W/kg

**SAR(1 g) = 3.95 W/kg**

Deviation(1 g) = -0.25%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191**

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Body; Medium parameters used (interpolated):  
 $f = 5750 \text{ MHz}$ ;  $\sigma = 6.181 \text{ S/m}$ ;  $\epsilon_r = 47.068$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-07-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016  
Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5750 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.8 W/kg

**SAR(1 g) = 3.47 W/kg**

Deviation(1 g) = -8.80%



0 dB = 8.56 W/kg = 9.32 dBW/kg