

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 22, 24, & 27 LTE

Applicant Name:

LG Electronics MobileComm U.S.A 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States**

Date of Testing:

12/27/2016 - 1/4/2017, 1/26/2017

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1612232004.ZNF

FCC ID: ZNFUS110

LG ELECTRONICS MOBILECOMM U.S.A APPLICANT:

Application Type: Certification

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

§2; §22; §24; §27 FCC Rule Part(s):

Test Procedure(s): ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02

EUT Type: Portable Handset

Model: LG-US110

Additional Model(s): LGUS110, US110

Test Device Serial No.: identical prototype [S/N: 00130, 00131]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dog 1 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 1 of 116
© 2017 PCTEST Engineering	Laboratory, Inc.	·		V 5.1



TABLE OF CONTENTS

FCC	PART 2	22, 24, & 27 MEASUREMENT REPORT	3
1.0		RODUCTION	
	1.1	Scope	5
	1.2	Testing Facility	5
2.0	PRO	DDUCT INFORMATION	6
	2.1	Equipment Description	6
	2.2	Device Capabilities	6
	2.3	Test Configuration	6
	2.4	EMI Suppression Device(s)/Modifications	6
3.0	DES	SCRIPTION OF TESTS	7
	3.1	Measurement Procedure	7
	3.1	Block C Frequency Range	7
	3.2	Cellular - Base Frequency Blocks	7
	3.3	Cellular - Mobile Frequency Blocks	7
	3.4	PCS - Base Frequency Blocks	7
	3.5	PCS - Mobile Frequency Blocks	8
	3.6	AWS - Base Frequency Blocks	8
	3.7	AWS - Mobile Frequency Blocks	8
	3.8	Radiated Power and Radiated Spurious Emissions	9
4.0	MEA	ASUREMENT UNCERTAINTY	10
5.0	TES	ST EQUIPMENT CALIBRATION DATA	11
6.0	SAM	IPLE CALCULATIONS	12
7.0	TES	ST RESULTS	13
	7.1	Summary	13
	7.2	Occupied Bandwidth	14
	7.3	Spurious and Harmonic Emissions at Antenna Terminal	33
	7.4	Band Edge Emissions at Antenna Terminal	52
	7.5	Peak-Average Ratio	86
	7.6	Radiated Power (ERP/EIRP)	93
	7.7	Radiated Spurious Emissions Measurements	99
	7.8	Frequency Stability / Temperature Variation	107
8.0	CON	NCLUSION	116

FCC ID: ZNFUS110	PCTEST FCC P	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 2 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 2 of 116





MEASUREMENT REPORT



FCC Part 22, 24, & 27

§2.1033 General Information

APPLICANT: LG Electronics MobileComm U.S.A

APPLICANT ADDRESS: 1000 Sylvan Avenue

Englewood Cliffs, NJ 07632, United States

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA

FCC RULE PART(S): §2; §22; §24; §27

BASE MODEL: LG-US110 **FCC ID:** ZNFUS110

FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)

FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)

Test Device Serial No.: 00130, 00131 ☐ Production ☐ Engineering

DATE(S) OF TEST: 12/27/2016 - 1/4/2017, 1/26/2017

TEST REPORT S/N: 0Y1612232004.ZNF

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.





Test Report S/N: Test Dates: EUT Type:	Manager
Tost report one. Tost butes.	of 116
0Y1612232004.ZNF	3 of 116









FCC Part 22, 24, & 27

			ERP/	EIRP		
Mode	FCC Rule Part	Tx Frequency (MHz)	Max. Pow er (W)	Max. Pow er (dBm)	Emission Designator	Modulation
LTE Band 13	27	779.5 - 784.5	0.106	20.24	4M51G7D	QPSK
LTE Band 13	27	779.5 - 784.5	0.093	19.68	4M51W7D	16QAM
LTE Band 13	27	782	0.107	20.28	8M96G7D	QPSK
LTE Band 13	27	782	0.086	19.34	8M93W7D	16QAM
LTE Band 5	22H	824.7 - 848.3	0.124	20.93	1M12G7D	QPSK
LTE Band 5	22H	824.7 - 848.3	0.090	19.55	1M12W7D	16QAM
LTE Band 5	22H	825.5 - 847.5	0.125	20.97	2M71G7D	QPSK
LTE Band 5	22H	825.5 - 847.5	0.104	20.18	2M71W7D	16QAM
LTE Band 5	22H	826.5 - 846.5	0.130	21.15	4M50G7D	QPSK
LTE Band 5	22H	826.5 - 846.5	0.114	20.55	4M50W7D	16QAM
LTE Band 5	22H	829 - 844	0.132	21.19	8M97G7D	QPSK
LTE Band 5	22H	829 - 844	0.104	20.19	8M95W7D	16QAM
LTE Band 4	27	1710.7 - 1754.3	0.265	24.24	1M11G7D	QPSK
LTE Band 4	27	1710.7 - 1754.3	0.212	23.26	1M12W7D	16QAM
LTE Band 4	27	1711.5 - 1753.5	0.268	24.28	2M71G7D	QPSK
LTE Band 4	27	1711.5 - 1753.5	0.223	23.49	2M71W7D	16QAM
LTE Band 4	27	1712.5 - 1752.5	0.261	24.17	4M50G7D	QPSK
LTE Band 4	27	1712.5 - 1752.5	0.228	23.59	4M48W7D	16QAM
LTE Band 4	27	1715 - 1750	0.267	24.27	8M98G7D	QPSK
LTE Band 4	27	1715 - 1750	0.218	23.39	8M96W7D	16QAM
LTE Band 4	27	1717.5 - 1747.5	0.268	24.28	13M5G7D	QPSK
LTE Band 4	27	1717.5 - 1747.5	0.212	23.26	13M5W7D	16QAM
LTE Band 4	27	1720 - 1745	0.258	24.11	18M0G7D	QPSK
LTE Band 4	27	1720 - 1745	0.222	23.46	18M0W7D	16QAM
LTE Band 2	24E	1850.7 - 1909.3	0.248	23.95	1M12G7D	QPSK
LTE Band 2	24E	1850.7 - 1909.3	0.193	22.86	1M12W7D	16QAM
LTE Band 2	24E	1851.5 - 1908.5	0.240	23.81	2M71G7D	QPSK
LTE Band 2	24E	1851.5 - 1908.5	0.199	23.00	2M71W7D	16QAM
LTE Band 2	24E	1852.5 - 1907.5	0.235	23.70	4M50G7D	QPSK
LTE Band 2	24E	1852.5 - 1907.5	0.194	22.87	4M49W7D	16QAM
LTE Band 2	24E	1855 - 1905	0.238	23.77	8M98G7D	QPSK
LTE Band 2	24E	1855 - 1905	0.193	22.86	8M95W7D	16QAM
LTE Band 2	24E	1857.5 - 1902.5	0.240	23.81	13M5G7D	QPSK
LTE Band 2	24E	1857.5 - 1902.5	0.202	23.06	13M5W7D	16QAM
LTE Band 2	24E	1860 - 1900	0.243	23.86	17M9G7D	QPSK
LTE Band 2	24E	1860 - 1900	0.198	22.96	18M0W7D	16QAM

EUT Overview

FCC ID: ZNFUS110	FCC	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		D 4 -5 440
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 4 of 116



1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Internt'i (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Daga F of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 5 of 116
© 2017 PCTEST Engineering	Laboratory Inc			V 5 1



2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFUS110**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1), Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFUS110	FCC P	- (OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 6 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		rage 0 01 110



3.0 DESCRIPTION OF TESTS


3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-D-2010) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

3.1 Block C Frequency Range §27.5(b)(3)


Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

3.2 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A* Low + A) BLOCK 3: 890 – 891.5 MHz (A* High) BLOCK 2: 880 – 890 MHz (B) BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A) BLOCK 3: 845 – 846.5 MHz (A* High) BLOCK 2: 835 – 845 MHz (B) BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks



 FCC ID: ZNFUS110
 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)
 LG Quality Manager

 Test Report S/N: 0Y1612232004.ZNF
 Test Dates: 12/27/2016 - 1/4/2017, 1/26/2017
 EUT Type: Portable Handset
 Page 7 of 116



1950 1970 1990 1930 BLOCK 1: 1930 - 1945 MHz (A) BLOCK 4: 1965 - 1970 MHz (E) BLOCK 2: 1945 - 1950 MHz (D) BLOCK 5: 1970 - 1975 MHz (F) BLOCK 3: 1950 - 1965 MHz (B) BLOCK 6: 1975 - 1990 MHz (C) 3.5 **PCS - Mobile Frequency Blocks** §24.229 D В Ε F C 1850 1870 1890 1910 BLOCK 1: 1850 - 1865 MHz (A) BLOCK 4: 1885 - 1890 MHz (E) BLOCK 2: 1865 - 1870 MHz (D) BLOCK 5: 1890 - 1895 MHz (F) BLOCK 3: 1870 - 1885 MHz (B) BLOCK 6: 1895 - 1910 MHz (C) 3.6 **AWS - Base Frequency Blocks** §27.5(h) BASE 2110 2120 2130 2135 2140 2145 2155 В С D Ε F BLOCK 4: 2135 - 2140 MHz (D) BLOCK 1: 2110 - 2120 MHz (A) BLOCK 2: 2120 - 2130 MHz (B) BLOCK 5: 2140 - 2145 MHz (E) BLOCK 3: 2130 - 2135 MHz (C) BLOCK 6: 2145 - 2155 MHz (F) 3.7 **AWS - Mobile Frequency Blocks** §27.5(h) MOBILE 1710 1720 1730 1740 1745 1755 1735 В С D E BLOCK 1: 1710 - 1720 MHz (A) BLOCK 4: 1735 - 1740 MHz (D) BLOCK 2: 1720 - 1730 MHz (B) BLOCK 5: 1740 - 1745 MHz (E) BLOCK 3: 1730 - 1735 MHz (C) BLOCK 6: 1745 - 1755 MHz (F)

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 0 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 8 of 116
© 2017 PCTEST Engineering	Laboratory, Inc.	•		V 5.1



3.8 Radiated Power and Radiated Spurious Emissions §2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(b.10) §27.50(d.4) §27.53(f) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

Where, Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] - cable loss [dB].

The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log₁₀(Power [Watts]).

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 0 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 9 of 116
© 2017 PCTEST Engineering Laboratory, Inc.				V 5.1



4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (±dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFUS110	FCC P	(OEDTIEIO ATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 10 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 10 of 116



TEST EQUIPMENT CALIBRATION DATA 5.0

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Tx3 Licensed Transmitter Cable Set 7,		Annual	7/12/2017	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/4/2016	Annual	3/4/2017	RE1
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/1/2016	Annual	3/1/2017	MY52350166
Anritsu	MT8820C	Radio Communication Analyzer	4/14/2016	Annual	4/14/2017	6201240328
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Annual	2/26/2017	441112
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/28/2016	Biennial	8/28/2018	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/11/2016	Annual	7/11/2017	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/6/2016	Annual	7/6/2017	13SH10-1000/U1000-1
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	3/4/2016	Annual	3/4/2017	11210140001
Mini-Circuits	SSG-4000HP	USB Synthesized Signal Generator		N/A		11208010032
Mini-Circuits	TVA-11-422	RF Power Amp		N/A		QA1303002
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
PCTEST	-	EMC Switch System	7/6/2016	Annual	7/6/2017	NM2
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

1. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFUS110	PCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 11 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 11 of 116
© 2017 PCTEST Engineering Laboratory, Inc.				V 5.1



6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission, telemetry, telecommand

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz W = Amplitude/Angle Modulated 7 = Quantized/Digital Info D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80).

FCC ID: ZNFUS110	FCC P	et. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 10 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 12 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			



TEST RESULTS 7.0

7.1 Summary

Company Name: LG Electronics MobileComm U.S.A

FCC ID: ZNFUS110

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

Mode(s):

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
2.1049	Occupied Bandwidth	N/A		PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(c) 27.53(h)	Out of Band Emissions	> 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A	CONDUCTED	PASS	See RF Exposure Report
2.1055. 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power (Band 5)	< 7 Watts max. ERP		PASS	Section 7.6
27.50(b.10)	Effective Radiated Power (Band 13)	< 3 Watts max. ERP		PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP	RADIATED	PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(c) 27.53(h)	Undesirable Emissions	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.7
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction 2) table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.4.

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT		Approved by:
FCC ID: ZNF05110	ENGINEERING LABORATORY, INC.	(CERTIFICATION)		Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 13 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		rage 13 01 110



7.2 Occupied Bandwidth §2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 - Section 4.2

Test Settings

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW \geq 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2-7 were repeated after changing the RBW such that it would be within 1-5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: ZNFUS110	PCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 14 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 14 of 116





Plot 7-1. Occupied Bandwidth Plot (Band 13 - 5.0MHz QPSK - RB Size 25)



Plot 7-2. Occupied Bandwidth Plot (Band 13 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	⊕ rg	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 15 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 15 01 116
© 2017 PCTEST Engineering Laboratory Inc.				





Plot 7-3. Occupied Bandwidth Plot (Band 13 - 10.0MHz QPSK - RB Size 50)



Plot 7-4. Occupied Bandwidth Plot (Band 13 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 16 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 16 of 116
© 2017 PCTEST Engineering	Laboratory Inc			V 5 1





Plot 7-5. Occupied Bandwidth Plot (Band 5 - 1.4MHz QPSK - RB Size 6)



Plot 7-6. Occupied Bandwidth Plot (Band 5 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 17 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 17 of 116
2017 PCTEST Engineering Laboratory, Inc.				V 5.1

V 5 1





Plot 7-7. Occupied Bandwidth Plot (Band 5 - 3.0MHz QPSK - RB Size 15)



Plot 7-8. Occupied Bandwidth Plot (Band 5 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFUS110	FCC P	(OEDTIFICATION))		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 10 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 18 of 116





Plot 7-9. Occupied Bandwidth Plot (Band 5 - 5.0MHz QPSK - RB Size 25)



Plot 7-10. Occupied Bandwidth Plot (Band 5 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFUS110	FCC P	(OEDTIEIO ATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 10 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 19 of 116





Plot 7-11. Occupied Bandwidth Plot (Band 5 - 10.0MHz QPSK - RB Size 50)



Plot 7-12. Occupied Bandwidth Plot (Band 5 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFUS110	FCC F	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 20 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			






Plot 7-13. Occupied Bandwidth Plot (Band 4 - 1.4MHz QPSK - RB Size 6)



Plot 7-14. Occupied Bandwidth Plot (Band 4 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Page 21 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		raye 2101110





Plot 7-15. Occupied Bandwidth Plot (Band 4 – 3.0MHz QPSK – RB Size 15)



Plot 7-16. Occupied Bandwidth Plot (Band 4 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFUS110	FCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 22 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 22 of 116






Plot 7-17. Occupied Bandwidth Plot (Band 4 - 5.0MHz QPSK - RB Size 25)



Plot 7-18. Occupied Bandwidth Plot (Band 4 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFUS110	FCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 22 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 23 of 116






Plot 7-19. Occupied Bandwidth Plot (Band 4 - 10.0MHz QPSK - RB Size 50)



Plot 7-20. Occupied Bandwidth Plot (Band 4 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 24 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 24 01 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1






Plot 7-21. Occupied Bandwidth Plot (Band 4 - 15.0MHz QPSK - RB Size 75)



Plot 7-22. Occupied Bandwidth Plot (Band 4 - 15.0MHz 16-QAM - RB Size 75)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 25 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 25 01 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1





Plot 7-23. Occupied Bandwidth Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 7-24. Occupied Bandwidth Plot (Band 4 - 20.0MHz 16-QAM - RB Size 100)

FCC ID: ZNFUS110	FCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 96 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 26 of 116





Plot 7-25. Occupied Bandwidth Plot (Band 2 - 1.4MHz QPSK - RB Size 6)



Plot 7-26. Occupied Bandwidth Plot (Band 2 - 1.4MHz 16-QAM - RB Size 6)

FCC ID: ZNFUS110	FCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 07 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 27 of 116





Plot 7-27. Occupied Bandwidth Plot (Band 2 - 3.0MHz QPSK - RB Size 15)



Plot 7-28. Occupied Bandwidth Plot (Band 2 - 3.0MHz 16-QAM - RB Size 15)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 28 of 116





Plot 7-29. Occupied Bandwidth Plot (Band 2 - 5.0MHz QPSK - RB Size 25)



Plot 7-30. Occupied Bandwidth Plot (Band 2 - 5.0MHz 16-QAM - RB Size 25)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 29 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 29 01 110
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1

V 5 1





Plot 7-31. Occupied Bandwidth Plot (Band 2 - 10.0MHz QPSK - RB Size 50)



Plot 7-32. Occupied Bandwidth Plot (Band 2 - 10.0MHz 16-QAM - RB Size 50)

FCC ID: ZNFUS110	FCC F	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 30 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1

V 5 1 11/28/2016





Plot 7-33. Occupied Bandwidth Plot (Band 2 - 15.0MHz QPSK - RB Size 75)



Plot 7-34. Occupied Bandwidth Plot (Band 2 - 15.0MHz 16-QAM - RB Size 75)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 21 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 31 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1





Plot 7-35. Occupied Bandwidth Plot (Band 2 - 20.0MHz QPSK - RB Size 100)



Plot 7-36. Occupied Bandwidth Plot (Band 2 - 20.0MHz 16-QAM - RB Size 100)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 32 of 116



7.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a) §27.53(c.2) §27.53(h)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is 43 + $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 - Section 6.0

Test Settings

- 1. Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Dogg 22 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 33 of 116






Plot 7-37. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)



Plot 7-38. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFUS110	FCC P	(OEDTIFICATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dogg 24 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 34 of 116






Plot 7-39. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-40. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 25 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 35 of 116
© 2017 PCTEST Engineering Laboratory, Inc.			V 5.1	






Plot 7-41. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-42. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: ZNFUS110	FCC P	(OERTIFICATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 26 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 36 of 116






Plot 7-43. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-44. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 27 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 37 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1






Plot 7-45. Conducted Spurious Plot (Band 13 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-46. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0- Low Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 38 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1






Plot 7-47. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-48. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFUS110	FCC P	(OFFICIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 20 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 39 of 116






Plot 7-49. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-50. Conducted Spurious Plot (Band 5 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 40 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 40 of 116






Plot 7-51. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-52. Conducted Spurious Plot (Band 5 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: ZNFUS110	FCC P	(OEDTIEIOATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 41 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 41 of 116






Plot 7-53. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-54. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 40 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 42 of 116
© 2017 PCTEST Engineering	2017 PCTEST Engineering Laboratory, Inc.			V 5.1






Plot 7-55. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)




Plot 7-56. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFUS110	FCC P	(OFFITION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 42 of 446
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 43 of 116





Plot 7-57. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-58. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 44 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 44 of 116





Plot 7-59. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-60. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: ZNFUS110	FCC P	(OFFITION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 45 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 45 of 116






Plot 7-61. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-62. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: ZNFUS110	FCC P	Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	⊕ LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 46 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 46 of 116
© 2017 PCTEST Engineering	Laboratory Inc			V 5.1






Plot 7-63. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-64. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)

FCC ID: ZNFUS110	FCC P	t. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	① LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Dags 47 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 47 of 116





Plot 7-65. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-66. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFUS110	FCC P	(OEDTIEIOATIONI)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 40 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 48 of 116






Plot 7-67. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-68. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: ZNFUS110	FCC P	(OEDTIFICATION)		Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Daga 40 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 49 of 116






Plot 7-69. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-70. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Daga 50 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 50 of 116
© 2017 PCTEST Engineering	Laboratory Inc			V 5.1





Plot 7-71. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-72. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: ZNFUS110	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:		Daga 51 of 116
0Y1612232004.ZNF	12/27/2016 - 1/4/2017, 1/26/2017	Portable Handset		Page 51 of 116
© 2017 PCTEST Engineering	Laboratory Inc			V 5.1