



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
<http://www.pctest.com>



## MEASUREMENT REPORT FCC PART 15.407 UNII 802.11a/n/ac

**Applicant Name:**  
LG Electronics USA, Inc.  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
3/21/2019-5/3/2019  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M1903070034-10-R1.ZNF

<b>FCC ID:</b>	<b>ZNFV450VM</b>
<b>APPLICANT:</b>	<b>LG Electronics USA, Inc.</b>

<b>Application Type:</b>	Class II Permissive Change
<b>Model:</b>	LM-V450VM
<b>Additional Model(s):</b>	LMV450VM, V450VM
<b>EUT Type:</b>	Portable Handset
<b>Frequency Range:</b>	5180 – 5825MHz
<b>FCC Classification:</b>	Unlicensed National Information Infrastructure (UNII)
<b>FCC Rule Part(s):</b>	Part 15 Subpart E (15.407)
<b>Test Procedure(s):</b>	ANSI C63.10-2013, KDB 789033 D02 v02r01, KDB 648474 D03 v01r04, KDB 662911 D01 v02r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1903070034-10-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President



<b>FCC ID:</b> ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 1 of 85

# TABLE OF CONTENTS

1.0	INTRODUCTION.....	3
1.1	Scope.....	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description.....	4
2.2	Device Capabilities.....	4
2.3	Test Configuration.....	6
2.4	EMI Suppression Device(s)/Modifications.....	6
3.0	DESCRIPTION OF TESTS.....	7
3.1	Evaluation Procedure.....	7
3.2	Radiated Emissions.....	7
3.3	Environmental Conditions.....	7
4.0	ANTENNA REQUIREMENTS.....	8
5.0	MEASUREMENT UNCERTAINTY.....	9
6.0	TEST EQUIPMENT CALIBRATION DATA.....	10
7.0	TEST RESULTS.....	11
7.1	Summary.....	11
7.2	Radiated Spurious Emission Measurements – Above 1GHz.....	12
7.2.1.	SISO Antenna-1 Radiated Spurious Emission Measurements.....	15
7.2.2.	SISO Antenna-2 Radiated Spurious Emission Measurements.....	26
7.2.3.	MIMO/CDD Radiated Spurious Emission Measurements.....	37
7.2.5.	SISO Antenna-1 Radiated Band Edge Measurements (20MHz BW).....	51
7.2.6.	SISO Antenna-1 Radiated Band Edge Measurements (40MHz BW).....	54
7.2.7.	SISO Antenna-1 Radiated Band Edge Measurements (80MHz BW).....	57
7.2.8.	SISO Antenna-2 Radiated Band Edge Measurements (20MHz BW).....	60
7.2.9.	SISO Antenna-2 Radiated Band Edge Measurements (40MHz BW).....	63
7.2.10.	SISO Antenna-2 Radiated Band Edge Measurements (80MHz BW).....	66
7.2.11.	CDD Radiated Band Edge Measurements (20MHz BW).....	69
7.2.12.	MIMO Radiated Band Edge Measurements (20MHz BW).....	72
7.2.13.	MIMO Radiated Band Edge Measurements (40MHz BW).....	75
7.2.14.	MIMO Radiated Band Edge Measurements (80MHz BW).....	78
7.3	Radiated Spurious Emissions Measurements – Below 1GHz.....	81
8.0	CONCLUSION.....	85

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1-ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset
		Page 2 of 85

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 3 of 85

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFV450VM**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

**Test Device Serial No.:** 05870, 05862

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, 5G NR Bands n261/n260

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
42	5210	56	5280	120	5600	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	144	5720	165	5825

Table 2-1. 802.11a / 802.11n / 802.11ac (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	118	5590	159	5795
				:	:		
				142	5710		

Table 2-2. 802.11n / 802.11ac (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
				:	:		
				138	5690		

Table 2-3. 802.11ac (80MHz BW) Frequency / Channel Operations

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 4 of 85

**Notes:**

- 5GHz NII operation is possible in 20MHz, and 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013 and KDB 789033 D02 v02r01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles				
802.11 Mode/Band		Duty Cycle [%]		
		ANT1	ANT2	MIMO
5GHz	a	98.3	98.3	98.3
	n (HT20)	98.2	98.1	98.1
	ac (HT20)	98.1	98.2	98.2
	n (HT40)	97.2	97.3	97.3
	ac (HT40)	97.3	97.3	97.4
	ac (HT80)	97.0	97.0	97.0

**Table 2-4. Measured Duty Cycles**

- The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD/MIMO	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
5GHz	11a	✓	✓	✗	✗	✓	✓
	11n/ac (20MHz)	✓	✓	✓	✓	✓	✓
	11n/ac (40MHz)	✓	✓	✓	✓	✓	✓
	11ac (80MHz)	✓	✓	✓	✓	✓	✓

**Table 2-5. Frequency / Channel Operations**

✓ = Support ; ✗ = NOT Support

**SISO** = Single Input Single Output

**SDM** = Spatial Diversity Multiplexing – MIMO function

Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps (802.11a)  
 6.5/7.2, 13/14.4, 19.5/21.7, 26/28.9, 39/43.3, 52/57.8, 58.5/65, 65/72.2 (n – 20MHz)  
 13.5/15, 27/30, 40.5/45, 54/60, 81/90, 108/120, 121.5/135, 135/150 (n – 40MHz BW)  
 29.3/32.5, 58.5/65, 87.8/97.5, 117/130, 175.5/195, 234/260, 263.3/292.5, 292.5/325, 351/390, 390/433.3 (ac – 80MHz BW)  
 13/14.4, 26.28.9, 39/43.3, 52/57.8, 78/86.7, 104/115.6, 117/130, 130/144.4Mbps (MIMO n/ac – 20MHz)  
 156/173Mbps (MIMO ac – 20MHz)  
 27/30, 54/60, 81/90, 108/120, 162/180, 216/240, 243,270, 270/300Mbps (MIMO n/ac – 40MHz) 324/360, 360/400Mbps (MIMO ac – 40MHz)  
 58.5/65, 117/130, 175.5/195, 234/260, 351/390, 468/520, 526.5/585, 585/650, 702/780, 780/866.7Mbps (MIMO ac – 80MHz)

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 5 of 85

### 2.3 Test Configuration

The EUT was tested per the guidance of KDB 789033 D02 v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing. See Section 3.2 for radiated emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: PWMA-W815A while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 6 of 85

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

### 3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

### 3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 7 of 85

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The EUT complies with the requirement of §15.203.

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 8 of 85

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 9 of 85

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-2	Conducted Cable Set (25GHz)	8/23/2018	Annual	8/23/2019	WL25-2
Agilent	N9030A	PXA Signal Analyzer (44GHz)	5/25/2018	Annual	5/25/2019	MY52350166
Agilent	N9038A	MXE EMI Receiver	6/11/2018	Annual	6/11/2019	MY51210133
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2017	Biennial	10/10/2019	121034
COM-Power	PAM-103	Pre-Amplifier (1-1000MHz)	9/17/2018	Annual	9/17/2019	441119
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-10	Small Horn (26.5 - 40GHz)	8/9/2018	Biennial	8/9/2020	130993
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/9/2018	Biennial	8/9/2020	135427
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	6/18/2018	Biennial	6/18/2020	114451
Huber + Suhner	Sucoflex 102A	40GHz Radiated Cable Set	8/23/2018	Annual	8/23/2019	251425001
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	9/19/2018	Annual	9/19/2019	100040
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/21/2018	Annual	5/21/2019	100342
Rohde & Schwarz	TS-PR40	26.5-40 GHz Pre-Amplifier	9/19/2018	Annual	9/19/2019	100037
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	8/9/2018	Annual	8/9/2019	100348
Rohde & Schwarz	ESW44	EMI Test Receiver	11/20/2018	Annual	11/20/2019	101570
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/2/2018	Annual	7/2/2019	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/18/2018	Annual	6/18/2019	102134
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 10 of 85

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics USA, Inc.  
 FCC ID: ZNFV450VM  
 FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(b.1), (2), (3), (4)	RSS-247 [6.2]	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])	RADIATED	PASS	Section 7.2
15.205, 15.407(b.1), (4), (5), (6)	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.2, 7.3

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 11 of 85

## 7.2 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW), 802.11n (40MHz BW), and 802.11ac (80MHz)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.***

***For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.***

***For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.***

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-2 per Section 15.209 and RSS-Gen (8.9).***

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
Above 960.0 MHz	500	3

**Table 7-2. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5  
KDB 789033 D02 v02r01 – Section G

### Test Settings

#### Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times \text{span/RBW}$ )
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 12 of 85

### Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 13 of 85

**Test Notes**

1. All emissions that lie in the restricted bands (denoted by a \* next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-2.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-2. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.
8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

**Sample Calculations**

**Determining Spurious Emissions Levels**


- Field Strength Level [dBμV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dBμV/m] – Limit [dBμV/m]

**Radiated Band Edge Measurement Offset**


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.2 was calculated using the formula:  
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Pre-amplifier Gain

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 14 of 85


## 7.2.1 SISO Antenna-1 Radiated Spurious Emission Measurements



**Plot 7-1. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11a – U1 Ch. 40)**




**Plot 7-2. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11a – U2A Ch. 56)**



**Plot 7-3. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11a – U2C Ch. 120)**


FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 15 of 85




**Plot 7-4. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11a – U3 Ch. 157)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 16 of 85

## SISO Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz)



**Plot 7-5. Radiated Spurious Plot 18GHz - 26.5GHz SISO ANT1 (802.11a)**



**Plot 7-6. Radiated Spurious Plot 26.5GHz - 40GHz SISO ANT1 (802.11a)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 17 of 85

## SISO Antenna-1 Radiated Spurious Emission Measurements

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	-	-	-70.12	15.41	0.00	52.29	68.20	-15.91
* 15540.00	Average	V	-	-	-83.05	22.36	0.00	46.31	53.98	-7.67
* 15540.00	Peak	V	-	-	-71.04	22.36	0.00	58.32	73.98	-15.66
* 20720.00	Average	V	-	-	-73.82	17.17	-9.54	40.81	53.98	-13.17
* 20720.00	Peak	V	-	-	-64.74	17.17	-9.54	49.89	73.98	-24.09
25900.00	Peak	V	-	-	-63.25	19.34	-9.54	53.55	68.20	-14.65

Table 7-3. Radiated Measurements

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	-	-	-71.25	18.78	0.00	54.53	68.20	-13.67
* 15600.00	Average	V	-	-	-85.10	27.80	0.00	49.70	53.98	-4.28
* 15600.00	Peak	V	-	-	-73.57	27.80	0.00	61.23	73.98	-12.75
* 20800.00	Average	V	-	-	-73.64	17.31	-9.54	41.12	53.98	-12.86
* 20800.00	Peak	V	-	-	-64.59	17.31	-9.54	50.18	73.98	-23.80
26000.00	Peak	V	-	-	-63.12	19.60	-9.54	53.94	68.20	-14.26

Table 7-4. Radiated Measurements

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 18 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.38	15.49	0.00	52.11	68.20	-16.09
15720.00	Average	V	-	-	-83.09	22.76	0.00	46.67	53.98	-7.31
15720.00	Peak	V	-	-	-71.19	22.76	0.00	58.57	73.98	-15.41
20960.00	Average	V	-	-	-75.56	17.60	-9.54	39.49	53.98	-14.49
20960.00	Peak	V	-	-	-64.36	17.60	-9.54	50.69	73.98	-23.29
26200.00	Peak	V	-	-	-63.23	19.73	-9.54	53.95	68.20	-14.25

**Table 7-5. Radiated Measurements**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	V	-	-	-72.67	18.78	0.00	53.11	68.20	-15.09
* 15600.00	Average	V	-	-	-84.77	27.80	0.00	50.03	53.98	-3.95
* 15600.00	Peak	V	-	-	-74.33	27.80	0.00	60.47	73.98	-13.51
* 20800.00	Average	V	-	-	-75.55	17.31	-9.54	39.21	53.98	-14.77
* 20800.00	Peak	V	-	-	-64.35	17.31	-9.54	50.41	73.98	-23.57
26000.00	Peak	V	-	-	-63.22	19.60	-9.54	53.84	68.20	-14.36

**Table 7-6. Radiated Measurements with WCP**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 19 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-70.74	15.68	0.00	51.94	68.20	-16.26
* 15780.00	Average	V	-	-	-82.63	22.73	0.00	47.10	53.98	-6.88
* 15780.00	Peak	V	-	-	-72.14	22.73	0.00	57.59	73.98	-16.39
* 21040.00	Average	V	-	-	-72.70	17.67	-9.54	42.42	53.98	-11.56
* 21040.00	Peak	V	-	-	-65.42	17.67	-9.54	49.71	73.98	-24.27
26300.00	Peak	V	-	-	-64.35	20.29	-9.54	53.40	68.20	-14.80

**Table 7-7. Radiated Measurements**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-72.14	15.95	0.00	50.81	68.20	-17.39
* 15840.00	Average	V	-	-	-83.53	23.15	0.00	46.62	53.98	-7.36
* 15840.00	Peak	V	-	-	-71.72	23.15	0.00	58.43	73.98	-15.55
* 21120.00	Average	V	-	-	-74.34	17.83	-9.54	40.95	53.98	-13.03
* 21120.00	Peak	V	-	-	-66.49	17.83	-9.54	48.80	73.98	-25.18
26400.00	Peak	V	-	-	-63.61	20.07	-9.54	53.93	68.20	-14.27

**Table 7-8. Radiated Measurements**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 20 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10640.00	Average	V	-	-	-82.69	16.08	0.00	40.39	53.98	-13.59
10640.00	Peak	V	-	-	-70.03	16.08	0.00	53.05	73.98	-20.93
15960.00	Average	V	-	-	-83.54	23.20	0.00	46.66	53.98	-7.32
15960.00	Peak	V	-	-	-72.99	23.20	0.00	57.21	73.98	-16.77
21280.00	Average	V	-	-	-73.61	17.98	-9.54	41.83	53.98	-12.15
21280.00	Peak	V	-	-	-66.38	17.98	-9.54	49.06	73.98	-24.92
26600.00	Peak	V	-	-	-66.00	19.42	-9.54	50.88	68.20	-17.32

**Table 7-9. Radiated Measurements**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-70.48	15.68	0.00	52.20	68.20	-16.00
* 15780.00	Average	V	-	-	-83.30	22.73	0.00	46.43	53.98	-7.55
* 15780.00	Peak	V	-	-	-70.74	22.73	0.00	58.99	73.98	-14.99
* 21040.00	Average	V	-	-	-74.55	17.67	-9.54	40.58	53.98	-13.40
* 21040.00	Peak	V	-	-	-66.72	17.67	-9.54	48.41	73.98	-25.57
26300.00	Peak	V	-	-	-66.88	20.29	-9.54	50.86	68.20	-17.34

**Table 7-10. Radiated Measurements with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 21 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
11000.00	Average	V	-	-	-82.06	17.05	0.00	41.99	53.98	-11.99
11000.00	Peak	V	-	-	-70.23	17.05	0.00	53.82	73.98	-20.16
16500.00	Peak	V	-	-	-71.14	24.58	0.00	60.44	68.20	-7.76
22000.00	Peak	V	-	-	-66.66	18.43	-9.54	49.23	68.20	-18.97
27500.00	Peak	V	-	-	-64.16	20.02	-9.54	53.32	68.20	-14.88

**Table 7-11. Radiated Measurements**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5600MHz  
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
11200.00	Average	V	-	-	-82.05	16.62	0.00	41.57	53.98	-12.41
11200.00	Peak	V	-	-	-70.35	16.62	0.00	53.27	73.98	-20.71
16800.00	Peak	V	-	-	-71.69	24.32	0.00	59.63	68.20	-8.57
22400.00	Average	V	-	-	-72.45	19.18	-9.54	44.19	53.98	-9.79
22400.00	Peak	V	-	-	-65.28	19.18	-9.54	51.36	73.98	-22.62
28000.00	Peak	V	-	-	-66.52	20.40	-9.54	51.33	68.20	-16.87

**Table 7-12. Radiated Measurements**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 22 of 85

Worst Case Mode: 802.11a  
Worst Case Transfer Rate: 6Mbps  
Distance of Measurements: 1 & 3 Meters  
Operating Frequency: 5720MHz  
Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-83.22	17.60	0.00	41.38	53.98	-12.60
* 11440.00	Peak	V	-	-	-71.44	17.60	0.00	53.16	73.98	-20.82
17160.00	Peak	V	-	-	-70.38	24.61	0.00	61.23	68.20	-6.97
* 22880.00	Average	V	-	-	-72.71	18.88	-9.54	43.63	53.98	-10.35
* 22880.00	Peak	V	-	-	-65.65	18.88	-9.54	50.69	73.98	-23.29
28600.00	Peak	V	-	-	-66.25	20.08	-9.54	51.28	68.20	-16.92

**Table 7-13. Radiated Measurements**

Worst Case Mode: 802.11a  
Worst Case Transfer Rate: 6Mbps  
Distance of Measurements: 1 & 3 Meters  
Operating Frequency: 5600MHz  
Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	V	-	-	-82.06	16.62	0.00	41.56	53.98	-12.42
* 11200.00	Peak	V	-	-	-69.71	16.62	0.00	53.91	73.98	-20.07
16800.00	Peak	V	-	-	-71.22	24.32	0.00	60.10	68.20	-8.10
22400.00	Average	V	-	-	-74.53	19.18	-9.54	42.11	53.98	-11.87
22400.00	Peak	V	-	-	-66.52	19.18	-9.54	50.12	73.98	-23.86
28000.00	Peak	V	-	-	-64.25	20.40	-9.54	53.61	68.20	-14.59

**Table 7-14. Radiated Measurements with WCP**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 23 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	V	-	-	-82.84	17.49	0.00	41.65	53.98	-12.33
* 11490.00	Peak	V	-	-	-70.85	17.49	0.00	53.64	73.98	-20.34
17235.00	Peak	V	-	-	-71.37	25.28	0.00	60.91	68.20	-7.29
* 22980.00	Average	V	-	-	-75.65	19.03	-9.54	40.84	53.98	-13.14
* 22980.00	Peak	V	-	-	-65.48	19.03	-9.54	51.01	73.98	-22.97
28725.00	Peak	V	-	-	-65.22	20.24	-9.54	52.48	68.20	-15.72

**Table 7-15. Radiated Measurements**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-83.43	21.02	0.00	44.59	53.98	-9.39
* 11570.00	Peak	V	-	-	-72.45	21.02	0.00	55.57	73.98	-18.41
17355.00	Peak	V	-	-	-73.51	29.63	0.00	63.12	68.20	-5.08
23140.00	Peak	V	-	-	-63.45	18.82	-9.54	52.83	68.20	-15.37
28925.00	Peak	V	-	-	-62.75	-5.04	-9.54	29.66	68.20	-38.54

**Table 7-16. Radiated Measurements**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 24 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-83.41	21.21	0.00	44.80	53.98	-9.18
* 11650.00	Peak	V	-	-	-73.20	21.21	0.00	55.01	73.98	-18.97
17475.00	Peak	V	-	-	-73.98	29.76	0.00	62.78	68.20	-5.42
23300.00	Peak	V	-	-	-64.55	18.40	-9.54	51.31	68.20	-16.89
29125.00	Peak	V	-	-	-63.55	-7.31	-9.54	26.60	68.20	-41.60

**Table 7-17. Radiated Measurements**


Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-83.17	21.21	0.00	45.04	53.98	-8.94
* 11650.00	Peak	V	-	-	-73.38	21.21	0.00	54.83	73.98	-19.15
17475.00	Peak	V	-	-	-73.90	29.76	0.00	62.86	68.20	-5.34
23300.00	Peak	V	-	-	-66.55	18.40	-9.54	49.31	68.20	-18.89
29125.00	Peak	V	-	-	-64.52	19.45	-9.54	52.39	68.20	-15.81


**Table 7-18. Radiated Measurements with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 25 of 85


## 7.2.2. SISO Antenna-2 Radiated Spurious Emission Measurements



Plot 7-7. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11a – U1 Ch. 40)




Plot 7-8. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11a – U2A Ch. 56)



Plot 7-9. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11a – U2C Ch. 120)


FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1-ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 26 of 85




**Plot 7-10. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11a – U3 Ch. 157)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 27 of 85

## SISO Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)



**Plot 7-11. Radiated Spurious Plot above 18GHz - 26.5GHz SISO ANT2 (802.11a)**



**Plot 7-12. Radiated Spurious Plot 26.5GHz - 40GHz SISO ANT2 (802.11a)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 28 of 85

## SISO Antenna-2 Radiated Spurious Emission Measurements

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.98	18.99	0.00	56.01	68.20	-12.19
* 15540.00	Average	V	-	-	-83.98	27.73	0.00	50.75	53.98	-3.23
* 15540.00	Peak	V	-	-	-71.78	27.73	0.00	62.95	73.98	-11.03
* 20720.00	Average	V	-	-	-75.44	17.17	-9.54	39.19	53.98	-14.79
* 20720.00	Peak	V	-	-	-69.22	17.17	-9.54	45.41	73.98	-28.57
25900.00	Peak	V	-	-	-66.77	19.34	-9.54	50.02	68.20	-18.18

**Table 7-19. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	-	-	-70.48	19.36	0.00	55.88	68.20	-12.32
* 15600.00	Average	V	-	-	-84.05	27.61	0.00	50.56	53.98	-3.42
* 15600.00	Peak	V	-	-	-72.06	27.61	0.00	62.55	73.98	-11.43
* 20800.00	Average	V	-	-	-73.24	17.31	-9.54	41.52	53.98	-12.46
* 20800.00	Peak	V	-	-	-69.05	17.31	-9.54	45.71	73.98	-28.26
26000.00	Peak	V	-	-	-66.52	19.60	-9.54	50.54	68.20	-17.66

**Table 7-20. Radiated Measurements SISO ANT2**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 29 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.48	19.72	0.00	56.24	68.20	-11.96
* 15720.00	Average	V	-	-	-84.05	27.41	0.00	50.36	53.98	-3.62
* 15720.00	Peak	V	-	-	-72.06	27.41	0.00	62.35	73.98	-11.63
* 20960.00	Average	V	-	-	-72.93	17.60	-9.54	42.13	53.98	-11.85
* 20960.00	Peak	V	-	-	-69.54	17.60	-9.54	45.51	73.98	-28.47
26200.00	Peak	V	-	-	-66.80	19.73	-9.54	50.38	68.20	-17.82

**Table 7-21. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.70	19.72	0.00	56.02	68.20	-12.18
* 15720.00	Average	V	-	-	-84.69	27.41	0.00	49.72	53.98	-4.26
* 15720.00	Peak	V	-	-	-72.90	27.41	0.00	61.51	73.98	-12.47
* 20960.00	Average	V	-	-	-73.01	17.60	-9.54	42.05	53.98	-11.93
* 20960.00	Peak	V	-	-	-68.94	17.60	-9.54	46.11	73.98	-27.87
26200.00	Peak	V	-	-	-66.61	19.73	-9.54	50.57	68.20	-17.63

**Table 7-22. Radiated Measurements SISO ANT2 with WCP**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 30 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	-	-	-71.44	15.71	0.00	51.27	68.20	-16.93
* 15780.00	Average	H	-	-	-85.03	23.37	0.00	45.34	53.98	-8.64
* 15780.00	Peak	H	-	-	-72.36	23.37	0.00	58.01	73.98	-15.97
* 21040.00	Average	V	-	-	-73.67	17.67	-9.54	41.46	53.98	-12.52
* 21040.00	Peak	V	-	-	-68.89	17.67	-9.54	46.24	73.98	-27.74
26300.00	Peak	V	-	-	-66.51	20.29	-9.54	51.23	68.20	-16.97

**Table 7-23. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	H	-	-	-70.84	16.16	0.00	52.32	68.20	-15.88
* 15840.00	Average	H	-	-	-84.26	22.64	0.00	45.38	53.98	-8.60
* 15840.00	Peak	H	-	-	-71.86	22.64	0.00	57.78	73.98	-16.20
* 21120.00	Average	V	-	-	-73.74	17.83	-9.54	41.56	53.98	-12.42
* 21120.00	Peak	V	-	-	-68.49	17.83	-9.54	46.80	73.98	-27.18
26400.00	Peak	V	-	-	-67.14	20.07	-9.54	50.39	68.20	-17.81

**Table 7-24. Radiated Measurements SISO ANT2**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 31 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-83.47	17.01	0.00	40.54	53.98	-13.44
* 10640.00	Peak	H	-	-	-71.30	17.01	0.00	52.71	73.98	-21.27
* 15960.00	Average	H	-	-	-84.71	22.56	0.00	44.85	53.98	-9.13
* 15960.00	Peak	H	-	-	-71.74	22.56	0.00	57.82	73.98	-16.16
* 21280.00	Average	V	-	-	-72.44	17.98	-9.54	43.00	53.98	-10.98
* 21280.00	Peak	V	-	-	-69.54	17.98	-9.54	45.90	73.98	-28.08
26600.00	Peak	V	-	-	-66.98	20.40	-9.54	50.88	68.20	-17.32

**Table 7-25. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-83.35	17.01	0.00	40.66	53.98	-13.32
* 10640.00	Peak	H	-	-	-70.98	17.01	0.00	53.03	73.98	-20.95
* 15960.00	Average	H	-	-	-84.75	22.56	0.00	44.81	53.98	-9.17
* 15960.00	Peak	H	-	-	-72.40	22.56	0.00	57.16	73.98	-16.82
* 21280.00	Average	H	-	-	-73.14	17.98	-9.54	42.29	53.98	-11.68
* 21280.00	Peak	H	-	-	-65.45	17.98	-9.54	49.98	73.98	-23.99
26600.00	Peak	H	-	-	-65.89	20.40	-9.54	51.97	68.20	-16.23

**Table 7-26. Radiated Measurements SISO ANT2 with WCP**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 32 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11000.00	Average	H	-	-	-83.24	17.07	0.00	40.83	53.98	-13.15
* 11000.00	Peak	H	-	-	-71.33	17.07	0.00	52.74	73.98	-21.24
16500.00	Peak	V	-	-	-72.97	23.05	0.00	57.08	68.20	-11.12
22000.00	Peak	V	-	-	-65.72	18.43	-9.54	50.16	68.20	-18.04
27500.00	Peak	V	-	-	-63.04	20.02	-9.54	54.44	68.20	-13.76

**Table 7-27. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5600MHz  
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
11200.00	Average	H	-	-	-83.84	17.21	0.00	40.37	53.98	-13.61
11200.00	Peak	H	-	-	-72.39	17.21	0.00	51.82	73.98	-22.16
16800.00	Peak	H	-	-	-72.29	22.51	0.00	57.22	68.20	-10.98
22400.00	Average	V	-	-	-71.83	19.18	-9.54	44.81	53.98	-9.17
22400.00	Peak	V	-	-	-64.69	19.18	-9.54	51.95	73.98	-22.03
28000.00	Peak	V	-	-	-64.09	20.40	-9.54	53.76	68.20	-14.44

**Table 7-28. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 33 of 85

Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	V	-	-	-82.05	19.97	0.00	44.92	53.98	-9.06
* 11200.00	Peak	V	-	-	-70.35	19.97	0.00	56.62	73.98	-17.36
16800.00	Peak	V	-	-	-71.69	28.82	0.00	64.13	68.20	-4.07
* 22400.00	Average	V	-	-	-71.83	19.18	-9.54	44.81	53.98	-9.17
* 22400.00	Peak	V	-	-	-64.69	19.18	-9.54	51.95	73.98	-22.03
28000.00	Peak	V	-	-	-64.09	-4.74	-9.54	28.63	68.20	-39.57

**Table 7-29. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	H	-	-	-83.88	18.12	0.00	41.24	53.98	-12.74
* 11440.00	Peak	H	-	-	-72.42	18.12	0.00	52.70	73.98	-21.28
17160.00	Peak	H	-	-	-72.03	22.54	0.00	57.51	68.20	-10.69
* 22880.00	Average	V	-	-	-73.07	18.88	-9.54	43.27	53.98	-10.71
* 22880.00	Peak	V	-	-	-65.97	18.88	-9.54	50.36	73.98	-23.62
28600.00	Peak	V	-	-	-63.14	20.08	-9.54	54.40	68.20	-13.80

**Table 7-30. Radiated Measurements SISO ANT2 with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 34 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	V	400	93	-83.52	20.36	0.00	43.84	53.98	-10.14
* 11490.00	Peak	V	400	93	-70.73	20.36	0.00	56.63	73.98	-17.35
17235.00	Peak	V	-	-	-72.29	29.51	0.00	64.22	68.20	-3.98
* 22980.00	Average	V	-	-	-71.74	19.03	-9.54	44.75	53.98	-9.23
* 22980.00	Peak	V	-	-	-64.82	19.03	-9.54	51.67	73.98	-22.31
28725.00	Peak	V	-	-	-63.12	-5.89	-9.54	28.45	68.20	-39.75

**Table 7-31. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-83.60	21.02	0.00	44.42	53.98	-9.56
* 11570.00	Peak	V	-	-	-73.15	21.02	0.00	54.87	73.98	-19.11
17355.00	Peak	V	-	-	-74.05	29.63	0.00	62.58	68.20	-5.62
23140.00	Peak	V	-	-	-65.08	18.82	-9.54	51.20	68.20	-17.00
28925.00	Peak	V	-	-	-62.75	-5.04	-9.54	29.67	68.20	-38.53

**Table 7-32. Radiated Measurements SISO ANT2**

FCC ID: ZNFV450VM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 35 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11650.00	Average	V	400	4	-83.48	21.21	0.00	44.73	53.98	-9.25
* 11650.00	Peak	V	400	4	-71.72	21.21	0.00	56.49	73.98	-17.49
17475.00	Peak	V	-	-	-73.58	29.76	0.00	63.18	68.20	-5.02
23300.00	Peak	V	-	-	-64.14	18.40	-9.54	51.72	68.20	-16.48
29125.00	Peak	V	-	-	-61.91	-7.31	-9.54	28.24	68.20	-39.96

**Table 7-33. Radiated Measurements SISO ANT2**


Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-83.43	21.02	0.00	44.59	53.98	-9.39
* 11570.00	Peak	V	-	-	-73.08	21.02	0.00	54.94	73.98	-19.04
17355.00	Peak	V	-	-	-73.09	29.63	0.00	63.54	68.20	-4.66
23140.00	Peak	V	-	-	-69.20	18.82	-9.54	47.08	68.20	-21.12
28925.00	Peak	V	-	-	-53.39	-5.04	-9.54	39.03	68.20	-29.17


**Table 7-34. Radiated Measurements SISO ANT2 with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 36 of 85


### 7.2.3. MIMO/CDD Radiated Spurious Emission Measurements



**Plot 7-13. Radiated Spurious Plot above 1GHz MIMO/CDD (802.11a – U1 Ch. 40)**




**Plot 7-14. Radiated Spurious Plot above 1GHz MIMO/CDD (802.11a – U2A Ch. 56)**



**Plot 7-15. Radiated Spurious Plot above 1GHz MIMO/CDD (802.11a – U2C Ch. 120)**


FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 37 of 85




**Plot 7-16. Radiated Spurious Plot above 1GHz MIMO/CDD (802.11a – U3 Ch. 157)**

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 38 of 85

### MIMO/CDD Radiated Spurious Emissions Measurements (Above 18GHz)



**Plot 7-17. Radiated Spurious Plot above 18GHz - 26.5GHz MIMO/CDD (802.11a)**



**Plot 7-18. Radiated Spurious Plot 26.5GHz - 40GHz MIMO/CDD (802.11a)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 39 of 85

## MIMO/CDD Radiated Spurious Emission Measurements

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	-	-	-70.72	18.99	0.00	55.27	68.20	-12.93
* 15540.00	Average	V	-	-	-84.44	27.73	0.00	50.29	53.98	-3.69
* 15540.00	Peak	V	-	-	-71.92	27.73	0.00	62.81	73.98	-11.17
* 20720.00	Average	V	-	-	-81.07	17.17	-9.54	33.56	53.98	-20.42
* 20720.00	Peak	V	-	-	-69.14	17.17	-9.54	45.49	73.98	-28.49
25900.00	Peak	V	-	-	-68.15	19.34	-9.54	48.65	68.20	-19.55

Table 7-35. Radiated Measurements MIMO/CDD

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	-	-	-70.87	19.36	0.00	55.49	68.20	-12.71
* 15600.00	Average	V	-	-	-84.37	27.61	0.00	50.24	53.98	-3.74
* 15600.00	Peak	V	-	-	-72.76	27.61	0.00	61.85	73.98	-12.13
* 20800.00	Average	V	-	-	-80.55	17.31	-9.54	34.21	53.98	-19.77
* 20800.00	Peak	V	-	-	-68.08	17.31	-9.54	46.69	73.98	-27.29
26000.00	Peak	V	-	-	-68.11	19.60	-9.54	48.95	68.20	-19.25

Table 7-36. Radiated Measurements MIMO/CDD

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 40 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.95	19.72	0.00	55.77	68.20	-12.43
* 15720.00	Average	V	-	-	-85.15	27.41	0.00	49.26	53.98	-4.72
* 15720.00	Peak	V	-	-	-73.29	27.41	0.00	61.12	73.98	-12.86
* 20960.00	Average	V	-	-	-80.85	17.60	-9.54	34.20	53.98	-19.78
* 20960.00	Peak	V	-	-	-69.30	17.60	-9.54	45.76	73.98	-28.22
26200.00	Peak	V	-	-	-68.33	19.73	-9.54	48.85	68.20	-19.35

**Table 7-37. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.56	15.01	0.00	51.45	68.20	-16.75
* 15720.00	Average	V	-	-	-85.09	23.64	0.00	45.55	53.98	-8.43
* 15720.00	Peak	V	-	-	-73.08	23.64	0.00	57.56	73.98	-16.42
* 20960.00	Average	V	-	-	-81.35	17.60	-9.54	33.70	53.98	-20.28
* 20960.00	Peak	V	-	-	-69.60	17.60	-9.54	45.45	73.98	-28.53
26200.00	Peak	V	-	-	-68.42	19.73	-9.54	48.76	68.20	-19.44

**Table 7-38. Radiated Measurements MIMO/CDD with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 41 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-70.66	19.44	0.00	55.78	68.20	-12.42
* 15780.00	Average	V	-	-	-85.03	27.10	0.00	49.07	53.98	-4.91
* 15780.00	Peak	V	-	-	-73.02	27.10	0.00	61.08	73.98	-12.90
* 21040.00	Average	V	-	-	-80.70	17.67	-9.54	34.42	53.98	-19.55
* 21040.00	Peak	V	-	-	-69.73	17.67	-9.54	45.40	73.98	-28.58
26300.00	Peak	V	-	-	-68.22	20.29	-9.54	49.52	68.20	-18.68

**Table 7-39. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-70.75	19.62	0.00	55.87	68.20	-12.33
* 15840.00	Average	V	-	-	-83.91	27.05	0.00	50.14	53.98	-3.84
* 15840.00	Peak	V	-	-	-71.96	27.05	0.00	62.09	73.98	-11.89
* 21120.00	Average	V	-	-	-80.79	17.83	-9.54	34.51	53.98	-19.47
* 21120.00	Peak	V	-	-	-68.96	17.83	-9.54	46.33	73.98	-27.65
26400.00	Peak	V	-	-	-68.38	20.07	-9.54	49.15	68.20	-19.05

**Table 7-40. Radiated Measurements MIMO/CDD**

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 42 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	V	-	-	-83.37	19.97	0.00	43.60	53.98	-10.38
* 10640.00	Peak	V	-	-	-70.47	19.97	0.00	56.50	73.98	-17.48
* 15960.00	Average	V	-	-	-84.77	27.35	0.00	49.58	53.98	-4.40
* 15960.00	Peak	V	-	-	-72.76	27.35	0.00	61.59	73.98	-12.39
* 21280.00	Average	V	-	-	-80.77	17.98	-9.54	34.66	53.98	-19.32
* 21280.00	Peak	V	-	-	-69.61	17.98	-9.54	45.83	73.98	-28.15
26600.00	Peak	V	-	-	-53.90	-5.12	-9.54	38.43	68.20	-29.77

**Table 7-41. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10640.00	Average	V	-	-	-83.66	17.01	0.00	40.35	53.98	-13.63
* 10640.00	Peak	V	-	-	-71.37	17.01	0.00	52.64	73.98	-21.34
* 15960.00	Average	V	-	-	-84.62	22.56	0.00	44.94	53.98	-9.04
* 15960.00	Peak	V	-	-	-72.07	22.56	0.00	57.49	73.98	-16.49
* 21280.00	Average	V	-	-	-81.04	17.98	-9.54	34.39	53.98	-19.58
21280.00	Peak	V	-	-	-70.14	17.98	-9.54	45.29	73.98	-28.68
26600.00	Peak	V	-	-	-54.04	-5.12	-9.54	38.30	68.20	-29.90

**Table 7-42. Radiated Measurements MIMO/CDD with WCP**

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset		Page 43 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	V	354	39	-83.18	20.31	0.00	44.13	53.98	-9.85
* 11000.00	Peak	V	354	39	-71.16	20.31	0.00	56.15	73.98	-17.83
16500.00	Peak	V	-	-	-71.67	28.49	0.00	63.82	68.20	-4.38
22000.00	Peak	V	-	-	-70.36	18.43	-9.54	45.53	68.20	-22.67
27500.00	Peak	V	-	-	-52.34	-6.38	-9.54	38.73	68.20	-29.47

**Table 7-43. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5600MHz  
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	V	-	-	-83.88	19.97	0.00	43.09	53.98	-10.89
* 11200.00	Peak	V	-	-	-72.00	19.97	0.00	54.97	73.98	-19.01
16800.00	Peak	V	-	-	-72.46	28.82	0.00	63.36	68.20	-4.84
* 22400.00	Average	V	-	-	-81.23	19.18	-9.54	35.41	53.98	-18.57
* 22400.00	Peak	V	-	-	-69.66	19.18	-9.54	46.98	73.98	-27.00
28000.00	Peak	V	-	-	-53.24	-4.74	-9.54	39.48	68.20	-28.72

**Table 7-44. Radiated Measurements MIMO/CDD**

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 44 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-84.16	20.26	0.00	43.10	53.98	-10.88
* 11440.00	Peak	V	-	-	-72.22	20.26	0.00	55.04	73.98	-18.94
17160.00	Peak	V	-	-	-72.10	29.62	0.00	64.52	68.20	-3.68
* 22880.00	Average	V	-	-	-81.23	18.88	-9.54	35.10	53.98	-18.88
* 22880.00	Peak	V	-	-	-69.35	18.88	-9.54	46.99	73.98	-26.99
28600.00	Peak	V	-	-	-53.21	-6.22	-9.54	38.02	68.20	-30.18

**Table 7-45. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	V	355	14	-83.54	17.07	0.00	40.53	53.98	-13.45
* 11000.00	Peak	V	355	14	-71.75	17.07	0.00	52.32	73.98	-21.66
16500.00	Peak	V	-	-	-72.87	23.05	0.00	57.18	68.20	-11.02
22000.00	Peak	V	-	-	-64.12	18.43	-9.54	51.77	68.20	-16.43
27500.00	Peak	V	-	-	-54.14	-6.38	-9.54	36.93	68.20	-31.27

**Table 7-46. Radiated Measurements MIMO/CDD with WCP**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 45 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	V	349	65	-84.19	20.36	0.00	43.17	53.98	-10.81
* 11490.00	Peak	V	349	65	-71.52	20.36	0.00	55.84	73.98	-18.14
17235.00	Peak	V	132	282	-72.67	29.51	0.00	63.84	68.20	-4.36
* 22980.00	Average	V	-	-	-81.22	19.03	-9.54	35.27	53.98	-18.71
* 22980.00	Peak	V	-	-	-69.69	19.03	-9.54	46.79	73.98	-27.18
28725.00	Peak	V	-	-	-52.23	-5.89	-9.54	39.34	69.20	-29.86

**Table 7-47. Radiated Measurements MIMO/CDD**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-83.47	21.02	0.00	44.55	53.98	-9.43
* 11570.00	Peak	V	-	-	-71.51	21.02	0.00	56.51	73.98	-17.47
17355.00	Peak	V	-	-	-74.06	29.63	0.00	62.57	68.20	-5.63
23140.00	Peak	V	-	-	-70.10	18.82	-9.54	46.17	68.20	-22.03
28925.00	Peak	V	-	-	-52.07	-5.04	-9.54	40.34	68.20	-27.86

**Table 7-48. Radiated Measurements MIMO/CDD**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 46 of 85

Worst Case Mode: 802.11a  
Worst Case Transfer Rate: 6Mbps  
Distance of Measurements: 1 & 3 Meters  
Operating Frequency: 5825MHz  
Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-83.64	21.21	0.00	44.57	53.98	-9.41
* 11650.00	Peak	V	-	-	-71.87	21.21	0.00	56.34	73.98	-17.64
17475.00	Peak	V	-	-	-73.12	29.76	0.00	63.64	68.20	-4.56
23300.00	Peak	V	-	-	-68.84	18.40	-9.54	47.02	68.20	-21.18
29125.00	Peak	V	-	-	-52.37	-7.31	-9.54	37.79	68.20	-30.41

**Table 7-49. Radiated Measurements MIMO/CDD**


Worst Case Mode: 802.11a  
Worst Case Transfer Rate: 6Mbps  
Distance of Measurements: 1 & 3 Meters  
Operating Frequency: 5745MHz  
Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	V	121	337	-84.33	18.05	0.00	40.72	53.98	-13.26
* 11490.00	Peak	V	121	337	-72.44	18.05	0.00	52.61	73.98	-21.37
17235.00	Peak	V	128	321	-72.34	22.88	0.00	57.54	68.20	-10.66
22980.00	Average	V	-	-	-74.45	19.03	-9.54	42.04	53.98	-11.94
22980.00	Peak	V	-	-	-71.34	19.03	-9.54	45.15	73.98	-28.83
28725.00	Peak	V	-	-	-53.12	-5.89	-9.54	38.45	69.20	-30.75


**Table 7-50. Radiated Measurements MIMO/CDD with WCP**

FCC ID: ZNFV450VM		<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 47 of 85

## MIMO/CDD Radiated Spurious Emissions Measurements (Above 18GHz)



**Plot 7-19. Radiated Spurious Plot above 18GHz - 26.5GHz MIMO/CDD (802.11a)**




**Plot 7-20. Radiated Spurious Plot 26.5GHz - 40GHz MIMO/CDD (802.11a)**

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 48 of 85


### 7.2.4. Simultaneous Tx Radiated Spurious Emissions Measurements (Below 1GHz) §15.209; RSS-Gen [8.9]

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1	2
Channel	6	36
Operating Frequency (MHz)	2437MHz	5180MHz
Data Rate (Mbps)	1Mbps	6Mbps
Mode	b	a

Table 7-51. Config-1 (ANT1 2.4GHz & ANT2 5GHz)




Plot 7-21. Radiated Spurious Plot below 1GHz (2.4GHz – 5GHz)




Plot 7-22. Radiated Spurious Plot above 1GHz (2.4GHz – 5GHz)

FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 49 of 85



**Plot 7-23. Radiated Spurious Plot 18GHz - 26.5GHz (Dual Band Simult. Tx)**



**Plot 7-24. Radiated Spurious Plot above 26.5GHz (Dual Band Simult. Tx)**


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 50 of 85

### 7.2.5. SISO Antenna-1 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




**Plot 7-25. Radiated Lower Band Edge Plot (Average – UNII Band 1)**




**Plot 7-26. Radiated Lower Band Edge Plot (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




**Plot 7-27. Radiated Upper Band Edge Plot (Average – UNII Band 2A)**




**Plot 7-28. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 51 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-29. Radiated Lower Band Edge Plot (Average – UNII Band 2C)**



**Plot 7-30. Radiated Lower Band Edge Plot (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-31. Radiated Upper Band Edge Plot (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1-ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 52 of 85	

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100



**Plot 7-32. Radiated Band Edge Plot (Average – WCP)**




**Plot 7-33. Radiated Band Edge Plot (Peak – WCP)**


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1-ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 53 of 85

### 7.2.6. SISO Antenna-1 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38




**Plot 7-34. Radiated Lower Band Edge Plot (Average – UNII Band 1)**




**Plot 7-35. Radiated Lower Band Edge Plot (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62




**Plot 7-36. Radiated Upper Band Edge Plot (Average – UNII Band 2A)**




**Plot 7-37. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 54 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5510MHz  
 Channel: 102




**Plot 7-38. Radiated Lower Band Edge Plot (Average – UNII Band 2C)**



**Plot 7-39. Radiated Lower Band Edge Plot (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5795MHz  
 Channel: 159




**Plot 7-40. Radiated Upper Band Edge Plot (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1-ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 55 of 85	

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5310MHz  
 Channel: 62



**Plot 7-41. Radiated Band Edge Plot (Average – WCP)**




**Plot 7-42. Radiated Band Edge Plot (Peak – WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 56 of 85

### 7.2.7. SISO Antenna-1 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




**Plot 7-43. Radiated Lower Band Edge Plot (Average – UNII Band 1)**




**Plot 7-44. Radiated Lower Band Edge Plot (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58




**Plot 7-45. Radiated Upper Band Edge Plot (Average – UNII Band 2A)**




**Plot 7-46. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 57 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106




**Plot 7-47. Radiated Lower Band Edge Plot (Average – UNII Band 2C)**



**Plot 7-48. Radiated Lower Band Edge Plot (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5775MHz  
 Channel: 155




**Plot 7-49. Radiated Upper Band Edge Plot (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1-ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 58 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106



**Plot 7-50. Radiated Band Edge Plot (Average – WCP)**




**Plot 7-51. Radiated Band Edge Plot (Peak – WCP)**


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10- R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 59 of 85

### 7.2.8. SISO Antenna-2 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




**Plot 7-52. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1)**




**Plot 7-53. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




**Plot 7-54. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A)**




**Plot 7-55. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 60 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-56. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C)**



**Plot 7-57. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165



**Plot 7-58. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 61 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-59. Radiated Band Edge Plot SISO ANT2 (Average - WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 62 of 85

### 7.2.9. SISO Antenna-2 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38




**Plot 7-60. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1)**




**Plot 7-61. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62




**Plot 7-62. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A)**




**Plot 7-63. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 63 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5510MHz  
 Channel: 102




**Plot 7-64. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C)**



**Plot 7-65. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5795MHz  
 Channel: 159




**Plot 7-66. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 64 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5510MHz  
 Channel: 102



**Plot 7-67. Radiated Band Edge Plot SISO ANT2 (Average – WCP)**




**Plot 7-68. Radiated Band Edge Plot SISO ANT2 (Peak – WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 65 of 85

### 7.2.10. SISO Antenna-2 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




**Plot 7-69. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1)**




**Plot 7-70. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1)**

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58




**Plot 7-71. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A)**




**Plot 7-72. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 66 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106




**Plot 7-73. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C)**



**Plot 7-74. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5775MHz  
 Channel: 155




**Plot 7-75. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 67 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5290MHz  
 Channel: 58



**Plot 7-76. Radiated Band Edge Plot SISO ANT2 (Average – WCP)**




**Plot 7-77. Radiated Band Edge Plot SISO ANT2 (Peak – WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 68 of 85

### 7.2.11. CDD Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36




**Plot 7-78. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)**




**Plot 7-79. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)**

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64




**Plot 7-80. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)**




**Plot 7-81. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 69 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-82. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)**



**Plot 7-83. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)**


Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-84. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 70 of 85

Worst Case Mode: 802.11a  
 Worst Case Transfer Rate: 6Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64



**Plot 7-85. Radiated Band Edge Plot MIMO (Average – WCP)**




**Plot 7-86. Radiated Band Edge Plot MIMO (Peak – WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 71 of 85

## 7.2.12. MIMO Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




**Plot 7-87. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)**




**Plot 7-88. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)**

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




**Plot 7-89. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)**




**Plot 7-90. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 72 of 85

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-91. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)**



**Plot 7-92. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)**


Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-93. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)**

FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 73 of 85

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64



**Plot 7-94. Radiated Band Edge Plot MIMO (Average – WCP)**




**Plot 7-95. Radiated Band Edge Plot MIMO (Peak – WCP)**


<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 74 of 85

### 7.2.13. MIMO Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5190MHz  
 Channel: 38




**Plot 7-96. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)**




**Plot 7-97. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)**

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5310MHz  
 Channel: 62




**Plot 7-98. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)**




**Plot 7-99. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 75 of 85

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5510MHz  
 Channel: 102




**Plot 7-100. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)**



**Plot 7-101. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)**


Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5795MHz  
 Channel: 159




**Plot 7-102. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 76 of 85

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5310MHz  
 Channel: 62



**Plot 7-103. Radiated Band Edge Plot ANT (Average – WCP)**




**Plot 7-104. Radiated Band Edge Plot ANT (Peak – WCP)**


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 77 of 85

### 7.2.14. MIMO Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5210MHz  
 Channel: 42




**Plot 7-105. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)**




**Plot 7-106. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)**

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5290MHz  
 Channel: 58




**Plot 7-107. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)**




**Plot 7-108. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)**

FCC ID: ZNFV450VM			<b>MEASUREMENT REPORT          (CLASS II PERMISSIVE CHANGE)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset		Page 78 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106




**Plot 7-109. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)**



**Plot 7-110. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)**


Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5775MHz  
 Channel: 155




**Plot 7-111. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)**

FCC ID: ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 79 of 85

Worst Case Mode: 802.11ac  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5290MHz  
 Channel: 58



**Plot 7-112. Radiated Band Edge Plot ANT (Average – WCP)**



**Plot 7-113. Radiated Band Edge Plot ANT (Peak – WCP)**

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT</b> <b>(CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 80 of 85

### 7.3 Radiated Spurious Emissions Measurements – Below 1GHz §15.209; RSS-Gen [8.9]

#### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

*All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-52 per Section 15.209 and RSS-Gen (8.9).*

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-52. Radiated Limits

#### Test Procedures Used

ANSI C63.10-2013

#### Test Settings


##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10- R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 81 of 85

### Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-2. Radiated Test Setup < 30MHz**



**Figure 7-3. Radiated Test Setup < 1GHz**


FCC ID: ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		Approved by: Quality Manager
Test Report S/N: 1M1903070034-10-R1.ZNF	Test Dates: 3/21/2019-5/3/2019	EUT Type: Portable Handset	Page 82 of 85

**Test Notes**

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-52.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 83 of 85

**Radiated Spurious Emissions Measurements (Below 1GHz)**  
**§15.209; RSS-Gen [8.9]**



**Plot 7-114. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157)**

<b>FCC ID:</b> ZNFV450VM	<b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10-R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 84 of 85

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFV450VM** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.

<b>FCC ID:</b> ZNFV450VM	 <b>MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1903070034-10- R1.ZNF	<b>Test Dates:</b> 3/21/2019-5/3/2019	<b>EUT Type:</b> Portable Handset	Page 85 of 85