

APPENDIX D: TOTAL EXPOSURE RATIO

FCC ID: ZNFV600VM	 NEAR-FIELD POWER DENSITY EVALUATION REPORT 	Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset	APPENDIX D: Page 1 of 6

The Total Exposure Ratio (TER) is calculated by combining all SAR measurements and power density measurements after normalizing to their respective limits. The general expression is below.

$$TER = \sum_{a=1}^A \frac{SAR_a}{SAR_a, limit} + \sum_{b=1}^B \frac{psPD_b}{psPD_b, limit} < 1$$

The TER shall be less than unity to ensure compliance with the limits.

$$\sum_{n=1}^N \frac{4G SAR_n}{4G SAR_n, limit} + \sum_{m=1}^M \frac{5G mmW NR psPD_m}{5G mmW NR psPD_m, limit} + \sum_{p=1}^P \frac{WLAN SAR_p}{WLAN SAR_p, limit} < 1$$

Qualcomm® Smart Transmit algorithm for WWAN adds directly the time-averaged RF exposure from 4G and time-averaged RF exposure from 5G mmW NR. Smart Transmit algorithm controls the total RF exposure from both 4G and 5G mmW NR to not exceed FCC limit. Therefore, per FCC guidance, TER does not need to be evaluated directly for the 4G and 5G simultaneous compliance via summation. The following equations are derived later in Appendix D. The validation of the time-averaging algorithm and compliance under the Tx varying transmission scenario for WWAN technologies are reported in Part 2 report. The report SN could be found in Bibliography section.

$$\sum_{n=1}^N \frac{4G SAR_n}{4G SAR_n, limit} + \sum_{p=1}^P \frac{WLAN SAR_p}{WLAN SAR_p, limit} < 1$$

$$\sum_{m=1}^M \frac{5G mmW NR psPD_m}{5G mmW NR psPD_m, limit} + \sum_{p=1}^P \frac{WLAN SAR_p}{WLAN SAR_p, limit} < 1$$

For 5G mmW NR, since there is total design-related uncertainty arising from TxAGC and device-to-device variation, the worst-case RF exposure should be determined by accounting for this device uncertainty of 2.8 dB. Smart Transmit algorithm limits PD exposure to 75% of maximum to provide at least 25% margin allocated for 4G LTE anchor due to the 3 dB reserve power margin used in the device. Therefore, 5G mmW NR RF exposure for this DUT is evaluated by reported psPD calculated as:

$$reported_psPD = 75\% \times PD_design_target + 2.8 dB = 7.5 W/m^2$$

Note that since not all the beams supported by this EUT are measured, *reported_psPD* cannot be computed based on limited *measured psPD* data. Alternatively, since *measured psPD* for all the beams will be $\leq PD_design_target + 2.8 dB$ uncertainty, *reported_psPD* is computed based on this worst-case PSPD as shown above.

FCC ID: ZNFV600VM	 NEAR-FIELD POWER DENSITY EVALUATION REPORT 	Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset	APPENDIX D: Page 2 of 6

The compliance analysis for simultaneous transmission scenarios of WWAN (4G LTE & 5G mmW NR) with Smart Transmit and 4G & WLAN can be found in two reports indicated in the table below. This appendix demonstrates compliance for the 5G + WLAN scenarios. The report SNs can be found in Bibliography section.

	Simultaneous Scenario	Evaluation Report
1.	4G LTE WWAN + WLAN	FCC SAR Evaluation Report (Part 1)
2.	4G LTE WWAN + 5G mmW NR WWAN	RF Exposure Part 2 Test Report

RF exposure compliance with 5G mmW NR WWAN+WLAN simultaneous transmission scenarios is demonstrated for various radio configurations below.

Note that the above *reported psPD* applies to the worst-surface of the DUT at 2mm evaluation distance. For this DUT, the worst-surface(s) are listed in Table 1-9.

Worst-case PD on other surfaces of the DUT are calculated from simulated PD data (see Section 4.6 of Power Density Simulation Report, report SN could be found in Section 1.7 - Bibliography), by multiplying reported psPD with the highest proportion out of all beams and out of all three channels in each band, where the adjustment for each beam/channel is computed as the proportion of “simulated PD on desired surface” to “simulated PD on worst-surface”. For example, to determine worst-case PD on front surface (needed for Head RF Exposure evaluation during simultaneous transmission), highest proportion of (simulated PD on front surface)/(simulated PD on worst surface) was determined out of all supported beams and out of all three channels by the DUT in each band.

In some cases, the simulation vs measurement for some surfaces can exceed the device's total uncertainty. In those cases, if the measured psPD > simulated adjusted psPD (assuming a linear congruency of the psPD across surfaces), then 75% of the measured value (based on the 3 dB reserve power margin) should be used towards the simultaneous TX analysis. Table D-1 lists the relevant worst-case reported psPD values based on the additional surfaces and evaluation distances needed to perform the TER analysis. The highest of the adjusted Reported_psPD and Measured Total psPD* 0.75 was chosen for TER analysis and the chosen values are indicated by bolded psPD values.

FCC ID: ZNFV600VM	 PCTEST NEAR-FIELD POWER DENSITY EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset	APPENDIX D: Page 3 of 6	

**Table D-1
5G mmW NR psPD**

NR Band	Surface	Evaluation Distance (mm)	Adjustment Factor due to Simulation	Adjusted Reported psPD (W/m2)	Measured Total psPD (W/m2)	Reported Total psPD x 0.75 (W/m2)
n261	Back	2	1.000	7.500	-	-
	Front	2	0.583	4.373	1.86	1.395
	Top	2	0.176	1.320	1.2	0.900
	Right	2	1.000	7.500	-	-
	Left	2	0.935	7.013	2.93	2.198
n260	Back	2	1.000	7.500	-	-
	Front	2	0.621	4.658	1.35	1.0125
	Top	2	0.120	0.900	0.86	0.645
	Right	2	1.000	7.500	-	-
	Left	2	0.869	6.518	1.72	1.290

Note: Adjusted factor is (simulated PD on desired exposure plane)/(PD on worst-surface at 2mm evaluation distance) out of all beams and out of all channels. See Power Density Simulation Report, report SN could be found in Section 1.7 – Bibliography.

FCC ID: ZNFV600VM	 NEAR-FIELD POWER DENSITY EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset	APPENDIX D: Page 4 of 6	

Table D-2
5G mmW NR Head Total Exposure Ratio

	psPD	2.4 GHz WLAN Ant1 at 14.5 dBm	2.4 GHz WLAN Ant2 at 14.5 dBm	2.4 GHz WLAN MIMO at 17.5 dBm	Bluetooth	5 GHz WLAN Ant1 at 14 dBm	5 GHz WLAN Ant2 at 14 dBm	5 GHz WLAN MIMO at 17 dBm	psPD + 2.4 GHz WLAN Ant1	psPD + 2.4 GHz WLAN Ant2	psPD + 2.4 GHz WLAN MIMO	psPD + 2.4 GHz WLAN Ant2 + BT	psPD + BT+ 5 GHz WLAN Ant1	psPD + BT+ 5 GHz WLAN Ant2	psPD + BT+ 5 GHz WLAN MIMO	psPD + 2.4 GHz WLAN MIMO + 5 GHz WLAN MIMO
		Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	WLAN Ant1	WLAN Ant2	WLAN MIMO	WLAN Ant2 + BT	WLAN Ant1	WLAN Ant2	WLAN MIMO
	W/m ²	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	1+2	1+3	1+4	1+3+5	1+5+6	1+5+7	1+5+8	1+4+8
Applicable Limit	10.0	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Reported Value	4.558	0.437	0.442	0.513	0.279	0.328	0.271	0.321								
Ratio to Limit	0.466	0.273	0.276	0.321	0.174	0.205	0.169	0.201	0.739	0.742	0.786	0.916	0.845	0.810	0.841	0.987

Table D-3
5G mmW NR Body-Worn Total Exposure Ratio - Back Side at 10 mm

	psPD	2.4 GHz WLAN Ant1 at 19.5 dBm	2.4 GHz WLAN Ant2 at 19.5 dBm	2.4 GHz WLAN MIMO at 17.5 dBm	Bluetooth	5 GHz WLAN Ant1 at 17 dBm	5 GHz WLAN Ant2 at 17 dBm	5 GHz WLAN MIMO at 17 dBm	psPD + 2.4 GHz WLAN Ant1	psPD + 2.4 GHz WLAN Ant2	psPD + 2.4 GHz WLAN Ant1 + 2.4 GHz WLAN Ant2	psPD + 2.4 GHz WLAN Ant2 + BT	psPD + BT+ 5 GHz WLAN Ant1	psPD + BT+ 5 GHz WLAN Ant2	psPD + BT+ 5 GHz WLAN MIMO	psPD + 2.4 GHz WLAN MIMO + 5 GHz WLAN MIMO
		Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	WLAN Ant1	WLAN Ant2	WLAN Ant1 + 2.4 GHz WLAN Ant2	WLAN Ant2 + BT	WLAN Ant1	WLAN Ant2	WLAN MIMO
	W/m ²	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	1+2	1+3	1+2+3	1+3+5	1+5+6	1+5+7	1+5+8	1+4+8
Applicable Limit	10.0	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Reported Value	7.500	0.189	0.139	0.101	0.036	0.313	0.314	0.157	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911
Ratio to Limit	0.750	0.118	0.087	0.063	0.023	0.196	0.196	0.098	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911

Table D-4
5G mmW NR Hotspot Total Exposure Ratio

	psPD	2.4 GHz WLAN Ant1 at 19.5 dBm	2.4 GHz WLAN Ant2 at 19.5 dBm	2.4 GHz WLAN MIMO at 17.5 dBm	Bluetooth	5 GHz WLAN Ant1 at 17 dBm	5 GHz WLAN Ant2 at 17 dBm	5 GHz WLAN MIMO at 17 dBm	psPD + 2.4 GHz WLAN Ant1	psPD + 2.4 GHz WLAN Ant2	psPD + 2.4 GHz WLAN Ant1 + 2.4 GHz WLAN Ant2	psPD + 2.4 GHz WLAN Ant2 + BT	psPD + BT+ 5 GHz WLAN Ant1	psPD + BT+ 5 GHz WLAN Ant2	psPD + BT+ 5 GHz WLAN MIMO	psPD + 2.4 GHz WLAN MIMO + 5 GHz WLAN MIMO
		Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	Reported SAR	WLAN Ant1	WLAN Ant2	WLAN Ant1 + 2.4 GHz WLAN Ant2	WLAN Ant2 + BT	WLAN Ant1	WLAN Ant2	WLAN MIMO
	W/m ²	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	W/kg	1+2	1+3	1+2+3	1+3+5	1+5+6	1+5+7	1+5+8	1+4+8
Applicable Limit	10.0	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Back Side at 10mm	7.500	0.189	0.139	0.101	0.036	0.313	0.314	0.157	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911
Ratio to Limit	0.750	0.118	0.087	0.063	0.023	0.196	0.196	0.098	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911
Front Side at 10mm	4.558	0.29	0.21*	0.162	0.059	0.313*	0.248*	0.125*	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911
Ratio to Limit	0.466	0.181	0.136	0.101	0.036	0.196	0.156	0.078	0.868	0.837	0.955	0.859	0.969	0.969	0.871	0.911
Top Edge at 10mm	1.320	0.420*	0.314	0.362	0.038	0.313*	0.128	0.125*	0.395	0.328	0.591	0.352	0.351	0.236	0.234	0.436
Ratio to Limit	0.132	0.263	0.196	0.226	0.024	0.196	0.080	0.078	0.395	0.328	0.591	0.352	0.351	0.236	0.234	0.436
Right Edge at 10mm	7.500	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.750	0.750	0.750	0.750	0.750	0.750	0.750	0.750
Reported Value	7.500	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.750	0.750	0.750	0.750	0.750	0.750	0.750	0.750
Ratio to Limit	0.750	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.750	0.750	0.750	0.750	0.750	0.750	0.750	0.750
Left Edge at 10mm	7.013	0.420	0.024	0.116	0.102	0.313*	0.248*	0.125*	0.964	0.716	0.979	0.780	0.901	0.920	0.843	0.852
Ratio to Limit	0.701	0.263	0.015	0.073	0.064	0.196	0.155	0.078	0.964	0.716	0.979	0.780	0.901	0.920	0.843	0.852

* Note: For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst-case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.

Table D-5
5G mmW NR Phablet Total Exposure Ratio

	psPD	5 GHz WLAN Ant1 at 17 dBm	5 GHz WLAN Ant2 at 17 dBm	5 GHz WLAN MIMO at 17 dBm	psPD + 5 GHz WLAN Ant1	psPD + 5 GHz WLAN Ant2	psPD + 5 GHz WLAN MIMO
		Reported SAR	Reported SAR	Reported SAR	WLAN Ant1	WLAN Ant2	WLAN MIMO
	W/m ²	W/kg	W/kg	W/kg	1+2	1+3	1+4
Applicable Limit	10.0	4.0	4.0	4.0	1.0	1.0	1.0
Reported Value	7.500	0.909	0.858	0.735			
Ratio to Limit	0.750	0.227	0.215	0.184	0.977	0.965	0.934

FCC ID: ZNFV600VM		NEAR-FIELD POWER DENSITY EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset			APPENDIX D: Page 5 of 6

Notes:

1. Worst-case power density results for each test configuration among all antenna arrays (QTM-0, QTM-1, QTM-2) and among all supported bands (n261, n260) were considered for TER analysis.
2. For back side, front side, top edge, left edge, and right edge, power density results at 2 mm were considered as a more conservative evaluation for 10 mm body-worn/hotspot.
3. Per FCC guidance, the bands/modes that are not required to be evaluated for Phablet SAR are not considered for TER analysis.
4. Per FCC guidance, for power density measurements, a test separation distance of 2 mm was used for phablet configuration due to probe restraints.
5. Worst-case front side reported psPD was considered for Head TER analysis.
6. The worst-case between Adjusted Reported_psPD and Measured Total psPD x 0.75 was chosen for TER analysis. The bolded psPD values in Table D-1 indicate the worst-case Reported psPD used in TER analysis.

The above numerical summed PD and SAR for all the worst-case simultaneous transmission conditions were below the Total Exposure Ratio. Therefore, the above analysis is sufficient to determine no further test cases are required and that simultaneous transmission is compliant to the FCC RF Exposure Limit.

FCC ID: ZNFV600VM	 NEAR-FIELD POWER DENSITY EVALUATION REPORT 	Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset	APPENDIX D: Page 6 of 6

Mathematical Derivation of TER Compliance

$$\text{Total Normalized RFx} = \text{Normalized RFx}_{\text{Time Averaged WWAN}} + \text{Normalized RFx}_{\text{WLAN}} \leq 1.0 \quad (1)$$

Since WWAN Smart Transmit algorithm adds directly the time-averaged RF exposure from 4G and time-averaged RF exposure from 5G mmW NR, per chipset manufacturer's guidance, Normalized RF exposure from 4G and from 5G mmW NR could be assumed as

$$\text{Normalized RFx}_{\text{Time Averaged WWAN}} = \frac{4G \text{ SAR}}{4G \text{ SAR Limit}} + \frac{5G \text{ mmW NR psPD}}{5G \text{ mmW NR psPD Limit}} \leq 1.0 \quad (2)$$

Smart Transmit algorithm assumes that 4G and 5G mmW NR hotspots are co-located and therefore:

$$\text{Time Averaged WWAN} = [x(t) \times A] + [(1-x(t)) \times B] \leq 1.0 \text{ Normalized Limit} \quad (3)$$

A = Max normalized time-averaged SAR exposure from 4G

B = Max normalized time-averaged PD exposure from 5G mmW NR

$x(t)$ = Ranges between $[0,1]$

$x(t) \times A$ = Percentage of normalized time-averaged RF exposure from 4G

$(1-x(t)) \times B$ = Remaining percentage of RF exposure contribution from 5G mmW NR

Smart Transmit controls "x" in real time such that the sum of these exposures never exceeds 1.0 Normalized Limit. If the equations below (4a, 4b) are proven, then, mathematically equation (5) would be proven.

$$A + \text{norm. SAR from WLAN} \leq 1.0 \text{ normalized limit} \quad (4a)$$

$$B + \text{norm. SAR from WLAN} \leq 1.0 \text{ normalized limit} \quad (4b)$$

$$[x(t) \times A] + [(1-x(t)) \times B] + \text{norm. SAR from WLAN} \leq 1.0 \text{ normalized limit} \quad (5)$$

Without 5G mmW NR, Smart Transmit limits the maximum RF exposure contributed from 4G to 100% normalized exposure. With 5G mmW NR, Smart Transmit limits the maximum RF exposure contributed from 5G mmW NR to 75% normalized exposure to guarantee at least 25% margin allocated to 4G LTE anchor to maintain the link.

Therefore,

$$\text{Smart Tx WWAN: } A = \max(\text{normalized SAR exposure from 4G}) \leq 1.0 \text{ normalized limit} \quad (6a)$$

$$\text{Smart Tx WWAN: } B = 0.75 \times \max(\text{normalized PD exposure from 5G mmW NR}) \leq 1.0 \text{ normalized limit} \quad (6b)$$

To demonstrate simultaneous transmission compliance in equation (1), below equations (7a & 7b) obtained by combining equations (4a & 4b) and (6a & 6b), should be proven for simultaneous transmission compliance:

$$\text{Total Normalized RFx} = \text{Normalized SAR}_{4G \text{ WWAN}} + \text{Normalized SAR}_{\text{WLAN}} < 1.0 \quad (7a)$$

$$\text{Total Normalized RFx} = 0.75 \times \text{Normalized psPD}_{5G \text{ mmW NR WWAN}} + \text{Normalized SAR}_{\text{WLAN}} < 1.0 \quad (7b)$$

which are re-written as:

$$\text{Total Normalized RFx} = \frac{4G \text{ SAR}}{4G \text{ SAR Limit}} + \frac{\text{WLAN SAR}}{\text{WLAN SAR Limit}} < 1 \quad (8a)$$

$$\text{Total Normalized RFx} = 0.75 * \frac{5G \text{ mmW NR psPD}}{5G \text{ mmW NR psPD Limit}} + \frac{\text{WLAN SAR}}{\text{WLAN SAR Limit}} < 1 \quad (8b)$$

Analysis for equation (8a) is performed in Section 12 of FCC SAR Evaluation Report (Part 1). Analysis for equation (8b) is performed in this appendix, Tables D-2 to D-5.

FCC ID: ZNFV600VM	 PCTEST NEAR-FIELD POWER DENSITY EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/31/2019 – 1/31/2020	DUT Type: Portable Handset		APPENDIX D: Page 7 of 6