



MEASUREMENT REPORT LTE / NR

Applicant Name:
LG Electronics USA, Inc.
111 Sylvan Avenue, North Building
Englewood Cliffs, NJ 07632
United States


Date of Testing:
9/19 - 9/20/2020
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M2009170147-01.ZNF

| | |
|-------------------|---------------------------------|
| FCC ID: | ZNFV600VM |
| APPLICANT: | LG Electronics USA, Inc. |

Application Type: Class II Permissive Change
Model: LM-V600VM
Additional Model(s): LMV600VM, V600VM, LM-V600QM5, LMV600QM5, V600QM5, LM-V600QM6, LMV600QM6, V600QM6
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): 22, 24, & 27
Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01
Class II Permissive Change: Please see FCC change document

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



| | | | | |
|--|---|--|---|--|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  LG | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 1 of 16 | |

TABLE OF CONTENTS

| | | |
|-----|--|----|
| 1.0 | INTRODUCTION | 3 |
| 1.1 | Scope | 3 |
| 1.2 | PCTEST Test Location..... | 3 |
| 1.3 | Test Facility / Accreditations..... | 3 |
| 2.0 | PRODUCT INFORMATION..... | 4 |
| 2.1 | Equipment Description | 4 |
| 2.2 | Device Capabilities..... | 4 |
| 2.3 | Test Configuration | 4 |
| 2.4 | EMI Suppression Device(s)/Modifications | 4 |
| 3.0 | DESCRIPTION OF TESTS | 5 |
| 3.1 | Measurement Procedure | 5 |
| 3.2 | Radiated Power and Radiated Spurious Emissions | 5 |
| 4.0 | MEASUREMENT UNCERTAINTY | 6 |
| 5.0 | TEST EQUIPMENT CALIBRATION DATA | 7 |
| 6.0 | SAMPLE CALCULATIONS | 8 |
| 7.0 | TEST RESULTS | 9 |
| 7.1 | Summary | 9 |
| 7.2 | Radiated Spurious Emissions Measurements..... | 10 |
| 8.0 | CONCLUSION..... | 16 |

| | | | | |
|--|--|--|---|--|
| FCC ID: ZNFV600VM |  Proud to be part of  element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 2 of 16 | |

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  Proud to be part of  element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 3 of 16 |

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFV600VM**. The test data contained in this report pertains only to the emissions due to the EUT's LTE/NR function.

Test Device Serial No.: 2664, 2672

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (n66, n2, n5, n260, n261), 802.11b/g/n/ac/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

| | | | | |
|--|---|--|---|--|
| FCC ID: ZNFV600VM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 4 of 16 |

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power [Watts]})$.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST [®] Proud to be part of element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 5 of 16 |

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution | Expanded Uncertainty (\pm dB) |
|----------------------------------|----------------------------------|
| Conducted Bench Top Measurements | 1.13 |
| Radiated Disturbance (<1GHz) | 4.98 |
| Radiated Disturbance (>1GHz) | 5.07 |
| Radiated Disturbance (>18GHz) | 5.09 |

| | | | | |
|---|--|--|--|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  LG | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 6 of 16 |

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------|------------|------------------------------|-----------|--------------|-----------|---------------|
| Emco | 3115 | Horn Antenna (1-18GHz) | 6/18/2020 | Biennial | 6/18/2022 | 9704-5182 |
| ETS Lindgren | 3164-08 | Quad Ridge Horn Antenna | 3/12/2020 | Biennial | 3/12/2022 | 128337 |
| Mini-Circuits | SSG-4000HP | Synthesized Signal Generator | N/A | | | 11208010032 |
| Rohde & Schwarz | ESU26 | EMI Test Receiver (26.5GHz) | 7/15/2020 | Annual | 7/15/2021 | 100342 |
| Rohde & Schwarz | ESU40 | EMI Test Receiver (40GHz) | 9/23/2019 | Annual | 9/23/2020 | 100348 |
| Rohde & Schwarz | SFUNIT-Rx | Shielded Filter Unit | 2/10/2020 | Annual | 2/10/2021 | 102134 |
| Sunol | DRH-118 | Horn Antenna (1-18GHz) | 10/3/2019 | Biennial | 10/3/2021 | A050307 |

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 7 of 16 | |

6.0 SAMPLE CALCULATIONS

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

| | | | | |
|--|---|--|---|--|
| FCC ID: ZNFV600VM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 8 of 16 |

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFV600VM
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE/NR

| FCC Part Section(s) | Test Description | Test Limit | Test Condition | Test Result | Reference |
|---------------------|-----------------------|--|----------------|-------------|-------------|
| 2.1053 | Undesirable Emissions | $> 43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions | RADIATED | PASS | Section 7.2 |

Table 7-1. Summary of Radiated Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

| | | | | |
|---|--|--|--|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  LG | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 9 of 16 | |

7.2 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

| | | | | |
|--|---|--|---|--|
| FCC ID: ZNFV600VM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 10 of 16 |

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 5) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 11 of 16 |

NR Band n2 + B13



Plot 7-1. Radiated Spurious Plot above 1GHz (EN-DC Band n2 + B13)

| | |
|-------------------------|-------------|
| Sample #: | 2664 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 1860.0 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 13 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 1080.5 | V | - | - | -77.93 | -2.53 | 26.54 | -68.72 | -13.00 | -55.72 |
| 2639.5 | V | - | - | -79.71 | 5.20 | 32.49 | -62.77 | -13.00 | -49.77 |
| 2940.5 | V | 302 | 179 | -71.87 | 6.58 | 41.71 | -53.54 | -13.00 | -40.54 |
| 3419.0 | V | - | - | -80.51 | 7.38 | 33.87 | -61.38 | -13.00 | -48.38 |

Table 7-2. Radiated Spurious Data (EN-DC Band n2 + B13– Low Channel)

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST® Proud to be part of element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 12 of 16 |

| | |
|-------------------------|-------------|
| Sample #: | 2664 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 1880.0 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 13 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 1098.0 | V | - | - | -77.94 | -2.00 | 27.06 | -68.20 | -13.00 | -55.20 |
| 2662.0 | V | 252 | 23 | -78.59 | 5.05 | 33.46 | -61.80 | -13.00 | -48.80 |
| 2978.0 | V | 333 | 84 | -73.23 | 6.01 | 39.78 | -55.47 | -13.00 | -42.47 |
| 3444.0 | V | - | - | -80.31 | 7.47 | 34.16 | -61.09 | -13.00 | -48.09 |
| 4076.0 | V | - | - | -81.14 | 8.14 | 34.00 | -61.26 | -13.00 | -48.26 |
| 4542.0 | V | - | - | -81.30 | 8.99 | 34.69 | -60.56 | -13.00 | -47.56 |
| 4858.0 | V | - | - | -81.18 | 9.14 | 34.96 | -60.30 | -13.00 | -47.30 |

Table 7-3. Radiated Spurious Data (EN-DC Band n2 + B13– Mid Channel)


| | |
|-------------------------|-------------|
| Sample #: | 2664 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 1900.0 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 13 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 1115.5 | V | - | - | -77.93 | -1.76 | 27.31 | -67.95 | -13.00 | -54.95 |
| 2684.5 | V | - | - | -79.97 | 5.27 | 32.30 | -62.95 | -13.00 | -49.95 |
| 3015.5 | V | 268 | 267 | -78.70 | 7.64 | 35.94 | -59.32 | -13.00 | -46.32 |
| 3469.0 | V | - | - | -80.49 | 7.26 | 33.77 | -61.49 | -13.00 | -48.49 |

Table 7-4. Radiated Spurious Data (EN-DC Band n2 + B13– High Channel)

| | | | | |
|--|--|--|---|--|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 13 of 16 | |

NR Band n5 + B66



Plot 7-2. Radiated Spurious Plot above 1GHz (EN-DC Band n5 + B66)

| | |
|-------------------------|-------------|
| Sample #: | 2672 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 834.0 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 66 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 2554.0 | V | 141 | 323 | -63.85 | 5.51 | 48.66 | -46.60 | -13.00 | -33.60 |
| 2606.0 | V | 135 | 242 | -51.91 | 5.26 | 60.35 | -34.91 | -13.00 | -21.91 |
| 4274.0 | V | 162 | 196 | -77.68 | 9.60 | 38.92 | -56.34 | -13.00 | -43.34 |

Table 7-5. Radiated Spurious Data (EN-DC Band n5 + B66– Low Channel)

| | | | | |
|---|--|--|---|---------------------------------|
| FCC ID: ZNFV600VM |  PCTEST® Proud to be part of element | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 14 of 16 | |

| | |
|-------------------------|-------------|
| Sample #: | 2672 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 836.5 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 66 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB μ V/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------------|------------------------------------|-------------|-------------|
| 2581.5 | V | 123 | 238 | -64.74 | 5.42 | 47.68 | -47.58 | -13.00 | -34.58 |
| 2653.5 | V | 153 | 29 | -56.90 | 4.92 | 55.02 | -40.23 | -13.00 | -27.23 |
| 3418.0 | V | 299 | 354 | -72.57 | 7.39 | 41.82 | -53.44 | -13.00 | -40.44 |
| 3562.0 | V | 166 | 7 | -80.79 | 8.12 | 34.33 | -60.93 | -13.00 | -47.93 |
| 4326.5 | V | 382 | 358 | -64.40 | 10.13 | 52.73 | -42.53 | -13.00 | -29.53 |
| 4398.5 | V | - | - | -81.29 | 10.64 | 36.35 | -58.91 | -13.00 | -45.91 |
| 5163.0 | V | - | - | -81.60 | 10.64 | 36.04 | -59.22 | -13.00 | -46.22 |

Table 7-6. Radiated Spurious Data (EN-DC Band n5 + B66– Mid Channel)

| | |
|-------------------------|-------------|
| Sample #: | 2672 |
| Bandwidth (MHz): | 20 |
| Frequency (MHz): | 839.0 |
| RB / Offset: | 1 / 50 |
| Mode: | EN-DC |
| Anchor Band: | LTE Band 66 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB μ V/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------------|------------------------------------|-------------|-------------|
| 2609.0 | V | 146 | 309 | -64.04 | 5.26 | 48.22 | -47.03 | -13.00 | -34.03 |
| 2701.0 | V | 136 | 233 | -52.11 | 5.43 | 60.32 | -34.94 | -13.00 | -21.94 |
| 3448.0 | V | 261 | 351 | -71.04 | 7.42 | 43.38 | -51.87 | -13.00 | -38.87 |
| 4379.0 | V | 265 | 29 | -75.37 | 10.46 | 42.09 | -53.17 | -13.00 | -40.17 |
| 5218.0 | V | - | - | -82.22 | 11.49 | 36.27 | -58.98 | -13.00 | -45.98 |

Table 7-7. Radiated Spurious Data (EN-DC Band n5 + B66– High Channel)

| | | | | |
|--|--|--|---|--|
| FCC ID: ZNFV600VM |  PCTEST Proud to be part of  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | Page 15 of 16 | |

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFV600VM** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules for LTE/NR operation only.

| | | | | |
|--|---|--|---|--|
| FCC ID: ZNFV600VM |  <small>Proud to be part of  element</small> | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M2009170147-01.ZNF | Test Dates: 9/19 - 9/20/2020 | EUT Type: Portable Handset | | Page 16 of 16 |