



**FCC CFR47 PART 15 SUBPART C
CLASS II PERMISSIVE CHANGE**

CERTIFICATION TEST REPORT

FOR

**Cellular/PCS CDMA/EVDO/GSM/GPRS/EDGE, PCS WCDMA/HSPA and AWS LTE
Phone with Bluetooth&WLAN&NFC**

MODEL NUMBER: VS950, LG-VS950, LGVS950

FCC ID: ZNFVS950

REPORT NUMBER: 12U14455-2

ISSUE DATE: JUNE 18, 2012

Prepared for
**LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NJ 07632**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES (UL CCS)
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	06/18/12	Initial Issue	T. LEE

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	5
4.2. <i>SAMPLE CALCULATION</i>	5
4.3. <i>MEASUREMENT UNCERTAINTY</i>	5
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>MAXIMUM OUTPUT POWER</i>	6
5.3. <i>DESCRIPTION OF CLASS II PERMISSIVE CHANGE</i>	6
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	6
5.5. <i>MODEL DIFFERNECE</i>	6
5.6. <i>SOFTWARE AND FIRMWARE</i>	6
5.7. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.8. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. RADIATED TEST RESULTS	11
7.1. <i>LIMITS AND PROCEDURE</i>	11
7.2. <i>TRANSMITTER ABOVE 1 GHz</i>	12
7.2.1. <i>BASIC DATA RATE GFSK MODULATION</i>	12
7.2.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	21
7.3. <i>WORST-CASE BELOW 1 GHz</i>	30
8. AC POWER LINE CONDUCTED EMISSIONS	33
9. SETUP PHOTOS	37

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NJ 07632

EUT DESCRIPTION: Cellular / PCS CDMA, GSM, WCDMA, and LTE Phone
With Bluetooth&WLAN + NFC

MODEL: VS950, LG-VS950, LGVS950

SERIAL NUMBER: 990001510000722 (Radiated), 990001510000714 (Conducted),

DATE TESTED: JUNE 14~16, 2012

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

Compliance Certification Services (UL CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:

Tested By:



TIM LEE
STAFF ENGINEER
UL CCS

TOM CHEN
EMC ENGINEER
UL CCS

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Cellular/PCS CDMA, GSM, WCDMA and LTE Phone with Bluetooth & WLAN + NFC

The unit supports AFH mode. The manufacturer attested the following.

- It is in compliance with Bluetooth Specification 1.2 or later specification.
- The number of hopping channel in AFH mode is 79 channels
- The output power do not transmit over than 125 mW
- The channel separation is based upon 2/3 of 20 dB channel bandwidth

5.2. MAXIMUM OUTPUT POWER

The measured average power values were within ± 0.5 dB of the original values. Refer to original report number "12U14390-2A FCC IC BLUETOOTH Report" for exact output power values and for all antenna port results.

5.3. DESCRIPTION OF CLASS II PERMISSIVE CHANGE

The change filed under this application has the following changes.

- Hardware Changes (Antenna Pattern and PCB Adjustments)
- Software Changes (Fixed Bugs and User Interface)

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a Monopole antenna, with a maximum gain of -1.1 dBi.

5.5. MODEL DIFFERNECE

Model LG-VS950 is identical to Models LGVS950 and VS950 except for model designation.

5.6. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was Android Version 4.0.3

The test utility software used during testing was VS9500CA

5.7. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Based on the baseline scan, the worst-case data rates were:

GFSK DH5 mode
8PSK 3-DH5 mode

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


Support Equipment List			
Description	Manufacturer	Model	Serial Number
AC ADAPTER	LG ELECTRONICS	MCS-01WR	RA1Z0051473

I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC	1	MINI USB	UN-SHELEDDED	1.0m	LG-DLC300 (BA21)

TEST SETUP

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	07/14/12
Antenna, Horn, 18 GHz	EMCO	3115	C00945	06/29/12
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	11/11/12
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01016	07/12/12
Horn Antenna, 26.5 GHz	ARA	MWH-1826/B	C00589	07/28/12
Horn Antenna, 40 GHz	ARA	MWH-2640/B	C00981	05/10/13
Preamplifier, 40 GHz	Miteq	NSP4000-SP2	C00990	03/14/13
Reject Filter, 2.0-2.9 GHz	Micro-Tronics	BRM50702	N02684	CNR
High Pass Filter, 7.6 GHz	Micro-Tronics	HPM13195	N02682	CNR
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01159	04/09/13
Peak Power Meter	Agilent	N1911A	1260847C	08/04/12
Peak Power Sensor	Agilent	E9323A	1244073F	08/04/12
Reject Filter, 5.725-5.825 GHz	Micro-Tronics	BRC13192	N02676	CNR
Reject Filter, 2.4-2.5 GHz	Micro-Tronics	BRM50702	N02685	CNR
Highpass Filter, 7.6 GHz	Micro-Tronics	HPM13195	N02682	CNR
EMI Test Receiver, 30MHz	R & S	ESHS 20	N02396	08/19/13
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	12/13/12

7. RADIATED TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

7.2. TRANSMITTER ABOVE 1 GHz


7.2.1. BASIC DATA RATE GFSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)







HARMONICS AND SPURIOUS EMISSIONS

High Frequency Measurement													
Compliance Certification Services, Fremont 5m Chamber													
Test Engr:		Tom Chen											
Date:		06/16/12											
Project #:		12U14455											
Company:		LG Electronics Inc.											
Test Target:		FCC Class B											
Mode Oper:		Bluetooth GFSK, TX mode											
f	Measurement Frequency	Amp	Preamp Gain	Average Field Strength Limit									
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Peak Field Strength Limit									
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Margin vs. Average Limit									
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Margin vs. Peak Limit									
CL	Cable Loss	HPF	High Pass Filter										
f	Dist	Read	AF	CL	Amp	D Corr	Fltr	Corr.	Limit	Margin	Ant. Pol.	Det.	Notes
GHz	(m)	dBuV	dB/m	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	V/H	P/A/Q/P	
2402MHz GFSK													
4.804	3.0	50.7	33.1	6.3	-34.8	0.0	0.0	55.3	74.0	-18.7	V	P	
4.804	3.0	37.6	33.1	6.3	-34.8	0.0	0.0	42.1	54.0	-11.9	V	A	
4.804	3.0	48.5	33.1	6.3	-34.8	0.0	0.0	53.0	74.0	-21.0	H	P	
4.804	3.0	36.1	33.1	6.3	-34.8	0.0	0.0	40.6	54.0	-13.4	H	A	
2441MHz GFSK													
4.882	3.0	47.6	33.1	6.3	-34.8	0.0	0.0	52.3	74.0	-21.7	H	P	
4.882	3.0	35.3	33.1	6.3	-34.8	0.0	0.0	40.0	54.0	-14.0	H	A	
4.882	3.0	51.5	33.1	6.3	-34.8	0.0	0.0	56.1	74.0	-17.9	V	P	
4.882	3.0	37.6	33.1	6.3	-34.8	0.0	0.0	42.2	54.0	-11.8	V	A	
2480MHz GFSK													
4.960	3.0	50.3	33.2	6.4	-34.8	0.0	0.0	55.0	74.0	-19.0	V	P	
4.960	3.0	36.9	33.2	6.4	-34.8	0.0	0.0	41.6	54.0	-12.4	V	A	
4.960	3.0	47.1	33.2	6.4	-34.8	0.0	0.0	51.8	74.0	-22.2	H	P	
4.960	3.0	34.9	33.2	6.4	-34.8	0.0	0.0	39.7	54.0	-14.3	H	A	
Rev. 4.1.2.7													
Note: No other emissions were detected above the system noise floor.													


7.2.2. ENHANCED DATA RATE 8PSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS

High Frequency Measurement
 Compliance Certification Services, Fremont 5m Chamber

Test Engr: Tom Chen
 Date: 06/16/12
 Project #: 12U14455
 Company: LG Electronics Inc.
 Test Target: FCC Class B
 Mode Oper: Bluetooth 8PSK, TX mode

f Measurement Frequency Amp Preamp Gain Average Field Strength Limit
 Dist Distance to Antenna D Corr Distance Correct to 3 meters Peak Field Strength Limit
 Read Analyzer Reading Avg Average Field Strength @ 3 m Margin vs. Average Limit
 AF Antenna Factor Peak Calculated Peak Field Strength Margin vs. Peak Limit
 CL Cable Loss HPF High Pass Filter


f GHz	Dist (m)	Read dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Corr dB	Limit dB	Margin dB	Ant. Pol. V/H	Det. P/A/QP	Notes
2402MHz 8PSK													
4.804	3.0	48.6	33.1	6.3	-34.8	0.0	0.0	53.1	74.0	-20.9	V	P	
4.804	3.0	35.2	33.1	6.3	-34.8	0.0	0.0	39.7	54.0	-14.3	V	A	
4.804	3.0	46.8	33.1	6.3	-34.8	0.0	0.0	51.4	74.0	-22.6	H	P	
4.804	3.0	33.8	33.1	6.3	-34.8	0.0	0.0	38.3	54.0	-15.7	H	A	
2441MHz 8PSK													
4.882	3.0	46.5	33.1	6.3	-34.8	0.0	0.0	51.1	74.0	-22.9	H	P	
4.882	3.0	33.5	33.1	6.3	-34.8	0.0	0.0	38.1	54.0	-15.9	H	A	
4.882	3.0	48.7	33.1	6.3	-34.8	0.0	0.0	53.3	74.0	-20.7	V	P	
4.882	3.0	35.0	33.1	6.3	-34.8	0.0	0.0	39.6	54.0	-14.4	V	A	
2480MHz 8PSK													
4.960	3.0	45.2	33.2	6.4	-34.8	0.0	0.0	50.0	74.0	-24.0	H	P	
4.960	3.0	32.5	33.2	6.4	-34.8	0.0	0.0	37.3	54.0	-16.7	H	A	
4.960	3.0	48.0	33.2	6.4	-34.8	0.0	0.0	52.8	74.0	-21.2	V	P	
4.960	3.0	34.5	33.2	6.4	-34.8	0.0	0.0	39.3	54.0	-14.7	V	A	

Rev. 4.1.2.7


Note: No other emissions were detected above the system noise floor.

7.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



HORIZONTAL AND VERTICAL DATA

Project No:12U14456								
Client Name:LG Electronics Inc.								
Model /Device:VS 950								
Config /Other:with USB charger, Headset								
Test By:Tom Chen								

Horizontal 30 - 1000MHz

Test Frequency	Meter Reading	Detector	T122 Sunol Bilog.TXT (dB)	5mB Amp Path 30-1000MHz (dB)	dBuV/m	CFR 47 Part 15 Class B 3m	Margin	Polarity
31.9384	32.46	PK	19.9	-29.3	23.06	40	-16.94	Horz
53.8429	52.23	PK	7.3	-29	30.53	40	-9.47	Horz
57.2352	51.03	PK	7.3	-29	29.33	40	-10.67	Horz
95.9073	40.52	PK	9.1	-28.6	21.02	43.5	-22.48	Horz
135.4516	40.5	PK	13.7	-28.2	26	43.5	-17.5	Horz
151.9285	45.58	PK	12.5	-28	30.08	43.5	-13.42	Horz

Vertical 30 - 1000MHz

Test Frequency	Meter Reading	Detector	T122 Sunol Bilog.TXT (dB)	5mB Amp Path 30-1000MHz (dB)	dBuV/m	CFR 47 Part 15 Class B 3m	Margin	Polarity
31.5508	37.48	PK	20.3	-29.3	28.48	40	-11.52	Vert
36.7846	45.05	PK	16.3	-29.2	32.15	40	-7.85	Vert
41.6307	41.94	PK	12.6	-29.2	25.34	40	-14.66	Vert
53.0675	48.67	PK	7.5	-29	27.17	40	-12.83	Vert
56.7506	48.69	PK	7.3	-29	26.99	40	-13.01	Vert
144.3685	39.37	PK	12.8	-28.1	24.07	43.5	-19.43	Vert

8. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

Project No:12U14455									
Client Name:LG Electronics Inc.									
Model/Device:VS950 /USB charger & Headset									
Test Volt/Freq:115 VAC / 60 HZ									
Test By:Tom Chen									


Line-L1 .15 - 30MHz

Test Frequency	Meter Reading	Detector	T24 IL L1.TXT (dB)	LC Cables 1&3.TXT (dB)	dB(uVolts)	CFR 47 Part 15 Class B QP	Margin	CFR 47 Part 15 Class B Avg	Margin
0.168	40.76	PK	0.1	0	40.86	65.1	-24.24	-	-
0.168	18.29	Av	0.1	0	18.39	-	-	55.1	-36.71
0.5145	38.46	PK	0.1	0	38.56	56	-17.44	-	-
0.5145	27.59	Av	0.1	0	27.69	-	-	46	-18.31
4.56	36.17	PK	0.1	0.1	36.37	56	-19.63	-	-
4.56	25.7	Av	0.1	0.1	25.9	-	-	46	-20.1

Line-L2 .15 - 30MHz

Test Frequency	Meter Reading	Detector	T24 IL L2.TXT (dB)	LC Cables 2&3.TXT (dB)	dB(uVolts)	CFR 47 Part 15 Class B QP	Margin	CFR 47 Part 15 Class B Avg	Margin
0.15	36.49	PK	0.1	0	36.59	66	-29.41	-	-
0.15	13.18	Av	0.1	0	13.28	-	-	56	-42.72
0.5055	30.46	PK	0.1	0	30.56	56	-25.44	-	-
0.5055	14.51	Av	0.1	0	14.61	-	-	46	-31.39
4.2315	28.66	PK	0.1	0.1	28.86	56	-27.14	-	-
4.2315	16.37	Av	0.1	0.1	16.57	-	-	46	-29.43

LINE 1 RESULTS



LINE 2 RESULTS

