



FCC 47 CFR PART 22 SUBPART H
FCC 47 CFR PART 24 SUBPART E
FCC 47 CFR PART 27 SUBPART L
CERTIFICATION TEST REPORT

FOR
GSM/CDMA/WCDMA + LTE Phone Bluetooth, WLAN (2.4GHz & 5GHz) and NFC

MODEL NUMBER: VS980, LGVS980 and LG-VS980

FCC ID: ZNFVS980

REPORT NUMBER: 13U15118-1, Revision C
ISSUE DATE: July 15, 2013

Prepared for

LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NJ 07632

Prepared by

UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP[®]

NVLAP LAB CODE 200065-0

Revision History

Issue			
Rev.	Date	Revisions	Revised By
---	05/26/13	Initial Issue	P. Kim
A	07/05/13	Added 16QAM Mode in Maximum Power Section	I.Netto
B	07/09/13	Update labels and administrative information	P. Kim
C	07/15/13	Update accessory information, Section 5.6 Description of Test Set Up - Support Equipment	P. Kim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	8
4.2. <i>SAMPLE CALCULATION</i>	8
4.3. <i>MEASUREMENT UNCERTAINTY</i>	8
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	9
5.2. <i>MAXIMUM OUTPUT POWER</i>	9
5.3. <i>SOFTWARE AND FIRMWARE</i>	11
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	11
5.5. <i>WORST-CASE CONFIGURATION AND MODE</i>	12
5.6. <i>DESCRIPTION OF TEST SETUP</i>	12
6. TEST AND MEASUREMENT EQUIPMENT	14
7. RF POWER OUTPUT VERIFICATION	15
7.1. <i>GPRS MODE</i>	15
7.1.1. <i>GSM and GPRS</i>	16
7.1.2. <i>EGPRS</i>	17
7.2. <i>CDMA MODE</i>	18
7.2.1. <i>CDMA 1xRtt</i>	18
7.2.2. <i>CDMA EV-DO</i>	19
7.3. <i>UMTS REL 99 MODE</i>	20
7.3.1. <i>WCDMA REL 99</i>	21
7.4. <i>HSDPA REL 7</i>	22
7.5. <i>HSUPA REL 6</i>	24
7.6. <i>LTE BAND 4</i>	26
7.7. <i>LTE BAND 13</i>	30
8. Peak to Average Power Ratio.....	31
8.1. <i>GPRS</i>	31
8.1. <i>EGPRS</i>	33

8.1. CDMA RTT	35
8.1. CDMA EV-DO	37
8.1. WCDMA REL99	39
8.1. WCDMA HSUPA	41
8.1. LTE BAND 4 5MHz	43
8.1. LTE BAND 4 10MHz	45
8.1. LTE BAND 4 15MHz	47
8.1. LTE BAND 4 20MHz	49
8.1. LTE BAND 13 10MHz	51
9. CONDUCTED TEST RESULTS	53
9.1. OCCUPIED BANDWIDTH	53
9.1.1. GPRS MODE	59
9.1.1. EGPRS MODE	65
9.1.2. CMDA 2000 MODE	71
9.1.1. CDMA EV-DO MODE	77
9.1.2. UMTS REL 99 MODE	83
9.1.1. HSUPA MODE	89
9.1.4. LTE BAND 13-10 MHz BANDWIDTH	142
9.2. BAND EDGE	146
9.2.1. GPRS MODE	147
9.2.1. EGPRS MODE	150
9.2.2. UMTS REL 99 MODE	153
9.2.3. UMTS HSUPA MODE	156
9.2.1. CDMA 1xRtt MODE	160
9.2.2. CDMA EV-DO MODE	164
9.2.3. LTE BAND 4-5MHZ BANDWIDTH	168
9.2.4. LTE BAND 4-10MHZ BANDWIDTH	180
9.2.5. LTE BAND 4-15MHZ BANDWIDTH	194
9.2.6. LTE BAND 4-20MHZ BANDWIDTH	205
9.2.7. LTE BAND 13-10MHz BANDWIDTH	219
OUT OF BAND EMISSIONS	227
9.2.8. GPRS MODE	228
9.2.1. EGPRS MODE	234
9.2.2. UMTS REL 99 MODE	240

9.2.3.	UMTS HSUPA MODE.....	246
9.2.4.	LTE BAND 4-5MHz BANDWIDTH	251
9.2.5.	LTE BAND 4-10MHz BANDWIDTH	256
9.2.6.	LTE BAND 4-15MHz BANDWIDTH	261
9.2.7.	LTE BAND 4-20MHz BANDWIDTH	267
9.2.8.	LTE BAND 13-10MHz BANDWIDTH	273
10.	FREQUENCY STABILITY.....	275
10.1.1.	CELL, GPRS MODULATION – MID CHANNEL	276
10.1.2.	PCS, GPRS MODULATION – MID CHANNEL.....	277
10.1.3.	CELL WCDMA – MID CHANNEL	278
10.1.4.	PCS WCDMA – MID CHANNEL.....	279
10.1.5.	LTE BAND 4 – MID CHANNEL (1732.5 MHz)	280
10.1.6.	LTE BAND 13 – MID CHANNEL (782.0 MHz)	280
11.	RADIATED TEST RESULTS	281
11.1.	<i>RADIATED POWER (ERP & EIRP)</i>	281
11.1.1.	GPRS 850 (Cellular Band)	287
11.1.2.	GPRS 1900 (PCS Band)	288
11.1.3.	EGPRS 850 (Cellular Band)	289
11.1.4.	EGPRS 1900 (PCS Band).....	290
11.1.5.	UMTS 850 REL 99 (Cellular Band).....	291
11.1.6.	UMTS 850 REL 99 (PCS Band)	292
11.1.7.	UMTS 850 HSUPA (Cellular Band)	293
11.1.8.	UMTS 850 HSUPA (PCS Band)	294
11.1.9.	CDMA 1xRtt (Cellular Band).....	295
11.1.10.	CDMA 1xRtt (PCS Band)	296
11.1.11.	CDMA EV-DO (Cellular Band).....	297
11.1.12.	CDMA EV-DO (PCS Band)	298
11.1.13.	LTE BAND 4-5MHz BANDWIDTH.....	299
11.1.14.	LTE BAND 4-10MHz BANDWIDTH.....	301
11.1.15.	LTE BAND 4-15MHz BANDWIDTH.....	303
11.1.16.	LTE BAND 4-20MHz BANDWIDTH.....	305
11.1.17.	LTE BAND 13-10MHz BANDWIDTH.....	307
11.2.	<i>FIELD STRENGTH OF SPURIOUS RADIATION.....</i>	308
11.2.1.	GPRS (Cellular Band)	309

11.2.2.	GPRS (Cellular Band) with Wireless Adapter	310
11.2.3.	GPRS (PCS Band)	311
11.2.4.	GPRS (PCS) with Wireless Adapter	312
11.2.5.	EGPRS (Cellular Band)	313
11.2.6.	EGPRS (Cellular Band) with Wireless Adapter	314
11.2.7.	EGPRS (PCS Band).....	315
11.2.8.	EGPRS (PCS Band) with Wireless Adapter.....	316
11.2.9.	WCDMA REL 99 (Cellular Band).....	317
11.2.10.	WCDMA (Cellular Band) with Wireless Adapter	318
11.2.11.	WCDMA REL 99 (PCS Band).....	319
11.2.12.	WCDMA (PCS Band) with Wireless Adapter	320
11.2.13.	WCDMA HSUPA (Cellular Band)	321
11.2.14.	WCDMA HSUPA (Cell Band) with Wireless Adapter	322
11.2.15.	WCDMA HSUPA (PCS Band)	323
11.2.16.	WCDMA HSUPA (PCS Band) with Wireless Adapter	324
11.2.17.	CDMA 1xRTT (Cellular Band)	325
11.2.18.	CDMA 2000 (Cell Band) with Wireless Adapter	326
11.2.19.	CDMA 2000 (PCS Band).....	327
11.2.20.	CDMA 2000 (PCS Band) with Wireless Adapter.....	328
11.2.21.	CDMA EV-DO (Cellular Band).....	329
11.2.22.	CDMA EV-DO (Cell Band) with Wireless Adapter.....	330
11.2.23.	CDMA EV-DO (PCS Band)	331
11.2.24.	CDMA EV-DO (PCS Band) with Wireless Adapter	332
11.2.25.	LTE BAND 4-5MHz BANDWIDTH.....	333
11.2.26.	LTE BAND 4-10MHz BANDWIDTH.....	337
11.2.27.	LTE BAND 4-15MHz BANDWIDTH.....	341
11.2.28.	LTE BAND 4-20MHz BANDWIDTH.....	345
11.2.29.	LTE BAND 13-10MHz BANDWIDTH.....	349
12.	SETUP PHOTOS	351

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S. A. INC

EUT DESCRIPTION: GSM/CDMA/WCDMA + LTE Phone Bluetooth, WLAN (2.4GHz & 5GHz) and NFC

MODEL: VS980, LGVS980 and LG-VS980

SERIAL NUMBER: (CONDUCTED) 990002590002174
(RADIATED) 9900026590002182

DATE TESTED: May 22 – June 8, 2013

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 22H AND 24E	PASS

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For

UL Verification Services Inc By:



Tested By:



PHILIP KIM
WISE OPERATIONS MANAGER
UL Verification Services Inc

STEVEN TRAN
WISE LAB TECHNICIAN
UL Verification Services Inc

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-C, FCC CFR 47 Part 2, FCC CFR 47 Part 22, and FCC CFR Part 24.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dB_V/m) = Measured Voltage (dB_V) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

$$36.5 \text{ dB}_V + 18.7 \text{ dB}/m + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dB}_V/m$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a LTE Phone Bluetooth, WLAN(2.4GHz & 5GHz) and NFC

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak of both conducted and ERP / EIRP output powers as follows:

Part 22 Cellular Band					
Frequency range (MHz)	Modulation	Conducted		ERP	
		dBm	mW	dBm	mW
824.2 - 848.8	GPRS	33.20	2089.3	29.27	845.3
824.2 - 848.8	EGPRS	26.70	467.7	26.89	488.7

Part 24 PCS Band					
Frequency range (MHz)	Modulation	Conducted		EIRP	
		dBm	mW	dBm	mW
1850.2-1909.8	GPRS	30.60	1148.2	29.01	796.2
1850.2-1909.8	EGPRS	26.70	467.7	25.97	395.4

Part 22 Cellular Band					
Frequency range (MHz)	Modulation	Conducted		ERP	
		dBm	mW	dBm	mW
824.7 - 848.31	CDMA (1xRTT)	25.20	331.1	23.46	221.8
824.7 - 848.31	1xEVDO Rel 0	25.20	331.1	25.62	364.8

Part 24 PCS Band					
Frequency range (MHz)	Modulation	Conducted		EIRP	
		dBm	mW	dBm	mW
1851.25 - 1908.75	CDMA (1xRTT)	24.70	295.1	23.90	245.5
1851.25 - 1908.75	1xEVDO Rel 0	24.70	295.1	23.99	250.6

Part 22 Cellular Band					
Frequency range (MHz)	Modulation	Conducted		ERP	
		dBm	mW	dBm	mW
826.4 - 846.6	REL 99	23.70	234.4	20.73	118.3
826.4 - 846.6	HSUPA	23.70	234.4	22.00	158.5

Part 24 PCS Band

Frequency range (MHz)	Modulation	Conducted		EIRP	
		dBm	mW	dBm	mW
1852.4 – 1907.6	REL 99	23.70	234.4	24.66	292.4
1852.4 – 1907.6	HSUPA	23.70	234.4	22.58	181.1

Part 27L LTE Band 4 MODE (5 MHz BANDWIDTH)

Frequency range (MHz)	Modulation	Start RB and RB offset	Conducted		EIRP	
			dBm	mW	dBm	mW
1712.5-1752.5	QPSK	1/0	23.50	223.9	20.63	115.6
	16QAM		22.70	186.2	19.63	91.8

Part 27L LTE Band 4 MODE (10.0- MHz BANDWIDTH)

Frequency range (MHz)	Modulation	Start RB and RB offset	Conducted		EIRP	
			dBm	mW	dBm	mW
1715-1750	QPSK	1/0	23.60	229.1	21.61	144.9
	16QAM		22.60	182.0	20.61	115.1

Part 27L LTE Band 4 MODE (15.0 MHz BANDWIDTH)

Frequency range (MHz)	Modulation	Start RB and RB offset	Conducted		EIRP	
			dBm	mW	dBm	mW
1717.5-1747.5	QPSK	1/0	23.70	234.4	20.61	115.1
	16QAM		22.60	182.0	19.61	91.4

Part 27L LTE Band 4 MODE (20.0 MHz BANDWIDTH)

Frequency range (MHz)	Modulation	Start RB and RB offset	Conducted		EIRP	
			dBm	mW	dBm	mW
1720.0-1745	QPSK	100/0	23.60	229.1	20.33	107.9
	16QAM		22.60	182.0	19.43	87.7

Part 27 LTE Band 13 MODE (10 MHz BANDWIDTH)

Frequency range (MHz)	Modulation	Start RB and RB offset	Conducted		ERP	
			dBm	mW	dBm	mW
777.0 - 787.0	QPSK	1/0	23.60	229.1	21.20	131.8
	16QAM		22.60	182.0	20.10	102.3

5.3. SOFTWARE AND FIRMWARE

The test utility software used during was VS9800RA and firmware used was g2_vzw-userdebug 4.2.2 JDQ39B VS9800RA.1368678220.

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an integral antenna with a maximum peak gain as follow:

Frequency (MHz)	Gain (dBi)
850MHz	-3.99
1900MHz	-0.27
1700MHz	-2.48
750MHz	-4.13

5.5. WORST-CASE CONFIGURATION AND MODE

Based on the investigation results, the highest peak power and enhanced data rate is the worst-case scenario for all measurements.

Worst-case modes: GPRS, UMTS WCDMA and UMTS HSUPA Sub-test 3.

Since the EUT is a portable device, to determine the worst/highest emissions, the X, Y, and Z orientations of the EUT with respect to the turntable and the worst among them with headset and an AC adapter were investigated. After the investigations, Y-Orientation without AC adapter and headset was the worst case for cell bands, and Z-Orientation for PCS bands.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	TEN PAO	MCS-04WT2	NA	NA
Headset	I-SOUND	EAB62729001	NA	NA

I/O CABLES (CONDUCTED SETUP)



I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	RF	1	Antenna Port	Un-Shielded	0.2m	NA
2	RF In/Out	1	Call Box	Un-Shielded	0.5m	NA
3	RF Out	1	Spectrum Analyzer	None	None	NA

I/O CABLES (RADIATED SETUP)

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	DC	1	DC	Un-shielded	1m	NA
2	Jack	1	Earphone	Un-shielded	1.2m	NA

TEST SETUP

The EUT is a stand-alone device. A link is established between the EUT and the communications test set.

SETUP DIAGRAM FOR RF CONDUCTED TESTS**SETUP DIAGRAM FOR RF RADIATED TESTS**

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Horn, 18 GHz	EMCO	3115	C00872	10/25/13
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00885	12/11/13
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01179	02/26/14
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	10/22/13
Communication Test Set	Agilent / HP	E5515C	C01086	06/20/13
Temperature / Humidity Chamber	Thermotron	SE 600-10-10	C00930	01/09/14
Highpass Filter, 1.5 GHz	Micro-Tronics	HPM13193	N02689	CNR
Highpass Filter, 2.7 GHz	Micro-Tronics	HPM13194	N02687	CNR
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01016	08/14/13
Vector signal generator, 6 GHz	Agilent / HP	E4438C	None	07/06/13
Antenna, Tuned Dipole 400~1000 MHz	ETS	3121C DB4	C00993	02/14/14

7. RF POWER OUTPUT VERIFICATION

7.1. GPRS MODE

TEST PROCEDURE

The transmitter output was connected to the input terminal of Directional Coupler via calibrated coaxial cable. The output coupling terminal of the Directional Coupler was directly connected to a spectrum analyzer while the output through terminal connected to the communication test set via calibrated coaxial cable.

The output power was measured with the spectrum analyzer at the low, middle and high channel in each band.

- Set the spectrum analyzer span wide enough or greater than the modulated signal BW.
- Set a spectrum analyzer at peak detection mode with $VBW \geq RBW \geq 26dB$ BW, typically 3MHz.
- Set a marker to point the corresponding peak value.

GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/900/1800/1900

Press Connection control to choose the different menus

Press RESET > choose all to reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM+GPRS or GSM+EGPRS

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config bottom on the right twice to select and change the number of time slots and power setting

- > Slot configuration > Uplink/Gamma
- > 33 dBm for GPRS 850/900
- > 27 dBm for EGPRS 850/900
- > 30 dBm for GPRS1800/1900
- > 26 dBm for EGPRS1800/1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0> 4 dB

Slot Config > Unchanged (if already set under MS Signal)

TCH > choose desired test channel

Hopping >

Off

Main Timeslot >

3 (Default)

Network

Coding Scheme > CS1 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1PSR Bit Pattern

AF/RF

Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection

Press Signal On to turn on the signal and change settings

RESULTS

7.1.1. GSM and GPRS

CELL

Mode	Ch.	f (MHz)	1 time slots	
			Avg	
GSM	128	824.2	33.1	
	190	836.6	32.9	
	251	848.8	33	

	Ch.	f (MHz)	1 time slots	2 time slots
			Avg	Avg
GPRS	128	824.2	32.70	31.00
	190	836.6	32.90	31.10
	251	848.8	33.00	31.20

PCS

Mode	Ch.	f (MHz)	1 time slots	
			Avg	
GSM	512	1850.2	30.5	
	661	1880.0	30.6	
	810	1909.8	30.6	

	Ch.	f (MHz)	1 time slots	2 time slots
			Avg	Avg
GPRS	512	1850.2	30.40	28.40
	661	1880.0	30.60	28.40
	810	1909.8	30.60	28.50

7.1.2. EGPRS

CELL

	Ch.	f (MHz)	1 time slots	2 time slots
			Avg	Avg
GPRS	128	824.2	27.00	27.00
	190	836.6	27.00	27.00
	251	848.8	26.90	26.90

PCS

	Ch.	f (MHz)	1 time slots	2 time slots
			Avg	Avg
GPRS	512	1850.2	26.60	26.50
	661	1880.0	26.50	26.50
	810	1909.8	26.60	26.50

7.2. CDMA MODE

7.2.1. CDMA 1xRtt

BC0

Band	Mode	Ch	Freq. (MHz)	Avg Pwr (dBm)
BC 0	RC1 SO55 (Loopback)	1013	824.70	25.2
		384	836.52	25.1
		777	848.31	25.1
	RC3 SO55 (Loopback)	1013	824.70	25.1
		384	836.52	25.2
		777	848.31	25.2
	RC3 SO32 (+F-SCH)	1013	824.70	25.1
		384	836.52	25.1
		777	848.31	25.0

BC1

Band	Mode	Ch	Freq. (MHz)	Avg Pwr (dBm)
BC 1	RC1 SO55 (Loopback)	25	1851.25	24.6
		600	1880.00	24.6
		1175	1908.75	24.7
	RC3 SO55 (Loopback)	25	1851.25	24.6
		600	1880.00	24.6
		1175	1908.75	24.7
	RC3 SO32 (+F-SCH)	25	1851.25	24.7
		600	1880.00	24.7
		1175	1908.75	24.7

7.2.2. CDMA EV-DO

BC0

Band	FTAP Rate	Channel	f (MHz)	Avg Pwr (dBm)
BC0	307.2 kbps (2 slot, QPSK)	1013	824.70	25.1
		384	836.52	25.0
		777	848.31	25.1

BC1

Band	FTAP Rate	Channel	f (MHz)	Avg Pwr (dBm)
BC 1	307.2 kbps (2 slot, QPSK)	25	1851.25	24.7
		600	1880.00	24.7
		1175	1908.75	24.7

7.3. UMTS REL 99 MODE

TEST PROCEDURE

The transmitter output was connected to the input terminal of Directional Coupler via calibrated coaxial cable. The output coupling terminal of the Directional Coupler was directly connected to a spectrum analyzer while the output through terminal connected to the communication test set via calibrated coaxial cable.

The output power was measured with the spectrum analyzer at the low, middle and high channel in each band.

- Set the spectrum analyzer span wide enough or greater than the modulated signal BW.
- Set a spectrum analyzer at peak detection mode with $VBW \geq RBW \geq 26dB$ BW, typically 5MHz.
- Set a marker to point the corresponding peak value.

TEST PROCEDURE

The following summary of these settings are illustrated below:

	Mode	Rel99
	Subtest	-
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	HSDPA FRC	Not Applicable
	HSUPA Test	Not Applicable
	Power Control Algorithm	Algorithm2
	β_c	Not Applicable
	β_d	Not Applicable
	β_{ec}	Not Applicable
	β_c/β_d	8/15
	β_{hs}	Not Applicable
	β_{ed}	Not Applicable

RESULTS**7.3.1. WCDMA REL 99****CELL**

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
W-CDMA Band V	Rel 99 (RMC, 12.2 kbps)	4132	826.4	23.6
		4183	836.6	23.6
		4233	846.6	23.6

PCS

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
W-CDMA Band II	Rel 99 (RMC, 12.2 kbps)	9262	1852.4	23.5
		9400	1880.0	23.6
		9538	1907.6	23.5

7.4. HSDPA REL 7

The following 4 Sub-tests were completed according to Release 6 and later procedures in section 5.2 of 3GPP TS34.121.

Summary of settings are illustrated below:

	Mode	Rel5 HSDPA			
		1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR (dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Result**CELL**

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	23.5
		4183	836.6	0	23.5
		4233	846.6	0	23.5
	Subtest 2	4132	826.4	0	23.6
		4183	836.6	0	23.5
		4233	846.6	0	23.4
	Subtest 3	4132	826.4	0.5	23.0
		4183	836.6	0.5	23.0
		4233	846.6	0.5	23.0
	Subtest 4	4132	826.4	0.5	23.0
		4183	836.6	0.5	23.0
		4233	846.6	0.5	23.1

PCS

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band II	Subtest 1	9262	1852.4	0	23.5
		9400	1880.0	0	23.7
		9538	1907.6	0	23.7
	Subtest 2	9262	1852.4	0	23.5
		9400	1880.0	0	23.6
		9538	1907.6	0	23.5
	Subtest 3	9262	1852.4	0.5	23.0
		9400	1880.0	0.5	23.2
		9538	1907.6	0.5	23.0
	Subtest 4	9262	1852.4	0.5	23.1
		9400	1880.0	0.5	23.2
		9538	1907.6	0.5	23.0

Note * Maximum output power levels that are possible for all subtests reported.

7.5. HSUPA REL 6

TEST PROCEDURE

The following summary of these settings are illustrated below:

	Mode	Rel6 HSUPA	Rel6 HSUPA	Rel6 HSUPA	Rel6 HSUPA	Rel6 HSUPA
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
HSDPA Specific Settings	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15	56/75	47/15
	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
HSUPA Specific Settings	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	$A_{hs} = \beta_{hs}/\beta_c$	30/15				
	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	12
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	67
HSUPA Specific Settings	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_TFCIs	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO 23 E-TFCI 75 E-TFCI PO 26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO 23 E-TFCI 75 E-TFCI PO 26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO 23 E-TFCI 75 E-TFCI PO 26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO 23 E-TFCI 75 E-TFCI PO 26 E-TFCI 81 E-TFCI PO 27	

RESULTS**CELL**

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
WCDMA Band V	Subtest 1	4132	826.4	0	22.7
		4183	836.6	0	22.9
		4233	846.6	0	23.0
	Subtest 2	4132	826.4	2	21.6
		4183	836.6	2	21.4
		4233	846.6	2	21.6
	Subtest 3	4132	826.4	1	22.4
		4183	836.6	1	22.7
		4233	846.6	1	22.2
	Subtest 4	4132	826.4	2	21.8
		4183	836.6	2	21.9
		4233	846.6	2	21.6
	Subtest 5	4132	826.4	0	23.6
		4183	836.6	0	23.6
		4233	846.6	0	23.6

PCS

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band II	Subtest 1	9262	1852.4	0	22.8
		9400	1880.0	0	23.1
		9538	1907.6	0	23.0
	Subtest 2	9262	1852.4	2	21.4
		9400	1880.0	2	21.6
		9538	1907.6	2	21.6
	Subtest 3	9262	1852.4	1	22.9
		9400	1880.0	1	23.0
		9538	1907.6	1	22.6
	Subtest 4	9262	1852.4	2	22.2
		9400	1880.0	2	21.8
		9538	1907.6	2	22.2
	Subtest 5	9262	1852.4	0	23.6
		9400	1880.0	0	23.7
		9538	1907.6	0	23.6

Note * Maximum output power levels that are possible for all subtests reported.

7.6. LTE BAND 4

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average Power (dBm)	
							Maximum Power	Power Reduction
20	20050	1720.0	QPSK	1	0	0	23.6	19.6
				1	49	0	23.6	19.5
				1	99	0	23.6	19.5
				50	0	1	22.3	19.4
				50	24	1	22.2	19.4
				50	49	1	22.2	19.4
				100	0	1	22.3	19.4
			16QAM	1	0	1	22.6	19.2
				1	49	1	22.6	19.5
				1	99	1	22.5	19.4
				50	0	2	21.3	19.4
				50	24	2	21.2	19.4
				50	49	2	21.2	19.4
				100	0	2	21.3	19.4
20	20175	1732.5	QPSK	1	0	0	23.4	19.6
				1	49	0	23.3	19.5
				1	99	0	23.6	19.5
				50	0	1	22.3	19.5
				50	24	1	22.4	19.4
				50	49	1	22.3	19.5
				100	0	1	22.3	19.5
			16QAM	1	0	1	21.9	19.3
				1	49	1	21.8	19.2
				1	99	1	21.8	19.4
				50	0	2	21.3	19.5
				50	24	2	21.3	19.4
				50	49	2	21.4	19.5
				100	0	2	21.3	19.5
20	20300	1745.0	QPSK	1	0	0	23.6	19.6
				1	49	0	23.6	19.6
				1	99	0	23.4	19.5
				50	0	1	22.4	19.5
				50	24	1	22.4	19.5
				50	49	1	22.3	19.5
				100	0	1	22.4	19.5
			16QAM	1	0	1	22.2	19.7
				1	49	1	22.2	19.6
				1	99	1	22.1	19.6
				50	0	2	21.5	19.5
				50	24	2	21.4	19.4
				50	49	2	21.3	19.4
				100	0	2	21.3	19.4

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Avg Pwr (dBm)	
15	20025	1717.5	QPSK	1	0	0	23.7	19.7
				1	37	0	23.4	19.6
				1	74	0	23.5	19.7
				36	0	1	22.3	19.6
				36	18	1	22.3	19.6
				36	37	1	22.2	19.6
				75	0	1	22.2	19.6
			16QAM	1	0	1	22.6	19.6
				1	37	1	22.4	19.4
				1	74	1	22.5	19.5
				36	0	2	21.4	19.5
				36	18	2	21.3	19.5
				36	37	2	21.3	19.5
				75	0	2	21.3	19.5
15	20175	1732.5	QPSK	1	0	0	23.6	19.6
				1	37	0	23.6	19.6
				1	74	0	23.5	19.4
				36	0	1	22.3	19.5
				36	18	1	22.3	19.4
				36	37	1	22.4	19.5
				75	0	1	22.3	19.5
			16QAM	1	0	1	22.5	19.5
				1	37	1	22.5	19.4
				1	74	1	22.5	19.3
				36	0	2	21.3	19.5
				36	18	2	21.3	19.5
				36	37	2	21.4	19.5
				75	0	2	21.3	19.4
15	20325	1747.5	QPSK	1	0	0	23.5	19.6
				1	37	0	23.6	19.6
				1	74	0	23.4	19.6
				36	0	1	22.4	19.6
				36	18	1	22.4	19.6
				36	37	1	22.3	19.6
				75	0	1	22.3	19.6
			16QAM	1	0	1	22.3	19.7
				1	37	1	22.4	19.7
				1	74	1	22.3	19.7
				36	0	2	21.3	19.6
				36	18	2	21.3	19.6
				36	37	2	21.2	19.6
				75	0	2	21.2	19.6

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Avg Pwr (dBm)	
10	20000	1715.0	QPSK	1	0	0	23.4	19.6
				1	24	0	23.4	19.7
				1	49	0	23.4	19.7
				25	0	1	22.3	19.6
				25	12	1	22.2	19.6
				25	24	1	22.2	19.6
				50	0	1	22.1	19.5
			16QAM	1	0	1	21.9	19.7
				1	24	1	21.8	19.7
				1	49	1	21.8	19.4
				25	0	2	21.3	19.6
				25	12	2	21.3	19.6
				25	24	2	21.3	19.6
				50	0	2	21.2	19.4
10	20175	1732.5	QPSK	1	0	0	23.4	19.5
				1	24	0	23.4	19.4
				1	49	0	23.5	19.4
				25	0	1	22.3	19.4
				25	12	1	22.2	19.4
				25	24	1	22.2	19.4
				50	0	1	22.3	19.5
			16QAM	1	0	1	21.9	19.3
				1	24	1	21.8	19.2
				1	49	1	22.0	19.2
				25	0	2	21.3	19.5
				25	12	2	21.2	19.5
				25	24	2	21.2	19.5
				50	0	2	21.2	19.5
10	20350	1750.0	QPSK	1	0	0	23.6	19.6
				1	24	0	23.5	19.5
				1	49	0	23.4	19.5
				25	0	1	22.3	19.6
				25	12	1	22.1	19.5
				25	24	1	22.2	19.6
				50	0	1	22.2	19.6
			16QAM	1	0	1	22.6	19.7
				1	24	1	22.4	19.7
				1	49	1	22.4	19.7
				25	0	2	21.3	19.6
				25	12	2	21.2	19.5
				25	24	2	21.2	19.6
				50	0	2	21.1	19.5

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Avg Pwr (dBm)	
5	19975	1712.5	QPSK	1	0	0	23.5	19.7
				1	12	0	23.6	19.7
				1	24	0	23.5	19.7
				12	0	1	22.2	19.5
				12	6	1	22.3	19.6
				12	11	1	22.4	19.6
				25	0	1	22.2	19.6
			16QAM	1	0	1	22.5	19.5
				1	12	1	22.5	19.6
				1	24	1	22.5	19.6
				12	0	2	21.3	19.5
				12	6	2	21.3	19.6
				12	11	2	21.4	19.6
				25	0	2	21.3	19.6
5	20175	1732.5	QPSK	1	0	0	23.5	19.6
				1	12	0	23.6	19.6
				1	24	0	23.5	19.5
				12	0	1	22.2	19.5
				12	6	1	22.3	19.5
				12	11	1	22.3	19.4
				25	0	1	22.3	19.5
			16QAM	1	0	1	22.5	19.6
				1	12	1	22.5	19.5
				1	24	1	22.5	19.5
				12	0	2	21.3	19.5
				12	6	2	21.4	19.5
				12	11	2	21.4	19.5
				25	0	2	21.3	19.5
5	20375	1752.5	QPSK	1	0	0	23.4	19.6
				1	12	0	23.4	19.7
				1	24	0	23.4	19.6
				12	0	1	22.2	19.6
				12	6	1	22.3	19.6
				12	11	1	22.3	19.6
				25	0	1	22.2	19.6
			16QAM	1	0	1	22.7	19.6
				1	12	1	22.7	19.6
				1	24	1	22.6	19.6
				12	0	2	21.2	19.5
				12	6	2	21.2	19.6
				12	11	2	21.2	19.5
				25	0	2	21.1	19.6


7.7. LTE BAND 13


BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average Power (dBm)	
							Maximum Power	Power Reduction
10	23230	782.0	QPSK	1	0	0	23.6	19.6
				1	24	0	23.6	19.5
				1	49	0	23.5	19.5
				25	0	1	22.3	19.5
				25	12	1	22.3	19.5
				25	24	1	22.3	19.4
				50	0	1	22.2	19.4
			16QAM	1	0	1	22.6	19.7
				1	24	1	22.6	19.7
				1	49	1	22.6	19.7
				25	0	2	21.4	19.5
				25	12	2	21.3	19.5
				25	24	2	21.3	19.4
				50	0	2	21.2	19.3

8. Peak to Average Power Ratio

8.1. GPRS


CELL






8.1. EGPRS


CELL






8.1. CDMA RTT


BC0






8.1. CDMA EV-DO


BC0






8.1. WCDMA REL99


CELL






8.1. WCDMA HSUPA


CELL






8.1. LTE BAND 4 5MHz


QPSK






8.1. LTE BAND 4 10MHz


QPSK






8.1. LTE BAND 4 15MHz


QPSK






8.1. LTE BAND 4 20MHz


QPSK






8.1. LTE BAND 13 10MHz

QPSK





9. CONDUCTED TEST RESULTS

9.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

MODES TESTED

- GPRS
- CDMA 2000, CDMA EV-DO
- UMTS REL 99, and HSUPA
- LTE Band 4 and Band 13

RESULTS

Band	Mode	Channel	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
Cellular	GPRS	128	824.20	251.1908	313.718
		190	836.60	249.8958	312.290
		251	848.80	237.0533	319.434
PCS	GPRS	512	1850.2	250.3149	313.234
		661	1880.0	239.9879	317.742
		810	1909.8	236.9014	301.649

Band	Mode	Channel	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
Cellular	EGPRS	128	824.20	234.7905	308.489
		190	836.60	247.6150	315.780
		251	848.80	245.6720	314.796
PCS	EGPRS	512	1850.2	234.6144	308.196
		661	1880.0	251.0225	324.157
		810	1909.8	259.2402	313.888

Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
Cellular	CDMA 1xRtt	4357	826.4	1.2782	1.411
		4408	836.6	1.2795	1.394
		4458	846.6	1.2616	1.427
PCS		9662	1852.4	1.2897	1.415
		9800	1880	1.2522	1.391
		9938	1907.6	1.2905	1.404

Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
Cellular	CDMA EV-DO	4357	826.4	1.3334	2.573
		4408	836.6	1.2949	1.914
		4458	846.6	1.3007	1.627
PCS		9662	1852.4	1.2767	1.437
		9800	1880	1.2766	1.375
		9938	1907.6	1.2846	1.553

Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
Cellular	REL 99	4357	826.4	4.1808	4.619
		4408	836.6	4.1358	4.603
		4458	846.6	4.1228	4.536
PCS		9662	1852.4	4.1299	4.582
		9800	1880	4.1024	4.571
		9938	1907.6	4.0797	4.609

Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
Cellular	HUSPA	4357	826.4	4.2672	4.507
		4408	836.6	4.1233	4.536
		4458	846.6	4.1630	4.550
PCS		9662	1852.4	4.1353	4.572
		9800	1880	4.1793	4.462
		9938	1907.6	4.2429	4.534


Band	Mode	RB/RB SIZE	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
LTE Band 4	5.0 MHz BAND QPSK	12/6	1712.5	2.1610	2.511
		25/0		4.4585	4.693
		12/6		2.1506	2.591
		25/0		4.3955	4.676
	5.0 MHz BAND QPSK	12/6	1732.5	2.1300	2.447
		25/0		4.4817	4.671
		12/6		2.1536	2.591
		25/0		4.4420	4.790
	5.0 MHz BAND QPSK	12/6	1752.5	2.1485	2.364
		25/0		4.4955	4.670
		12/6		2.1480	2.486
		25/0		4.4280	4.728
	10 MHz BAND QPSK	25/12	1715.0	4.4372	4.618
		50/0		8.9944	9.603
		25/12		4.4065	5.159
		50/0		8.9222	9.215
	10 MHz BAND QPSK	25/12	1732.5	4.4839	4.977
		50/0		8.7718	9.188
		25/12		4.4562	4.911
		50/0		8.8889	9.159
	10 MHz BAND QPSK	25/12	1750.0	4.4373	4.912
		50/0		8.9203	9.456
		25/12		4.4706	5.034
		50/0		8.8600	9.209


Band	Mode	RB/RB SIZE	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
LTE Band 4	15 MHz BAND QPSK	36/18	1717.5	6.4760	7.072
	15 MHz BAND QPSK	75/0		13.4456	13.729
	15 MHz BAND 16QAM	36/18	1732.5	6.4355	7.543
	15 MHz BAND 16QAM	75/0		13.3586	13.881
	15 MHz BAND QPSK	36/18	1747.5	6.3742	7.773
	15 MHz BAND QPSK	75/0		13.4732	13.840
	15 MHz BAND 16QAM	36/18	1720.0	6.4144	7.127
	15 MHz BAND 16QAM	75/0		13.2917	13.771
	15 MHz BAND QPSK	36/18	1732.5	6.4371	7.079
	15 MHz BAND QPSK	75/0		13.2706	13.934
	15 MHz BAND 16QAM	36/18	1745.0	6.4765	7.304
	15 MHz BAND 16QAM	75/0		13.3808	14.071
	20 MHz BAND QPSK	100/0	1720.0	17.8635	18.743
	20 MHz BAND QPSK	50/25		9.0141	9.769
	20 MHz BAND 16QAM	100/0	1732.5	18.0903	18.690
	20 MHz BAND 16QAM	50/25		8.8336	9.243
	20 MHz BAND QPSK	50/25	1745.0	8.9451	9.385
	20 MHz BAND QPSK	100/0		17.6026	18.490
	20 MHz BAND 16QAM	50/25	1745.0	8.8629	9.176
	20 MHz BAND 16QAM	100/0		17.6791	18.636
	20 MHz BAND QPSK	50/25	1745.0	8.9517	9.590
	20 MHz BAND QPSK	100/0		17.9712	18.641
	20 MHz BAND 16QAM	50/25	1745.0	8.7800	9.602
	20 MHz BAND 16QAM	100/0		17.5805	18.622


Band	Mode	RB/RB SIZE	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
LTE Band 13	10 MHz BAND QPSK	25/12	782	4.4242	4.730
		50/0		8.8731	9.318
	10 MHz BAND 16QAM	25/12		4.4983	4.736
		50/0		8.9514	9.174


9.1.1. GPRS MODE


CELL BAND









PCS Band








9.1.1. EGPRS MODE


CELL BAND









PCS Band








9.1.2. CDMA 2000 MODE


CELL Band









PCS Band








9.1.1. CDMA EV-DO MODE


CELL Band









PCS Band








9.1.2. UMTS REL 99 MODE


CELL Band









PCS Band








9.1.1. HSUPA MODE


CELL Band









PCS Band








9.1.2. LTE BAND 4-5MHz BANDWIDTH


LOW-QPSK








LOW-16QAM




MID-QPSK





MID-16QAM





HIGH-QPSK


HIGH CH, RB25_0






HIGH-16QAM





LTE BAND 4-10MHz BANDWIDTH**LOW-QPSK**





LOW-16QAM


MID-QPSK





MID-16QAM



HIGH-QPSK





HIGH-16QAM





9.1.3. LTE BAND 4-15MHz BANDWIDTH


LOW-QPSK








LOW-16QAM





MID-QPSK





MID-16QAM





HIGH-QPSK





HIGH-16QAM





LTE BAND 4-20MHz BANDWIDTH**LOW-QPSK**





LOW-16QAM





MID-QPSK





MID-16QAM



HIGH-QPSK





HIGH-16QAM





9.1.4. LTE BAND 13-10 MHz BANDWIDTH

LOW-QPSK





LOW-16QAM



9.2. BAND EDGE

RULE PART(S)

FCC: §22.359, 24.238

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

The transmitter output was connected to a Agilent 8960 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:

- Set the spectrum analyzer span to include the block edge frequency (824, 848, 1850, 1910MHz)
- Set a marker to point the corresponding band edge frequency in each test case.
- Set display line at -13 dBm
- Set resolution bandwidth to at least 1% of emission bandwidth.


MODES TESTED


- GPRS
- UMTS REL 99, and HSUPA
- CDMA 1xRtt, CDMA EV-DO
- LTE Band 4 and Band 13



RESULTS

9.2.1. GPRS MODE

CELL BAND









PCS BAND

9.2.1. EGPRS MODE

CELL BAND









PCS BAND

9.2.2. UMTS REL 99 MODE

CELL BAND








PCS BAND


9.2.3. UMTS HSUPA MODE

CELL BAND






PCS BAND





9.2.1. CDMA 1xRtt MODE

CELL Band







PCS Band





9.2.2. CDMA EV-DO MODE

CELL Band








PCS Band






9.2.3. LTE BAND 4-5MHZ BANDWIDTH



LOW-QPSK











HIGH-QPSK





LOW-16QAM










HIGH-16QAM








9.2.4. LTE BAND 4-10MHZ BANDWIDTH


LOW-QPSK















HIGH-QPSK












LOW-16QAM






HIGH-16QAM










9.2.5. LTE BAND 4-15MHZ BANDWIDTH



LOW-QPSK












HIGH-QPSK






LOW-16QAM






HIGH-QPSK








9.2.6. LTE BAND 4-20MHZ BANDWIDTH



LOW-QPSK















HIGH-QPSK








LOW-16QAM






HIGH-16QAM











9.2.7. LTE BAND 13-10MHz BANDWIDTH


LOW-QPSK












LOW-16QAM







OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

For each out of band emissions measurement:

- Set display line at -13 dBm
- Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.


MODES TESTED


- GPRS, EGPRS
- CDMA 1xRtt, CDMA EV-DO
- UMTS REL 99, and HSUPA
- LTE Band 4, Band 13


RESULTS


9.2.8. GPRS MODE


CELL BAND









PCS BAND








9.2.1. EGPRS MODE


CELL BAND









PCS BAND








9.2.2. UMTS REL 99 MODE


CELL BAND









PCS BAND









9.2.3. UMTS HSUPA MODE


CELL BAND






PCS BAND








9.2.4. LTE BAND 4-5MHz BANDWIDTH



QPSK









16QAM





9.2.5. LTE BAND 4-10MHz BANDWIDTH



QPSK









16QAM





9.2.6. LTE BAND 4-15MHz BANDWIDTH


QPSK









16QAM








9.2.7. LTE BAND 4-20MHz BANDWIDTH


QPSK









16QAM






9.2.8. LTE BAND 13-10MHz BANDWIDTH

QPSK



16QAM

10. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235

LIMITS

- §22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.
- §24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE

Use Agilent 8960 with Frequency Error measurement capability.

- Temp. = -30° to $+50^{\circ}\text{C}$
- Voltage = 85% - 115%

Frequency Stability vs Temperature:

The EUT is place inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until $+50^{\circ}\text{C}$ is reached.

Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

MODES TESTED

- GPRS
- UMTS
- LTE

RESULTS

See the following pages

10.1.1. CELL, GPRS MODULATION – MID CHANNEL

Reference Frequency: Cellular Mid Channel 836.600027MHz @ 20°C Limit: to stay +- 2.5 ppm = 2091.500 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	836.600000	-0.006	2.5
3.70	40	836.600000	-0.006	2.5
3.70	30	836.599992	0.004	2.5
3.70	20	836.599995	0	2.5
3.70	10	836.599996	-0.001	2.5
3.70	0	836.600001	-0.007	2.5
3.70	-10	836.599997	-0.002	2.5
3.70	-20	836.599991	0.005	2.5
3.70	-30	836.599994	0.001	2.5

Reference Frequency: Cellular Mid Channel 836.600027MHz @ 20°C Limit: to stay +- 2.5 ppm = 2091.500 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	20	836.599995	0	2.5
4.20	20	836.599998	-0.004	2.5
3.30	20	836.599997	-0.002	2.5

10.1.2. PCS, GPRS MODULATION – MID CHANNEL

Reference Frequency: PCS Mid Channel 1880.000036MHz @ 20°C Limit: within the authorized block or +- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse (MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1880.000017	-0.016	2.5
3.70	40	1880.000001	-0.008	2.5
3.70	30	1880.000007	-0.011	2.5
3.70	20	1879.999986	0	2.5
3.70	10	1879.999990	-0.002	2.5
3.70	0	1879.999987	-0.001	2.5
3.70	-10	1879.999988	-0.001	2.5
3.70	-20	1879.999986	0.000	2.5
3.70	-30	1879.999988	-0.001	2.5

Reference Frequency: PCS Mid Channel 1880.000036MHz @ 20°C Limit: within the authorized block or +- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse (MHz)	Delta (ppm)	Limit (ppm)
3.70	20	1879.999986	0.00000	2.5
4.20	20	1879.999997	-0.00585	2.5
3.30	20	1880.000001	-0.00798	2.5

10.1.3. CELL WCDMA – MID CHANNEL

		Limit: to stay +- 2.5 ppm = 2091.500 Hz		
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	836.600000	0.000	2.5
3.70	40	836.600000	0.000	2.5
3.70	30	836.600000	0.000	2.5
3.70	20	836.600000	0	2.5
3.70	10	836.600000	0.000	2.5
3.70	0	836.600000	0.000	2.5
3.70	-10	836.600000	0.000	2.5
3.70	-20	836.600000	0.000	2.5
3.70	-30	836.600000	0.000	2.5

Reference Frequency: Cellular Mid Channel 836.60000MHz @ 20°C				
Limit: to stay +- 2.5 ppm = 2091.500 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	20	836.600000	0	2.5
4.20	20	836.600000	0.000	2.5
3.30	20	836.600000	0.000	2.5

10.1.4. PCS WCDMA – MID CHANNEL

Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1879.999995	-0.001	2.5
3.70	40	1879.999995	-0.001	2.5
3.70	30	1879.999994	0.000	2.5
3.70	20	1879.999994	0	2.5
3.70	10	1879.999994	0.000	2.5
3.70	0	1879.999994	0.000	2.5
3.70	-10	1879.999994	0.000	2.5
3.70	-20	1879.999993	0.001	2.5
3.70	-30	1879.999994	0.000	2.5

Reference Frequency: PCS Mid Channel 1880.000036MHz @ 20°C				
Limit: within the authorized block or +/- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
			Delta (ppm)	Limit (ppm)
3.70	20	1879.999994	0.00000	2.5
4.20	20	1879.999993	0.00053	2.5
3.30	20	1879.999994	0.00000	2.5

10.1.5. LTE BAND 4 – MID CHANNEL (1732.5 MHz)

Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1732.500012	0.000	2.5
3.70	40	1732.500011	0.000	2.5
3.70	30	1732.500010	0.001	2.5
3.70	20	1732.500012	0	2.5
3.70	10	1732.500012	0.000	2.5
3.70	0	1732.500011	0.001	2.5
3.70	-10	1732.500012	0.000	2.5
3.70	-20	1732.500013	-0.001	2.5
3.70	-30	1732.500013	-0.001	2.5

Reference Frequency: Cellular Mid Channel 1732.500012MHz @ 20°C
Limit: to stay +- 2.5 ppm = 4331.250 Hz

Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	20	1732.500012	0	2.5
3.30	20	1732.500013	-0.001	2.5
4.26	20	1732.500012	0.000	2.5

10.1.6. LTE BAND 13 – MID CHANNEL (782.0 MHz)

Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	781.999998	0.001	2.5
3.70	40	781.999999	0.000	2.5
3.70	30	781.999998	0.001	2.5
3.70	20	781.999999	0	2.5
3.70	10	781.999999	0.000	2.5
3.70	0	781.999998	0.001	2.5
3.70	-10	781.999998	0.001	2.5
3.70	-20	781.999998	0.001	2.5
3.70	-30	781.999999	0.000	2.5

Reference Frequency: Cellular Mid Channel 1782.00000MHz
Limit: to stay +- 2.5 ppm = 1955.000 Hz

Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	20	781.999999	0	2.5
3.30	20	781.999999	0.000	2.5
4.26	20	781.999998	0.001	2.5

11. RADIATED TEST RESULTS

11.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

TEST PROCEDURE

ANSI / TIA / EIA 603 Clause 2.2.17

The ERP/EIRP power was measured with the spectrum analyzer which attached with receiver antenna via calibrated cable. The measurements have been taken at the low, middle and high channel in each band.

- Set the spectrum analyzer span wide enough or greater than the modulated signal BW.
- Set a spectrum analyzer at peak detection mode with $\text{VBW} \geq \text{RBW} \geq 26\text{dB}$ BW, typically 3MHz for GSM and 5MHz for WCDMA modes respectively.
- Set a marker to point the corresponding peak value.
- Channel integration power method should be applied if emission BW is greater than 5MHz.

MODES TESTED

- GSM, and GPRS
- UMTS, REL 99, and HSUPA
- LTE 4, LTE 13

RESULTS**GPRS**

Mode	Channel	f (MHz)	ERP	
			dBm	mW
GPRS	128	824.20	29.27	845.28
	190	836.60	28.40	691.83
	251	848.80	29.16	824.14

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
GPRS	512	1850.20	29.01	796.16
	661	1880.00	28.56	717.79
	810	1909.80	27.80	602.56

EGPRS

Mode	Channel	f (MHz)	ERP	
			dBm	mW
EGPRS	128	824.20	26.89	488.65
	190	836.60	25.73	374.11
	251	848.80	26.30	426.58

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
EGPRS	512	1850.20	25.24	334.20
	661	1880.00	25.97	395.37
	810	1909.80	22.19	165.58

REL 99

Mode	Channel	f (MHz)	ERP	
			dBm	mW
REL 99	4357	826.40	20.05	101.16
	4408	836.60	20.73	118.30
	4458	846.60	19.86	96.83

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
REL 99	9662	1852.40	24.66	292.42
	9800	1880.00	24.24	265.46
	9938	1907.60	20.21	104.95

HSUPA

Mode	Channel	f (MHz)	ERP	
			dBm	mW
HSUPA	4357	826.40	20.51	112.46
	4405	836.00	20.77	119.40
	4455	846.00	22.00	158.49

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
HSUPA	9662	1852.40	22.58	181.13
	9800	1880.00	22.29	169.43
	9938	1907.60	19.48	88.72

CDMA 1xRtt

Mode	Channel	f (MHz)	ERP	
			dBm	mW
CDMA 1xRtt	1013	824.70	23.46	221.82
	384	836.52	23.29	213.30
	777	848.31	23.19	208.45

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
CDMA 1xRtt	25	1851.25	23.90	245.47
	600	1880.00	22.50	177.83
	1175	1908.75	22.59	181.55

CDMA EV-DO

Mode	Channel	f (MHz)	ERP	
			dBm	mW
CDMA EV-DO	1013	824.70	25.62	364.75
	384	836.52	25.41	347.54
	777	848.31	25.29	338.06

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
CDMA EV-DO	25	1851.25	23.99	250.61
	600	1880.00	23.53	225.42
	1175	1908.75	23.27	212.32

LTE BAND 4

Mode	RB/RB Offset	f (MHz)	EIRP	
			dBm	mW
5.0 MHZ BAND QPSK	1/0	1712.50	20.63	115.61
		1732.50	19.19	82.99
		1752.50	20.41	109.90
5.0 MHZ BAND 16QAM	1/0	1712.50	19.63	91.83
		1732.50	18.29	67.45
		1752.50	19.41	87.30
10.0 MHZ BAND QPSK	1/0	1715.00	19.53	89.74
		1732.50	18.69	73.96
		1750.00	21.61	144.88
10.0 MHZ BAND 16QAM	1/0	1715.00	18.43	69.66
		1732.50	17.69	58.75
		1750.00	20.61	115.08
15.0 MHZ BAND QPSK	1/0	1717.50	20.33	107.89
		1732.50	18.69	73.96
		1747.50	20.61	115.08
15.0 MHZ BAND 16QAM	1/0	1717.50	19.33	85.70
		1732.50	17.69	58.75
		1747.50	19.61	91.41
20.0 MHZ BAND QPSK	1/0	1720.00	20.33	107.89
		1732.50	18.69	73.96
		1745.00	20.11	102.57
20.0 MHZ BAND 16QAM	1/0	1720.00	19.43	87.70
		1732.50	17.69	58.75
		1745.00	19.11	81.47

LTE BAND 13

Mode	RB/RB Offset	f (MHz)	ERP	
			dBm	mW
10 MHz QPSK	1/0	782.00	21.20	131.83
		782.00	20.10	102.33

11.1.1. GPRS 850 (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/27/13															
Test Engineer:	Steven Tran															
Configuration:	X position, EUT only															
Mode:	TX, GPRS850, Average															
<u>Test Equipment:</u>																
Receiving: Sunol T243 and Chamber B N-type Cable (Setup this one for testing EUT)																
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes								
Low Ch																
824.20	20.69	V	0.5	0.0	20.19	38.5	-18.3									
824.20	29.77	H	0.5	0.0	29.27	38.5	-9.2									
Mid Ch																
836.60	20.02	V	0.5	0.0	19.52	38.5	-18.9									
836.60	28.90	H	0.5	0.0	28.40	38.5	-10.0									
High Ch																
848.80	20.98	V	0.5	0.0	20.48	38.5	-18.0									
848.80	29.66	H	0.5	0.0	29.16	38.5	-9.3									
Rev. 3.17.11																

11.1.2. GPRS 1900 (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/27/13															
Test Engineer:	Steven Tran															
Configuration:	EUT W/ HEADSET+CHARGER, Z POSITION															
Mode:	Tx, GPRS Mode PCS Band, Avg															
<u>Test Equipment:</u>																
Receiving: Horn T59, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.850	21.2	V	0.85	8.62	29.01	33.0	-4.0									
1.850	16.0	H	0.85	8.47	23.62	33.0	-9.4									
Mid Ch																
1.880	21.0	V	0.85	8.46	28.56	33.0	-4.4									
1.880	15.4	H	0.85	8.36	22.93	33.0	-10.1									
High Ch																
1.910	20.4	V	0.85	8.30	27.80	33.0	-5.2									
1.910	14.8	H	0.85	8.25	22.23	33.0	-10.8									
Rev. 3.17.11																

11.1.3. EGPRS 850 (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/27/13															
Test Engineer:	Steven Tran															
Configuration:	EUT only, x position, Avg Detector															
Mode:	Tx, EGPRS Mode Cell Band															
<u>Test Equipment:</u>																
Receiving: Sunol T243, and Chamber B N-type Cable (Setup this one for testing EUT)																
Substitution: Dipole S/N: 00022117, 4ft SMA Cable (SN # 208947003) Warehouse.																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes								
Low ch																
824.20	18.34	V	0.6	0.0	17.74	38.5	-20.7									
824.20	27.49	H	0.6	0.0	26.89	38.5	-11.6									
Mid ch																
836.60	17.07	V	0.6	0.0	16.47	38.5	-22.0									
836.60	26.33	H	0.6	0.0	25.73	38.5	-12.7									
High ch																
848.80	18.29	V	0.6	0.0	17.69	38.5	-20.8									
848.80	26.90	H	0.6	0.0	26.30	38.5	-12.1									
Rev. 3.17.11																

11.1.4. EGPRS 1900 (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/27/13															
Test Engineer:	Steven Tran															
Configuration:	EUT+Headset+Charger, Z position, Avg Detector															
Mode:	Tx, EGPRS Mode PCS Band															
<u>Test Equipment:</u>																
Receiving: Horn T59, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.850	17.5	V	0.85	8.62	25.24	33.0	-7.8									
1.850	12.5	H	0.85	8.47	20.13	33.0	-12.9									
Mid Ch																
1.880	18.4	V	0.85	8.46	25.97	33.0	-7.0									
1.880	13.0	H	0.85	8.36	20.55	33.0	-12.5									
High Ch																
1.910	14.7	V	0.85	8.30	22.19	33.0	-10.8									
1.910	8.1	H	0.85	8.25	15.54	33.0	-17.5									
Rev. 3.17.11																

11.1.5. UMTS 850 REL 99 (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B								
Company: LG Project #: 13U15118 Date: 05/30/13 Test Engineer: Steven Tran Configuration: Z position, EUT only, Avg Detector Mode: WCDMA, Rel 99 850								
Test Equipment:								
Receiving: Sunol T243, and Chamber B N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00022117, 4ft SMA Cable (SN # 208947003) Warehouse.								
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
826.40	13.23	V	0.6	0.0	12.63	38.5	-25.8	
826.40	20.65	H	0.6	0.0	20.05	38.5	-18.4	
Mid ch								
836.60	13.96	V	0.6	0.0	13.36	38.5	-25.1	
836.60	21.33	H	0.6	0.0	20.73	38.5	-17.7	
High Ch								
846.60	13.68	V	0.6	0.0	13.08	38.5	-25.4	
846.60	20.46	H	0.6	0.0	19.86	38.5	-18.6	

Rev. 3.17.11

11.1.6. UMTS 850 REL 99 (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/28/13															
Test Engineer:	Steven Tran															
Configuration:	EUT, x position w/ headset and charger, Avg detector															
Mode:	TX, UMTS REL 99 1900															
Test Equipment:																
Receiving: Horn T73, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1852.400	10.7	V	0.85	8.38	18.27	33.0	-14.7									
1852.400	16.9	H	0.85	8.59	24.66	33.0	-8.3									
Mid Ch																
1.880	10.4	V	0.85	8.26	17.77	33.0	-15.2									
1.880	16.5	H	0.85	8.55	24.24	33.0	-8.8									
High Ch																
1907.600	6.3	V	0.85	8.21	13.68	33.0	-19.3									
1907.600	12.5	H	0.85	8.54	20.21	33.0	-12.8									
Rev. 3.17.11																

11.1.7. UMTS 850 HSUPA (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/30/13															
Test Engineer:	Steven Tran															
Configuration:	Z Configuration, EUT w/ headset and charger, Avg detector															
Mode:	WCDMA, Rel 99 850															
Test Equipment:																
Receiving: Sunol T243, and Chamber B N-type Cable (Setup this one for testing EUT)																
Substitution: Dipole S/N: 00022117, 4ft SMA Cable (SN # 208947003) Warehouse.																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes								
Low Ch																
826.40	12.33	V	0.6	0.0	11.73	38.5	-26.7									
826.40	21.11	H	0.6	0.0	20.51	38.5	-17.9									
Mid ch																
836.60	12.73	V	0.6	0.0	12.13	38.5	-26.3									
836.60	21.37	H	0.6	0.0	20.77	38.5	-17.7									
High Ch																
846.60	12.68	V	0.6	0.0	12.08	38.5	-26.4									
846.60	22.60	H	0.6	0.0	22.00	38.5	-16.4									
Rev. 3.17.11																

11.1.8. UMTS 850 HSUPA (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/30/13															
Test Engineer:	Steven Tran															
Configuration:	EUT, x position w/ headset and charger, Avg detector															
Mode:	TX, UMTS HSUPA Subset 5 1900															
<u>Test Equipment:</u>																
Receiving: Horn T73, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1852.400	8.0	V	0.85	8.38	15.56	33.0	-17.4									
1852.400	14.8	H	0.85	8.59	22.58	33.0	-10.4									
Mid Ch																
1.880	8.3	V	0.85	8.26	15.71	33.0	-17.3									
1.880	14.6	H	0.85	8.55	22.29	33.0	-10.7									
High Ch																
1907.600	7.1	V	0.85	8.21	14.50	33.0	-18.5									
1907.600	11.8	H	0.85	8.54	19.48	33.0	-13.5									
Rev. 3.17.11																

11.1.9. CDMA 1xRtt (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B								
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
824.70	16.32	V	0.6	0.0	15.72	38.5	-22.7	
824.70	24.06	H	0.6	0.0	23.46	38.5	-15.0	
Mid ch								
836.52	16.46	V	0.6	0.0	15.86	38.5	-22.6	
836.52	23.89	H	0.6	0.0	23.29	38.5	-15.2	
High Ch								
848.31	16.86	V	0.6	0.0	16.26	38.5	-22.2	
848.31	23.79	H	0.6	0.0	23.19	38.5	-15.3	

Rev. 3.17.11

11.1.10. CDMA 1xRtt (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/30/13															
Test Engineer:	Steven Tran															
Configuration:	EUT, x position w/ headset and charger, Avg detector															
Mode:	TX, UMTS REL 99 1900															
<u>Test Equipment:</u>																
Receiving: Horn T73, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1851.250	9.0	V	0.85	8.38	16.48	33.0	-16.5									
1851.250	16.2	H	0.85	8.59	23.90	33.0	-9.1									
Mid Ch																
1.880	6.4	V	0.85	8.26	13.83	33.0	-19.2									
1.880	14.8	H	0.85	8.55	22.50	33.0	-10.5									
High Ch																
1908.750	5.4	V	0.85	8.21	12.77	33.0	-20.2									
1908.750	14.9	H	0.85	8.54	22.59	33.0	-10.4									
Rev. 3.17.11																

11.1.11. CDMA EV-DO (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	06/07/13															
Test Engineer:	Steven Tran															
Configuration:	Z position, EUT only, Avg Detector															
Mode:	CDMA 850 EV-DO															
Test Equipment:																
Receiving: Sunol T243, and Chamber B N-type Cable (Setup this one for testing EUT)																
Substitution: Dipole S/N: 00022117, 4ft SMA Cable (SN # 208947003) Warehouse.																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes								
Low Ch																
824.70	19.55	V	0.6	0.0	18.95	38.5	-19.5									
824.70	26.22	H	0.6	0.0	25.62	38.5	-12.8									
Mid ch																
836.52	18.50	V	0.6	0.0	17.90	38.5	-20.5									
836.52	26.01	H	0.6	0.0	25.41	38.5	-13.0									
High Ch																
848.31	16.86	V	0.6	0.0	16.26	38.5	-22.2									
848.31	25.89	H	0.6	0.0	25.29	38.5	-13.2									
Rev. 3.17.11																

11.1.12. CDMA EV-DO (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B																
Company:	LG															
Project #:	13U15118															
Date:	05/30/13															
Test Engineer:	Steven Tran															
Configuration:	EUT, x position w/charger, Avg detector															
Mode:	TX, CDMA EV-DO 1900, AVG detector															
<u>Test Equipment:</u>																
Receiving: Horn T73, and Chamber B SMA Cables																
Substitution: Horn T217 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1851.250	10.8	V	0.85	8.38	18.33	33.0	-14.7									
1851.250	16.3	H	0.85	8.59	23.99	33.0	-9.0									
Mid Ch																
1.880	8.8	V	0.85	8.26	16.25	33.0	-16.8									
1.880	15.8	H	0.85	8.55	23.53	33.0	-9.5									
High Ch																
1908.750	7.7	V	0.85	8.21	15.06	33.0	-17.9									
1908.750	15.6	H	0.85	8.54	23.27	33.0	-9.7									
Rev. 3.17.11																

11.1.13. LTE BAND 4-5MHz BANDWIDTH

QPSK (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 5MHz BW QPSK, Average, RB1-0															
Test Equipment:																
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.713	13.3	V	0.85	8.16	20.63	30.0	-9.4									
1.713	10.8	H	0.85	8.59	18.54	30.0	-11.5									
Mid Ch																
1.733	11.9	V	0.85	8.11	19.19	30.0	-10.8									
1.733	10.3	H	0.85	8.69	18.16	30.0	-11.8									
High Ch																
1.753	13.2	V	0.85	8.07	20.41	30.0	-9.6									
1.753	11.5	H	0.85	8.79	19.41	30.0	-10.6									
Rev. 3.17.11																

16QAM (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 5MHz BW 16QAM, Average, RB1-0															
<u>Test Equipment:</u>																
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
<u>Low Ch</u>																
1.713	12.3	V	0.85	8.16	19.63	30.0	-10.4									
1.713	9.5	H	0.85	8.59	17.24	30.0	-12.8									
<u>Mid Ch</u>																
1.733	11.0	V	0.85	8.11	18.29	30.0	-11.7									
1.733	9.4	H	0.85	8.69	17.26	30.0	-12.7									
<u>High Ch</u>																
1.753	12.2	V	0.85	8.07	19.41	30.0	-10.6									
1.753	10.6	H	0.85	8.79	18.51	30.0	-11.5									
Rev. 3.17.11																

11.1.14. LTE BAND 4-10MHz BANDWIDTH

QPSK (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 10MHz BW															
Test Equipment:	QPSK, Average, RB1-0															
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.715	12.2	V	0.85	8.16	19.53	30.0	-10.5									
1.715	10.2	H	0.85	8.59	17.94	30.0	-12.1									
Mid Ch																
1.733	11.4	V	0.85	8.11	18.69	30.0	-11.3									
1.733	9.8	H	0.85	8.69	17.66	30.0	-12.3									
High Ch																
1.750	14.4	V	0.85	8.07	21.61	30.0	-8.4									
1.750	12.1	H	0.85	8.79	20.01	30.0	-10.0									
Rev. 3.17.11																

16QAM (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 10MHz BW 16QAM, Average, RB1-0															
Test Equipment:																
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.715	11.1	V	0.85	8.16	18.43	30.0	-11.6									
1.715	9.1	H	0.85	8.59	16.84	30.0	-13.2									
Mid Ch																
1.733	10.4	V	0.85	8.11	17.69	30.0	-12.3									
1.733	8.8	H	0.85	8.69	16.66	30.0	-13.3									
High Ch																
1.750	13.4	V	0.85	8.07	20.61	30.0	-9.4									
1.750	11.0	H	0.85	8.79	18.91	30.0	-11.1									
Rev. 3.17.11																

11.1.15. LTE BAND 4-15MHz BANDWIDTH**QPSK (EIRP)**

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 15MHz BW															
Test Equipment:	QPSK, Average, RB1-0															
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.718	13.0	V	0.85	8.16	20.33	30.0	-9.7									
1.718	10.8	H	0.85	8.59	18.54	30.0	-11.5									
Mid Ch																
1.733	11.4	V	0.85	8.11	18.69	30.0	-11.3									
1.733	9.4	H	0.85	8.69	17.26	30.0	-12.7									
High Ch																
1.748	13.4	V	0.85	8.07	20.61	30.0	-9.4									
1.748	12.0	H	0.85	8.79	19.91	30.0	-10.1									
Rev. 3.17.11																

16QAM (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 15MHz BW 16QAM, Average, RB1-0															
<u>Test Equipment:</u>																
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.718	12.0	V	0.85	8.16	19.33	30.0	-10.7									
1.718	9.8	H	0.85	8.59	17.54	30.0	-12.5									
Mid Ch																
1.733	10.4	V	0.85	8.11	17.69	30.0	-12.3									
1.733	8.4	H	0.85	8.69	16.26	30.0	-13.7									
High Ch																
1.748	12.4	V	0.85	8.07	19.61	30.0	-10.4									
1.748	10.9	H	0.85	8.79	18.81	30.0	-11.2									
Rev. 3.17.11																

11.1.16. LTE BAND 4-20MHz BANDWIDTH**QPSK (EIRP)**

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 20MHz BW															
Test Equipment:	QPSK, Average, RB1-0															
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.720	13.0	V	0.85	8.16	20.33	30.0	-9.7									
1.720	12.4	H	0.85	8.59	20.14	30.0	-9.9									
Mid Ch																
1.733	11.4	V	0.85	8.11	18.69	30.0	-11.3									
1.733	10.6	H	0.85	8.69	18.46	30.0	-11.5									
High Ch																
1.745	12.9	V	0.85	8.07	20.11	30.0	-9.9									
1.745	11.7	H	0.85	8.79	19.61	30.0	-10.4									
Rev. 3.17.11																

16QAM (EIRP)

High Frequency Fundamental Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin Pang															
Configuration:	EUT Only															
Mode:	LTE band 4, 20MHz BW 16QAM, Average, RB1-0															
Test Equipment:																
Receiving: Horn T344, and Chamber B SMA Cables																
Substitution: Horn T60 Substitution, 4ft SMA Cable (244639001) Warehouse																
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes								
Low Ch																
1.720	12.1	V	0.85	8.16	19.43	30.0	-10.6									
1.720	11.3	H	0.85	8.59	19.04	30.0	-11.0									
Mid Ch																
1.733	10.4	V	0.85	8.11	17.69	30.0	-12.3									
1.733	9.7	H	0.85	8.69	17.56	30.0	-12.4									
High Ch																
1.745	11.9	V	0.85	8.07	19.11	30.0	-10.9									
1.745	10.8	H	0.85	8.79	18.71	30.0	-11.3									
Rev. 3.17.11																

11.1.17. LTE BAND 13-10MHz BANDWIDTH**QPSK and 16QAM (ERP)**

High Frequency Substitution Measurement Compliance Certification Services Chamber D																
Company:	LG															
Project #:	VS980															
Date:	05/25/13															
Test Engineer:	Chin PANG															
Configuration:	EUT Only															
Mode:	TX, LTE BAND 13 QPSK and 16QAM, 10MHz, Average															
Test Equipment:																
Receiving: Sunol T402, and Chamber D N-type Cable (Setup this one for testing EUT)																
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes								
RB=1-0, QPSK																
782.00	12.00	V	0.5	0.0	11.50	38.5	-26.9									
782.00	21.70	H	0.5	0.0	21.20	38.5	-17.2									
RB=1-0, 16QAM																
782.00	11.00	V	0.5	0.0	10.50	38.5	-27.9									
782.00	20.60	H	0.5	0.0	20.10	38.5	-18.3									
Rev. 3.17.11																

11.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238

LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

MODES TESTED

- GPRS, EGPRS
- UMTS REL 99, and HSUPA
- LTE Band 4 and Band 13

RESULTS

11.2.1. GPRS (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	05/23/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT w/ charger								
Mode:	Tx, 850MHz GPRS MODE								
Chamber	Pre-amplifier	Filter	Limit						
5m Chamber B	T34 8449B	Filter 1	Part 22						
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.2MHz)									
1.648	-19.7	V	3.0	37.4	1.0	-56.0	-13.0	-43.0	
2.473	-15.1	V	3.0	36.4	1.0	-50.5	-13.0	-37.5	
1.648	-17.1	H	3.0	37.4	1.0	-53.5	-13.0	-40.5	
2.473	-14.7	H	3.0	36.4	1.0	-50.1	-13.0	-37.1	
Mid Ch, (836.6MHz)									
1.673	-22.4	V	3.0	37.3	1.0	-58.7	-13.0	-45.7	
2.510	-18.1	V	3.0	36.4	1.0	-53.5	-13.0	-40.5	
1.673	-20.7	H	3.0	37.3	1.0	-57.0	-13.0	-44.0	
2.510	-15.1	H	3.0	36.4	1.0	-50.5	-13.0	-37.5	
High Ch, (848.8MHz)									
1.698	-21.5	V	3.0	37.3	1.0	-57.8	-13.0	-44.8	
2.546	-20.3	V	3.0	36.3	1.0	-55.6	-13.0	-42.6	
1.698	-23.5	H	3.0	37.3	1.0	-59.8	-13.0	-46.8	
2.546	-16.1	H	3.0	36.3	1.0	-51.4	-13.0	-38.4	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.2. GPRS (Cellular Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT w/wireless ac								
Mode:	Tx, 850MHz GPRS MODE								
Chamber	Pre-amplifier	Filter	Limit						
5m Chamber B	T34 8449B	Filter 1	Part 22						
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.2MHz)									
1.648	-25.7	V	3.0	37.4	1.0	-62.1	-13.0	-49.1	
2.473	-24.0	V	3.0	36.4	1.0	-59.4	-13.0	-46.4	
1.648	-19.5	H	3.0	37.4	1.0	-55.9	-13.0	-42.9	
2.473	-20.8	H	3.0	36.4	1.0	-56.2	-13.0	-43.2	
Mid Ch, (836.6MHz)									
1.673	-27.1	V	3.0	37.3	1.0	-63.4	-13.0	-50.4	
2.510	-19.0	V	3.0	36.4	1.0	-54.4	-13.0	-41.4	
1.673	-26.2	H	3.0	37.3	1.0	-62.5	-13.0	-49.5	
2.510	-13.8	H	3.0	36.4	1.0	-49.2	-13.0	-36.2	
High Ch, (848.8MHz)									
1.698	-25.4	V	3.0	37.3	1.0	-61.7	-13.0	-48.7	
2.546	-22.3	V	3.0	36.3	1.0	-57.6	-13.0	-44.6	
1.698	-19.6	H	3.0	37.3	1.0	-55.9	-13.0	-42.9	
2.546	-17.8	H	3.0	36.3	1.0	-53.1	-13.0	-40.1	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.3. GPRS (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	05/23/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT with charger								
Mode:	Tx, 1900MHz GPRS MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T34 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.700	-13.4	V	3.0	35.4	1.0	-47.8	-13.0	-34.8	
5.551	-11.5	V	3.0	34.7	1.0	-45.3	-13.0	-32.3	
3.700	-13.6	H	3.0	35.4	1.0	-48.0	-13.0	-35.0	
5.551	-7.3	H	3.0	34.7	1.0	-41.1	-13.0	-28.1	
Mid Ch, 1880MHz									
3.760	-11.2	V	3.0	35.3	1.0	-45.6	-13.0	-32.6	
5.640	-12.6	V	3.0	34.7	1.0	-46.3	-13.0	-33.3	
3.760	-11.1	H	3.0	35.3	1.0	-45.5	-13.0	-32.5	
5.640	-10.1	H	3.0	34.7	1.0	-43.8	-13.0	-30.8	
High Ch, 1909.8MHz									
3.820	-11.8	V	3.0	35.3	1.0	-46.1	-13.0	-33.1	
5.729	-14.4	V	3.0	34.7	1.0	-48.1	-13.0	-35.1	
3.820	-11.0	H	3.0	35.3	1.0	-45.3	-13.0	-32.3	
5.729	-10.9	H	3.0	34.7	1.0	-44.6	-13.0	-31.6	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.4. GPRS (PCS) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT with wireless ac								
Mode:	Tx, 1900MHz GPRS MODE								
	Chamber		Pre-amplifier		Filter		Limit		
	5m Chamber B		T34 8449B		Filter 1		Part 24		
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.700	-13.4	V	3.0	35.4	1.0	-47.8	-13.0	-34.8	
5.551	-16.3	V	3.0	34.7	1.0	-50.0	-13.0	-37.0	
3.700	-12.9	H	3.0	35.4	1.0	-47.3	-13.0	-34.3	
5.551	-14.5	H	3.0	34.7	1.0	-48.3	-13.0	-35.3	
Mid Ch, 1880MHz									
3.760	-11.8	V	3.0	35.3	1.0	-46.1	-13.0	-33.1	
5.640	-16.6	V	3.0	34.7	1.0	-50.3	-13.0	-37.3	
3.760	-11.8	H	3.0	35.3	1.0	-46.2	-13.0	-33.2	
5.640	-15.6	H	3.0	34.7	1.0	-49.3	-13.0	-36.3	
High Ch, 1909.8MHz									
3.820	-15.1	V	3.0	35.3	1.0	-49.4	-13.0	-36.4	
5.729	-17.2	V	3.0	34.7	1.0	-50.9	-13.0	-37.9	
3.820	-13.5	H	3.0	35.3	1.0	-47.8	-13.0	-34.8	
5.729	-15.1	H	3.0	34.7	1.0	-48.8	-13.0	-35.8	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.5. EGPRS (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	05/23/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT w/ charger								
Mode:	Tx, 850MHz EGPRS MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T34 8449B		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.2MHz)									
1.648	-22.4	V	3.0	37.4	1.0	-58.8	-13.0	-45.8	
1.648	-16.1	H	3.0	37.4	1.0	-52.5	-13.0	-39.5	
Mid Ch, (836.6MHz)									
1.673	-24.4	V	3.0	37.3	1.0	-60.7	-13.0	-47.7	
1.673	-22.6	H	3.0	37.3	1.0	-58.9	-13.0	-45.9	
High Ch, (848.8MHz)									
1.698	-24.0	V	3.0	37.3	1.0	-60.3	-13.0	-47.3	
1.698	-21.6	H	3.0	37.3	1.0	-57.9	-13.0	-44.9	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.6. EGPRS (Cellular Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT w/ wireless ac								
Mode:	Tx, 850MHz EGPRS MODE								
Chamber	Pre-amplifier	Filter	Limit						
5m Chamber B	T34 8449B	Filter 1	Part 22						
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.2MHz)									
1.648	-27.7	V	3.0	37.4	1.0	-64.0	-13.0	-51.0	
1.648	-26.3	H	3.0	37.4	1.0	-62.6	-13.0	-49.6	
Mid Ch, (836.6MHz)									
1.673	-27.4	V	3.0	37.3	1.0	-63.8	-13.0	-50.8	
1.673	-25.8	H	3.0	37.3	1.0	-62.2	-13.0	-49.2	
High Ch, (848.8MHz)									
1.698	-24.1	V	3.0	37.3	1.0	-60.4	-13.0	-47.4	
1.698	-19.4	H	3.0	37.3	1.0	-55.7	-13.0	-42.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

11.2.7. EGPRS (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT with charger								
Mode:	Tx, 1900MHz EGPRS MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T34 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.700	-16.6	V	3.0	35.4	1.0	-51.0	-13.0	-38.0	
5.551	-15.0	V	3.0	34.7	1.0	-48.8	-13.0	-35.8	
3.700	-14.6	H	3.0	35.4	1.0	-49.0	-13.0	-36.0	
5.551	-10.7	H	3.0	34.7	1.0	-44.4	-13.0	-31.4	
Mid Ch, 1880MHz									
3.760	-12.5	V	3.0	35.3	1.0	-46.8	-13.0	-33.8	
5.640	-16.3	V	3.0	34.7	1.0	-50.0	-13.0	-37.0	
3.760	-13.3	H	3.0	35.3	1.0	-47.7	-13.0	-34.7	
5.640	-13.1	H	3.0	34.7	1.0	-46.9	-13.0	-33.9	
High Ch, 1909.8MHz									
3.820	-14.2	V	3.0	35.3	1.0	-48.5	-13.0	-35.5	
5.729	-18.1	V	3.0	34.7	1.0	-51.9	-13.0	-38.9	
3.820	-13.4	H	3.0	35.3	1.0	-47.7	-13.0	-34.7	
5.729	-15.5	H	3.0	34.7	1.0	-49.3	-13.0	-36.3	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.8. EGPRS (PCS Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, EUT with wireless ac								
Mode:	Tx, 1900MHz EGPRS MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T34 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.700	-15.1	V	3.0	35.4	1.0	-49.5	-13.0	-36.5	
5.551	-19.3	V	3.0	34.7	1.0	-53.0	-13.0	-40.0	
3.700	-14.0	H	3.0	35.4	1.0	-48.4	-13.0	-35.4	
5.551	-18.3	H	3.0	34.7	1.0	-52.0	-13.0	-39.0	
Mid Ch, 1880MHz									
3.760	-15.7	V	3.0	35.3	1.0	-50.0	-13.0	-37.0	
5.640	-20.3	V	3.0	34.7	1.0	-54.1	-13.0	-41.1	
3.760	-14.7	H	3.0	35.3	1.0	-49.1	-13.0	-36.1	
5.640	-19.8	H	3.0	34.7	1.0	-53.5	-13.0	-40.5	
High Ch, 1909.8MHz									
3.820	-17.1	V	3.0	35.3	1.0	-51.4	-13.0	-38.4	
5.729	-18.3	V	3.0	34.7	1.0	-52.0	-13.0	-39.0	
3.820	-14.6	H	3.0	35.3	1.0	-48.9	-13.0	-35.9	
5.729	-17.6	H	3.0	34.7	1.0	-51.3	-13.0	-38.3	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.9. WCDMA REL 99 (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	Z Configuration, All Peripherals Attached								
Mode:	TX, UMTS 850MHz, Rel 99								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		FCC Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.4MHz)									
1.653	-14.5	V	3.0	35.5	1.0	-49.0	-13.0	-36.0	
1.653	-15.5	H	3.0	35.5	1.0	-50.0	-13.0	-37.0	
Mid Channel (836.6MHz)									
1.673	-13.1	V	3.0	35.5	1.0	-47.6	-13.0	-34.6	
1.673	-14.8	H	3.0	35.5	1.0	-49.3	-13.0	-36.3	
High Channel (846.8MHz)									
1.694	-9.7	V	3.0	35.5	1.0	-44.3	-13.0	-31.3	
1.694	-6.7	H	3.0	35.5	1.0	-41.2	-13.0	-28.2	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.10. WCDMA (Cellular Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X Configuration, w/ wireless AC								
Mode:	TX, UMTS 850MHz, Rel 99								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		FCC Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.4MHz)									
1.653	-25.7	V	3.0	35.5	1.0	-60.3	-13.0	-47.3	
1.653	-20.8	H	3.0	35.5	1.0	-55.4	-13.0	-42.4	
Mid Channel (836.6MHz)									
1.673	-25.1	V	3.0	35.5	1.0	-59.6	-13.0	-46.6	
1.673	-23.2	H	3.0	35.5	1.0	-57.7	-13.0	-44.7	
High Channel (846.8MHz)									
1.694	-16.4	V	3.0	35.5	1.0	-50.9	-13.0	-37.9	
1.694	-9.8	H	3.0	35.5	1.0	-44.3	-13.0	-31.3	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

11.2.11. WCDMA REL 99 (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, AC Adapter Plugged								
Mode:	Tx, 1900MHz WCDMA Rel 99 MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.705	-21.5	V	3.0	35.4	1.0	-55.9	-13.0	-42.9	
3.705	-21.3	H	3.0	35.4	1.0	-55.7	-13.0	-42.7	
Mid Ch, 1880.0MHz									
3.760	-21.4	V	3.0	35.3	1.0	-55.8	-13.0	-42.8	
3.760	-18.4	H	3.0	35.3	1.0	-52.7	-13.0	-39.7	
High Ch, 1907.6MHz									
3.815	-23.2	V	3.0	35.3	1.0	-57.5	-13.0	-44.5	
3.815	-21.0	H	3.0	35.3	1.0	-55.3	-13.0	-42.3	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.12. WCDMA (PCS Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/04/13								
Test Engineer:	Steven Tran								
Configuration:	X position, Headset and Wireless Adapter								
Mode:	Tx, 1900MHz WCDMA Rel 99 MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.705	-24.1	V	3.0	35.4	1.0	-58.5	-13.0	-45.5	
3.705	-21.0	H	3.0	35.4	1.0	-55.4	-13.0	-42.4	
Mid Ch, 1880.0MHz									
3.760	-24.0	V	3.0	35.3	1.0	-58.3	-13.0	-45.3	
3.760	-22.0	H	3.0	35.3	1.0	-56.3	-13.0	-43.3	
High Ch, 1907.6MHz									
3.815	-23.3	V	3.0	35.3	1.0	-57.6	-13.0	-44.6	
3.815	-21.8	H	3.0	35.3	1.0	-56.1	-13.0	-43.1	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.13. WCDMA HSUPA (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/06/13								
Test Engineer:	Steven Tran								
Configuration:	Z position, all peripheals								
Mode:	Tx, 850MHz WCDMA HSUPA MODE								
Chamber	Pre-amplifier		Filter		Limit				
5m Chamber B	T145 8449B		Filter 1		FCC Part 22				
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.4MHz)									
1.653	-21.9	V	3.0	35.5	1.0	-56.4	-13.0	-43.4	
1.653	-21.9	H	3.0	35.5	1.0	-56.4	-13.0	-43.4	
Mid Channel (836.6MHz)									
1.673	-22.3	V	3.0	35.5	1.0	-56.8	-13.0	-43.8	
1.673	-23.7	H	3.0	35.5	1.0	-58.2	-13.0	-45.2	
High Channel (846.8MHz)									
1.694	-21.3	V	3.0	35.5	1.0	-55.8	-13.0	-42.8	
1.694	-23.0	H	3.0	35.5	1.0	-57.6	-13.0	-44.6	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

11.2.14. WCDMA HSUPA (Cell Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/06/13								
Test Engineer:	Steven Tran								
Configuration:	X position with wireless ac								
Mode:	Tx, 850MHz WCDMA HSUPA MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		FCC Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.4MHz)									
1.653	-23.5	V	3.0	35.5	1.0	-58.1	-13.0	-45.1	
1.653	-22.7	H	3.0	35.5	1.0	-57.2	-13.0	-44.2	
Mid Channel (836.6MHz)									
1.673	-23.8	V	3.0	35.5	1.0	-58.4	-13.0	-45.4	
1.673	-23.2	H	3.0	35.5	1.0	-57.7	-13.0	-44.7	
High Channel (846.8MHz)									
1.694	-18.7	V	3.0	35.5	1.0	-53.2	-13.0	-40.2	
1.694	-14.9	H	3.0	35.5	1.0	-49.4	-13.0	-36.4	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.15. WCDMA HSUPA (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/06/13								
Test Engineer:	Steven Tran								
Configuration:	EUT, x position, all peripheals attached								
Mode:	Tx, 1900MHz WCDMA HSDPA MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.705	-23.1	V	3.0	35.4	1.0	-57.5	-13.0	-44.5	
3.705	-21.4	H	3.0	35.4	1.0	-55.8	-13.0	-42.8	
Mid Ch, 1880.0MHz									
3.760	-23.4	V	3.0	35.3	1.0	-57.7	-13.0	-44.7	
3.760	-22.9	H	3.0	35.3	1.0	-57.2	-13.0	-44.2	
High Ch, 1907.6MHz									
3.815	-23.0	V	3.0	35.3	1.0	-57.3	-13.0	-44.3	
3.815	-22.4	H	3.0	35.3	1.0	-56.7	-13.0	-43.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

11.2.16. WCDMA HSUPA (PCS Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/06/13								
Test Engineer:	Steven Tran								
Configuration:	X position with wireless ac								
Mode:	Tx, 1900MHz WCDMA HSDPA MODE								
Chamber		Pre-amplifier		Filter		Limit			
5m Chamber B		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.705	-22.2	V	3.0	35.4	1.0	-56.5	-13.0	-43.5	
3.705	-20.7	H	3.0	35.4	1.0	-55.0	-13.0	-42.0	
Mid Ch, 1880.0MHz									
3.760	-22.9	V	3.0	35.3	1.0	-57.2	-13.0	-44.2	
3.760	-22.5	H	3.0	35.3	1.0	-56.8	-13.0	-43.8	
High Ch, 1907.6MHz									
3.815	-22.9	V	3.0	35.3	1.0	-57.3	-13.0	-44.3	
3.815	-21.8	H	3.0	35.3	1.0	-56.1	-13.0	-43.1	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.17. CDMA 1xRTT (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, CDMA2000, BC0, 1xRTT								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.7 MHz)									
1.649	-22.5	V	3.0	32.7	1.0	-54.1	-13.0	-41.1	
2.474	-22.3	V	3.0	31.4	1.0	-52.7	-13.0	-39.7	
1.649	-23.7	H	3.0	32.7	1.0	-55.3	-13.0	-42.3	
2.474	-23.1	H	3.0	31.4	1.0	-53.5	-13.0	-40.5	
Mid Ch, (836.52MHz)									
1.673	-24.4	V	3.0	32.6	1.0	-56.0	-13.0	-43.0	
2.509	-23.1	V	3.0	31.5	1.0	-53.6	-13.0	-40.6	
1.673	-24.6	H	3.0	32.6	1.0	-56.2	-13.0	-43.2	
2.509	-23.0	H	3.0	31.5	1.0	-53.5	-13.0	-40.5	
High Ch, (848.31MHz)									
1.697	-24.4	V	3.0	32.6	1.0	-56.0	-13.0	-43.0	
2.545	-23.1	V	3.0	31.4	1.0	-53.6	-13.0	-40.6	
1.697	-25.5	H	3.0	32.6	1.0	-57.1	-13.0	-44.1	
2.545	-24.2	H	3.0	31.4	1.0	-54.6	-13.0	-41.6	
Rev. 05.31.13 Note: No other emissions were detected above the system noise floor.									

11.2.18. CDMA 2000 (Cell Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with all peripheals (wireless ac)								
Mode:	TX, CDMA2000, BC0, 1xRTT								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.7 MHz)									
1.649	-24.4	V	3.0	32.7	1.0	-56.0	-13.0	-43.0	
1.649	-25.4	H	3.0	32.7	1.0	-57.1	-13.0	-44.1	
Mid Ch, (836.52MHz)									
1.673	-25.0	V	3.0	32.6	1.0	-56.6	-13.0	-43.6	
1.673	-26.6	H	3.0	32.6	1.0	-58.2	-13.0	-45.2	
High Ch, (848.31MHz)									
1.697	-24.1	V	3.0	32.6	1.0	-55.7	-13.0	-42.7	
1.697	-25.5	H	3.0	32.6	1.0	-57.0	-13.0	-44.0	
Rev. 05.31.13 Note: No other emissions were detected above the system noise floor.									

11.2.19. CDMA 2000 (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, CDMA2000, BC1, 1xRTT								
Chamber	Pre-amplifier		Filter		Limit				
3m Chamber F	T145 8449B		Filter 1		Part 24				
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1851.25 MHz)									
3.703	-24.9	V	3.0	30.2	1.0	-54.1	-13.0	-41.1	
5.554	-25.0	V	3.0	28.4	1.0	-52.4	-13.0	-39.4	
11.108	-19.7	V	3.0	22.8	1.0	-41.5	-13.0	-28.5	
3.703	-24.3	H	3.0	30.2	1.0	-53.5	-13.0	-40.5	
5.554	-25.5	H	3.0	28.4	1.0	-52.9	-13.0	-39.9	
5.554	-25.5	H	3.0	28.4	1.0	-52.9	-13.0	-39.9	
Mid Ch, (1880 MHz)									
3.760	-19.9	V	3.0	30.1	1.0	-49.1	-13.0	-36.1	
5.640	-22.8	V	3.0	28.3	1.0	-50.1	-13.0	-37.1	
11.280	-21.0	V	3.0	22.7	1.0	-42.7	-13.0	-29.7	
3.760	-23.3	H	3.0	30.1	1.0	-52.4	-13.0	-39.4	
5.640	-23.4	H	3.0	28.3	1.0	-50.7	-13.0	-37.7	
11.280	-24.3	H	3.0	22.7	1.0	-46.0	-13.0	-33.0	
High Ch, (1908.75MHz)									
3.818	-23.9	V	3.0	30.1	1.0	-53.0	-13.0	-40.0	
5.726	-27.7	V	3.0	28.2	1.0	-54.9	-13.0	-41.9	
11.452	-19.3	V	3.0	22.7	1.0	-41.0	-13.0	-28.0	
3.818	-24.3	H	3.0	30.1	1.0	-53.4	-13.0	-40.4	
5.726	-26.3	H	3.0	28.2	1.0	-53.5	-13.0	-40.5	
11.452	-20.6	H	3.0	22.7	1.0	-42.3	-13.0	-29.3	

Rev. 05.31.13
Note: No other emissions were detected above the system noise floor.

11.2.20. CDMA 2000 (PCS Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	EUT w/ wireless ac								
Mode:	TX, CDMA2000, BC1, 1xRTT								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1851.25 MHz)									
3.703	-28.3	V	3.0	30.2	1.0	-57.5	-13.0	-44.5	
3.703	-28.8	H	3.0	30.2	1.0	-58.0	-13.0	-45.0	
Mid Ch, (1880 MHz)									
3.760	-26.6	V	3.0	30.1	1.0	-55.7	-13.0	-42.7	
3.760	-27.4	H	3.0	30.1	1.0	-56.5	-13.0	-43.5	
High Ch, (1908.75MHz)									
3.818	-29.4	V	3.0	30.1	1.0	-58.5	-13.0	-45.5	
3.818	-29.0	H	3.0	30.1	1.0	-58.1	-13.0	-45.1	

Rev. 05.31.13
Note: No other emissions were detected above the system noise floor.

11.2.21. CDMA EV-DO (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	Z position, EUT with ac adapter								
Mode:	TX, CDMA, BC0, EVDO								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.7 MHz)									
1.649	-24.3	V	3.0	32.7	1.0	-56.0	-13.0	-43.0	
1.649	-25.2	H	3.0	32.7	1.0	-56.9	-13.0	-43.9	
Mid Ch, (836.52MHz)									
1.673	-24.5	V	3.0	32.6	1.0	-56.1	-13.0	-43.1	
1.673	-26.8	H	3.0	32.6	1.0	-58.4	-13.0	-45.4	
High Ch, (848.31MHz)									
1.697	-25.5	V	3.0	32.6	1.0	-57.1	-13.0	-44.1	
1.697	-25.8	H	3.0	32.6	1.0	-57.3	-13.0	-44.3	
Rev. 05.31.13 Note: No other emissions were detected above the system noise floor.									

11.2.22. CDMA EV-DO (Cell Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with all peripherals (wireless ac)								
Mode:	TX, CDMA, BC0, EVDO								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (824.7 MHz)									
1.649	-24.4	V	3.0	32.7	1.0	-56.0	-13.0	-43.0	
1.649	-25.4	H	3.0	32.7	1.0	-57.1	-13.0	-44.1	
Mid Ch, (836.52MHz)									
1.673	-25.0	V	3.0	32.6	1.0	-56.6	-13.0	-43.6	
1.673	-26.6	H	3.0	32.6	1.0	-58.2	-13.0	-45.2	
High Ch, (848.31MHz)									
1.697	-24.1	V	3.0	32.6	1.0	-55.7	-13.0	-42.7	
1.697	-25.5	H	3.0	32.6	1.0	-57.0	-13.0	-44.0	
Rev. 05.31.13									
Note: No other emissions were detected above the system noise floor.									

11.2.23. CDMA EV-DO (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	EUT, x position, ac adapter								
Mode:	TX, CDMA, BC1, EVDO								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1851.25 MHz)									
3.703	-27.7	V	3.0	30.2	1.0	-56.9	-13.0	-43.9	
3.703	-27.4	H	3.0	30.2	1.0	-56.6	-13.0	-43.6	
Mid Ch, (1880 MHz)									
3.760	-27.7	V	3.0	30.1	1.0	-56.9	-13.0	-43.9	
3.760	-27.1	H	3.0	30.1	1.0	-56.3	-13.0	-43.3	
High Ch, (1908.75MHz)									
3.818	-29.8	V	3.0	30.1	1.0	-58.9	-13.0	-45.9	
3.818	-29.2	H	3.0	30.1	1.0	-58.3	-13.0	-45.3	
Rev. 05.31.13 Note: No other emissions were detected above the system noise floor.									

11.2.24. CDMA EV-DO (PCS Band) with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/07/13								
Test Engineer:	Steven Tran								
Configuration:	EUT w/ wireless ac								
Mode:	TX, CDMA, BC1, EVDO								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 24			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1851.25 MHz)									
3.703	-27.9	V	3.0	30.2	1.0	-57.1	-13.0	-44.1	
3.703	-28.2	H	3.0	30.2	1.0	-57.4	-13.0	-44.4	
Mid Ch, (1880 MHz)									
3.760	-26.0	V	3.0	30.1	1.0	-55.1	-13.0	-42.1	
3.760	-27.0	H	3.0	30.1	1.0	-56.1	-13.0	-43.1	
High Ch, (1908.75MHz)									
3.818	-28.5	V	3.0	30.1	1.0	-57.6	-13.0	-44.6	
3.818	-26.8	H	3.0	30.1	1.0	-55.9	-13.0	-42.9	

Rev. 05.31.13
Note: No other emissions were detected above the system noise floor.

11.2.25. LTE BAND 4-5MHz BANDWIDTH**QPSK**

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:									
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 5MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber D		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1712.5 MHz)									
3.420	-26.0	V	3.0	26.5	1.0	-51.5	-13.0	-38.5	
5.138	-30.4	V	3.0	24.4	1.0	-53.8	-13.0	-40.8	
3.420	-25.3	H	3.0	26.5	1.0	-50.7	-13.0	-37.7	
5.138	-29.0	H	3.0	24.4	1.0	-52.3	-13.0	-39.3	
Mid Ch, (1732.5 MHz)									
3.465	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.198	-27.6	V	3.0	24.3	1.0	-50.9	-13.0	-37.9	
3.465	-26.3	H	3.0	26.4	1.0	-51.7	-13.0	-38.7	
5.198	-29.0	H	3.0	24.3	1.0	-52.3	-13.0	-39.3	
High Ch, (1752.5 MHz)									
3.505	-26.0	V	3.0	26.4	1.0	-51.4	-13.0	-38.4	
5.258	-30.5	V	3.0	24.3	1.0	-53.7	-13.0	-40.7	
3.505	-26.3	H	3.0	26.4	1.0	-51.6	-13.0	-38.6	
5.258	-27.9	H	3.0	24.3	1.0	-51.2	-13.0	-38.2	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

QPSK with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/11/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 5MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber D		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1712.5 MHz)									
3.420	-23.2	V	3.0	26.5	1.0	-48.6	-13.0	-35.6	
5.138	-28.5	V	3.0	24.4	1.0	-51.8	-13.0	-38.8	
3.420	-24.6	H	3.0	26.5	1.0	-50.0	-13.0	-37.0	
5.138	-28.4	H	3.0	24.4	1.0	-51.7	-13.0	-38.7	
Mid Ch, (1732.5 MHz)									
3.465	-24.3	V	3.0	26.4	1.0	-49.7	-13.0	-36.7	
5.198	-28.2	V	3.0	24.3	1.0	-51.5	-13.0	-38.5	
3.465	-24.1	H	3.0	26.4	1.0	-49.5	-13.0	-36.5	
5.198	-23.1	H	3.0	24.3	1.0	-46.4	-13.0	-33.4	
High Ch, (1752.5 MHz)									
3.505	-24.4	V	3.0	26.4	1.0	-49.7	-13.0	-36.7	
5.258	-29.7	V	3.0	24.3	1.0	-52.9	-13.0	-39.9	
3.505	-24.7	H	3.0	26.4	1.0	-50.1	-13.0	-37.1	
5.258	-29.4	H	3.0	24.3	1.0	-52.6	-13.0	-39.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:									
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 5MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber D		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1712.5 MHz)									
3.420	-26.8	V	3.0	26.5	1.0	-52.3	-13.0	-39.3	
5.138	-31.4	V	3.0	24.4	1.0	-54.8	-13.0	-41.8	
3.420	-26.0	H	3.0	26.5	1.0	-51.4	-13.0	-38.4	
5.138	-29.8	H	3.0	24.4	1.0	-53.1	-13.0	-40.1	
Mid Ch, (1732.5 MHz)									
3.465	-27.7	V	3.0	26.4	1.0	-53.1	-13.0	-40.1	
5.198	-28.1	V	3.0	24.3	1.0	-51.4	-13.0	-38.4	
3.465	-27.3	H	3.0	26.4	1.0	-52.7	-13.0	-39.7	
5.198	-29.6	H	3.0	24.3	1.0	-52.9	-13.0	-39.9	
High Ch, (1752.5 MHz)									
3.505	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.258	-31.2	V	3.0	24.3	1.0	-54.4	-13.0	-41.4	
3.505	-27.8	H	3.0	26.4	1.0	-53.1	-13.0	-40.1	
5.258	-28.0	H	3.0	24.3	1.0	-51.3	-13.0	-38.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company: Project #: 13U15118 Date: 06/10/13 Test Engineer: Steven Tran Configuration: EUT with wireless AC Mode: TX, LTE band 4, 5MHz BW, 16QAM									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber D		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1712.5 MHz)									
3.420	-27.1	V	3.0	26.5	1.0	-52.6	-13.0	-39.6	
5.138	-31.9	V	3.0	24.4	1.0	-55.2	-13.0	-42.2	
3.420	-27.6	H	3.0	26.5	1.0	-53.1	-13.0	-40.1	
5.138	-31.4	H	3.0	24.4	1.0	-54.7	-13.0	-41.7	
Mid Ch, (1732.5 MHz)									
3.465	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.198	-29.4	V	3.0	24.3	1.0	-52.7	-13.0	-39.7	
3.465	-26.8	H	3.0	26.4	1.0	-52.2	-13.0	-39.2	
5.198	-27.1	H	3.0	24.3	1.0	-50.4	-13.0	-37.4	
High Ch, (1752.5 MHz)									
3.505	-27.8	V	3.0	26.4	1.0	-53.2	-13.0	-40.2	
5.258	-31.5	V	3.0	24.3	1.0	-54.8	-13.0	-41.8	
3.505	-27.9	H	3.0	26.4	1.0	-53.3	-13.0	-40.3	
5.258	-26.9	H	3.0	24.3	1.0	-50.2	-13.0	-37.2	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

11.2.26. LTE BAND 4-10MHz BANDWIDTH**QPSK**

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 10MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1715 MHz)									
3.430	-25.0	V	3.0	26.5	1.0	-50.5	-13.0	-37.5	
5.145	-25.5	V	3.0	24.4	1.0	-48.8	-13.0	-35.8	
3.430	-23.3	H	3.0	26.5	1.0	-48.7	-13.0	-35.7	
5.145	-26.0	H	3.0	24.4	1.0	-49.3	-13.0	-36.3	
Mid Ch, (1732.5 MHz)									
3.456	-26.0	V	3.0	26.4	1.0	-51.4	-13.0	-38.4	
5.184	-25.5	V	3.0	24.3	1.0	-48.9	-13.0	-35.9	
3.456	-24.3	H	3.0	26.4	1.0	-49.7	-13.0	-36.7	
5.184	-27.0	H	3.0	24.3	1.0	-50.3	-13.0	-37.3	
High Ch, (1750 MHz)									
3.491	-26.0	V	3.0	26.4	1.0	-51.4	-13.0	-38.4	
5.237	-28.5	V	3.0	24.3	1.0	-51.8	-13.0	-38.8	
3.491	-25.3	H	3.0	26.4	1.0	-50.7	-13.0	-37.7	
5.237	-27.0	H	3.0	24.3	1.0	-50.2	-13.0	-37.2	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

QPSK with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/11/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 10MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1715 MHz)									
3.430	-23.4	V	3.0	26.5	1.0	-48.9	-13.0	-35.9	
5.145	-29.2	V	3.0	24.4	1.0	-52.5	-13.0	-39.5	
3.430	-20.4	H	3.0	26.5	1.0	-45.8	-13.0	-32.8	
5.145	-20.9	H	3.0	24.4	1.0	-44.2	-13.0	-31.2	
Mid Ch, (1732.5 MHz)									
3.456	-21.6	V	3.0	26.4	1.0	-47.0	-13.0	-34.0	
5.184	-25.6	V	3.0	24.3	1.0	-48.9	-13.0	-35.9	
3.456	-22.5	H	3.0	26.4	1.0	-47.9	-13.0	-34.9	
5.184	-22.5	H	3.0	24.3	1.0	-45.8	-13.0	-32.8	
High Ch, (1750 MHz)									
3.491	-21.8	V	3.0	26.4	1.0	-47.2	-13.0	-34.2	
5.237	-26.8	V	3.0	24.3	1.0	-50.1	-13.0	-37.1	
3.491	-23.8	H	3.0	26.4	1.0	-49.2	-13.0	-36.2	
5.237	-23.9	H	3.0	24.3	1.0	-47.2	-13.0	-34.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 10MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1715 MHz)									
3.430	-26.0	V	3.0	26.5	1.0	-51.5	-13.0	-38.5	
5.145	-26.5	V	3.0	24.4	1.0	-49.8	-13.0	-36.8	
3.430	-24.3	H	3.0	26.5	1.0	-49.7	-13.0	-36.7	
5.145	-27.2	H	3.0	24.4	1.0	-50.5	-13.0	-37.5	
Mid Ch, (1732.5 MHz)									
3.456	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.184	-26.7	V	3.0	24.3	1.0	-50.1	-13.0	-37.1	
3.456	-25.3	H	3.0	26.4	1.0	-50.7	-13.0	-37.7	
5.184	-27.8	H	3.0	24.3	1.0	-51.1	-13.0	-38.1	
High Ch, (1750 MHz)									
3.491	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.237	-30.5	V	3.0	24.3	1.0	-53.8	-13.0	-40.8	
3.491	-26.3	H	3.0	26.4	1.0	-51.7	-13.0	-38.7	
5.237	-27.8	H	3.0	24.3	1.0	-51.0	-13.0	-38.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/10/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 10MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1715 MHz)									
3.430	-24.8	V	3.0	26.5	1.0	-50.3	-13.0	-37.3	
5.145	-25.1	V	3.0	24.4	1.0	-48.5	-13.0	-35.5	
3.430	-27.5	H	3.0	26.5	1.0	-53.0	-13.0	-40.0	
5.145	-23.2	H	3.0	24.4	1.0	-46.5	-13.0	-33.5	
Mid Ch, (1732.5 MHz)									
3.456	-27.0	V	3.0	26.4	1.0	-52.4	-13.0	-39.4	
5.184	97.4	V	3.0	24.3	1.0	74.1	-13.0	87.1	
3.456	-27.2	H	3.0	26.4	1.0	-52.6	-13.0	-39.6	
5.184	-19.5	H	3.0	24.3	1.0	-42.8	-13.0	-29.8	
High Ch, (1750 MHz)									
3.491	-27.4	V	3.0	26.4	1.0	-52.8	-13.0	-39.8	
5.237	-32.4	V	3.0	24.3	1.0	-55.7	-13.0	-42.7	
3.491	-26.2	H	3.0	26.4	1.0	-51.6	-13.0	-38.6	
5.237	-31.1	H	3.0	24.3	1.0	-54.3	-13.0	-41.3	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.27. LTE BAND 4-15MHz BANDWIDTH**QPSK**

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 15MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1717.5 MHz)									
3.435	-25.5	V	3.0	30.4	1.0	-54.9	-13.0	-41.9	
5.153	-28.6	V	3.0	28.7	1.0	-56.3	-13.0	-43.3	
3.435	-24.3	H	3.0	30.4	1.0	-53.7	-13.0	-40.7	
5.153	-26.0	H	3.0	28.7	1.0	-53.7	-13.0	-40.7	
Mid Ch, (1732.5 MHz)									
3.452	-25.0	V	3.0	30.4	1.0	-54.4	-13.0	-41.4	
5.178	-29.5	V	3.0	28.7	1.0	-57.3	-13.0	-44.3	
3.452	-24.3	H	3.0	30.4	1.0	-53.7	-13.0	-40.7	
5.178	-28.0	H	3.0	28.7	1.0	-55.7	-13.0	-42.7	
High Ch, (1747.5 MHz)									
3.495	-24.5	V	3.0	30.4	1.0	-53.9	-13.0	-40.9	
5.243	-27.5	V	3.0	28.7	1.0	-55.2	-13.0	-42.2	
3.495	-23.3	H	3.0	30.4	1.0	-52.6	-13.0	-39.6	
5.243	-26.9	H	3.0	28.7	1.0	-54.6	-13.0	-41.6	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

QPSK with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/11/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 15MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1717.5 MHz)									
3.435	-22.8	V	3.0	30.4	1.0	-52.2	-13.0	-39.2	
5.153	-27.9	V	3.0	28.7	1.0	-55.6	-13.0	-42.6	
3.435	-23.2	H	3.0	30.4	1.0	-52.6	-13.0	-39.6	
5.153	-25.5	H	3.0	28.7	1.0	-53.2	-13.0	-40.2	
Mid Ch, (1732.5 MHz)									
3.452	-20.2	V	3.0	30.4	1.0	-49.7	-13.0	-36.7	
5.178	-24.5	V	3.0	28.7	1.0	-52.2	-13.0	-39.2	
3.452	-20.9	H	3.0	30.4	1.0	-50.3	-13.0	-37.3	
5.178	-25.6	H	3.0	28.7	1.0	-53.3	-13.0	-40.3	
High Ch, (1747.5 MHz)									
3.495	-22.3	V	3.0	30.4	1.0	-51.6	-13.0	-38.6	
5.243	-30.1	V	3.0	28.7	1.0	-57.7	-13.0	-44.7	
3.495	-24.9	H	3.0	30.4	1.0	-54.2	-13.0	-41.2	
5.243	-22.7	H	3.0	28.7	1.0	-50.3	-13.0	-37.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 15MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1717.5 MHz)									
3.435	-26.0	V	3.0	30.4	1.0	-55.4	-13.0	-42.4	
5.153	-29.1	V	3.0	28.7	1.0	-56.8	-13.0	-43.8	
3.435	-24.9	H	3.0	30.4	1.0	-54.3	-13.0	-41.3	
5.153	-27.0	H	3.0	28.7	1.0	-54.7	-13.0	-41.7	
Mid Ch, (1732.5 MHz)									
3.452	-25.6	V	3.0	30.4	1.0	-55.0	-13.0	-42.0	
5.178	-29.3	V	3.0	28.7	1.0	-57.1	-13.0	-44.1	
3.452	-24.8	H	3.0	30.4	1.0	-54.2	-13.0	-41.2	
5.178	-28.0	H	3.0	28.7	1.0	-55.7	-13.0	-42.7	
High Ch, (1747.5 MHz)									
3.495	-25.0	V	3.0	30.4	1.0	-54.4	-13.0	-41.4	
5.243	-28.2	V	3.0	28.7	1.0	-55.9	-13.0	-42.9	
3.495	-24.3	H	3.0	30.4	1.0	-53.6	-13.0	-40.6	
5.243	-27.3	H	3.0	28.7	1.0	-55.0	-13.0	-42.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/10/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 15MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1717.5 MHz)									
3.435	-25.2	V	3.0	30.4	1.0	-54.6	-13.0	-41.6	
5.153	-29.5	V	3.0	28.7	1.0	-57.3	-13.0	-44.3	
3.435	-25.8	H	3.0	30.4	1.0	-55.2	-13.0	-42.2	
5.153	-28.4	H	3.0	28.7	1.0	-56.2	-13.0	-43.2	
Mid Ch, (1732.5 MHz)									
3.452	-24.6	V	3.0	30.4	1.0	-54.0	-13.0	-41.0	
5.178	-25.9	V	3.0	28.7	1.0	-53.7	-13.0	-40.7	
3.452	-23.5	H	3.0	30.4	1.0	-52.9	-13.0	-39.9	
5.178	-18.0	H	3.0	28.7	1.0	-45.8	-13.0	-32.8	
High Ch, (1747.5 MHz)									
3.495	-25.2	V	3.0	30.4	1.0	-54.6	-13.0	-41.6	
5.243	-29.8	V	3.0	28.7	1.0	-57.4	-13.0	-44.4	
3.495	-25.0	H	3.0	30.4	1.0	-54.4	-13.0	-41.4	
5.243	-28.5	H	3.0	28.7	1.0	-56.2	-13.0	-43.2	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

11.2.28. LTE BAND 4-20MHz BANDWIDTH**QPSK**

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 20MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1720 MHz)									
3.423	-24.0	V	3.0	30.4	1.0	-53.5	-13.0	-40.5	
5.133	-28.4	V	3.0	28.8	1.0	-56.2	-13.0	-43.2	
3.423	-24.8	H	3.0	30.4	1.0	-54.2	-13.0	-41.2	
5.133	-27.0	H	3.0	28.8	1.0	-54.7	-13.0	-41.7	
Mid Ch, (1732.5 MHz)									
3.447	-23.0	V	3.0	30.4	1.0	-52.4	-13.0	-39.4	
5.198	-26.6	V	3.0	28.7	1.0	-54.3	-13.0	-41.3	
3.447	-23.3	H	3.0	30.4	1.0	-52.7	-13.0	-39.7	
5.198	-23.0	H	3.0	28.7	1.0	-50.7	-13.0	-37.7	
High Ch, (1745 MHz)									
3.470	-25.0	V	3.0	30.4	1.0	-54.4	-13.0	-41.4	
5.206	-28.6	V	3.0	28.7	1.0	-56.3	-13.0	-43.3	
3.470	-25.3	H	3.0	30.4	1.0	-54.7	-13.0	-41.7	
5.206	-28.0	H	3.0	28.7	1.0	-55.7	-13.0	-42.7	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

QPSK with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/11/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 20MHz BW, QPSK								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1720 MHz)									
3.423	-16.6	V	3.0	30.4	1.0	-46.1	-13.0	-33.1	
5.133	-20.6	V	3.0	28.8	1.0	-48.4	-13.0	-35.4	
3.423	-18.1	H	3.0	30.4	1.0	-47.5	-13.0	-34.5	
5.133	-22.3	H	3.0	28.8	1.0	-50.1	-13.0	-37.1	
Mid Ch, (1732.5 MHz)									
3.447	-22.5	V	3.0	30.4	1.0	-51.9	-13.0	-38.9	
5.198	-24.9	V	3.0	28.7	1.0	-52.6	-13.0	-39.6	
3.447	-20.5	H	3.0	30.4	1.0	-50.0	-13.0	-37.0	
5.198	-22.0	H	3.0	28.7	1.0	-49.7	-13.0	-36.7	
High Ch, (1745 MHz)									
3.470	-22.8	V	3.0	30.4	1.0	-52.2	-13.0	-39.2	
5.206	-24.1	V	3.0	28.7	1.0	-51.8	-13.0	-38.8	
3.470	101.1	H	3.0	30.4	1.0	71.7	-13.0	84.7	
5.206	-21.6	H	3.0	28.7	1.0	-49.3	-13.0	-36.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

16QAM

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/01/13								
Test Engineer:	Chin Pang								
Configuration:	EUT only								
Mode:	TX, LTE band 4, 20MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1720 MHz)									
3.423	-25.0	V	3.0	30.4	1.0	-54.5	-13.0	-41.5	
5.133	-28.8	V	3.0	28.8	1.0	-56.6	-13.0	-43.6	
3.423	-25.3	H	3.0	30.4	1.0	-54.7	-13.0	-41.7	
5.133	-27.4	H	3.0	28.8	1.0	-55.1	-13.0	-42.1	
Mid Ch, (1732.5 MHz)									
3.447	-23.7	V	3.0	30.4	1.0	-53.1	-13.0	-40.1	
5.198	-27.1	V	3.0	28.7	1.0	-54.8	-13.0	-41.8	
3.447	-24.3	H	3.0	30.4	1.0	-53.7	-13.0	-40.7	
5.198	-23.6	H	3.0	28.7	1.0	-51.3	-13.0	-38.3	
High Ch, (1745 MHz)									
3.470	-25.3	V	3.0	30.4	1.0	-54.7	-13.0	-41.7	
5.206	-29.0	V	3.0	28.7	1.0	-56.7	-13.0	-43.7	
3.470	-26.0	H	3.0	30.4	1.0	-55.4	-13.0	-42.4	
5.206	-28.5	H	3.0	28.7	1.0	-56.2	-13.0	-43.2	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

16QAM with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/10/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 4, 20MHz BW, 16QAM								
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		T145 8449B		Filter 1		Part 27			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (1720 MHz)									
3.423	-28.4	V	3.0	30.4	1.0	-57.9	-13.0	-44.9	
5.133	-35.1	V	3.0	28.8	1.0	-62.9	-13.0	-49.9	
3.423	-28.8	H	3.0	30.4	1.0	-58.2	-13.0	-45.2	
5.133	-30.8	H	3.0	28.8	1.0	-58.6	-13.0	-45.6	
Mid Ch, (1732.5 MHz)									
3.447	-26.2	V	3.0	30.4	1.0	-55.6	-13.0	-42.6	
5.198	99.7	V	3.0	28.7	1.0	72.0	-13.0	85.0	
3.447	-22.2	H	3.0	30.4	1.0	-51.6	-13.0	-38.6	
5.198	-24.4	H	3.0	28.7	1.0	-52.1	-13.0	-39.1	
High Ch, (1745 MHz)									
3.470	-30.1	V	3.0	30.4	1.0	-59.5	-13.0	-46.5	
5.206	-35.5	V	3.0	28.7	1.0	-63.2	-13.0	-50.2	
3.470	-30.6	H	3.0	30.4	1.0	-60.0	-13.0	-47.0	
5.206	-31.9	H	3.0	28.7	1.0	-59.6	-13.0	-46.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

11.2.29. LTE BAND 13-10MHz BANDWIDTH**QPSK and 16QAM**

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Chamber		Pre-amplifier		Filter		Limit			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
QPSK									
Mid Ch, (782 MHz)									
1.564	-16.6	V	3.0	30.7	1.0	-46.3	-13.0	-33.3	
2.346	-13.2	V	3.0	28.9	1.0	-41.1	-13.0	-28.1	
1.564	-19.9	H	3.0	30.7	1.0	-49.6	-13.0	-36.6	
2.346	-18.8	H	3.0	28.9	1.0	-46.6	-13.0	-33.6	
16QAM									
Mid Ch, (782 MHz)									
1.564	-17.7	V	3.0	30.7	1.0	-47.4	-13.0	-34.4	
2.346	-16.8	V	3.0	28.9	1.0	-44.7	-13.0	-31.7	
1.564	-21.9	H	3.0	30.7	1.0	-51.6	-13.0	-38.6	
2.346	-19.8	H	3.0	28.9	1.0	-47.6	-13.0	-34.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

QPSK and 16QAM with Wireless Adapter

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement									
Company:	LG								
Project #:	13U15118								
Date:	06/11/13								
Test Engineer:	Steven Tran								
Configuration:	EUT with wireless ac								
Mode:	TX, LTE band 13, 10MHz, QPSK/16QAM								
Chamber	Pre-amplifier	Filter	Limit						
3m Chamber F	T145 8449B	Filter 1	Part 27						
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
QPSK									
Mid Ch, (782 MHz)									
1.564	-23.7	V	3.0	30.7	1.0	-53.4	-13.0	-40.4	
2.346	-19.6	V	3.0	28.9	1.0	-47.4	-13.0	-34.4	
1.564	-20.7	H	3.0	30.7	1.0	-50.4	-13.0	-37.4	
2.346	-22.5	H	3.0	28.9	1.0	-50.4	-13.0	-37.4	
16QAM									
Mid Ch, (782 MHz)									
1.564	-24.7	V	3.0	30.7	1.0	-54.4	-13.0	-41.4	
2.346	-21.1	V	3.0	28.9	1.0	-49.0	-13.0	-36.0	
1.564	-21.1	H	3.0	30.7	1.0	-50.8	-13.0	-37.8	
2.346	-22.8	H	3.0	28.9	1.0	-50.7	-13.0	-37.7	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									