

# EMI CERTIFICATION REPORT

**Applicant:**

**LG Electronics MobileComm U.S.A., Inc.**  
**1000 Sylvan Avenue, Englewood Cliffs NJ 07632**

**Date of Receipt: February 12, 2015****Date of Issue: February 26, 2015****Test Report No. HCT-E-1502-F046****HCT FRN: 0005866421****FCC ID:****ZNFW150****Rule Part(s) / Standard(s):** FCC CFR 47 PART 15 Subpart B Class B**FCC Classification:** JBP (Part 15 B – Class B Computing Device Peripheral)**EUT Type:** SMART WATCH with Bluetooth and WLAN**Model Name:** LG-W150**Additional Model Name:** LGW150, W150**Test Port:** USB Port**Date of Test:** February 23, 2015 - February 25, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**

**Kyoung-Hee Yoon**  
**Test Engineer**  
**EMC Team**  
**Certification Division**

**Reviewed By**

**Jin-Pyo Hong**  
**Technical Manager**  
**EMC Team**  
**Certification Division**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1502-F046	February 26, 2015	Initial Release



## TABLE OF CONTENTS

	<b>PAGE</b>
1. GENERAL INFORMATION .....	4
1.1 Description of EUT .....	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Test Facility .....	5
1.4 Tested System Details.....	6
1.5 Cable Description .....	7
1.6 Noise Suppression Parts on Cable. (I/O Cable) .....	7
2. DESCRIPTION OF TEST.....	8
3. PRELIMINARY TEST .....	11
3.1 Conducted Emission Test .....	11
3. 2 Radiated Emission Test .....	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY .....	12
4.1 Conducted Emission Test .....	12
4.2 Radiated Emission Test .....	19
5. LIST OF TEST EQUIPMENT .....	21
6. CONCLUSION .....	22

**ATTACHMENT:     TEST SETUP PHOTOGRAPHS**



## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**  
Its basic purpose is used for communications.

<b>Model</b>	LG-W150
<b>FCC ID</b>	ZNFW150
<b>Additional Model</b>	LGW150, W150
<b>EUT Type</b>	SMART WATCH with Bluetooth and WLAN

### 1.2 Related Submittal(s) / Grant(s)

Original submittal only.



### 1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



## 1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-W150	LG	ZNFW150	Notebook PC,
Cradle	SDT-330	PNTelcom	-	EUT, USB cable
USB cable	EAD62377902	Ningbo Broad	-	EUT, Notebook PC
USB cable	EAD62377903	KSD	-	EUT, Notebook PC
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway



## 1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT(with Cradle)	Micro USB	Y	Y	(P)1.0
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

\* The marked "(D)" means the data cable and "(P)" means the power cable.

## 1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT(with Cradle)	Micro USB	N	N/A	Y	Both End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



## 2. DESCRIPTION OF TEST

### 2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 7

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### [ Conducted Emission Limits ]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

\*Decreases with the logarithm of the frequency.



## 2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a 3 m shield room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

### [ Radiated Emission Limits ]

Frequency (MHz)	Antenna Distance (m)	Field Strength ( $\mu\text{V}/\text{m}$ )	Quasi-Peak (dB( $\mu\text{V}$ ))/m)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak (dB( $\mu\text{V}$ ))/m)	Average (dB( $\mu\text{V}$ ))/m)
Above 1 000	3	74	54




## 2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

## 2.3 Configuration of Tested System





### 3. PRELIMINARY TEST

#### 3.1 Conducted Emission Test

It was tested Data Link mode, after connecting all peripheral devices.

**Operation Mode:**       Data Link mode

#### 3.2 Radiated Emission Test

It was tested Data Link mode, after connecting all peripheral devices.

**Operation Mode:**       Data Link mode



## 4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY


### 4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Quasi-Peak, CISPR-Average
<b>Bandwidth</b>	9 kHz (6 dB)
<b>Operation Mode</b>	Data Link mode
<b>USB Cable Type</b>	Ningbo Broad <b>*NOTE:</b> The worst-case emissions are reported.
<b>Kind of Test Site</b>	Shielded Room
<b>Temperature</b>	19.8 °C
<b>Relative Humidity</b>	26.0 %
<b>Test Date</b>	February 25, 2015

#### - Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage = Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

**Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)**




## QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	43.6	9.000	L1	9.6	22.3	65.9
0.158000	41.6	9.000	L1	9.6	24.0	65.6
0.196000	51.5	9.000	L1	9.6	12.3	63.8
0.202000	50.9	9.000	L1	9.7	12.6	63.5
0.208000	50.1	9.000	L1	9.7	13.2	63.3
0.214000	47.4	9.000	L1	9.7	15.6	63.0
4.038000	38.9	9.000	L1	9.9	17.1	56.0
4.124000	37.8	9.000	L1	9.9	18.2	56.0
4.170000	38.9	9.000	L1	9.9	17.2	56.0
4.530000	39.2	9.000	L1	9.9	16.8	56.0
4.672000	38.3	9.000	L1	9.9	17.7	56.0
4.676000	37.4	9.000	L1	9.9	18.6	56.0
15.076000	31.0	9.000	L1	10.2	29.0	60.0
15.572000	31.4	9.000	L1	10.2	28.6	60.0
17.346000	31.6	9.000	L1	10.2	28.4	60.0
17.772000	31.3	9.000	L1	10.3	28.7	60.0
17.914000	30.8	9.000	L1	10.3	29.2	60.0
18.342000	29.4	9.000	L1	10.3	30.6	60.0



## CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.158000	15.2	9.000	L1	9.6	40.4	55.6
0.190000	26.2	9.000	L1	9.6	27.8	54.0
0.196000	34.0	9.000	L1	9.6	19.8	53.8
0.202000	34.6	9.000	L1	9.7	18.9	53.5
0.210000	31.6	9.000	L1	9.7	21.6	53.2
0.260000	25.9	9.000	L1	9.7	25.5	51.4
4.038000	29.8	9.000	L1	9.9	16.2	46.0
4.108000	30.2	9.000	L1	9.9	15.8	46.0
4.174000	30.7	9.000	L1	9.9	15.3	46.0
4.322000	30.4	9.000	L1	9.9	15.6	46.0
4.532000	30.3	9.000	L1	9.9	15.7	46.0
4.676000	30.0	9.000	L1	9.9	16.0	46.0
15.572000	24.1	9.000	L1	10.2	25.9	50.0
16.144000	24.1	9.000	L1	10.2	25.9	50.0
17.066000	24.3	9.000	L1	10.2	25.7	50.0
17.346000	24.5	9.000	L1	10.2	25.5	50.0
17.914000	22.8	9.000	L1	10.3	27.2	50.0
18.056000	21.8	9.000	L1	10.3	28.2	50.0

**Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)**



## QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	47.0	9.000	N	9.6	19.0	66.0
0.192000	53.4	9.000	N	9.6	10.5	63.9
0.198000	54.0	9.000	N	9.6	9.7	63.7
0.202000	53.7	9.000	N	9.6	9.8	63.5
0.206000	53.1	9.000	N	9.6	10.3	63.4
0.212000	52.0	9.000	N	9.6	11.1	63.1
4.392000	39.0	9.000	N	9.9	17.0	56.0
4.428000	38.6	9.000	N	9.9	17.4	56.0
4.534000	39.0	9.000	N	9.9	17.0	56.0
4.604000	38.9	9.000	N	9.9	17.1	56.0
4.608000	38.0	9.000	N	9.9	18.0	56.0
4.678000	37.9	9.000	N	9.9	18.1	56.0
15.514000	30.9	9.000	N	10.2	29.1	60.0
17.856000	32.6	9.000	N	10.3	27.4	60.0
17.924000	32.4	9.000	N	10.3	27.6	60.0
18.060000	32.9	9.000	N	10.3	27.1	60.0
18.064000	31.8	9.000	N	10.3	28.2	60.0
18.274000	30.8	9.000	N	10.3	29.2	60.0



## CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	22.8	9.000	N	9.6	33.2	56.0
0.192000	31.9	9.000	N	9.6	22.0	53.9
0.198000	36.8	9.000	N	9.6	16.9	53.7
0.202000	36.7	9.000	N	9.6	16.8	53.5
0.206000	35.8	9.000	N	9.6	17.6	53.4
0.212000	31.1	9.000	N	9.6	22.0	53.1
4.392000	30.6	9.000	N	9.9	15.4	46.0
4.428000	30.6	9.000	N	9.9	15.4	46.0
4.532000	30.7	9.000	N	9.9	15.3	46.0
4.608000	30.4	9.000	N	9.9	15.6	46.0
4.612000	30.2	9.000	N	9.9	15.8	46.0
4.678000	30.4	9.000	N	9.9	15.6	46.0
15.514000	24.7	9.000	N	10.2	25.3	50.0
15.584000	24.3	9.000	N	10.2	25.7	50.0
17.498000	25.5	9.000	N	10.2	24.5	50.0
17.856000	24.7	9.000	N	10.3	25.3	50.0
18.060000	24.0	9.000	N	10.3	26.0	50.0
18.274000	22.4	9.000	N	10.3	27.6	50.0



## 4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

### -For Measurement Below 1 GHz

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Quasi-Peak
<b>Bandwidth</b>	120 kHz (6 dB)
<b>Operation Mode</b>	Data Link mode
<b>USB Cable Type</b>	Ningbo Broad <b>*NOTE:</b> The worst-case emissions are reported.
<b>Kind of Test Site</b>	3 m semi anechoic chamber
<b>Temperature</b>	19.2 °C
<b>Relative Humidity</b>	28.0 %
<b>Test Date</b>	February 23, 2015

Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
71.781643	32.6	231.0	H	179.0	13.7	7.4	40.0
266.554309	34.2	100.0	H	119.0	16.9	11.8	46.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



## -For Measurement Above 1 GHz

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
<b>Highest Operating Frequency</b>	1.2 GHz
<b>Testing Frequency Range</b>	1 GHz to 6 GHz
<b>Operation Mode</b>	Data Link mode
<b>USB Cable Type</b>	Ningbo Broad <b>*NOTE:</b> The worst-case emissions are reported.
<b>Kind of Test Site</b>	3 m semi anechoic chamber
<b>Temperature</b>	19.2 °C
<b>Relative Humidity</b>	28.0 %
<b>Test Date</b>	February 23, 2015

Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1332.214429	50.5	100.0	V	14.0	-9.3	23.5	74.0
1997.845691	56.8	100.0	V	29.0	-7.8	17.2	74.0
3199.649298	53.1	246.0	V	35.0	-4.2	20.9	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1332.214429	32.8	100.0	V	14.0	-9.3	21.2	54.0
1997.845691	38.5	100.0	V	29.0	-7.8	15.5	54.0
3199.649298	34.5	246.0	V	35.0	-4.2	19.5	54.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



## 5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
-------------	---------------------	-------------------	----------------------	--------------------------	-----------------

### Conducted Emission

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/>	LISN	EMCO	3816/2SH	9706-1070	1 year	04.07.2014
<input checked="" type="checkbox"/>	LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-

### Radiated Emission

#### -For measurement below 1 GHz

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/>	Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17 2014
<input checked="" type="checkbox"/>	Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/>	Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/>	Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
<input type="checkbox"/>	Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/>	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-

#### -For measurement above 1 GHz

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/>	Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/>	Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/>	Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/>	Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.11.2014
<input checked="" type="checkbox"/>	Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.11. 2014
<input checked="" type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	12.13. 2012
<input type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9120D	1151	2 year	07.05.2013
<input type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18. 2014
<input type="checkbox"/>	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	10.30. 2013
<input type="checkbox"/>	Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.23. 2014
<input type="checkbox"/>	Power Amplifier	CERNEX	CBL26405040	19660	1 year	04.04. 2014
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-



## 6. CONCLUSION

The data collected shows that the **EUT Type: SMART WATCH with Bluetooth and WLAN, FCC ID: ZNFW150, Model: LG-W150** complies with §15.107 and §15.109 of the FCC rules.