



TEST REPORT

No. I18Z60007-WMD01

for

LG Electronics MobileComm USA, Inc.

Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model Name: LM-X210BM, LMX210BM, X210BM

FCC ID: ZNFX210BM

with

Hardware Version: Rev.1.0

Software Version: V09c

Issued Date: 2018-03-15



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|----------------------|-----------------|--------------------|-------------------|
| I18Z60007-WMD01 | Rev.0 | 1st edition | 2018-03-15 |

CONTENTS

| | |
|---|-----------|
| 1. TEST LABORATORY | 4 |
| 1.1. TESTING LOCATION | 4 |
| 1.2. TESTING ENVIRONMENT | 4 |
| 1.3. PROJECT DATA | 4 |
| 1.4. SIGNATURE | 4 |
| 2. CLIENT INFORMATION | 5 |
| 2.1. APPLICANT INFORMATION | 5 |
| 2.2. MANUFACTURER INFORMATION | 5 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 6 |
| 3.1. ABOUT EUT | 6 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 6 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST | 6 |
| 3.4. NORMAL ACCESSORY SETTING | 6 |
| 3.5. GENERAL DESCRIPTION | 6 |
| 4. REFERENCE DOCUMENTS | 8 |
| 4.1. REFERENCE DOCUMENTS FOR TESTING | 8 |
| 5. LABORATORY ENVIRONMENT | 9 |
| 6. SUMMARY OF TEST RESULTS | 10 |
| 7. TEST EQUIPMENTS UTILIZED | 11 |
| ANNEX A: MEASUREMENT RESULTS | 12 |
| A.1 OUTPUT POWER | 12 |
| A.2 EMISSION LIMIT | 18 |
| A.3 FREQUENCY STABILITY | 24 |
| A.4 OCCUPIED BANDWIDTH | 27 |
| A.5 EMISSION BANDWIDTH | 40 |
| A.6 BAND EDGE COMPLIANCE | 52 |
| A.7 CONDUCTED SPURIOUS EMISSION | 59 |
| A.8 PEAK-TO-AVERAGE POWER RATIO | 75 |
| ANNEX B: ACCREDITATION CERTIFICATE | 77 |

1. Test Laboratory

1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,
Haidian District, Beijing, P. R. China 100191

1.2. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2017-12-26

Testing End Date: 2018-03-15

1.4. Signature



Shen Yi

(Prepared this test report)



Zhou Yu

(Reviewed this test report)



Zhao Hui Lin

Deputy Director of the laboratory
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: LG Electronics MobileComm USA, Inc.
Address /Post: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
Contact: /
Email: /
Telephone: /
Fax: /

2.2. Manufacturer Information

Company Name: Jiaxing Yongrui Electron Technology Co., Ltd.
Address /Post: NO.777 Yazhong Road, Daqiao Town, Nanhu District, Jiaxing City ,Zhejiang
Contact: /
Email: /
Telephone: /
Fax: /

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|------------------------|---|
| Description | Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN |
| Model Name | LM-X210BM,LMX210BM,X210BM |
| FCC ID | ZNFX210BM |
| Antenna | Embedded |
| Output power | 31.82dBm maximum ERP measured for GSM850 |
| Extreme vol. Limits | 3.6VDC to 4.4VDC (nominal: 3.85VDC) |
| Extremetemp. Tolerance | -10°C to +55°C |

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

The EUT is a variant model of LM-X210FM,LMX210FM,X210FM. All the result is coming from the initial model.

3.2. Internal Identification of EUT used during the test

| EUT ID* | IMEI | HW Version | SW Version | Date of receipt |
|---------|-----------------|------------|------------|-----------------|
| UT08a | 353459090006023 | Rev.1.0 | V09c | 2017-12-25 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description |
|--------------|--|
| AE1 | Battery |
| AE2 | Travel charger |
| AE1 | |
| Model | BL-45F1F |
| Manufacturer | Shenzhen BYD Lithium Battery Company Limited |
| Capacitance | 2500mAh |
| AE2 | |
| Model | EAY64009102 |
| Manufacturer | Sunlin Electronics Co.,Ltd. |

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery was used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN with integrated antenna. Manual and specifications of the EUT were provided to



fulfil the test.



4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|----------------|--|--------------------|
| FCC Part 24 | PERSONAL COMMUNICATIONS SERVICES | 10-1-16 Edition |
| FCC Part 22 | PUBLIC MOBILE SERVICES | 10-1-16 Edition |
| ANSI/TIA-603-E | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards | 2015 |
| ANSI C63.26 | American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services | 2015 |
| KDB 971168 D01 | Measurement Guidance for Certification of Licensed Digital Transmitters | v02r03 |

5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

| | |
|--------------------------|----------------------------|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 80 % |
| Shielding effectiveness | > 110 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 0.5 Ω |

Fully-anechoic chamber 2 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 30 °C |
| Relative humidity | Min. = 35 %, Max. = 60 % |
| Shielding effectiveness | > 110 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 1 Ω |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 4000 MHz |

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 30 °C |
| Relative humidity | Min. = 35 %, Max. = 60 % |
| Shielding effectiveness | > 100 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 0.5 Ω |
| Normalised site attenuation (NSA) | < ±3.5 dB, 3 m distance |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 3000 MHz |

6. SUMMARY OF TEST RESULTS

GSM850

| Items | List | Clause in FCC rules | Verdict |
|-------|-----------------------------|---------------------|---------|
| 1 | Output Power | 22.913(a) | P |
| 2 | Emission Limit | 2.1051/22.917 | P |
| 3 | Frequency Stability | 2.1055 | P |
| 4 | Occupied Bandwidth | 2.1049(h)(i) | P |
| 5 | Emission Bandwidth | 22.917(b) | P |
| 6 | Band Edge Compliance | 22.917(b) | P |
| 7 | Conducted Spurious Emission | 2.1057/22.917 | P |

PCS1900

| Items | List | Clause in FCC rules | Verdict |
|-------|-----------------------------|---------------------|---------|
| 1 | Output Power | 24.232(c) | P |
| 2 | Emission Limit | 2.1051/24.238 | P |
| 3 | Frequency Stability | 2.1055/24.235 | P |
| 4 | Occupied Bandwidth | 2.1049(h)(i) | P |
| 5 | Emission Bandwidth | 24.238(b) | P |
| 6 | Band Edge Compliance | 24.238(b) | P |
| 7 | Conducted Spurious Emission | 2.1057/24.238 | P |

7. Test Equipments Utilized

| NO. | Description | TYPE | series number | MANUFACTURE | CAL DUE DATE | Calibration interval |
|-----|--------------------------------------|----------|---------------|--------------|--------------|----------------------|
| 1 | Test Receiver | ESU26 | 100235 | R&S | 2018-04-01 | 1 year |
| 2 | Test Receiver | ESU26 | 100376 | R&S | 2018-04-27 | 1 year |
| 3 | EMI Antenna | 3117 | 00058889 | ETS-Lindgren | 2020-05-27 | 3 year |
| 4 | Universal Radio Communication Tester | CMU200 | 108646 | R&S | 2018-12-06 | 1 year |
| 5 | Universal Radio Communication Tester | CMW500 | 159082 | R&S | 2018-12-06 | 1 year |
| 6 | Spectrum Analyzer | FSU26 | 200030 | R&S | 2018-06-10 | 1 year |
| 7 | EMI Antenna | VULB9163 | 9163-235 | Schwarzbeck | 2019-05-10 | 3 year |
| 8 | Signal Generator | SMF100A | 101295 | R&S | 2018-12-23 | 1 year |
| 9 | Climate chamber | SH-242 | 93008556 | ESPEC | 2019-12-21 | 2 year |
| 10 | Loop Antenna | HFH2-Z2 | 829324/007 | R&S | 2018-12-14 | 3 year |

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

| | Power step | Nominal Peak output power (dBm) |
|-------|------------|---------------------------------|
| GSM | 5 | 33dBm(2W) |
| GPRS | 3 | 33dBm(2W) |
| EGPRS | 6 | 33dBm(2W) |

Measurement result

GSM(GMSK)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 824.2 | 5 | 33.67 |
| 836.6 | 5 | 33.23 |
| 848.8 | 5 | 33.33 |

GPRS(GMSK,1Slot)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 824.2 | 3 | 33.60 |
| 836.6 | 3 | 33.18 |
| 848.8 | 3 | 33.32 |

EGPRS(8PSK,1Slot)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 824.2 | 6 | 26.12 |
| 836.6 | 6 | 26.84 |
| 848.8 | 6 | 25.59 |

PCS1900

| | Power step | Nominal Peak output power (dBm) |
|-------|------------|---------------------------------|
| GSM | 0 | 30dBm(1W) |
| GPRS | 3 | 30dBm(1W) |
| EGPRS | 5 | 30dBm(1W) |

Measurement result

GSM(GMSK)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 1850.2 | 0 | 29.62 |
| 1880.0 | 0 | 29.83 |
| 1909.8 | 0 | 29.96 |

GPRS(GMSK,1Slot)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 1850.2 | 3 | 29.61 |
| 1880.0 | 3 | 29.95 |
| 1909.8 | 3 | 29.95 |

EGPRS(8PSK,1Slot)

| Frequency(MHz) | Power Step | Output power(dBm) |
|----------------|------------|-------------------|
| 1850.2 | 5 | 25.31 |
| 1880.0 | 5 | 25.20 |
| 1909.8 | 5 | 25.10 |

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2015 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP

Limits

| | Power Step | Burst Peak ERP (dBm) |
|-------|------------|----------------------|
| GSM | 5 | ≤38.45dBm (7W) |
| GPRS | 3 | ≤38.45dBm (7W) |
| EGPRS | 6 | ≤38.45dBm (7W) |

Measurement result

GSM

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | Correction (dB) | ERP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------------|----------|------------|------------|--------------|
| 824.20 | -19.34 | 2.26 | 45.79 | 0.96 | 2.15 | 31.82 | 38.45 | 6.63 | H |
| 836.60 | -19.19 | 2.26 | 45.66 | 0.82 | 2.15 | 31.70 | 38.45 | 6.75 | H |
| 848.80 | -20.11 | 2.28 | 45.54 | 0.79 | 2.15 | 30.65 | 38.45 | 7.80 | H |

GPRS

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | Correction (dB) | ERP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------------|----------|------------|------------|--------------|
| 824.20 | -19.37 | 2.26 | 45.79 | 0.96 | 2.15 | 31.79 | 38.45 | 6.66 | H |
| 836.60 | -19.21 | 2.26 | 45.66 | 0.82 | 2.15 | 31.68 | 38.45 | 6.77 | H |
| 848.80 | -20.10 | 2.28 | 45.54 | 0.79 | 2.15 | 30.66 | 38.45 | 7.79 | H |

EGPRS-8PSK

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | Correction (dB) | ERP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------------|----------|------------|------------|--------------|
| 824.20 | -26.91 | 2.26 | 45.79 | 0.96 | 2.15 | 24.25 | 38.45 | 14.20 | H |
| 836.60 | -26.11 | 2.26 | 45.66 | 0.82 | 2.15 | 24.78 | 38.45 | 13.67 | H |
| 848.80 | -26.42 | 2.28 | 45.54 | 0.79 | 2.15 | 24.34 | 38.45 | 14.11 | H |

Frequency: 824.20MHz

Peak ERP(dBm)=P_{Mea}(-19.34dBm)-P_{cl}(2.26dB)-P_{Ag}(-45.79dB)-G_a(-0.96dB)-2.15dB=31.82 dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP

Limits

| | Power Step | Burst Peak EIRP (dBm) |
|-------|------------|-----------------------|
| GSM | 0 | ≤33dBm (2W) |
| GPRS | 3 | ≤33dBm (2W) |
| EGPRS | 5 | ≤33dBm (2W) |

Measurement result

GSM

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | EIRP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------|------------|------------|--------------|
| 1850.20 | -21.58 | 2.93 | 43.75 | 4.87 | 29.97 | 33.00 | 3.03 | H |
| 1880.00 | -20.18 | 2.85 | 43.75 | 4.82 | 31.24 | 33.00 | 1.76 | V |
| 1909.80 | -19.86 | 2.89 | 43.77 | 4.76 | 31.56 | 33.00 | 1.44 | H |

GPRS

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | EIRP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------|------------|------------|--------------|
| 1850.20 | -21.59 | 2.93 | 43.75 | 4.87 | 29.96 | 33.00 | 3.04 | H |
| 1880.00 | -20.17 | 2.85 | 43.75 | 4.82 | 31.25 | 33.00 | 1.75 | V |
| 1909.80 | -19.85 | 2.89 | 43.77 | 4.76 | 31.57 | 33.00 | 1.43 | H |

EGPRS-8PSK

| Frequency(MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a Antenna Gain(dB) | EIRP(dBm) | Limit(dBm) | Margin(dB) | Polarization |
|----------------|------------------------|----------------------|----------------------|---------------------------------|-----------|------------|------------|--------------|
| 1850.20 | -25.54 | 2.93 | 43.75 | 4.87 | 26.01 | 33.00 | 6.99 | H |
| 1880.00 | -24.64 | 2.85 | 43.75 | 4.82 | 26.78 | 33.00 | 6.22 | V |
| 1909.80 | -24.24 | 2.89 | 43.77 | 4.76 | 27.18 | 33.00 | 5.82 | H |

Frequency: 1909.80MHz

Peak EIRP(dBm)= P_{Mea}(-19.85dBm) - P_{cl}(2.89dB) - P_{Ag}(-43.77dB) - G_a (-4.76dB) = 31.57dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurement procedures in TIA-603E-2015 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

| Frequency | Channel | Frequency Range | Result |
|-------------|---------|-----------------|--------|
| GSM 850MHz | Low | 30MHz-10GHz | Pass |
| | Middle | 30MHz-10GHz | Pass |
| | High | 30MHz-10GHz | Pass |
| GSM 1900MHz | Low | 30MHz-20GHz | Pass |
| | Middle | 30MHz-20GHz | Pass |
| | High | 30MHz-20GHz | Pass |

A.2.5 Sweep Table

| Working Frequency | Subrange (GHz) | RBW | VBW | Sweep time (s) |
|-------------------|----------------|--------|--------|----------------|
| 850MHz | 0.03~1 | 100KHz | 300KHz | 10 |
| | 1-2 | 1 MHz | 3 MHz | 2 |
| | 2~5 | 1 MHz | 3 MHz | 3 |
| | 5~8 | 1 MHz | 3 MHz | 3 |
| | 8~10 | 1 MHz | 3 MHz | 3 |
| 1900MHz | 0.03~1 | 100KHz | 300KHz | 10 |
| | 1-2 | 1 MHz | 3 MHz | 2 |
| | 2~5 | 1 MHz | 3 MHz | 3 |
| | 5~8 | 1 MHz | 3 MHz | 3 |
| | 8~11 | 1 MHz | 3 MHz | 3 |
| | 11~14 | 1 MHz | 3 MHz | 3 |
| | 14~18 | 1 MHz | 3 MHz | 3 |
| | 18~20 | 1 MHz | 3 MHz | 2 |

GSM Mode Channel 128/824.2MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|------------|--------------|
| 1648.01 | -50.40 | 3.56 | 5.23 | 2.15 | -50.88 | -13.00 | 37.90 | H |
| 2472.00 | -45.55 | 4.59 | 6.02 | 2.15 | -46.27 | -13.00 | 33.30 | H |
| 3301.02 | -53.91 | 5.29 | 7.72 | 2.15 | -53.63 | -13.00 | 40.60 | H |
| 4121.02 | -54.14 | 6.04 | 9.02 | 2.15 | -53.31 | -13.00 | 40.30 | V |
| 4944.01 | -53.74 | 6.70 | 9.84 | 2.15 | -52.75 | -13.00 | 39.80 | H |
| 5770.01 | -52.62 | 7.23 | 10.55 | 2.15 | -51.45 | -13.00 | 38.40 | H |

GSM Mode Channel 190/836.6MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|------------|--------------|
| 1674.01 | -54.55 | 3.58 | 5.19 | 2.15 | -55.09 | -13.00 | 42.10 | V |
| 2510.00 | -43.03 | 4.63 | 6.12 | 2.15 | -43.69 | -13.00 | 30.70 | V |
| 3350.02 | -53.68 | 5.32 | 7.84 | 2.15 | -53.31 | -13.00 | 40.30 | V |
| 4185.02 | -53.59 | 6.17 | 9.09 | 2.15 | -52.82 | -13.00 | 39.80 | V |
| 5020.01 | -53.67 | 6.57 | 9.93 | 2.15 | -52.46 | -13.00 | 39.50 | H |
| 5861.01 | -52.83 | 7.27 | 10.53 | 2.15 | -51.72 | -13.00 | 38.70 | V |

GSM Mode Channel 251/848.8MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|------------|--------------|
| 1698.01 | -50.79 | 3.60 | 5.14 | 2.15 | -51.40 | -13.00 | 38.40 | H |
| 2546.00 | -46.43 | 4.66 | 6.18 | 2.15 | -47.06 | -13.00 | 34.10 | H |
| 3393.02 | -54.15 | 5.36 | 7.94 | 2.15 | -53.72 | -13.00 | 40.70 | V |
| 4247.02 | -53.90 | 6.24 | 9.15 | 2.15 | -53.14 | -13.00 | 40.10 | V |
| 5089.01 | -52.67 | 6.74 | 10.02 | 2.15 | -51.54 | -13.00 | 38.50 | V |
| 5946.01 | -52.40 | 7.47 | 10.51 | 2.15 | -51.51 | -13.00 | 38.50 | V |

GSM Mode Channel 512/1850.2MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|----------------|-------------|------------|--------------|
| 3702.02 | -54.38 | 6.42 | 8.48 | -52.32 | -13.00 | 39.32 | V |
| 5545.02 | -54.38 | 7.18 | 10.59 | -50.97 | -13.00 | 37.97 | V |
| 7406.01 | -54.49 | 8.13 | 12.09 | -50.53 | -13.00 | 37.53 | H |
| 9258.01 | -53.79 | 9.06 | 13.25 | -49.60 | -13.00 | 36.60 | H |
| 11105.01 | -51.40 | 9.81 | 13.18 | -48.03 | -13.00 | 35.03 | V |
| 12950.01 | -49.29 | 10.49 | 13.47 | -46.31 | -13.00 | 33.31 | H |

GSM Mode Channel 661/1880.0MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|----------------|-------------|------------|--------------|
| 3757.02 | -55.03 | 6.27 | 8.56 | -52.74 | -13.00 | 39.74 | V |
| 5642.02 | -52.12 | 7.27 | 10.57 | -48.82 | -13.00 | 35.82 | V |
| 7525.01 | -53.53 | 8.29 | 12.22 | -49.60 | -13.00 | 36.60 | V |
| 9401.01 | -54.57 | 9.04 | 13.34 | -50.27 | -13.00 | 37.27 | V |
| 11282.01 | -51.31 | 9.89 | 13.14 | -48.06 | -13.00 | 35.06 | V |
| 13151.01 | -48.14 | 10.71 | 13.71 | -45.14 | -13.00 | 32.14 | V |

GSM Mode Channel 810/1909.8MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin(dB) | Polarization |
|----------------|------------------------|-----------|--------------|----------------|-------------|------------|--------------|
| 3819.02 | -53.63 | 6.08 | 8.65 | -51.06 | -13.00 | 38.06 | H |
| 5735.02 | -51.97 | 7.29 | 10.55 | -48.71 | -13.00 | 35.71 | H |
| 7639.01 | -54.56 | 8.15 | 12.31 | -50.40 | -13.00 | 37.40 | H |
| 9544.01 | -54.19 | 9.38 | 13.36 | -50.21 | -13.00 | 37.21 | H |
| 11461.01 | -51.40 | 9.91 | 13.11 | -48.20 | -13.00 | 35.20 | H |
| 13377.01 | -48.22 | 10.57 | 14.03 | -44.76 | -13.00 | 31.76 | V |

A.3 FREQUENCY STABILITY

A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -10°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from -10°C to 50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.3.2 Measurement Limit

A.3.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.4VDC, with a nominal voltage of 3.85VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.3.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section

2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.3.3 Measurement results

GSM 850

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.6 | 11 | 0.013 |
| 3.85 | 9 | 0.011 |
| 4.4 | 8 | 0.010 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -10 | 10 | 0.012 |
| 0 | 21 | 0.025 |
| 10 | 13 | 0.015 |
| 20 | 10 | 0.012 |
| 30 | 9 | 0.010 |
| 40 | 15 | 0.018 |
| 50 | 12 | 0.015 |

EGPRS 850 - 8PSK

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.6 | -58 | 0.069 |
| 3.85 | -62 | 0.074 |
| 4.4 | -60 | 0.072 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -10 | -55 | 0.065 |
| 0 | -64 | 0.076 |
| 10 | -64 | 0.076 |
| 20 | -56 | 0.067 |
| 30 | -67 | 0.080 |
| 40 | -56 | 0.067 |
| 50 | -56 | 0.067 |

PCS 1900

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.6 | 12 | 0.006 |
| 3.85 | 12 | 0.006 |
| 4.4 | 12 | 0.007 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -10 | -6 | 0.003 |
| 0 | -9 | 0.005 |
| 10 | -25 | 0.013 |
| 20 | -13 | 0.007 |
| 30 | -13 | 0.007 |
| 40 | -11 | 0.006 |
| 50 | -7 | 0.004 |

EGPRS 1900 - 8PSK

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.6 | -49 | 0.026 |
| 3.85 | -60 | 0.032 |
| 4.4 | -52 | 0.028 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -10 | -57 | 0.030 |
| 0 | -55 | 0.029 |
| 10 | -56 | 0.030 |
| 20 | -57 | 0.030 |
| 30 | -56 | 0.030 |
| 40 | -60 | 0.032 |
| 50 | -64 | 0.034 |

A.4 OCCUPIED BANDWIDTH

Reference

FCC: CFR Part 2.1049(h)(i)

A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

GSM 850(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 824.2 | 246.795 |
| 836.6 | 244.391 |
| 848.8 | 245.994 |


GSM 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:01:54

Channel 190-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 10:02:26

Channel 251-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:02:59

GPRS 850(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 824.2 | 246.795 |
| 836.6 | 245.994 |
| 848.8 | 243.590 |


GPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:41:12

Channel 190-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 10:41:45

Channel 251-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:42:17

EGPRS 850-8PSK(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 824.2 | 246.795 |
| 836.6 | 241.987 |
| 848.8 | 241.987 |


EGPRS 850-8PSK

Channel 128-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 11:07:21

Channel 190-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 11:07:53

Channel 251-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 11:08:25

PCS 1900(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 1850.2 | 245.192 |
| 1880.0 | 243.590 |
| 1909.8 | 245.994 |


PCS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:20:35

Channel 661-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 10:21:07

Channel 810-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:21:39

GPRS 1900(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 1850.2 | 244.391 |
| 1880.0 | 244.391 |
| 1909.8 | 244.391 |


GPRS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:53:42

Channel 661-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 10:54:15

Channel 810-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 10:54:47

EGPRS 1900-8PSK(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(kHz) |
|----------------|-----------------------------------|
| 1850.2 | 243.590 |
| 1880.0 | 245.192 |
| 1909.8 | 245.192 |


EGPRS 1900-8PSK

Channel 512-Occupied Bandwidth (99% BW)




Date: 28.DEC.2017 11:18:23

Channel 661-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 11:18:56

Channel 810-Occupied Bandwidth (99% BW)



Date: 28.DEC.2017 11:19:28

A.5 EMISSION BANDWIDTH

Reference

FCC: CFR Part 22.917(b), 24.238(a)

A.5.1 Emission Bandwidth Results


The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

GSM 850

| Frequency(MHz) | Emission Bandwidth (kHz) |
|----------------|---------------------------|
| 824.2 | 314.10 |
| 836.6 | 312.50 |
| 848.8 | 312.50 |


GSM 850

Channel 128-Emission Bandwidth




Date: 28.DEC.2017 10:04:07

Channel 190-Emission Bandwidth



Date: 28.DEC.2017 10:05:14

Channel 251-Emission Bandwidth




Date: 28.DEC.2017 10:06:22

GPRS 850

| Frequency(MHz) | Emission Bandwidth (kHz) |
|----------------|---------------------------|
| 824.2 | 314.10 |
| 836.6 | 318.91 |
| 848.8 | 314.10 |


GPRS 850

Channel 128-Emission Bandwidth




Date: 28.DEC.2017 10:43:26

Channel 190-Emission Bandwidth



Date: 28.DEC.2017 10:44:33

Channel 251-Emission Bandwidth




Date: 28.DEC.2017 10:45:40

EGPRS 850-8PSK

| Frequency(MHz) | Emission Bandwidth (kHz) |
|----------------|---------------------------|
| 824.2 | 312.50 |
| 836.6 | 307.69 |
| 848.8 | 308.49 |


EGPRS 850-8PSK

Channel 128-Emission Bandwidth




Date: 28.DEC.2017 11:09:34

Channel 190-Emission Bandwidth



Date: 28.DEC.2017 11:10:41

Channel 251-Emission Bandwidth




Date: 28.DEC.2017 11:11:49

PCS 1900

| Frequency(MHz) | Emission Bandwidth (kHz) |
|----------------|---------------------------|
| 1850.2 | 314.90 |
| 1880.0 | 314.90 |
| 1909.8 | 318.11 |


PCS 1900

Channel 512-Emission Bandwidth




Date: 28.DEC.2017 10:22:48

Channel 661-Emission Bandwidth



Date: 28.DEC.2017 10:23:55

Channel 810-Emission Bandwidth




Date: 28.DEC.2017 10:25:03

GPRS 1900

| Frequency(MHz) | Emission Bandwidth (kHz) |
|----------------|---------------------------|
| 1850.2 | 313.30 |
| 1880.0 | 317.31 |
| 1909.8 | 316.51 |


GPRS 1900

Channel 512-Emission Bandwidth




Date: 28.DEC.2017 10:55:55

Channel 661-Emission Bandwidth



Date: 28.DEC.2017 10:57:03

Channel 810-Emission Bandwidth




Date: 28.DEC.2017 10:58:10

EGPRS 1900-8PSK

| Frequency(MHz) | Emission Bandwidth(kHz) |
|----------------|--------------------------|
| 1850.2 | 316.51 |
| 1880.0 | 310.90 |
| 1909.8 | 307.69 |


EGPRS 1900-8PSK

Channel 512-Emission Bandwidth




Date: 28.DEC.2017 11:20:36

Channel 661-Emission Bandwidth



Date: 28.DEC.2017 11:21:43

Channel 810-Emission Bandwidth



Date: 28.DEC.2017 11:22:50

A.6 BAND EDGE COMPLIANCE

Reference

FCC: CFR Part 22.917(b), 24.238(a)


Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.


According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 28.DEC.2017 10:06:31



Ref 25 dBm Att 20 dB RBW 5 kHz VBW 20 kHz SWT 300 ms Marker 1 [T1] -13.99 dBm 849.020833333 MHz


dBm V11W

22.4

Center 849 MHz 100 kHz/ Span 1 MHz


©Copyright. All rights reserved by CTTL.

GPRS 850 LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 28.DEC.2017 10:45:49

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 16.JAN.2018 09:23:49

EGPRS 850-8PSK LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 28.DEC.2017 11:11:58

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 28.DEC.2017 11:14:02




LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 28.DEC.2017 10:27:16

GPRS 1900 LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 28.DEC.2017 10:58:19

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810




Date: 28.DEC.2017 11:00:23

EGPRS 1900-8PSK LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 28.DEC.2017 11:22:59

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810



Date: 28.DEC.2017 11:25:02

A.7 CONDUCTED SPURIOUS EMISSION

Reference

FCC: CFR Part 2.1057, 22.917, 24.238.

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

GSM850 Transmitter

| Channel | Frequency (MHz) |
|---------|-----------------|
| 128 | 824.2 |
| 190 | 836.6 |
| 251 | 848.8 |

PCS1900 Transmitter

| Channel | Frequency (MHz) |
|---------|-----------------|
| 512 | 1850.2 |
| 661 | 1880.0 |
| 810 | 1909.8 |

A. 7.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A.7.3 Measurement result

GSM850

Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 28.DEC.2017 10:11:01


Channel 128: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:11:30

Channel 128: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:11:58

Channel 128: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:12:26

Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 28.DEC.2017 10:12:55


Channel 190: 1GHz –2.5GHz

Spurious emission limit –13dBm




Date: 28.DEC.2017 10:13:23

Channel 190: 2.5GHz –7.5GHz
Spurious emission limit –13dBm



Date: 28.DEC.2017 10:13:51

Channel 190: 7.5GHz –10GHz
Spurious emission limit –13dBm




Date: 28.DEC.2017 10:14:19

Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 28.DEC.2017 10:14:48


Channel 251: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:15:16

Channel 251: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:15:44

Channel 251: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:16:12

PCS1900

Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:29:42

Channel 512: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 28.DEC.2017 10:30:10

Channel 512: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:30:38


Channel 512: 7.5GHz –10GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:31:06

Channel 512: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:31:35


Channel 512: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:32:03


Channel 661: 30MHz – 1GHz
Spurious emission limit –13dBm



Date: 28.DEC.2017 10:32:31


Channel 661: 1GHz –2.5GHz
Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.




Date: 28.DEC.2017 10:33:00

Channel 661: 2.5GHz –7.5GHz
Spurious emission limit –13dBm



Date: 28.DEC.2017 10:33:28


Channel 661: 7.5GHz –10GHz
Spurious emission limit –13dBm



Date: 28.DEC.2017 10:33:56

Channel 661: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:34:24

Channel 661: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:34:52

Channel 810: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 28.DEC.2017 10:35:21

Channel 810: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 28.DEC.2017 10:35:49

Channel 810: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:36:17


Channel 810: 7.5GHz – 10GHz
Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:36:46

Channel 810: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:37:14

Channel 810: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 28.DEC.2017 10:37:42

A.8 PEAK-TO-AVERAGE POWER RATIO

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 5.7.1:

- Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Set the measurement interval to 1 ms
- Record the maximum PAPR level associated with a probability of 0.1%

A.8.1 Measurement limit


not exceed 13 dB

A.8.2 Measurement results

| | CH | Frequency(MHz) | PAPR(dB) |
|---------|-----|----------------|----------|
| GSM1900 | 661 | 1880.0 | 7.724 |

GSM 1900

Channel 661-PAPR




Date: 28.DEC.2017 10:29:07

| GPRS1900 | CH | Frequency(MHz) | PAPR(dB) |
|----------|-----|----------------|----------|
| | 661 | 1880.0 | 7.724 |

GPRS 1900

Channel 661-PAPR




Date: 28.DEC.2017 11:02:14

| EGPRS1900 | CH | Frequency(MHz) | PAPR(dB) |
|-----------|-----|----------------|----------|
| | 661 | 1880.0 | 10..897 |



EGPRS 1900

Channel 661-PAPR



Date: 28.DEC.2017 11:26:54

ANNEX B: Accreditation Certificate

| |
|---|
| <p>United States Department of Commerce National Institute of Standards and Technology</p> <p>NVLAP[®]</p> <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <p>2017-08-22 through 2018-09-30 <i>Effective Dates</i></p> <p></p> <p> <i>For the National Voluntary Laboratory Accreditation Program</i></p> |
|---|

END OF REPORT