



FCC RF Test Report

APPLICANT : LG Electronics Mobile Comm USA
EQUIPMENT : Smart phone
BRAND NAME : LG
MODEL NAME : LG-X210mb
FCC ID : ZNFX210MB
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Nov. 20, 2015 and testing was completed on Dec. 22, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5

1.1 Applicant 5

1.2 Manufacturer 5

1.3 Product Feature of Equipment Under Test 5

1.4 Product Specification subjective to this standard 6

1.5 Accessories and Support Equipment 6

1.6 Modification of EUT 7

1.7 Testing Location 7

1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

2.1 Carrier Frequency Channel 8

2.2 Pre-Scanned RF Power 9

2.3 Test Mode 10

2.4 Connection Diagram of Test System 11

2.5 Support Unit used in test configuration and system 13

2.6 EUT Operation Test Setup 13

2.7 Measurement Results Explanation Example 13

3 TEST RESULT 14

3.1 6dB Bandwidth Measurement 14

3.2 Output Power Measurement 16

3.3 Power Spectral Density Measurement 18

3.4 Conducted Band Edges and Spurious Emission Measurement 20

3.5 Radiated Band Edges and Spurious Emission Measurement 33

3.6 AC Conducted Emission Measurement 41

3.7 Antenna Requirements 47

4 LIST OF MEASURING EQUIPMENT 48

5 UNCERTAINTY OF EVALUATION 49

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED TEST RESULTS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 2.21 dB at 2387.310 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.75 dB at 3.780 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

LG Electronics Mobile Comm USA
1000 Sylvan Avenue Englewood Cliffs, NJ 07632

1.2 Manufacturer

Arima Communications Corp.
6F, No.866, Jhongjheng Rd., Jhonghe Dist., New Taipei City 23586, Taiwan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart phone
Brand Name	LG
Model Name	LG-X210mb
FCC ID	ZNFX210MB
EUT supports Radios application	GSM/GPRS/EGPRS(Downlink Only)/WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/WLAN 2.4GHz 802.11b/g/n HT20/HT40/Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 356240070005949/356240070005956 Radiation: 356240070005303/356240070005311 Conduction: 356240070005204/356240070005212
HW Version	5541MB-002
SW Version	LGX210g-00-v10a-334-20-dec-09-2015+0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 20.78 dBm (0.1197 W) 802.11g : 23.21 dBm (0.2094 W) 802.11n HT20 : 23.01 dBm (0.2000 W) 802.11n HT40 : 23.04 dBm (0.2014 W)
Antenna Type/Gain	802.11b/g/n : IFA Antenna with gain 0.11 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Accessories and Support Equipment

Specification of Accessory				
AC Adapter	Brand Name	LG	P/N	SSAD0038201(STA-U17WD)
	Power Rating	I/P: 100-240Vac, 0.2A, O/P: 5Vdc, 0.85A		
Battery	Brand Name	LG	P/N	EAC63079701(BL-46ZH)
	Power Rating	3.8Vdc, 2125mAh		
USB Cable	Brand Name	NINGBO	P/N	EAD62377902(LG0108)
	Signal Line Type	0.98m shielded without core		
Earphone	Brand Name	LG	P/N	EAB64228801(BHS300-K0)
	Signal Line Type	1.10meter, non-shielded cable without core		



1.6 Modification of EUT

No modifications are made to the EUT during all test items.

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH03-KS	CO01-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X/Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate	Channel	2Mbps	5.5Mbps	11Mbps
		1Mbps				
CH 01	2412 MHz	20.72	CH 11	20.70	20.60	20.76
CH 06	2437 MHz	20.18				
CH 11	2462 MHz	20.78				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	21.98	CH 11	21.92	21.87	21.69	21.96	21.63	22.88	23.12
CH 06	2437 MHz	21.81								22.74
CH 11	2462 MHz	22.15								23.21

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	21.91	CH 01	22.14	21.76	21.92	21.82	22.96	22.89	23.01
CH 06	2437 MHz	21.85								22.39
CH 11	2462 MHz	21.46								22.52

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	22.71	CH 03	21.92	21.87	22.01	21.95	22.98	22.84	23.04
CH 06	2437 MHz	22.25								22.63
CH 09	2452 MHz	22.37								22.51



2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.


<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	54 Mbps
802.11n HT20	MCS7
802.11n HT40	MCS7

Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performance with Adapter, Earphone, and USB Cable.	

2.4 Connection Diagram of Test System


<WLAN 802.11b/g/n HT20 Tx Mode>



<WLAN 802.11n HT40 Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
3.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.5 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A of this test report.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song







Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 4 DEC. 2015 10:20:06

High Channel Plot




Date: 4 DEC. 2015 10:20:41

Spurious Emission 30MHz~3GHz



Date: 4 DEC. 2015 10:20:54

Spurious Emission 2GHz~25GHz




Date: 4 DEC. 2015 10:21:03



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 18 DEC.2015 22:33:12

Low Channel Plot




Date: 18 DEC.2015 22:33:22

Spurious Emission 30MHz~3GHz



Date: 21 DEC.2015 14:11:23

Spurious Emission 2GHz~25GHz




Date: 18 DEC.2015 22:33:43



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 18 DEC.2015 22:36:28

Spurious Emission 30MHz~3GHz



Date: 21 DEC.2015 14:18:39

Spurious Emission 2GHz~25GHz




Date: 18 DEC.2015 22:36:48



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 18 DEC.2015 22:39:36

High Channel Plot




Date: 18 DEC.2015 22:39:57

Spurious Emission 30MHz~3GHz



Date: 21 DEC.2015 14:20:44

Spurious Emission 2GHz~25GHz




Date: 18 DEC.2015 22:40:46



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 18 DEC.2015 22:44:59

Low Channel Plot




Date: 18 DEC.2015 22:45:12

Spurious Emission 30MHz~3GHz



Date: 21 DEC.2015 14:25:01

Spurious Emission 2GHz~25GHz




Date: 18 DEC.2015 22:46:19




Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 18 DEC.2015 22:54:06

High Channel Plot




Date: 18 DEC.2015 22:54:54

Spurious Emission 30MHz~3GHz



Date: 21 DEC.2015 14:28:53

Spurious Emission 2GHz~25GHz




Date: 18 DEC.2015 22:55:16



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	03	Test Engineer :	Issac Song


WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level




Date: 4. DEC. 2015 11:15:35

Low Channel Plot




Date: 4. DEC. 2015 11:16:02

Spurious Emission 30MHz~3GHz



Date: 4. DEC. 2015 11:17:04

Spurious Emission 2GHz~25GHz




Date: 4. DEC. 2015 11:17:13




Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	09	Test Engineer :	Issac Song

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$; $\text{VBW} \geq \text{RBW}$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1 \text{ GHz}$ for peak measurement.


For average measurement:

 - $\text{VBW} = 10 \text{ Hz}$, when duty cycle is no less than 98 percent.
 - $\text{VBW} \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	99.63	-	-	10Hz
802.11g	83.02	0.18	5.56	10kHz
2.4GHz 802.11n HT20	82.00	0.15	6.67	10kHz
2.4GHz 802.11n HT40	54.07	0.10	10.00	10kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges


Please refer to Appendix B.



3.5.7 Duty Cycle Plot

802.11b


Data Rate: 1Mbps





802.11g


Data Rate: 54Mbps





802.11n HT20


Data Rate: MCS7





802.11n HT40

Data Rate: MCS7



3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-20151024 LINE
 mode : Mode 1
 : 356240070005204/356240070005212

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.43	46.70	-10.59	57.29	36.30	0.23	10.17	QP
2	0.43	36.70	-10.59	47.29	26.30	0.23	10.17	Average
3	0.68	43.09	-12.91	56.00	32.70	0.24	10.15	QP
4	0.68	31.89	-14.11	46.00	21.50	0.24	10.15	Average
5	0.97	39.89	-16.11	56.00	29.50	0.25	10.14	QP
6	0.97	28.99	-17.01	46.00	18.60	0.25	10.14	Average
7	1.26	44.26	-11.74	56.00	33.89	0.23	10.14	QP
8	1.26	34.56	-11.44	46.00	24.19	0.23	10.14	Average
9	1.52	44.25	-11.75	56.00	33.90	0.21	10.14	QP
10	1.52	35.25	-10.75	46.00	24.90	0.21	10.14	Average
11	1.76	44.23	-11.77	56.00	33.90	0.19	10.14	QP
12	1.76	35.53	-10.47	46.00	25.20	0.19	10.14	Average
13	2.11	44.92	-11.08	56.00	34.60	0.18	10.14	QP
14	2.11	35.92	-10.08	46.00	25.60	0.18	10.14	Average
15	2.55	43.53	-12.47	56.00	33.20	0.18	10.15	QP
16	2.55	35.83	-10.17	46.00	25.50	0.18	10.15	Average
17	2.78	42.83	-13.17	56.00	32.50	0.18	10.15	QP



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-20151024 LINE

mode : Mode 1
 : 356240070005204/356240070005212

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	2.78	35.43	-10.57	46.00	25.10	0.18	10.15	Average
19	3.35	43.64	-12.36	56.00	33.29	0.19	10.16	QP
20	3.35	35.84	-10.16	46.00	25.49	0.19	10.16	Average
21	3.78	44.25	-11.75	56.00	33.90	0.19	10.16	QP
22 *	3.78	36.25	-9.75	46.00	25.90	0.19	10.16	Average
23	4.20	42.56	-13.44	56.00	32.20	0.19	10.17	QP
24	4.20	34.76	-11.24	46.00	24.40	0.19	10.17	Average
25	4.72	40.97	-15.03	56.00	30.60	0.19	10.18	QP
26	4.72	32.97	-13.03	46.00	22.60	0.19	10.18	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-N-20151024 NEUTRAL
 mode : Mode 1
 : 356240070005204/356240070005212

Freq	Level	Over Limit	Limit	Read	LISN	Cable	Remark
MHz	dBuV		dB	dBuV	dB	dB	
1 *	0.43	46.79	-10.41	57.20	36.30	0.32	10.17 QP
2	0.43	36.19	-11.01	47.20	25.70	0.32	10.17 Average
3	0.47	43.28	-13.26	56.54	32.80	0.32	10.16 QP
4	0.47	33.08	-13.46	46.54	22.60	0.32	10.16 Average
5	0.55	39.39	-16.61	56.00	28.90	0.33	10.16 QP
6	0.55	29.09	-16.91	46.00	18.60	0.33	10.16 Average
7	0.70	40.69	-15.31	56.00	30.20	0.34	10.15 QP
8	0.70	30.79	-15.21	46.00	20.30	0.34	10.15 Average
9	0.78	42.00	-14.00	56.00	31.50	0.35	10.15 QP
10	0.78	31.80	-14.20	46.00	21.30	0.35	10.15 Average
11	1.09	42.21	-13.79	56.00	31.70	0.37	10.14 QP
12	1.09	34.11	-11.89	46.00	23.60	0.37	10.14 Average
13	1.40	41.31	-14.69	56.00	30.80	0.37	10.14 QP
14	1.40	33.71	-12.29	46.00	23.20	0.37	10.14 Average
15	1.77	42.02	-13.98	56.00	31.50	0.38	10.14 QP
16	1.77	33.82	-12.18	46.00	23.30	0.38	10.14 Average
17	2.00	43.62	-12.38	56.00	33.10	0.38	10.14 QP



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-20151024 NEUTRAL

mode : Mode 1
 : 356240070005204/356240070005212

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	2.00	34.72	-11.28	46.00	24.20	0.38	10.14	Average
19	2.36	43.62	-12.38	56.00	33.09	0.38	10.15	QP
20	2.36	34.92	-11.08	46.00	24.39	0.38	10.15	Average
21	2.51	43.02	-12.98	56.00	32.49	0.38	10.15	QP
22	2.51	34.42	-11.58	46.00	23.89	0.38	10.15	Average
23	2.69	42.32	-13.68	56.00	31.80	0.37	10.15	QP
24	2.69	34.12	-11.88	46.00	23.60	0.37	10.15	Average
25	3.33	41.73	-14.27	56.00	31.20	0.37	10.16	QP
26	3.33	33.73	-12.27	46.00	23.20	0.37	10.16	Average
27	3.94	41.73	-14.27	56.00	31.19	0.37	10.17	QP
28	3.94	33.73	-12.27	46.00	23.19	0.37	10.17	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2015	Dec. 04, 2015~ Dec. 22, 2015	May 03, 2016	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Dec. 04, 2015~ Dec. 22, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Dec. 04, 2015~ Dec. 22, 2015	Jan. 22, 2016	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Sep. 10, 2015	Dec. 22, 2015	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz-44GHz	Jun. 05, 2015	Dec. 22, 2015	Jun. 04, 2016	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2015	Dec. 22, 2015	Nov. 09, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz-2GHz	Jun. 25, 2015	Dec. 22, 2015	Jun. 24, 2016	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-135 6	1GHz~18GHz	Jun. 25, 2015	Dec. 22, 2015	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz ~40GHz	Mar. 03, 2015	Dec. 22, 2015	Mar. 02, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz-3000M Hz	Aug. 10, 2015	Dec. 22, 2015	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Oct. 24, 2015	Dec. 22, 2015	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Dec. 22, 2015	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 22, 2015	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 22, 2015	NCR	Radiation (03CH03-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Sep. 10, 2015	Dec. 02, 2015	Sep. 09, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Dec. 02, 2015	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Dec. 02, 2015	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Dec. 02, 2015	Oct. 23, 2016	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Issac Song	Temperature:	24~25	°C
Test Date:	2015/12/04~2015/12/22	Relative Humidity:	49~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.79	10.03	0.50	Pass
11b	1Mbps	1	6	2437	12.74	10.01	0.50	Pass
11b	1Mbps	1	11	2462	12.89	10.03	0.50	Pass
11g	54Mbps	1	1	2412	17.63	16.50	0.50	Pass
11g	54Mbps	1	6	2437	17.73	16.52	0.50	Pass
11g	54Mbps	1	11	2462	17.73	16.50	0.50	Pass
HT20	MCS7	1	1	2412	18.48	17.74	0.50	Pass
HT20	MCS7	1	6	2437	18.48	17.76	0.50	Pass
HT20	MCS7	1	11	2462	18.48	17.74	0.50	Pass
HT40	MCS7	1	3	2422	36.16	35.68	0.50	Pass
HT40	MCS7	1	6	2437	36.16	35.13	0.50	Pass
HT40	MCS7	1	9	2452	36.26	35.45	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	20.72	30.00	0.11	20.83	36.00	Pass
11b	1Mbps	1	6	2437	20.18	30.00	0.11	20.29	36.00	Pass
11b	1Mbps	1	11	2462	20.78	30.00	0.11	20.89	36.00	Pass
11g	54Mbps	1	1	2412	23.12	30.00	0.11	23.23	36.00	Pass
11g	54Mbps	1	6	2437	22.74	30.00	0.11	22.85	36.00	Pass
11g	54Mbps	1	11	2462	23.21	30.00	0.11	23.32	36.00	Pass
HT20	MCS7	1	1	2412	23.01	30.00	0.11	23.12	36.00	Pass
HT20	MCS7	1	6	2437	22.39	30.00	0.11	22.50	36.00	Pass
HT20	MCS7	1	11	2462	22.52	30.00	0.11	22.63	36.00	Pass
HT40	MCS7	1	3	2422	23.04	30.00	0.11	23.15	36.00	Pass
HT40	MCS7	1	6	2437	22.63	30.00	0.11	22.74	36.00	Pass
HT40	MCS7	1	9	2452	22.51	30.00	0.11	22.62	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.02	17.91
11b	1Mbps	1	6	2437	0.02	17.33
11b	1Mbps	1	11	2462	0.02	18.00
11g	54Mbps	1	1	2412	0.12	12.96
11g	54Mbps	1	6	2437	0.12	12.43
11g	54Mbps	1	11	2462	0.12	13.12
HT20	MCS7	1	1	2412	0.12	12.74
HT20	MCS7	1	6	2437	0.12	12.44
HT20	MCS7	1	11	2462	0.12	12.17
HT40	MCS7	1	3	2422	0.23	14.08
HT40	MCS7	1	6	2437	0.23	13.69
HT40	MCS7	1	9	2452	0.23	13.53

TEST RESULTS DATA
Peak Power Density





2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.10	0.11	8.00	Pass
11b	1Mbps	1	6	2437	-5.29	0.11	8.00	Pass
11b	1Mbps	1	11	2462	-5.32	0.11	8.00	Pass
11g	54Mbps	1	1	2412	-12.39	0.11	8.00	Pass
11g	54Mbps	1	6	2437	-12.60	0.11	8.00	Pass
11g	54Mbps	1	11	2462	-11.70	0.11	8.00	Pass
HT20	MCS7	1	1	2412	-13.09	0.11	8.00	Pass
HT20	MCS7	1	6	2437	-12.91	0.11	8.00	Pass
HT20	MCS7	1	11	2462	-13.02	0.11	8.00	Pass
HT40	MCS7	1	3	2422	-14.24	0.11	8.00	Pass
HT40	MCS7	1	6	2437	-14.88	0.11	8.00	Pass
HT40	MCS7	1	9	2452	-14.61	0.11	8.00	Pass







Appendix B. Radiated Test Results

WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Band Edge @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Fundamental Emission @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Fundamental Emission @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Band Edge @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Fundamental Emission @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Fundamental Emission @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Fundamental Emission @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak	<p>Graph showing Peak Level (dBuV/m) vs Frequency (MHz) for Horizontal polarization. The signal level is approximately 105.3 dBuV/m at 2400 MHz and drops to about 58.5 dBuV/m at 2483.5 MHz. A red horizontal line indicates the FCC PART 15C -6dB limit at approximately 70.2 dBuV/m.</p>	<p>Graph showing Peak Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The signal level is approximately 105.3 dBuV/m at 2400 MHz and drops to about 58.5 dBuV/m at 2483.5 MHz. A red horizontal line indicates the FCC PART 15C -6dB limit at approximately 70.2 dBuV/m.</p>
Average	<p>Graph showing Average Level (dBuV/m) vs Frequency (MHz) for Horizontal polarization. The signal level is approximately 93.6 dBuV/m at 2400 MHz and drops to about 46.8 dBuV/m at 2483.5 MHz. A red horizontal line indicates the FCC PART 15C (AVG) -6dB limit at approximately 46.8 dBuV/m.</p>	<p>Graph showing Average Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The signal level is approximately 93.6 dBuV/m at 2400 MHz and drops to about 46.8 dBuV/m at 2483.5 MHz. A red horizontal line indicates the FCC PART 15C (AVG) -6dB limit at approximately 46.8 dBuV/m.</p>







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Fundamental Emission @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak	 <p>Peak Horizontal Spectrum Plot: The graph shows Level (dBuV/m) on the y-axis (0 to 117) and Frequency (MHz) on the x-axis (2400 to 2483.5). A blue signal trace shows a peak between 2450 and 2470 MHz. A red horizontal line indicates the FCC PART 15C limit at 64dB. A vertical blue line marks the center frequency at 2462 MHz.</p>	 <p>Peak Vertical Spectrum Plot: The graph shows Level (dBuV/m) on the y-axis (0 to 117) and Frequency (MHz) on the x-axis (2400 to 2483.5). A blue signal trace shows a peak between 2450 and 2470 MHz. A red horizontal line indicates the FCC PART 15C limit at 64dB. A vertical blue line marks the center frequency at 2462 MHz.</p>
Average	 <p>Average Horizontal Spectrum Plot: The graph shows Level (dBuV/m) on the y-axis (0 to 117) and Frequency (MHz) on the x-axis (2400 to 2483.5). A blue signal trace shows a peak between 2450 and 2470 MHz. A red horizontal line indicates the FCC PART 15C (AVG) limit at 58.5dB. A vertical blue line marks the center frequency at 2462 MHz.</p>	 <p>Average Vertical Spectrum Plot: The graph shows Level (dBuV/m) on the y-axis (0 to 117) and Frequency (MHz) on the x-axis (2400 to 2483.5). A blue signal trace shows a peak between 2450 and 2470 MHz. A red horizontal line indicates the FCC PART 15C (AVG) limit at 58.5dB. A vertical blue line marks the center frequency at 2462 MHz.</p>



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Fundamental Emission @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Fundamental Emission @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak	<p>Peak Horizontal plot showing Level (dBuV/m) vs Frequency (MHz). The signal level is approximately 93.6 dBuV/m between 2430 MHz and 2450 MHz, with a peak at 2440 MHz. The FCC PART 15C limit is 81.9 dBuV/m.</p>	<p>Peak Vertical plot showing Level (dBuV/m) vs Frequency (MHz). The signal level is approximately 93.6 dBuV/m between 2430 MHz and 2450 MHz, with a peak at 2440 MHz. The FCC PART 15C limit is 81.9 dBuV/m.</p>
Average	<p>Average Horizontal plot showing Level (dBuV/m) vs Frequency (MHz). The signal level is approximately 81.9 dBuV/m between 2430 MHz and 2450 MHz, with a peak at 2440 MHz. The FCC PART 15C (AVG) limit is 46.8 dBuV/m.</p>	<p>Average Vertical plot showing Level (dBuV/m) vs Frequency (MHz). The signal level is approximately 81.9 dBuV/m between 2430 MHz and 2450 MHz, with a peak at 2440 MHz. The FCC PART 15C (AVG) limit is 46.8 dBuV/m.</p>







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Fundamental Emission @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Band Edge @ 3m)	
ANT	CH03 2422MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Band Edge @ 3m)	
ANT	CH03 2422MHz	
1	Horizontal	Vertical
Peak	 <p>Level (dBuV/m) vs Frequency (MHz) plot for Peak Horizontal. The y-axis ranges from 11.7 to 117 dBuV/m. The x-axis ranges from 2460 to 2500 MHz. A blue line shows the signal level, which is mostly below 58.5 dBuV/m. A red horizontal line at 70.2 dBuV/m is labeled 'FCC PART 15C -6dB'. A vertical blue line is at 2422 MHz.</p>	 <p>Level (dBuV/m) vs Frequency (MHz) plot for Peak Vertical. The y-axis ranges from 11.7 to 117 dBuV/m. The x-axis ranges from 2460 to 2500 MHz. A blue line shows the signal level, which is mostly below 58.5 dBuV/m. A red horizontal line at 70.2 dBuV/m is labeled 'FCC PART 15C -6dB'. A vertical blue line is at 2422 MHz.</p>
Average	 <p>Level (dBuV/m) vs Frequency (MHz) plot for Average Horizontal. The y-axis ranges from 11.7 to 117 dBuV/m. The x-axis ranges from 2460 to 2500 MHz. A blue line shows the average signal level, which is mostly below 46.8 dBuV/m. A red horizontal line at 46.8 dBuV/m is labeled 'FCC PART 15C (AVG) -6dB'. A vertical blue line is at 2422 MHz.</p>	 <p>Level (dBuV/m) vs Frequency (MHz) plot for Average Vertical. The y-axis ranges from 11.7 to 117 dBuV/m. The x-axis ranges from 2460 to 2500 MHz. A blue line shows the average signal level, which is mostly below 46.8 dBuV/m. A red horizontal line at 46.8 dBuV/m is labeled 'FCC PART 15C (AVG) -6dB'. A vertical blue line is at 2422 MHz.</p>







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Fundamental Emission @ 3m)	
ANT	CH03 2422MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11 n HT40 (Band Edge @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11 n HT40 (Band Edge @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak	 <p>Peak Horizontal Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red horizontal line at 70.2 dBuV/m labeled 'FCC PART 15C', and a vertical blue line at 2437 MHz. The y-axis ranges from 11.7 to 117 dBuV/m, and the x-axis ranges from 2460 to 2500 MHz.</p>	 <p>Peak Vertical Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red horizontal line at 70.2 dBuV/m labeled 'FCC PART 15C', and a vertical blue line at 2437 MHz. The y-axis ranges from 11.7 to 117 dBuV/m, and the x-axis ranges from 2460 to 2500 MHz.</p>
Average	 <p>Average Horizontal Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red horizontal line at 58.5 dBuV/m labeled 'FCC PART 15C (AVG)', and a vertical blue line at 2437 MHz. The y-axis ranges from 11.7 to 117 dBuV/m, and the x-axis ranges from 2460 to 2500 MHz.</p>	 <p>Average Vertical Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red horizontal line at 58.5 dBuV/m labeled 'FCC PART 15C (AVG)', and a vertical blue line at 2437 MHz. The y-axis ranges from 11.7 to 117 dBuV/m, and the x-axis ranges from 2460 to 2500 MHz.</p>







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Fundamental Emission @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
Average		







WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11 n HT40 (Band Edge @ 3m)	
ANT	CH09 2452MHz	
1	Horizontal	Vertical
Peak		
Average		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11 n HT40 (Band Edge @ 3m)	
ANT	CH09 2452MHz	
1	Horizontal	Vertical
Peak		
Average		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11 n HT40 (Fundamental Emission @ 3m)	
ANT	CH09 2452MHz	
1	Horizontal	Vertical
Peak		
Average		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		





WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic @ 3m)	
ANT	CH01 2412MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic @ 3m)	
ANT	CH11 2462MHz	
1	Horizontal	Vertical
Peak		



WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Harmonic @ 3m)	
ANT	CH03 2422MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Harmonic @ 3m)	
ANT	CH06 2437MHz	
1	Horizontal	Vertical
Peak		
WIFI	2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Harmonic @ 3m)	
ANT	CH09 2452MHz	
1	Horizontal	Vertical
Peak		



WIFI	Emission below 1GHz	
ANT	2.4GHz WIFI 802.11n HT40 (LF)	
1	Horizontal	Vertical
Peak		



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2385.6	51.68	-22.32	74	56.11	27	5.59	37.02	100	196	P	H
		2390	40.96	-13.04	54	45.39	27	5.59	37.02	100	196	A	H
	*	2413.444	96.94	-	-	101.2	27.13	5.61	37	100	196	P	H
	*	2413.36	94.43	-	-	98.69	27.13	5.61	37	100	196	A	H
		2378.4	52.16	-21.84	74	56.66	26.95	5.57	37.02	341	283	P	V
		2390	42.47	-11.53	54	46.9	27	5.59	37.02	341	283	A	V
	*	2413.444	99.76	-	-	104.02	27.13	5.61	37	341	283	P	V
	*	2413.36	97.32	-	-	101.58	27.13	5.61	37	341	283	A	V
802.11b CH 06 2437MHz	*	2438.243	98.68	-	-	102.61	27.39	5.65	36.97	101	289	P	H
	*	2438.326	96.2	-	-	100.13	27.39	5.65	36.97	101	289	A	H
	*	2438.243	101.58	-	-	105.51	27.39	5.65	36.97	337	302	P	V
	*	2438.326	99.1	-	-	103.03	27.39	5.65	36.97	337	302	A	V
802.11b CH 11 2462MHz	*	2460.788	101.36	-	-	105.14	27.51	5.67	36.96	180	242	P	H
	*	2460.872	98.88	-	-	102.66	27.51	5.67	36.96	180	242	A	H
		2488.52	52.85	-21.15	74	56.3	27.77	5.71	36.93	180	242	P	H
		2483.52	43.06	-10.94	54	46.67	27.64	5.69	36.94	180	242	A	H
	*	2463.376	103.78	-	-	107.56	27.51	5.67	36.96	300	279	P	V
	*	2463.293	101.27	-	-	105.05	27.51	5.67	36.96	300	279	A	V
		2488.44	54.04	-19.96	74	57.49	27.77	5.71	36.93	300	279	P	V
		2483.52	44.78	-9.22	54	48.39	27.64	5.69	36.94	300	279	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		3618	48.03	-25.97	74	48.62	29.12	6.86	36.57	100	360	P	H
		4824	48.71	-25.29	74	46.03	31.51	7.85	36.68	100	360	P	H
		3618	52.11	-21.89	74	52.7	29.12	6.86	36.57	100	360	P	V
		3618	45.62	-8.38	54	46.21	29.12	6.86	36.57	100	360	A	V
		4824	51.16	-22.84	74	48.48	31.51	7.85	36.68	100	282	P	V
		4824	46.83	-7.17	54	44.15	31.51	7.85	36.68	100	282	A	V
802.11b CH 06 2437MHz		3654	46.97	-27.03	74	47.47	29.17	6.88	36.55	100	360	P	H
		4875	45.87	-28.13	74	43.05	31.59	7.89	36.66	100	360	P	H
		7311	46.78	-27.22	74	39.86	34.03	9.58	36.69	100	0	P	H
		3657	50.47	-23.53	74	50.97	29.17	6.88	36.55	100	360	P	V
		3657	44.71	-9.29	54	45.21	29.17	6.88	36.55	100	360	A	V
		4875	44.73	-29.27	74	41.91	31.59	7.89	36.66	100	360	P	V
802.11b CH 11 2462MHz		4923	45.15	-28.85	74	42.21	31.67	7.92	36.65	100	360	P	H
		7386	47.71	-26.29	74	40.44	34.29	9.76	36.78	100	0	P	H
		4923	45.5	-28.5	74	42.56	31.67	7.92	36.65	100	360	P	V
		7386	48.94	-25.06	74	41.67	34.29	9.76	36.78	100	78	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.92	54.96	-19.04	74	59.39	27	5.59	37.02	100	269	P	H
		2390	45.08	-8.92	54	49.51	27	5.59	37.02	100	269	A	H
	*	2417.785	97.38	-	-	101.64	27.13	5.61	37	100	269	P	H
	*	2416.867	89.89	-	-	94.15	27.13	5.61	37	100	269	A	H
		2388.21	57.09	-16.91	74	61.52	27	5.59	37.02	145	320	P	V
		2389.29	47.86	-6.14	54	52.29	27	5.59	37.02	145	320	A	V
	*	2418.788	98.04	-	-	102.3	27.13	5.61	37	145	320	P	V
	*	2415.865	92.16	-	-	96.42	27.13	5.61	37	145	320	A	V
802.11g CH 06 2437MHz	*	2442	98.59	-	-	102.52	27.39	5.65	36.97	168	37	P	H
	*	2439.83	91.47	-	-	95.4	27.39	5.65	36.97	168	37	A	H
	*	2438.744	100.41	-	-	104.34	27.39	5.65	36.97	165	341	P	V
	*	2442.084	93.09	-	-	97.02	27.39	5.65	36.97	165	341	A	V
802.11g CH 11 2462MHz	*	2465.297	102.06	-	-	105.84	27.51	5.67	36.96	154	217	P	H
	*	2465.213	95.01	-	-	98.79	27.51	5.67	36.96	154	217	A	H
		2484.16	62.22	-11.78	74	65.83	27.64	5.69	36.94	154	217	P	H
	!	2483.92	50.55	-3.45	54	54.16	27.64	5.69	36.94	154	217	A	H
	*	2464.963	100.66	-	-	104.44	27.51	5.67	36.96	100	276	P	V
	*	2465.046	92.74	-	-	96.52	27.51	5.67	36.96	100	276	A	V
		2483.88	60.31	-13.69	74	63.92	27.64	5.69	36.94	100	276	P	V
	!	2484.28	50.17	-3.83	54	53.78	27.64	5.69	36.94	100	276	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	42.91	-31.09	74	40.23	31.51	7.85	36.68	100	360	P	H
		4824	42.93	-31.07	74	40.25	31.51	7.85	36.68	100	360	P	V
802.11g CH 06 2437MHz		4875	42.41	-31.59	74	39.59	31.59	7.89	36.66	100	360	P	H
		7311	45.18	-28.82	74	38.26	34.03	9.58	36.69	100	0	P	H
		4875	42.47	-31.53	74	39.65	31.59	7.89	36.66	100	360	P	V
802.11g CH 11 2462MHz		7311	46.59	-27.41	74	39.67	34.03	9.58	36.69	100	0	P	V
		4923	43.02	-30.98	74	40.08	31.67	7.92	36.65	100	360	P	H
		7386	45.15	-28.85	74	37.88	34.29	9.76	36.78	100	0	P	H
		4923	44	-30	74	41.06	31.67	7.92	36.65	100	360	P	V
802.11g CH 11 2462MHz		7386	45.81	-28.19	74	38.54	34.29	9.76	36.78	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2388.93	54.61	-19.39	74	59.04	27	5.59	37.02	100	43	P	H
		2388.57	44.16	-9.84	54	48.59	27	5.59	37.02	100	43	A	H
	*	2413.527	96.13	-	-	100.39	27.13	5.61	37	100	43	P	H
	*	2419.957	89.35	-	-	93.45	27.26	5.63	36.99	100	43	A	H
		2389.74	53.1	-20.9	74	57.53	27	5.59	37.02	375	57	P	V
		2386.95	43.16	-10.84	54	47.59	27	5.59	37.02	375	57	A	V
	*	2407.181	94.61	-	-	98.87	27.13	5.61	37	375	57	P	V
	*	2410.354	88.02	-	-	92.28	27.13	5.61	37	375	57	A	V
802.11n HT20 CH 06 2437MHz	*	2439.162	96.44	-	-	100.37	27.39	5.65	36.97	100	97	P	H
	*	2444.923	89.49	-	-	93.42	27.39	5.65	36.97	100	97	A	H
	*	2437.909	95.57	-	-	99.5	27.39	5.65	36.97	100	360	P	V
	*	2433.901	87.21	-	-	91.31	27.26	5.63	36.99	100	360	A	V
802.11n HT20 CH 11 2462MHz	*	2464.879	102.41	-	-	106.19	27.51	5.67	36.96	100	275	P	H
	*	2469.305	95	-	-	98.78	27.51	5.67	36.96	100	275	A	H
		2488.12	57.23	-16.77	74	60.68	27.77	5.71	36.93	100	275	P	H
		2483.68	47.3	-6.7	54	50.91	27.64	5.69	36.94	100	275	A	H
	*	2465.13	98.02	-	-	101.8	27.51	5.67	36.96	306	207	P	V
	*	2465.13	90.79	-	-	94.57	27.51	5.67	36.96	306	207	A	V
		2486.04	53.86	-20.14	74	57.47	27.64	5.69	36.94	306	207	P	V
	2484.16	44.68	-9.32	54	48.29	27.64	5.69	36.94	306	207	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		3618	54.4	-19.6	74	54.99	29.12	6.86	36.57	100	271	P	H
HT20		3618	45.11	-8.89	54	45.7	29.12	6.86	36.57	100	271	A	H
CH 01		4824	43.16	-30.84	74	40.48	31.51	7.85	36.68	157	268	P	H
2412MHz		4824	42.56	-31.44	74	39.88	31.51	7.85	36.68	124	287	P	V
802.11n		4875	42.2	-31.8	74	39.38	31.59	7.89	36.66	100	360	P	H
HT20		7311	45.42	-28.58	74	38.5	34.03	9.58	36.69	100	0	P	H
CH 06		4875	41.98	-32.02	74	39.16	31.59	7.89	36.66	100	360	P	V
2437MHz		7311	45.96	-28.04	74	39.04	34.03	9.58	36.69	100	0	P	V
802.11n		4923	43.76	-30.24	74	40.82	31.67	7.92	36.65	125	94	P	H
HT20		7386	46.23	-27.77	74	38.96	34.29	9.76	36.78	274	164	P	H
CH 11		4923	42.73	-31.27	74	39.79	31.67	7.92	36.65	138	61	P	V
2462MHz		7386	47.28	-26.72	74	40.01	34.29	9.76	36.78	194	283	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2390	60.88	-13.12	74	65.31	27	5.59	37.02	305	54	P	H
		2389.29	47.77	-6.23	54	52.2	27	5.59	37.02	305	54	A	H
	*	2432.064	95.86	-	-	99.96	27.26	5.63	36.99	305	54	P	H
	*	2428.39	89.17	-	-	93.27	27.26	5.63	36.99	305	54	A	H
		2486.8	56.77	-17.23	74	60.38	27.64	5.69	36.94	305	54	P	H
		2484.88	45.42	-8.58	54	49.03	27.64	5.69	36.94	305	54	A	H
		2388.48	63.45	-10.55	74	67.88	27	5.59	37.02	100	74	P	V
	!	2387.31	51.79	-2.21	54	56.22	27	5.59	37.02	100	74	A	V
	*	2416.115	98.36	-	-	102.62	27.13	5.61	37	100	70	P	V
	*	2428.39	91	-	-	95.1	27.26	5.63	36.99	100	70	A	V
802.11n HT40 CH 06 2437MHz		2484.44	57.23	-16.77	74	60.84	27.64	5.69	36.94	100	70	P	V
		2483.64	46.36	-7.64	54	49.97	27.64	5.69	36.94	100	70	A	V
		2370.57	51.35	-22.65	74	55.85	26.95	5.57	37.02	113	57	P	H
		2342.31	42.7	-11.3	54	47.33	26.86	5.52	37.01	113	57	A	H
	*	2439.496	94.85	-	-	98.78	27.39	5.65	36.97	113	57	P	H
	*	2445.007	87.21	-	-	91.14	27.39	5.65	36.97	113	57	A	H
		2491.16	56.14	-17.86	74	59.59	27.77	5.71	36.93	113	57	P	H
		2488	46.07	-7.93	54	49.52	27.77	5.71	36.93	113	57	A	H
		2387.94	55.29	-18.71	74	59.72	27	5.59	37.02	100	81	P	V
		2389.29	44.45	-9.55	54	48.88	27	5.59	37.02	100	81	A	V
*	2442.668	99.18	-	-	103.11	27.39	5.65	36.97	100	81	P	V	
*	2442.919	90.43	-	-	94.36	27.39	5.65	36.97	100	81	A	V	
	2483.92	60.03	-13.97	74	63.64	27.64	5.69	36.94	100	81	P	V	
	2487.72	47.64	-6.36	54	51.09	27.77	5.71	36.93	100	81	A	V	



802.11n HT40 CH 09 2452MHz		2326.11	51.41	-22.59	74	56.1	26.82	5.5	37.01	400	308	P	H
		2384.7	42.26	-11.74	54	46.76	26.95	5.57	37.02	400	308	A	H
	*	2454.024	96.62	-	-	100.4	27.51	5.67	36.96	400	308	P	H
	*	2458.533	89.34	-	-	93.12	27.51	5.67	36.96	400	308	A	H
		2489.2	57.17	-16.83	74	60.62	27.77	5.71	36.93	400	308	P	H
		2488.28	47.45	-6.55	54	50.9	27.77	5.71	36.93	400	308	A	H
		2386.95	51.53	-22.47	74	55.96	27	5.59	37.02	100	277	P	V
		2377.95	42.71	-11.29	54	47.21	26.95	5.57	37.02	100	277	A	V
	*	2449.599	99.61	-	-	103.54	27.39	5.65	36.97	100	277	P	V
	*	2453.69	91.8	-	-	95.58	27.51	5.67	36.96	100	277	A	V
		2485.16	61.74	-12.26	74	65.35	27.64	5.69	36.94	100	277	P	V
!	2488	51.15	-2.85	54	54.6	27.77	5.71	36.93	100	277	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		4845	43.05	-30.95	74	40.34	31.53	7.86	36.68	241	318	P	H
HT40		7266	45.73	-28.27	74	38.95	33.93	9.51	36.66	124	281	P	H
CH 03		4845	43.66	-30.34	74	40.95	31.53	7.86	36.68	124	85	P	V
2422MHz		7266	45.63	-28.37	74	38.85	33.93	9.51	36.66	122	187	P	V
802.11n		4875	43.02	-30.98	74	40.2	31.59	7.89	36.66	131	294	P	H
HT40		7311	45.82	-28.18	74	38.9	34.03	9.58	36.69	281	67	P	H
CH 06		4875	43.01	-30.99	74	40.19	31.59	7.89	36.66	124	329	P	V
2437MHz		7311	45.65	-28.35	74	38.73	34.03	9.58	36.69	167	41	P	V
802.11n		4905	42.8	-31.2	74	39.9	31.64	7.91	36.65	100	360	P	H
HT40		7356	45.4	-28.6	74	38.27	34.19	9.69	36.75	100	0	P	H
CH 09		4905	42.67	-31.33	74	39.77	31.64	7.91	36.65	100	360	P	V
2452MHz		7356	46.67	-27.33	74	39.54	34.19	9.69	36.75	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		31.94	18.53	-21.47	40	32.07	18.22	0.79	32.55	100	67	P	H
		38.73	15.58	-24.42	40	32.54	14.79	0.79	32.54	-	-	P	H
		98.87	9.18	-34.32	43.5	29.26	11.19	1.04	32.31	-	-	P	H
		168.71	10.89	-32.61	43.5	30.91	10.99	1.44	32.45	-	-	P	H
		540.22	17.2	-28.8	46	27.76	18.55	2.64	31.75	-	-	P	H
		894.27	20.76	-25.24	46	26.4	22.5	3.5	31.64	-	-	P	H
		30.97	29.3	-10.7	40	42.38	18.71	0.79	32.58	100	254	P	V
		39.7	25.31	-14.69	40	42.78	14.3	0.79	32.56	-	-	P	V
		53.28	17.19	-22.81	40	41.03	7.92	0.79	32.55	-	-	P	V
		91.11	10.09	-33.41	43.5	31.08	10.31	1.04	32.34	-	-	P	V
		569.32	17.07	-28.93	46	27.19	18.86	2.72	31.7	-	-	P	V
	945.68	21.43	-24.57	46	27.44	21.69	3.68	31.38	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.