



SAR EVALUATION REPORT

Applicant Name:

LG Electronics U.S.A., Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

06/27/19 - 07/15/19

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1906260111-01-R1.ZNF

FCC ID:

ZNFX320PM

APPLICANT:

LG ELECTRONICS U.S.A., INC.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

LM-X320PM

Additional Model(s):

LMX320PM, X320PM

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.28	0.41	0.41
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.36	0.39	0.42
PCE	UMTS 850	826.40 - 846.60 MHz	0.36	0.50	0.51
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.58	1.02	1.02
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.59	0.74	0.78
PCE	CDMA/EVDO BC10 (\$90S)	817.90 - 823.10 MHz	0.40	0.60	0.70
PCE	CDMA/EVDO BC0 (\$22H)	824.70 - 848.31 MHz	0.37	0.51	0.56
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.60	0.76	0.75
PCE	LTE Band 71	665.5 - 695.5 MHz	0.18	0.39	0.39
PCE	LTE Band 12	699.7 - 715.3 MHz	0.28	0.43	0.46
PCE	LTE Band 13	779.5 - 784.5 MHz	0.45	0.44	0.49
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.44	0.64	0.87
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	N/A	N/A	N/A
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.78	1.07	1.07
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.67	0.76	0.76
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.29	0.75	1.29
PCE	2.4 GHz WLAN	2412 - 2462 MHz	0.97	0.14	0.14
DTS	Bluetooth	2402 - 2480 MHz	0.14	N/A	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.57	1.30	1.52

Note: This revised Test Report (S/N: 1M1906260111-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortaez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 1 of 90	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS.....	14
6	TEST CONFIGURATION POSITIONS.....	15
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS	26
10	SYSTEM VERIFICATION.....	54
11	SAR DATA SUMMARY	56
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	73
13	SAR MEASUREMENT VARIABILITY	82
14	ADDITIONAL TESTING PER FCC GUIDANCE	83
15	EQUIPMENT LIST	86
16	MEASUREMENT UNCERTAINTIES.....	87
17	CONCLUSION.....	88
18	REFERENCES	89
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: DOWNLINK LTE CA RF CONDUCTED POWERS		

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 2 of 90	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
CDMA/EVDO BC10 (§90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (§22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 3 of 90

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slot	1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.6	33.6	31.0	26.5	26.5
	Nominal	33.1	33.1	30.5	26.0	26.0
GSM/GPRS/EDGE 1900	Maximum	30.8	30.8	28.0	25.5	25.5
	Nominal	30.3	30.3	27.5	25.0	25.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	25.3	25.3	24.3
	Nominal	24.8	24.8	23.8
UMTS Band 4 (1750 MHz)	Maximum	24.8	24.8	23.8
	Nominal	24.3	24.3	23.3
UMTS Band 2 (1900 MHz)	Maximum	24.8	24.8	23.8
	Nominal	24.3	24.3	23.3

FCC ID: ZNFX320PM				Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 4 of 90

Mode / Band		Modulated Average (dBm)
CDMA/EVDO BC10 (§90S)	Maximum	25.3
	Nominal	24.8
CDMA/EVDO BC0 (§22H)	Maximum	25.3
	Nominal	24.8
PCS CDMA/EVDO	Maximum	24.8
	Nominal	24.3

Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	25.3
	Nominal	24.8
LTE Band 12	Maximum	25.3
	Nominal	24.8
LTE Band 13	Maximum	25.3
	Nominal	24.8
LTE Band 26 (Cell)	Maximum	25.3
	Nominal	24.8
LTE Band 5 (Cell)	Maximum	25.3
	Nominal	24.8
LTE Band 66 (AWS)	Maximum	24.8
	Nominal	24.3
LTE Band 4 (AWS)	Maximum	24.8
	Nominal	24.3
LTE Band 25 (PCS)	Maximum	24.8
	Nominal	24.3
LTE Band 2 (PCS)	Maximum	24.8
	Nominal	24.3
LTE Band 41 (PC3)	Maximum	24.8
	Nominal	24.3
LTE Band 41 (PC2)	Maximum	27.8
	Nominal	27.3

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 5 of 90

Mode / Band		Modulated Average (dBm)				
Channel		1	2	3 - 9	10	11
IEEE 802.11b (2.4 GHz)	Maximum	16.0				
	Nominal	15.0				
IEEE 802.11g (2.4 GHz)	Maximum	15.0	15.5	15.5	15.5	15.5
	Nominal	14.0	14.5	14.5	14.5	14.5
IEEE 802.11n (2.4 GHz)	Maximum	15.0	15.5	15.5	15.5	15.5
	Nominal	14.0	14.5	14.5	14.5	14.5

Mode / Band		Modulated Average (dBm)
Bluetooth	Maximum	10.5
	Nominal	9.5
Bluetooth LE	Maximum	5.5
	Nominal	4.5

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 6 of 90

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
EVDO BC10 (§90S)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC0 (§22H)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	No	Yes
LTE Band 71	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 7 of 90

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	1x CDMA voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
2	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^ Bluetooth Tethering is considered
3	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
4	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^ Bluetooth Tethering is considered
5	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^ Bluetooth Tethering is considered
7	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	
8	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^ Bluetooth Tethering is considered
9	CDMA/EVDO data + 2.4 GHz WI-FI	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
10	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
11	GPRS/EDGE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
12	GPRS/EDGE + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered

- 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- This device supports VOLTE.
- This device supports VoWIFI.
- This device supports Bluetooth Tethering.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn and hotspot Bluetooth SAR was not required; $[(11/10) * \sqrt{2.480}] = 1.7 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 8 of 90

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01v03r01.

This device supports LTE Carrier Aggregation (CA) in the downlink. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix G.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports both Power Class 2 (PC2) and Power Class 3 (PC3) for LTE Band 41. Per May 2017 TCB Workshop Notes, SAR tests were performed with Power Class 3 (given the specific UL/DL limitations for Power Class 2). Additionally, SAR testing for the power class condition was evaluated for the highest configuration in Power Class 3 for each test configuration to confirm the results were scalable linearly (See Section 14.1).

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 9 of 90

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE Band 41 Power Class 2/3)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 10 of 90	

LTE Information					
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 71 (665.5 - 695.5 MHz)				
	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 71: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 71: 5 MHz	665.5 (133147)		680.5 (133297)		695.5 (133447)
LTE Band 71: 10 MHz	668 (133172)		680.5 (133297)		693 (133422)
LTE Band 71: 15 MHz	670.5 (133197)		680.5 (133297)		690.5 (133397)
LTE Band 71: 20 MHz	673 (133222)		680.5 (133297)		688 (133372)
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)		784.5 (23255)
LTE Band 13: 10 MHz	N/A		782 (23230)		N/A
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	821.5 (26765)		831.5 (26865)		841.5 (26965)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)		1779.3 (132665)
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)		1778.5 (132657)
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)		1777.5 (132647)
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)		1775 (132622)
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)		1772.5 (132597)
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)		1770 (132572)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	DL UE Cat 6, UL UE Cat 5				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 11. It supports carrier aggregation features as shown in Appendix G. All other uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 11 Features are not supported: Relay, HetNet, Enhanced MIMO, eCIC, WiFi Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 11 of 90

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 12 of 90

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid $\Delta z_{\text{zoom}}(n)$	Graded Grid		
				$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 13 of 90

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 14 of 90

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 15 of 90




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 16 of 90

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 17 of 90

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 18 of 90

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 19 of 90

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with EVDO capabilities, the 3G SAR test reduction procedure is applied to EVDO Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 20 of 90

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 21 of 90

primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 22 of 90	

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 23 of 90

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.7.3 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.7.4 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 24 of 90

bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.7.5 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.4).

8.7.6 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 25 of 90

9.1 CDMA Conducted Powers

Table 9-1
Maximum Conducted Power

				Loopback			Data			
Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	25.06	25.04	25.04	25.14	25.14	25.25	25.03
Cellular	1013	22H	824.7	25.28	25.27	25.28	25.30	25.30	25.07	25.30
	384	22H	836.52	25.16	25.18	25.22	25.30	25.29	24.87	25.15
	777	22H	848.31	25.12	25.12	25.14	25.23	25.22	24.88	25.14
PCS	25	24E	1851.25	24.53	24.57	24.56	24.56	24.59	24.51	24.49
	600	24E	1880	24.66	24.72	24.70	24.69	24.73	24.59	24.60
	1175	24E	1908.75	24.79	24.79	24.80	24.79	24.80	24.63	24.71

Note: RC1 is only applicable for IS-95 compatibility. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v06 4.1.g), only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.




Figure 9-1
Power Measurement Setup

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 26 of 90

9.2 GSM Conducted Powers

Table 9-2
Maximum Conducted Power

Maximum Burst-Averaged Output Power						
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	33.53	33.45	30.57	26.49	26.16
	190	33.60	33.50	30.67	26.50	26.29
	251	33.58	33.49	30.66	26.39	26.50
GSM 1900	512	30.30	30.29	27.04	25.43	25.23
	661	30.34	30.35	27.09	25.38	25.21
	810	30.41	30.43	27.30	25.42	25.25

Calculated Maximum Frame-Averaged Output Power						
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	24.50	24.42	24.55	17.46	20.14
	190	24.57	24.47	24.65	17.47	20.27
	251	24.55	24.46	24.64	17.36	20.48
GSM 1900	512	21.27	21.26	21.02	16.40	19.21
	661	21.31	21.32	21.07	16.35	19.19
	810	21.38	21.40	21.28	16.39	19.23

GSM 850	Frame Avg.Targets:	24.07	24.07	24.48	16.97	19.98
GSM 1900		21.27	21.27	21.48	15.97	18.98

FCC ID: ZNFX320PM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset			Page 27 of 90

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 10 (Max 2 Tx uplink slots)
EDGE Multislot class: 10 (Max 2 Tx uplink slots)
DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 28 of 90

9.3 UMTS Conducted Powers

Table 9-3
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	25.30	25.22	25.25	24.63	24.61	24.80	24.78	24.70	24.80	-
99		12.2 kbps AMR	25.26	25.26	25.24	24.60	24.62	24.80	24.74	24.77	24.62	-
6	HSDPA	Subtest 1	25.21	25.21	25.23	23.35	23.34	23.41	23.33	23.32	23.40	0
6		Subtest 2	25.20	25.17	25.26	23.33	23.30	23.37	23.30	23.32	23.35	0
6		Subtest 3	24.80	24.77	24.78	22.82	22.80	22.89	22.81	22.88	22.83	0.5
6		Subtest 4	24.75	24.75	24.73	22.81	22.85	22.89	22.82	22.83	22.86	0.5
6	HSUPA	Subtest 1	21.72	21.65	21.68	21.26	21.13	21.23	21.23	21.27	21.30	0
6		Subtest 2	21.66	21.48	21.62	21.22	21.15	21.25	21.14	21.11	21.10	2
6		Subtest 3	22.65	22.65	22.66	22.23	22.19	22.29	22.18	22.20	22.21	1
6		Subtest 4	21.20	21.23	21.22	20.71	20.66	20.73	20.66	20.69	20.78	2
6		Subtest 5	22.80	22.81	22.83	22.32	22.36	22.35	22.30	22.32	22.34	0

This device does not support DC-HSDPA.



Figure 9-3
Power Measurement Setup

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 29 of 90

9.4 LTE Conducted Powers

9.4.1

LTE Band 71

Table 9-4
LTE Band 71 Conducted Powers - 20 MHz Bandwidth

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.90	0	0
	1	50	24.96		0
	1	99	24.70		0
	50	0	23.90	0-1	1
	50	25	24.01		1
	50	50	24.00		1
	100	0	23.95		1
16QAM	1	0	23.82	0-1	1
	1	50	24.22		1
	1	99	23.95		1
	50	0	22.97	0-2	2
	50	25	22.99		2
	50	50	22.99		2
	100	0	22.97		2
64QAM	1	0	23.04	0-2	2
	1	50	23.16		2
	1	99	22.90		2
	50	0	21.99	0-3	3
	50	25	22.06		3
	50	50	22.06		3
	100	0	21.96		3

Note: LTE Band 71 at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX320PM				Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 30 of 90

Table 9-5
LTE Band 71 Conducted Powers - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.92	0	0
	1	36	24.94		0
	1	74	24.84		0
	36	0	24.04	0-1	1
	36	18	24.04		1
	36	37	24.03		1
	75	0	24.01		1
16QAM	1	0	24.10	0-1	1
	1	36	24.11		1
	1	74	24.00		1
	36	0	23.01	0-2	2
	36	18	23.04		2
	36	37	23.03		2
	75	0	23.01		2
64QAM	1	0	23.15	0-2	2
	1	36	23.15		2
	1	74	23.01		2
	36	0	22.04	0-3	3
	36	18	22.06		3
	36	37	22.04		3
	75	0	22.00		3

Note: LTE Band 71 at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 31 of 90

Table 9-6
LTE Band 71 Conducted Powers - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.95	24.95	24.90	0	0
	1	25	25.00	25.03	24.92		0
	1	49	24.83	24.86	24.83		0
	25	0	23.94	24.01	23.99	0-1	1
	25	12	24.08	24.06	24.00		1
	25	25	24.12	24.04	23.89		1
16QAM	50	0	24.06	24.04	23.96	0-1	1
	1	0	23.93	24.10	24.00		1
	1	25	24.12	24.20	24.05		1
	1	49	24.00	24.10	24.03	0-2	1
	25	0	22.93	23.03	23.00		2
	25	12	23.09	23.05	22.99		2
64QAM	25	25	23.11	23.02	22.87	0-2	2
	50	0	23.05	23.04	22.93		2
	1	0	23.05	23.16	23.13		0-2
	1	25	23.20	23.25	23.16	2	
	1	49	23.04	23.07	23.00	2	
	25	0	21.95	22.03	22.00	0-3	3
25	12	22.10	22.06	22.02	3		
25	25	22.14	22.02	21.88	3		
	50	0	22.07	22.03	21.97		3

Table 9-7
LTE Band 71 Conducted Powers - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.90	24.82	24.80	0	0
	1	12	25.10	25.09	25.04		0
	1	24	24.80	24.82	24.79		0
	12	0	23.95	23.96	23.96	0-1	1
	12	6	24.05	24.02	24.00		1
	12	13	24.04	23.95	23.92		1
16QAM	25	0	24.01	23.97	23.98	0-1	1
	1	0	23.92	24.04	24.00		1
	1	12	24.19	24.30	24.22		1
	1	24	23.88	24.01	23.93	0-2	1
	12	0	22.93	23.00	22.96		2
	12	6	23.04	23.08	23.04		2
64QAM	12	13	23.06	23.00	22.96	0-2	2
	25	0	22.98	23.00	22.98		2
	1	0	23.00	23.08	23.00	0-2	2
	1	12	23.23	23.21	23.23		2
	1	24	22.98	23.04	23.00	0-3	2
	12	0	21.95	22.02	22.00		3
12	6	22.05	22.08	22.04	3		
12	13	22.09	22.01	21.96	3		
	25	0	22.01	22.00	21.99		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 32 of 90	

9.4.2

LTE Band 12

Table 9-8
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.03	0	0
	1	25	25.04		0
	1	49	24.96		0
	25	0	24.22	0-1	1
	25	12	24.16		1
	25	25	24.01		1
	50	0	24.16		1
16QAM	1	0	24.20	0-1	1
	1	25	24.22		1
	1	49	24.03		1
	25	0	23.17	0-2	2
	25	12	23.14		2
	25	25	23.06		2
	50	0	23.13		2
64QAM	1	0	23.23	0-2	2
	1	25	23.00		2
	1	49	23.00		2
	25	0	22.14	0-3	3
	25	12	22.18		3
	25	25	22.12		3
	50	0	22.12		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 33 of 90

Table 9-9
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.93	25.06	24.94	0	0
	1	12	25.20	25.23	25.22		0
	1	24	24.93	24.99	25.00		0
	12	0	24.29	24.20	24.15	0-1	1
	12	6	24.14	24.26	24.16		1
	12	13	24.08	24.18	24.08		1
	25	0	24.09	24.14	24.14		1
16QAM	1	0	24.07	24.15	24.03	0-1	1
	1	12	24.30	24.24	24.30		1
	1	24	24.06	24.15	23.98		1
	12	0	23.10	23.17	23.15	0-2	2
	12	6	23.16	23.19	23.06		2
	12	13	23.09	23.09	23.08		2
	25	0	23.07	23.14	23.02		2
64QAM	1	0	23.13	23.20	23.02	0-2	2
	1	12	23.23	23.20	23.09		2
	1	24	23.08	23.05	23.23		2
	12	0	22.14	22.19	22.20	0-3	3
	12	6	22.17	22.21	22.20		3
	12	13	22.12	22.14	22.09		3
	25	0	22.12	22.16	22.16		3

Table 9-10
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.98	25.08	25.04	0	0
	1	7	25.21	25.20	25.20		0
	1	14	25.02	25.03	25.04		0
	8	0	24.07	24.11	24.11	0-1	1
	8	4	24.12	24.12	24.13		1
	8	7	24.08	24.09	24.18		1
	15	0	24.13	24.14	24.14		1
16QAM	1	0	24.13	24.23	24.17	0-1	1
	1	7	24.30	24.26	24.21		1
	1	14	24.24	24.16	24.14		1
	8	0	23.13	23.17	23.13	0-2	2
	8	4	23.16	23.18	23.17		2
	8	7	23.14	23.15	23.12		2
	15	0	23.11	23.12	23.10		2
64QAM	1	0	23.15	23.25	23.19	0-2	2
	1	7	23.25	23.24	23.28		2
	1	14	23.20	23.11	23.20		2
	8	0	22.15	22.18	22.00	0-3	3
	8	4	22.18	22.20	22.19		3
	8	7	22.16	22.15	22.15		3
	15	0	22.14	22.16	22.13		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 34 of 90

Table 9-11
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.80	24.85	24.84	0	0
	1	2	24.98	25.00	25.00		0
	1	5	24.83	24.83	24.82		0
	3	0	24.91	24.98	24.96		0
	3	2	24.95	25.01	24.99		0
	3	3	24.94	24.97	24.95		0
	6	0	23.97	24.01	24.00	0-1	1
16QAM	1	0	23.89	24.00	23.96	0-1	1
	1	2	24.16	24.16	24.12		1
	1	5	23.95	24.01	23.95		1
	3	0	23.90	23.97	23.98		1
	3	2	23.96	24.00	23.97		1
	3	3	23.93	23.98	23.93		1
	6	0	23.02	23.05	23.03	0-2	2
64QAM	1	0	22.98	23.03	23.00	0-2	2
	1	2	23.12	23.21	23.16		2
	1	5	23.01	23.00	22.99		2
	3	0	22.98	23.05	23.04		2
	3	2	23.02	23.08	23.07		2
	3	3	23.01	23.04	22.99		2
	6	0	21.99	22.02	21.98	0-3	3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 35 of 90

9.4.3

LTE Band 13

Table 9-12
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.02	0	0
	1	25	25.04		0
	1	49	24.90		0
	25	0	24.15	0-1	1
	25	12	24.10		1
	25	25	24.00		1
	50	0	24.12		1
16QAM	1	0	24.27	0-1	1
	1	25	24.26		1
	1	49	24.05		1
	25	0	23.14	0-2	2
	25	12	23.09		2
	25	25	23.03		2
	50	0	23.09		2
64QAM	1	0	23.19	0-2	2
	1	25	23.30		2
	1	49	23.00		2
	25	0	22.20	0-3	3
	25	12	22.15		3
	25	25	22.11		3
	50	0	22.17		3

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 36 of 90

Table 9-13
LTE Band 13 Conducted Powers - 5 MHz Bandwidth
LTE Band 13
5 MHz Bandwidth

Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.03	0	0
	1	12	25.18		0
	1	24	24.89		0
	12	0	24.11	0-1	1
	12	6	24.15		1
	12	13	24.05		1
	25	0	24.10		1
16QAM	1	0	24.18	0-1	1
	1	12	24.24		1
	1	24	24.06		1
	12	0	23.09	0-2	2
	12	6	23.15		2
	12	13	23.03		2
	25	0	23.07		2
64QAM	1	0	23.16	0-2	2
	1	12	23.29		2
	1	24	23.05		2
	12	0	22.15	0-3	3
	12	6	22.22		3
	12	13	22.12		3
	25	0	22.14		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 37 of 90

9.4.4

LTE Band 26 (Cell)

Table 9-14
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.96	0	0
	1	36	24.97		0
	1	74	24.91		0
	36	0	24.19	0-1	1
	36	18	24.21		1
	36	37	24.13		1
	75	0	24.11		1
16QAM	1	0	24.19	0-1	1
	1	36	24.15		1
	1	74	24.06		1
	36	0	23.12	0-2	2
	36	18	23.11		2
	36	37	23.06		2
	75	0	23.11		2
64QAM	1	0	23.24	0-2	2
	1	36	23.27		2
	1	74	23.26		2
	36	0	22.20	0-3	3
	36	18	22.17		3
	36	37	22.12		3
	75	0	22.13		3

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 38 of 90

Table 9-15
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.02	24.98	25.04	0	0
	1	25	25.10	25.15	25.17		0
	1	49	24.98	24.97	25.04		0
	25	0	24.15	24.22	24.29	0-1	1
	25	12	24.11	24.21	24.22		1
	25	25	24.15	24.18	24.10		1
	50	0	24.16	24.21	24.24		1
16QAM	1	0	24.19	24.27	24.28	0-1	1
	1	25	24.25	24.29	24.27		1
	1	49	24.28	24.13	24.27		1
	25	0	23.13	23.20	23.30	0-2	2
	25	12	23.08	23.18	23.23		2
	25	25	23.15	23.15	23.11		2
	50	0	23.13	23.18	23.22		2
64QAM	1	0	23.23	23.25	23.27	0-2	2
	1	25	23.28	23.28	23.27		2
	1	49	23.26	23.18	23.22		2
	25	0	22.20	22.23	22.28	0-3	3
	25	12	22.19	22.21	22.25		3
	25	25	22.18	22.17	22.15		3
	50	0	22.18	22.21	22.25		3

Table 9-16
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.95	24.97	25.00	0	0
	1	12	25.21	25.12	25.21		0
	1	24	24.90	24.97	25.00		0
	12	0	24.08	24.12	24.24	0-1	1
	12	6	24.15	24.23	24.24		1
	12	13	24.08	24.17	24.09		1
	25	0	24.12	24.19	24.18		1
16QAM	1	0	24.15	24.24	24.28	0-1	1
	1	12	24.30	24.29	24.30		1
	1	24	24.09	24.15	24.21		1
	12	0	23.08	23.19	23.26	0-2	2
	12	6	23.15	23.24	23.25		2
	12	13	23.07	23.16	23.10		2
	25	0	23.11	23.14	23.19		2
64QAM	1	0	23.21	23.23	23.25	0-2	2
	1	12	23.27	23.28	23.24		2
	1	24	23.08	23.21	23.21		2
	12	0	22.16	22.20	22.28	0-3	3
	12	6	22.22	22.25	22.30		3
	12	13	22.15	22.20	22.12		3
	25	0	22.17	22.19	22.23		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 39 of 90

Table 9-17
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.05	25.09	25.11	0	0
	1	7	25.18	25.25	25.24		0
	1	14	25.02	25.08	25.11		0
	8	0	24.08	24.17	24.20	0-1	1
	8	4	24.09	24.19	24.20		1
	8	7	24.09	24.18	24.18		1
	15	0	24.10	24.22	24.21		1
16QAM	1	0	24.25	24.28	24.30	0-1	1
	1	7	24.25	24.29	24.29		1
	1	14	24.22	24.24	24.29		1
	8	0	23.14	23.20	23.25	0-2	2
	8	4	23.16	23.23	23.24		2
	8	7	23.13	23.22	23.20		2
	15	0	23.07	23.18	23.17		2
64QAM	1	0	23.24	23.28	23.24	0-2	2
	1	7	23.25	23.30	23.30		2
	1	14	23.24	23.30	23.29		2
	8	0	22.20	22.25	22.28	0-3	3
	8	4	22.22	22.26	22.28		3
	8	7	22.21	22.25	22.24		3
	15	0	22.13	22.22	22.21		3

Table 9-18
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.99	25.01	25.03	0	0
	1	2	25.13	25.16	25.18		0
	1	5	24.97	25.01	25.06		0
	3	0	25.10	25.13	25.16		0
	3	2	25.14	25.14	25.20		0
	3	3	25.08	25.12	25.15		0
	6	0	24.12	24.20	24.25	0-1	1
16QAM	1	0	24.22	24.27	24.19	0-1	1
	1	2	24.30	24.25	24.30		1
	1	5	24.14	24.26	24.23		1
	3	0	24.15	24.20	24.21		1
	3	2	24.18	24.22	24.25		1
	3	3	24.15	24.19	24.21	1	
64QAM	6	0	23.18	23.26	23.30	0-2	2
	1	0	23.23	23.25	23.28	0-2	2
	1	2	23.30	23.26	23.29		2
	1	5	23.20	23.26	23.23		2
	3	0	23.22	23.25	23.28		2
	3	2	23.22	23.30	23.28		2
	3	3	23.21	23.24	23.27		2
6	0	22.18	22.21	22.25	0-3	3	

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 40 of 90

9.4.5

LTE Band 66 (AWS)

Table 9-19
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.73	24.51	24.67	0	0
	1	50	24.80	24.68	24.79		0
	1	99	24.56	24.43	24.55		0
	50	0	23.76	23.77	23.79	0-1	1
	50	25	23.80	23.76	23.79		1
	50	50	23.76	23.63	23.75		1
	100	0	23.78	23.69	23.78		1
16QAM	1	0	23.79	23.80	23.76	0-1	1
	1	50	23.76	23.60	23.72		1
	1	99	23.68	23.80	23.77		1
	50	0	22.80	22.75	22.78	0-2	2
	50	25	22.76	22.69	22.75		2
	50	50	22.71	22.62	22.80		2
	100	0	22.71	22.65	22.78		2
64QAM	1	0	22.78	22.53	22.80	0-2	2
	1	50	22.75	22.80	22.80		2
	1	99	22.71	22.54	22.71		2
	50	0	21.75	21.72	21.70	0-3	3
	50	25	21.80	21.72	21.74		3
	50	50	21.76	21.70	21.78		3
	100	0	21.75	21.73	21.71		3

Table 9-20
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.69	24.46	24.65	0	0
	1	36	24.74	24.53	24.80		0
	1	74	24.56	24.41	24.74		0
	36	0	23.80	23.65	23.73	0-1	1
	36	18	23.75	23.62	23.76		1
	36	37	23.75	23.59	23.73		1
	75	0	23.79	23.68	23.72		1
16QAM	1	0	23.77	23.70	23.77	0-1	1
	1	36	23.72	23.79	23.80		1
	1	74	23.70	23.74	23.80		1
	36	0	22.71	22.62	22.72	0-2	2
	36	18	22.72	22.66	22.78		2
	36	37	22.77	22.57	22.76		2
	75	0	22.75	22.65	22.77		2
64QAM	1	0	22.75	22.56	22.70	0-2	2
	1	36	22.77	22.59	22.76		2
	1	74	22.65	22.48	22.66		2
	36	0	21.70	21.50	21.59	0-3	3
	36	18	21.69	21.47	21.65		3
	36	37	21.69	21.45	21.64		3
	75	0	21.71	21.46	21.64		3

FCC ID: ZNFX320PM			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 41 of 90		

Table 9-21
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.67	24.39	24.63	0	0
	1	25	24.80	24.60	24.80		0
	1	49	24.67	24.36	24.74		0
	25	0	23.80	23.54	23.73	0-1	1
	25	12	23.79	23.57	23.77		1
	25	25	23.74	23.52	23.77		1
16QAM	50	0	23.80	23.59	23.80	0-1	1
	1	0	23.80	23.66	23.80		1
	1	25	23.80	23.73	23.76		1
	1	49	23.79	23.71	23.74	0-2	1
	25	0	22.80	22.60	22.71		2
	25	12	22.78	22.61	22.71		2
64QAM	25	25	22.75	22.60	22.73	0-2	2
	50	0	22.73	22.58	22.74		2
	1	0	22.77	22.59	22.72		0-2
	1	25	22.80	22.75	22.80	2	
	1	49	22.75	22.56	22.70	0-3	
	25	0	21.71	21.52	21.60		3
25	12	21.72	21.51	21.68	3		
64QAM	25	25	21.77	21.46	21.65	0-3	3
	50	0	21.73	21.49	21.63		3

Table 9-22
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.26	24.39	0	0
	1	12	24.71	24.49	24.65		0
	1	24	24.48	24.26	24.42		0
	12	0	23.61	23.33	23.55	0-1	1
	12	6	23.55	23.37	23.59		1
	12	13	23.51	23.28	23.56		1
16QAM	25	0	23.57	23.30	23.59	0-1	1
	1	0	23.75	23.57	23.55		1
	1	12	23.80	23.59	23.80		1
	1	24	23.66	23.52	23.60	0-2	1
	12	0	22.57	22.36	22.53		2
	12	6	22.64	22.35	22.60		2
64QAM	12	13	22.59	22.33	22.48	0-2	2
	25	0	22.54	22.32	22.61		2
	1	0	22.78	22.48	22.69		0-2
	1	12	22.80	22.69	22.80	2	
	1	24	22.71	22.48	22.65	2	
	64QAM	12	0	21.68	21.44	21.64	0-3
12		6	21.74	21.50	21.68	3	
12		13	21.67	21.42	21.60	3	
25		0	21.69	21.44	21.62		3

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 42 of 90	

Table 9-23
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.56	24.34	24.52	0	0
	1	7	24.66	24.40	24.66		0
	1	14	24.51	24.28	24.53		0
	8	0	23.58	23.32	23.59	0-1	1
	8	4	23.60	23.37	23.60		1
	8	7	23.55	23.28	23.56		1
	15	0	23.61	23.32	23.57		1
16QAM	1	0	23.72	23.76	23.73	0-1	1
	1	7	23.80	23.75	23.80		1
	1	14	23.63	23.79	23.69		1
	8	0	22.57	22.41	22.57	0-2	2
	8	4	22.59	22.44	22.58		2
	8	7	22.55	22.42	22.55		2
	15	0	22.65	22.40	22.53		2
64QAM	1	0	22.79	22.54	22.61	0-2	2
	1	7	22.80	22.60	22.74		2
	1	14	22.72	22.44	22.61		2
	8	0	21.66	21.40	21.60	0-3	3
	8	4	21.68	21.46	21.61		3
	8	7	21.65	21.43	21.58		3
	15	0	21.61	21.36	21.54		3

Table 9-24
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.44	24.35	24.42	0	0
	1	2	24.56	24.41	24.56		0
	1	5	24.46	24.33	24.43		0
	3	0	24.71	24.39	24.59		0
	3	2	24.75	24.47	24.66		0
	3	3	24.65	24.40	24.64		0
	6	0	23.56	23.32	23.61	0-1	1
16QAM	1	0	23.62	23.16	23.64	0-1	1
	1	2	23.73	23.27	23.74		1
	1	5	23.65	23.18	23.68		1
	3	0	23.61	23.40	23.47		1
	3	2	23.65	23.39	23.52		1
	3	3	23.67	23.44	23.47		1
	6	0	22.65	22.51	22.64	0-2	2
64QAM	1	0	22.68	22.48	22.61	0-2	2
	1	2	22.79	22.57	22.70		2
	1	5	22.71	22.43	22.61		2
	3	0	22.67	22.46	22.59		2
	3	2	22.72	22.48	22.60		2
	3	3	22.69	22.48	22.57		2
	6	0	21.64	21.41	21.59	0-3	3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 43 of 90

9.4.6

LTE Band 25 (PCS)

Table 9-25
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.56	24.58	24.46	0	0
	1	50	24.75	24.80	24.79		0
	1	99	24.51	24.59	24.59		0
	50	0	23.77	23.80	23.79	0-1	1
	50	25	23.79	23.71	23.77		1
	50	50	23.70	23.75	23.74		1
	100	0	23.70	23.76	23.77		1
16QAM	1	0	23.60	23.80	23.74	0-1	1
	1	50	23.75	23.77	23.80		1
	1	99	23.74	23.71	23.65		1
	50	0	22.65	22.70	22.78	0-2	2
	50	25	22.58	22.75	22.78		2
	50	50	22.65	22.74	22.65		2
	100	0	22.65	22.75	22.72		2
64QAM	1	0	22.52	22.73	22.71	0-2	2
	1	50	22.80	22.40	22.80		2
	1	99	22.68	22.46	22.70		2
	50	0	21.77	21.80	21.80	0-3	3
	50	25	21.71	21.73	21.79		3
	50	50	21.69	21.77	21.68		3
	100	0	21.65	21.71	21.71		3

Table 9-26
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.40	24.47	24.61	0	0
	1	36	24.58	24.74	24.72		0
	1	74	24.44	24.48	24.60		0
	36	0	23.67	23.62	23.72	0-1	1
	36	18	23.75	23.73	23.71		1
	36	37	23.65	23.70	23.71		1
	75	0	23.67	23.67	23.72		1
16QAM	1	0	23.47	23.80	23.76	0-1	1
	1	36	23.63	23.78	23.77		1
	1	74	23.55	23.79	23.73		1
	36	0	22.53	22.59	22.63	0-2	2
	36	18	22.59	22.71	22.64		2
	36	37	22.55	22.66	22.66		2
	75	0	22.57	22.70	22.62		2
64QAM	1	0	22.50	22.63	22.68	0-2	2
	1	36	22.63	22.79	22.78		2
	1	74	22.51	22.64	22.61		2
	36	0	21.55	21.67	21.76	0-3	3
	36	18	21.62	21.71	21.74		3
	36	37	21.56	21.70	21.70		3
	75	0	21.54	21.65	21.68		3

FCC ID: ZNFX320PM			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset				Page 44 of 90

Table 9-27
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.41	24.53	24.56	0	0
	1	25	24.59	24.76	24.73		0
	1	49	24.47	24.61	24.58		0
	25	0	23.55	23.70	23.78	0-1	1
	25	12	23.62	23.72	23.75		1
	25	25	23.58	23.71	23.67		1
	50	0	23.59	23.71	23.74		1
16QAM	1	0	23.53	23.67	23.73	0-1	1
	1	25	23.63	23.80	23.80		1
	1	49	23.59	23.73	23.69		1
	25	0	22.49	22.68	22.75	0-2	2
	25	12	22.56	22.69	22.73		2
	25	25	22.51	22.67	22.64		2
	50	0	22.53	22.67	22.71		2
64QAM	1	0	22.55	22.69	22.71	0-2	2
	1	25	22.69	22.80	22.80		2
	1	49	22.60	22.74	22.66		2
	25	0	21.55	21.73	21.78	0-3	3
	25	12	21.62	21.75	21.78		3
	25	25	21.57	21.74	21.71		3
	50	0	21.59	21.72	21.78		3

Table 9-28
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.36	24.50	24.52	0	0
	1	12	24.64	24.75	24.77		0
	1	24	24.38	24.53	24.53		0
	12	0	23.48	23.61	23.73	0-1	1
	12	6	23.56	23.71	23.74		1
	12	13	23.54	23.62	23.60		1
	25	0	23.50	23.67	23.69		1
16QAM	1	0	23.53	23.66	23.63	0-1	1
	1	12	23.71	23.77	23.80		1
	1	24	23.52	23.66	23.62		1
	12	0	22.45	22.59	22.69	0-2	2
	12	6	22.51	22.69	22.70		2
	12	13	22.49	22.62	22.54		2
	25	0	22.45	22.62	22.63		2
64QAM	1	0	22.45	22.64	22.64	0-2	2
	1	12	22.76	22.80	22.79		2
	1	24	22.49	22.61	22.55		2
	12	0	21.49	21.65	21.76	0-3	3
	12	6	21.57	21.74	21.77		3
	12	13	21.53	21.65	21.64		3
	25	0	21.51	21.67	21.71		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 45 of 90

Table 9-29
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.43	24.59	24.61	0	0
	1	7	24.54	24.75	24.73		0
	1	14	24.46	24.61	24.60		0
	8	0	23.46	23.62	23.66	0-1	1
	8	4	23.51	23.69	23.70		1
	8	7	23.47	23.64	23.64		1
	15	0	23.52	23.67	23.71		1
16QAM	1	0	23.59	23.74	23.70	0-1	1
	1	7	23.67	23.80	23.79		1
	1	14	23.57	23.77	23.68		1
	8	0	22.49	22.66	22.67	0-2	2
	8	4	22.50	22.69	22.68		2
	8	7	22.46	22.70	22.61		2
	15	0	22.42	22.65	22.60		2
64QAM	1	0	22.57	22.72	22.73	0-2	2
	1	7	22.69	22.76	22.80		2
	1	14	22.54	22.76	22.66		2
	8	0	21.53	21.70	21.74	0-3	3
	8	4	21.58	21.78	21.75		3
	8	7	21.54	21.73	21.68		3
	15	0	21.51	21.71	21.70		3

Table 9-30
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.38	24.55	24.54	0	0
	1	2	24.51		24.66		0
	1	5	24.38	24.54	24.54		0
	3	0	24.48	24.65	24.66		0
	3	2	24.53	24.67	24.69		0
	3	3	24.48	24.65	24.68		0
	6	0	23.52	23.67	23.71	0-1	1
16QAM	1	0	23.56	23.72	23.63	0-1	1
	1	2	23.63	23.77	23.72		1
	1	5	23.53	23.69	23.61		1
	3	0	23.50	23.67	23.60		1
	3	2	23.52	23.69	23.63		1
	3	3	23.48	23.68	23.61		1
	6	0	22.54	22.72	22.69	0-2	2
64QAM	1	0	22.56	22.72	22.66	0-2	2
	1	2	22.63		22.74		2
	1	5	22.53	22.68	22.62		2
	3	0	22.57	22.70	22.65		2
	3	2	22.53	22.72	22.69		2
	3	3	22.55	22.75	22.65		2
	6	0	21.52	21.70	21.68	0-3	3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 46 of 90

9.4.7

LTE Band 41

Table 9-31
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.30	24.39	24.56	24.28	24.26	0	0
	1	50	24.40	24.72	24.74	24.58	24.33		0
	1	99	24.22	24.41	24.37	24.35	24.08		0
	50	0	23.14	23.58	23.66	23.40	23.37	0-1	1
	50	25	23.23	23.55	23.57	23.39	23.33		1
	50	50	23.35	23.50	23.52	23.36	23.19		1
	100	0	23.37	23.34	23.65	23.46	23.37		1
16QAM	1	0	23.40	23.53	23.66	23.38	23.39	0-1	1
	1	50	23.53	23.71	23.74	23.56	23.47		1
	1	99	23.30	23.54	23.48	23.44	23.22		1
	50	0	22.42	22.64	22.69	22.48	22.47	0-2	2
	50	25	22.45	22.61	22.62	22.45	22.38		2
	50	50	22.40	22.57	22.63	22.42	22.28		2
	100	0	22.47	22.62	22.69	22.51	22.40		2
64QAM	1	0	22.00	22.14	22.21	22.04	22.15	0-2	2
	1	50	22.12	22.33	22.38	22.23	22.36		2
	1	99	21.86	22.19	22.13	22.08	22.03		2
	50	0	21.46	21.70	21.77	21.53	21.46	0-3	3
	50	25	21.48	21.68	21.71	21.51	21.43		3
	50	50	21.45	21.66	21.67	21.49	21.32		3
	100	0	21.43	21.62	21.73	21.48	21.39		3

Table 9-32
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.27	24.34	24.55	24.29	24.13	0	0
	1	36	24.41	24.50	24.59	24.36	24.21		0
	1	74	24.27	24.45	24.48	24.16	23.93		0
	36	0	23.38	23.52	23.77	23.47	23.31	0-1	1
	36	18	23.44	23.55	23.77	23.48	23.31		1
	36	37	23.46	23.52	23.74	23.37	23.17		1
	75	0	23.34	23.42	23.60	23.34	23.22		1
16QAM	1	0	23.35	23.43	23.69	23.37	23.26	0-1	1
	1	36	23.52	23.56	23.70	23.38	23.33		1
	1	74	23.33	23.52	23.57	23.28	23.08		1
	36	0	22.39	22.49	22.74	22.42	22.29	0-2	2
	36	18	22.44	22.53	22.68	22.46	22.27		2
	36	37	22.44	22.53	22.66	22.37	22.18		2
	75	0	22.39	22.50	22.67	22.41	22.26		2
64QAM	1	0	21.91	22.01	22.29	21.99	21.91	0-2	2
	1	36	22.08	22.12	22.33	22.10	21.90		2
	1	74	21.96	22.11	22.21	21.89	21.70		2
	36	0	21.43	21.52	21.72	21.41	21.28	0-3	3
	36	18	21.45	21.54	21.71	21.43	21.23		3
	36	37	21.44	21.53	21.63	21.34	21.11		3
	75	0	21.44	21.57	21.73	21.40	21.26		3

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 47 of 90

Table 9-33
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	24.30	24.29	24.60	24.31	24.17	0	0	
	1	25	24.23	24.16	24.55	24.25	24.08		0-1	0
	1	49	24.28	24.36	24.51	24.31	24.02			0
	25	0	23.40	23.37	23.68	23.34	23.31	1		
	25	12	23.43	23.41	23.68	23.43	23.23	1		
	25	25	23.40	23.37	23.66	23.39	23.11	1		
	50	0	23.32	23.33	23.52	23.32	23.19	1		
16QAM	1	0	23.34	23.36	23.69	23.39	23.31	0-1	1	
	1	25	23.19	23.34	23.52	23.19	23.23		0-2	1
	1	49	23.37	23.43	23.62	23.44	23.12			1
	25	0	22.35	22.40	22.54	22.37	22.19	2		
	25	12	22.30	22.41	22.60	22.35	22.16	2		
	25	25	22.32	22.34	22.62	22.30	22.07	2		
	50	0	22.40	22.41	22.65	22.44	22.31	2		
64QAM	1	0	21.96	21.93	22.32	21.95	21.93	0-2	2	
	1	25	21.90	21.93	22.29	21.79	21.79		0-3	2
	1	49	21.93	21.98	22.20	21.94	21.77			2
	25	0	21.41	21.50	21.76	21.40	21.32	3		
	25	12	21.49	21.49	21.73	21.46	21.27	3		
	25	25	21.47	21.45	21.74	21.47	21.17	3		
	50	0	21.38	21.48	21.71	21.44	21.29	3		

Table 9-34
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.19	24.20	24.44	24.10	24.04	0	0
	1	12	24.35	24.46	24.66	24.44	24.24		0
	1	24	24.21	24.22	24.45	24.09	23.93		0
	12	0	23.32	23.35	23.61	23.31	23.14	0-1	1
	12	6	23.42	23.45	23.72	23.38	23.26		1
	12	13	23.37	23.33	23.65	23.29	23.07		1
16QAM	25	0	23.35	23.33	23.61	23.16	23.14	0-1	1
	1	0	23.32	23.28	23.55	23.22	23.17		1
	1	12	23.51	23.56	23.79	23.43	23.37		1
	1	24	23.27	23.29	23.56	23.18	23.09	0-2	1
	12	0	22.34	22.39	22.65	22.31	22.22		2
	12	6	22.41	22.32	22.73	22.35	22.20		2
64QAM	12	13	22.40	22.29	22.67	22.29	22.16	0-2	2
	25	0	22.25	22.25	22.53	22.21	22.13		2
	1	0	21.90	21.93	22.15	21.84	21.83	0-2	2
	1	12	22.14	22.20	22.46	22.20	22.05		2
	1	24	21.90	21.91	22.19	21.83	21.65	0-3	2
	12	0	21.35	21.35	21.65	21.32	21.21		3
12	6	21.46	21.49	21.70	21.44	21.22	3		
	12	13	21.38	21.34	21.62	21.29	21.17		3
	25	0	21.39	21.40	21.67	21.30	21.19		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 48 of 90	

9.4.8

LTE Band 41 Power Class 2

Table 9-35
LTE Band 41 PC2 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	27.16	27.32	27.40	27.15	27.10	0	0
	1	50	27.55	27.51	27.55	27.35	27.18		0
	1	99	27.08	27.34	27.22	27.21	26.93		0
	50	0	26.12	26.47	26.58	26.35	26.25	0-1	1
	50	25	26.25	26.46	26.48	26.35	26.20		1
	50	50	26.21	26.44	26.47	26.32	26.04		1
	100	0	26.29	26.34	26.57	26.37	26.20		1
16QAM	1	0	26.39	26.54	26.64	26.36	26.40	0-1	1
	1	50	26.52	26.75	26.76	26.57	26.48		1
	1	99	26.33	26.55	26.47	26.44	26.22		1
	50	0	25.24	25.50	25.57	25.41	25.30	0-2	2
	50	25	25.29	25.47	25.58	25.41	25.24		2
	50	50	25.25	25.45	25.48	25.39	25.12		2
	100	0	25.32	25.51	25.61	25.43	25.23		2
64QAM	1	0	25.09	25.27	25.39	25.15	25.21	0-2	2
	1	50	25.29	25.49	25.56	25.35	25.46		2
	1	99	25.01	25.29	25.26	25.22	25.35		2
	50	0	24.35	24.57	24.62	24.36	24.29	0-3	3
	50	25	24.39	24.57	24.58	24.35	24.24		3
	50	50	24.35	24.53	24.53	24.33	24.13		3
	100	0	24.33	24.59	24.63	24.36	24.27		3

Table 9-36
LTE Band 41 PC2 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	27.31	27.38	27.35	27.22	27.45	0	0
	1	36	27.39	27.42	27.40	27.35	27.48		0
	1	74	27.38	27.35	27.20	27.30	27.50		0
	36	0	26.70	26.55	26.60	26.55	26.76	0-1	1
	36	18	26.71	26.55	26.55	26.54	26.75		1
	36	37	26.68	26.51	26.51	26.50	26.70		1
	75	0	26.59	26.59	26.50	26.59	26.68		1
16QAM	1	0	26.55	26.50	26.70	26.49	26.65	0-1	1
	1	36	26.62	26.55	26.68	26.45	26.69		1
	1	74	26.68	26.60	26.65	26.51	26.60		1
	36	0	25.65	25.50	25.72	25.51	25.62	0-2	2
	36	18	25.67	25.52	25.78	25.59	25.68		2
	36	37	25.66	25.56	25.75	25.55	25.69		2
	75	0	25.60	25.61	25.68	25.48	25.70		2
64QAM	1	0	25.49	25.49	25.45	25.51	25.66	0-2	2
	1	36	25.55	25.48	25.61	25.60	25.63		2
	1	74	25.62	25.39	25.58	25.66	25.63		2
	36	0	24.68	24.78	24.80	24.71	24.65	0-3	3
	36	18	24.62	24.72	24.79	24.70	24.66		3
	36	37	24.60	24.75	24.78	24.70	24.69		3
	75	0	24.65	24.80	24.79	24.75	24.72		3

FCC ID: ZNFX320PM			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 49 of 90		

Table 9-37
LTE Band 41 PC2 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	27.49	27.30	27.35	27.35	27.55	0	0
	1	25	27.45	27.35	27.33	27.30	27.49		0
	1	49	27.48	27.48	27.41	27.35	27.50		0
	25	0	26.45	26.51	26.68	26.55	26.70	0-1	1
	25	12	26.50	26.50	26.68	26.59	26.68		1
	25	25	26.48	26.48	26.62	26.51	26.69		1
	50	0	26.52	26.45	26.60	26.50	26.65		1
16QAM	1	0	26.53	26.39	26.70	26.59	26.60	0-1	1
	1	25	26.64	26.45	26.71	26.55	26.65		1
	1	49	26.60	26.50	26.75	26.50	26.67		1
	25	0	25.45	25.59	25.39	25.58	25.66	0-2	2
	25	12	25.48	25.61	25.42	25.60	25.60		2
	25	25	25.41	25.60	25.49	25.61	25.62		2
64QAM	50	0	25.43	25.65	25.47	25.65	25.63	0-2	2
	1	0	25.40	25.49	25.50	25.70	25.69		2
	1	25	25.45	25.55	25.55	25.72	25.72	0-2	2
	1	49	25.50	25.60	25.61	25.68	25.70		0-3
	25	0	24.52	24.45	24.40	24.79	24.80	3	
	25	12	24.58	24.50	24.48	24.75	24.71	3	
	25	25	24.59	24.51	24.45	24.70	24.72	3	
50	0	24.60	24.52	24.50	24.78	24.75	3		

Table 9-38
LTE Band 41 PC2 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	27.30	27.45	27.50	27.47	27.40	0	0
	1	12	27.33	27.48	27.49	27.45	27.33		0
	1	24	27.28	27.40	27.43	27.40	27.35		0
	12	0	26.63	26.55	26.60	26.72	26.40	0-1	1
	12	6	26.60	26.61	26.62	26.70	26.42		1
	12	13	26.64	26.49	26.68	26.68	26.38		1
16QAM	25	0	26.65	26.55	26.58	26.55	26.55	0-1	1
	1	0	26.73	26.70	26.51	26.50	26.61		1
	1	12	26.65	26.71	26.66	26.58	26.59		1
	1	24	26.59	26.66	26.60	26.50	26.51	0-2	1
	12	0	25.57	25.40	25.61	25.72	25.55		2
	12	6	25.49	25.48	25.62	25.73	25.60		2
64QAM	12	13	25.48	25.49	25.60	25.70	25.61	0-2	2
	25	0	25.50	25.50	25.66	25.68	25.63		2
	1	0	25.46	25.55	25.67	25.62	25.49	0-2	2
	1	12	25.48	25.61	25.64	25.63	25.55		2
	1	24	25.49	25.68	25.70	25.65	25.51	0-3	2
	12	0	24.30	24.35	24.79	24.80	24.50		3
12	6	24.35	24.40	24.80	24.71	24.52	3		
	12	13	24.38	24.49	24.80	24.76	24.42		3
	25	0	24.41	24.55	24.75	24.70	24.48		3

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 50 of 90

9.5 WLAN Conducted Powers

Table 9-39
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.91	14.27	14.66
2417	2		14.87	14.68
2437	6	15.59	14.83	14.68
2462	11	15.89	15.32	15.22

Note: The bolded data rates and channel above were tested for SAR.

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.




Figure 9-4
Power Measurement Setup

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 51 of 90

9.6 Bluetooth Conducted Powers


Table 9-40
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	10.23	10.532
2441	1.0	39	10.34	10.824
2480	1.0	78	9.76	9.472
2402	2.0	0	7.28	5.341
2441	2.0	39	7.00	5.016
2480	2.0	78	6.63	4.602
2402	3.0	0	7.36	5.447
2441	3.0	39	7.08	5.111
2480	3.0	78	6.71	4.687

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 52 of 90	

Figure 9-5
Bluetooth Transmission Plot



Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.880ms}{3.750ms} * 100\% = 76.8\%$$




Figure 9-6
Power Measurement Setup

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 53 of 90

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
7/10/2019	750H	21.3	680	0.858	41.233	0.888	42.305	-3.38%	-2.53%
			695	0.863	41.192	0.889	42.227	-2.92%	-2.45%
			700	0.864	41.176	0.889	42.201	-2.81%	-2.43%
			710	0.867	41.149	0.890	42.149	-2.58%	-2.37%
			720	0.871	41.126	0.891	42.097	-2.24%	-2.31%
			725	0.873	41.114	0.891	42.071	-2.02%	-2.27%
			740	0.878	41.075	0.893	41.994	-1.68%	-2.19%
			755	0.883	41.035	0.894	41.916	-1.23%	-2.10%
			770	0.888	40.993	0.895	41.838	-0.78%	-2.02%
			785	0.893	40.948	0.896	41.760	-0.33%	-1.94%
6/27/2019	835H	21.9	820	0.918	41.771	0.899	41.578	2.11%	0.46%
			835	0.923	41.734	0.900	41.500	2.56%	0.56%
			850	0.928	41.704	0.916	41.500	1.31%	0.49%
7/8/2019	835H	20.0	820	0.885	40.118	0.899	41.578	-1.56%	-3.51%
			835	0.890	40.098	0.900	41.500	-1.11%	-3.38%
			850	0.896	40.083	0.916	41.500	-2.18%	-3.41%
7/8/2019	1750H	21.0	1710	1.329	40.120	1.348	40.142	-1.41%	-0.05%
			1750	1.353	40.052	1.371	40.079	-1.31%	-0.07%
			1790	1.378	39.983	1.394	40.016	-1.15%	-0.08%
7/3/2019	1900H	21.1	1850	1.427	40.800	1.400	40.000	1.93%	2.00%
			1880	1.447	40.752	1.400	40.000	3.36%	1.88%
			1910	1.467	40.722	1.400	40.000	4.79%	1.81%
7/8/2019	1900H	21.9	1850	1.425	41.031	1.400	40.000	1.79%	2.58%
			1880	1.444	40.980	1.400	40.000	3.14%	2.45%
			1910	1.463	40.934	1.400	40.000	4.50%	2.33%
7/1/2019	2450H	21.3	2400	1.771	39.484	1.756	39.289	0.85%	0.50%
			2450	1.808	39.401	1.800	39.200	0.44%	0.51%
			2500	1.847	39.328	1.855	39.136	-0.43%	0.49%
			2550	1.886	39.251	1.909	39.073	-1.20%	0.46%
			2600	1.926	39.163	1.964	39.009	-1.93%	0.39%
			2650	1.967	39.082	2.018	38.945	-2.53%	0.38%
			2700	2.007	39.002	2.073	38.882	-3.18%	0.31%
7/8/2019	750B	23.8	680	0.919	57.533	0.958	55.804	-4.07%	3.10%
			695	0.924	57.502	0.959	55.745	-3.65%	3.15%
			700	0.925	57.490	0.959	55.726	-3.55%	3.17%
			710	0.929	57.470	0.960	55.687	-3.23%	3.20%
			720	0.933	57.446	0.961	55.648	-2.91%	3.23%
			725	0.934	57.435	0.961	55.629	-2.81%	3.25%
			740	0.939	57.402	0.963	55.570	-2.49%	3.30%
			755	0.945	57.369	0.964	55.512	-1.97%	3.35%
			770	0.950	57.337	0.965	55.453	-1.55%	3.40%
			785	0.955	57.300	0.966	55.395	-1.14%	3.44%
			800	0.960	57.269	0.967	55.336	-0.72%	3.49%
			820	0.965	55.272	0.969	55.258	-0.41%	0.03%
			835	0.971	55.240	0.970	55.200	0.10%	0.07%
			850	0.977	55.186	0.988	55.154	-1.11%	0.06%
			820	0.966	55.077	0.969	55.258	-0.31%	-0.33%
7/14/2019	835B	20.1	835	0.973	55.054	0.970	55.200	0.31%	-0.26%
			850	0.977	55.024	0.988	55.154	-1.11%	-0.24%
			1710	1.460	52.571	1.463	53.537	-0.21%	-1.80%
7/1/2019	1750B	21.5	1750	1.505	52.424	1.488	53.432	1.14%	-1.89%
			1790	1.551	52.287	1.514	53.326	2.44%	-1.95%
			1710	1.402	53.538	1.463	53.537	-4.17%	0.00%
7/15/2019	1750B	21.4	1750	1.429	53.479	1.488	53.432	-3.97%	0.09%
			1790	1.456	53.437	1.514	53.326	-3.83%	0.21%
			1850	1.526	52.767	1.520	53.300	0.39%	-1.00%
7/8/2019	1900B	22.6	1880	1.561	52.673	1.520	53.300	2.70%	-1.18%
			1910	1.594	52.587	1.520	53.300	4.87%	-1.34%
			2300	1.863	52.555	1.809	52.900	2.99%	-0.65%
7/15/2019	2300B	22.9	2310	1.875	52.522	1.816	52.887	3.25%	-0.69%
			2320	1.886	52.492	1.826	52.873	3.29%	-0.72%
			2450	2.035	51.648	1.950	52.700	4.36%	-2.00%
			2500	2.094	51.512	2.021	52.636	3.61%	-2.14%
			2550	2.158	51.371	2.092	52.573	3.15%	-2.29%
			2600	2.218	51.237	2.163	52.509	2.54%	-2.42%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset			Page 54 of 90

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
E	750	HEAD	07/10/2019	22.5	21.3	0.200	1003	3589	1.540	8.280	7.700	-7.00%
H	835	HEAD	06/27/2019	23.4	21.9	0.200	4d132	7406	1.960	9.590	9.800	2.19%
H	835	HEAD	07/08/2019	20.5	20.0	0.200	4d132	7406	1.900	9.590	9.500	-0.94%
E	1750	HEAD	07/08/2019	21.4	21.0	0.100	1008	3589	3.730	36.200	37.300	3.04%
G	1900	HEAD	07/03/2019	22.2	21.1	0.100	5d149	7409	4.080	39.300	40.800	3.82%
G	1900	HEAD	07/08/2019	22.0	21.9	0.100	5d149	7409	3.990	39.300	39.900	1.53%
E	2450	HEAD	07/01/2019	22.1	21.3	0.100	797	3589	5.320	52.700	53.200	0.95%
E	2600	HEAD	07/01/2019	22.1	21.3	0.100	1126	3589	5.750	54.500	57.500	5.50%
D	750	BODY	07/08/2019	22.8	22.1	0.200	1003	3914	1.730	8.580	8.650	0.82%
O	835	BODY	07/09/2019	20.3	20.0	0.200	4d047	7538	2.040	9.470	10.200	7.71%
O	835	BODY	07/14/2019	20.3	20.1	0.200	4d047	7538	2.080	9.470	10.400	9.82%
I	1750	BODY	07/01/2019	22.7	21.5	0.100	1150	7357	3.970	36.600	39.700	8.47%
G	1750	BODY	07/15/2019	21.9	21.4	0.100	1150	7409	3.810	36.600	38.100	4.10%
J	1900	BODY	07/08/2019	20.1	22.6	0.100	5d080	7488	4.160	39.200	41.600	6.12%
J	1900	BODY	07/10/2019	22.9	22.6	0.100	5d080	7488	4.090	39.200	40.900	4.34%
K	2450	BODY	07/10/2019	22.7	22.5	0.100	719	7417	5.140	50.100	51.400	2.59%
K	2600	BODY	07/10/2019	22.7	22.5	0.100	1004	7417	5.340	54.800	53.400	-2.55%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 55 of 90

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.6	33.60	0.01	Right	Cheek	00870	1	1:8.3	0.263	1.000	0.263	
836.60	190	GSM 850	GSM	33.6	33.60	-0.18	Right	Tilt	00870	1	1:8.3	0.168	1.000	0.168	
836.60	190	GSM 850	GSM	33.6	33.60	0.06	Left	Cheek	00870	1	1:8.3	0.266	1.000	0.266	A1
836.60	190	GSM 850	GSM	33.6	33.60	0.05	Left	Tilt	00870	1	1:8.3	0.165	1.000	0.165	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.02	Right	Cheek	00870	2	1:4.15	0.258	1.079	0.278	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.02	Right	Tilt	00870	2	1:4.15	0.167	1.079	0.180	
836.60	190	GSM 850	GPRS	31.0	30.67	0.00	Left	Cheek	00870	2	1:4.15	0.245	1.079	0.264	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.13	Left	Tilt	00870	2	1:4.15	0.159	1.079	0.172	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.8	30.34	0.06	Right	Cheek	00869	1	1:8.3	0.147	1.112	0.163	
1880.00	661	GSM 1900	GSM	30.8	30.34	-0.07	Right	Tilt	00869	1	1:8.3	0.097	1.112	0.108	
1880.00	661	GSM 1900	GSM	30.8	30.34	0.16	Left	Cheek	00869	1	1:8.3	0.272	1.112	0.302	
1880.00	661	GSM 1900	GSM	30.8	30.34	0.00	Left	Tilt	00869	1	1:8.3	0.132	1.112	0.147	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.12	Right	Cheek	00869	2	1:4.15	0.159	1.233	0.196	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.06	Right	Tilt	00869	2	1:4.15	0.109	1.233	0.134	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.17	Left	Cheek	00869	2	1:4.15	0.292	1.233	0.360	A2
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.05	Left	Tilt	00869	2	1:4.15	0.153	1.233	0.189	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFX320PM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset			Page 56 of 90

Table 11-3
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.05	Right	Cheek	00870	1:1	0.353	1.019	0.360	
836.60	4183	UMTS 850	RMC	25.3	25.22	0.01	Right	Tilt	00870	1:1	0.195	1.019	0.199	
836.60	4183	UMTS 850	RMC	25.3	25.22	0.00	Left	Cheek	00870	1:1	0.356	1.019	0.363	A3
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.09	Left	Tilt	00870	1:1	0.211	1.019	0.215	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-4
UMTS 1750 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.02	Right	Cheek	00870	1:1	0.276	1.045	0.288	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.04	Right	Tilt	00870	1:1	0.380	1.045	0.397	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.00	Left	Cheek	00870	1:1	0.552	1.045	0.577	A4
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.07	Left	Tilt	00870	1:1	0.245	1.045	0.256	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.13	Right	Cheek	00869	1:1	0.332	1.023	0.340	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	-0.13	Right	Tilt	00869	1:1	0.210	1.023	0.215	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.10	Left	Cheek	00869	1:1	0.579	1.023	0.592	A5
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.12	Left	Tilt	00869	1:1	0.253	1.023	0.259	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 57 of 90

Table 11-6
CDMA BC10 (§90S) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.3	25.04	0.04	Right	Cheek	00870	1:1	0.340	1.062	0.361	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.3	25.04	0.08	Right	Tilt	00870	1:1	0.194	1.062	0.206	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.3	25.04	-0.05	Left	Cheek	00870	1:1	0.322	1.062	0.342	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.3	25.04	-0.07	Left	Tilt	00870	1:1	0.210	1.062	0.223	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.3	25.03	0.13	Right	Cheek	00870	1:1	0.372	1.064	0.396	A6
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.3	25.03	-0.01	Right	Tilt	00870	1:1	0.199	1.064	0.212	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.3	25.03	0.18	Left	Cheek	00870	1:1	0.338	1.064	0.360	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.3	25.03	0.01	Left	Tilt	00870	1:1	0.202	1.064	0.215	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-7
CDMA BC0 (§22H) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.3	25.18	0.06	Right	Cheek	00870	1:1	0.336	1.028	0.345	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.3	25.18	-0.15	Right	Tilt	00870	1:1	0.187	1.028	0.192	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.3	25.18	0.06	Left	Cheek	00870	1:1	0.326	1.028	0.335	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.3	25.18	0.04	Left	Tilt	00870	1:1	0.183	1.028	0.188	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.3	25.15	0.00	Right	Cheek	00870	1:1	0.354	1.035	0.366	A7
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.3	25.15	0.01	Right	Tilt	00870	1:1	0.179	1.035	0.185	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.3	25.15	-0.02	Left	Cheek	00870	1:1	0.331	1.035	0.343	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.3	25.15	0.07	Left	Tilt	00870	1:1	0.182	1.035	0.188	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 58 of 90

Table 11-8
PCS CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.8	24.72	-0.07	Right	Cheek	00869	1:1	0.357	1.019	0.364	
1880.00	600	PCS CDMA	RC3 / SO55	24.8	24.72	0.02	Right	Tilt	00869	1:1	0.221	1.019	0.225	
1880.00	600	PCS CDMA	RC3 / SO55	24.8	24.72	0.11	Left	Cheek	00869	1:1	0.550	1.019	0.560	
1880.00	600	PCS CDMA	RC3 / SO55	24.8	24.72	0.05	Left	Tilt	00869	1:1	0.260	1.019	0.265	
1880.00	600	PCS CDMA	EVDO Rev. A	24.8	24.60	-0.08	Right	Cheek	00869	1:1	0.284	1.047	0.297	
1880.00	600	PCS CDMA	EVDO Rev. A	24.8	24.60	0.03	Right	Tilt	00869	1:1	0.190	1.047	0.199	
1880.00	600	PCS CDMA	EVDO Rev. A	24.8	24.60	0.03	Left	Cheek	00869	1:1	0.572	1.047	0.599	A8
1880.00	600	PCS CDMA	EVDO Rev. A	24.8	24.60	-0.12	Left	Tilt	00869	1:1	0.245	1.047	0.257	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-9
LTE Band 71 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	0.02	0	Right	Cheek	QPSK	1	50	00865	1:1	0.166	1.081	0.179	A9
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.08	1	Right	Cheek	QPSK	50	25	00865	1:1	0.134	1.069	0.143	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.08	0	Right	Tilt	QPSK	1	50	00865	1:1	0.089	1.081	0.096	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.06	1	Right	Tilt	QPSK	50	25	00865	1:1	0.071	1.069	0.076	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	0.09	0	Left	Cheek	QPSK	1	50	00865	1:1	0.165	1.081	0.178	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.08	1	Left	Cheek	QPSK	50	25	00865	1:1	0.123	1.069	0.131	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	0.07	0	Left	Tilt	QPSK	1	50	00865	1:1	0.082	1.081	0.089	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.13	1	Left	Tilt	QPSK	50	25	00865	1:1	0.061	1.069	0.065	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 59 of 90

Table 11-10
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	-0.01	0	Right	Cheek	QPSK	1	25	00865	1:1	0.255	1.062	0.271	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.04	1	Right	Cheek	QPSK	25	0	00865	1:1	0.209	1.019	0.213	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	0.12	0	Right	Tilt	QPSK	1	25	00865	1:1	0.120	1.062	0.127	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	-0.12	1	Right	Tilt	QPSK	25	0	00865	1:1	0.104	1.019	0.106	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	-0.01	0	Left	Cheek	QPSK	1	25	00865	1:1	0.262	1.062	0.278	A10
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.05	1	Left	Cheek	QPSK	25	0	00865	1:1	0.202	1.019	0.206	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	0.06	0	Left	Tilt	QPSK	1	25	00865	1:1	0.144	1.062	0.153	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.04	1	Left	Tilt	QPSK	25	0	00865	1:1	0.107	1.019	0.109	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.05	0	Right	Cheek	QPSK	1	25	00865	1:1	0.419	1.062	0.445	A11
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.06	1	Right	Cheek	QPSK	25	0	00865	1:1	0.292	1.035	0.302	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	-0.03	0	Right	Tilt	QPSK	1	25	00865	1:1	0.222	1.062	0.236	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.04	1	Right	Tilt	QPSK	25	0	00865	1:1	0.146	1.035	0.151	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	-0.05	0	Left	Cheek	QPSK	1	25	00865	1:1	0.340	1.062	0.361	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.02	1	Left	Cheek	QPSK	25	0	00865	1:1	0.259	1.035	0.268	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.08	0	Left	Tilt	QPSK	1	25	00865	1:1	0.202	1.062	0.215	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.07	1	Left	Tilt	QPSK	25	0	00865	1:1	0.160	1.035	0.166	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-12
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	-0.01	0	Right	Cheek	QPSK	1	36	00864	1:1	0.403	1.079	0.435	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	-0.07	1	Right	Cheek	QPSK	36	18	00864	1:1	0.338	1.021	0.345	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.00	0	Right	Tilt	QPSK	1	36	00864	1:1	0.217	1.079	0.234	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.07	1	Right	Tilt	QPSK	36	18	00864	1:1	0.182	1.021	0.186	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.01	0	Left	Cheek	QPSK	1	36	00864	1:1	0.408	1.079	0.440	A12
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.04	1	Left	Cheek	QPSK	36	18	00864	1:1	0.330	1.021	0.337	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.02	0	Left	Tilt	QPSK	1	36	00864	1:1	0.255	1.079	0.275	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.04	1	Left	Tilt	QPSK	36	18	00864	1:1	0.208	1.021	0.212	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 60 of 90

Table 11-13
LTE Band 66 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	0.10	0	Right	Cheek	QPSK	1	50	00865	1:1	0.295	1.000	0.295	A13
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.06	1	Right	Cheek	QPSK	50	25	00865	1:1	0.235	1.000	0.235	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	0.07	0	Right	Tilt	QPSK	1	50	00865	1:1	0.343	1.000	0.343	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.15	1	Right	Tilt	QPSK	50	25	00865	1:1	0.256	1.000	0.256	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	0.01	0	Left	Cheek	QPSK	1	50	00865	1:1	0.738	1.000	0.738	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.8	24.68	0.00	0	Left	Cheek	QPSK	1	50	00865	1:1	0.713	1.028	0.733	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.8	24.79	0.06	0	Left	Cheek	QPSK	1	50	00865	1:1	0.782	1.002	0.784	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.05	1	Left	Cheek	QPSK	50	25	00865	1:1	0.577	1.000	0.577	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	0.09	0	Left	Tilt	QPSK	1	50	00865	1:1	0.268	1.000	0.268	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.04	1	Left	Tilt	QPSK	50	25	00865	1:1	0.209	1.000	0.209	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Head										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

Table 11-14
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	0.02	0	Right	Cheek	QPSK	1	50	00866	1:1	0.376	1.000	0.376	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.01	1	Right	Cheek	QPSK	50	0	00866	1:1	0.273	1.000	0.273	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.02	0	Right	Tilt	QPSK	1	50	00866	1:1	0.245	1.000	0.245	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.12	1	Right	Tilt	QPSK	50	0	00866	1:1	0.176	1.000	0.176	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.8	24.75	0.08	0	Left	Cheek	QPSK	1	50	00866	1:1	0.632	1.012	0.640	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.01	0	Left	Cheek	QPSK	1	50	00866	1:1	0.637	1.000	0.637	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.8	24.79	-0.10	0	Left	Cheek	QPSK	1	50	00866	1:1	0.671	1.002	0.672	A14
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.06	1	Left	Cheek	QPSK	50	0	00866	1:1	0.510	1.000	0.510	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.02	0	Left	Tilt	QPSK	1	50	00866	1:1	0.276	1.000	0.276	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.11	1	Left	Tilt	QPSK	50	0	00866	1:1	0.199	1.000	0.199	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Head										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 61 of 90

Table 11-15
LTE Band 41 Head SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.00	0	Right	Cheek	QPSK	1	50	00865	1:1.58	0.143	1.014	0.145	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.04	1	Right	Cheek	QPSK	50	0	00865	1:1.58	0.118	1.033	0.122	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.17	0	Right	Tilt	QPSK	1	50	00865	1:1.58	0.125	1.014	0.127	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.13	1	Right	Tilt	QPSK	50	0	00865	1:1.58	0.088	1.033	0.091	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.07	0	Left	Cheek	QPSK	1	50	00865	1:1.58	0.193	1.014	0.196	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.08	1	Left	Cheek	QPSK	50	0	00865	1:1.58	0.149	1.033	0.154	
Power Class 2	2593.00	40620	Mid	LTE Band 41	20	27.8	27.55	0.02	0	Left	Cheek	QPSK	1	50	00865	1:2.31	0.276	1.059	0.292	A15
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.16	0	Left	Tilt	QPSK	1	50	00865	1:1.58	0.116	1.014	0.118	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.16	1	Left	Tilt	QPSK	50	0	00865	1:1.58	0.096	1.033	0.099	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-16
DTS Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	16.0	15.91	0.04	Right	Cheek	01175	1	99.0	0.620	-	1.021	1.010	-	
2412	1	802.11b	DSSS	22	16.0	15.91	-0.03	Right	Tilt	01175	1	99.0	0.552	-	1.021	1.010	-	
2412	1	802.11b	DSSS	22	16.0	15.91	0.17	Left	Cheek	01175	1	99.0	1.210	0.775	1.021	1.010	0.799	
2437	6	802.11b	DSSS	22	16.0	15.59	0.09	Left	Cheek	01175	1	99.0	1.476	0.876	1.099	1.010	0.972	A16
2462	11	802.11b	DSSS	22	16.0	15.89	0.05	Left	Cheek	01175	1	99.0	1.073	0.676	1.026	1.010	0.701	
2412	1	802.11b	DSSS	22	16.0	15.91	-0.14	Left	Tilt	01175	1	99.0	0.880	0.621	1.021	1.010	0.640	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-17
DSS Head SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441.00	39	Bluetooth	FHSS	10.5	10.34	0.14	Right	Cheek	01175	1	76.8	0.061	1.038	1.302	0.082	
2441.00	39	Bluetooth	FHSS	10.5	10.34	0.12	Right	Tilt	01175	1	76.8	0.057	1.038	1.302	0.077	
2441.00	39	Bluetooth	FHSS	10.5	10.34	-0.08	Left	Cheek	01175	1	76.8	0.102	1.038	1.302	0.138	A17
2441.00	39	Bluetooth	FHSS	10.5	10.34	-0.10	Left	Tilt	01175	1	76.8	0.086	1.038	1.302	0.116	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 62 of 90

11.2 Standalone Body-Worn SAR Data

Table 11-18
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.6	33.60	-0.01	10 mm	00870	1	1:8.3	back	0.354	1.000	0.354	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.07	10 mm	00870	2	1:4.15	back	0.382	1.079	0.412	A18
1880.00	661	GSM 1900	GSM	30.8	30.34	-0.04	10 mm	00869	1	1:8.3	back	0.291	1.112	0.324	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.02	10 mm	00869	2	1:4.15	back	0.314	1.233	0.387	A19
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.04	10 mm	00870	N/A	1:1	back	0.491	1.019	0.500	A21
1712.40	1312	UMTS 1750	RMC	24.8	24.63	0.01	10 mm	00870	N/A	1:1	back	0.981	1.040	1.020	A23
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.00	10 mm	00870	N/A	1:1	back	0.972	1.045	1.016	
1752.60	1513	UMTS 1750	RMC	24.8	24.80	0.01	10 mm	00870	N/A	1:1	back	0.952	1.000	0.952	
1852.40	9262	UMTS 1900	RMC	24.8	24.78	0.03	10 mm	00869	N/A	1:1	back	0.709	1.005	0.713	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.00	10 mm	00869	N/A	1:1	back	0.718	1.023	0.735	A24
1907.60	9538	UMTS 1900	RMC	24.8	24.80	0.03	10 mm	00869	N/A	1:1	back	0.710	1.000	0.710	
820.10	564	CDMA BC10 (\$90S)	TDSO / SO32	25.3	25.14	0.01	10 mm	00870	N/A	1:1	back	0.582	1.038	0.604	A26
836.52	384	CDMA BC0 (\$22H)	TDSO / SO32	25.3	25.29	-0.02	10 mm	00869	N/A	1:1	back	0.509	1.002	0.510	A28
1851.25	25	PCS CDMA	TDSO / SO32	24.8	24.59	-0.12	10 mm	00869	N/A	1:1	back	0.708	1.050	0.743	
1880.00	600	PCS CDMA	TDSO / SO32	24.8	24.73	0.00	10 mm	00869	N/A	1:1	back	0.748	1.016	0.760	A30
1908.75	1175	PCS CDMA	TDSO / SO32	24.8	24.80	0.01	10 mm	00869	N/A	1:1	back	0.701	1.000	0.701	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 63 of 90

Table 11-19
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.04	0	00864	QPSK	1	50	10 mm	back	1:1	0.356	1.081	0.385	A32
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	-0.02	1	00864	QPSK	50	25	10 mm	back	1:1	0.281	1.069	0.300	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	0.00	0	00864	QPSK	1	25	10 mm	back	1:1	0.406	1.062	0.431	A33
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.01	1	00864	QPSK	25	0	10 mm	back	1:1	0.321	1.019	0.327	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	-0.01	0	00864	QPSK	1	25	10 mm	back	1:1	0.412	1.062	0.438	A35
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.04	1	00864	QPSK	25	0	10 mm	back	1:1	0.332	1.035	0.344	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	-0.03	0	00864	QPSK	1	36	10 mm	back	1:1	0.592	1.079	0.639	A37
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.00	1	00864	QPSK	36	18	10 mm	back	1:1	0.483	1.021	0.493	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.14	0	00864	QPSK	1	50	10 mm	back	1:1	1.070	1.000	1.070	A39
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.8	24.68	0.01	0	00864	QPSK	1	50	10 mm	back	1:1	0.979	1.028	1.006	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.8	24.79	-0.12	0	00864	QPSK	1	50	10 mm	back	1:1	0.916	1.002	0.918	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.00	1	00864	QPSK	50	25	10 mm	back	1:1	0.819	1.000	0.819	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.8	23.77	0.00	1	00864	QPSK	50	0	10 mm	back	1:1	0.780	1.007	0.785	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.8	23.79	0.01	1	00864	QPSK	50	0	10 mm	back	1:1	0.765	1.002	0.767	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.78	-0.02	1	00864	QPSK	100	0	10 mm	back	1:1	0.803	1.005	0.807	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.01	0	00864	QPSK	1	50	10 mm	back	1:1	1.060	1.000	1.060	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.8	24.75	0.06	0	00865	QPSK	1	50	10 mm	back	1:1	0.733	1.012	0.742	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.05	0	00865	QPSK	1	50	10 mm	back	1:1	0.759	1.000	0.759	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.8	24.79	-0.01	0	00865	QPSK	1	50	10 mm	back	1:1	0.762	1.002	0.764	A40
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.02	1	00865	QPSK	50	0	10 mm	back	1:1	0.583	1.000	0.583	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak									Body										
Uncontrolled Exposure/General Population									1.6 W/kg (mW/g)										
									averaged over 1 gram										

Note: Blue entry indicates variability measurement.

Table 11-20
LTE Band 41 Body-Worn SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	-0.04	0	00865	QPSK	1	50	10 mm	back	1:1.58	0.521	1.014	0.528	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	-0.02	1	00865	QPSK	50	0	10 mm	back	1:1.58	0.405	1.033	0.418	
Power Class 2	2593.00	40620	Mid	LTE Band 41	20	27.8	27.55	-0.01	0	00865	QPSK	1	50	10 mm	back	1:2.31	0.706	1.059	0.748	A41
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body											
Spatial Peak									1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population									averaged over 1 gram											

Table 11-21
DTS Body-Worn SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	16.0	15.91	-0.01	10 mm	01175	1	back	99.0	0.221	0.136	1.021	1.010	0.140	A43
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 64 of 90

11.3 Standalone Hotspot SAR Data

Table 11-22
GPRS/UMTS/CDMA Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.07	10 mm	00870	2	1:4.15	back	0.382	1.079	0.412	A18
836.60	190	GSM 850	GPRS	31.0	30.67	-0.02	10 mm	00870	2	1:4.15	front	0.366	1.079	0.395	
836.60	190	GSM 850	GPRS	31.0	30.67	0.02	10 mm	00870	2	1:4.15	bottom	0.176	1.079	0.190	
836.60	190	GSM 850	GPRS	31.0	30.67	-0.07	10 mm	00870	2	1:4.15	right	0.377	1.079	0.407	
836.60	190	GSM 850	GPRS	31.0	30.67	0.00	10 mm	00870	2	1:4.15	left	0.236	1.079	0.255	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.02	10 mm	00869	2	1:4.15	back	0.314	1.233	0.387	
1880.00	661	GSM 1900	GPRS	28.0	27.09	0.01	10 mm	00869	2	1:4.15	front	0.242	1.233	0.298	
1880.00	661	GSM 1900	GPRS	28.0	27.09	-0.07	10 mm	00869	2	1:4.15	bottom	0.244	1.233	0.301	
1880.00	661	GSM 1900	GPRS	28.0	27.09	-0.08	10 mm	00869	2	1:4.15	left	0.337	1.233	0.416	A20
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.04	10 mm	00870	N/A	1:1	back	0.491	1.019	0.500	
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.01	10 mm	00870	N/A	1:1	front	0.484	1.019	0.493	
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.02	10 mm	00870	N/A	1:1	bottom	0.222	1.019	0.226	
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.01	10 mm	00870	N/A	1:1	right	0.499	1.019	0.508	A22
836.60	4183	UMTS 850	RMC	25.3	25.22	-0.01	10 mm	00870	N/A	1:1	left	0.307	1.019	0.313	
1712.40	1312	UMTS 1750	RMC	24.8	24.63	0.01	10 mm	00870	N/A	1:1	back	0.981	1.040	1.020	A23
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.00	10 mm	00870	N/A	1:1	back	0.972	1.045	1.016	
1752.60	1513	UMTS 1750	RMC	24.8	24.80	0.01	10 mm	00870	N/A	1:1	back	0.952	1.000	0.952	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.11	10 mm	00870	N/A	1:1	front	0.764	1.045	0.798	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.01	10 mm	00870	N/A	1:1	bottom	0.612	1.045	0.640	
1712.40	1312	UMTS 1750	RMC	24.8	24.63	0.00	10 mm	00870	N/A	1:1	left	0.726	1.040	0.755	
1732.40	1412	UMTS 1750	RMC	24.8	24.61	0.00	10 mm	00870	N/A	1:1	left	0.772	1.045	0.807	
1752.60	1513	UMTS 1750	RMC	24.8	24.80	0.00	10 mm	00870	N/A	1:1	left	0.848	1.000	0.848	
1852.40	9262	UMTS 1900	RMC	24.8	24.78	0.03	10 mm	00869	N/A	1:1	back	0.709	1.005	0.713	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.00	10 mm	00869	N/A	1:1	back	0.718	1.023	0.735	
1907.60	9538	UMTS 1900	RMC	24.8	24.80	0.03	10 mm	00869	N/A	1:1	back	0.710	1.000	0.710	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.10	10 mm	00869	N/A	1:1	front	0.555	1.023	0.568	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	-0.03	10 mm	00869	N/A	1:1	bottom	0.535	1.023	0.547	
1852.40	9262	UMTS 1900	RMC	24.8	24.78	-0.08	10 mm	00869	N/A	1:1	left	0.713	1.005	0.717	
1880.00	9400	UMTS 1900	RMC	24.8	24.70	0.05	10 mm	00869	N/A	1:1	left	0.762	1.023	0.780	A25
1907.60	9538	UMTS 1900	RMC	24.8	24.80	0.01	10 mm	00869	N/A	1:1	left	0.757	1.000	0.757	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.3	25.25	0.02	10 mm	00870	N/A	1:1	back	0.580	1.012	0.587	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.3	25.25	-0.01	10 mm	00870	N/A	1:1	front	0.548	1.012	0.555	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.3	25.25	-0.05	10 mm	00870	N/A	1:1	bottom	0.246	1.012	0.249	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.3	25.25	0.09	10 mm	00870	N/A	1:1	right	0.690	1.012	0.698	A27
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.3	25.25	0.05	10 mm	00870	N/A	1:1	left	0.420	1.012	0.425	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.3	24.87	-0.01	10 mm	00869	N/A	1:1	back	0.498	1.104	0.550	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.3	24.87	-0.02	10 mm	00869	N/A	1:1	front	0.458	1.104	0.506	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.3	24.87	0.02	10 mm	00869	N/A	1:1	bottom	0.209	1.104	0.231	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.3	24.87	-0.06	10 mm	00869	N/A	1:1	right	0.507	1.104	0.560	A29
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.3	24.87	0.02	10 mm	00869	N/A	1:1	left	0.267	1.104	0.295	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.8	24.59	0.00	10 mm	00869	N/A	1:1	back	0.549	1.050	0.576	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.8	24.59	0.07	10 mm	00869	N/A	1:1	front	0.486	1.050	0.510	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.8	24.59	0.07	10 mm	00869	N/A	1:1	bottom	0.484	1.050	0.508	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.8	24.51	-0.13	10 mm	00869	N/A	1:1	left	0.627	1.069	0.670	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.8	24.59	-0.06	10 mm	00869	N/A	1:1	left	0.664	1.050	0.697	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.8	24.63	-0.01	10 mm	00869	N/A	1:1	left	0.717	1.040	0.746	A31
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFX320PM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 65 of 90	

Table 11-23
LTE Band 71 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.04	0	00864	QPSK	1	50	10 mm	back	1:1	0.356	1.081	0.385	A32
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	-0.02	1	00864	QPSK	50	25	10 mm	back	1:1	0.281	1.069	0.300	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.04	0	00864	QPSK	1	50	10 mm	front	1:1	0.341	1.081	0.369	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.03	1	00864	QPSK	50	25	10 mm	front	1:1	0.273	1.069	0.292	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.04	0	00864	QPSK	1	50	10 mm	bottom	1:1	0.162	1.081	0.175	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.01	1	00864	QPSK	50	25	10 mm	bottom	1:1	0.135	1.069	0.144	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.01	0	00864	QPSK	1	50	10 mm	right	1:1	0.202	1.081	0.218	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.01	1	00864	QPSK	50	25	10 mm	right	1:1	0.156	1.069	0.167	
680.50	133297	Mid	LTE Band 71	20	25.3	24.96	-0.01	0	00864	QPSK	1	50	10 mm	left	1:1	0.177	1.081	0.191	
680.50	133297	Mid	LTE Band 71	20	24.3	24.01	0.00	1	00864	QPSK	50	25	10 mm	left	1:1	0.139	1.069	0.149	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-24
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	0.00	0	00864	QPSK	1	25	10 mm	back	1:1	0.406	1.062	0.431	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.01	1	00864	QPSK	25	0	10 mm	back	1:1	0.321	1.019	0.327	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	-0.13	0	00864	QPSK	1	25	10 mm	front	1:1	0.408	1.062	0.433	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	-0.10	1	00864	QPSK	25	0	10 mm	front	1:1	0.337	1.019	0.343	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	0.00	0	00864	QPSK	1	25	10 mm	bottom	1:1	0.204	1.062	0.217	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.00	1	00864	QPSK	25	0	10 mm	bottom	1:1	0.148	1.019	0.151	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	-0.13	0	00864	QPSK	1	25	10 mm	right	1:1	0.433	1.062	0.460	A34
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	-0.06	1	00864	QPSK	25	0	10 mm	right	1:1	0.332	1.019	0.338	
707.50	23095	Mid	LTE Band 12	10	25.3	25.04	-0.01	0	00864	QPSK	1	25	10 mm	left	1:1	0.307	1.062	0.326	
707.50	23095	Mid	LTE Band 12	10	24.3	24.22	0.03	1	00864	QPSK	25	0	10 mm	left	1:1	0.240	1.019	0.245	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 66 of 90	

Table 11-25
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	-0.01	0	00864	QPSK	1	25	10 mm	back	1:1	0.412	1.062	0.438	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.04	1	00864	QPSK	25	0	10 mm	back	1:1	0.332	1.035	0.344	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.02	0	00864	QPSK	1	25	10 mm	front	1:1	0.439	1.062	0.466	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.05	1	00864	QPSK	25	0	10 mm	front	1:1	0.346	1.035	0.358	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.13	0	00864	QPSK	1	25	10 mm	bottom	1:1	0.218	1.062	0.232	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	-0.02	1	00864	QPSK	25	0	10 mm	bottom	1:1	0.159	1.035	0.165	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.02	0	00864	QPSK	1	25	10 mm	right	1:1	0.457	1.062	0.485	A36
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.03	1	00864	QPSK	25	0	10 mm	right	1:1	0.363	1.035	0.376	
782.00	23230	Mid	LTE Band 13	10	25.3	25.04	0.02	0	00864	QPSK	1	25	10 mm	left	1:1	0.324	1.062	0.344	
782.00	23230	Mid	LTE Band 13	10	24.3	24.15	0.05	1	00864	QPSK	25	0	10 mm	left	1:1	0.252	1.035	0.261	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-26
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	-0.03	0	00864	QPSK	1	36	10 mm	back	1:1	0.592	1.079	0.639	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.00	1	00864	QPSK	36	18	10 mm	back	1:1	0.483	1.021	0.493	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	-0.01	0	00864	QPSK	1	36	10 mm	front	1:1	0.561	1.079	0.605	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.00	1	00864	QPSK	36	18	10 mm	front	1:1	0.439	1.021	0.448	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	-0.02	0	00864	QPSK	1	36	10 mm	bottom	1:1	0.292	1.079	0.315	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.01	1	00864	QPSK	36	18	10 mm	bottom	1:1	0.233	1.021	0.238	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.00	0	00864	QPSK	1	36	10 mm	right	1:1	0.810	1.079	0.874	A38
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	0.01	1	00864	QPSK	36	18	10 mm	right	1:1	0.607	1.021	0.620	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.11	0.01	1	00864	QPSK	75	0	10 mm	right	1:1	0.585	1.045	0.611	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.00	0	00864	QPSK	1	36	10 mm	left	1:1	0.436	1.079	0.470	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.3	24.21	-0.01	1	00864	QPSK	36	18	10 mm	left	1:1	0.334	1.021	0.341	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.3	24.97	0.00	0	00864	QPSK	1	36	10 mm	right	1:1	0.724	1.079	0.781	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry indicates variability measurement.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 67 of 90	

Table 11-27
LTE Band 66 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.14	0	00864	QPSK	1	50	10 mm	back	1:1	1.070	1.000	1.070	A39
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.8	24.68	0.01	0	00864	QPSK	1	50	10 mm	back	1:1	0.979	1.028	1.006	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.8	24.79	-0.12	0	00864	QPSK	1	50	10 mm	back	1:1	0.916	1.002	0.918	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.00	1	00864	QPSK	50	25	10 mm	back	1:1	0.819	1.000	0.819	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.8	23.77	0.00	1	00864	QPSK	50	0	10 mm	back	1:1	0.780	1.007	0.785	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.8	23.79	0.01	1	00864	QPSK	50	0	10 mm	back	1:1	0.765	1.002	0.767	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.78	-0.02	1	00864	QPSK	100	0	10 mm	back	1:1	0.803	1.005	0.807	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.08	0	00864	QPSK	1	50	10 mm	front	1:1	0.802	1.000	0.802	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.8	24.68	0.01	0	00864	QPSK	1	50	10 mm	front	1:1	0.807	1.028	0.830	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.8	24.79	0.00	0	00864	QPSK	1	50	10 mm	front	1:1	0.794	1.002	0.796	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.00	1	00864	QPSK	50	25	10 mm	front	1:1	0.612	1.000	0.612	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.78	0.00	1	00864	QPSK	100	0	10 mm	front	1:1	0.624	1.005	0.627	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.03	0	00864	QPSK	1	50	10 mm	bottom	1:1	0.636	1.000	0.636	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	-0.02	1	00864	QPSK	50	25	10 mm	bottom	1:1	0.504	1.000	0.504	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	0.00	0	00864	QPSK	1	50	10 mm	left	1:1	0.745	1.000	0.745	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.8	23.80	0.03	1	00864	QPSK	50	25	10 mm	left	1:1	0.589	1.000	0.589	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.8	24.80	-0.01	0	00864	QPSK	1	50	10 mm	back	1:1	1.060	1.000	1.060	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g)											
								averaged over 1 gram											

Note: Blue entry indicates variability measurement.

Table 11-28
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.8	24.75	0.06	0	00865	QPSK	1	50	10 mm	back	1:1	0.733	1.012	0.742	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.05	0	00865	QPSK	1	50	10 mm	back	1:1	0.759	1.000	0.759	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.8	24.79	-0.01	0	00865	QPSK	1	50	10 mm	back	1:1	0.762	1.002	0.764	A40
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.02	1	00865	QPSK	50	0	10 mm	back	1:1	0.583	1.000	0.583	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.01	0	00865	QPSK	1	50	10 mm	front	1:1	0.590	1.000	0.590	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.02	1	00865	QPSK	50	0	10 mm	front	1:1	0.453	1.000	0.453	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	-0.17	0	00865	QPSK	1	50	10 mm	bottom	1:1	0.591	1.000	0.591	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	-0.05	1	00865	QPSK	50	0	10 mm	bottom	1:1	0.461	1.000	0.461	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.8	24.80	0.06	0	00865	QPSK	1	50	10 mm	left	1:1	0.740	1.000	0.740	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.8	23.80	0.00	1	00865	QPSK	50	0	10 mm	left	1:1	0.571	1.000	0.571	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 68 of 90	

Table 11-29
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	-0.04	0	00865	QPSK	1	50	10 mm	back	1:1.58	0.521	1.014	0.528	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	-0.02	1	00865	QPSK	50	0	10 mm	back	1:1.58	0.405	1.033	0.418	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.06	0	00865	QPSK	1	50	10 mm	front	1:1.58	0.525	1.014	0.532	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.00	1	00865	QPSK	50	0	10 mm	front	1:1.58	0.417	1.033	0.431	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.8	24.40	-0.14	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.916	1.096	1.004	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.8	24.72	-0.14	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.945	1.019	0.963	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	-0.03	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.977	1.014	0.991	
Power Class 3	2636.50	41055	Mid-High	LTE Band 41	20	24.8	24.58	-0.13	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.832	1.052	0.875	
Power Class 3	2680.00	41490	High	LTE Band 41	20	24.8	24.33	-0.13	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.786	1.114	0.876	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.8	23.35	-0.13	1	00865	QPSK	50	50	10 mm	bottom	1:1.58	0.703	1.109	0.780	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.8	23.58	-0.13	1	00865	QPSK	50	0	10 mm	bottom	1:1.58	0.712	1.052	0.749	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	-0.14	1	00865	QPSK	50	0	10 mm	bottom	1:1.58	0.729	1.033	0.753	
Power Class 3	2636.50	41055	Mid-High	LTE Band 41	20	23.8	23.40	-0.13	1	00865	QPSK	50	0	10 mm	bottom	1:1.58	0.668	1.096	0.732	
Power Class 3	2680.00	41490	High	LTE Band 41	20	23.8	23.37	-0.13	1	00865	QPSK	50	0	10 mm	bottom	1:1.58	0.635	1.104	0.701	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.65	-0.12	1	00865	QPSK	100	0	10 mm	bottom	1:1.58	0.701	1.035	0.726	
Power Class 2	2506.00	39750	Low	LTE Band 41	20	27.8	27.55	-0.14	0	00865	QPSK	1	50	10 mm	bottom	1:2.31	1.220	1.059	1.292	A42
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.12	0	00865	QPSK	1	50	10 mm	right	1:1.58	0.179	1.014	0.182	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.09	1	00865	QPSK	50	0	10 mm	right	1:1.58	0.144	1.033	0.149	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	0.03	0	00865	QPSK	1	50	10 mm	left	1:1.58	0.199	1.014	0.202	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	23.8	23.66	0.01	1	00865	QPSK	50	0	10 mm	left	1:1.58	0.150	1.033	0.155	
Power Class 2	2506.00	39750	Low	LTE Band 41	20	27.8	27.55	0.09	0	00865	QPSK	1	50	10 mm	bottom	1:2.31	1.200	1.059	1.271	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.8	24.74	-0.10	0	00865	QPSK	1	50	10 mm	bottom	1:1.58	0.945	1.014	0.958	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																				
Spatial Peak									Body											
Uncontrolled Exposure/General Population									1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry indicates variability measurement.

Table 11-30
WLAN Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.												W/kg	(W/kg)				
2412	1	802.11b	DSSS	22	16.0	15.91	-0.01	10 mm	01175	1	back	99.0	0.221	0.136	1.021	1.010	0.140	A43
2412	1	802.11b	DSSS	22	16.0	15.91	0.14	10 mm	01175	1	front	99.0	0.197	-	1.021	1.010	-	
2412	1	802.11b	DSSS	22	16.0	15.91	0.12	10 mm	01175	1	top	99.0	0.192	-	1.021	1.010	-	
2412	1	802.11b	DSSS	22	16.0	15.91	0.14	10 mm	01175	1	right	99.0	0.092	-	1.021	1.010	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body									
Spatial Peak									1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population									averaged over 1 gram									

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 69 of 90

11.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 70 of 90

- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
- CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1X Advanced was not more than 0.25 dB higher than the maximum powers for 1X.

UMTS Notes:

- UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

- LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
- MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
- A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
- Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
- TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
- Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not > 0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
- This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per FCC Guidance, all SAR tests were performed using Power Class 3. SAR with power class 2 at the available duty factor was additionally performed for the power class 3 configuration with the highest SAR configuration for each exposure conditions. Please see Section 14 for linearity results.

WLAN Notes:

- For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 71 of 90

2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.3 for more information.
3. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.6 for the time domain plot and calculation for the duty factor of the device.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 72 of 90

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	10.50	10	0.231

Note: Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 73 of 90

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.278	0.972	1.250
	GSM/GPRS 1900	0.360	0.972	1.332
	UMTS 850	0.363	0.972	1.335
	UMTS 1750	0.577	0.972	1.549
	UMTS 1900	0.592	0.972	1.564
	CDMA/EVDO BC10 (§90S)	0.396	0.972	1.368
	CDMA/EVDO BC0 (§22H)	0.366	0.972	1.338
	PCS CDMA/EVDO	0.599	0.972	1.571
	LTE Band 71	0.179	0.972	1.151
	LTE Band 12	0.278	0.972	1.250
	LTE Band 13	0.445	0.972	1.417
	LTE Band 26 (Cell)	0.440	0.972	1.412
	LTE Band 66 (AWS)	0.784	0.972	See Table Below
	LTE Band 25 (PCS)	0.672	0.972	See Table Below
	LTE Band 41	0.292	0.972	1.264

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Head SAR	Right Cheek	0.295	0.972*	1.267	N/A
	Right Tilt	0.343	0.972*	1.315	N/A
	Left Cheek	0.784	0.972	See Note 1	0.03
	Left Tilt	0.268	0.640	0.908	N/A
Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Head SAR	Right Cheek	0.376	0.972*	1.348	N/A
	Right Tilt	0.245	0.972*	1.217	N/A
	Left Cheek	0.672	0.972	See Note 1	0.03
	Left Tilt	0.276	0.640	0.916	N/A

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 74 of 90

Table 12-3
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.278	0.138	0.416
	GSM/GPRS 1900	0.360	0.138	0.498
	UMTS 850	0.363	0.138	0.501
	UMTS 1750	0.577	0.138	0.715
	UMTS 1900	0.592	0.138	0.730
	CDMA/EVDO BC10 (§90S)	0.396	0.138	0.534
	CDMA/EVDO BC0 (§22H)	0.366	0.138	0.504
	PCS CDMA/EVDO	0.599	0.138	0.737
	LTE Band 71	0.179	0.138	0.317
	LTE Band 12	0.278	0.138	0.416
	LTE Band 13	0.445	0.138	0.583
	LTE Band 26 (Cell)	0.440	0.138	0.578
	LTE Band 66 (AWS)	0.784	0.138	0.922
	LTE Band 25 (PCS)	0.672	0.138	0.810
	LTE Band 41	0.292	0.138	0.430

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.6 for detailed SPLS ratio analysis..

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 75 of 90	

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.412	0.140	0.552
	GSM/GPRS 1900	0.387	0.140	0.527
	UMTS 850	0.500	0.140	0.640
	UMTS 1750	1.020	0.140	1.160
	UMTS 1900	0.735	0.140	0.875
	CDMA BC10 (§90S)	0.604	0.140	0.744
	CDMA BC0 (§22H)	0.510	0.140	0.650
	PCS CDMA	0.760	0.140	0.900
	LTE Band 71	0.385	0.140	0.525
	LTE Band 12	0.431	0.140	0.571
	LTE Band 13	0.438	0.140	0.578
	LTE Band 26 (Cell)	0.639	0.140	0.779
	LTE Band 66 (AWS)	1.070	0.140	1.210
	LTE Band 25 (PCS)	0.764	0.140	0.904
	LTE Band 41	0.748	0.140	0.888

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 76 of 90	

Table 12-5
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.412	0.231	0.643
	GSM/GPRS 1900	0.387	0.231	0.618
	UMTS 850	0.500	0.231	0.731
	UMTS 1750	1.020	0.231	1.251
	UMTS 1900	0.735	0.231	0.966
	CDMA BC10 (§90S)	0.604	0.231	0.835
	CDMA BC0 (§22H)	0.510	0.231	0.741
	PCS CDMA	0.760	0.231	0.991
	LTE Band 71	0.385	0.231	0.616
	LTE Band 12	0.431	0.231	0.662
	LTE Band 13	0.438	0.231	0.669
	LTE Band 26 (Cell)	0.639	0.231	0.870
	LTE Band 66 (AWS)	1.070	0.231	1.301
	LTE Band 25 (PCS)	0.764	0.231	0.995
	LTE Band 41	0.748	0.231	0.979

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 77 of 90

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.412	0.140	0.552
	GPRS 1900	0.416	0.140	0.556
	UMTS 850	0.508	0.140	0.648
	UMTS 1750	1.020	0.140	1.160
	UMTS 1900	0.780	0.140	0.920
	EVDO BC10 (§90S)	0.698	0.140	0.838
	EVDO BC0 (§22H)	0.560	0.140	0.700
	PCS EVDO	0.746	0.140	0.886
	LTE Band 71	0.385	0.140	0.525
	LTE Band 12	0.460	0.140	0.600
	LTE Band 13	0.485	0.140	0.625
	LTE Band 26 (Cell)	0.874	0.140	1.014
	LTE Band 66 (AWS)	1.070	0.140	1.210
	LTE Band 25 (PCS)	0.764	0.140	0.904
	LTE Band 41	1.292	0.140	1.432

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 78 of 90	

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.412	0.231	0.643
	GPRS 1900	0.416	0.231	0.647
	UMTS 850	0.508	0.231	0.739
	UMTS 1750	1.020	0.231	1.251
	UMTS 1900	0.780	0.231	1.011
	EVDO BC10 (§90S)	0.698	0.231	0.929
	EVDO BC0 (§22H)	0.560	0.231	0.791
	PCS EVDO	0.746	0.231	0.977
	LTE Band 71	0.385	0.231	0.616
	LTE Band 12	0.460	0.231	0.691
	LTE Band 13	0.485	0.231	0.716
	LTE Band 26 (Cell)	0.874	0.231	1.105
	LTE Band 66 (AWS)	1.070	0.231	1.301
	LTE Band 25 (PCS)	0.764	0.231	0.995
	LTE Band 41	1.292	0.231	1.523

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 79 of 90

12.6 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is

≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2} \text{ (Head)}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.6.1 Head SAR SPLSR Evaluation and Analysis

Table 12-8
Peak SAR Locations for Head SAR – Left Cheek


Mode/Band	x (mm)	y (mm)	z (mm)
2.4 GHz WLAN	21.04	325.24	-174.03
LTE Band 66 (AWS)	56.51	253.47	-174.11
LTE Band 25 (PCS)	53.45	251.66	-175.86

Table 12-9
Head SAR – Left Cheek to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
LTE Band 66 (AWS)	2.4 GHz WLAN	0.784	0.972	1.756	80.06	0.03	1
LTE Band 25 (PCS)	2.4 GHz WLAN	0.672	0.972	1.644	80.42	0.03	2

FCC ID: ZNFX320PM		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset			Page 80 of 90

Table 12-10
Head SAR – Left Cheek to Peak Location Separation Ratio Plots



12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis for all the worst-case simultaneous transmission conditions is sufficient to determine that simultaneous transmission cases will not exceed SAR limits and therefore no measured volumetric simultaneous SAR is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 81 of 90

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
850	831.50	26865	LTE Band 26 (Cell), 15 MHz Bandwidth	QPSK, 1 RB, 36 RB Offset	right	10 mm	0.810	0.724	1.12	N/A	N/A	N/A	N/A
1750	1720.00	132072	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	back	10 mm	1.070	1.060	1.01	N/A	N/A	N/A	N/A
2450	2506.00	39750	LTE Band 41 Power Class 2, 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	bottom	10 mm	1.220	1.200	1.02	N/A	N/A	N/A	N/A
2600	2593.00	40620	LTE Band 41, 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	bottom	10 mm	0.977	0.945	1.03	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram						

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 82 of 90

14 ADDITIONAL TESTING PER FCC GUIDANCE

14.1 LTE Band 41 Power Class 2 and Power Class 3 Linearity

This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per May 2017 TCB Workshop Notes based on the device behavior, all SAR tests were performed using Power Class 3. SAR with Power Class 2 at the highest power and available duty factor was additionally performed for the Power Class 3 configuration with the highest SAR for each exposure condition. The linearity between the Power Class 2 and Power Class 3 SAR results and the respective frame averaged powers was calculated to determine that the results were linear. Per May 2017 TCB Workshop, no additional SAR measurements were required since the linearity between power classes was < 10% and all reported SAR values were < 1.4 W/kg for 1g and < 3.5 W/kg for 10g.

LTE Band 41 SAR testing with power class 2 at the highest power and available duty factor was additionally performed for the power class 3 configuration with the highest SAR for each exposure condition.

Table 14-1
LTE Band 41 Head Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.8	27.8
Measured Output Power (dBm)	24.74	27.55
Measured SAR (W/kg)	0.193	0.276
Measured Power (mW)	297.85	568.85
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	188.54	246.31
% deviation from expected linearity		9.46%




Figure 14-1
LTE Band 41 Head Linearity

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 83 of 90

Table 14-2
LTE Band 41 Body-Worn Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.8	27.8
Measured Output Power (dBm)	24.74	27.55
Measured SAR (W/kg)	0.521	0.706
Measured Power (mW)	297.85	568.85
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	188.54	246.31
% deviation from expected linearity		3.72%




Figure 14-2
LTE Band 41 Body-Worn Linearity

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 84 of 90

Table 14-3
LTE Band 41 Hotspot Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.8	27.8
Measured Output Power (dBm)	24.4	27.55
Measured SAR (W/kg)	0.916	1.2
Measured Power (mW)	275.42	568.85
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	174.34	246.31
% deviation from expected linearity		-7.27%




Figure 14-3
LTE Band 41 Hotspot Linearity

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 85 of 90

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	7/30/2018	Annual	7/30/2019	MY4000670
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/30/2018	Annual	8/30/2019	MY40003841
Agilent	8753ES	Network Analyzer	3/19/2019	Annual	3/19/2020	MY40001472
Agilent	E4438C	ESG Vector Signal Generator	5/22/2019	Annual	5/22/2020	MY45091346
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	12/18/2018	Annual	12/18/2019	GB42230325
Agilent	E5515C	Wireless Communications Test Set	2/28/2018	Biennial	2/28/2020	GB41450275
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Agilent	N5182A	MXG Vector Signal Generator	11/28/2018	Annual	11/28/2019	MY47420603
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	UY46470561
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Amplifier Research	150A100C	DC Amplifier	CBT	N/A	CBT	348812
Anritsu	MA24106A	USB Power Sensor	7/17/2018	Annual	7/17/2019	1827527
Anritsu	MA24106A	USB Power Sensor	7/17/2018	Annual	7/17/2019	1827528
Anritsu	MA2411B	Pulse Power Sensor	10/30/2018	Annual	10/30/2019	1126066
Anritsu	MA2411B	Pulse Power Sensor	10/30/2018	Annual	10/30/2019	1207470
Anritsu	ML2495A	Power Meter	10/21/2018	Annual	10/21/2019	941001
Anritsu	ML2495A	Power Meter	11/20/2018	Annual	11/20/2019	1039008
Anritsu	MT8000A	Radio Communication Test Station	11/14/2018	Annual	11/14/2019	6261914237
Anritsu	MT8820C	Radio Communication Analyzer	3/29/2019	Annual	3/29/2020	6201300731
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Control Company	4040	Therm./ Clock/ Humidity Monitor	1/8/2019	Annual	1/8/2020	160473909
Control Company	4352	Ultra Long Stem Thermometer	2/28/2018	Biennial	2/28/2020	170330160
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	7/2/2019	Annual	7/2/2020	MY53401181
Keysight Technologies	AT/N6705B	DC Power Supply	CBT	N/A	CBT	MY53001315
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	4/19/2019	Annual	4/19/2020	11401010036
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6°CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	11/1/2017	Biennial	11/1/2019	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMW500	Radio Communication tester	8/3/2018	Annual	8/3/2019	140144
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	10/30/2018	Annual	10/30/2019	164948
Seekonk	NC-100	Torque Wrench	11/1/2017	Biennial	11/1/2019	N/A
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/11/2018	Annual	9/11/2019	1091
SPEAG	D750V3	750 MHz SAR Dipole	1/15/2018	Biennial	1/15/2020	1003
SPEAG	D835V2	835 MHz SAR Dipole	1/22/2019	Annual	1/22/2020	4d132
SPEAG	D1765V2	1765 MHz SAR Dipole	5/23/2018	Biennial	5/23/2020	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Annual	10/23/2019	5d149
SPEAG	D2300V2	2300 MHz SAR Dipole	8/13/2018	Annual	8/13/2019	1073
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Biennial	9/11/2019	797
SPEAG	D2600V2	2600 MHz SAR Dipole	8/13/2018	Annual	8/13/2019	1126
SPEAG	D835V2	835 MHz SAR Dipole	3/13/2019	Annual	3/13/2020	4d047
SPEAG	D1750V2	1750 MHz SAR Dipole	10/22/2018	Annual	10/22/2019	1150
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Annual	10/23/2019	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/17/2017	Biennial	8/17/2019	719
SPEAG	D2600V2	2600 MHz SAR Dipole	4/11/2018	Biennial	4/11/2020	1004
SPEAG	EX3DV4	SAR Probe	1/25/2019	Annual	1/25/2020	3589
SPEAG	EX3DV4	SAR Probe	5/16/2019	Annual	5/16/2020	7406
SPEAG	EX3DV4	SAR Probe	6/19/2019	Annual	6/19/2020	7409
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	3914
SPEAG	EX3DV4	SAR Probe	5/16/2019	Annual	5/16/2020	7538
SPEAG	EX3DV4	SAR Probe	4/24/2019	Annual	4/24/2020	7357
SPEAG	EX3DV4	SAR Probe	1/24/2019	Annual	1/24/2020	7488
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	7417
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/22/2018	Annual	8/22/2019	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/8/2019	Annual	5/8/2020	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/20/2019	Annual	6/20/2020	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/14/2019	Annual	2/14/2020	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/8/2019	Annual	5/8/2020	728
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/18/2019	Annual	4/18/2020	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2019	Annual	1/15/2020	1530
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/13/2019	Annual	2/13/2020	665

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFX320PM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset		Page 86 of 90

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 87 of 90

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: ZNFX320PM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 88 of 90	

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 89 of 90

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFX320PM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260111-01-R1.ZNF	Test Dates: 06/27/19 - 07/15/19	DUT Type: Portable Handset	Page 90 of 90

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.096$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GSM 850, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.38 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.342 W/kg

SAR(1 g) = 0.266 W/kg



0 dB = 0.318 W/kg = -4.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, _GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.447 \text{ S/m}$; $\epsilon_r = 40.752$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1880 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Left Head, Cheek, Mid.ch, 2 Tx slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.79 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.444 W/kg

SAR(1 g) = 0.292 W/kg



0 dB = 0.386 W/kg = -4.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.096$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Left Head, Cheek, Mid.ch


Area Scan (8x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.45 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.447 W/kg

SAR(1 g) = 0.356 W/kg



0 dB = 0.416 W/kg = -3.81 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.342 \text{ S/m}$; $\epsilon_r = 40.082$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1732.4 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.12 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.842 W/kg

SAR(1 g) = 0.552 W/kg



0 dB = 0.743 W/kg = -1.29 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.447 \text{ S/m}$; $\epsilon_r = 40.752$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.84 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.839 W/kg

SAR(1 g) = 0.579 W/kg



0 dB = 0.740 W/kg = -1.31 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, Cellular CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 820.1$ MHz; $\sigma = 0.885$ S/m; $\epsilon_r = 40.118$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 820.1 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rev. A, Rule Part 90S, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.99 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.471 W/kg

SAR(1 g) = 0.372 W/kg



0 dB = 0.436 W/kg = -3.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.096$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.52 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rev. A, Rule Part 22H, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.49 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.354 W/kg



0 dB = 0.420 W/kg = -3.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.444 \text{ S/m}$; $\epsilon_r = 40.98$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1880 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO Rev A, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.88 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.885 W/kg

SAR(1 g) = 0.572 W/kg



0 dB = 0.775 W/kg = -1.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.858 \text{ S/m}$; $\epsilon_r = 41.232$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 680.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 71, Right Head, Cheek, Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.70 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.206 W/kg

SAR(1 g) = 0.166 W/kg



0 dB = 0.190 W/kg = -7.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.866 \text{ S/m}$; $\epsilon_r = 41.156$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 707.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 12, Left Head, Cheek, Mid.ch, QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.33 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.320 W/kg

SAR(1 g) = 0.262 W/kg



0 dB = 0.302 W/kg = -5.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.892 \text{ S/m}$; $\epsilon_r = 40.957$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 782 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 13, Right Head, Cheek, Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.89 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.523 W/kg

SAR(1 g) = 0.419 W/kg



0 dB = 0.492 W/kg = -3.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.922 \text{ S/m}$; $\epsilon_r = 41.743$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 6-27-2019; Ambient Temp: 23.4°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 831.5 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: SAM 30 with CRP v5.0 right; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 26 (Cell.), Left Head, Cheek, Mid.ch, 15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.15 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.516 W/kg

SAR(1 g) = 0.408 W/kg



0 dB = 0.478 W/kg = -3.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.365 \text{ S/m}$; $\epsilon_r = 40.017$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1770 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Left Head, Cheek, High.ch, 20 MHz Bandwidth, QPSK, 1 RB,
50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.21 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.782 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00866

Communication System: UID 0, LTE Band 25 (PCS), Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.464 \text{ S/m}$; $\epsilon_r = 40.727$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1905 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.50 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.671 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2593 MHz; Duty Cycle: 1:2.31

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 1.92 \text{ S/m}$; $\epsilon_r = 39.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.25, 6.25, 6.25) @ 2593 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 41 PC2, Left Head, Cheek, Mid.ch, QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.72 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.496 W/kg

SAR(1 g) = 0.276 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 01175

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.798 \text{ S/m}$; $\epsilon_r = 39.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2437 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head, Cheek, Ch 6, 1 Mbps


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.71 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.91 W/kg

SAR(1 g) = 0.876 W/kg



0 dB = 1.42 W/kg = 1.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 01175

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.302

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.801 \text{ S/m}$; $\epsilon_r = 39.416$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2441 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth, Left Head, Cheek, Ch 39, 1 Mbps


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.217 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.233 W/kg

SAR(1 g) = 0.102 W/kg



0 dB = 0.180 W/kg = -7.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.051$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 836.6 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.91 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.528 W/kg

SAR(1 g) = 0.382 W/kg



0 dB = 0.470 W/kg = -3.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 51.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.09 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.624 W/kg

SAR(1 g) = 0.314 W/kg



0 dB = 0.506 W/kg = -2.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 51.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Left Edge, Mid.ch, 2 Tx Slots


Area Scan (13x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.37 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.586 W/kg

SAR(1 g) = 0.337 W/kg



0 dB = 0.494 W/kg = -3.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.051$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 836.6 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.52 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.491 W/kg



0 dB = 0.605 W/kg = -2.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.051$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 836.6 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Body SAR, Right Edge, Mid.ch


Area Scan (10x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.09 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.756 W/kg

SAR(1 g) = 0.499 W/kg



0 dB = 0.659 W/kg = -1.81 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1712.4 \text{ MHz}$; $\sigma = 1.463 \text{ S/m}$; $\epsilon_r = 52.562$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.7°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1712.4 MHz; Calibrated: 4/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/18/2019

Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Body SAR, Back side, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.23 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.981 W/kg



0 dB = 1.43 W/kg = 1.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.561 \text{ S/m}$; $\epsilon_r = 52.673$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.89 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.718 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.561 \text{ S/m}$; $\epsilon_r = 52.673$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Left Edge, Mid.ch


Area Scan (13x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.87 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.762 W/kg



0 dB = 1.12 W/kg = 0.49 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.966 \text{ S/m}$; $\epsilon_r = 55.077$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 820.1 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA Rule Part 90S, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.55 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.811 W/kg

SAR(1 g) = 0.582 W/kg



0 dB = 0.720 W/kg = -1.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00870

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.966 \text{ S/m}$; $\epsilon_r = 55.077$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 820.1 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rule Part 90S, Body SAR, Right Edge, Mid.ch


Area Scan (10x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.79 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.690 W/kg



0 dB = 0.915 W/kg = -0.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.051$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 836.52 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.05 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.712 W/kg

SAR(1 g) = 0.509 W/kg



0 dB = 0.633 W/kg = -1.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.051$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 836.52 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rule Part 22H, Body SAR, Right Edge, Mid.ch


Area Scan (10x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.24 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.769 W/kg

SAR(1 g) = 0.507 W/kg



0 dB = 0.671 W/kg = -1.73 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 51.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: PCS CDMA, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.28 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.748 W/kg



0 dB = 1.21 W/kg = 0.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00869

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.594 \text{ S/m}$; $\epsilon_r = 51.778$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1908.75 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO, Body SAR, Left Edge, High.ch


Area Scan (13x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.95 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.717 W/kg



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.919 \text{ S/m}$; $\epsilon_r = 57.532$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 680.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 71, Body SAR, Back side, Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.20 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.536 W/kg

SAR(1 g) = 0.356 W/kg



0 dB = 0.455 W/kg = -3.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.928 \text{ S/m}$; $\epsilon_r = 57.475$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 707.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 12, Body SAR, Back side, Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.09 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.599 W/kg

SAR(1 g) = 0.406 W/kg



0 dB = 0.508 W/kg = -2.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.928 \text{ S/m}$; $\epsilon_r = 57.475$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 707.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 12, Body SAR, Right Edge, Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (11x15x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.69 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.629 W/kg

SAR(1 g) = 0.433 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.954 \text{ S/m}$; $\epsilon_r = 57.307$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 782 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 13, Body SAR, Back side, Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.95 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.583 W/kg

SAR(1 g) = 0.412 W/kg



0 dB = 0.507 W/kg = -2.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.954 \text{ S/m}$; $\epsilon_r = 57.307$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 782 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 13, Body SAR, Right Edge, Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (13x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.35 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.457 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.97 \text{ S/m}$; $\epsilon_r = 55.247$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-09-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 831.5 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch, 15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.86 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.811 W/kg

SAR(1 g) = 0.592 W/kg



0 dB = 0.725 W/kg = -1.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.97 \text{ S/m}$; $\epsilon_r = 55.247$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-09-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 831.5 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 26 (Cell.), Body SAR, Right Edge, Mid.ch, 15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset


Area Scan (11x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.42 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.810 W/kg



0 dB = 1.08 W/kg = 0.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00864

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1720 \text{ MHz}$; $\sigma = 1.471 \text{ S/m}$; $\epsilon_r = 52.534$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.7°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1720 MHz; Calibrated: 4/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/18/2019

Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 66 (AWS), Body SAR, Back side, Low.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.59 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 1.07 W/kg



0 dB = 1.50 W/kg = 1.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.59 \text{ S/m}$; $\epsilon_r = 51.789$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1905 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.18 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.762 W/kg



0 dB = 1.23 W/kg = 0.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2593 MHz; Duty Cycle: 1:2.31

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.21 \text{ S/m}$; $\epsilon_r = 51.256$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.37, 7.37, 7.37) @ 2593 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41 PC2, Body SAR, Back side, Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB,
50 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.66 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.706 W/kg



0 dB = 1.14 W/kg = 0.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 00865

Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2506 MHz; Duty Cycle: 1:2.31

Medium: 2450 MHz Body Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.102 \text{ S/m}$; $\epsilon_r = 51.495$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2506 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: LTE Band 41 PC2, Body SAR, Bottom Edge, Low.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.05 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 1.22 W/kg



0 dB = 1.90 W/kg = 2.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX320PM; Type: Portable Handset; Serial: 01175

Communication System: UID 0, _IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.992 \text{ S/m}$; $\epsilon_r = 51.735$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2412 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 1, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.624 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.278 W/kg

SAR(1 g) = 0.136 W/kg



0 dB = 0.219 W/kg = -6.60 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.881 \text{ S/m}$; $\epsilon_r = 41.048$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 750 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 1.54 W/kg

Deviation(1 g) = -7.00%



0 dB = 2.10 W/kg = 3.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.923 \text{ S/m}$; $\epsilon_r = 41.734$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 6-27-2019; Ambient Temp: 23.4°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: SAM 30 with CRP v5.0 right; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.99 W/kg

SAR(1 g) = 1.96 W/kg

Deviation(1 g) = 2.19%



0 dB = 2.63 W/kg = 4.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.89 \text{ S/m}$; $\epsilon_r = 40.098$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 1.9 W/kg

Deviation(1 g) = -0.94%



0 dB = 2.55 W/kg = 4.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.353 \text{ S/m}$; $\epsilon_r = 40.052$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1750 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.73 W/kg

Deviation(1 g) = 3.04%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.46 \text{ S/m}$; $\epsilon_r = 40.732$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1900 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.92 W/kg

SAR(1 g) = 4.08 W/kg

Deviation(1 g) = 3.82%



0 dB = 6.52 W/kg = 8.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 40.949$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1900 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.61 W/kg

SAR(1 g) = 3.99 W/kg

Deviation(1 g) = 1.53%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.808 \text{ S/m}$; $\epsilon_r = 39.401$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2450 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.32 W/kg

Deviation(1 g) = 0.95%



0 dB = 9.00 W/kg = 9.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 1.926$ S/m; $\epsilon_r = 39.163$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.25, 6.25, 6.25) @ 2600 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.6 W/kg

SAR(1 g) = 5.75 W/kg

Deviation(1 g) = 5.50%



0 dB = 9.89 W/kg = 9.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.943 \text{ S/m}$; $\epsilon_r = 57.38$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-08-2019; Ambient Temp: 22.8°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 750 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.55 W/kg

SAR(1 g) = 1.73 W/kg

Deviation(1 g) = 0.82%



0 dB = 2.28 W/kg = 3.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.971 \text{ S/m}$; $\epsilon_r = 55.24$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-09-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.08 W/kg

SAR(1 g) = 2.04 W/kg

Deviation(1 g) = 7.71%



0 dB = 2.72 W/kg = 4.35 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 55.054$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-14-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn728; Calibrated: 5/8/2019

Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.18 W/kg

SAR(1 g) = 2.08 W/kg

Deviation(1 g) = 9.82%



0 dB = 2.80 W/kg = 4.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.505$ S/m; $\epsilon_r = 52.424$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.7°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1750 MHz; Calibrated: 4/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/18/2019

Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.26 W/kg

SAR(1 g) = 3.97 W/kg

Deviation(1 g) = 8.47%



0 dB = 6.07 W/kg = 7.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.429 \text{ S/m}$; $\epsilon_r = 53.479$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-15-2019; Ambient Temp: 21.9°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN7409; ConvF(7.85, 7.85, 7.85) @ 1750 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.81 W/kg

Deviation(1 g) = 4.10%



0 dB = 5.85 W/kg = 7.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 52.616$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1900 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.70 W/kg

SAR(1 g) = 4.16 W/kg

Deviation(1 g) = 6.12%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 51.803$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1900 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.81 W/kg

SAR(1 g) = 4.09 W/kg

Deviation(1 g) = 4.34%



0 dB = 6.43 W/kg = 8.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.035 \text{ S/m}$; $\epsilon_r = 51.648$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2450 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.7 W/kg

SAR(1 g) = 5.14 W/kg

Deviation(1 g) = 2.59%



0 dB = 8.63 W/kg = 9.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.218$ S/m; $\epsilon_r = 51.237$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.37, 7.37, 7.37) @ 2600 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 5.34 W/kg

Deviation(1 g) = -2.55%



0 dB = 9.29 W/kg = 9.68 dBW/kg

APPENDIX C: PROBE CALIBRATION

**Calibration Laboratory of
Schmid & Partner
Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1003_Jan18**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1003**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 15, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Leli Klysner** Name
Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Name
Function: **Technical Manager**

Signature

Leli Klysner

Katja Pokovic

Issued: January 15, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5.0 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.9 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.28 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.42 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.0 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.58 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.43 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.71 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	53.8 Ω - 2.1 j Ω
Return Loss	- 27.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.2 Ω - 6.2 j Ω
Return Loss	- 24.0 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.043 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 21, 2009

Appendix (Additional assessments outside the scope of SCS 0108)

Measurement Conditions

DASY system configuration, as far as not given on page 1 and 3.

Phantom	SAM Head Phantom	For usage with cSAR3DV2-R/L
---------	------------------	-----------------------------

SAR result with SAM Head (Top)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.98 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	7.94 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.33 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.32 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Mouth)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.05 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.22 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.52 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Neck)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.01 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.06 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.52 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Ear)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.67 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.70 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.15 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	4.60 W/kg ± 16.9 % (k=2)

DASY5 Validation Report for Head TSL

Date: 12.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 40.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.11 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.15 W/kg

SAR(1 g) = 2.1 W/kg; SAR(10 g) = 1.37 W/kg


Maximum value of SAR (measured) = 2.80 W/kg



Impedance Measurement Plot for Head TSL

12 Jan 2018 13:14:07
CH1 S11 1 U FS 1: 53.754 Ω -2.0996 Ω 101.07 pF 750.000 000 MHz

*
De1
CA




Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-27.643 dB 750.000 000 MHz

CA

Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 12.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.96 \text{ S/m}$; $\epsilon_r = 55$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.19, 10.19, 10.19); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x8x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 57.31 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.43 W/kg


Maximum value of SAR (measured) = 2.83 W/kg



Impedance Measurement Plot for Body TSL

12 Jan 2018 13:13:21
CH1 S11 1 U FS 1: 49.234 Ω -6.1934 Ω 34.264 pF 750.000 000 MHz

*
De1
CA




Avg
16
H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1:-24.047 dB 750.000 000 MHz

CA

Avg
16

H1d



DASY5 Validation Report for SAM Head

Date: 15.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 44.2$; $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: SAM Head
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

SAM Head/Top/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.79 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.89 W/kg

SAR(1 g) = 1.98 W/kg; SAR(10 g) = 1.33 W/kg

Maximum value of SAR (measured) = 2.58 W/kg

SAM Head/Mouth/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.85 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.94 W/kg

SAR(1 g) = 2.05 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.62 W/kg

SAM Head/Neck/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.29 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.78 W/kg

SAR(1 g) = 2.01 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.56 W/kg



SAM Head/Ear/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.01 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.31 W/kg

SAR(1 g) = 1.67 W/kg; SAR(10 g) = 1.15 W/kg

Maximum value of SAR (measured) = 2.11 W/kg



0 dB = 2.58 W/kg = 4.12 dBW/kg

Certification of Calibration

Object D750V3 – SN: 1003

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.

Extension Calibration date: 1/15/2019

Description: SAR Validation Dipole at 750 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	2/8/2018	Annual	2/8/2019	US39170122
Agilent	N5182A	MXG Vector Signal Generator	4/18/2018	Annual	4/18/2019	MY47420800
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1339018
Anritsu	ML2495A	Power Meter	10/21/2018	Annual	10/21/2019	941001
Control Company	4040	Therm./Clock/Humidity Monitor	3/31/2017	Biennial	3/31/2019	170232394
Control Company	4352	Ultra Long Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330156
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Seekonk	NC-100	Torque Wrench	7/11/2018	Annual	7/11/2019	N/A
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/3/2018	Annual	10/3/2019	1558
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/18/2018	Annual	6/18/2019	1334
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/11/2018	Annual	9/11/2019	1091
SPEAG	EX3DV4	SAR Probe	8/23/2018	Annual	8/23/2019	7308
SPEAG	EX3DV4	SAR Probe	6/25/2018	Annual	6/25/2019	7409

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Brodie Halfoster	Test Engineer	<i>BRODIE HALFOSTER</i>
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	<i>KOK</i>

DIPOLE CALIBRATION EXTENSION

Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.

The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 23.0 dBm	Measured Head SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Head (10g) W/kg @ 23.0 dBm	Measured Head SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
1/15/2018	1/15/2019	1.043	1.656	1.75	5.68%	1.08	1.15	6.09%	53.8	54.8	1	-2.1	-2.2	0.1	-27.6	-25.8	6.50%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 23.0 dBm	Measured Body SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
1/15/2018	1/15/2019	1.043	1.716	1.84	7.23%	1.14	1.23	7.71%	49.2	49	0.2	-6.2	-5.1	1.1	-24	-25.6	-6.80%	PASS