



RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch12, 2.45 GHz - 2.50GHz**

RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch13, 2.45 GHz - 2.50GHz**

RE - Power-2.38GHz-2.45GHz





Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.43GHz


RE - Power-2.45GHz-2.5GHz



3


Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz

RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch12, 2.45 GHz - 2.50GHz**

RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch13, 2.45 GHz - 2.50GHz**

RE - Power-2.38GHz-2.45GHz




Fig.A.6.2.9 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1,  
2.38 GHz - 2.45GHz

RE - Power-2.45GHz-2.5GHz






Fig.A.6.2.10 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11,  
2.45 GHz - 2.50GHz

RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.11 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch12, 2.45 GHz - 2.50GHz**

RE - Power-2.45GHz-2.5GHz



**Fig.A.6.2.12 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch13, 2.45 GHz - 2.50GHz**



## **A.7. AC Power-line Conducted Emission**

### **Method of Measurement: See ANSI C63.10-2013-clause 6.2**

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.<sup>36</sup> Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

### **Test Condition:**

<b>Voltage (V)</b>	<b>Frequency (Hz)</b>
120	60

**Measurement Result and limit:**

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	<b>P</b>
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	<b>P</b>
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Conclusion: Pass**

**Test graphs as below:**

Traffic: Set.1




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.703500	37.3	2000.0	9.000	On	L1	19.8	18.7	56.0
0.825000	39.5	2000.0	9.000	On	L1	19.7	16.5	56.0
1.788000	36.8	2000.0	9.000	On	L1	19.7	19.2	56.0
2.859000	33.8	2000.0	9.000	On	L1	19.7	22.2	56.0
9.361500	35.4	2000.0	9.000	On	L1	19.8	24.6	60.0
11.607000	36.1	2000.0	9.000	On	L1	19.9	23.9	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.685500	28.4	2000.0	9.000	On	L1	19.8	17.6	46.0
0.766500	29.3	2000.0	9.000	On	L1	19.7	16.7	46.0
1.846500	28.0	2000.0	9.000	On	L1	19.7	18.0	46.0
2.881500	25.2	2000.0	9.000	On	L1	19.7	20.8	46.0
3.655500	24.8	2000.0	9.000	On	L1	19.6	21.2	46.0
11.170500	27.1	2000.0	9.000	On	L1	19.9	22.9	50.0



Idle: Set.1




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.555000	36.6	2000.0	9.000	On	N	19.9	19.4	56.0
0.825000	39.5	2000.0	9.000	On	L1	19.7	16.5	56.0
1.918500	35.8	2000.0	9.000	On	L1	19.7	20.2	56.0
2.908500	33.7	2000.0	9.000	On	L1	19.7	22.3	56.0
9.874500	36.0	2000.0	9.000	On	L1	19.8	24.0	60.0
11.755500	37.3	2000.0	9.000	On	L1	19.9	22.7	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.559500	28.3	2000.0	9.000	On	N	19.9	17.7	46.0
0.825000	29.9	2000.0	9.000	On	L1	19.7	16.1	46.0
1.851000	28.2	2000.0	9.000	On	L1	19.7	17.8	46.0
2.890500	25.1	2000.0	9.000	On	L1	19.7	20.9	46.0
3.651000	24.8	2000.0	9.000	On	L1	19.6	21.2	46.0
10.464000	26.7	2000.0	9.000	On	L1	19.8	23.3	50.0

## ANNEX B: Accreditation Certificate

United States Department of Commerce  
National Institute of Standards and Technology



### Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

**Telecommunication Technology Labs, CAICT**

Beijing  
China


*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

**Electromagnetic Compatibility & Telecommunications**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2016-09-29 through 2017-09-30  
Effective Dates



  
For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*