



SAR EVALUATION REPORT

Applicant Name:
 LG Electronics U.S.A., Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 07/01/19 - 07/19/19
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 1M1906260110-01-R1.ZNF

FCC ID: ZNFX420TM
APPLICANT: LG ELECTRONICS U.S.A., INC.

DUT Type: Portable Handset
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: LM-X420TM
Additional Models: LMX420TM, X420TM

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)	10g Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.45	0.58	0.58	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.38	0.39	0.42	N/A
PCE	UMTS 850	825.40 - 846.60 MHz	0.28	0.42	0.42	N/A
PCE	UMTS 1755	1712.4 - 1752.6 MHz	0.43	1.11	1.11	3.14
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.58	0.73	0.74	3.05
PCE	CDMA/EVDO BC10 (900S)	817.90 - 823.10 MHz	0.21	0.35	0.32	N/A
PCE	CDMA/EVDO BC0 (S22H)	824.70 - 848.31 MHz	0.32	0.43	0.39	N/A
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.69	0.83	0.80	2.76
PCE	LTE Band 71	665.5 - 695.5 MHz	0.23	0.43	0.43	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.24	0.40	0.48	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.25	0.32	0.32	N/A
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.30	0.37	0.37	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.36	0.81	0.81	2.83
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.57	0.79	0.85	2.93
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 41	2498.5 - 2537.5 MHz	0.27	0.41	0.69	N/A
DTS	2.4 GHz WLAN	2412 - 2482 MHz	1.10	0.75	0.75	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	0.63	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.58	0.56	N/A	2.19
NII	U-NII-2C	5500 - 5720 MHz	0.81	0.54	N/A	1.84
NII	U-NII-3	5745 - 5825 MHz	0.95	0.68	0.68	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.12	< 0.1	< 0.1	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.55	1.58	1.57	3.98

Note: This revised Test Report (S/N: 1M1906260110-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
 President





The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 1 of 116	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	13
3	INTRODUCTION	14
4	DOSIMETRIC ASSESSMENT	15
5	DEFINITION OF REFERENCE POINTS.....	16
6	TEST CONFIGURATION POSITIONS.....	17
7	RF EXPOSURE LIMITS	21
8	FCC MEASUREMENT PROCEDURES.....	22
9	RF CONDUCTED POWERS	29
10	SYSTEM VERIFICATION.....	65
11	SAR DATA SUMMARY	69
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	90
13	SAR MEASUREMENT VARIABILITY	107
14	ADDITIONAL TESTING PER FCC GUIDANCE	109
15	EQUIPMENT LIST.....	112
16	MEASUREMENT UNCERTAINTIES.....	113
17	CONCLUSION.....	114
18	REFERENCES	115
APPENDIX A:	SAR TEST PLOTS	
APPENDIX B:	SAR DIPOLE VERIFICATION PLOTS	
APPENDIX C:	PROBE AND DIPOLE CALIBRATION CERTIFICATES	
APPENDIX D:	SAR TISSUE SPECIFICATIONS	
APPENDIX E:	SAR SYSTEM VALIDATION	
APPENDIX F:	DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS	
APPENDIX G:	POWER REDUCTION VERIFICATION	
APPENDIX H:	DOWNLINK LTE CA RF CONDUCTED POWERS	

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 2 of 116	



1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
CDMA/EVDO BC10 (§90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (§22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

1.2 Power Reduction for SAR

This device uses a power reduction mechanism for SAR compliance. The power reduction mechanism is activated when the device is used in close proximity to the user's body. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 3 of 116	

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications



This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power



Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	32.7	32.7	32.2	30.7	29.2	26.7	26.7	26.2	25.7
	Nominal	32.2	32.2	31.7	30.2	28.7	26.2	26.2	25.7	25.2
GSM/GPRS/EDGE 1900	Maximum	31.2	31.2	29.2	27.2	25.7	26.2	26.2	25.2	25.2
	Nominal	30.7	30.7	28.7	26.7	25.2	25.7	25.7	24.7	24.7

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	25.2	25.2	25.2
	Nominal	24.7	24.7	24.7
UMTS Band 4 (1750 MHz)	Maximum	24.4	24.4	24.4
	Nominal	23.9	23.9	23.9
UMTS Band 2 (1900 MHz)	Maximum	24.4	24.4	24.4
	Nominal	23.9	23.9	23.9

Mode / Band		Modulated Average (dBm)
CDMA/EVDO BC10 (§90S)	Maximum	25.2
	Nominal	24.7
CDMA/EVDO BC0 (§22H)	Maximum	25.2
	Nominal	24.7
PCS CDMA/EVDO	Maximum	24.7
	Nominal	24.2

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 4 of 116



Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	25.2
	Nominal	24.7
LTE Band 12	Maximum	25.2
	Nominal	24.7
LTE Band 17	Maximum	25.2
	Nominal	24.7
LTE Band 13	Maximum	23.2
	Nominal	22.7
LTE Band 26 (Cell)	Maximum	25.2
	Nominal	24.7
LTE Band 5 (Cell)	Maximum	25.2
	Nominal	24.7
LTE Band 66 (AWS)	Maximum	24.4
	Nominal	23.9
LTE Band 4 (AWS)	Maximum	24.4
	Nominal	23.9
LTE Band 25 (PCS)	Maximum	24.4
	Nominal	23.9
LTE Band 2 (PCS)	Maximum	24.4
	Nominal	23.9
LTE Band 41 (PC3)	Maximum	24.2
	Nominal	23.7
LTE Band 41 (PC2)	Maximum	27.2
	Nominal	26.7

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 5 of 116	

Mode / Band		Modulated Average (dBm)						
Channel		1	2	3	4-6	7-9	10	11
IEEE 802.11b (2.4 GHz)	Maximum	22.0	22.0	22.0	22.0	22.0	22.0	22.0
	Nominal	21.0	21.0	21.0	21.0	21.0	21.0	21.0
IEEE 802.11g (2.4 GHz)	Maximum	17.5	19.5	21.5	22.0	21.0	19.0	17.0
	Nominal	16.5	18.5	20.5	21.0	20.0	18.0	16.0
IEEE 802.11n (2.4 GHz)	Maximum	16.5	18.5	20.5	21.0	20.0	18.0	16.0
	Nominal	15.5	17.5	19.5	20.0	19.0	17.0	15.0

Mode / Band		Modulated Average (dBm)																
		20 MHz Bandwidth								40 MHz Bandwidth								80 MHz Bandwidth
Channel		36	40-60	64	100	104-136	140-149	153-161	165	38	46-54	62-102	110	118-126	134	142	151-159	42-155
IEEE 802.11a (5 GHz)	Maximum	17.5	18.0	17.5	16.0	17.5	17.5	18.5	17.5									
	Nominal	16.5	17.0	16.5	15.0	16.5	16.5	17.5	16.5									
IEEE 802.11n (5 GHz)	Maximum	14.5	15.0	14.5	13.0	14.5	14.5	15.5	14.5	13.5	15.5	13.5	15.5	15.5	15.5	15.5	15.5	
	Nominal	13.5	14.0	13.5	12.0	13.5	13.5	14.5	13.5	12.5	14.5	12.5	14.5	14.5	14.5	14.5	14.5	
IEEE 802.11ac (5 GHz)	Maximum	15.0	15.5	15.0	13.5	15.0	15.0	16.0	15.0	13.0	15.0	13.0	15.0	15.0	15.0	15.0	15.0	12.5
	Nominal	14.0	14.5	14.0	12.5	14.0	14.0	15.0	14.0	12.0	14.0	12.0	14.0	14.0	14.0	14.0	14.0	11.5

Mode/Band		Modulated Average (dBm)
Bluetooth (DH5)	Maximum	8.0
	Nominal	7.0
Bluetooth (2-DH5)	Maximum	8.0
	Nominal	7.0
Bluetooth (3-DH5)	Maximum	8.0
	Nominal	7.0
Bluetooth LE	Maximum	0.0
	Nominal	-1.0



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 6 of 116

1.3.2 Reduced Power

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 4 (1750 MHz)	Maximum	22.7	22.7	22.7
	Nominal	22.2	22.2	22.2
UMTS Band 2 (1900 MHz)	Maximum	22.7	22.7	22.7
	Nominal	22.2	22.2	22.2



Mode / Band		Modulated Average (dBm)
PCS CDMA/EVDO	Maximum	23.0
	Nominal	22.5

Mode / Band		Modulated Average (dBm)
LTE Band 66 (AWS)	Maximum	22.9
	Nominal	22.4
LTE Band 4 (AWS)	Maximum	22.9
	Nominal	22.4
LTE Band 25 (PCS)	Maximum	22.9
	Nominal	22.4
LTE Band 2 (PCS)	Maximum	22.9
	Nominal	22.4

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 7 of 116	

Mode / Band		Modulated Average (dBm)						
Channel		1	2	3	4-6	7-9	10	11
IEEE 802.11b (2.4 GHz)	Maximum	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	Nominal	16.5	16.5	16.5	16.5	16.5	16.5	16.5
IEEE 802.11g (2.4 GHz)	Maximum	13.0	15.0	17.0	17.5	16.5	14.5	12.5
	Nominal	12.0	14.0	16.0	16.5	15.5	13.5	11.5
IEEE 802.11n (2.4 GHz)	Maximum	13.0	15.0	17.0	17.5	16.5	14.5	12.5
	Nominal	12.0	14.0	16.0	16.5	15.5	13.5	11.5

Mode / Band		Modulated Average (dBm)																
		20 MHz Bandwidth								40 MHz Bandwidth								80 MHz Bandwidth
Channel		36	40-60	64	100	104-136	140-149	153-161	165	38	46-54	62-102	110	118-126	134	142	151-159	42-155
IEEE 802.11a (5 GHz)	Maximum	13.0	13.5	13.0	11.5	13.0	13.0	14.0	13.0									
	Nominal	12.0	12.5	12.0	10.5	12.0	12.0	13.0	12.0									
IEEE 802.11n (5 GHz)	Maximum	13.0	13.5	13.0	11.5	13.0	13.0	14.0	13.0	11.5	13.5	12.0	13.0	13.5	13.5	13.5	13.5	
	Nominal	12.0	12.5	12.0	10.5	12.0	12.0	13.0	12.0	10.5	12.5	11.0	12.0	12.5	12.5	12.5	12.5	
IEEE 802.11ac (5 GHz)	Maximum	12.5	13.5	13.0	11.5	13.0	13.0	14.0	13.0	11.5	13.5	12.0	13.0	13.5	13.5	13.5	13.5	12.5
	Nominal	11.5	12.5	12.0	10.5	12.0	12.0	13.0	12.0	10.5	12.5	11.0	12.0	12.5	12.5	12.5	12.5	11.5

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 8 of 116

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

**Table 1-1
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
EVDO BC10 (§90S)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC0 (§22H)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	No	Yes
LTE Band 71	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-2A, U-NII-2C operations are disabled.



1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 9 of 116	

**Table 1-2
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	1x CDMA voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
2	1x CDMA voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
3	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
4	1x CDMA voice + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
5	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
6	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
7	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
8	GSM voice + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
9	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	Yes	
10	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
11	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
12	UMTS + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
13	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	Yes	
14	LTE + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
15	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
16	LTE + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
17	CDMA/EVDO data + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
18	CDMA/EVDO data + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
19	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes^*	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
20	CDMA/EVDO data + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^*	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
21	GPRS/EDGE + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
22	GPRS/EDGE + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
23	GPRS/EDGE + 2.4 GHz Bluetooth	Yes^*	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
24	GPRS/EDGE + 2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes^*	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered

- 2.4 GHz WLAN and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for U-NII-1 and U-NII-3 by S/W, therefore U-NII2A and U-NII2C were not evaluated for wireless router conditions.
- This device supports VOLTE.
- This device supports VoWIFI.
- This device supports Bluetooth Tethering.



1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-2A & U-NII-2C WIFI, only 2.4 GHz, U-NII-1, and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

This device supports IEEE 802.11ac with the following features:

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 10 of 116	

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 1 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4GHz WLAN, Bluetooth, U-NII-1 WLAN, and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.



CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01v03r01.

This device supports LTE Carrier Aggregation (CA) in the downlink. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix H.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (See Section 6.9 for more information)

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports both Power Class 2 (PC2) and Power Class 3 (PC3) for LTE Band 41. Per May 2017 TCB Workshop Notes, SAR tests were performed with Power Class 3 (given the specific UL/DL limitations for Power Class 2). Additionally, SAR testing for the power class condition was evaluated for the highest configuration in Power Class 3 for each test configuration to confirm the results were scalable linearly (See Section 14.1).



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 11 of 116	

1.8 Guidance Applied



- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- FCC KDB Publication 616217 D04v01r02 (Proximity Sensor)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE Band 41 Power Class 2/3)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 12 of 116	

LTE Information						
Form Factor	Portable Handset					
Frequency Range of each LTE transmission band	LTE Band 71 (665.5 - 695.5 MHz)					
	LTE Band 12 (699.7 - 715.3 MHz)					
	LTE Band 17 (706.5 - 713.5 MHz)					
	LTE Band 13 (779.5 - 784.5 MHz)					
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)					
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)					
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)					
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)					
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)					
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)					
	LTE Band 41 (2498.5 - 2687.5 MHz)					
	Channel Bandwidths	LTE Band 71: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
		LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
LTE Band 17: 5 MHz, 10 MHz						
LTE Band 13: 5 MHz, 10 MHz						
LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz						
LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz						
LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz						
LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz						
LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz						
LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz						
LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz						
Channel Numbers and Frequencies (MHz)		Low	Low-Mid	Mid	Mid-High	High
		LTE Band 71: 5 MHz				
LTE Band 71: 10 MHz						
LTE Band 71: 15 MHz						
LTE Band 71: 20 MHz						
LTE Band 12: 1.4 MHz						
LTE Band 12: 3 MHz						
LTE Band 12: 5 MHz						
LTE Band 12: 10 MHz						
LTE Band 17: 5 MHz						
LTE Band 17: 10 MHz						
LTE Band 13: 5 MHz						
LTE Band 13: 10 MHz						
LTE Band 26 (Cell): 1.4 MHz						
LTE Band 26 (Cell): 3 MHz						
LTE Band 26 (Cell): 5 MHz						
LTE Band 26 (Cell): 10 MHz						
LTE Band 26 (Cell): 15 MHz						
LTE Band 5 (Cell): 1.4 MHz						
LTE Band 5 (Cell): 3 MHz						
LTE Band 5 (Cell): 5 MHz						
LTE Band 5 (Cell): 10 MHz						
LTE Band 66 (AWS): 1.4 MHz						
LTE Band 66 (AWS): 3 MHz						
LTE Band 66 (AWS): 5 MHz						
LTE Band 66 (AWS): 10 MHz						
LTE Band 66 (AWS): 15 MHz						
LTE Band 66 (AWS): 20 MHz						
LTE Band 4 (AWS): 1.4 MHz						
LTE Band 4 (AWS): 3 MHz						
LTE Band 4 (AWS): 5 MHz						
LTE Band 4 (AWS): 10 MHz						
LTE Band 4 (AWS): 15 MHz						
LTE Band 4 (AWS): 20 MHz						
LTE Band 25 (PCS): 1.4 MHz						
LTE Band 25 (PCS): 3 MHz						
LTE Band 25 (PCS): 5 MHz						
LTE Band 25 (PCS): 10 MHz						
LTE Band 25 (PCS): 15 MHz						
LTE Band 25 (PCS): 20 MHz						
LTE Band 2 (PCS): 1.4 MHz						
LTE Band 2 (PCS): 3 MHz						
LTE Band 2 (PCS): 5 MHz						
LTE Band 2 (PCS): 10 MHz						
LTE Band 2 (PCS): 15 MHz						
LTE Band 2 (PCS): 20 MHz						
LTE Band 41: 5 MHz						
LTE Band 41: 10 MHz						
LTE Band 41: 15 MHz						
LTE Band 41: 20 MHz						
UE Category	DL UE Cat 6, UL UE Cat 5					
Modulations Supported in UL	QPSK, 16QAM, 64QAM					
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES					
A-MPR (Additional MPR) disabled for SAR Testing?	YES					
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations					
LTE Additional Information	This device does not support full CA features on 3GPP Release 10. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eCIC, WIFI Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.					

FCC ID: ZNFX420TM		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 13 of 116	

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 14 of 116	

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.






Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{area}, \Delta y_{area}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{zoom}, \Delta y_{zoom}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 15 of 116

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 5-2
Front, back and side view of SAM Twin Phantom






Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 16 of 116

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 17 of 116




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.






Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 18 of 116

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.



6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 19 of 116	



support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR > 1.2 W/kg.

6.9 Proximity Sensor Considerations

This device uses a power reduction mechanism to reduce output powers in certain use conditions when the device is used close the user's body.

When the device's antenna is within a certain distance of the user, the sensor activates and reduces the maximum allowed output power. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, additional evaluation is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antennas.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 20 of 116	

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 21 of 116

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”



The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 22 of 116

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.



The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with EVDO capabilities, the 3G SAR test reduction procedure is applied to EVDO Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 23 of 116	

4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification



Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH_n and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 24 of 116	

configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.6 SAR Measurement Conditions for LTE



LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 25 of 116	

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:



- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 26 of 116

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.3 U-NII-2C and U-NII-3



The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1-ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 27 of 116	

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.



8.7.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 28 of 116	

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

**Table 9-1
Maximum Conducted Power**

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	25.17	24.98	25.15	25.05	25.03	24.98	25.09
Cellular	1013	22H	824.7	25.17	25.10	25.20	25.18	25.14	25.17	25.15
	384	22H	836.52	25.11	25.14	25.15	25.13	25.05	25.09	25.12
	777	22H	848.31	25.20	25.08	25.15	25.20	25.17	25.13	25.18
PCS	25	24E	1851.25	24.41	24.40	24.47	24.41	24.43	24.48	24.48
	600	24E	1880	24.45	24.41	24.41	24.44	24.41	24.51	24.50
	1175	24E	1908.75	24.35	24.37	24.48	24.37	24.36	24.54	24.53

**Table 9-2
Reduced Conducted Power**

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
PCS	25	1851.25	22.70	22.70	22.74	22.70	22.69	22.74	22.75
	600	1880	22.68	22.68	22.72	22.68	22.68	22.71	22.72
	1175	1908.75	22.76	22.72	22.71	22.74	22.72	22.78	22.78

Note: RC1 is only applicable for IS-95 compatibility. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v06 4.1.g), only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.





**Figure 9-1
Power Measurement Setup**

FCC ID: ZNFX420TM	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 29 of 116	

9.2 GSM Conducted Powers

**Table 9-3
Maximum Conducted Power**

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.09	32.42	31.83	30.39	28.71	26.62	26.57	25.91	25.19
	190	32.20	32.45	31.88	30.44	28.79	26.70	26.52	25.89	25.14
	251	32.17	32.47	31.89	30.46	28.77	26.63	26.61	25.82	25.20
GSM 1900	512	31.20	31.20	28.80	26.60	25.48	25.80	25.73	25.06	24.77
	661	31.19	31.19	28.74	26.54	25.33	26.04	25.70	24.99	24.73
	810	31.18	31.17	28.82	26.56	25.34	25.71	25.57	24.96	24.66
Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.06	23.39	25.81	26.13	25.70	17.59	20.55	21.65	22.18
	190	23.17	23.42	25.86	26.18	25.78	17.67	20.50	21.63	22.13
	251	23.14	23.44	25.87	26.20	25.76	17.60	20.59	21.56	22.19
GSM 1900	512	22.17	22.17	22.78	22.34	22.47	16.77	19.71	20.80	21.76
	661	22.16	22.16	22.72	22.28	22.32	17.01	19.68	20.73	21.72
	810	22.15	22.14	22.80	22.30	22.33	16.68	19.55	20.70	21.65
GSM 850	Frame	23.17	23.17	25.68	25.94	25.69	17.17	20.18	21.44	22.19
GSM 1900	Avg.Targets:	21.67	21.67	22.68	22.44	22.19	16.67	19.68	20.44	21.69

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 30 of 116



Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 12 (Max 4 Tx Uplink slots)
EDGE Multislot class: 12 (Max 4 Tx Uplink slots)
DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.		SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 31 of 116	

9.3 UMTS Conducted Powers

**Table 9-4
Maximum Conducted Power**

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	25.18	25.15	25.20	24.32	24.19	24.02	24.38	24.39	24.40	-
99		12.2 kbps AMR	25.20	25.18	25.19	24.34	24.20	24.02	24.40	24.35	24.34	-
6	HSDPA	Subtest 1	24.70	24.58	24.67	23.28	23.19	23.11	23.11	23.10	23.22	0
6		Subtest 2	24.66	24.55	24.65	23.33	23.14	23.09	23.27	23.21	23.27	0
6		Subtest 3	24.20	24.17	24.19	22.65	22.61	22.56	22.78	22.70	22.81	0.5
6		Subtest 4	24.22	24.16	24.20	22.82	22.67	22.54	22.73	22.77	22.87	0.5
6	HSUPA	Subtest 1	24.83	24.68	24.67	23.63	23.51	23.35	23.58	23.50	23.63	0
6		Subtest 2	22.74	22.62	22.68	21.52	21.30	21.19	21.55	21.44	21.53	2
6		Subtest 3	23.74	23.65	23.61	22.50	22.36	22.19	22.53	22.48	22.55	1
6		Subtest 4	22.74	22.60	22.69	21.45	21.35	21.19	21.61	21.19	21.59	2
6		Subtest 5	24.75	24.67	24.68	23.54	23.27	23.22	23.63	23.52	23.64	0



**Table 9-5
Reduced Conducted Power**

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.68	22.69	22.57	22.46	22.36	22.51	-
99		12.2 kbps AMR	22.70	22.70	22.57	22.47	22.36	22.53	-
6	HSDPA	Subtest 1	21.96	21.95	21.69	21.51	21.53	21.61	0
6		Subtest 2	22.01	21.92	21.68	21.52	21.51	21.63	0
6		Subtest 3	21.51	21.34	21.18	21.04	21.05	21.10	0.5
6		Subtest 4	21.45	21.32	21.21	21.09	21.03	21.09	0.5
6	HSUPA	Subtest 1	21.93	21.85	21.66	21.54	21.48	21.59	0
6		Subtest 2	19.80	19.96	19.66	19.52	19.40	19.57	2
6		Subtest 3	20.96	20.93	20.66	20.50	20.43	20.56	1
6		Subtest 4	19.95	19.91	19.70	19.52	19.45	19.53	2
6		Subtest 5	21.97	21.81	21.67	21.56	21.44	21.54	0

This device does not support DC-HSDPA.



**Figure 9-3
Power Measurement Setup**

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 32 of 116	



9.4 LTE Conducted Powers

9.4.1 LTE Band 71

Table 9-6
LTE Band 71 Conducted Powers - 20 MHz Bandwidth

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.16	0	0
	1	50	24.82		0
	1	99	25.18		0
	50	0	23.99	0-1	1
	50	25	23.97		1
	50	50	24.09		1
	100	0	24.06		1
16QAM	1	0	24.16	0-1	1
	1	50	23.98		1
	1	99	24.20		1
	50	0	23.03	0-2	2
	50	25	23.02		2
	50	50	23.20		2
	100	0	23.06		2
64QAM	1	0	23.17	0-2	2
	1	50	22.98		2
	1	99	23.13		2
	50	0	22.01	0-3	3
	50	25	22.10		3
	50	50	22.17		3
	100	0	22.04		3



Note: LTE Band 71 at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 33 of 116

**Table 9-7
LTE Band 71 Conducted Powers - 15 MHz Bandwidth**

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.95	0	0
	1	36	24.64		0
	1	74	24.89		0
	36	0	23.94	0-1	1
	36	18	23.82		1
	36	37	23.79		1
	75	0	23.84		1
16QAM	1	0	24.15	0-1	1
	1	36	23.93		1
	1	74	24.18		1
	36	0	22.89	0-2	2
	36	18	22.82		2
	36	37	22.76		2
	75	0	22.90		2
64QAM	1	0	23.15	0-2	2
	1	36	22.92		2
	1	74	23.20		2
	36	0	21.80	0-3	3
	36	18	21.77		3
	36	37	21.70		3
	75	0	21.87		3

Note: LTE Band 71 at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 34 of 116

**Table 9-8
LTE Band 71 Conducted Powers - 10 MHz Bandwidth**

LTE Band 71 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	25.01	25.14	25.18	0	0	
	1	25	25.19	24.94	25.12		0	
	1	49	25.14	25.01	24.97		0	
	25	0	24.17	24.05	24.06	0-1	1	
	25	12	24.12	23.97	24.00		1	
	25	25	24.17	23.89	23.93		1	
16QAM	50	0	24.16	23.98	23.97	0-1	1	
	1	0	24.16	23.90	24.14		0-1	1
	1	25	24.20	23.85	24.13			1
	1	49	24.19	23.80	24.10	0-2		1
	25	0	23.14	23.05	22.97		2	
	25	12	23.10	23.00	23.00		2	
64QAM	25	25	23.10	22.94	23.00	0-2	2	
	50	0	23.19	22.94	22.94		2	
	1	0	23.13	23.18	23.00		0-2	2
	1	25	23.07	22.99	23.09	2		
	1	49	23.20	23.19	23.01	2		
	64QAM	25	0	22.08	22.05	22.09	0-3	3
25		12	22.13	21.99	22.01	3		
25		25	22.20	22.02	22.00	3		
50		0	22.18	21.98	22.10	3		

**Table 9-9
LTE Band 71 Conducted Powers - 5 MHz Bandwidth**

LTE Band 71 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	25.11	25.00	24.92	0	0	
	1	12	25.16	25.00	24.76		0	
	1	24	25.13	24.87	24.85		0	
	12	0	24.16	23.98	24.05	0-1	1	
	12	6	24.20	23.93	23.89		1	
	12	13	24.20	23.88	23.97		1	
16QAM	25	0	24.20	23.92	23.85	0-1	1	
	1	0	24.19	24.18	24.17		0-1	1
	1	12	24.10	24.19	24.20			1
	1	24	24.00	24.12	24.12	0-2		1
	12	0	23.20	22.99	23.03		2	
	12	6	23.19	22.98	22.87		2	
64QAM	12	13	23.05	22.99	22.91	0-2	2	
	25	0	23.18	22.94	22.97		2	
	1	0	23.20	23.15	23.11		0-2	2
	1	12	23.17	23.12	23.04	2		
	1	24	23.12	23.03	23.12	0-3		2
	12	0	22.09	22.00	22.05		3	
12	6	22.01	22.04	21.92	3			
64QAM	12	13	22.17	21.93	22.00	0-3	3	
	25	0	22.18	21.92	22.00		3	

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 35 of 116	

9.4.2

LTE Band 12

Table 9-10
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.05	0	0
	1	25	25.07		0
	1	49	25.11		0
	25	0	24.02	0-1	1
	25	12	24.05		1
	25	25	23.97		1
	50	0	23.96		1
16QAM	1	0	24.17	0-1	1
	1	25	24.11		1
	1	49	24.20		1
	25	0	23.13	0-2	2
	25	12	23.19		2
	25	25	23.05		2
	50	0	23.12		2
64QAM	1	0	23.12	0-2	2
	1	25	22.92		2
	1	49	23.20		2
	25	0	22.18	0-3	3
	25	12	22.20		3
	25	25	22.07		3
	50	0	22.01		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 36 of 116	

Table 9-11
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.84	25.10	25.20	0	0	
	1	12	25.00	25.02	25.10		0	
	1	24	24.93	24.94	25.04		0	
	16QAM	12	0	23.94	23.92	24.09	0-1	1
		12	6	23.83	23.87	24.10		1
		12	13	23.81	23.88	24.03		1
		25	0	23.91	23.85	24.05		1
64QAM	1	0	23.90	23.94	24.04	0-1	1	
	1	12	23.89	23.98	24.05		1	
	1	24	23.85	23.89	24.03		1	
	16QAM	12	0	22.91	23.07	23.13	0-2	2
		12	6	22.86	22.79	23.11		2
		12	13	22.84	22.91	23.11		2
		25	0	22.91	22.91	23.10		2
64QAM	1	0	23.07	23.06	23.19	0-2	2	
	1	12	23.18	23.05	23.18		2	
	1	24	23.00	23.07	23.20		2	
	16QAM	12	0	21.93	21.91	22.16	0-3	3
		12	6	21.91	21.86	22.16		3
		12	13	21.87	21.96	22.14		3
		25	0	21.91	21.98	22.19		3

Table 9-12
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.81	24.94	25.17	0	0	
	1	7	25.00	24.93	25.14		0	
	1	14	24.94	24.89	25.16		0	
	16QAM	8	0	23.80	23.88	24.06	0-1	1
		8	4	23.79	23.89	24.14		1
		8	7	23.80	23.80	24.08		1
		15	0	23.75	23.87	24.13		1
64QAM	1	0	24.00	23.80	24.09	0-1	1	
	1	7	23.99	24.10	24.16		1	
	1	14	24.12	23.98	24.15		1	
	16QAM	8	0	22.87	23.00	23.11	0-2	2
		8	4	22.88	22.90	23.12		2
		8	7	22.88	22.82	23.11		2
		15	0	22.80	22.83	23.10		2
64QAM	1	0	23.04	22.94	23.18	0-2	2	
	1	7	23.06	23.05	23.13		2	
	1	14	23.13	23.02	23.20		2	
	16QAM	8	0	21.83	21.89	22.13	0-3	3
		8	4	22.05	21.91	22.16		3
		8	7	22.00	21.85	22.12		3
		15	0	21.85	21.87	22.11		3





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 37 of 116	

Table 9-13
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.76	24.72	24.98	0	0
	1	2	24.89	24.82	25.01		0
	1	5	24.84	24.63	24.99		0
	3	0	24.79	24.76	24.93		0
	3	2	24.94	24.82	25.02		0
	3	3	24.72	24.76	24.96		0
16QAM	6	0	23.83	23.75	24.11	0-1	1
	1	0	23.99	23.91	24.11	0-1	1
	1	2	24.00	23.88	24.14		1
	1	5	23.93	23.97	24.14		1
	3	0	23.83	23.80	24.12		1
	3	2	23.91	24.00	24.14		1
3	3	23.80	23.91	24.16	1		
64QAM	6	0	22.87	22.79	23.13	0-2	2
	1	0	22.99	22.89	23.12	0-2	2
	1	2	23.00	22.92	23.13		2
	1	5	23.01	23.00	23.14		2
	3	0	22.95	22.94	23.12		2
	3	2	22.95	23.17	23.19		2
3	3	22.89	23.03	23.16	2		
	6	0	21.87	21.71	22.06	0-3	3



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 38 of 116

9.4.3

LTE Band 13

Table 9-14
 LTE Band 13 Conducted Powers - 10 MHz Bandwidth



LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.15	0	0
	1	25	22.82		0
	1	49	22.65		0
	25	0	21.96	0-1	1
	25	12	21.87		1
	25	25	21.73		1
	50	0	21.88		1
16QAM	1	0	22.20	0-1	1
	1	25	22.08		1
	1	49	22.20		1
	25	0	20.62	0-2	2
	25	12	20.72		2
	25	25	20.57		2
	50	0	20.70		2
64QAM	1	0	21.14	0-2	2
	1	25	21.20		2
	1	49	21.17		2
	25	0	19.79	0-3	3
	25	12	19.67		3
	25	25	19.71		3
	50	0	19.85		3

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 39 of 116

**Table 9-15
LTE Band 13 Conducted Powers - 5 MHz Bandwidth**

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.68	0	0
	1	12	22.66		0
	1	24	22.66		0
	12	0	21.65	0-1	1
	12	6	21.64		1
	12	13	21.60		1
	25	0	21.67		1
16QAM	1	0	22.06	0-1	1
	1	12	22.00		1
	1	24	21.96		1
	12	0	20.60	0-2	2
	12	6	20.60		2
	12	13	20.60		2
	25	0	20.55		2
64QAM	1	0	21.00	0-2	2
	1	12	20.93		2
	1	24	20.92		2
	12	0	19.77	0-3	3
	12	6	19.77		3
	12	13	19.74		3
	25	0	19.60		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 40 of 116

9.4.4

LTE Band 26 (Cell)

Table 9-16
 LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.13	0	0
	1	36	24.92		0
	1	74	25.20		0
	36	0	23.92	0-1	1
	36	18	24.00		1
	36	37	23.91		1
	75	0	23.99		1
16QAM	1	0	24.03	0-1	1
	1	36	24.14		1
	1	74	24.19		1
	36	0	23.04	0-2	2
	36	18	23.08		2
	36	37	23.02		2
	75	0	23.03		2
64QAM	1	0	23.20	0-2	2
	1	36	22.95		2
	1	74	23.09		2
	36	0	21.99	0-3	3
	36	18	22.04		3
	36	37	21.97		3
	75	0	22.02		3

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 41 of 116	

Table 9-17
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	25.00	24.79	24.93	0	0	
	1	25	24.87	24.58	24.80		0	
	1	49	24.82	24.79	24.90		0	
	25	0	23.96	23.84	24.16	0-1	1	
	25	12	23.85	23.75	23.83		1	
	25	25	23.91	23.86	23.86		1	
16QAM	50	0	23.96	23.84	23.96	0-1	1	
	1	0	24.19	24.05	24.06		0-1	1
	1	25	24.16	24.02	23.93			1
	1	49	24.19	24.19	23.80	0-2		1
	25	0	22.99	22.91	23.09		2	
	25	12	22.88	22.72	22.85		2	
64QAM	25	25	22.99	22.87	23.05	0-2	2	
	50	0	22.93	22.87	22.95		2	
	1	0	23.15	23.00	23.10		0-2	2
	1	25	22.95	22.78	22.92	2		
	1	49	22.97	23.00	22.90	0-3		2
	25	0	21.93	21.80	22.00		3	
25	12	21.94	21.71	21.87	3			
25	25	21.98	21.82	22.02	0-3	3		
50	0	22.00	21.89	22.03		3		

Table 9-18
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.94	24.79	24.88	0	0	
	1	12	24.77	24.72	24.70		0	
	1	24	24.82	24.79	24.59		0	
	16QAM	12	0	23.91	23.71	23.86	0-1	1
		12	6	23.88	23.81	23.73		1
		12	13	23.75	23.76	23.66		1
25		0	23.83	23.70	23.58	1		
64QAM	1	0	24.19	24.00	24.14	0-1	1	
	1	12	24.16	24.12	24.20		1	
	1	24	24.14	24.02	23.87		1	
	12	0	22.98	22.77	22.82	0-2	2	
	12	6	22.94	22.81	22.75		2	
64QAM	12	13	22.78	22.81	22.75	0-2	2	
	25	0	22.81	22.75	22.80		2	
	1	0	23.11	22.91	23.15		0-2	2
	1	12	23.07	22.97	22.80	2		
	1	24	22.94	23.00	22.65	2		
	12	0	22.04	21.77	21.84	0-3		3
	12	6	21.95	21.86	21.78		3	
12	13	21.80	21.81	21.75	3			
25	0	21.80	21.72	21.88	0-3	3		





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 42 of 116	

Table 9-19
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.00	24.80	24.74	0	0
	1	7	24.95	24.81	24.60		0
	1	14	24.85	24.81	24.56		0
	8	0	23.78	23.70	23.77	0-1	1
	8	4	23.82	23.70	23.75		1
	8	7	23.76	23.75	23.74		1
	15	0	23.78	23.77	23.65		1
16QAM	1	0	24.19	24.06	23.86	0-1	1
	1	7	24.10	24.11	23.80		1
	1	14	23.98	23.99	23.60		1
	8	0	22.86	22.73	22.72	0-2	2
	8	4	22.94	22.76	22.76		2
	8	7	22.89	22.82	22.79		2
	15	0	22.85	22.77	22.69		2
64QAM	1	0	23.09	23.03	22.90	0-2	2
	1	7	23.20	23.00	22.82		2
	1	14	23.06	22.94	22.73		2
	8	0	21.90	21.77	21.71	0-3	3
	8	4	21.95	21.70	21.71		3
	8	7	21.93	21.80	21.72		3
	15	0	21.81	21.78	21.70		3

Table 9-20
LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.92	24.66	24.72	0	0
	1	2	24.95	24.68	24.88		0
	1	5	24.85	24.81	24.72		0
	3	0	24.78	24.73	24.60		0
	3	2	24.79	24.70	24.68		0
	3	3	24.81	24.75	24.54		0
	6	0	23.81	23.61	23.67	0-1	1
16QAM	1	0	24.15	23.93	23.73	0-1	1
	1	2	24.19	23.88	23.66		1
	1	5	24.03	23.82	23.60		1
	3	0	23.90	23.82	23.75		1
	3	2	23.88	23.89	23.78		1
	3	3	23.83	23.81	23.75		1
	6	0	22.90	22.69	22.80	0-2	2
64QAM	1	0	23.15	22.80	22.78	0-2	2
	1	2	23.12	22.77	22.79		2
	1	5	23.06	22.85	22.78		2
	3	0	22.92	22.81	22.83		2
	3	2	22.90	22.83	22.88		2
	3	3	22.84	22.70	22.76		2
	6	0	21.88	21.60	21.66	0-3	3

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 43 of 116

9.4.5

LTE Band 66 (AWS)

Table 9-21
LTE Band 66 (AWS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.40	24.32	24.22	0	0	
	1	50	24.18	23.97	23.94		0	
	1	99	24.23	24.14	24.11		0	
	50	0	23.09	23.08	23.02	0-1	1	
	50	25	23.01	23.03	22.92		1	
	50	50	23.06	23.06	22.83		1	
16QAM	100	0	23.07	23.06	22.95	0-1	1	
	1	0	23.11	23.40	23.40		0-1	1
	1	50	23.08	23.32	23.34			1
	1	99	23.13	23.14	23.21	0-2		1
	50	0	22.07	22.13	21.99		2	
	50	25	21.99	22.04	21.89		2	
64QAM	50	50	22.08	22.11	21.81	0-2	2	
	100	0	22.12	22.12	21.91		2	
	1	0	22.40	22.40	22.38		0-2	2
	1	50	22.34	22.24	22.06	2		
	1	99	22.33	22.06	22.23	0-3		2
	50	0	21.02	21.21	21.02		3	
50	25	21.03	21.15	20.94	3			
64QAM	50	50	21.06	21.12	20.89	0-3	3	
	100	0	21.08	21.13	20.85		3	

Table 9-22
LTE Band 66 (AWS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.38	24.29	24.17	0	0	
	1	36	24.19	24.01	23.98		0	
	1	74	24.02	24.11	24.05		0	
	36	0	22.93	22.88	22.74	0-1	1	
	36	18	22.91	22.89	22.70		1	
	36	37	22.73	22.82	22.67		1	
16QAM	75	0	22.86	22.90	22.80	0-1	1	
	1	0	22.93	23.11	22.95		0-1	1
	1	36	23.07	23.07	22.96			1
	1	74	22.99	23.06	22.73	0-2		1
	36	0	21.91	21.91	21.84		2	
	36	18	21.86	21.91	21.81		2	
64QAM	36	37	21.75	21.87	21.61	0-2	2	
	75	0	21.82	21.86	21.75		2	
	1	0	22.10	22.10	21.94		0-2	2
	1	36	22.10	22.36	21.93	2		
	1	74	22.06	22.18	21.85	0-3		2
	36	0	20.93	20.90	20.86		3	
36	18	20.94	20.90	20.72	3			
64QAM	36	37	20.78	20.89	20.59	0-3	3	
	75	0	20.78	20.81	20.69		3	



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 44 of 116

Table 9-23
LTE Band 66 (AWS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.39	24.20	24.14	0	0	
	1	25	24.16	23.79	23.65		0	
	1	49	24.38	24.25	23.77		0	
	25	0	23.06	23.05	22.92	0-1	1	
	25	12	22.92	22.86	22.63		1	
	25	25	22.85	22.75	22.58		1	
16QAM	50	0	22.92	22.86	22.74	0-1	1	
	1	0	23.26	23.05	22.81		0-1	1
	1	25	23.12	23.21	22.71			1
	1	49	23.23	22.99	22.77	0-2		1
	25	0	21.97	21.84	21.90		2	
	25	12	21.91	21.83	21.66		2	
64QAM	25	25	21.87	21.78	21.66	0-2	2	
	50	0	21.83	21.72	21.69		2	
	1	0	22.07	21.94	21.90		0-2	2
	1	25	21.99	21.70	21.48	2		
	1	49	22.08	21.95	21.61	0-3		2
	25	0	21.00	20.86	20.88		3	
	25	12	20.94	20.81	20.58		3	
	25	25	20.83	20.73	20.62	0-3	3	
50	0	20.92	20.82	20.74	3			

Table 9-24
LTE Band 66 (AWS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]		
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)				
			Conducted Power [dBm]						
QPSK	1	0	24.32	24.09	23.80	0	0		
	1	12	24.12	23.98	23.72		0		
	1	24	24.05	23.92	23.60		0		
	16QAM	12	0	23.00	22.98	22.80	0-1	1	
		12	6	22.95	22.72	22.53		1	
		12	13	22.85	22.68	22.50		1	
25		0	22.88	22.81	22.70	1			
64QAM	1	0	23.17	23.11	22.92	0-1	1		
	1	12	23.29	23.07	22.98		1		
	1	24	23.13	22.95	22.60		1		
	16QAM	12	0	21.91	21.75	21.73	0-2	2	
		12	6	21.88	21.75	21.60		2	
		12	13	21.86	21.73	21.60		2	
64QAM		25	0	21.89	21.77	21.60	0-2	2	
		1	0	22.13	22.17	21.88		0-3	2
		1	12	22.12	22.03	21.77			2
	1	24	22.00	21.88	21.58	0-3	2		
	12	0	21.00	20.86	20.80		3		
	12	6	20.95	20.82	20.53		3		
64QAM	12	13	20.96	20.77	20.67	0-3	3		
	25	0	20.90	20.75	20.58		3		



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 45 of 116	

Table 9-25
LTE Band 66 (AWS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.12	24.05	0	0
	1	7	24.29	24.25	23.94		0
	1	14	24.13	24.13	23.87		0
	8	0	23.02	23.06	22.90	0-1	1
	8	4	22.95	22.87	22.57		1
	8	7	22.80	22.77	22.55		1
	15	0	22.85	22.64	22.62		1
16QAM	1	0	23.00	22.94	22.72	0-1	1
	1	7	23.05	22.89	22.77		1
	1	14	22.94	22.75	22.63		1
	8	0	21.91	21.69	22.20	0-2	2
	8	4	21.96	21.75	21.62		2
	8	7	21.88	21.39	21.48		2
	15	0	21.85	21.63	21.56		2
64QAM	1	0	22.08	21.88	21.86	0-2	2
	1	7	22.00	22.07	21.65		2
	1	14	22.05	21.60	21.62		2
	8	0	20.92	20.84	20.60	0-3	3
	8	4	21.03	20.77	20.59		3
	8	7	20.95	20.73	20.49		3
	15	0	20.90	20.70	20.56		3

Table 9-26
LTE Band 66 (AWS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.11	23.95	0	0
	1	2	24.38	24.13	24.00		0
	1	5	24.23	24.15	23.88		0
	3	0	23.91	23.79	23.58	0-1	0
	3	2	24.01	23.81	23.64		0
	3	3	23.83	23.85	23.58		0
	6	0	22.95	22.77	22.62		1
16QAM	1	0	23.20	23.10	22.82	0-1	1
	1	2	23.17	23.05	22.92		1
	1	5	23.09	23.00	22.83		1
	3	0	23.10	22.84	22.70	0-2	1
	3	2	23.23	23.00	22.76		1
	3	3	23.04	23.00	22.68		1
	6	0	22.04	21.91	21.71		2
64QAM	1	0	22.17	22.07	21.86	0-2	2
	1	2	22.13	21.88	21.79		2
	1	5	22.12	21.99	21.79		2
	3	0	22.12	21.95	21.82	0-3	2
	3	2	22.14	22.01	21.74		2
	3	3	22.10	22.01	21.73		2
	6	0	20.94	20.89	20.60		3



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 46 of 116

Table 9-27
LTE Band 66 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.90	22.82	22.85	0	0
	1	50	22.72	22.72	22.55		0
	1	99	22.83	22.87	22.83		0
	50	0	22.87	22.85	22.82	0-1	0
	50	25	22.83	22.74	22.77		0
	50	50	22.90	22.84	22.74		0
	100	0	22.79	22.81	22.88		0
16QAM	1	0	22.74	22.77	22.86	0-1	0
	1	50	22.59	22.81	22.74		0
	1	99	22.87	22.89	22.83		0
	50	0	22.26	22.31	22.40	0-2	0.5
	50	25	22.36	22.26	22.32		0.5
	50	50	22.31	22.30	22.26		0.5
	100	0	22.37	22.38	22.31		0.5
64QAM	1	0	22.23	22.39	22.39	0-2	0.5
	1	50	22.35	22.13	22.33		0.5
	1	99	22.27	22.40	22.40		0.5
	50	0	21.34	21.36	21.36	0-3	1.5
	50	25	21.27	21.29	21.28		1.5
	50	50	21.36	21.31	21.33		1.5
	100	0	21.36	21.34	21.29		1.5

Table 9-28
LTE Band 66 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.65	22.57	22.44	0	0
	1	36	22.72	22.52	22.60		0
	1	74	22.73	22.60	22.78		0
	36	0	22.62	22.66	22.50	0-1	0
	36	18	22.68	22.65	22.54		0
	36	37	22.60	22.68	22.47		0
	75	0	22.58	22.79	22.45		0
16QAM	1	0	22.59	22.80	22.71	0-1	0
	1	36	22.45	22.77	22.90		0
	1	74	22.56	22.69	22.57		0
	36	0	22.36	22.24	22.10	0-2	0.5
	36	18	22.34	22.28	22.11		0.5
	36	37	22.05	22.23	21.98		0.5
	75	0	22.15	22.09	22.08		0.5
64QAM	1	0	22.40	22.11	22.07	0-2	0.5
	1	36	22.31	21.94	22.28		0.5
	1	74	22.22	22.03	22.23		0.5
	36	0	21.28	21.28	21.36	0-3	1.5
	36	18	21.20	21.25	21.12		1.5
	36	37	21.35	21.21	21.12		1.5
	75	0	21.30	21.21	21.23		1.5



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 47 of 116	

Table 9-29
LTE Band 66 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.67	22.59	22.70	0	0
	1	25	22.60	22.55	22.51		0
	1	49	22.56	22.73	22.80		0
	25	0	22.65	22.46	22.62	0-1	0
	25	12	22.62	22.50	22.66		0
	25	25	22.58	22.44	22.64		0
16QAM	50	0	22.63	22.43	22.58	0-1	0
	1	0	22.56	22.75	22.60		0
	1	25	22.46	22.88	22.57		0
	1	49	22.60	22.81	22.45	0-2	0
	25	0	22.11	22.34	22.24		0.5
	25	12	22.23	22.25	22.22		0.5
64QAM	25	25	22.32	22.36	22.12	0-2	0.5
	50	0	22.29	22.21	22.24		0.5
	1	0	22.32	22.32	22.25		0.5
	1	25	22.26	22.28	22.30	0-3	0.5
	1	49	22.30	22.24	22.32		0.5
	25	0	21.25	21.28	21.26		1.5
64QAM	25	12	21.34	21.25	21.12	0-3	1.5
	25	25	21.35	21.21	21.12		1.5
	50	0	21.30	21.21	21.23	1.5	

Table 9-30
LTE Band 66 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.67	22.81	22.78	0	0
	1	12	22.60	22.55	22.64		0
	1	24	22.56	22.73	22.67		0
	12	0	22.65	22.69	22.72	0-1	0
	12	6	22.62	22.70	22.68		0
	12	13	22.58	22.77	22.76		0
16QAM	25	0	22.63	22.67	22.81	0-1	0
	1	0	22.78	22.78	22.51		0
	1	12	22.73	22.70	22.48		0
	1	24	22.68	22.60	22.36	0-2	0
	12	0	22.11	22.04	22.02		0.5
	12	6	22.23	21.95	22.09		0.5
64QAM	12	13	22.08	21.98	22.11	0-2	0.5
	25	0	22.01	21.99	22.12		0.5
	1	0	22.34	22.24	22.27		0-3
	1	12	22.33	22.19	22.12	0.5	
	1	24	22.20	22.20	22.14	0.5	
	64QAM	12	0	20.96	20.95	20.99	0-3
12		6	20.92	20.98	20.92	1.5	
12		13	20.95	20.93	20.93	1.5	
25		0	21.02	21.03	20.99	1.5	





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 48 of 116	

Table 9-31
LTE Band 66 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.74	22.80	22.80	0	0
	1	7	22.69	22.53	22.66		0
	1	14	22.56	22.58	22.57		0
	8	0	22.63	22.59	22.44	0-1	0
	8	4	22.67	22.52	22.46		0
	8	7	22.63	22.50	22.44		0
	15	0	22.68	22.56	22.44		0
16QAM	1	0	22.61	22.78	22.62	0-1	0
	1	7	22.77	22.69	22.83		0
	1	14	22.67	22.89	22.47		0
	8	0	22.23	22.10	22.09	0-2	0.5
	8	4	22.16	22.13	22.11		0.5
	8	7	22.19	22.10	22.17		0.5
	15	0	22.25	22.11	22.12		0.5
64QAM	1	0	22.33	22.24	22.27	0-2	0.5
	1	7	22.22	22.19	22.25		0.5
	1	14	22.29	22.14	22.22		0.5
	8	0	21.24	21.29	21.16	0-3	1.5
	8	4	21.26	21.23	21.12		1.5
	8	7	21.23	21.21	21.13		1.5
	15	0	21.33	21.29	21.19		1.5

Table 9-32
LTE Band 66 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.70	22.74	22.90	0	0
	1	2	22.59	22.63	22.57		0
	1	5	22.54	22.52	22.58		0
	3	0	22.51	22.47	22.32	0-1	0
	3	2	22.66	22.66	22.45		0
	3	3	22.60	22.46	22.33		0
	6	0	22.59	22.58	22.42		0
16QAM	1	0	22.44	22.89	22.47	0-1	0
	1	2	22.50	22.83	22.48		0
	1	5	22.55	22.77	22.48		0
	3	0	22.50	22.70	22.40	0-2	0
	3	2	22.59	22.79	22.49		0
	3	3	22.54	22.78	22.42		0
	6	0	22.20	22.23	22.25		0.5
64QAM	1	0	22.23	22.26	22.27	0-2	0.5
	1	2	22.15	22.25	22.28		0.5
	1	5	22.21	22.20	22.30		0.5
	3	0	22.18	22.16	22.08	0-3	0.5
	3	2	22.15	22.18	22.15		0.5
	3	3	22.12	22.20	22.07		0.5
	6	0	21.19	21.09	21.12		1.5

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 49 of 116

9.4.6 LTE Band 25 (PCS)

Table 9-33
LTE Band 25 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.36	24.39	24.40	0	0
	1	50	24.09	24.32	23.91		0
	1	99	24.24	24.30	23.96		0
	50	0	23.23	23.31	23.32	0-1	1
	50	25	23.02	23.29	23.16		1
	50	50	23.06	23.26	23.14		1
	100	0	23.22	23.30	23.31		1
16QAM	1	0	23.40	23.23	23.40	0-1	1
	1	50	23.12	23.00	23.36		1
	1	99	23.37	23.27	23.25		1
	50	0	22.20	21.79	22.18	0-2	2
	50	25	21.94	21.75	22.17		2
	50	50	22.08	21.84	22.10		2
	100	0	22.10	21.89	22.23		2
64QAM	1	0	22.30	22.07	22.40	0-2	2
	1	50	22.23	22.06	22.24		2
	1	99	21.93	22.09	22.24		2
	50	0	21.23	20.77	21.24	0-3	3
	50	25	21.03	20.68	21.15		3
	50	50	21.05	20.74	21.14		3
	100	0	21.02	20.81	21.12		3

Table 9-34
LTE Band 25 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.28	24.10	24.21	0	0
	1	36	24.02	23.88	23.94		0
	1	74	23.52	23.93	23.61		0
	36	0	23.15	23.06	23.07	0-1	1
	36	18	23.00	22.94	22.92		1
	36	37	22.90	22.95	23.00		1
	75	0	22.98	22.95	23.04		1
16QAM	1	0	23.34	23.35	23.36	0-1	1
	1	36	23.09	23.31	23.28		1
	1	74	23.23	23.10	22.81		1
	36	0	22.08	22.03	21.92	0-2	2
	36	18	21.98	21.87	21.93		2
	36	37	21.92	21.88	21.97		2
	75	0	22.08	22.00	22.09		2
64QAM	1	0	22.39	22.30	22.30	0-2	2
	1	36	22.08	22.06	22.00		2
	1	74	21.99	22.19	21.96		2
	36	0	21.07	20.93	20.94	0-3	3
	36	18	21.02	20.98	20.89		3
	36	37	20.88	20.89	20.89		3
	75	0	21.03	20.96	21.00		3



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 50 of 116

Table 9-35
LTE Band 25 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.02	23.96	24.20	0	0
	1	25	24.23	24.00	23.91		0
	1	49	24.15	23.98	23.42		0
	25	0	23.11	23.07	23.39	0-1	1
	25	12	23.00	22.92	23.20		1
	25	25	23.09	22.83	23.07		1
16QAM	50	0	23.11	22.91	23.21	0-1	1
	1	0	23.37	23.26	23.38		1
	1	25	23.34	23.26	23.40		1
	1	49	23.38	23.30	22.65	0-2	1
	25	0	22.20	22.09	22.40		2
	25	12	22.03	21.94	22.23		2
64QAM	25	25	22.10	21.85	22.07	0-2	2
	50	0	22.10	21.96	22.18		2
	1	0	22.15	22.14	22.27		2
	1	25	22.14	21.92	21.87	0-2	2
	1	49	22.11	21.85	21.60		2
	25	0	21.17	21.08	21.38		0-3
25	12	21.10	20.93	21.15	3		
25	25	21.18	20.91	21.25	3		
	50	0	21.14	20.92	21.17		3

Table 9-36
LTE Band 25 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.14	24.08	24.33	0	0
	1	12	24.00	23.90	24.25		0
	1	24	23.91	23.93	23.60		0
	12	0	23.12	22.93	23.30	0-1	1
	12	6	23.04	22.85	23.14		1
	12	13	23.07	22.85	23.08		1
16QAM	25	0	23.03	22.85	23.15	0-1	1
	1	0	23.32	23.19	23.37		1
	1	12	23.35	23.27	23.34		1
	1	24	23.20	23.06	22.81	0-2	1
	12	0	22.08	21.94	22.35		2
	12	6	22.07	21.85	22.02		2
64QAM	12	13	22.12	21.94	22.02	0-2	2
	25	0	21.99	21.93	22.11		2
	1	0	22.25	22.13	22.36		0-2
	1	12	22.17	22.00	22.32	2	
	1	24	22.12	21.94	21.89	2	
	64QAM	12	0	21.20	20.96	21.29	0-3
12		6	21.08	20.94	21.15	3	
12		13	21.12	20.99	21.11	3	
25		0	21.10	20.95	21.13	3	



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 51 of 116	

Table 9-37
LTE Band 25 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.07	23.90	24.26	0	0
	1	7	24.10	23.87	24.04		0
	1	14	24.00	23.75	23.83		0
	8	0	23.15	23.00	23.24	0-1	1
	8	4	23.09	22.94	23.13		1
	8	7	23.03	22.88	23.18		1
16QAM	15	0	23.06	22.91	23.13	0-1	1
	1	0	23.24	23.04	23.39		1
	1	7	23.21	23.12	23.38		1
	1	14	23.20	23.03	23.09	0-2	1
	8	0	22.18	21.95	22.33		2
	8	4	22.08	21.88	22.19		2
64QAM	8	7	22.03	21.87	22.09	0-2	2
	15	0	22.00	21.93	22.11		2
	1	0	22.26	22.00	22.40		0-2
	1	7	22.32	22.11	22.30	2	
	1	14	22.26	22.00	22.18	0-3	
	8	0	21.20	21.01	21.38		3
8	4	21.11	20.96	21.19	3		
64QAM	8	7	21.07	20.90	21.21	0-3	3
	15	0	21.06	20.90	21.07		3

Table 9-38
LTE Band 25 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.04	23.94	24.06	0	0
	1	2	24.16	23.97	24.07		0
	1	5	23.91	23.86	23.78		0
	3	0	23.94	23.84	23.98	0-1	0
	3	2	24.05	23.84	23.92		0
	3	3	23.91	23.74	23.80		0
16QAM	6	0	22.99	22.79	23.07	0-1	1
	1	0	23.18	23.03	23.22		1
	1	2	23.26	23.00	23.24		1
	1	5	23.16	22.89	23.04	0-1	1
	3	0	23.11	22.98	23.15		1
	3	2	23.09	22.94	23.14		1
64QAM	3	3	23.07	22.93	23.00	0-2	1
	6	0	22.04	21.89	22.25		2
	1	0	22.16	22.09	22.34		0-2
	1	2	22.21	22.08	22.27	2	
	1	5	22.15	22.00	22.09	2	
	3	0	22.08	22.02	22.32	0-2	2
3	2	22.17	21.99	22.22	2		
3	3	22.08	21.91	22.13	2		
64QAM	6	0	20.97	20.85	21.06	0-3	3



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 52 of 116	

Table 9-39
LTE Band 25 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.86	22.90	22.82	0	0
	1	50	22.70	22.78	22.58		0
	1	99	22.74	22.76	22.68		0
	50	0	22.78	22.87	22.86	0-1	0
	50	25	22.72	22.70	22.85		0
	50	50	22.75	22.76	22.77		0
	100	0	22.72	22.71	22.78		0
16QAM	1	0	22.81	22.81	22.87	0-1	0
	1	50	22.78	22.83	22.74		0
	1	99	22.88	22.65	22.83		0
	50	0	22.39	22.36	22.34	0-2	0.5
	50	25	22.25	22.26	22.35		0.5
	50	50	22.34	22.26	22.29		0.5
	100	0	22.37	22.34	22.32		0.5
64QAM	1	0	22.34	22.40	22.35	0-2	0.5
	1	50	22.11	22.17	22.33		0.5
	1	99	22.40	22.24	22.25		0.5
	50	0	21.31	21.38	21.39	0-3	1.5
	50	25	21.29	21.28	21.28		1.5
	50	50	21.25	21.22	21.33		1.5
	100	0	21.27	21.22	21.23		1.5

Table 9-40
LTE Band 25 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.77	22.78	22.58	0	0
	1	36	22.57	22.51	22.59		0
	1	74	22.69	22.69	22.49		0
	36	0	22.56	22.58	22.69	0-1	0
	36	18	22.62	22.60	22.74		0
	36	37	22.51	22.61	22.81		0
	75	0	22.62	22.62	22.74		0
16QAM	1	0	22.56	22.58	22.65	0-1	0
	1	36	22.58	22.44	22.67		0
	1	74	22.50	22.60	22.70		0
	36	0	22.20	22.17	22.22	0-2	0.5
	36	18	22.22	22.20	22.30		0.5
	36	37	22.26	22.17	22.36		0.5
	75	0	22.16	22.08	22.35		0.5
64QAM	1	0	22.28	22.25	22.20	0-2	0.5
	1	36	22.21	22.28	22.28		0.5
	1	74	22.24	22.26	22.30		0.5
	36	0	21.29	21.26	21.17	0-3	1.5
	36	18	21.32	21.29	21.20		1.5
	36	37	21.25	21.37	21.19		1.5
	75	0	21.37	21.26	21.15		1.5



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 53 of 116

Table 9-41
LTE Band 25 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.69	22.70	22.69	0	0
	1	25	22.43	22.35	22.55		0
	1	49	22.63	22.53	22.82		0
	25	0	22.62	22.56	22.90	0-1	0
	25	12	22.62	22.55	22.83		0
	25	25	22.69	22.43	22.81		0
16QAM	50	0	22.70	22.51	22.85	0-1	0
	1	0	22.65	22.78	22.79		0
	1	25	22.59	22.54	22.81		0
	1	49	22.40	22.77	22.70	0-2	0
	25	0	22.21	22.30	22.39		0.5
	25	12	22.23	22.28	22.34		0.5
64QAM	25	25	22.16	21.98	22.34	0-2	0.5
	50	0	22.25	22.36	22.36		0.5
	1	0	22.20	22.26	22.22		0.5
	1	25	22.21	22.20	22.19	0-2	0.5
	1	49	22.29	22.23	22.28		0.5
	25	0	21.29	21.25	21.25		0-3
25	12	21.30	21.20	21.20	1.5		
25	25	21.29	21.15	21.21	1.5		
	50	0	21.34	21.25	21.24		1.5

Table 9-42
LTE Band 25 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.75	22.81	22.65	0	0
	1	12	22.84	22.51	22.46		0
	1	24	22.75	22.61	22.66		0
	12	0	22.68	22.48	22.80	0-1	0
	12	6	22.66	22.54	22.79		0
	12	13	22.66	22.58	22.69		0
16QAM	25	0	22.68	22.47	22.80	0-1	0
	1	0	22.78	22.78	22.85		0
	1	12	22.80	22.86	22.80		0
	1	24	22.69	22.61	22.75	0-2	0
	12	0	22.21	22.07	22.36		0.5
	12	6	22.23	22.11	22.34		0.5
64QAM	12	13	22.24	22.07	22.26	0-2	0.5
	25	0	22.12	22.27	22.32		0.5
	1	0	22.22	22.36	22.35		0-2
	1	12	22.25	22.33	22.30	0.5	
	1	24	22.15	22.37	22.27	0.5	
	64QAM	12	0	21.27	21.37	21.24	0-3
12		6	21.25	21.37	21.38	1.5	
12		13	21.23	21.36	21.35	1.5	
25		0	21.26	21.30	21.33	1.5	





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 54 of 116

Table 9-43
LTE Band 25 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.50	22.62	22.78	0	0
	1	7	22.52	22.39	22.89		0
	1	14	22.45	22.36	22.80		0
	8	0	22.58	22.40	22.83	0-1	0
	8	4	22.72	22.46	22.68		0
	8	7	22.58	22.37	22.57		0
	15	0	22.59	22.40	22.80		0
16QAM	1	0	22.56	22.67	22.77	0-1	0
	1	7	22.58	22.67	22.87		0
	1	14	22.48	22.65	22.76		0
	8	0	22.30	22.22	22.37	0-2	0.5
	8	4	22.27	22.19	22.29		0.5
	8	7	22.25	22.30	22.27		0.5
	15	0	22.29	22.25	22.24		0.5
64QAM	1	0	22.15	22.25	22.29	0-2	0.5
	1	7	22.20	22.33	22.32		0.5
	1	14	22.19	22.28	22.31		0.5
	8	0	21.28	21.29	21.37	0-3	1.5
	8	4	21.33	21.33	21.22		1.5
	8	7	21.27	21.31	21.26		1.5
	15	0	21.29	21.12	21.13		1.5

Table 9-44
LTE Band 25 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.55	22.30	22.46	0	0
	1	2	22.55	22.43	22.57		0
	1	5	22.60	22.23	22.42		0
	3	0	22.57	22.30	22.52	0-1	0
	3	2	22.60	22.40	22.56		0
	3	3	22.50	22.22	22.53		0
	6	0	22.57	22.40	22.54		0
16QAM	1	0	22.75	22.64	22.68	0-1	0
	1	2	22.84	22.70	22.70		0
	1	5	22.75	22.54	22.67		0
	3	0	22.64	22.52	22.54	0-2	0
	3	2	22.70	22.60	22.65		0
	3	3	22.60	22.50	22.50		0
	6	0	22.13	21.95	22.13		0.5
64QAM	1	0	22.38	22.18	22.40	0-2	0.5
	1	2	22.25	22.20	22.40		0.5
	1	5	22.33	22.00	22.25		0.5
	3	0	22.17	22.05	22.30	0-3	0.5
	3	2	22.23	21.95	22.21		0.5
	3	3	22.20	21.92	22.20		0.5
	6	0	21.05	20.90	21.05		1.5

FCC ID: ZNFX420TM	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 55 of 116	

9.4.7

LTE Band 41

Table 9-45
LTE Band 41 PC3 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.20	24.16	23.90	24.11	24.12	0	0
	1	50	24.14	24.06	24.07	24.17	23.96		0
	1	99	24.12	24.13	23.92	24.18	24.08		0
	50	0	23.19	23.08	23.06	23.05	22.98	0-1	1
	50	25	23.20	23.04	23.11	23.09	22.97		1
	50	50	23.17	23.02	23.18	23.19	22.96		1
16QAM	100	0	23.16	22.99	23.12	23.07	22.97	0-1	1
	1	0	23.15	23.07	23.00	23.05	23.14		1
	1	50	23.03	23.00	22.96	23.15	22.98		1
	1	99	23.09	23.09	23.10	23.17	23.20	0-2	1
	50	0	22.13	22.15	22.00	22.12	22.00		2
	50	25	22.15	22.14	22.07	22.15	21.96		2
64QAM	50	50	22.02	22.07	22.12	22.11	22.02	0-2	2
	100	0	22.15	22.11	22.19	22.07	22.01		2
	1	0	21.99	22.02	21.85	22.00	22.05		0-3
	1	50	21.92	22.19	21.80	22.08	21.79	2	
	1	99	21.89	22.03	21.88	22.01	21.92	2	
	50	0	21.17	21.20	21.11	21.08	21.13	0-3	3
50	25	21.15	21.13	21.19	21.14	21.07	3		
50	50	21.00	21.03	21.20	21.14	21.03	3		
100	0	21.02	21.05	21.15	21.08	21.10	3		

Table 9-46
LTE Band 41 PC3 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	24.06	24.07	23.52	23.90	24.08	0	0	
	1	36	23.94	23.80	23.66	24.11	23.91		0	
	1	74	23.97	23.86	23.96	24.12	24.12		0	
	36	0	23.14	22.88	22.66	23.05	23.08	0-1	1	
	36	18	23.16	22.86	22.71	23.01	22.87		1	
	36	37	23.11	22.84	22.89	23.11	23.06		1	
16QAM	75	0	23.11	22.83	22.68	23.04	23.09	0-1	1	
	1	0	23.18	22.95	22.66	22.92	23.04		0-2	1
	1	36	23.07	22.77	22.86	23.13	23.14			1
	1	74	23.12	22.73	23.04	23.02	23.09	0-2		1
	36	0	22.09	21.81	21.58	22.07	22.04		2	
	36	18	22.01	21.85	21.79	21.79	22.00		2	
64QAM	36	37	22.03	21.79	21.80	21.83	22.07	0-2	2	
	75	0	22.05	21.82	21.77	22.01	22.08		2	
	1	0	21.88	21.73	22.07	22.03	22.15		0-3	2
	1	36	22.01	21.74	21.80	22.00	21.87	2		
	1	74	22.10	21.79	21.75	22.03	22.07	2		
	36	0	21.08	20.82	20.79	20.98	21.05	0-3	3	
36	18	21.03	20.85	20.77	20.89	21.06	3			
36	37	21.01	20.75	20.82	20.85	21.07	3			
75	0	21.05	20.83	20.79	21.19	21.12	3			



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 56 of 116	

Table 9-47
LTE Band 41 PC3 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.19	24.03	24.00	24.20	24.02	0	0
	1	25	24.06	23.99	23.79	24.11	24.17		0
	1	49	24.16	24.20	23.97	24.10	24.19		0
	25	0	23.16	23.19	23.06	23.12	23.19	0-1	1
	25	12	23.15	23.08	22.82	23.16	23.14		1
	25	25	23.08	23.16	22.80	23.17	23.15		1
16QAM	50	0	23.10	23.15	22.82	23.18	23.18	0-1	1
	1	0	23.11	23.04	22.95	23.10	23.20		1
	1	25	23.06	22.92	22.83	23.17	23.16		1
	1	49	23.03	23.06	23.01	23.18	23.07	0-2	2
	25	0	22.15	22.16	21.75	22.15	22.02		2
	25	12	22.15	22.03	21.72	22.18	22.07		2
64QAM	25	25	22.09	22.09	21.71	22.14	22.12	0-2	2
	50	0	22.14	22.15	21.71	22.09	22.14		2
	1	0	22.08	22.06	22.01	22.16	22.11		0-2
	1	25	22.12	21.76	21.98	22.09	22.10	2	
	1	49	22.06	21.98	22.07	22.17	22.12	2	
	25	0	20.96	21.12	20.79	21.09	21.07	0-3	3
	25	12	21.01	21.00	20.80	21.13	21.15		3
	25	25	20.87	21.05	20.98	21.14	20.98		3
50	0	21.04	21.13	21.02	21.18	20.97	3		

Table 9-48
LTE Band 41 PC3 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	23.85	23.76	23.73	24.14	24.11	0	0	
	1	12	23.71	23.99	23.78	23.85	24.13		0	
	1	24	23.74	23.97	23.79	23.79	24.11		0	
	12	0	22.92	23.04	22.71	23.02	23.06	0-1	1	
	12	6	22.95	23.08	22.70	23.05	23.12		1	
	12	13	22.85	23.06	22.70	23.01	23.09		1	
16QAM	25	0	22.89	23.14	22.79	22.98	23.10	0-1	1	
	1	0	22.76	23.11	22.73	23.12	23.16		0-1	1
	1	12	22.70	23.12	22.82	23.19	23.05			1
	1	24	22.80	23.12	22.71	23.14	23.09	0-2		2
	12	0	21.91	22.17	21.77	22.02	22.11		2	
	12	6	21.88	22.03	21.72	21.98	22.16		2	
64QAM	12	13	21.82	22.04	21.70	22.11	22.17	0-2	2	
	25	0	21.88	22.11	21.78	22.14	22.15		2	
	1	0	22.12	22.16	21.95	22.00	22.20		0-2	2
	1	12	21.97	22.13	22.17	22.16	22.19	2		
	1	24	22.14	22.05	22.18	22.03	22.03	0-3		2
	12	0	20.83	21.18	20.71	21.11	21.12		3	
	12	6	20.82	21.10	20.69	21.15	21.17		3	
	12	13	20.79	21.05	20.80	21.07	21.19		3	
25	0	20.78	21.10	20.76	21.02	21.15	3			





FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 57 of 116

Table 9-49
LTE Band 41 PC2 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth											
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]		
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)				
			Conducted Power [dBm]								
QPSK	1	0	26.96	26.98	26.80	26.80	26.61	0	0		
	1	50	26.81	27.01	26.81	26.88	26.70		0		
	1	99	26.75	27.17	26.89	26.65	26.72		0		
	QPSK	50	0	26.19	26.20	25.71	26.16	26.12	0-1	1	
		50	25	26.18	26.17	25.75	26.17	26.05		1	
		50	50	26.15	26.14	25.77	26.17	26.08		1	
		100	0	26.16	26.18	25.73	26.16	26.13		1	
16QAM		1	0	26.17	26.09	25.93	26.05	25.95		0-1	1
		1	50	26.14	26.13	26.17	26.12	25.92			1
	1	99	26.01	26.20	26.20	26.00	25.82	1			
	16QAM	50	0	25.17	25.11	24.75	24.90	25.11	0-2	2	
		50	25	25.18	25.13	24.76	25.17	25.05		2	
		50	50	25.03	25.13	24.80	25.15	25.04		2	
		100	0	25.18	25.20	24.84	25.13	25.08		2	
64QAM	1	0	25.00	25.00	24.84	24.80	24.87	0-2	2		
	1	50	24.89	24.92	24.92	24.90	24.65		2		
	1	99	24.91	24.91	24.92	25.08	24.75		2		
	64QAM	50	0	24.18	24.20	23.77	24.20	24.13	0-3	3	
		50	25	24.19	24.18	23.73	24.20	24.12		3	
		50	50	24.13	24.19	23.80	24.20	24.12		3	
		100	0	24.16	24.11	23.65	24.15	24.14		3	

Table 9-50
LTE Band 41 PC2 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	26.81	27.12	26.71	27.02	26.94	0	0	
	1	36	26.87	26.93	26.72	26.98	26.71		0	
	1	74	26.76	27.05	26.75	26.93	26.68		0	
	QPSK	36	0	25.74	26.12	25.71	26.13	26.02	0-1	1
		36	18	25.73	26.01	25.82	26.01	26.11		1
		36	37	25.70	26.17	25.79	25.93	26.14		1
		75	0	25.78	26.13	25.87	25.98	26.14		1
16QAM		1	0	25.99	26.12	25.70	26.04	26.00		0-1
	1	36	25.83	26.15	25.85	25.78	26.03	1		
	1	74	25.71	26.12	25.69	25.92	26.07	1		
	16QAM	36	0	24.85	25.09	24.79	25.14	25.12	0-2	2
		36	18	24.81	25.16	24.78	24.97	25.04		2
		36	37	24.70	25.05	24.83	24.73	25.08		2
		75	0	24.79	25.06	24.69	25.02	25.02		2
64QAM	1	0	25.11	25.19	24.83	25.11	25.15	0-2	2	
	1	36	25.14	25.07	24.70	25.12	25.09		2	
	1	74	24.89	25.14	24.70	25.09	25.14		2	
	64QAM	36	0	24.11	24.00	23.96	23.93	24.17	0-3	3
		36	18	24.12	24.05	23.90	23.97	24.15		3
		36	37	24.08	24.03	23.78	24.04	24.14		3
		75	0	24.12	24.15	23.83	24.09	24.13		3



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 58 of 116	

**Table 9-51
LTE Band 41 PC2 Conducted Powers - 10 MHz Bandwidth**

Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
Conducted Power [dBm]										
QPSK	1	0	26.72	27.18	26.84	26.82	27.02	0	0	
	1	25	26.74	27.04	26.72	26.78	26.66		0	
	1	49	26.72	26.94	26.70	26.73	26.69		0	
	16QAM	25	0	25.74	25.96	25.71	25.93	25.97	0-1	1
		25	12	25.72	26.11	25.87	25.81	26.06		1
		25	25	25.74	26.14	25.96	25.73	26.11		1
64QAM		50	0	25.72	26.15	25.74	25.78	26.09	0-1	1
		1	0	26.01	26.19	25.79	25.84	25.95		1
		1	25	25.76	26.20	25.80	25.78	25.98		1
	16QAM	1	49	25.77	25.94	25.69	25.72	26.02	0-2	1
		25	0	24.74	25.07	24.85	24.94	25.07		2
		25	12	24.79	24.97	24.68	24.77	24.99		2
64QAM		25	25	24.77	24.93	24.69	24.78	25.06	0-2	2
		50	0	24.75	25.09	24.76	24.82	24.97		2
		1	0	24.78	25.17	24.92	24.91	25.12		2
	16QAM	1	25	24.97	25.16	24.71	24.92	25.09	0-3	2
		1	49	24.88	25.12	24.80	24.89	25.09		2
		25	0	23.98	23.97	24.07	23.73	24.12		3
64QAM		25	12	24.05	24.11	23.76	23.77	24.10	0-3	3
		25	25	24.01	24.10	23.69	23.84	24.09		3
		50	0	23.94	24.06	23.70	24.10	23.98		3

**Table 9-52
LTE Band 41 PC2 Conducted Powers - 5 MHz Bandwidth**

LTE Band 41 5 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
Conducted Power [dBm]										
QPSK	1	0	26.83	27.05	27.01	27.05	26.77	0	0	
	1	12	26.77	26.94	26.97	27.11	26.69		0	
	1	24	26.70	26.97	26.83	26.95	26.73		0	
	16QAM	12	0	25.98	26.12	25.99	26.05	25.96	0-1	1
		12	6	26.01	25.98	25.86	26.03	25.92		1
		12	13	26.11	25.95	25.90	26.02	25.71		1
64QAM		25	0	26.12	25.98	25.92	26.07	25.86	0-1	1
		1	0	26.14	26.11	26.03	25.89	26.11		1
		1	12	26.09	25.91	25.96	25.92	26.13		1
	16QAM	1	24	26.15	26.17	25.77	25.95	26.07	0-2	1
		12	0	25.19	25.14	25.08	25.05	25.14		2
		12	6	24.98	25.01	25.11	25.07	25.11		2
64QAM		12	13	24.97	24.97	25.00	24.89	24.98	0-2	2
		25	0	24.72	25.03	25.13	24.97	25.12		2
		1	0	25.04	25.13	24.99	25.14	24.78		2
	16QAM	1	12	24.94	25.06	25.09	25.16	24.95	0-2	2
		1	24	25.06	25.16	25.10	25.13	24.82		2
		12	0	23.98	24.18	24.16	24.15	23.96		3
64QAM		12	6	24.09	24.03	24.12	24.20	23.89	0-3	3
		12	13	24.16	23.94	23.96	24.18	23.79		3
		25	0	24.05	23.92	24.02	24.17	23.90		3

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 59 of 116	

9.5 WLAN Conducted Powers

Table 9-53
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	21.73	16.54	16.41
2417	2	N/A	19.49	17.71
2422	3	N/A	21.49	20.32
2427	4	N/A	21.78	20.08
2437	6	21.97	21.89	20.83
2442	7	N/A	20.85	19.81
2452	9	N/A	20.84	19.88
2457	10	N/A	18.96	17.12
2462	11	21.96	16.85	15.94

Table 9-54
5 GHz WLAN Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	17.30	14.28	14.62
5200	40	17.46	14.52	15.24
5220	44	17.51	14.55	15.16
5240	48	17.69	14.58	15.06
5260	52	17.83	14.67	15.28
5280	56	17.73	14.69	15.33
5300	60	17.80	14.77	15.29
5320	64	17.38	14.29	14.78
5500	100	15.50	12.85	13.32
5520	104	17.36	13.80	14.44
5600	120	17.37	14.18	14.73
5620	124	17.47	14.14	14.58
5720	144	16.83	13.96	14.94
5745	149	17.33	13.85	14.90
5765	153	18.34	15.37	15.80
5785	157	18.45	15.42	15.83
5805	161	18.42	15.47	15.92
5825	165	17.05	14.21	14.99





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 60 of 116	

Table 9-55
2.4 GHz WLAN Reduced Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	17.09	12.41	12.67
2417	2	N/A	14.56	14.51
2422	3	N/A	16.48	16.23
2427	4	N/A	17.10	17.09
2432	5	N/A	17.17	16.83
2437	6	17.43	16.96	16.86
2442	7	N/A	15.67	15.77
2447	8	N/A	15.91	15.64
2452	9	N/A	15.94	15.73
2457	10	N/A	13.89	13.79
2462	11	16.84	11.99	11.59

Table 9-56
5 GHz WLAN Reduced Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	12.28	12.18	12.04
5200	40	13.20	13.20	13.10
5220	44	13.20	13.14	13.10
5240	48	13.30	13.34	13.20
5260	52	12.77	12.75	12.75
5280	56	12.80	12.76	12.80
5300	60	12.75	12.69	12.63
5320	64	12.40	12.40	12.30
5500	100	11.07	10.95	11.03
5600	120	12.35	12.40	12.42
5620	124	12.40	12.43	12.41
5720	144	12.20	12.35	12.26
5745	149	12.30	12.33	12.28
5765	153	13.35	13.39	13.54
5785	157	13.50	13.61	13.61
5805	161	13.63	13.68	13.71
5825	165	12.47	12.43	12.41

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 61 of 116

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	11.28	11.04
5230	46	13.04	12.92
5270	54	13.23	13.01
5310	62	11.47	11.19
5510	102	11.27	11.00
5590	118	13.11	12.75
5630	126	12.96	12.79
5710	142	13.14	12.93
5755	151	13.25	12.87
5795	159	13.22	12.93

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.






Figure 9-4
Power Measurement Setup



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 62 of 116	

9.6 Bluetooth Conducted Powers

Table 9-57
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Avg Conducted Power
				[dBm]
2402	1.0	GFSK	0	6.60
2441	1.0	GFSK	39	7.50
2480	1.0	GFSK	78	6.97
2402	2.0	$\pi/4$ -DQPSK	0	5.95
2441	2.0	$\pi/4$ -DQPSK	39	6.91
2480	2.0	$\pi/4$ -DQPSK	78	6.32
2402	3.0	8DPSK	0	6.00
2441	3.0	8DPSK	39	6.96
2480	3.0	8DPSK	78	6.42

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 63 of 116	




Figure 9-5
Bluetooth Transmission Plot

Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.89ms}{3.75ms} * 100\% = 77.1\%$$




Figure 9-6
Power Measurement Setup



FCC ID: ZNFX420TM	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 64 of 116

10 SYSTEM VERIFICATION

10.1 Tissue Verification

**Table 10-1
Measured Head Tissue Properties**



Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
7/10/2019	750H	21.3	680	0.858	41.233	0.888	42.305	-3.38%	-2.53%
			695	0.863	41.192	0.889	42.227	-2.92%	-2.45%
			700	0.864	41.176	0.889	42.201	-2.81%	-2.43%
			710	0.867	41.149	0.890	42.149	-2.58%	-2.37%
			740	0.878	41.075	0.893	41.994	-1.68%	-2.19%
			755	0.883	41.035	0.894	41.916	-1.23%	-2.10%
			770	0.888	40.993	0.895	41.838	-0.78%	-2.02%
7/3/2019	835H	22.0	785	0.893	40.948	0.896	41.760	-0.33%	-1.94%
			820	0.926	42.113	0.899	41.578	3.00%	1.29%
			835	0.932	42.078	0.900	41.500	3.56%	1.39%
7/8/2019	835H	20.0	850	0.937	42.045	0.916	41.500	2.29%	1.31%
			820	0.885	40.118	0.899	41.578	-1.56%	-3.51%
			835	0.890	40.098	0.900	41.500	-1.11%	-3.38%
7/8/2019	1750H	21.0	850	0.896	40.083	0.916	41.500	-2.18%	-3.41%
			1710	1.329	40.120	1.348	40.142	-1.41%	-0.05%
			1750	1.353	40.052	1.371	40.079	-1.31%	-0.07%
7/3/2019	1900H	21.1	1790	1.378	39.983	1.394	40.016	-1.15%	-0.08%
			1850	1.427	40.800	1.400	40.000	1.93%	2.00%
			1880	1.447	40.752	1.400	40.000	3.36%	1.88%
7/8/2019	1900H	21.9	1910	1.467	40.722	1.400	40.000	4.79%	1.81%
			1850	1.425	41.031	1.400	40.000	1.79%	2.58%
			1880	1.444	40.980	1.400	40.000	3.14%	2.45%
7/10/2019	1900H	21.6	1910	1.463	40.934	1.400	40.000	4.50%	2.33%
			1850	1.412	40.289	1.400	40.000	0.86%	0.72%
			1880	1.431	40.266	1.400	40.000	2.21%	0.66%
7/11/2019	2450H	21.3	1910	1.450	40.233	1.400	40.000	3.57%	0.58%
			2400	1.771	39.484	1.756	39.289	0.85%	0.50%
			2450	1.808	39.401	1.800	39.200	0.44%	0.51%
7/15/2019	2450H	20.7	2500	1.847	39.328	1.855	39.136	-0.43%	0.49%
			2400	1.810	38.585	1.756	39.289	3.08%	-1.79%
			2450	1.849	38.492	1.800	39.200	2.72%	-1.81%
7/18/2019	2450H	20.9	2500	1.890	38.417	1.855	39.136	1.89%	-1.84%
			2400	1.770	37.847	1.756	39.289	0.80%	-3.67%
			2450	1.806	37.758	1.800	39.200	0.33%	-3.68%
7/11/2019	2600H	21.3	2500	1.845	37.690	1.855	39.136	-0.54%	-3.69%
			2600	1.926	39.163	1.964	39.009	-1.93%	0.39%
			2650	1.967	39.092	2.018	38.945	-2.53%	0.38%
07/19/2019	5200H-5800H	22.3	2700	2.007	39.002	2.073	38.882	-3.18%	0.31%
			5180	4.480	35.191	4.635	36.009	-3.34%	-2.27%
			5200	4.505	35.161	4.655	35.986	-3.22%	-2.29%
			5220	4.522	35.132	4.676	35.963	-3.29%	-2.31%
			5240	4.542	35.097	4.696	35.940	-3.28%	-2.35%
			5260	4.562	35.050	4.717	35.917	-3.29%	-2.41%
			5280	4.587	35.007	4.737	35.894	-3.17%	-2.47%
			5300	4.611	34.996	4.758	35.871	-3.09%	-2.44%
			5320	4.631	34.961	4.778	35.849	-3.08%	-2.48%
			5500	4.822	34.643	4.963	35.643	-2.84%	-2.81%
			5520	4.845	34.604	4.983	35.620	-2.77%	-2.85%
			5540	4.874	34.565	5.004	35.597	-2.60%	-2.90%
			5560	4.898	34.531	5.024	35.574	-2.51%	-2.93%
			5580	4.919	34.494	5.045	35.551	-2.50%	-2.97%
			5600	4.939	34.452	5.065	35.529	-2.49%	-3.03%
			5620	4.964	34.419	5.086	35.506	-2.40%	-3.06%
			5640	4.990	34.382	5.106	35.483	-2.27%	-3.10%
			5660	5.011	34.342	5.127	35.460	-2.26%	-3.15%
			5680	5.033	34.331	5.147	35.437	-2.21%	-3.12%
			5700	5.057	34.293	5.168	35.414	-2.15%	-3.17%
			5745	5.112	34.202	5.214	35.363	-1.96%	-3.28%
			5765	5.133	34.179	5.234	35.340	-1.93%	-3.29%
			5785	5.155	34.147	5.255	35.317	-1.90%	-3.31%
			5800	5.167	34.116	5.270	35.300	-1.95%	-3.35%
			5805	5.171	34.106	5.275	35.294	-1.97%	-3.37%
			5825	5.195	34.063	5.296	35.271	-1.91%	-3.42%

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 65 of 116

**Table 10-2
Measured Body Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
7/10/2019	750B	24.3	700	0.918	54.770	0.959	55.726	-4.28%	-1.72%
			710	0.927	54.660	0.960	55.687	-3.44%	-1.84%
			740	0.955	54.353	0.963	55.570	-0.83%	-2.19%
			755	0.969	54.191	0.964	55.512	0.52%	-2.38%
			770	0.984	54.036	0.965	55.453	1.97%	-2.56%
			785	0.998	53.883	0.966	55.395	3.31%	-2.73%
7/12/2019	750B	24.8	800	1.013	53.728	0.967	55.336	4.76%	-2.91%
			680	0.918	57.637	0.958	55.804	-4.18%	3.28%
			695	0.923	57.611	0.959	55.745	-3.75%	3.35%
			710	0.928	57.576	0.960	55.687	-3.33%	3.39%
			740	0.939	57.520	0.963	55.570	-2.49%	3.51%
			755	0.944	57.497	0.964	55.512	-2.07%	3.58%
7/9/2019	835B	20.0	820	0.965	55.272	0.969	55.258	-0.41%	0.03%
			835	0.971	55.240	0.970	55.200	0.10%	0.07%
			850	0.977	55.186	0.988	55.154	-1.11%	0.06%
7/11/2019	835B	22.5	820	0.963	54.159	0.969	55.258	-0.62%	-1.99%
			835	0.978	54.026	0.970	55.200	0.82%	-2.13%
			850	0.993	53.887	0.988	55.154	0.51%	-2.30%
7/3/2019	1750B	21.9	1710	1.497	51.941	1.463	53.537	2.32%	-2.98%
			1750	1.543	51.760	1.488	53.432	3.70%	-3.13%
			1790	1.586	51.573	1.514	53.326	4.76%	-3.29%
7/8/2019	1750B	22.4	1710	1.421	52.883	1.463	53.537	-2.87%	-1.22%
			1750	1.467	52.748	1.488	53.432	-1.41%	-1.28%
			1790	1.509	52.593	1.514	53.326	-0.33%	-1.37%
7/3/2019	1900B	23.4	1850	1.521	53.366	1.520	53.300	0.07%	0.12%
			1880	1.556	53.257	1.520	53.300	2.37%	-0.08%
			1910	1.591	53.169	1.520	53.300	4.67%	-0.25%
7/8/2019	1900B	22.6	1850	1.526	52.767	1.520	53.300	0.39%	-1.00%
			1880	1.561	52.673	1.520	53.300	2.70%	-1.18%
			1910	1.594	52.587	1.520	53.300	4.87%	-1.34%
7/10/2019	1900B	22.6	1850	1.527	51.963	1.520	53.300	0.46%	-2.51%
			1880	1.563	51.862	1.520	53.300	2.83%	-2.70%
			1910	1.595	51.774	1.520	53.300	4.93%	-2.86%
7/29/2019	1900B	23.5	1850	1.494	52.299	1.520	53.300	-1.71%	-1.88%
			1880	1.530	52.200	1.520	53.300	0.66%	-2.06%
			1910	1.563	52.136	1.520	53.300	2.83%	-2.18%
7/10/2019	2450B	23.0	2400	1.979	51.763	1.902	52.767	4.05%	-1.90%
			2450	2.035	51.648	1.950	52.700	4.36%	-2.00%
			2500	2.094	51.512	2.021	52.636	3.61%	-2.14%
			2600	2.218	51.237	2.163	52.509	2.54%	-2.42%
			2650	2.282	51.064	2.234	52.445	2.15%	-2.63%
			2700	2.343	50.927	2.305	52.382	1.65%	-2.78%
7/18/2019	2450B	22.8	2400	1.983	51.640	1.902	52.767	4.26%	-2.14%
			2450	2.041	51.486	1.950	52.700	4.67%	-2.30%
			2500	2.103	51.332	2.021	52.636	4.06%	-2.48%
07/08/2019	5200B-5800B	21.3	5240	5.441	49.374	5.346	48.960	1.78%	0.85%
			5260	5.471	49.331	5.369	48.933	1.90%	0.81%
			5280	5.497	49.307	5.393	48.906	1.93%	0.82%
			5300	5.523	49.277	5.416	48.879	1.98%	0.81%
			5320	5.553	49.236	5.439	48.851	2.10%	0.79%
			5500	5.813	48.901	5.650	48.607	2.88%	0.60%
			5520	5.847	48.873	5.673	48.580	3.07%	0.60%
			5540	5.877	48.809	5.696	48.553	3.18%	0.53%
			5560	5.908	48.761	5.720	48.526	3.29%	0.48%
			5580	5.941	48.730	5.743	48.499	3.45%	0.48%
			5600	5.968	48.695	5.766	48.471	3.50%	0.46%
			5620	5.997	48.660	5.790	48.444	3.58%	0.45%
			5700	6.127	48.517	5.883	48.336	4.15%	0.37%
			5745	6.197	48.434	5.936	48.275	4.40%	0.33%
			5765	6.226	48.367	5.959	48.248	4.48%	0.25%
			5785	6.257	48.336	5.982	48.220	4.60%	0.24%
			5800	6.281	48.327	6.000	48.200	4.68%	0.26%
			5805	6.289	48.321	6.006	48.193	4.71%	0.27%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 66 of 116

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.


Table 10-3
System Verification Results – 1g

SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
E	750	HEAD	07/10/2019	22.5	21.3	0.200	1003	3589	1.540	8.280	7.700	-7.00%
H	835	HEAD	07/03/2019	21.9	22.0	0.200	4d132	7406	2.050	9.590	10.250	6.88%
H	835	HEAD	07/08/2019	20.5	20.0	0.200	4d132	7406	1.900	9.590	9.500	-0.94%
E	1750	HEAD	07/08/2019	21.4	21.0	0.100	1008	3589	3.730	36.200	37.300	3.04%
G	1900	HEAD	07/03/2019	22.2	21.1	0.100	5d149	7409	4.080	39.300	40.800	3.82%
G	1900	HEAD	07/08/2019	22.0	21.9	0.100	5d149	7409	3.990	39.300	39.900	1.53%
G	1900	HEAD	07/10/2019	21.1	21.6	0.100	5d149	7409	4.030	39.300	40.300	2.54%
E	2450	HEAD	07/01/2019	22.1	21.3	0.100	797	3589	5.320	52.700	53.200	0.95%
E	2450	HEAD	07/15/2019	21.4	20.7	0.100	797	3589	5.210	52.700	52.100	-1.14%
E	2450	HEAD	07/18/2019	23.8	20.9	0.100	797	3589	5.350	52.700	53.500	1.52%
E	2600	HEAD	07/01/2019	22.1	21.3	0.100	1126	3589	5.750	54.500	57.500	5.50%
H	5250	HEAD	07/19/2019	23.4	22.3	0.050	1237	7406	3.910	81.300	78.200	-3.81%
H	5600	HEAD	07/19/2019	23.4	22.3	0.050	1237	7406	4.000	85.700	80.000	-6.65%
H	5750	HEAD	07/19/2019	23.4	22.3	0.050	1237	7406	3.980	80.600	79.600	-1.24%
D	750	BODY	07/10/2019	23.5	22.5	0.200	1003	3914	1.840	8.580	9.200	7.23%
D	750	BODY	07/12/2019	23.4	22.9	0.200	1003	3914	1.740	8.580	8.700	1.40%
O	835	BODY	07/09/2019	20.3	20.0	0.200	4d047	7538	2.040	9.470	10.200	7.71%
H	835	BODY	07/11/2019	21.8	22.5	0.200	4d132	7406	2.070	9.670	10.350	7.03%
I	1750	BODY	07/03/2019	23.9	21.9	0.100	1150	7357	3.780	36.600	37.800	3.28%
I	1750	BODY	07/08/2019	22.3	21.6	0.100	1150	7357	3.810	36.600	38.100	4.10%
J	1900	BODY	07/03/2019	21.9	23.4	0.100	5d080	7488	4.210	39.200	42.100	7.40%
J	1900	BODY	07/08/2019	20.1	22.6	0.100	5d080	7488	4.160	39.200	41.600	6.12%
J	1900	BODY	07/10/2019	22.9	22.6	0.100	5d080	7488	4.090	39.200	40.900	4.34%
J	1900	BODY	07/29/2019	20.7	23.5	0.100	5d080	7488	4.100	39.200	41.000	4.59%
K	2450	BODY	07/10/2019	22.7	22.5	0.100	719	7417	5.140	50.100	51.400	2.59%
K	2450	BODY	07/18/2019	22.6	22.2	0.100	719	7417	5.220	50.100	52.200	4.19%
K	2600	BODY	07/10/2019	22.7	22.5	0.100	1004	7417	5.340	54.800	53.400	-2.55%
L	5250	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	3.670	75.900	73.400	-3.29%
L	5600	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	4.240	79.900	84.800	6.13%
L	5750	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	3.680	76.700	73.600	-4.04%

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 67 of 116	

**Table 10-4
System Verification Results – 10g**



System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
I	1750	BODY	07/08/2019	22.3	21.6	0.100	1150	7357	2.010	19.400	20.100	3.61%
J	1900	BODY	07/10/2019	22.9	22.6	0.100	5d080	7488	2.100	20.600	21.000	1.94%
L	5250	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	1.020	21.100	20.400	-3.32%
L	5600	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	1.160	22.300	23.200	4.04%
L	5750	BODY	07/08/2019	22.2	21.6	0.050	1057	7308	1.030	21.200	20.600	-2.83%



**Figure 10-1
System Verification Setup Diagram**



**Figure 10-2
System Verification Setup Photo**

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 68 of 116

11 SAR DATA SUMMARY



11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.20	0.01	Right	Cheek	05574	1	1:8.3	0.213	1.122	0.239	
836.60	190	GSM 850	GSM	32.7	32.20	0.02	Right	Tilt	05574	1	1:8.3	0.103	1.122	0.116	
836.60	190	GSM 850	GSM	32.7	32.20	-0.04	Left	Cheek	05574	1	1:8.3	0.203	1.122	0.228	
836.60	190	GSM 850	GSM	32.7	32.20	0.00	Left	Tilt	05574	1	1:8.3	0.102	1.122	0.114	
836.60	190	GSM 850	GPRS	30.7	30.44	0.10	Right	Cheek	05574	3	1:2.76	0.426	1.062	0.452	A1
836.60	190	GSM 850	GPRS	30.7	30.44	-0.01	Right	Tilt	05574	3	1:2.76	0.199	1.062	0.211	
836.60	190	GSM 850	GPRS	30.7	30.44	0.07	Left	Cheek	05574	3	1:2.76	0.410	1.062	0.435	
836.60	190	GSM 850	GPRS	30.7	30.44	-0.03	Left	Tilt	05574	3	1:2.76	0.203	1.062	0.216	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	31.2	31.19	-0.03	Right	Cheek	05566	1	1:8.3	0.156	1.002	0.156	
1880.00	661	GSM 1900	GSM	31.2	31.19	0.02	Right	Tilt	05566	1	1:8.3	0.134	1.002	0.134	
1880.00	661	GSM 1900	GSM	31.2	31.19	0.06	Left	Cheek	05566	1	1:8.3	0.296	1.002	0.297	
1880.00	661	GSM 1900	GSM	31.2	31.19	0.03	Left	Tilt	05566	1	1:8.3	0.148	1.002	0.148	
1880.00	661	GSM 1900	GPRS	27.2	26.54	-0.03	Right	Cheek	05566	3	1:2.76	0.176	1.164	0.205	
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.14	Right	Tilt	05566	3	1:2.76	0.144	1.164	0.168	
1880.00	661	GSM 1900	GPRS	27.2	26.54	-0.09	Left	Cheek	05566	3	1:2.76	0.323	1.164	0.376	A2
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.09	Left	Tilt	05566	3	1:2.76	0.169	1.164	0.197	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 69 of 116

**Table 11-3
UMTS 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.04	Right	Cheek	05558	1:1	0.280	1.012	0.283	A3
836.60	4183	UMTS 850	RMC	25.2	25.15	0.06	Right	Tilt	05558	1:1	0.143	1.012	0.145	
836.60	4183	UMTS 850	RMC	25.2	25.15	0.02	Left	Cheek	05558	1:1	0.279	1.012	0.282	
836.60	4183	UMTS 850	RMC	25.2	25.15	0.02	Left	Tilt	05558	1:1	0.154	1.012	0.156	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (W/kg) averaged over 1 gram							

**Table 11-4
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.08	Right	Cheek	05574	1:1	0.216	1.050	0.227	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.05	Right	Tilt	05574	1:1	0.147	1.050	0.154	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.01	Left	Cheek	05574	1:1	0.407	1.050	0.427	A4
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.00	Left	Tilt	05574	1:1	0.205	1.050	0.215	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-5
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.11	Right	Cheek	05566	1:1	0.307	1.002	0.308	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.06	Right	Tilt	05566	1:1	0.302	1.002	0.303	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.07	Left	Cheek	05566	1:1	0.581	1.002	0.582	A5
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.03	Left	Tilt	05566	1:1	0.279	1.002	0.280	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 70 of 116	

**Table 11-6
CDMA BC10 (§90S) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	24.98	0.03	Right	Cheek	05558	1:1	0.200	1.052	0.210	A6
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	24.98	0.07	Right	Tilt	05558	1:1	0.099	1.052	0.104	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	24.98	0.04	Left	Cheek	05558	1:1	0.193	1.052	0.203	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.2	24.98	0.05	Left	Tilt	05558	1:1	0.112	1.052	0.118	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.09	0.07	Right	Cheek	05558	1:1	0.180	1.026	0.185	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.09	0.03	Right	Tilt	05558	1:1	0.092	1.026	0.094	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.09	0.02	Left	Cheek	05558	1:1	0.179	1.026	0.184	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.2	25.09	0.12	Left	Tilt	05558	1:1	0.100	1.026	0.103	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-7
CDMA BC0 (§22H) Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	25.2	25.14	0.06	Right	Cheek	05558	1:1	0.308	1.014	0.312	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	25.2	25.14	0.03	Right	Tilt	05558	1:1	0.145	1.014	0.147	
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	25.2	25.14	-0.03	Left	Cheek	05558	1:1	0.315	1.014	0.319	A7
836.52	384	CDMA BC0 (§22H)	RC3 / SO55	25.2	25.14	-0.02	Left	Tilt	05558	1:1	0.148	1.014	0.150	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	25.2	25.12	0.04	Right	Cheek	05558	1:1	0.290	1.019	0.296	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	25.2	25.12	-0.01	Right	Tilt	05558	1:1	0.138	1.019	0.141	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	25.2	25.12	0.03	Left	Cheek	05558	1:1	0.272	1.019	0.277	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. A	25.2	25.12	0.04	Left	Tilt	05558	1:1	0.145	1.019	0.148	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 71 of 116	

**Table 11-8
PCS CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.01	Right	Cheek	05541	1:1	0.296	1.069	0.316	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	-0.03	Right	Tilt	05541	1:1	0.303	1.069	0.324	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.02	Left	Cheek	05541	1:1	0.629	1.069	0.672	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.06	Left	Tilt	05541	1:1	0.305	1.069	0.326	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.50	0.11	Right	Cheek	05541	1:1	0.293	1.047	0.307	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.50	0.01	Right	Tilt	05541	1:1	0.297	1.047	0.311	
1851.25	25	PCS CDMA	EVDO Rev. A	24.7	24.48	-0.04	Left	Cheek	05541	1:1	0.659	1.052	0.693	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.50	0.04	Left	Cheek	05541	1:1	0.661	1.047	0.692	A8
1908.75	1175	PCS CDMA	EVDO Rev. A	24.7	24.53	-0.01	Left	Cheek	05541	1:1	0.580	1.040	0.603	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.50	0.10	Left	Tilt	05541	1:1	0.323	1.047	0.338	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-9
LTE Band 71 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	-0.14	0	Right	Cheek	QPSK	1	99	05558	1:1	0.228	1.005	0.229	A9
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	-0.10	1	Right	Cheek	QPSK	50	50	05558	1:1	0.156	1.026	0.160	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.00	0	Right	Tilt	QPSK	1	99	05558	1:1	0.119	1.005	0.120	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.08	1	Right	Tilt	QPSK	50	50	05558	1:1	0.083	1.026	0.085	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	-0.04	0	Left	Cheek	QPSK	1	99	05558	1:1	0.216	1.005	0.217	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.07	1	Left	Cheek	QPSK	50	50	05558	1:1	0.148	1.026	0.152	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.03	0	Left	Tilt	QPSK	1	99	05558	1:1	0.120	1.005	0.121	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.02	1	Left	Tilt	QPSK	50	50	05558	1:1	0.082	1.026	0.084	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram												

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 72 of 116	

**Table 11-10
LTE Band 12 Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.02	0	Right	Cheek	QPSK	1	49	05558	1:1	0.231	1.021	0.236	A10
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	-0.01	1	Right	Cheek	QPSK	25	12	05558	1:1	0.189	1.035	0.196	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	-0.12	0	Right	Tilt	QPSK	1	49	05558	1:1	0.121	1.021	0.124	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	0.02	1	Right	Tilt	QPSK	25	12	05558	1:1	0.093	1.035	0.096	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	-0.13	0	Left	Cheek	QPSK	1	49	05558	1:1	0.229	1.021	0.234	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	-0.12	1	Left	Cheek	QPSK	25	12	05558	1:1	0.177	1.035	0.183	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.12	0	Left	Tilt	QPSK	1	49	05558	1:1	0.114	1.021	0.116	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	0.07	1	Left	Tilt	QPSK	25	12	05558	1:1	0.092	1.035	0.095	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-11
LTE Band 13 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	-0.01	0	Right	Cheek	QPSK	1	0	05558	1:1	0.247	1.012	0.250	A11
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	-0.10	1	Right	Cheek	QPSK	25	0	05558	1:1	0.188	1.057	0.199	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.10	0	Right	Tilt	QPSK	1	0	05558	1:1	0.125	1.012	0.127	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.00	1	Right	Tilt	QPSK	25	0	05558	1:1	0.103	1.057	0.109	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.03	0	Left	Cheek	QPSK	1	0	05558	1:1	0.223	1.012	0.226	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.11	1	Left	Cheek	QPSK	25	0	05558	1:1	0.161	1.057	0.170	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.03	0	Left	Tilt	QPSK	1	0	05558	1:1	0.137	1.012	0.139	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.08	1	Left	Tilt	QPSK	25	0	05558	1:1	0.101	1.057	0.107	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-12
LTE Band 26 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.01	0	Right	Cheek	QPSK	1	74	05558	1:1	0.295	1.000	0.295	A12
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.01	1	Right	Cheek	QPSK	36	18	05558	1:1	0.176	1.047	0.184	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.01	0	Right	Tilt	QPSK	1	74	05558	1:1	0.145	1.000	0.145	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	-0.01	1	Right	Tilt	QPSK	36	18	05558	1:1	0.089	1.047	0.093	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.14	0	Left	Cheek	QPSK	1	74	05558	1:1	0.267	1.000	0.267	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.13	1	Left	Cheek	QPSK	36	18	05558	1:1	0.184	1.047	0.193	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.09	0	Left	Tilt	QPSK	1	74	05558	1:1	0.156	1.000	0.156	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.02	1	Left	Tilt	QPSK	36	18	05558	1:1	0.100	1.047	0.105	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 73 of 116	

**Table 11-13
LTE Band 66 (AWS) Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.04	0	Right	Cheek	QPSK	1	0	05574	1:1	0.206	1.000	0.206	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.07	1	Right	Cheek	QPSK	50	0	05574	1:1	0.172	1.074	0.185	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.09	0	Right	Tilt	QPSK	1	0	05574	1:1	0.089	1.000	0.089	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.04	1	Right	Tilt	QPSK	50	0	05574	1:1	0.067	1.074	0.072	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.00	0	Left	Cheek	QPSK	1	0	05574	1:1	0.356	1.000	0.356	A13
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.08	1	Left	Cheek	QPSK	50	0	05574	1:1	0.274	1.074	0.294	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.15	0	Left	Tilt	QPSK	1	0	05574	1:1	0.214	1.000	0.214	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.14	1	Left	Tilt	QPSK	50	0	05574	1:1	0.186	1.074	0.200	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-14
LTE Band 25 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.14	0	Right	Cheek	QPSK	1	0	05566	1:1	0.307	1.000	0.307	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.10	1	Right	Cheek	QPSK	50	0	05566	1:1	0.230	1.019	0.234	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.07	0	Right	Tilt	QPSK	1	0	05566	1:1	0.247	1.000	0.247	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.04	1	Right	Tilt	QPSK	50	0	05566	1:1	0.214	1.019	0.218	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.16	0	Left	Cheek	QPSK	1	0	05566	1:1	0.565	1.000	0.565	A14
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.09	1	Left	Cheek	QPSK	50	0	05566	1:1	0.425	1.019	0.433	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.09	0	Left	Tilt	QPSK	1	0	05566	1:1	0.271	1.000	0.271	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.08	1	Left	Tilt	QPSK	50	0	05566	1:1	0.223	1.019	0.227	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-15
LTE Band 41 Head SAR**

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.03	0	Right	Cheek	QPSK	1	0	05558	1:1.58	0.210	1.000	0.210	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.03	1	Right	Cheek	QPSK	50	25	05558	1:1.58	0.162	1.000	0.162	
Power Class 2	2506.00	39750	Low	LTE Band 41	20	27.2	26.96	-0.07	0	Right	Cheek	QPSK	1	0	05558	1:2.31	0.252	1.057	0.266	A15
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.14	0	Right	Tilt	QPSK	1	0	05558	1:1.58	0.104	1.000	0.104	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.12	1	Right	Tilt	QPSK	50	25	05558	1:1.58	0.081	1.000	0.081	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.04	0	Left	Cheek	QPSK	1	0	05558	1:1.58	0.178	1.000	0.178	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.04	1	Left	Cheek	QPSK	50	25	05558	1:1.58	0.145	1.000	0.145	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.2	24.20	-0.05	0	Left	Tilt	QPSK	1	0	05558	1:1.58	0.085	1.000	0.085	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.2	23.20	0.20	1	Left	Tilt	QPSK	50	25	05558	1:1.58	0.055	1.000	0.055	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 74 of 116	

**Table 11-16
DTS Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	17.5	17.09	0.10	Right	Cheek	1	05699	1	99.9	1.201	0.779	1.099	1.001	0.857	
2437	6	802.11b	DSSS	22	17.5	17.43	0.15	Right	Cheek	1	05699	1	99.9	1.696	1.080	1.016	1.001	1.098	A16
2462	11	802.11b	DSSS	22	17.5	16.84	0.20	Right	Cheek	1	05699	1	99.9	1.216	0.820	1.164	1.001	0.955	
2412	1	802.11b	DSSS	22	17.5	17.09	0.08	Right	Tilt	1	05699	1	99.9	1.047	0.594	1.099	1.001	0.653	
2437	6	802.11b	DSSS	22	17.5	17.43	0.08	Right	Tilt	1	05699	1	99.9	1.507	0.865	1.016	1.001	0.880	
2437	6	802.11b	DSSS	22	17.5	17.43	0.10	Left	Cheek	1	05699	1	99.9	0.758	0.536	1.016	1.001	0.545	
2437	6	802.11b	DSSS	22	17.5	17.43	0.21	Left	Tilt	1	05699	1	99.9	0.740	0.547	1.016	1.001	0.556	
2437	6	802.11b	DSSS	22	17.5	17.43	0.16	Right	Cheek	1	05699	1	99.9	1.532	0.958	1.016	1.001	0.974	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement.

**Table 11-17
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #	
MHz	Ch.												W/kg	(W/kg)			(W/kg)		
5270	54	802.11n	OFDM	40	13.5	13.23	0.10	Right	Cheek	05681	13.5	98.5	1.053	0.539	1.064	1.015	0.582		
5270	54	802.11n	OFDM	40	13.5	13.23	0.15	Right	Tilt	05681	13.5	98.5	0.866	0.413	1.064	1.015	0.446		
5270	54	802.11n	OFDM	40	13.5	13.23	0.11	Left	Cheek	05681	13.5	98.5	0.581	-	1.064	1.015	-		
5270	54	802.11n	OFDM	40	13.5	13.23	0.10	Left	Tilt	05681	13.5	98.5	0.452	-	1.064	1.015	-		
5590	118	802.11n	OFDM	40	13.5	13.11	0.12	Right	Cheek	05681	13.5	98.5	1.458	0.681	1.094	1.015	0.756		
5710	142	802.11n	OFDM	40	13.5	13.14	0.11	Right	Cheek	05681	13.5	98.5	1.856	0.734	1.086	1.015	0.809		
5710	142	802.11n	OFDM	40	13.5	13.14	0.13	Right	Tilt	05681	13.5	98.5	0.989	-	1.086	1.015	-		
5710	142	802.11n	OFDM	40	13.5	13.14	0.12	Left	Cheek	05681	13.5	98.5	1.010	0.397	1.086	1.015	0.438		
5710	142	802.11n	OFDM	40	13.5	13.14	0.19	Left	Tilt	05681	13.5	98.5	0.824	-	1.086	1.015	-		
5765	153	802.11a	OFDM	20	14.0	13.35	0.17	Right	Cheek	05681	6	99.2	2.078	0.796	1.161	1.008	0.932		
5785	157	802.11a	OFDM	20	14.0	13.50	0.11	Right	Cheek	05681	6	99.2	2.082	0.793	1.122	1.008	0.897		
5805	161	802.11a	OFDM	20	14.0	13.63	0.13	Right	Cheek	05681	6	99.2	2.099	0.862	1.089	1.008	0.946	A17	
5805	161	802.11a	OFDM	20	14.0	13.63	0.12	Right	Tilt	05681	6	99.2	1.348	0.600	1.089	1.008	0.659		
5805	161	802.11a	OFDM	20	14.0	13.63	0.18	Left	Cheek	05681	6	99.2	1.319	-	1.089	1.008	-		
5805	161	802.11a	OFDM	20	14.0	13.63	-0.21	Left	Tilt	05681	6	99.2	1.090	-	1.089	1.008	-		
5805	161	802.11a	OFDM	20	14.0	13.63	-0.12	Right	Cheek	05681	6	99.2	0.927	0.821	1.089	1.008	0.901		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1-ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 75 of 116

**Table 11-18
DSS Head SAR**



MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441.00	39	Bluetooth	FHSS	8.0	7.50	-0.01	Right	Cheek	05699	1	77.1	0.084	1.122	1.297	0.122	A18
2441.00	39	Bluetooth	FHSS	8.0	7.50	0.02	Right	Tilt	05699	1	77.1	0.057	1.122	1.297	0.083	
2441.00	39	Bluetooth	FHSS	8.0	7.50	0.15	Left	Cheek	05699	1	77.1	0.043	1.122	1.297	0.063	
2441.00	39	Bluetooth	FHSS	8.0	7.50	0.07	Left	Tilt	05699	1	77.1	0.047	1.122	1.297	0.068	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram									

11.2 Standalone Body-Worn SAR Data

**Table 11-19
GSM/UMTS/CDMA Body-Worn SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.20	0.02	10 mm	05558	1	1:8.3	back	0.280	1.122	0.314	
836.60	190	GSM 850	GPRS	30.7	30.44	-0.05	10 mm	05558	3	1:2.76	back	0.547	1.062	0.581	A19
1880.00	661	GSM 1900	GSM	31.2	31.19	0.07	10 mm	05566	1	1:8.3	back	0.319	1.002	0.320	
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.02	10 mm	05566	3	1:2.76	back	0.331	1.164	0.385	A21
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.02	10 mm	05558	N/A	1:1	back	0.416	1.012	0.421	A23
1712.40	1312	UMTS 1750	RMC	24.4	24.32	0.00	10 mm	05541	N/A	1:1	back	0.962	1.019	0.980	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.06	10 mm	05541	N/A	1:1	back	1.060	1.050	1.113	A24
1752.60	1513	UMTS 1750	RMC	24.4	24.02	0.02	10 mm	05541	N/A	1:1	back	0.963	1.091	1.051	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	-0.11	10 mm	05541	N/A	1:1	back	1.010	1.050	1.061	
1852.40	9262	UMTS 1900	RMC	24.4	24.38	0.00	10 mm	05574	N/A	1:1	back	0.723	1.005	0.727	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.02	10 mm	05574	N/A	1:1	back	0.717	1.002	0.718	
1907.60	9538	UMTS 1900	RMC	24.4	24.40	-0.19	10 mm	05574	N/A	1:1	back	0.728	1.000	0.728	A25
820.10	564	CDMA BC10 (§90S)	TDSO / SO32	25.2	25.03	0.10	10 mm	05558	N/A	1:1	back	0.333	1.040	0.346	A27
836.52	384	CDMA BC0 (§22H)	TDSO / SO32	25.2	25.05	-0.04	10 mm	05558	N/A	1:1	back	0.413	1.035	0.427	A29
1851.25	25	PCS CDMA	TDSO / SO32	24.7	24.43	-0.01	10 mm	05574	N/A	1:1	back	0.744	1.064	0.792	
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.41	-0.01	10 mm	05574	N/A	1:1	back	0.756	1.069	0.808	
1908.75	1175	PCS CDMA	TDSO / SO32	24.7	24.36	-0.11	10 mm	05574	N/A	1:1	back	0.768	1.081	0.830	A31
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entry represents variability measurement.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 76 of 116	

**Table 11-20
LTE Body-Worn SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.02	0	05566	QPSK	1	99	10 mm	back	1:1	0.427	1.005	0.429	A33
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.03	1	05566	QPSK	50	50	10 mm	back	1:1	0.306	1.026	0.314	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.04	0	05566	QPSK	1	49	10 mm	back	1:1	0.393	1.021	0.401	A34
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	-0.01	1	05566	QPSK	25	12	10 mm	back	1:1	0.323	1.035	0.334	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.01	0	05566	QPSK	1	0	10 mm	back	1:1	0.311	1.012	0.315	A36
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	-0.10	1	05566	QPSK	25	0	10 mm	back	1:1	0.255	1.057	0.270	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.06	0	05558	QPSK	1	74	10 mm	back	1:1	0.372	1.000	0.372	A37
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	-0.03	1	05558	QPSK	36	18	10 mm	back	1:1	0.254	1.047	0.266	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.03	0	05541	QPSK	1	0	10 mm	back	1:1	0.728	1.000	0.728	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.4	24.32	-0.01	0	05541	QPSK	1	0	10 mm	back	1:1	0.797	1.019	0.812	A38
1770.00	132572	High	LTE Band 66 (AWS)	20	24.4	24.22	0.03	0	05541	QPSK	1	0	10 mm	back	1:1	0.744	1.042	0.775	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.00	1	05541	QPSK	50	0	10 mm	back	1:1	0.605	1.074	0.650	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.07	-0.01	1	05541	QPSK	100	0	10 mm	back	1:1	0.604	1.079	0.652	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.4	24.36	0.05	0	05574	QPSK	1	0	10 mm	back	1:1	0.721	1.009	0.727	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.4	24.39	0.17	0	05574	QPSK	1	0	10 mm	back	1:1	0.763	1.002	0.765	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.01	0	05574	QPSK	1	0	10 mm	back	1:1	0.785	1.000	0.785	A39
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	-0.01	1	05574	QPSK	50	0	10 mm	back	1:1	0.618	1.019	0.630	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-21
LTE Band 41 Body-Worn SAR**

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.2	24.20	0.07	0	05541	QPSK	1	0	10 mm	back	1:1.58	0.284	1.000	0.284	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	23.2	23.20	-0.04	1	05541	QPSK	50	25	10 mm	back	1:1.58	0.232	1.000	0.232	
Power Class 2	2506.00	39750	Low	LTE Band 41	20	27.2	26.96	0.01	0	05541	QPSK	1	0	10 mm	back	1:2.31	0.384	1.057	0.406	A41
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-22
DTS Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		
2412	1	802.11b	DSSS	22	22.0	21.73	-0.01	10 mm	05681	1	back	99.9	0.727	0.488	1.064	1.001	0.520		
2437	6	802.11b	DSSS	22	22.0	21.97	-0.05	10 mm	05681	1	back	99.9	1.022	0.676	1.007	1.001	0.681		
2462	11	802.11b	DSSS	22	22.0	21.96	-0.06	10 mm	05681	1	back	99.9	1.086	0.747	1.009	1.001	0.754	A43	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 77 of 116

**Table 11-23
NII Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	18.0	17.83	-0.17	10 mm	05699	6	back	99.2	1.163	0.537	1.040	1.008	0.563	
5620	124	802.11a	OFDM	20	17.5	17.47	-0.05	10 mm	05699	6	back	99.2	1.156	0.530	1.007	1.008	0.538	
5765	153	802.11a	OFDM	20	18.5	18.34	-0.18	10 mm	05699	6	back	99.2	1.478	0.624	1.038	1.008	0.653	
5785	157	802.11a	OFDM	20	18.5	18.45	-0.02	10 mm	05699	6	back	99.2	1.479	0.645	1.012	1.008	0.658	
5805	161	802.11a	OFDM	20	18.5	18.42	-0.03	10 mm	05699	6	back	99.2	1.578	0.661	1.019	1.008	0.679	A44
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-24
DSS Body-Worn SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #	
MHz	Ch.											(W/kg)			(W/kg)		
2441	39	Bluetooth	FHSS	8.0	7.50	0.03	10 mm	05681	1	back	77.1	0.016	1.122	1.297	0.023	A45	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 78 of 116

11.3 Standalone Hotspot SAR Data



**Table 11-25
GPRS/UMTS/CDMA Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY MHz	Ch.	Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
836.60	190	GSM 850	GPRS	30.7	30.44	-0.05	10 mm	05558	3	1.2.76	back	0.547	1.062	0.581	
836.60	190	GSM 850	GPRS	30.7	30.44	-0.03	10 mm	05558	3	1.2.76	front	0.464	1.062	0.493	
836.60	190	GSM 850	GPRS	30.7	30.44	-0.21	10 mm	05558	3	1.2.76	bottom	0.207	1.062	0.220	
836.60	190	GSM 850	GPRS	30.7	30.44	-0.05	10 mm	05558	3	1.2.76	right	0.550	1.062	0.584	A20
836.60	190	GSM 850	GPRS	30.7	30.44	-0.02	10 mm	05558	3	1.2.76	left	0.293	1.062	0.311	
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.02	10 mm	05566	3	1.2.76	back	0.331	1.164	0.385	
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.10	10 mm	05566	3	1.2.76	front	0.350	1.164	0.407	
1880.00	661	GSM 1900	GPRS	27.2	26.54	-0.03	10 mm	05566	3	1.2.76	bottom	0.340	1.164	0.396	
1880.00	661	GSM 1900	GPRS	27.2	26.54	0.01	10 mm	05566	3	1.2.76	left	0.364	1.164	0.424	A22
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.02	10 mm	05558	N/A	1:1	back	0.416	1.012	0.421	A23
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.02	10 mm	05558	N/A	1:1	front	0.395	1.012	0.400	
836.60	4183	UMTS 850	RMC	25.2	25.15	0.04	10 mm	05558	N/A	1:1	bottom	0.143	1.012	0.145	
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.04	10 mm	05558	N/A	1:1	right	0.379	1.012	0.384	
836.60	4183	UMTS 850	RMC	25.2	25.15	-0.02	10 mm	05558	N/A	1:1	left	0.217	1.012	0.220	
1712.40	1312	UMTS 1750	RMC	24.4	24.32	0.00	10 mm	05541	N/A	1:1	back	0.962	1.019	0.980	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.06	10 mm	05541	N/A	1:1	back	1.060	1.050	1.113	A24
1752.60	1513	UMTS 1750	RMC	24.4	24.02	0.02	10 mm	05541	N/A	1:1	back	0.963	1.091	1.051	
1712.40	1312	UMTS 1750	RMC	24.4	24.32	-0.02	10 mm	05541	N/A	1:1	front	0.729	1.019	0.743	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.01	10 mm	05541	N/A	1:1	front	0.822	1.050	0.863	
1752.60	1513	UMTS 1750	RMC	24.4	24.02	-0.01	10 mm	05541	N/A	1:1	front	0.782	1.091	0.853	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	-0.01	10 mm	05541	N/A	1:1	bottom	0.612	1.050	0.643	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.00	10 mm	05541	N/A	1:1	left	0.759	1.050	0.797	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	-0.11	10 mm	05541	N/A	1:1	back	1.010	1.050	1.061	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.03	10 mm	05574	N/A	1:1	back	0.693	1.002	0.694	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.04	10 mm	05574	N/A	1:1	front	0.675	1.002	0.676	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.07	10 mm	05574	N/A	1:1	bottom	0.626	1.002	0.627	
1852.40	9262	UMTS 1900	RMC	24.4	24.38	-0.16	10 mm	05574	N/A	1:1	left	0.674	1.005	0.677	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.04	10 mm	05574	N/A	1:1	left	0.740	1.002	0.741	A26
1907.60	9538	UMTS 1900	RMC	24.4	24.40	-0.03	10 mm	05574	N/A	1:1	left	0.724	1.000	0.724	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	24.98	0.12	10 mm	05558	N/A	1:1	back	0.302	1.052	0.318	A28
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	24.98	0.01	10 mm	05558	N/A	1:1	front	0.268	1.052	0.282	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	24.98	-0.14	10 mm	05558	N/A	1:1	bottom	0.089	1.052	0.094	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	24.98	0.00	10 mm	05558	N/A	1:1	right	0.262	1.052	0.276	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. 0	25.2	24.98	0.03	10 mm	05558	N/A	1:1	left	0.165	1.052	0.174	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.2	25.09	0.04	10 mm	05558	N/A	1:1	back	0.383	1.026	0.393	A30
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.2	25.09	-0.04	10 mm	05558	N/A	1:1	front	0.338	1.026	0.347	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.2	25.09	0.04	10 mm	05558	N/A	1:1	bottom	0.139	1.026	0.143	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.2	25.09	-0.04	10 mm	05558	N/A	1:1	right	0.330	1.026	0.339	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. 0	25.2	25.09	0.01	10 mm	05558	N/A	1:1	left	0.198	1.026	0.203	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.48	0.03	10 mm	05574	N/A	1:1	back	0.758	1.052	0.797	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.01	10 mm	05574	N/A	1:1	back	0.720	1.045	0.752	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.54	-0.13	10 mm	05574	N/A	1:1	back	0.775	1.038	0.804	A32
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	0.04	10 mm	05574	N/A	1:1	front	0.693	1.045	0.724	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.06	10 mm	05574	N/A	1:1	bottom	0.713	1.045	0.745	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.02	10 mm	05574	N/A	1:1	left	0.657	1.045	0.687	

ANSI / IEEE C95.1 1992 - SAFETY LIMIT
Spatial Peak
Uncontrolled Exposure/General Population

Body
1.6 W/kg (mW/g)
averaged over 1 gram

Note: Blue entry represents variability measurement.



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 79 of 116

**Table 11-26
LTE Band 71 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.02	0	05566	QPSK	1	99	10 mm	back	1:1	0.427	1.005	0.429	A33
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.03	1	05566	QPSK	50	50	10 mm	back	1:1	0.306	1.026	0.314	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.03	0	05566	QPSK	1	99	10 mm	front	1:1	0.374	1.005	0.376	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.01	1	05566	QPSK	50	50	10 mm	front	1:1	0.278	1.026	0.285	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.00	0	05566	QPSK	1	99	10 mm	bottom	1:1	0.133	1.005	0.134	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	-0.08	1	05566	QPSK	50	50	10 mm	bottom	1:1	0.099	1.026	0.102	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	0.00	0	05566	QPSK	1	99	10 mm	right	1:1	0.396	1.005	0.398	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	0.17	1	05566	QPSK	50	50	10 mm	right	1:1	0.244	1.026	0.250	
680.50	133297	Mid	LTE Band 71	20	25.2	25.18	-0.14	0	05566	QPSK	1	99	10 mm	left	1:1	0.270	1.005	0.271	
680.50	133297	Mid	LTE Band 71	20	24.2	24.09	-0.14	1	05566	QPSK	50	50	10 mm	left	1:1	0.169	1.026	0.173	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-27
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.04	0	05566	QPSK	1	49	10 mm	back	1:1	0.393	1.021	0.401	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	-0.01	1	05566	QPSK	25	12	10 mm	back	1:1	0.323	1.035	0.334	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	-0.01	0	05566	QPSK	1	49	10 mm	front	1:1	0.375	1.021	0.383	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	0.02	1	05566	QPSK	25	12	10 mm	front	1:1	0.297	1.035	0.307	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.13	0	05566	QPSK	1	49	10 mm	bottom	1:1	0.108	1.021	0.110	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	-0.04	1	05566	QPSK	25	12	10 mm	bottom	1:1	0.081	1.035	0.084	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	-0.02	0	05566	QPSK	1	49	10 mm	right	1:1	0.474	1.021	0.484	A35
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	0.05	1	05566	QPSK	25	12	10 mm	right	1:1	0.373	1.035	0.386	
707.50	23095	Mid	LTE Band 12	10	25.2	25.11	0.00	0	05566	QPSK	1	49	10 mm	left	1:1	0.299	1.021	0.305	
707.50	23095	Mid	LTE Band 12	10	24.2	24.05	0.03	1	05566	QPSK	25	12	10 mm	left	1:1	0.243	1.035	0.252	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 80 of 116	

**Table 11-28
LTE Band 13 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.01	0	05566	QPSK	1	0	10 mm	back	1:1	0.311	1.012	0.315	A36
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	-0.10	1	05566	QPSK	25	0	10 mm	back	1:1	0.255	1.057	0.270	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.04	0	05566	QPSK	1	0	10 mm	front	1:1	0.294	1.012	0.298	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.02	1	05566	QPSK	25	0	10 mm	front	1:1	0.250	1.057	0.264	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.10	0	05566	QPSK	1	0	10 mm	bottom	1:1	0.138	1.012	0.140	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.03	1	05566	QPSK	25	0	10 mm	bottom	1:1	0.110	1.057	0.116	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	0.00	0	05566	QPSK	1	0	10 mm	right	1:1	0.239	1.012	0.242	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	-0.03	1	05566	QPSK	25	0	10 mm	right	1:1	0.223	1.057	0.236	
782.00	23230	Mid	LTE Band 13	10	23.2	23.15	-0.04	0	05566	QPSK	1	0	10 mm	left	1:1	0.152	1.012	0.154	
782.00	23230	Mid	LTE Band 13	10	22.2	21.96	0.00	1	05566	QPSK	25	0	10 mm	left	1:1	0.147	1.057	0.155	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-29
LTE Band 26 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.06	0	05558	QPSK	1	74	10 mm	back	1:1	0.372	1.000	0.372	A37
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	-0.03	1	05558	QPSK	36	18	10 mm	back	1:1	0.254	1.047	0.266	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.13	0	05558	QPSK	1	74	10 mm	front	1:1	0.311	1.000	0.311	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.10	1	05558	QPSK	36	18	10 mm	front	1:1	0.232	1.047	0.243	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.04	0	05558	QPSK	1	74	10 mm	bottom	1:1	0.128	1.000	0.128	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	-0.09	1	05558	QPSK	36	18	10 mm	bottom	1:1	0.086	1.047	0.090	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.01	0	05558	QPSK	1	74	10 mm	right	1:1	0.352	1.000	0.352	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.11	1	05558	QPSK	36	18	10 mm	right	1:1	0.269	1.047	0.282	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.2	25.20	-0.08	0	05558	QPSK	1	74	10 mm	left	1:1	0.205	1.000	0.205	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.2	24.00	0.13	1	05558	QPSK	36	18	10 mm	left	1:1	0.158	1.047	0.165	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 81 of 116	



**Table 11-30
LTE Band 66 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.03	0	05541	QPSK	1	0	10 mm	back	1:1	0.728	1.000	0.728	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.4	24.32	-0.01	0	05541	QPSK	1	0	10 mm	back	1:1	0.797	1.019	0.812	A38
1770.00	132572	High	LTE Band 66 (AWS)	20	24.4	24.22	0.03	0	05541	QPSK	1	0	10 mm	back	1:1	0.744	1.042	0.775	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.00	1	05541	QPSK	50	0	10 mm	back	1:1	0.605	1.074	0.650	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.07	-0.01	1	05541	QPSK	100	0	10 mm	back	1:1	0.604	1.079	0.652	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.02	0	05541	QPSK	1	0	10 mm	front	1:1	0.543	1.000	0.543	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	-0.02	1	05541	QPSK	50	0	10 mm	front	1:1	0.449	1.074	0.482	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.18	0	05541	QPSK	1	0	10 mm	bottom	1:1	0.406	1.000	0.406	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.04	1	05541	QPSK	50	0	10 mm	bottom	1:1	0.337	1.074	0.362	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.02	0	05541	QPSK	1	0	10 mm	left	1:1	0.580	1.000	0.580	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	-0.01	1	05541	QPSK	50	0	10 mm	left	1:1	0.471	1.074	0.506	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-31
LTE Band 25 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.01	0	05574	QPSK	1	0	10 mm	back	1:1	0.785	1.000	0.785	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	-0.01	1	05574	QPSK	50	0	10 mm	back	1:1	0.618	1.019	0.630	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.4	24.36	0.08	0	05574	QPSK	1	0	10 mm	front	1:1	0.824	1.009	0.831	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.4	24.39	0.00	0	05574	QPSK	1	0	10 mm	front	1:1	0.787	1.002	0.789	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.03	0	05574	QPSK	1	0	10 mm	front	1:1	0.852	1.000	0.852	A40
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.04	1	05574	QPSK	50	0	10 mm	front	1:1	0.655	1.019	0.667	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.31	0.05	1	05574	QPSK	100	0	10 mm	front	1:1	0.673	1.021	0.687	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.03	0	05574	QPSK	1	0	10 mm	bottom	1:1	0.671	1.000	0.671	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	-0.03	1	05574	QPSK	50	0	10 mm	bottom	1:1	0.544	1.019	0.554	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.09	0	05574	QPSK	1	0	10 mm	left	1:1	0.728	1.000	0.728	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	-0.08	1	05574	QPSK	50	0	10 mm	left	1:1	0.591	1.019	0.602	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.11	0	05574	QPSK	1	0	10 mm	front	1:1	0.839	1.000	0.839	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement.



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 82 of 116	

**Table 11-32
LTE Band 41 Hotspot SAR**

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Side	Modulation	Serial Number	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	RB Size	RB Offset	MPR [dB]	Spacing	Maximum Allowed Power	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	24.2	24.20	0.07	0	QPSK	1	0	10 mm	back	1:1.58	0.284	1.000	0.284	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	23.2	23.20	-0.04	1	QPSK	50	25	10 mm	back	1:1.58	0.232	1.000	0.232	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	24.2	24.20	0.18	0	QPSK	1	0	10 mm	front	1:1.58	0.316	1.000	0.316	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	23.2	23.20	-0.04	1	QPSK	50	25	10 mm	front	1:1.58	0.267	1.000	0.267	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	24.2	24.20	-0.14	0	QPSK	1	0	10 mm	bottom	1:1.58	0.458	1.000	0.458	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	23.2	23.20	-0.14	1	QPSK	50	25	10 mm	bottom	1:1.58	0.363	1.000	0.363	
Power Class 2	2506.00	39750	Low	LTE Band 41	20	05541	27.2	26.96	-0.13	0	QPSK	1	0	10 mm	bottom	1:2.31	0.648	1.057	0.685	A42
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	24.2	24.20	0.04	0	QPSK	1	0	10 mm	right	1:1.58	0.167	1.000	0.167	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	23.2	23.20	0.09	1	QPSK	50	25	10 mm	right	1:1.58	0.141	1.000	0.141	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	24.2	24.20	0.11	0	QPSK	1	0	10 mm	left	1:1.58	0.145	1.000	0.145	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	05541	23.2	23.20	0.09	1	QPSK	50	25	10 mm	left	1:1.58	0.138	1.000	0.138	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body										
Spatial Peak										1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population										averaged over 1 gram										



**Table 11-33
WLAN Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	22.0	21.73	-0.01	10 mm	05681	1	back	99.9	0.727	0.488	1.064	1.001	0.520	
2437	6	802.11b	DSSS	22	22.0	21.97	-0.05	10 mm	05681	1	back	99.9	1.022	0.676	1.007	1.001	0.681	
2462	11	802.11b	DSSS	22	22.0	21.96	-0.06	10 mm	05681	1	back	99.9	1.086	0.747	1.009	1.001	0.754	A43
2437	6	802.11b	DSSS	22	22.0	21.97	0.00	10 mm	05681	1	front	99.9	1.041	0.597	1.007	1.001	0.602	
2437	6	802.11b	DSSS	22	22.0	21.97	0.07	10 mm	05681	1	top	99.9	0.824	-	1.007	1.001	-	
2437	6	802.11b	DSSS	22	22.0	21.97	0.17	10 mm	05681	1	left	99.9	0.419	0.258	1.007	1.001	0.260	
5240	48	802.11a	OFDM	20	18.0	17.69	-0.19	10 mm	05699	6	back	99.2	1.217	0.583	1.074	1.008	0.631	
5240	48	802.11a	OFDM	20	18.0	17.69	-0.02	10 mm	05699	6	front	99.2	0.593	-	1.074	1.008	-	
5240	48	802.11a	OFDM	20	18.0	17.69	-0.18	10 mm	05699	6	top	99.2	0.813	0.366	1.074	1.008	0.396	
5240	48	802.11a	OFDM	20	18.0	17.69	-0.16	10 mm	05699	6	left	99.2	0.518	-	1.074	1.008	-	
5765	153	802.11a	OFDM	20	18.5	18.34	-0.18	10 mm	05699	6	back	99.2	1.478	0.624	1.038	1.008	0.653	
5785	157	802.11a	OFDM	20	18.5	18.45	-0.02	10 mm	05699	6	back	99.2	1.479	0.645	1.012	1.008	0.658	
5805	161	802.11a	OFDM	20	18.5	18.42	-0.03	10 mm	05699	6	back	99.2	1.578	0.661	1.019	1.008	0.679	A44
5785	157	802.11a	OFDM	20	18.5	18.45	-0.08	10 mm	05699	6	front	99.2	1.153	0.450	1.012	1.008	0.459	
5785	157	802.11a	OFDM	20	18.5	18.45	-0.16	10 mm	05699	6	top	99.2	1.124	-	1.012	1.008	-	
5785	157	802.11a	OFDM	20	18.5	18.45	0.07	10 mm	05699	6	left	99.2	0.675	-	1.012	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body								
Spatial Peak										1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population										averaged over 1 gram								

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 83 of 116	

**Table 11-34
DSS Hotspot SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	8.0	7.50	0.03	10 mm	05681	1	back	77.1	0.016	1.122	1.297	0.023	A46
2441	39	Bluetooth	FHSS	8.0	7.50	0.06	10 mm	05681	1	front	77.1	0.015	1.122	1.297	0.022	
2441	39	Bluetooth	FHSS	8.0	7.50	0.05	10 mm	05681	1	top	77.1	0.011	1.122	1.297	0.016	
2441	39	Bluetooth	FHSS	8.0	7.50	0.05	10 mm	05681	1	left	77.1	0.009	1.122	1.297	0.013	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 84 of 116	

11.4 Standalone Phablet SAR Data

**Table 11-35
UMTS/CDMA Phablet SAR Data**



MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.05	3 mm	05541	1:1	back	1.350	1.050	1.418	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.02	3 mm	05541	1:1	front	1.240	1.050	1.302	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	-0.01	4 mm	05541	1:1	bottom	0.779	1.050	0.818	
1712.40	1312	UMTS 1750	RMC	24.4	24.32	0.11	0 mm	05541	1:1	left	2.640	1.019	2.690	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.19	0 mm	05541	1:1	left	2.880	1.050	3.024	
1752.60	1513	UMTS 1750	RMC	24.4	24.02	0.09	0 mm	05541	1:1	left	2.880	1.091	3.142	A46
1712.40	1312	UMTS 1750	RMC	22.7	22.68	0.00	0 mm	05541	1:1	back	2.380	1.005	2.392	
1732.40	1412	UMTS 1750	RMC	22.7	22.69	0.00	0 mm	05541	1:1	back	2.550	1.002	2.555	
1752.60	1513	UMTS 1750	RMC	22.7	22.57	0.02	0 mm	05541	1:1	back	2.520	1.030	2.596	
1712.40	1312	UMTS 1750	RMC	22.7	22.68	0.10	0 mm	05541	1:1	front	2.070	1.005	2.080	
1732.40	1412	UMTS 1750	RMC	22.7	22.69	0.12	0 mm	05541	1:1	front	2.310	1.002	2.315	
1752.60	1513	UMTS 1750	RMC	22.7	22.57	0.06	0 mm	05541	1:1	front	2.280	1.030	2.348	
1732.40	1412	UMTS 1750	RMC	22.7	22.69	0.06	0 mm	05541	1:1	bottom	1.740	1.002	1.743	
1732.40	1412	UMTS 1750	RMC	24.4	24.19	0.03	0 mm	05541	1:1	left	2.870	1.050	3.014	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.03	3 mm	05574	1:1	back	1.650	1.002	1.653	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.13	3 mm	05574	1:1	front	1.330	1.002	1.333	
1880.00	9400	UMTS 1900	RMC	24.4	24.39	-0.06	4 mm	05574	1:1	bottom	0.801	1.002	0.803	
1852.40	9262	UMTS 1900	RMC	24.4	24.38	-0.07	0 mm	05574	1:1	left	3.030	1.005	3.045	A47
1880.00	9400	UMTS 1900	RMC	24.4	24.39	0.13	0 mm	05574	1:1	left	3.000	1.002	3.006	
1907.60	9538	UMTS 1900	RMC	24.4	24.40	-0.18	0 mm	05574	1:1	left	2.620	1.000	2.620	
1852.40	9262	UMTS 1900	RMC	22.7	22.46	-0.03	0 mm	05574	1:1	back	2.550	1.057	2.695	
1880.00	9400	UMTS 1900	RMC	22.7	22.36	0.02	0 mm	05574	1:1	back	2.430	1.081	2.627	
1907.60	9538	UMTS 1900	RMC	22.7	22.51	0.03	0 mm	05574	1:1	back	2.450	1.045	2.560	
1852.40	9262	UMTS 1900	RMC	22.7	22.46	0.02	0 mm	05574	1:1	front	2.150	1.057	2.273	
1880.00	9400	UMTS 1900	RMC	22.7	22.36	0.03	0 mm	05574	1:1	front	2.050	1.081	2.216	
1907.60	9538	UMTS 1900	RMC	22.7	22.51	0.03	0 mm	05574	1:1	front	2.060	1.045	2.153	
1880.00	9400	UMTS 1900	RMC	22.7	22.36	0.05	0 mm	05574	1:1	bottom	1.490	1.081	1.611	
1852.40	9262	UMTS 1900	RMC	24.4	24.38	-0.11	0 mm	05574	1:1	left	3.010	1.005	3.025	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.05	3 mm	05574	1:1	back	1.530	1.045	1.599	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	0.16	3 mm	05574	1:1	front	1.480	1.045	1.547	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.07	4 mm	05574	1:1	bottom	0.928	1.045	0.970	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.48	-0.01	0 mm	05574	1:1	left	2.620	1.052	2.756	A48
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.51	-0.03	0 mm	05574	1:1	left	2.600	1.045	2.717	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.54	-0.02	0 mm	05574	1:1	left	2.520	1.038	2.616	
1851.25	25	PCS CDMA	EVDO Rev. 0	23.0	22.74	0.00	0 mm	05574	1:1	back	2.480	1.062	2.634	
1880.00	600	PCS CDMA	EVDO Rev. 0	23.0	22.71	0.02	0 mm	05574	1:1	back	2.440	1.069	2.608	
1908.75	1175	PCS CDMA	EVDO Rev. 0	23.0	22.78	0.00	0 mm	05574	1:1	back	2.450	1.052	2.577	
1851.25	25	PCS CDMA	EVDO Rev. 0	23.0	22.74	0.03	0 mm	05574	1:1	front	2.250	1.062	2.390	
1880.00	600	PCS CDMA	EVDO Rev. 0	23.0	22.71	0.04	0 mm	05574	1:1	front	2.210	1.069	2.362	
1908.75	1175	PCS CDMA	EVDO Rev. 0	23.0	22.78	0.04	0 mm	05574	1:1	front	2.200	1.052	2.314	
1880.00	600	PCS CDMA	EVDO Rev. 0	23.0	22.71	-0.08	0 mm	05574	1:1	bottom	1.460	1.069	1.561	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams							

Note: Blue entry represents variability measurement.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 85 of 116	

**Table 11-36
LTE Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY	MHz	Ch.	Mode	Bandwidth	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Power Drift (dB)	MPR (dB)	Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g) (W/kg)	Scaling Factor	Reported SAR (10g) (W/kg)	Plot #
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	-0.03	0	05541	QPSK	1	0	3 mm	back	1:1	1.190	1.000	1.190	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	-0.01	1	05541	QPSK	50	0	3 mm	back	1:1	0.962	1.074	1.033	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	-0.01	0	05541	QPSK	1	0	3 mm	front	1:1	1.060	1.000	1.060	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	-0.01	1	05541	QPSK	50	0	3 mm	front	1:1	0.831	1.074	0.892	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	-0.03	0	05541	QPSK	1	0	4 mm	bottom	1:1	0.624	1.000	0.624	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	0.03	1	05541	QPSK	50	0	4 mm	bottom	1:1	0.522	1.074	0.561	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.4	24.40	0.01	0	05541	QPSK	1	0	0 mm	left	1:1	2.240	1.000	2.240	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.4	24.32	-0.05	0	05541	QPSK	1	0	0 mm	left	1:1	2.370	1.019	2.415	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.4	24.22	-0.07	0	05541	QPSK	1	0	0 mm	left	1:1	2.550	1.042	2.657	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.09	-0.05	1	05541	QPSK	50	0	0 mm	left	1:1	1.780	1.074	1.912	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.4	23.07	-0.03	1	05541	QPSK	100	0	0 mm	left	1:1	1.830	1.079	1.975	
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	-0.04	0	05541	QPSK	1	0	0 mm	back	1:1	2.320	1.000	2.320	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	22.9	22.87	0.02	0	05541	QPSK	1	99	0 mm	back	1:1	2.620	1.007	2.638	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.85	-0.01	0	05541	QPSK	1	0	0 mm	back	1:1	2.640	1.012	2.672	
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	0.04	0	05541	QPSK	50	50	0 mm	back	1:1	2.190	1.000	2.190	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	22.9	22.85	0.01	0	05541	QPSK	50	0	0 mm	back	1:1	2.300	1.012	2.328	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.82	0.02	0	05541	QPSK	50	0	0 mm	back	1:1	2.380	1.019	2.425	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.88	0.01	0	05541	QPSK	100	0	0 mm	back	1:1	2.310	1.005	2.322	
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	-0.03	0	05541	QPSK	1	0	0 mm	front	1:1	2.430	1.000	2.430	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	22.9	22.87	0.02	0	05541	QPSK	1	99	0 mm	front	1:1	2.780	1.007	2.779	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.85	-0.01	0	05541	QPSK	1	0	0 mm	front	1:1	2.800	1.012	2.834	A49
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	0.02	0	05541	QPSK	50	50	0 mm	front	1:1	2.240	1.000	2.240	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	22.9	22.85	-0.07	0	05541	QPSK	50	0	0 mm	front	1:1	2.370	1.012	2.398	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.82	0.00	0	05541	QPSK	50	0	0 mm	front	1:1	2.470	1.019	2.517	
1770.00	132572	High	LTE Band 66 (AWS)	20	22.9	22.88	0.02	0	05541	QPSK	100	0	0 mm	front	1:1	2.430	1.005	2.442	
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	-0.03	0	05541	QPSK	1	0	0 mm	bottom	1:1	1.470	1.000	1.470	
1720.00	132072	Low	LTE Band 66 (AWS)	20	22.9	22.90	-0.04	0	05541	QPSK	50	50	0 mm	bottom	1:1	1.420	1.000	1.420	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.03	0	05574	QPSK	1	0	3 mm	back	1:1	1.750	1.000	1.750	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.04	1	05574	QPSK	50	0	3 mm	back	1:1	1.340	1.019	1.365	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	0.16	0	05574	QPSK	1	0	3 mm	front	1:1	1.500	1.000	1.500	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.14	1	05574	QPSK	50	0	3 mm	front	1:1	1.150	1.019	1.172	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.05	0	05574	QPSK	1	0	4 mm	bottom	1:1	0.929	1.000	0.929	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.00	1	05574	QPSK	50	0	4 mm	bottom	1:1	0.704	1.019	0.717	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.4	24.36	0.16	0	05574	QPSK	1	0	0 mm	left	1:1	2.720	1.009	2.744	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.4	24.39	0.14	0	05574	QPSK	1	0	0 mm	left	1:1	2.510	1.002	2.515	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.4	24.40	-0.04	0	05574	QPSK	1	0	0 mm	left	1:1	2.780	1.000	2.780	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.4	23.23	-0.13	1	05574	QPSK	50	0	0 mm	left	1:1	1.860	1.040	1.934	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.4	23.31	-0.11	1	05574	QPSK	50	0	0 mm	left	1:1	1.830	1.021	1.868	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.32	0.11	1	05574	QPSK	50	0	0 mm	left	1:1	2.040	1.019	2.079	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.4	23.31	0.21	1	05574	QPSK	100	0	0 mm	left	1:1	2.010	1.021	2.052	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.9	22.86	-0.01	0	05574	QPSK	1	0	0 mm	back	1:1	2.900	1.009	2.926	A50
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.90	0.00	0	05574	QPSK	1	0	0 mm	back	1:1	2.840	1.000	2.840	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.82	-0.05	0	05574	QPSK	1	0	0 mm	back	1:1	2.820	1.019	2.874	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.9	22.78	-0.04	0	05574	QPSK	50	0	0 mm	back	1:1	2.720	1.028	2.796	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.87	-0.01	0	05574	QPSK	50	0	0 mm	back	1:1	2.720	1.007	2.739	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.86	0.12	0	05574	QPSK	50	0	0 mm	back	1:1	2.760	1.009	2.785	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.78	0.03	0	05574	QPSK	100	0	0 mm	back	1:1	2.780	1.028	2.837	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.9	22.86	0.13	0	05574	QPSK	1	0	0 mm	front	1:1	2.480	1.009	2.502	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.90	0.02	0	05574	QPSK	1	0	0 mm	front	1:1	2.390	1.000	2.390	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.82	0.18	0	05574	QPSK	1	0	0 mm	front	1:1	2.470	1.019	2.517	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.9	22.78	0.19	0	05574	QPSK	50	0	0 mm	front	1:1	2.410	1.028	2.477	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.87	0.02	0	05574	QPSK	50	0	0 mm	front	1:1	2.370	1.007	2.387	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.86	0.19	0	05574	QPSK	50	0	0 mm	front	1:1	2.470	1.009	2.492	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.9	22.78	0.20	0	05574	QPSK	100	0	0 mm	front	1:1	2.550	1.028	2.621	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.90	-0.06	0	05574	QPSK	1	0	0 mm	bottom	1:1	1.650	1.000	1.650	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.9	22.87	0.05	0	05574	QPSK	50	0	0 mm	bottom	1:1	1.570	1.007	1.581	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Phablet 4.0 W/kg (mW/g) averaged over 10 grams									

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 86 of 116

**Table 11-37
WLAN Phablet SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	18.0	17.83	-0.14	0 mm	05699	6	back	99.2	27.208	2.030	1.040	1.008	2.128	
5280	56	802.11a	OFDM	20	18.0	17.73	0.06	0 mm	05699	6	back	99.2	17.572	2.000	1.064	1.008	2.145	
5300	60	802.11a	OFDM	20	18.0	17.80	-0.09	0 mm	05699	6	back	99.2	23.721	2.050	1.047	1.008	2.164	
5260	52	802.11a	OFDM	20	18.0	17.83	0.10	0 mm	05699	6	front	99.2	13.283	1.090	1.040	1.008	1.143	
5260	52	802.11a	OFDM	20	18.0	17.83	-0.02	0 mm	05699	6	top	99.2	8.683	-	1.040	1.008	-	
5260	52	802.11a	OFDM	20	18.0	17.83	-0.13	0 mm	05699	6	left	99.2	4.770	0.618	1.040	1.008	0.648	
5620	124	802.11a	OFDM	20	17.5	17.47	-0.09	0 mm	05699	6	back	99.2	20.555	1.810	1.007	1.008	1.837	
5620	124	802.11a	OFDM	20	17.5	17.47	-0.19	0 mm	05699	6	front	99.2	12.296	0.880	1.007	1.008	0.893	
5620	124	802.11a	OFDM	20	17.5	17.47	-0.13	0 mm	05699	6	top	99.2	7.458	-	1.007	1.008	-	
5620	124	802.11a	OFDM	20	17.5	17.47	-0.21	0 mm	05699	6	left	99.2	3.744	0.553	1.007	1.008	0.561	
5300	60	802.11a	OFDM	20	18.0	17.80	-0.10	0 mm	05699	6	back	99.2	19.574	2.070	1.047	1.008	2.185	A51
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams										

Note: Blue entry represents variability measurement.

11.5 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
- Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (See Section 6.9 for more information).
- This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
- Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1-ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 87 of 116	

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

CDMA Notes:



1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
6. CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1X Advanced was not more than 0.25 dB higher than the maximum powers for 1X.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 88 of 116	



3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
7. This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per FCC Guidance, all SAR tests were performed using Power Class 3. SAR with power class 2 at the available duty factor was additionally performed for the power class 3 configuration with the highest SAR configuration for each exposure conditions. Please see Section 14 for linearity results.

WLAN Notes:

1. For held-to-ear, and hotspot, and phablet operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.7.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.6 for the time domain plot and calculation for the duty factor of the device.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 89 of 116	



12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg and ≤ 4 W/kg for 10g SAR. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 90 of 116



12.3 Head SAR Simultaneous Transmission Analysis

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.452	1.098	1.550
	GSM/GPRS 1900	0.376	1.098	1.474
	UMTS 850	0.283	1.098	1.381
	UMTS 1750	0.427	1.098	1.525
	UMTS 1900	0.582	1.098	See Table Below
	CDMA/EVDO BC10 (§90S)	0.210	1.098	1.308
	CDMA/EVDO BC0 (§22H)	0.319	1.098	1.417
	PCS CDMA/EVDO	0.693	1.098	See Table Below
	LTE Band 71	0.229	1.098	1.327
	LTE Band 12	0.236	1.098	1.334
	LTE Band 13	0.250	1.098	1.348
	LTE Band 26 (Cell)	0.295	1.098	1.393
	LTE Band 66 (AWS)	0.356	1.098	1.454
	LTE Band 25 (PCS)	0.565	1.098	See Table Below
LTE Band 41	0.266	1.098	1.364	



Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS CDMA SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Head SAR	Right Cheek	0.308	1.098	1.406	Head SAR	Right Cheek	0.316	1.098	1.414
	Right Tilt	0.303	0.880	1.183		Right Tilt	0.324	0.880	1.204
	Left Cheek	0.582	0.545	1.127		Left Cheek	0.672	0.545	1.217
	Left Tilt	0.280	0.556	0.836		Left Tilt	0.326	0.556	0.882
Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Head SAR	Right Cheek	0.307	1.098	1.405	Head SAR	Right Cheek	0.307	1.098	1.405
	Right Tilt	0.311	0.880	1.191		Right Tilt	0.247	0.880	1.127
	Left Cheek	0.693	0.545	1.238		Left Cheek	0.565	0.545	1.110
	Left Tilt	0.338	0.556	0.894		Left Tilt	0.271	0.556	0.827

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 91 of 116	

**Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**



Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.452	0.946	1.398
	GSM/GPRS 1900	0.376	0.946	1.322
	UMTS 850	0.283	0.946	1.229
	UMTS 1750	0.427	0.946	1.373
	UMTS 1900	0.582	0.946	1.528
	CDMA/EVDO BC10 (§90S)	0.210	0.946	1.156
	CDMA/EVDO BC0 (§22H)	0.319	0.946	1.265
	PCS CDMA/EVDO	0.693	0.946	See Table Below
	LTE Band 71	0.229	0.946	1.175
	LTE Band 12	0.236	0.946	1.182
	LTE Band 13	0.250	0.946	1.196
	LTE Band 26 (Cell)	0.295	0.946	1.241
	LTE Band 66 (AWS)	0.356	0.946	1.302
	LTE Band 25 (PCS)	0.565	0.946	1.511
LTE Band 41	0.266	0.946	1.212	

Simult Tx	Configuration	PCS CDMA SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Head SAR	Right Cheek	0.316	0.946	1.262	Head SAR	Right Cheek	0.307	0.946	1.253
	Right Tilt	0.324	0.659	0.983		Right Tilt	0.311	0.659	0.970
	Left Cheek	0.672	0.438	1.110		Left Cheek	0.693	0.438	1.131
	Left Tilt	0.326	0.946*	1.272		Left Tilt	0.338	0.946*	1.284

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 92 of 116

**Table 12-3
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)**



Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.452	0.122	0.574
	GSM/GPRS 1900	0.376	0.122	0.498
	UMTS 850	0.283	0.122	0.405
	UMTS 1750	0.427	0.122	0.549
	UMTS 1900	0.582	0.122	0.704
	CDMA/EVDO BC10 (§90S)	0.210	0.122	0.332
	CDMA/EVDO BC0 (§22H)	0.319	0.122	0.441
	PCS CDMA/EVDO	0.693	0.122	0.815
	LTE Band 71	0.229	0.122	0.351
	LTE Band 12	0.236	0.122	0.358
	LTE Band 13	0.250	0.122	0.372
	LTE Band 26 (Cell)	0.295	0.122	0.417
	LTE Band 66 (AWS)	0.356	0.122	0.478
	LTE Band 25 (PCS)	0.565	0.122	0.687
LTE Band 41	0.266	0.122	0.388	

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 93 of 116	

**Table 12-4
Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN (Held to Ear)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Head SAR	GSM/GPRS 850	0.452	0.122	0.946	1.520
	GSM/GPRS 1900	0.376	0.122	0.946	1.444
	UMTS 850	0.283	0.122	0.946	1.351
	UMTS 1750	0.427	0.122	0.946	1.495
	UMTS 1900	0.582	0.122	0.946	See Table Below
	CDMA/EVDO BC10 (§90S)	0.210	0.122	0.946	1.278
	CDMA/EVDO BC0 (§22H)	0.319	0.122	0.946	1.387
	PCS CDMA/EVDO	0.693	0.122	0.946	See Table Below
	LTE Band 71	0.229	0.122	0.946	1.297
	LTE Band 12	0.236	0.122	0.946	1.304
	LTE Band 13	0.250	0.122	0.946	1.318
	LTE Band 26 (Cell)	0.295	0.122	0.946	1.363
	LTE Band 66 (AWS)	0.356	0.122	0.946	1.424
	LTE Band 25 (PCS)	0.565	0.122	0.946	See Table Below
LTE Band 41	0.266	0.122	0.946	1.334	

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS CDMA SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Head SAR	Right Cheek	0.308	0.122	0.946	1.376	Head SAR	Right Cheek	0.316	0.122	0.946	1.384
	Right Tilt	0.303	0.083	0.659	1.045		Right Tilt	0.324	0.083	0.659	1.066
	Left Cheek	0.582	0.063	0.438	1.083		Left Cheek	0.672	0.063	0.438	1.173
	Left Tilt	0.280	0.068	0.946*	1.294		Left Tilt	0.326	0.068	0.946*	1.340
Simult Tx	Configuration	PCS EVDO SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Head SAR	Right Cheek	0.307	0.122	0.946	1.375	Head SAR	Right Cheek	0.307	0.122	0.946	1.375
	Right Tilt	0.311	0.083	0.659	1.053		Right Tilt	0.247	0.083	0.659	0.989
	Left Cheek	0.693	0.063	0.438	1.194		Left Cheek	0.565	0.063	0.438	1.066
	Left Tilt	0.338	0.068	0.946*	1.352		Left Tilt	0.271	0.068	0.946*	1.285



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 94 of 116	

12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body-Worn	GSM/GPRS 850	0.581	0.754	1.335	N/A
	GSM/GPRS 1900	0.385	0.754	1.139	N/A
	UMTS 850	0.421	0.754	1.175	N/A
	UMTS 1750	1.113	0.754	See Note 1	0.01
	UMTS 1900	0.728	0.754	1.482	N/A
	CDMA BC10 (§90S)	0.346	0.754	1.100	N/A
	CDMA BC0 (§22H)	0.427	0.754	1.181	N/A
	PCS CDMA	0.830	0.754	1.584	N/A
	LTE Band 71	0.429	0.754	1.183	N/A
	LTE Band 12	0.401	0.754	1.155	N/A
	LTE Band 13	0.315	0.754	1.069	N/A
	LTE Band 26 (Cell)	0.372	0.754	1.126	N/A
	LTE Band 66 (AWS)	0.812	0.754	1.566	N/A
	LTE Band 25 (PCS)	0.785	0.754	1.539	N/A
LTE Band 41	0.406	0.754	1.160	N/A	

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 95 of 116

**Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body-Worn	GSM/GPRS 850	0.581	0.679	1.260	N/A
	GSM/GPRS 1900	0.385	0.679	1.064	N/A
	UMTS 850	0.421	0.679	1.100	N/A
	UMTS 1750	1.113	0.679	See Note 1	0.02
	UMTS 1900	0.728	0.679	1.407	N/A
	CDMA BC10 (§90S)	0.346	0.679	1.025	N/A
	CDMA BC0 (§22H)	0.427	0.679	1.106	N/A
	PCS CDMA	0.830	0.679	1.509	N/A
	LTE Band 71	0.429	0.679	1.108	N/A
	LTE Band 12	0.401	0.679	1.080	N/A
	LTE Band 13	0.315	0.679	0.994	N/A
	LTE Band 26 (Cell)	0.372	0.679	1.051	N/A
	LTE Band 66 (AWS)	0.812	0.679	1.491	N/A
	LTE Band 25 (PCS)	0.785	0.679	1.464	N/A
LTE Band 41	0.406	0.679	1.085	N/A	

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 96 of 116	

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.581	0.023	0.604
	GSM/GPRS 1900	0.385	0.023	0.408
	UMTS 850	0.421	0.023	0.444
	UMTS 1750	1.113	0.023	1.136
	UMTS 1900	0.728	0.023	0.751
	CDMA BC10 (§90S)	0.346	0.023	0.369
	CDMA BC0 (§22H)	0.427	0.023	0.450
	PCS CDMA	0.830	0.023	0.853
	LTE Band 71	0.429	0.023	0.452
	LTE Band 12	0.401	0.023	0.424
	LTE Band 13	0.315	0.023	0.338
	LTE Band 26 (Cell)	0.372	0.023	0.395
	LTE Band 66 (AWS)	0.812	0.023	0.835
	LTE Band 25 (PCS)	0.785	0.023	0.808
LTE Band 41	0.406	0.023	0.429	





FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 97 of 116

Table 12-8
Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3		1+2+3	1+2	1+3
Body-Worn	GSM/GPRS 850	0.581	0.023	0.679	1.283	N/A	N/A	N/A
	GSM/GPRS 1900	0.385	0.023	0.679	1.087	N/A	N/A	N/A
	UMTS 850	0.421	0.023	0.679	1.123	N/A	N/A	N/A
	UMTS 1750	1.113	0.023	0.679	See Note 1	0.01	0.02	0.01
	UMTS 1900	0.728	0.023	0.679	1.430	N/A	N/A	N/A
	CDMA BC10 (§90S)	0.346	0.023	0.679	1.048	N/A	N/A	N/A
	CDMA BC0 (§22H)	0.427	0.023	0.679	1.129	N/A	N/A	N/A
	PCS CDMA	0.830	0.023	0.679	1.532	N/A	N/A	N/A
	LTE Band 71	0.429	0.023	0.679	1.131	N/A	N/A	N/A
	LTE Band 12	0.401	0.023	0.679	1.103	N/A	N/A	N/A
	LTE Band 13	0.315	0.023	0.679	1.017	N/A	N/A	N/A
	LTE Band 26 (Cell)	0.372	0.023	0.679	1.074	N/A	N/A	N/A
	LTE Band 66 (AWS)	0.812	0.023	0.679	1.514	N/A	N/A	N/A
	LTE Band 25 (PCS)	0.785	0.023	0.679	1.487	N/A	N/A	N/A
LTE Band 41	0.406	0.023	0.679	1.108	N/A	N/A	N/A	

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 98 of 116	

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-“).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	
		1	2	1+2	1+2
Hotspot SAR	GPRS 850	0.584	0.754	1.338	
	GPRS 1900	0.424	0.754	1.178	
	UMTS 850	0.421	0.754	1.175	
	UMTS 1750	1.113	0.754	See Table Below	
	UMTS 1900	0.741	0.754	1.495	
	EVDO BC10 (\$90S)	0.318	0.754	1.072	
	EVDO BC0 (\$22H)	0.393	0.754	1.147	
	PCS EVDO	0.804	0.754	1.558	
	LTE Band 71	0.429	0.754	1.183	
	LTE Band 12	0.484	0.754	1.238	
	LTE Band 13	0.315	0.754	1.069	
	LTE Band 26 (Cell)	0.372	0.754	1.126	
	LTE Band 66 (AWS)	0.812	0.754	1.566	
	LTE Band 25 (PCS)	0.852	0.754	See Table Below	
	LTE Band 41	0.685	0.754	1.439	

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2	1+2			1	2	1+2
Hotspot SAR	Back	1.113	0.754	See Note 1	0.02	Hotspot SAR	Back	0.785	0.754	1.539
	Front	0.863	0.602	1.465	N/A		Front	0.852	0.602	1.454
	Top	-	0.754*	0.754	N/A		Top	-	0.754*	0.754
	Bottom	0.643	-	0.643	N/A		Bottom	0.671	-	0.671
	Left	0.797	0.260	1.057	N/A		Left	0.728	0.260	0.988

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLSR ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLSR ratio analysis.





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 99 of 116	

Table 12-10
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	
Hotspot SAR	GPRS 850	0.584	0.679	1.263
	GPRS 1900	0.424	0.679	1.103
	UMTS 850	0.421	0.679	1.100
	UMTS 1750	1.113	0.679	See Table Below
	UMTS 1900	0.741	0.679	1.420
	EVDO BC10 (§90S)	0.318	0.679	0.997
	EVDO BC0 (§22H)	0.393	0.679	1.072
	PCS EVDO	0.804	0.679	1.483
	LTE Band 71	0.429	0.679	1.108
	LTE Band 12	0.484	0.679	1.163
	LTE Band 13	0.315	0.679	0.994
	LTE Band 26 (Cell)	0.372	0.679	1.051
	LTE Band 66 (AWS)	0.812	0.679	1.491
	LTE Band 25 (PCS)	0.852	0.679	1.531
	LTE Band 41	0.685	0.679	1.364

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Hotspot SAR	Back	1.113	0.679	See Note 1	0.02
	Front	0.863	0.459	1.322	N/A
	Top	-	0.396	0.396	N/A
	Bottom	0.643	-	0.643	N/A
	Left	0.797	0.679*	1.476	N/A

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLSR ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLSR ratio analysis.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 100 of 116

**Table 12-11
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.584	0.023	0.607
	GPRS 1900	0.424	0.023	0.447
	UMTS 850	0.421	0.023	0.444
	UMTS 1750	1.113	0.023	1.136
	UMTS 1900	0.741	0.023	0.764
	EVDO BC10 (§90S)	0.318	0.023	0.341
	EVDO BC0 (§22H)	0.393	0.023	0.416
	PCS EVDO	0.804	0.023	0.827
	LTE Band 71	0.429	0.023	0.452
	LTE Band 12	0.484	0.023	0.507
	LTE Band 13	0.315	0.023	0.338
	LTE Band 26 (Cell)	0.372	0.023	0.395
	LTE Band 66 (AWS)	0.812	0.023	0.835
	LTE Band 25 (PCS)	0.852	0.023	0.875
	LTE Band 41	0.685	0.023	0.708





FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 101 of 116	

Table 12-12
Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Hotspot SAR	GPRS 850	0.584	0.023	0.679	1.286
	GPRS 1900	0.424	0.023	0.679	1.126
	UMTS 850	0.421	0.023	0.679	1.123
	UMTS 1750	1.113	0.023	0.679	See Table Below
	UMTS 1900	0.741	0.023	0.679	1.443
	EVDO BC10 (\$90S)	0.318	0.023	0.679	1.020
	EVDO BC0 (\$22H)	0.393	0.023	0.679	1.095
	PCS EVDO	0.804	0.023	0.679	1.506
	LTE Band 71	0.429	0.023	0.679	1.131
	LTE Band 12	0.484	0.023	0.679	1.186
	LTE Band 13	0.315	0.023	0.679	1.017
	LTE Band 26 (Cell)	0.372	0.023	0.679	1.074
	LTE Band 66 (AWS)	0.812	0.023	0.679	1.514
	LTE Band 25 (PCS)	0.852	0.023	0.679	1.554
LTE Band 41	0.685	0.023	0.679	1.387	

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	Bluetooth SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Hotspot SAR	Back	1.113	0.023	0.679	See Note 1	0.01	0.02	0.01
	Front	0.863	0.022	0.459	1.344	N/A	N/A	N/A
	Top	-	0.016	0.396	0.412	N/A	N/A	N/A
	Bottom	0.643	-	-	0.643	N/A	N/A	N/A
	Left	0.797	0.013	0.679*	1.489	N/A	N/A	N/A

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 102 of 116

12.6 Phablet Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.



Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore, no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN (Phablet)

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Phablet SAR	Back	2.596	2.185	See Note 1	0.08	Phablet SAR	Back	2.695	2.185	See Note 1	0.09
	Front	2.348	1.143	3.491	N/A		Front	2.273	1.143	3.416	N/A
	Top	-	2.185*	2.185	N/A		Top	-	2.185*	2.185	N/A
	Bottom	1.743	-	1.743	N/A		Bottom	1.611	-	1.611	N/A
	Left	3.142	0.648	3.790	N/A		Left	3.045	0.648	3.693	N/A
Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Phablet SAR	Back	2.634	2.185	See Note 1	0.08	Phablet SAR	Back	2.672	2.185	See Note 1	0.09
	Front	2.390	1.143	3.533	N/A		Front	2.834	1.143	3.977	N/A
	Top	-	2.185*	2.185	N/A		Top	-	2.185*	2.185	N/A
	Bottom	1.561	-	1.561	N/A		Bottom	1.470	-	1.470	N/A
	Left	2.756	0.648	3.404	N/A		Left	2.657	0.648	3.305	N/A
Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Phablet SAR	Back	2.926	2.185	See Note 1	0.09	Phablet SAR	Back	2.926	2.185	See Note 1	0.09
	Front	2.621	1.143	3.764	N/A		Front	2.621	1.143	3.764	N/A
	Top	-	2.185*	2.185	N/A		Top	-	2.185*	2.185	N/A
	Bottom	1.650	-	1.650	N/A		Bottom	1.650	-	1.650	N/A
	Left	2.780	0.648	3.428	N/A		Left	2.780	0.648	3.428	N/A

- No evaluation was performed to determine the aggregate 10g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.10 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 103 of 116	

12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g and 4 W/kg for 10g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g and ≤ 0.10 for 10g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2} \text{ (Body-Worn, Hotspot, Phablet)}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.7.1 Back Side Body-Worn and Hotspot SPLSR Evaluation and Analysis

Table 12-14
Peak SAR Locations for Body-Worn and Hotspot Back Side

Mode/Band	x (mm)	y (mm)
2.4 GHz WLAN	-43.00	57.60
5 GHz WLAN	8.00	67.00
UMTS 1750	-1.00	-55.50
Bluetooth	-38.00	49.20

Table 12-15
Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
UMTS 1750	2.4 GHz WLAN	1.113	0.754	1.867	120.65	0.02	2
UMTS 1750	5 GHz WLAN	1.113	0.679	1.792	122.83	0.02	
UMTS 1750	Bluetooth	1.113	0.023	1.136	111.05	0.01	
Bluetooth	5 GHz WLAN	0.023	0.679	0.702	49.32	0.01	




FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 104 of 116	

Table 12-16
Back Side SAR to Peak Location Separation Ratio Plots





12.7.2 Back Side Phablet SPLSR Evaluation and Analysis

Table 12-17
Peak SAR Locations for Phablet Back Side


Mode/Band	x (mm)	y (mm)
5 GHz WLAN	9.00	65.00
UMTS 1750	-2.50	-60.00
UMTS 1900	0.50	-58.50
PCS EVDO	0.50	-60.00
LTE Band 66	-1.00	-60.00
LTE Band 25	0.50	-58.50

Table 12-18
Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLSR Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	$(a+b)^{1.5}/D_{a-b}$	
UMTS 1750	5 GHz WLAN	2.596	2.185	4.781	125.53	0.08	1
UMTS 1900	5 GHz WLAN	2.695	2.185	4.88	123.79	0.09	2
PCS EVDO	5 GHz WLAN	2.634	2.185	4.819	125.29	0.08	3
LTE Band 66	5 GHz WLAN	2.672	2.185	4.857	125.40	0.09	4
LTE Band 25	5 GHz WLAN	2.926	2.185	5.111	123.79	0.09	5



FCC ID: ZNFX420TM	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 105 of 116

**Table 12-19
Back Side SAR to Peak Location Separation Ratio Plots**



12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.2

FCC ID: ZNFX420TM	 <small>PCTEST ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 106 of 116	

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:



- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

**Table 13-1
Head SAR Measurement Variability Results**

HEAD VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Side	Test Position	Data Rate (Mbps)	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
2450	2437.00	6	802.11b, 22 MHz Bandwidth	DSSS	Right	Cheek	1	1.080	0.958	1.13	N/A	N/A	N/A	N/A
5750	5805.00	161	802.11a, 20 MHz Bandwidth	OFDM	Right	Cheek	6	0.862	0.821	1.05	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 13-2
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1732.40	1412	UMTS 1750	RMC	back	10 mm	1.060	1.010	1.05	N/A	N/A	N/A	N/A
1900	1905.00	26590	LTE Band 25 (PCS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	front	10 mm	0.852	0.839	1.02	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 107 of 116

**Table 13-3
Phablet SAR Measurement Variability Results**

PHABLET VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Data Rate (Mbps)	Side	Spacing	Measured SAR (10g)	1st Repeated SAR (10g)	Ratio	2nd Repeated SAR (10g)	Ratio	3rd Repeated SAR (10g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1732.40	1412	UMTS 1750	RMC	N/A	left	0 mm	2.880	2.870	1.00	N/A	N/A	N/A	N/A
1900	1852.40	9262	UMTS 1900	RMC	N/A	left	0 mm	3.030	3.010	1.01	N/A	N/A	N/A	N/A
5250	5300.00	60	802.11a, 20 MHz Bandwidth	OFDM	6	back	0 mm	2.050	2.070	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams							

13.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for 1g and <3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 108 of 116	

14 ADDITIONAL TESTING PER FCC GUIDANCE


14.1 LTE Band 41 Power Class 2 and Power Class 3 Linearity

This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per May 2017 TCB Workshop Notes based on the device behavior, all SAR tests were performed using Power Class 3. SAR with Power Class 2 at the highest power and available duty factor was additionally performed for the Power Class 3 configuration with the highest SAR for each exposure condition. The linearity between the Power Class 2 and Power Class 3 SAR results and the respective frame averaged powers was calculated to determine that the results were linear. Per May 2017 TCB Workshop, no additional SAR measurements were required since the linearity between power classes was < 10% and all reported SAR values were < 1.4 W/kg for 1g and < 3.5 W/kg for 10g.



LTE Band 41 SAR testing with power class 2 at the highest power and available duty factor was additionally performed for the power class 3 configuration with the highest SAR for each exposure condition.

**Table 14-1
LTE Band 41 Head Linearity Data**

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.2	27.2
Measured Output Power (dBm)	24.2	26.96
Measured SAR (W/kg)	0.21	0.252
Measured Power (mW)	263.03	496.59
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	166.50	215.02
% deviation from expected linearity		-7.08%




**Figure 14-1
LTE Band 41 Head Linearity**



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 109 of 116

**Table 14-2
LTE Band 41 Body-Worn Linearity Data**

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.2	27.2
Measured Output Power (dBm)	24.2	26.96
Measured SAR (W/kg)	0.284	0.384
Measured Power (mW)	263.03	496.59
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	166.50	215.02
% deviation from expected linearity		4.70%




**Figure 14-2
LTE Band 41 Body-Worn Linearity**



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 110 of 116

**Table 14-3
LTE Band 41 Hotspot Linearity Data**

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24.2	27.2
Measured Output Power (dBm)	24.2	26.96
Measured SAR (W/kg)	0.458	0.648
Measured Power (mW)	263.03	496.59
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	166.50	215.02
% deviation from expected linearity		9.55%



**Figure 14-3
LTE Band 41 Hotspot Linearity**



FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 111 of 116

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	3/11/2019	Annual	3/11/2020	US39170122
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/30/2018	Annual	8/30/2019	MY40003841
Agilent	E4438C	ESG Vector Signal Generator	3/8/2019	Biennial	3/8/2021	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	3/11/2019	Biennial	3/11/2021	MY45090700
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	12/18/2018	Annual	12/18/2019	GB42230325
Agilent	E5515C	Wireless Communications Test Set	5/22/2018	Biennial	5/22/2020	GB43193563
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Agilent	N5182A	MXG Vector Signal Generator	11/28/2018	Annual	11/28/2019	MY47420603
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	US46470561
Anritsu	MA24106A	USB Power Sensor	4/17/2019	Annual	4/17/2020	1344556
Anritsu	MA24106A	USB Power Sensor	4/17/2019	Annual	4/17/2020	1349514
Anritsu	MA2411B	Pulse Power Sensor	11/20/2018	Annual	11/20/2019	1339008
Anritsu	MA2411B	Pulse Power Sensor	3/6/2019	Annual	3/6/2020	1339018
Anritsu	MT8820C	Radio Communication Analyzer	3/29/2019	Annual	3/29/2020	6201300731
Anritsu	MT8821C	Radio Communication Analyzer	1/25/2019	Annual	1/25/2020	6261895213
Anritsu	MT8821C	Radio Communication Analyzer	3/6/2019	Annual	3/6/2020	6201381794
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647811
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647802
Control Company	4352	Ultra Long Stem Thermometer	11/29/2018	Biennial	11/29/2020	181766816
Control Company	4352	Ultra Long Stem Thermometer	11/29/2018	Biennial	11/29/2020	181766817
Anritsu	ML2496A	Power Meter	10/21/2018	Annual	10/21/2019	1138001
Anritsu	ML2495A	Power Meter	11/20/2018	Annual	11/20/2019	1039008
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mitutoyo	CD-6°CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Pasternack	NC-100	Torque Wrench	11/7/2017	Biennial	11/7/2019	N/A
Pasternack	NC-100	Torque Wrench	5/23/2018	Biennial	5/23/2020	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	4/15/2019	Annual	4/15/2020	167284
Rohde & Schwarz	CMW500	Radio Communication Tester	4/19/2019	Annual	4/19/2020	128633
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/30/2019	Annual	1/30/2020	162125
Rohde & Schwarz	CMW500	Radio Communication Tester	4/17/2019	Annual	4/17/2020	167285
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/7/2019	Annual	5/7/2020	1070
SPEAG	D5GHzv2	5 GHz SAR Dipole	1/16/2018	Biennial	1/16/2020	1057
SPEAG	D5GHzv2	5 GHz SAR Dipole	8/10/2018	Annual	8/10/2019	1237
SPEAG	D2600V2	2600 MHz SAR Dipole	4/11/2018	Biennial	4/11/2020	1004
SPEAG	D2600V2	2600 MHz SAR Dipole	8/13/2018	Annual	8/13/2019	1126
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Biennial	9/11/2019	797
SPEAG	D2450V2	2450 MHz SAR Dipole	8/17/2017	Biennial	8/17/2019	719
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Annual	10/23/2019	50080
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Annual	10/23/2019	5d149
SPEAG	D1750V2	1750 MHz SAR Dipole	10/22/2018	Annual	10/22/2019	1150
SPEAG	D1765V2	1765 MHz SAR Dipole	5/23/2018	Biennial	5/23/2020	1008
SPEAG	D835V2	835 MHz SAR Dipole	3/13/2019	Annual	3/13/2020	4d047
SPEAG	D835V2	835 MHz SAR Dipole	1/22/2019	Annual	1/22/2020	4d132
SPEAG	D750V3	750 MHz SAR Dipole	1/15/2018	Biennial	1/15/2020	1003
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/13/2019	Annual	2/13/2020	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/8/2019	Annual	5/8/2020	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/18/2019	Annual	4/18/2020	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/22/2018	Annual	8/22/2019	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2019	Annual	1/15/2020	1530
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/20/2019	Annual	6/20/2020	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/14/2019	Annual	2/14/2020	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/8/2019	Annual	5/8/2020	728
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/3/2018	Annual	10/3/2019	1558
SPEAG	EX3DV4	SAR Probe	8/23/2018	Annual	8/23/2019	7308
SPEAG	EX3DV4	SAR Probe	5/16/2019	Annual	5/16/2020	7538
SPEAG	EX3DV4	SAR Probe	1/25/2019	Annual	1/25/2020	3589
SPEAG	EX3DV4	SAR Probe	5/16/2019	Annual	5/16/2020	7406
SPEAG	EX3DV4	SAR Probe	6/19/2019	Annual	6/19/2020	7409
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	3914
SPEAG	EX3DV4	SAR Probe	4/24/2019	Annual	4/24/2020	7357
SPEAG	EX3DV4	SAR Probe	1/24/2019	Annual	1/24/2020	7488
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	7417



Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

Each equipment was used solely within its calibration period.

FCC ID: ZNFX420TM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 112 of 116

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 113 of 116

17 CONCLUSION

17.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset		Page 114 of 116

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFX420TM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 115 of 116	

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFX420TM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1906260110-01-R1.ZNF	Test Dates: 07/01/19 - 07/19/19	DUT Type: Portable Handset	Page 116 of 116

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76
Medium: 835 MHz Head; Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.933 \text{ S/m}$; $\epsilon_r = 42.074$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-03-2019; Ambient Temp: 21.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Right Head, Cheek, Mid.ch, 3 Tx slots


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.79 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.542 W/kg

SAR(1 g) = 0.426 W/kg



0 dB = 0.503 W/kg = -2.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76
Medium: 1900 Head; Medium parameters used: |
f = 1880 MHz; $\sigma = 1.447$ S/m; $\epsilon_r = 40.752$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1880 MHz; Calibrated: 6/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/20/2019
Phantom: Front; Type: QD 000 P40 CD; Serial: 1686
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Left Head, Cheek, Mid.ch, 3 Tx slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.28 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.509 W/kg

SAR(1 g) = 0.323 W/kg



0 dB = 0.425 W/kg = -3.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Head; Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.096$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.21 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.356 W/kg

SAR(1 g) = 0.280 W/kg



0 dB = 0.331 W/kg = -4.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Head; Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.342 \text{ S/m}$; $\epsilon_r = 40.082$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1732.4 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.05 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.643 W/kg

SAR(1 g) = 0.407 W/kg



0 dB = 0.559 W/kg = -2.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Head; Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.444 \text{ S/m}$; $\epsilon_r = 40.98$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1880 MHz; Calibrated: 6/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/20/2019
Phantom: Front; Type: QD 000 P40 CD; Serial: 1686
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.50 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.940 W/kg

SAR(1 g) = 0.581 W/kg



0 dB = 0.765 W/kg = -1.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, Cellular CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1
Medium: 835 Head; Medium parameters used (interpolated):
 $f = 820.1 \text{ MHz}$; $\sigma = 0.885 \text{ S/m}$; $\epsilon_r = 40.118$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 820.1 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 90S, Right Head, Cheek, Mid.ch


Area Scan (8x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.27 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.257 W/kg

SAR(1 g) = 0.200 W/kg



0 dB = 0.238 W/kg = -6.23 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558


Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium: 835 Head; Medium parameters used (interpolated):
 $f = 836.52 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.096$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.52 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 22H, Left Head, Cheek, Mid.ch

Area Scan (8x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 19.34 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.394 W/kg
SAR(1 g) = 0.315 W/kg



0 dB = 0.368 W/kg = -4.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Head; Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.431 \text{ S/m}$; $\epsilon_r = 40.266$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 07-10-2019; Ambient Temp: 21.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1880 MHz; Calibrated: 6/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/20/2019
Phantom: Front; Type: QD 000 P40 CD; Serial: 1686
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO Rev A, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.07 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.661 W/kg



0 dB = 0.863 W/kg = -0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1
Medium: 750 Head; Medium parameters used (interpolated):
 $f = 680.5 \text{ MHz}$; $\sigma = 0.858 \text{ S/m}$; $\epsilon_r = 41.232$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 680.5 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 71, Right Head, Cheek, Mid.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.25 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.228 W/kg



0 dB = 0.262 W/kg = -5.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Medium: 750 Head; Medium parameters used (interpolated):
 $f = 707.5$ MHz; $\sigma = 0.866$ S/m; $\epsilon_r = 41.156$; $\rho = 1000$ kg/m³
Phantom section: Right Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 707.5 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 49 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.19 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.231 W/kg



0 dB = 0.265 W/kg = -5.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1
Medium: 750 Head; Medium parameters used (interpolated):
 $f = 782 \text{ MHz}$; $\sigma = 0.892 \text{ S/m}$; $\epsilon_r = 40.957$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 782 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.30 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.310 W/kg

SAR(1 g) = 0.247 W/kg



0 dB = 0.290 W/kg = -5.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1
Medium: 835 Head; Medium parameters used (interpolated):
 $f = 831.5 \text{ MHz}$; $\sigma = 0.889 \text{ S/m}$; $\epsilon_r = 40.103$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 831.5 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch, 15 MHz Bandwidth,
QPSK, 1 RB, 74 RB Offset**


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.12 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.379 W/kg

SAR(1 g) = 0.295 W/kg



0 dB = 0.349 W/kg = -4.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1720 MHz; Duty Cycle: 1:1
Medium: 1750 Head; Medium parameters used (interpolated): |
f = 1720 MHz; $\sigma = 1.335$ S/m; $\epsilon_r = 40.103$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1720 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Left Head, Cheek, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.61 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.566 W/kg

SAR(1 g) = 0.356 W/kg



0 dB = 0.482 W/kg = -3.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1
Medium: 1900 Head; Medium parameters used (interpolated):
 $f = 1905 \text{ MHz}$; $\sigma = 1.46 \text{ S/m}$; $\epsilon_r = 40.942$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 07-08-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1905 MHz; Calibrated: 6/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/20/2019
Phantom: Front; Type: QD 000 P40 CD; Serial: 1686
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.89 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.931 W/kg

SAR(1 g) = 0.565 W/kg



0 dB = 0.745 W/kg = -1.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2506 MHz; Duty Cycle: 1:2.31
Medium: 2450 Head; Medium parameters used (interpolated):
 $f = 2506 \text{ MHz}$; $\sigma = 1.852 \text{ S/m}$; $\epsilon_r = 39.319$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2506 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41 PC2, Right Head, Cheek, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.10 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.474 W/kg

SAR(1 g) = 0.252 W/kg



0 dB = 0.386 W/kg = -4.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05699

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Head; Medium parameters used (interpolated):
 $f = 2437 \text{ MHz}$; $\sigma = 1.839 \text{ S/m}$; $\epsilon_r = 38.516$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 07-15-2019; Ambient Temp: 21.4°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2437 MHz; Calibrated: 1/25/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1450; Calibrated: 8/22/2018
Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek, Ch 6, 1 Mbps


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (8x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.95 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 2.55 W/kg

SAR(1 g) = 1.08 W/kg



0 dB = 1.81 W/kg = 2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05681

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used:

$f = 5805 \text{ MHz}$; $\sigma = 5.171 \text{ S/m}$; $\epsilon_r = 34.106$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-18-2019; Ambient Temp: 23.4°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7406; ConvF(5.23, 5.23, 5.23) @ 5805 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 20; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Right Head, Cheek, Ch 161, 6 Mbps


Area Scan (12x20x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.405 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 4.47 W/kg

SAR(1 g) = 0.862 W/kg



0 dB = 2.21 W/kg = 3.44 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05699

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.297

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.8 \text{ S/m}$; $\epsilon_r = 37.774$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section;

Test Date: 07-18-2019; Ambient Temp: 23.8°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2441 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth, Right Head, Cheek, Ch 39, 1Mbps


Area Scan (11x19x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.152 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.201 W/kg

SAR(1 g) = 0.084 W/kg



0 dB = 0.132 W/kg = -8.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 54.011$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.04 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.741 W/kg

SAR(1 g) = 0.547 W/kg



0 dB = 0.674 W/kg = -1.71 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558


Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 836.6$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 54.011$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Body SAR, Right Edge, Mid.ch, 3 Tx Slots

Area Scan (11x13x1): Measurement grid: dx=5mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.28 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.814 W/kg
SAR(1 g) = 0.550 W/kg



0 dB = 0.721 W/kg = -1.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566


Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76
Medium: 1900 Body; Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.556 \text{ S/m}$; $\epsilon_r = 53.257$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 21.9°C; Tissue Temp: 23.4°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 3 Tx Slots

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.37 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.628 W/kg
SAR(1 g) = 0.331 W/kg



0 dB = 0.514 W/kg = -2.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566


Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76
Medium: 1900 Body; Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.556 \text{ S/m}$; $\epsilon_r = 53.257$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 21.9°C; Tissue Temp: 23.4°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Left Edge, Mid.ch, 3 Tx Slots

Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm
Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.57 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.637 W/kg
SAR(1 g) = 0.364 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 54.011$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.6 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.91 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.416 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Body; Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.523 \text{ S/m}$; $\epsilon_r = 51.84$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 23.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1732.4 MHz; Calibrated: 4/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/18/2019
Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Body SAR, Back side, Mid.ch


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.55 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 1.06 W/kg



0 dB = 1.55 W/kg = 1.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1907.6 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 52.141$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-29-2019; Ambient Temp: 20.7°C; Tissue Temp: 23.5°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1907.6 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.41 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.728 W/kg



0 dB = 1.18 W/kg = 0.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.561 \text{ S/m}$; $\epsilon_r = 52.673$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1880 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Left Edge, Mid.ch


Area Scan (9x14x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.56 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.740 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 820.1 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 54.158$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 820.1 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA Rule Part 90S, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.49 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.451 W/kg

SAR(1 g) = 0.333 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 820.1 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 54.158$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 820.1 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rule Part 90S, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.74 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.403 W/kg

SAR(1 g) = 0.302 W/kg



0 dB = 0.366 W/kg = -4.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 836.52 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 54.012$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.52 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.84 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.558 W/kg

SAR(1 g) = 0.413 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 836.52 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 54.012$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2019; Ambient Temp: 21.8°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 836.52 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/8/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1715
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.01 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.520 W/kg

SAR(1 g) = 0.383 W/kg



0 dB = 0.471 W/kg = -3.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.594 \text{ S/m}$; $\epsilon_r = 51.778$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1908.75 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS CDMA, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.46 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.768 W/kg



0 dB = 1.24 W/kg = 0.93 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):

$f = 1908.75$ MHz; $\sigma = 1.594$ S/m; $\epsilon_r = 51.778$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1908.75 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.73 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.775 W/kg



0 dB = 1.25 W/kg = 0.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1
Medium: 750 Body; Medium parameters used (interpolated):
 $f = 680.5 \text{ MHz}$; $\sigma = 0.918 \text{ S/m}$; $\epsilon_r = 57.636$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-12-2019; Ambient Temp: 23.4°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 680.5 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/14/2019
Phantom: Twin-SAM V5.0 Left 30; Type: QD 000 P40 CD; Serial: 1687
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 71, Body SAR, Back side, Mid.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.72 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.578 W/kg

SAR(1 g) = 0.427 W/kg



0 dB = 0.522 W/kg = -2.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Medium: 750 Body; Medium parameters used (interpolated):
 $f = 707.5 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 54.688$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 707.5 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/14/2019
Phantom: Twin-SAM V5.0 Front 30; Type: QD 000 P40 CD; Serial: 1646
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 49 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.36 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.511 W/kg

SAR(1 g) = 0.393 W/kg



0 dB = 0.467 W/kg = -3.31 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Medium: 750 Body; Medium parameters used (interpolated):
 $f = 707.5 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 54.688$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 707.5 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/14/2019
Phantom: Twin-SAM V5.0 Front 30; Type: QD 000 P40 CD; Serial: 1646
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12, Body SAR, Right Edge, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 49 RB Offset**


Area Scan (11x15x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.08 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.705 W/kg

SAR(1 g) = 0.474 W/kg



0 dB = 0.622 W/kg = -2.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05566

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1
Medium: 750 Body; Medium parameters used (interpolated):
 $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 53.914$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3914; ConvF(9.73, 9.73, 9.73) @ 782 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/14/2019
Phantom: Twin-SAM V5.0 Front 30; Type: QD 000 P40 CD; Serial: 1646
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.76 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.414 W/kg

SAR(1 g) = 0.311 W/kg



0 dB = 0.377 W/kg = -4.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05558

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1
Medium: 835 Body; Medium parameters used (interpolated):
 $f = 831.5 \text{ MHz}$; $\sigma = 0.97 \text{ S/m}$; $\epsilon_r = 55.247$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-09-2019; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7538; ConvF(9.85, 9.85, 9.85) @ 831.5 MHz; Calibrated: 5/16/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn728; Calibrated: 5/8/2019
Phantom: Left Twin-SAM V5.0 30; Type: QD 000 P40 CD; Serial: 1792
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch, 15 MHz Bandwidth,
QPSK, 1 RB, 74 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.76 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.516 W/kg

SAR(1 g) = 0.372 W/kg



0 dB = 0.462 W/kg = -3.35 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, LTE Band 66 (AWS); 1745 MHz; Duty Cycle: 1:1
Medium: 1750 Body; Medium parameters used (interpolated):
 $f = 1745 \text{ MHz}$; $\sigma = 1.461 \text{ S/m}$; $\epsilon_r = 52.765$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1745 MHz; Calibrated: 4/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/18/2019
Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, Mid.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.40 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.797 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1905 \text{ MHz}$; $\sigma = 1.589 \text{ S/m}$; $\epsilon_r = 52.601$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1905 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.80 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.785 W/kg



0 dB = 1.27 W/kg = 1.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1905 \text{ MHz}$; $\sigma = 1.589 \text{ S/m}$; $\epsilon_r = 52.601$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 20.1°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1905 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Body SAR, Front side, High.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.15 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.852 W/kg



0 dB = 1.26 W/kg = 1.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541


Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2506 MHz; Duty Cycle: 1:2.31
Medium: 2450 Body; Medium parameters used (interpolated):
 $f = 2506 \text{ MHz}$; $\sigma = 2.102 \text{ S/m}$; $\epsilon_r = 51.495$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2506 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/13/2019
Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41 PC2, Body SAR, Back side, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**

Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$
Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 14.46 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.755 W/kg
SAR(1 g) = 0.384 W/kg



0 dB = 0.613 W/kg = -2.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, _LTE Band 41 (Class 2); Frequency: 2506 MHz; Duty Cycle: 1:2.31
Medium: 2450 Body; Medium parameters used (interpolated):
 $f = 2506 \text{ MHz}$; $\sigma = 2.102 \text{ S/m}$; $\epsilon_r = 51.495$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2506 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/13/2019
Phantom: Left Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375
Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41 PC2, Body SAR, Bottom Edge, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.64 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.648 W/kg



0 dB = 1.10 W/kg = 0.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05681

Communication System: UID 0, _IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1
Medium: 2450 Body; Medium parameters used (interpolated):
 $f = 2462 \text{ MHz}$; $\sigma = 2.049 \text{ S/m}$; $\epsilon_r = 51.615$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.7°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2462 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/13/2019
Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.56 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.747 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05699

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: 5GHz Body; Medium parameters used:

$f = 5805 \text{ MHz}$; $\sigma = 6.289 \text{ S/m}$; $\epsilon_r = 48.321$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7308; ConvF(4.18, 4.18, 4.18) @ 5805 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth, Body SAR, Ch 161, 6 Mbps, Back Side


Area Scan (11x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 10.33 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.72 W/kg

SAR(1 g) = 0.661 W/kg



0 dB = 1.58 W/kg = 1.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05681


Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.297
Medium: 2450 Body; Medium parameters used (interpolated):
 $f = 2441$ MHz; $\sigma = 2.031$ S/m; $\epsilon_r = 51.514$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-18-2019; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2441 MHz; Calibrated: 2/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/13/2019
Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: TP1375
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side

Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (9x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.823 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.03 W/kg
SAR(1 g) = 0.016 W/kg



0 dB = 0.0247 W/kg = -16.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, UMTS; 1752.6 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1752.6$ MHz; $\sigma = 1.47$ S/m; $\epsilon_r = 52.738$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1752.6 MHz; Calibrated: 4/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/18/2019

Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Phablet SAR, Left Edge, High.ch


Area Scan (10x14x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 69.92 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(10 g) = 2.88 W/kg



0 dB = 13.5 W/kg = 11.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, UMTS, Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1852.4 \text{ MHz}$; $\sigma = 1.53 \text{ S/m}$; $\epsilon_r = 51.955$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1852.4 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Phablet SAR, Left Edge, Low.ch


Area Scan (11x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 72.97 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 20.7 W/kg

SAR(10 g) = 3.03 W/kg



0 dB = 13.6 W/kg = 11.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574

Communication System: UID 0, CDMA, Frequency: 1851.25 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1851.25 \text{ MHz}$; $\sigma = 1.529 \text{ S/m}$; $\epsilon_r = 51.959$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1851.25 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO, Phablet SAR, Left Edge, Low.ch


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 65.93 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 15.9 W/kg

SAR(10 g) = 2.62 W/kg



0 dB = 11.3 W/kg = 10.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05541

Communication System: UID 0, LTE Band 66 (AWS); 1770 MHz; Duty Cycle: 1:1
Medium: 1750 Body; Medium parameters used (interpolated):
 $f = 1770$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 52.671$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(8.26, 8.26, 8.26) @ 1770 MHz; Calibrated: 4/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/18/2019
Phantom: Twin-SAM V4.0 Front Right; Type: QD 000 P40 CC; Serial: 1167
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Phablet SAR, Front side, High.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 62.35 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 18.7 W/kg

SAR(10 g) = 2.8 W/kg



0 dB = 10.9 W/kg = 10.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05574


Communication System: UID 0, LTE Band 25 (PCS); 1860 MHz; Duty Cycle: 1:1
Medium: 1900 Body; Medium parameters used (interpolated):
 $f = 1860 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 51.929$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-10-2019; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7488; ConvF(8.37, 8.37, 8.37) @ 1860 MHz; Calibrated: 1/24/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1530; Calibrated: 1/15/2019
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Phablet SAR, Back side, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 70.96 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 17.4 W/kg
SAR(10 g) = 2.9 W/kg



0 dB = 12.6 W/kg = 11.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFX420TM; Type: Portable Handset; Serial: 05699

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5GHz Body; Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.523 \text{ S/m}$; $\epsilon_r = 49.277$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7308; ConvF(4.48, 4.48, 4.48) @ 5300 MHz, Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, U-NII-2A, 20 MHz Bandwidth, Phablet SAR, Ch 60, 6 Mbps, Back Side


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 41.25 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 72.9 W/kg

SAR(10 g) = 2.07 W/kg



0 dB = 38.7 W/kg = 15.88 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.881 \text{ S/m}$; $\epsilon_r = 41.048$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-10-2019; Ambient Temp: 22.5°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(8.67, 8.67, 8.67) @ 750 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 1.54 W/kg

Deviation(1 g) = -7.00%



0 dB = 2.10 W/kg = 3.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 MHz Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 42.078$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-03-2019; Ambient Temp: 21.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.20 W/kg

SAR(1 g) = 2.05 W/kg

Deviation(1 g) = 6.88%



0 dB = 2.80 W/kg = 4.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.89 \text{ S/m}$; $\epsilon_r = 40.098$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-08-2019; Ambient Temp: 20.5°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7406; ConvF(9.78, 9.78, 9.78) @ 835 MHz; Calibrated: 5/16/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/8/2019

Phantom: Twin-SAM V5.0 Right 30; Type: QD 000 P40 CD; Serial: 1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 1.9 W/kg

Deviation(1 g) = -0.94%



0 dB = 2.55 W/kg = 4.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.353 \text{ S/m}$; $\epsilon_r = 40.052$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 21.4°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN3589; ConvF(7.31, 7.31, 7.31) @ 1750 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.73 W/kg

Deviation(1 g) = 3.04%



0 dB = 5.76 W/kg = 7.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.46 \text{ S/m}$; $\epsilon_r = 40.732$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1900 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.92 W/kg

SAR(1 g) = 4.08 W/kg

Deviation(1 g) = 3.82%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used (interpolated):
 $f = 1900 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 40.949$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-08-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1900 MHz; Calibrated: 6/19/2019
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/20/2019
Phantom: Front; Type: QD 000 P40 CD; Serial: 1686
Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)

Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Peak SAR (extrapolated) = 7.61 W/kg
SAR(1 g) = 3.99 W/kg
Deviation(1 g) = 1.53%



0 dB = 6.34 W/kg = 8.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.444$ S/m; $\epsilon_r = 40.244$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2019; Ambient Temp: 21.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7409; ConvF(8.01, 8.01, 8.01) @ 1900 MHz; Calibrated: 6/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/20/2019

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.71 W/kg

SAR(1 g) = 4.03 W/kg

Deviation(1 g) = 2.54%



0 dB = 6.41 W/kg = 8.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450$ MHz; $\sigma = 1.808$ S/m; $\epsilon_r = 39.401$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-01-2019; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2450 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.32 W/kg

Deviation(1 g) = 0.95%



0 dB = 9.00 W/kg = 9.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 835 to 2450 Head; Medium parameters used:

$f = 2450$ MHz; $\sigma = 1.849$ S/m; $\epsilon_r = 38.492$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-15-2019; Ambient Temp: 21.4°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2450 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 5.21 W/kg

Deviation(1 g) = -1.14%;



0 dB = 9.00 W/kg = 9.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.806 \text{ S/m}$; $\epsilon_r = 37.758$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-18-2019; Ambient Temp: 23.8°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2450 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 5.35 W/kg

Deviation(1 g) = 1.52%



0 dB = 9.08 W/kg = 9.58 dBW/kg