

# Antenna Part Approved Sheet

Edition: V2.0 Date: 2021.08.19 Number: \_\_\_\_\_

Stage of material:  Trial production  Batch production

supplier: Shenzhen Cicent Communication Technology Co., Ltd.

Supplier Address: 505-506 ,ABlock,Donglian Building,Chuangye 2 road,Baoan District,Shenzhen,Guangdong,P.R china

Material name: FPC antenna

Material code: 35.02.1100058-000

Specification and model: CRL260/FPC antenna, 2.4G/ First generation IPEX, Line length

330mm/T=0.2mm PET support plate

## Supplier audit

Supplier sign off:		
( Seal ):		

## ShanChuan Robot countersignature

Made by	Checked by	Approved by

Enclosure:  Sample drawings or specifications  FAI  Performance test report  
 Reliability test report

PS:



# Contents

I: The report of passive data .....	2
II: 3D Active test report of antenna.....	5
III: Matching circuit .....	5
IV: Environmental treatment.....	6
V: Structure file .....	7
VI: The report of size detection.....	8
VII: The report of Reliability test.....	9


Change record			
Compile / change date	Reason for change	Changed content	Version
2021.06.21	First edition	First edition	V1.0
2021.08.19	Structural update	Add hand tear position to the antenna	V2.0

## I: The report of passive data



Agilent E5071C

### VSWR(S11) parameter:






Efficiency:

2400-2480 MHz			
Frequency(MHz)	Efficiency	Efficiency(dB )	Gain(dBi)
2400	31.85%	-4.97	-1.38
2410	32.10%	-4.94	-1.47
2420	33.15%	-4.80	-1.25
2430	32.35%	-4.90	-1.02
2440	31.01%	-5.09	-0.92
2450	31.46%	-5.02	-0.66
2460	30.55%	-5.15	-0.75
2470	32.29%	-4.91	-0.66
2480	33.70%	-4.72	-0.70
Average value	32.05%	-4.94	-0.98


3D Antenna radiation pattern






## Antenna radiation pattern


Theta=90.00deg



Phi=90.00deg



Phi=0.00deg





## II: 3D Active test report of antenna

11M/11M	Channel	TRP (dBm)	TIS (dBm)
WIFI B	1	14. 2	-80. 3
	7	12. 8	-82. 1
	13	12. 3	-81. 7

6M/54M	Channel	TRP (dBm)	TIS (dBm)
WIFI G	1	14. 9	-71. 5
	7	13. 5	-71. 2
	13	12. 9	-71. 2

6. 5M/65M	Channel	TRP (dBm)	TIS (dBm)
WIFI N	1	14. 5	-65. 8
	7	13. 8	-65. 1
	13	13. 2	-65. 0



OTA Standard Chamber

## III: Matching circuit



---

IV: Environmental treatment



V: Structure file



## VI: The report of size detection

## Sample size inspection report

Model type: 1S

Material: FPC+Cable

Date: 20210805

The test items		The standard	Sample inspection status					Result of decision	NOTE
			1	2	3	4	5		
appearance	scratch	According to finished product inspection specification.	✓	✓	✓	✓	✓	OK	
	friction		✓	✓	✓	✓	✓	OK	
	dirt		✓	✓	✓	✓	✓	OK	
	variant		✓	✓	✓	✓	✓	OK	
	other		✓	✓	✓	✓	✓	OK	
Structure size	A1	34. 20±0. 20	34. 18	34. 26	34. 25	34. 25	34. 20	OK	
	A2	26. 11±0. 20	26. 14	26. 06	26. 18	26. 08	26. 10	OK	

Approver: Zhang Rencun

Reviewers: Zhang Rencun

Tester: Xu Xiaoyan



## VII: The report of Reliability test

Reliability Test										
		The project name	The standard	1S						
NO:	Reliability test items			Testing tools	Number of tests	The test results				
						OK	NG	NA		
1	Salt spray test	In a closed environment of $35 \pm 2^\circ\text{C}$ , humidity > 85%, PH value in the range of 6.5–7.2, after spraying with 5% ± 1% NaCl solution for 24h, the product was removed and gently rinsed with water, and placed at room temperature for 2H to check the appearance.	There is no foaming, oxidation and coating shedding on the surface of the product.	Salt spray tester	5pcs	OK				
2	Constant temperature and humidity test	Put the tested product into a constant temperature testing machine, and place it at a temperature of $55 \pm 2^\circ\text{C}$ and humidity of 93+/-3% (RH) for 10h; After taking out the sample, place it at room temperature for 2 hours to observe the appearance.	Surface warping, blistering, paint or coating peeling are not allowed.	Constant temperature and humidity box	5pcs	OK				

Tester: Xu Xiaoyan      Reviewers: Zhang Rencun      Approver: Zhang Rencun