

FCC PART 15 SUBPART C TEST REPORT

for

Wireless Microphone System

Model No.: WMICG4-HU

FCC ID: ZPJ-WMICG4-HU

of

Applicant: Coban Technologies, Inc

**Address: 11375 W. Sam Houston Parkway S. # 800 Houston Texas
77031 United States**

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21304-13152-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS	4
1.5	GENERAL INFORMATION OF TEST ITEM	4
1.6	TEST STANDARDS	5
2	TECHNICAL TEST	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST	7
2.4	GENERAL TEST PROCEDURE	9
3	TEST RESULTS (ENCLOSURE)	11
3.1	PEAK OUTPUT POWER (TRANSMITTER)	12
3.2	EQUIVALENT ISOTROPIC RADIATED POWER	16
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	16
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	17
3.5	SPURIOUS EMISSIONS (TX)	18
3.6	RADIATED EMISSION ON THE BAND EDGE	24
3.7	MINIMUM 6 DB BANDWIDTH	27
3.8	PEAK POWER SPECTRAL DENSITY	31
3.9	RADIATED EMISSION FROM DIGITAL PART	35
3.10	POWER LINE CONDUCTED EMISSION	36
	APPENDIX	39



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

Tester:

September 02, 2013

Robert Ren

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

September 02, 2013

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,
Wanli Dist., New Taipei City 207,
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1



Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.
Accredited number: ./.
Street: ./.
Town: ./.
Country: ./.
Telephone: ./.
Fax: ./.

1.3 Details of approval holder

Name: Coban Technologies, Inc
Street: 11375 W. Sam Houston Parkway S. # 800
Town: Houston Texas 77031
Country: United States
Telephone: 2812778288
Fax: 2812778256



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

1.4 Application details

Date of receipt of test item: April 26, 2013
Date of test: from April 29, 2013 to August 29, 2013

1.5 General information of Test item

Type of test item: Wireless Microphone System
Model Number: WMICG4-HU
Brand Name: ./.
Multi-listing model number: ./.
Photos: see Appendix

Technical data

Frequency band: 902 MHz – 928 MHz
Frequency (CH 1): 904.2 MHz
Frequency (CH 10): 915 MHz
Frequency (CH 19): 925.8 MHz
Number of Channels: 19
Operation modes: duplex
Modulation Type: OQPSK

Fixed point-to-point operation: Yes / No

Type of Antenna: External: Dipole Antenna / Internal: Monopole Antenna
Antenna gain: External: 1.57 dBi / Internal: -1.22 dBi
Power supply: Adaptor: (I/P: 100-240V / 50-60Hz / 0.2A; O/P: +12V / 0.5A)
Battery: 3.7V / 1400mAh / 5.18Wh

Emission designator: 1M90G1D



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Host device: none

Classification :

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input checked="" type="checkbox"/>

Transmitter

External Antenna

Power (CH 1):	Conducted: 23.96 dBm
Power (CH 10):	Conducted: 23.70 dBm
Power (CH 19):	Conducted: 23.35 dBm

Unom

Internal Antenna

Power (CH 1):	Conducted: 24.84 dBm
Power (CH 10):	Conducted: 24.73 dBm
Power (CH 19):	Conducted: 24.51 dBm


Manufacturer: (if applicable)

Name:	Shenzhen Honmax Technology Limited
Street:	6/F., Block B, Productivity Building, No.5 Gaoxin 2nd Avenue, High-tech Park, Nanshan District,
Town:	Shenzhen,
Country:	PRC

Additional information: ./.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.247 (2011-10)



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.

2.2 Test environment


Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Power supply: Adapter: I/P: 100-240Vac, 50-60Hz, 0.2A
O/P: 12Vdc, 0.5A
Battery: 3.7Vdc, 1400mAh, 5.18Wh

Extreme conditions parameters:



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2012/9/5	2013/9/4
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2012/12/21	2013/12/20
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2013/3/4	2014/3/3
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S	Pre-test Use	
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2013/7/10	2014/7/9
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2012/9/5	2013/9/4
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2012/9/5	2013/9/4
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2012/10/12	2013/10/11
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2013/7/3	2014/7/2
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2013/3/4	2014/3/3
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2013/3/21	2014/3/20
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2013/3/4	2014/3/3
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2013/3/4	2014/3/3
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2013/3/4	2014/3/3
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2013/5/31	2014/5/30
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2013/3/4	2014/3/3
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2012/11/28	2013/11/27
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	EMCO	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2012/10/5	2013/10/4
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2012/10/12	2013/10/11
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2013/3/4	2014/3/3
ETSTW-RE 106	Humidity Temperature Meter	TES-1366	091011113	TES	2012/12/4	2013/12/3
ETSTW-RE 111	TRILOG Super Broadband test Antenna	VULB 9160	9160-3309	Schwarz beck	2012/12/13	2013/12/12
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	None	T-Power	Function test	
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2013/1/11	2014/1/10
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2013/6/28	2014/6/27
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2013/8/16	2014/8/15
ETSTW-RE 126	5GHz Notch filter	5NSL11-5800/E221.3-O/O	1	K&L Microwave	2013/8/16	2014/8/15
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2013/3/4	2014/3/3
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2013/8/13	2014/8/12
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2013/8/13	2014/8/12
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2012/10/5	2013/10/4
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2013/1/11	2014/1/10
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2013/1/11	2014/1/10
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2013/1/11	2014/1/10
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2013/1/11	2014/1/10
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2012/9/18	2013/9/17
ETSTW-Cable 010	BNC Cable	5 M BNC Cable	None	JYE BAO CO.,LTD.	2013/3/4	2014/3/3
ETSTW-Cable 011	BNC Cable	BNC Cable 1	None	JYE BAO CO.,LTD.	Pre-test Use NCR	
ETSTW-Cable 012	N TYPE To SMA Cable	Cable 012	None	JYE BAO CO.,LTD.	2013/3/4	2014/3/3
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2013/3/4	2014/3/3
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2013/3/4	2014/3/3
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2013/3/4	2014/3/3
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2013/3/4	2014/3/3
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2013/3/26	2014/3/25
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2013/3/4	2014/3/3
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2013/3/4	2014/3/3
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2012/10/12	2013/10/11
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2012/10/12	2013/10/11
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2013/3/4	2014/3/3
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S_Cable 10)	238092	HUBER+SUHNER	2012/11/28	2013/11/27
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2012/11/28	2013/11/27
ETSTW-Cable 047	Microwave Cable	SUCOFLEX 104	325518	HUBER+SUHNER	2012/11/28	2013/11/27
ETSTW-Cable 053	N TYPE To SMA Cable	RG142	None	JYE BAO CO.,LTD.	2013/3/26	2014/3/25
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2013/6/20	2014/6/19
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2009 5.2 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2009 6.4 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
33 20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2009 6.3.1. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207, Taiwan (R.O.C.). The Registration Number: 930600.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log(\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.4-2009 10.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent isotropically radiated Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c): 15.209	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Minimum 6 dB Bandwidth	15.247(d)(2)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Peak Power Spectral Density	15.247(e)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part	15.109	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The following is intentionally left blank.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU


3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

External Antenna




MAX OUTPUT POWER

Date: 26.AUG.2013 22:59:12




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



MAX OUTPUT POWER
Date: 26.AUG.2013 22:59:36




MAX OUTPUT POWER
Date: 26.AUG.2013 22:59:57




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU


Internal Antenna



MAX OUTPUT POWER
Date: 26.AUG.2013 22:56:38




MAX OUTPUT POWER
Date: 26.AUG.2013 22:57:14



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU




MAX OUTPUT POWER
 Date: 26.AUG.2013 22:58:16

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain
 EIRP = -- dBm + -- dBi
 = -- dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

- S – Power Density
- P – Output power ERP
- R – Distance
- D – Cable Loss
- AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	--	Peak value
D	dB		
AG	dBi	--	
G		--	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	--	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0

Explanation: This test is not applicable. Please refer to the SAR report of WMICG4-HU.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.
For radiated emission tests, the analyzer setting was as followings:

- Frequency \leq 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)
- Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)
- Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

$$\text{Duty cycle correction} = 20 \log (\text{dwell time}/ 100\text{ms})$$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: See attached diagrams in Appendix.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements).

Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

Max. reading – 20 dB


Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log(\text{dwell time}/100\text{ms})$

Note: No duty cycle correction was added to the reading of EUT.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Summary table with radiated data of the test plots

External Antenna

Model: WMICG4-HU Date: 2013/04/29~2013/8/25
 Mode: TX 904.2MHz (CH1) Temperature: 24 °C Engineer: Leon
 Polarization: Horizontal Humidity: 60 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
76.6533	11.27	peak	10.43	21.70	40.00	-18.30	155	100
193.2865	15.08	peak	12.28	27.36	43.50	-16.14	130	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	52.92	---	-5.65	47.27	---	74.00	54.00	-26.73	155	100
2711.4230	56.67	44.75	-3.08	53.59	41.67	74.00	54.00	-12.33	355	100
3616.8000	41.23	---	-1.49	39.74	---	74.00	54.00	-34.26	350	100
4521.0000	42.01	---	0.17	42.18	---	74.00	54.00	-31.82	140	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
30.0000	23.79	peak	13.17	36.96	40.00	-3.04	235	100
76.6533	14.75	peak	10.43	25.18	40.00	-14.82	105	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	51.02	---	-5.65	45.37	---	74.00	54.00	-28.63	155	100
2711.4230	45.95	---	-3.08	42.87	---	74.00	54.00	-31.13	120	100
3616.8000	41.51	---	-1.49	40.02	---	74.00	54.00	-33.98	130	100
4521.0000	41.57	---	0.17	41.74	---	74.00	54.00	-32.26	175	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

Mode: TX 915MHz (CH10)
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7754	9.15	peak	13.81	22.96	40.00	-17.04	185	100
76.6533	9.63	peak	10.43	20.06	40.00	-19.94	120	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1827.6550	50.47	---	-5.80	44.67	---	74.00	54.00	-29.33	150	100
2739.4790	57.20	46.75	-3.08	54.12	43.67	74.00	54.00	-10.33	0	100
3660.0000	41.26	---	-1.38	39.88	---	74.00	54.00	-34.12	125	100
4575.0000	42.13	---	0.11	42.24	---	74.00	54.00	-31.76	90	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7754	16.56	peak	13.81	30.37	40.00	-9.63	230	100
76.6533	13.47	peak	10.43	23.90	40.00	-16.10	160	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	51.90	---	-5.65	46.25	---	74.00	54.00	-27.75	150	100
2739.4790	52.42	---	-3.08	49.34	---	74.00	54.00	-24.66	230	100
3660.0000	41.09	---	-1.38	39.71	---	74.00	54.00	-34.29	175	100
4575.0000	42.37	---	0.11	42.48	---	74.00	54.00	-31.52	140	100

Mode: TX 925.8MHz (CH19)
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
39.7194	8.68	peak	14.02	22.70	40.00	-17.30	200	100
76.6533	9.80	peak	10.43	20.23	40.00	-19.77	170	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	54.25	---	-5.65	48.60	---	74.00	54.00	-25.40	20	100
2767.5350	55.77	---	-3.07	52.70	---	74.00	54.00	-21.30	350	100
3703.2000	41.66	---	-1.27	40.39	---	74.00	54.00	-33.61	105	100
4629.0000	41.06	---	0.12	41.18	---	74.00	54.00	-32.82	130	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7756	16.82	peak	13.81	30.63	40.00	-9.37	185	100
74.7094	13.58	peak	10.78	24.36	40.00	-15.64	130	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	48.45	---	-5.65	42.80	---	74.00	54.00	-31.20	155	100
2767.5350	52.55	---	-3.07	49.48	---	74.00	54.00	-24.52	120	100
3703.2000	42.01	---	-1.27	40.74	---	74.00	54.00	-33.26	185	100
4629.0000	41.93	---	0.12	42.05	---	74.00	54.00	-31.95	100	100

Internal Antenna

Mode: TX 904.2MHz (CH1)

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
76.6533	9.58	peak	10.43	20.01	40.00	-19.99	135	100
360.4607	8.25	peak	17.38	25.63	46.00	-20.37	170	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1799.5990	68.68	53.20	-6.09	62.59	47.11	74.00	54.00	-6.89	215	100
2711.4230	59.59	46.09	-3.08	56.51	43.01	74.00	54.00	-10.99	360	100
3623.2470	50.46	---	-1.48	48.98	---	74.00	54.00	-25.02	20	100
4535.0700	45.53	---	0.16	45.69	---	74.00	54.00	-28.31	330	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7756	16.75	peak	13.81	30.56	40.00	-9.44	85	100
74.7094	13.03	peak	10.78	23.81	40.00	-16.19	130	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1799.5990	70.56	52.16	-6.09	64.47	46.07	74.00	54.00	-7.93	360	100
2711.4230	55.03	---	-3.08	51.95	---	74.00	54.00	-22.05	155	100
3623.2470	51.70	---	-1.48	50.22	---	74.00	54.00	-23.78	130	100
4535.0700	44.12	---	0.16	44.28	---	74.00	54.00	-29.72	100	100

Mode: TX 915MHz (CH10)

Polarization: Horizontal


Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7754	7.96	peak	13.81	21.77	40.00	-18.23	155	100
74.7094	9.35	peak	10.78	20.13	40.00	-19.87	120	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1827.6550	68.18	51.11	-5.80	62.38	45.31	74.00	54.00	-8.69	305	100
2739.4790	60.54	47.22	-3.08	57.46	44.14	74.00	54.00	-9.86	0	100
3651.3020	48.73	---	-1.40	47.33	---	74.00	54.00	-26.67	185	100
4575.0000	43.91	---	0.11	44.02	---	74.00	54.00	-29.98	130	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7756	16.70	peak	13.81	30.51	40.00	-9.49	195	100
76.6533	13.95	peak	10.43	24.38	40.00	-15.62	140	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1827.6550	70.03	51.26	-5.80	64.23	45.46	74.00	54.00	-8.54	0	100
2739.4790	55.59	---	-3.08	52.51	---	74.00	54.00	-21.49	255	100
3665.3310	51.11	---	-1.36	49.75	---	74.00	54.00	-24.25	150	100
4575.0000	42.78	---	0.11	42.89	---	74.00	54.00	-31.11	310	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

Mode: TX 925.8MHz (CH19)
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7754	8.19	peak	13.81	22.00	40.00	-18.00	235	100
78.5972	9.96	peak	10.09	20.05	40.00	-19.95	150	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	69.02	52.40	-5.65	63.37	46.75	74.00	54.00	-7.25	295	100
2767.5350	57.31	45.35	-3.07	54.24	42.28	74.00	54.00	-11.72	0	100
3707.4150	47.75	---	-1.27	46.48	---	74.00	54.00	-27.52	120	100
4629.0000	41.80	---	0.12	41.92	---	74.00	54.00	-32.08	160	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
37.7756	16.79	peak	13.81	30.60	40.00	-9.40	220	100
76.6533	14.21	peak	10.43	24.64	40.00	-15.36	175	100


Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
1841.6830	69.99	52.11	-5.65	64.34	46.46	74.00	54.00	-7.54	0	100
2767.5350	52.95	---	-3.07	49.88	---	74.00	54.00	-24.12	350	100
3707.4150	47.78	---	-1.27	46.51	---	74.00	54.00	-27.49	155	100
4629.0000	41.36	---	0.12	41.48	---	74.00	54.00	-32.52	30	100

Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.72 dB, 1-18 GHz = ± 5.33 dB, 18-40 GHz = ± 3.43 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
6. See attached diagrams in appendix.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 111, ETSTW-RE 088, ETSTW-RE 018




Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.6 Radiated Emission on the band edge

According to FCC rules part 15 subpart C §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

External Antenna




BANDEGE

Date: 26.AUG.2013 22:34:39




Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU




BANDEDGE
Date: 26.AUG.2013 22:34:17

Internal Antenna




BANDEDGE
Date: 26.AUG.2013 22:30:22



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU



BANDEDGE
 Date: 26.AUG.2013 22:32:23

Limit:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-RE 055, ETSTW-RE 050




Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.

External Antenna




6DB BANDWIDTH

Date: 26.AUG.2013 21:34:33



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



6DB BANDWIDTH
Date: 26.AUG.2013 21:32:23




6DB BANDWIDTH
Date: 26.AUG.2013 21:33:35



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Internal Antenna




6DB BANDWIDTH

Date: 26.AUG.2013 21:37:07




6DB BANDWIDTH

Date: 26.AUG.2013 21:38:29



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU




6DB BANDWIDTH
 Date: 26.AUG.2013 21:39:50

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 050




Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.8 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.
The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

External Antenna




POWER DENSITY

Date: 26.AUG.2013 22:40:30




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



POWER DENSITY
Date: 26.AUG.2013 22:41:18




POWER DENSITY
Date: 26.AUG.2013 22:41:39




Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Internal Antenna




POWER DENSITY

Date: 26.AUG.2013 22:42:41




POWER DENSITY

Date: 26.AUG.2013 22:42:56



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU



POWER DENSITY
 Date: 26.AUG.2013 22:43:24

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

3.9 Radiated Emission from Digital Part


FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030
ETSTW-RE 111

Explanation: The test results are listed in the separated test report no.: W6M21304-13152-P-15B.




Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU

3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.




Site : Chamber_03
 Condition : FCC Part 15 Class B Conduction (QP) Phase: N
 EUT : W6M21304-13152 Power : 120VAC
 M/N: WMICG4-HU
 Test Mode :
 Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.3478	24.64	QP	10.11	34.75	59.01	-24.26	
	0.3478	10.88	AVG	10.11	20.99	49.01	-28.02	
*	0.3857	27.89	QP	10.11	38.00	58.16	-20.16	
	0.3857	13.95	AVG	10.11	24.06	48.16	-24.10	
	0.5315	15.01	QP	10.12	25.13	56.00	-30.87	
	0.5315	2.59	AVG	10.12	12.71	46.00	-33.29	
	0.6282	20.47	QP	10.13	30.60	56.00	-25.40	
	0.6282	4.42	AVG	10.13	14.55	46.00	-31.45	
	0.7430	18.18	QP	10.13	28.31	56.00	-27.69	
	0.7430	5.19	AVG	10.13	15.32	46.00	-30.68	
	0.7947	16.31	QP	10.13	26.44	56.00	-29.56	
	0.7947	2.48	AVG	10.13	12.61	46.00	-33.39	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
 FCC ID: ZPJ-WMICG4-HU



Site : Chamber_03
 Condition : FCC Part 15 Class B Conduction (QP) Phase: L1
 EUT : W6M21304-13152 Power : 120VAC
 M/N: WMICG4-HU
 Test Mode :
 Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.3550	27.02	QP	10.11	37.13	58.84	-21.71	
	0.3550	19.48	AVG	10.11	29.59	48.84	-19.25	
	0.3852	29.75	QP	10.11	39.86	58.17	-18.31	
*	0.3852	21.30	AVG	10.11	31.41	48.17	-16.76	
	0.5967	19.66	QP	10.12	29.78	56.00	-26.22	
	0.5967	12.29	AVG	10.12	22.41	46.00	-23.59	
	0.6372	20.45	QP	10.13	30.58	56.00	-25.42	
	0.6372	12.07	AVG	10.13	22.20	46.00	-23.80	
	0.7452	17.27	QP	10.13	27.40	56.00	-28.60	
	0.7452	7.89	AVG	10.13	18.02	46.00	-27.98	
	1.0805	15.53	QP	10.14	25.67	56.00	-30.33	
	1.0805	6.64	AVG	10.14	16.78	46.00	-29.22	

Frequency	Level (dBuV)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

- Note:**
1. The formula of measured value as: Test Result = Reading + Correction Factor
 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. Measurement uncertainty = ±1.60 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
 6. Up Line: QP Limit Line, Down Line: Ave Limit Line.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 004, ETSTW-CE 006, ETSTW-RE 045



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Appendix



Measurement diagrams

Spurious Emissions radiated



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU


Radiated Emission-Transmitter
External Antenna
TX 904.2MHz (CH1)
Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

TX 915MHz (CH10) Antenna Polarization H




Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU


TX 925.8MHz (CH19) Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

Internal Antenna
TX 904.2MHz (CH1)
Antenna Polarization H




Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU


TX 915MHz (CH10) Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU

TX 925.8MHz (CH19) Antenna Polarization H




Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21304-13152-C-1
FCC ID: ZPJ-WMICG4-HU



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.