

# FCC Test Report

**FCC ID** : ZQ6-WUBB743GN  
**Equipment** : WiFi USB module  
**Model No.** : WUBB-743GN\_WO PIN  
**Brand Name** : Ampak  
**Applicant** : Ampak Technology Inc.  
**Address** : No.1 Jen Ai Road, Hsinchu Industrial  
Park,Hukou, Hsinchu,Taiwan, 30352  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Apr. 01, 2015  
**Tested Date** : Apr. 09 ~ Apr. 13, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	7
1.3	Test Setup Chart .....	7
1.4	The Equipment List .....	8
1.5	Test Standards .....	9
1.6	Measurement Uncertainty .....	9
<b>2</b>	<b>TEST CONFIGURATION .....</b>	<b>10</b>
2.1	Testing Condition .....	10
2.2	The Worst Test Modes and Channel Details .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>11</b>
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth .....	14
3.3	RF Output Power .....	17
3.4	Power Spectral Density .....	19
3.5	Unwanted Emissions into Restricted Frequency Bands .....	21
3.6	Emissions in Non-Restricted Frequency Bands .....	49
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>62</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR540101	Rev. 01	Initial issue	Apr. 20, 2015

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.156MHz 51.36 (Margin -14.29dB) - QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2390.00MHz 72.97 (Margin -1.03dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 23.65	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	MCS 0-7
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	1	MCS 0-7

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

### 1.1.2 Antenna Details

Ant. No.	Model	Type	Gain (dBi)	Connector
1	AG-021318-0244-A0-0000	Dipole	2	UFL

### 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3.3Vdc from host
-------------------	------------------

### 1.1.4 Accessories

N/A

### 1.1.5 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

### 1.1.6 Test Tool and Duty Cycle

Test Tool	MTool, version: 2.0.1.1		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	99.76%	0.01
	HT20	99.48%	0.02
	HT40	98.13%	0.08


### 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	default
11b	2437	default
11b	2462	default
11g	2412	default
11g	2437	default
11g	2462	default
HT20	2412	default
HT20	2437	default
HT20	2462	default
HT40	2422	default
HT40	2437	default
HT40	2452	default

### 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	DoC	USB, 0.6m shielded.

### 1.3 Test Setup Chart



## 1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 17, 2014	Oct. 16, 2015
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 17, 2014	Nov. 16, 2015
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 26, 2014	Nov. 25, 2015
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 31, 2014	Dec. 30, 2015
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 16, 2014	Sep. 15, 2015
Receiver	Agilent	N9038A	MY53290044	Oct. 21, 2014	Oct. 20, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-562	Jan. 19, 2015	Jan. 18, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 03, 2015	Feb. 02, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 10, 2014	Nov. 09, 2015
Preamplifier	EMC	EMC02325	980187	Sep. 26, 2014	Sep. 25, 2015
Preamplifier	Agilent	83017A	MY53270014	Sep. 17, 2014	Sep. 16, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22601/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 09, 2015	Feb. 08, 2016
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 09, 2015	Feb. 08, 2016
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 09, 2015	Feb. 08, 2016
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 09, 2015	Feb. 08, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.



<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 29, 2014	Sep. 28, 2015
Power Sensor	Anritsu	MA2411B	1207366	Sep. 29, 2014	Sep. 28, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r02

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ( $k=2$ ))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	$\pm 34.134$ Hz
Conducted power	$\pm 0.808$ dB
Power density	$\pm 0.463$ dB
Conducted emission	$\pm 2.670$ dB
AC conducted emission	$\pm 2.92$ dB
Radiated emission $\leq 1$ GHz	$\pm 3.99$ dB
Radiated emission $> 1$ GHz	$\pm 5.52$ dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 64%	Kevin Ma
Radiated Emissions	03CH03-WS	25°C / 65%	Aska Huang
RF Conducted	TH01-WS	23°C / 61%	Felix Sung

- FCC site registration No.: 390588
- IC site registration No.: 10807C-1

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	11g	2437	6 Mbps	---
Radiated Emissions $\leq$ 1GHz	11g	2437	6 Mbps	---
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	---
Maximum Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	
<b>NOTE:</b>				
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The <b>Z-plane</b> results were found as the worst case and were shown in this report.				

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Power Phase</b>	Line		


  



	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	LISN factor dB	cable loss dB	Remark
1*	0.162	40.08	55.34	-15.26	39.93	0.07	0.08	Average
2	0.162	49.72	65.34	-15.62	49.57	0.07	0.08	QP
3	0.238	29.46	52.17	-22.71	29.29	0.07	0.10	Average
4	0.238	39.20	62.17	-22.97	39.03	0.07	0.10	QP
5	0.415	22.38	47.55	-25.17	22.20	0.07	0.11	Average
6	0.415	34.22	57.55	-23.33	34.04	0.07	0.11	QP
7	0.541	19.15	46.00	-26.85	18.95	0.07	0.13	Average
8	0.541	32.71	56.00	-23.29	32.51	0.07	0.13	QP
9	1.888	21.26	46.00	-24.74	20.93	0.10	0.23	Average
10	1.888	31.62	56.00	-24.38	31.29	0.10	0.23	QP
11	9.302	30.11	50.00	-19.89	29.61	0.20	0.30	Average
12	9.302	35.63	60.00	-24.37	35.13	0.20	0.30	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB).  
 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Power Phase</b>	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	39.46	55.65	-16.19	39.31	0.07	0.08	Average
2*	0.156	51.36	65.65	-14.29	51.21	0.07	0.08	QP
3	0.252	29.16	51.69	-22.53	28.99	0.07	0.10	Average
4	0.252	40.45	61.69	-21.24	40.28	0.07	0.10	QP
5	0.389	26.33	48.08	-21.75	26.15	0.07	0.11	Average
6	0.389	38.23	58.08	-19.85	38.05	0.07	0.11	QP
7	0.564	20.00	46.00	-26.00	19.80	0.07	0.13	Average
8	0.564	33.63	56.00	-22.37	33.43	0.07	0.13	QP
9	2.077	23.66	46.00	-22.34	23.32	0.10	0.24	Average
10	2.077	32.97	56.00	-23.03	32.63	0.10	0.24	QP
11	9.204	23.12	50.00	-26.88	22.60	0.22	0.30	Average
12	9.204	29.57	60.00	-30.43	29.05	0.22	0.30	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).  
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

## 3.2 6dB and Occupied Bandwidth

### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures


#### 6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup




### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	1	2412	7.01	---	---	---	500
11b	1	2437	8.06	---	---	---	500
11b	1	2462	7.07	---	---	---	500
11g	1	2412	14.49	---	---	---	500
11g	1	2437	14.43	---	---	---	500
11g	1	2462	14.84	---	---	---	500
HT20	1	2412	15.42	---	---	---	500
HT20	1	2437	15.13	---	---	---	500
HT20	1	2462	15.54	---	---	---	500
HT40	1	2422	35.13	---	---	---	500
HT40	1	2437	35.13	---	---	---	500
HT40	1	2452	35.13	---	---	---	500



Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	1	2412	12.22	---	---	---
11b	1	2437	12.23	---	---	---
11b	1	2462	12.24	---	---	---
11g	1	2412	16.48	---	---	---
11g	1	2437	16.46	---	---	---
11g	1	2462	16.47	---	---	---
HT20	1	2412	17.52	---	---	---
HT20	1	2437	17.53	---	---	---
HT20	1	2462	17.52	---	---	---
HT40	1	2422	36.13	---	---	---
HT40	1	2437	36.19	---	---	---
HT40	1	2452	36.19	---	---	---





## 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain  $\leq$  6dBi, no any corresponding reduction is in output power limit.
- Antenna gain  $>$  6dBi
  - Non Fixed, point to point operations.  
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
  - Fixed, point to point operations  
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

### 3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
    2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
    3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
  - Power meter**
    1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power ( For reference only )
  - Power meter**
    1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.3.3 Test Setup



### 3.3.4 Test Result of Maximum Output Power

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Peak conducted output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	19.91	---	---	---	97.949	19.91	30.00
11b	1	2437	20.06	---	---	---	101.391	20.06	30.00
11b	1	2462	20.03	---	---	---	100.693	20.03	30.00
11g	1	2412	23.58	---	---	---	228.034	23.58	30.00
11g	1	2437	23.65	---	---	---	231.739	<b>23.65</b>	30.00
11g	1	2462	23.62	---	---	---	230.144	23.62	30.00
HT20	1	2412	22.51	---	---	---	178.238	22.51	30.00
HT20	1	2437	22.65	---	---	---	184.077	22.65	30.00
HT20	1	2462	22.46	---	---	---	176.198	22.46	30.00
HT40	1	2422	22.12	---	---	---	162.930	22.12	30.00
HT40	1	2437	22.16	---	---	---	164.437	22.16	30.00
HT40	1	2452	22.08	---	---	---	161.436	22.08	30.00

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted (average) output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	17.05	---	---	---	50.699	17.05	30.00
11b	1	2437	17.12	---	---	---	51.523	<b>17.12</b>	30.00
11b	1	2462	17.08	---	---	---	51.050	17.08	30.00
11g	1	2412	13.80	---	---	---	23.988	13.80	30.00
11g	1	2437	13.96	---	---	---	24.889	13.96	30.00
11g	1	2462	13.95	---	---	---	24.831	13.95	30.00
HT20	1	2412	12.87	---	---	---	19.364	12.87	30.00
HT20	1	2437	12.89	---	---	---	19.454	12.89	30.00
HT20	1	2462	12.81	---	---	---	19.099	12.81	30.00
HT40	1	2422	12.61	---	---	---	18.239	12.61	30.00
HT40	1	2437	12.64	---	---	---	18.365	12.64	30.00
HT40	1	2452	12.45	---	---	---	17.579	12.45	30.00

Note: Conducted average output power is for reference only.

## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures


- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 30kHz, VBW = 100kHz.
  2. Detector = Peak, Sweep time = auto couple.
  3. Trace mode = max hold, allow trace to fully stabilize.
  4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 100kHz, VBW = 300 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Set the sweep time to:  $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$ .
  4. Perform the measurement over a single sweep.
  5. Use the peak marker function to determine the maximum amplitude level.

### 3.4.3 Test Setup



### 3.4.4 Test Result of Power Spectral Density

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	1	2412	-5.86	8.00
11b	1	2437	-6.66	8.00
11b	1	2462	-4.23	8.00
11g	1	2412	-11.85	8.00
11g	1	2437	-12.79	8.00
11g	1	2462	-12.52	8.00
HT20	1	2412	-13.89	8.00
HT20	1	2437	-13.28	8.00
HT20	1	2462	-12.52	8.00
HT40	1	2422	-15.75	8.00
HT40	1	2437	-16.20	8.00
HT40	1	2452	-16.28	8.00



## 3.5 Unwanted Emissions into Restricted Frequency Bands

### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

**Note:**


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.5.3 Test Setup


#### Radiated Emissions below 1 GHz



#### Radiated Emissions above 1 GHz




### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2437						
Polarization	Horizontal								
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	63.95	36.96	40.00	-3.04	51.81	-14.85	Peak	---	---
2	165.80	37.37	43.50	-6.13	51.26	-13.89	Peak	---	---
3	232.73	37.23	46.00	-8.77	52.42	-15.19	Peak	---	---
4	527.61	36.75	46.00	-9.25	44.07	-7.32	Peak	---	---
5	769.14	38.05	46.00	-7.95	41.00	-2.95	Peak	---	---
6	898.15	40.52	46.00	-5.48	41.23	-0.71	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	63.95	35.43	40.00	-4.57	50.28	-14.85	Peak	---	---
2	165.80	32.37	43.50	-11.13	46.26	-13.89	Peak	---	---
3	232.73	30.87	46.00	-15.13	46.06	-15.19	Peak	---	---
4	566.41	32.24	46.00	-13.76	38.86	-6.62	Peak	---	---
5	696.39	33.17	46.00	-12.83	37.54	-4.37	Peak	---	---
6	797.27	41.12	46.00	-4.88	43.72	-2.60	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Horizontal		


  



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.72	54.00	-15.28	39.94	-1.22	Average	---	---
2	2390.00	52.32	74.00	-21.68	53.54	-1.22	Peak	---	---
3	3618.00	28.83	54.00	-25.17	26.53	2.30	Average	---	---
4	3618.00	41.67	74.00	-32.33	39.37	2.30	Peak	---	---
5	4824.00	35.90	54.00	-18.10	28.89	7.01	Average	---	---
6	4824.00	46.21	74.00	-27.79	39.20	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.44	54.00	-11.56	43.66	-1.22	Average	---	---
2	2390.00	55.98	74.00	-18.02	57.20	-1.22	Peak	---	---
3	3618.00	34.61	54.00	-19.39	32.31	2.30	Average	---	---
4	3618.00	43.85	74.00	-30.15	41.55	2.30	Peak	---	---
5	4824.00	33.14	54.00	-20.86	26.13	7.01	Average	---	---
6	4824.00	45.75	74.00	-28.25	38.74	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	29.20	54.00	-24.80	26.84	2.36	Average	---	---
2	3655.50	41.55	74.00	-32.45	39.19	2.36	Peak	---	---
3	4874.00	37.06	54.00	-16.94	30.25	6.81	Average	---	---
4	4874.00	46.79	74.00	-27.21	39.98	6.81	Peak	---	---
5	7311.00	37.80	54.00	-16.20	26.84	10.96	Average	---	---
6	7311.00	49.76	74.00	-24.24	38.80	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	34.91	54.00	-19.09	32.55	2.36	Average	---	---
2	3655.50	43.98	74.00	-30.02	41.62	2.36	Peak	---	---
3	4874.00	33.34	54.00	-20.66	26.53	6.81	Average	---	---
4	4874.00	45.37	74.00	-28.63	38.56	6.81	Peak	---	---
5	7311.00	38.89	54.00	-15.11	27.93	10.96	Average	---	---
6	7311.00	50.83	74.00	-23.17	39.87	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.05	54.00	-13.95	40.94	-0.89	Average	---	---
2	2483.50	52.68	74.00	-21.32	53.57	-0.89	Peak	---	---
3	3693.00	29.23	54.00	-24.77	26.81	2.42	Average	---	---
4	3693.00	41.80	74.00	-32.20	39.38	2.42	Peak	---	---
5	4924.00	36.15	54.00	-17.85	29.55	6.60	Average	---	---
6	4924.00	46.30	74.00	-27.70	39.70	6.60	Peak	---	---
7	7386.00	37.54	54.00	-16.46	26.42	11.12	Average	---	---
8	7386.00	49.65	74.00	-24.35	38.53	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	43.65	54.00	-10.35	44.54	-0.89	Average	---	---
2	2483.50	56.80	74.00	-17.20	57.69	-0.89	Peak	---	---
3	3693.00	34.51	54.00	-19.49	32.09	2.42	Average	---	---
4	3693.00	44.80	74.00	-29.20	42.38	2.42	Peak	---	---
5	4924.00	32.50	54.00	-21.50	25.90	6.60	Average	---	---
6	4924.00	45.29	74.00	-28.71	38.69	6.60	Peak	---	---
7	7386.00	38.53	54.00	-15.47	27.41	11.12	Average	---	---
8	7386.00	50.65	74.00	-23.35	39.53	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412																																																																						
Polarization	Horizontal																																																																								
																																																																									
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>43.88</td> <td>54.00</td> <td>-10.12</td> <td>45.10</td> <td>-1.22</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>64.94</td> <td>74.00</td> <td>-9.06</td> <td>66.16</td> <td>-1.22</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>3618.00</td> <td>28.77</td> <td>54.00</td> <td>-25.23</td> <td>26.47</td> <td>2.30</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>3618.00</td> <td>40.85</td> <td>74.00</td> <td>-33.15</td> <td>38.55</td> <td>2.30</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4824.00</td> <td>33.25</td> <td>54.00</td> <td>-20.75</td> <td>26.24</td> <td>7.01</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4824.00</td> <td>45.57</td> <td>74.00</td> <td>-28.43</td> <td>38.56</td> <td>7.01</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	2390.00	43.88	54.00	-10.12	45.10	-1.22	Average	---	2	2390.00	64.94	74.00	-9.06	66.16	-1.22	Peak	---	3	3618.00	28.77	54.00	-25.23	26.47	2.30	Average	---	4	3618.00	40.85	74.00	-33.15	38.55	2.30	Peak	---	5	4824.00	33.25	54.00	-20.75	26.24	7.01	Average	---	6	4824.00	45.57	74.00	-28.43	38.56	7.01	Peak	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																				
1	2390.00	43.88	54.00	-10.12	45.10	-1.22	Average	---																																																																	
2	2390.00	64.94	74.00	-9.06	66.16	-1.22	Peak	---																																																																	
3	3618.00	28.77	54.00	-25.23	26.47	2.30	Average	---																																																																	
4	3618.00	40.85	74.00	-33.15	38.55	2.30	Peak	---																																																																	
5	4824.00	33.25	54.00	-20.75	26.24	7.01	Average	---																																																																	
6	4824.00	45.57	74.00	-28.43	38.56	7.01	Peak	---																																																																	
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																									

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.47	54.00	-5.53	49.69	-1.22	Average	---	---
2	2390.00	72.81	74.00	-1.19	74.03	-1.22	Peak	---	---
3	3618.00	34.67	54.00	-19.33	32.37	2.30	Average	---	---
4	3618.00	44.73	74.00	-29.27	42.43	2.30	Peak	---	---
5	4824.00	33.37	54.00	-20.63	26.36	7.01	Average	---	---
6	4824.00	45.52	74.00	-28.48	38.51	7.01	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	29.32	54.00	-24.68	26.96	2.36	Average	---	---
2	3655.50	40.92	74.00	-33.08	38.56	2.36	Peak	---	---
3	4874.00	33.08	54.00	-20.92	26.27	6.81	Average	---	---
4	4874.00	45.36	74.00	-28.64	38.55	6.81	Peak	---	---
5	7311.00	37.43	54.00	-16.57	26.47	10.96	Average	---	---
6	7311.00	49.34	74.00	-24.66	38.38	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	34.84	54.00	-19.16	32.48	2.36	Average	---	---
2	3655.50	44.92	74.00	-29.08	42.56	2.36	Peak	---	---
3	4874.00	33.09	54.00	-20.91	26.28	6.81	Average	---	---
4	4874.00	45.49	74.00	-28.51	38.68	6.81	Peak	---	---
5	7311.00	37.19	54.00	-16.81	26.23	10.96	Average	---	---
6	7311.00	49.43	74.00	-24.57	38.47	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.34	54.00	-9.66	45.23	-0.89	Average	---	---
2	2483.50	64.86	74.00	-9.14	65.75	-0.89	Peak	---	---
3	3693.00	29.84	54.00	-24.16	27.42	2.42	Average	---	---
4	3693.00	40.98	74.00	-33.02	38.56	2.42	Peak	---	---
5	4924.00	32.96	54.00	-21.04	26.36	6.60	Average	---	---
6	4924.00	45.22	74.00	-28.78	38.62	6.60	Peak	---	---
7	7386.00	37.34	54.00	-16.66	26.22	11.12	Average	---	---
8	7386.00	49.59	74.00	-24.41	38.47	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.02	54.00	-5.98	48.91	-0.89	Average	---	---
2	2483.50	72.11	74.00	-1.89	73.00	-0.89	Peak	---	---
3	3693.00	35.04	54.00	-18.96	32.62	2.42	Average	---	---
4	3693.00	45.00	74.00	-29.00	42.58	2.42	Peak	---	---
5	4924.00	32.14	54.00	-21.86	25.54	6.60	Average	---	---
6	4924.00	44.91	74.00	-29.09	38.31	6.60	Peak	---	---
7	7386.00	37.36	54.00	-16.64	26.24	11.12	Average	---	---
8	7386.00	49.68	74.00	-24.32	38.56	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412																																																																						
Polarization	Horizontal																																																																								
																																																																									
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>44.12</td> <td>54.00</td> <td>-9.88</td> <td>45.34</td> <td>-1.22</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>65.12</td> <td>74.00</td> <td>-8.88</td> <td>66.34</td> <td>-1.22</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>3618.00</td> <td>28.64</td> <td>54.00</td> <td>-25.36</td> <td>26.34</td> <td>2.30</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>3618.00</td> <td>40.53</td> <td>74.00</td> <td>-33.47</td> <td>38.23</td> <td>2.30</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4824.00</td> <td>33.40</td> <td>54.00</td> <td>-20.60</td> <td>26.39</td> <td>7.01</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4824.00</td> <td>45.51</td> <td>74.00</td> <td>-28.49</td> <td>38.50</td> <td>7.01</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	2390.00	44.12	54.00	-9.88	45.34	-1.22	Average	---	2	2390.00	65.12	74.00	-8.88	66.34	-1.22	Peak	---	3	3618.00	28.64	54.00	-25.36	26.34	2.30	Average	---	4	3618.00	40.53	74.00	-33.47	38.23	2.30	Peak	---	5	4824.00	33.40	54.00	-20.60	26.39	7.01	Average	---	6	4824.00	45.51	74.00	-28.49	38.50	7.01	Peak	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																				
1	2390.00	44.12	54.00	-9.88	45.34	-1.22	Average	---																																																																	
2	2390.00	65.12	74.00	-8.88	66.34	-1.22	Peak	---																																																																	
3	3618.00	28.64	54.00	-25.36	26.34	2.30	Average	---																																																																	
4	3618.00	40.53	74.00	-33.47	38.23	2.30	Peak	---																																																																	
5	4824.00	33.40	54.00	-20.60	26.39	7.01	Average	---																																																																	
6	4824.00	45.51	74.00	-28.49	38.50	7.01	Peak	---																																																																	
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																									

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.88	54.00	-5.12	50.10	-1.22	Average	---	---
2	2390.00	72.97	74.00	-1.03	74.19	-1.22	Peak	---	---
3	3618.00	34.74	54.00	-19.26	32.44	2.30	Average	---	---
4	3618.00	44.98	74.00	-29.02	42.68	2.30	Peak	---	---
5	4824.00	33.50	54.00	-20.50	26.49	7.01	Average	---	---
6	4824.00	45.66	74.00	-28.34	38.65	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	29.21	54.00	-24.79	26.85	2.36	Average	---	---
2	3655.50	40.85	74.00	-33.15	38.49	2.36	Peak	---	---
3	4874.00	33.26	54.00	-20.74	26.45	6.81	Average	---	---
4	4874.00	45.12	74.00	-28.88	38.31	6.81	Peak	---	---
5	7311.00	37.24	54.00	-16.76	26.28	10.96	Average	---	---
6	7311.00	49.43	74.00	-24.57	38.47	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	34.69	54.00	-19.31	32.33	2.36	Average	---	---
2	3655.50	44.53	74.00	-29.47	42.17	2.36	Peak	---	---
3	4874.00	33.33	54.00	-20.67	26.52	6.81	Average	---	---
4	4874.00	45.30	74.00	-28.70	38.49	6.81	Peak	---	---
5	7311.00	37.29	54.00	-16.71	26.33	10.96	Average	---	---
6	7311.00	49.37	74.00	-24.63	38.41	10.96	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.88	54.00	-9.12	45.77	-0.89	Average	---	---
2	2483.50	65.33	74.00	-8.67	66.22	-0.89	Peak	---	---
3	3693.00	29.80	54.00	-24.20	27.38	2.42	Average	---	---
4	3693.00	40.91	74.00	-33.09	38.49	2.42	Peak	---	---
5	4924.00	33.02	54.00	-20.98	26.42	6.60	Average	---	---
6	4924.00	44.85	74.00	-29.15	38.25	6.60	Peak	---	---
7	7386.00	37.66	54.00	-16.34	26.54	11.12	Average	---	---
8	7386.00	49.83	74.00	-24.17	38.71	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.33	54.00	-5.67	49.22	-0.89	Average	---	---
2	2483.50	72.84	74.00	-1.16	73.73	-0.89	Peak	---	---
3	3693.00	34.91	54.00	-19.09	32.49	2.42	Average	---	---
4	3693.00	44.94	74.00	-29.06	42.52	2.42	Peak	---	---
5	4924.00	32.77	54.00	-21.23	26.17	6.60	Average	---	---
6	4924.00	45.03	74.00	-28.97	38.43	6.60	Peak	---	---
7	7386.00	37.30	54.00	-16.70	26.18	11.12	Average	---	---
8	7386.00	49.55	74.00	-24.45	38.43	11.12	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40


<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2422
<b>Polarization</b>	Horizontal		

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.71	54.00	-11.29	43.93	-1.22	Average	---	---
2	2390.00	66.43	74.00	-7.57	67.65	-1.22	Peak	---	---
3	3633.00	28.63	54.00	-25.37	26.30	2.33	Average	---	---
4	3633.00	40.66	74.00	-33.34	38.33	2.33	Peak	---	---
5	4844.00	33.18	54.00	-20.82	26.24	6.94	Average	---	---
6	4844.00	45.47	74.00	-28.53	38.53	6.94	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2422
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.60	54.00	-5.40	49.82	-1.22	Average	---	---
2	2390.00	70.73	74.00	-3.27	71.95	-1.22	Peak	---	---
3	3633.00	34.70	54.00	-19.30	32.37	2.33	Average	---	---
4	3633.00	44.88	74.00	-29.12	42.55	2.33	Peak	---	---
5	4844.00	33.15	54.00	-20.85	26.21	6.94	Average	---	---
6	4844.00	45.47	74.00	-28.53	38.53	6.94	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	28.79	54.00	-25.21	26.43	2.36	Average	---	---
2	3655.50	40.89	74.00	-33.11	38.53	2.36	Peak	---	---
3	4874.00	33.23	54.00	-20.77	26.42	6.81	Average	---	---
4	4874.00	45.17	74.00	-28.83	38.36	6.81	Peak	---	---
5	7311.00	37.50	54.00	-16.50	26.54	10.96	Average	---	---
6	7311.00	49.22	74.00	-24.78	38.26	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3655.50	34.66	54.00	-19.34	32.30	2.36	Average	---	---
2	3655.50	44.89	74.00	-29.11	42.53	2.36	Peak	---	---
3	4874.00	32.97	54.00	-21.03	26.16	6.81	Average	---	---
4	4874.00	45.20	74.00	-28.80	38.39	6.81	Peak	---	---
5	7311.00	37.07	54.00	-16.93	26.11	10.96	Average	---	---
6	7311.00	49.38	74.00	-24.62	38.42	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	42.21	54.00	-11.79	43.10	-0.89	Average	---	---
2	2483.50	62.17	74.00	-11.83	63.06	-0.89	Peak	---	---
3	3678.00	28.84	54.00	-25.16	26.45	2.39	Average	---	---
4	3678.00	41.01	74.00	-32.99	38.62	2.39	Peak	---	---
5	4904.00	33.04	54.00	-20.96	26.34	6.70	Average	---	---
6	4904.00	45.10	74.00	-28.90	38.40	6.70	Peak	---	---
7	7356.00	37.27	54.00	-16.73	26.21	11.06	Average	---	---
8	7356.00	49.44	74.00	-24.56	38.38	11.06	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	49.35	54.00	-4.65	50.24	-0.89	Average	---	---
2	2483.50	69.60	74.00	-4.40	70.49	-0.89	Peak	---	---
3	3678.00	34.74	54.00	-19.26	32.35	2.39	Average	---	---
4	3678.00	44.54	74.00	-29.46	42.15	2.39	Peak	---	---
5	4904.00	33.25	54.00	-20.75	26.55	6.70	Average	---	---
6	4904.00	45.07	74.00	-28.93	38.37	6.70	Peak	---	---
7	7356.00	36.71	54.00	-17.29	25.65	11.06	Average	---	---
8	7356.00	49.30	74.00	-24.70	38.24	11.06	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



## 3.6 Emissions in Non-Restricted Frequency Bands

### 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.6.3 Test Procedures


#### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

#### Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level


### 3.6.4 Test Setup




### 3.6.5 Unwanted Emissions into Non-Restricted Frequency Bands


#### 802.11b









802.11g












802.11n HT20












802.11n HT40







## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan,  
R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==