



**SGS-CSTC Standards
Technical Services
(Shanghai) Co., Ltd.**

588 West Jindu Road, Songjiang District, Shanghai, China
Telephone: +86 (0) 21 6191 5666
Fax: +86 (0) 21 6191 5655
ee.shanghai@sgs.com

FCC ID: ZQ8RC297A

IC: 135AD-RC297A

Report No.: SHEM120700101301
Page: 1 of 23

TEST REPORT

Application No. : SHEM120700101301

Applicant: Philips Electronics (Suzhou) Co.,Ltd.

209 ZhuYuan Road, Building B-3rd, 19~21 floor, SuZhou new district, Suzhou

FCC ID: ZQ8RC297A

IC: 135AD-RC297A

Fundamental Frequency : 2425MHz-2475MHz

Equipment Under Test (EUT):

EUT Name: Remote Control

Brand Name: Cogeco

Model No: RC2972501

Standards: FCC PART 15 SUBPART C, Section 15.249

RSS-210 Issue 8 (December 2010)

RSS-Gen Issue 3 (December 2010)

Date of Receipt: July 25, 2012

Date of Test: July 26, 2012 to Aug 08, 2012

Date of Issue: Aug 08, 2012

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Jim Xu
E&E Section Head
SGS-CSTC(Shanghai) Co., Ltd.

Neil Zhang
E&E Project Engineer
SGS-CSTC(Shanghai) Co., Ltd.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Test Summary

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Radiated emission	15.249 & 15.205	RSS-210 Issue 8 Annex A2.9 & Clause 2.2	Pass
Assigned bandwidth (20dB bandwidth)	15.215(c)	-	Complete
Occupied bandwidth	-	RSS-Gen Issue 3 Clause 4.6.1	Complete
Antenna Requirement	15.203	-	Pass
Power line conducted emission	15.207	RSS-Gen Issue 3 Clause 7.2.4	N/A

Noted 1: “-”means not require in the rules.

Noted 2: NA =Not Applicable



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T.....	4
4.3 DETAILS OF E.U.T	4
4.4 DESCRIPTION OF SUPPORT UNITS	4
4.5 STANDARDS APPLICABLE FOR TESTING	4
4.6 TEST LOCATION	4
4.7 MODE OF OPERATION DURING THE TEST / TEST PERIPHERALS USED.....	4
4.8 DEVIATION FROM STANDARDS	5
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
4.11 TEST FACILITY.....	5
4.12 TEST INSTRUMENTS.....	6
4.13 E.U.T. OPERATION	7
5 TEST PROCEDURE & MEASUREMENT DATA.....	8
5.1 SPURIOUS EMISSION TEST.....	8
5.2 20dB BANDWIDTH	17
5.3 99% OCCUPIED BANDWIDTH TEST.....	20
5.4 ANTENNA REQUIREMENT.....	23



4 General Information

4.1 Client Information

Applicant: Philips Electronics (Suzhou) Co.,Ltd.
Address of Applicant: 209 ZhuYuan Road , Building B-3rd ,19~21 floor,
SuZhou new district,Suzhou
Manufacturer: Philips Electronics (Suzhou) Co.,Ltd.
Address of Manufacturer: 209 ZhuYuan Road , Building B-3rd ,19~21 floor,
SuZhou new district,Suzhou

4.2 General Description of E.U.T.

EUT Name: Remote Control
Brand Name: Cogeco
Model No: RC2972501

4.3 Details of E.U.T.

EUT Power Supply: Battery 2*1.5V
Operation Frequency Range: The EUT application supports only 3 RF-channels;
these channels are the following:
CH15 2425 MHz
CH20 2450 MHz
CH25 2475 MHz
Hardware Version: Not supplied by client
Software Version: Not supplied by client

4.4 Description of Support Units

Name	Model No.	Remark
NA	NA	NA

4.5 Standards Applicable for Testing

47CFR Part 15 (2009)
ANSI C63.10: 2009

4.6 Test Location

All tests were performed at SGS E&E EMC lab

SGS-CSTC EMC Laboratory, No.588 West Jindu Road,Songjiang District,Shanghai,China

Tel:+86 21 6191 5666 Fax:+86 21 6191 5655

4.7 Mode of operation during the test / Test peripherals used

While testing the transmitter mode of the EUT, the internal modulation was used.
For the EUT is handheld device, so it was set up and tested in three axes (X and Y and Z).
The three axes were tested one by one while the test receiver worked as "max hold" continuously and the highest reading among the whole test procedure was recorded.



4.8 Deviation from Standards

None.

4.9 Other Information Requested by the Customer

None.

4.10 Test Confident level

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

4.11 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2014-07-26.

- FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2015-02-22.

- Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A. Expiry Date: 2014-09-20.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868 and C-4336 respectively. Date of Registration: 2012-05-29. Date of Expiry: 2015-05-28.



4.12 Test Instruments

Radiated Emission

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal.Due date
1	EMI test receiver	Rohde & Schwarz	ESU40	100109	2012-06-03	2013-06-01
2	Antenna	SCHWARZBECK	VULB916 8	9168-313	2011-10-28	2012-10-26
3	CONTROLLER	INNCO	CO200	474	/	/
4	Antenna	SCHWARZBECK	BBHA912 0D	9120D-67 9	2011-10-28	2012-10-26
5	Antenna	SCHWARZBECK	BBHA917 0	9170-373	2011-10-28	2012-10-26

Conducted Emission

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal.Due date
1	EMI test receiver	Rohde & Schwarz	ESCS30	100086	2012-06-03	2013-06-01
2	Line impedance stabilization network	SCHWARZBECK	NSLK812 7	8127-490	2012-05-07	2013-05-05

General Equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal.Due date
1	Digital pressure meter	YONGZHI	DYM3-01	101012	2011-11-18	2012-11-17
2	Digital Multimeter	FLUKE	17B	10560713	2011-08-24	2012-08-22
3	Temperature& humidity recorder	ShangHai weather meter work	ZJ 1-2B	0805126	2011-07-25	2012-07-23



4.13 E.U.T. Operation

Input voltage:	Battery 2*1.5V
Operating Environment:	
Temperature:	24.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	1010 mbar
EUT Operation:	<p>While testing the transmitter mode of the EUT, the internal modulation was used. For the EUT is handheld round-shaped device, it was set up and tested in three axes (X,Y&Z). The three axes were tested one by one while the test receiver worked as "max hold" continuously and the highest reading among the whole test procedure was recorded. And worst case is be found at "Y" position.</p> <p>The EUT has been tested under operating condition. Test program was used to control the EUT for staying in continuous Transmitting mode is programmed.</p> <p>Channel low (2425MHz) mid(2450MHz) high(2475MHz)</p>

5 Test Procedure & Measurement Data

5.1 Spurious Emission Test

Test Requirement:	FCC part 15.249 & 15.205		
Test date:	Aug. 2,2012 to Aug. 4,2012		
Limit:	15.249(a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:		

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 - 928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

15.249 (d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.


Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
Test instrumentation resolution bandwidth 120 kHz and Quasi-Peak detector applies (30 MHz - 1000 MHz). 1MHz resolution bandwidth and Peak detector apply (1000 MHz – 25GHz)
Above 1GHz
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until all frequency measured were complete.
7. The field strength of spurious emission was measured in the following position:EUT satnd-up position (Z axis),lie-down position (X, Y axis) .The worst emission was found in lie-down


position(X axis) and the worst case was recorded.

Radiated Test Set-up:

Radiated Emission Test Set-up, Frequency Below 1000MHz




Radiated Emission Test Set-up Frequency Over 1GHz



Low noise amplifier was used below 1GHz, High pass Filter was used above 1GHz.


Antenna Horizontal:



Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cabl e Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	40.14	21.00	13.29	24.70	0.56	10.15	40.00	-29.85	QP	HORIZONTAL
2	50.41	21.59	12.78	24.70	0.65	10.32	40.00	-29.68	QP	HORIZONTAL
3	62.65	21.87	11.83	24.70	0.75	9.75	40.00	-30.25	QP	HORIZONTAL
4	105.27	21.38	9.67	24.70	1.07	7.42	43.50	-36.08	QP	HORIZONTAL
5	144.84	22.31	12.39	24.70	1.25	11.25	43.50	-32.25	QP	HORIZONTAL
6	968.93	22.33	24.05	23.72	3.84	26.50	54.00	-27.50	QP	HORIZONTAL

Note: Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

Antenna Vertical:



Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cabl e Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	39.02	22.47	13.12	24.70	0.55	11.44	40.00	-28.56	QP	VERTICAL
2	44.90	21.92	13.10	24.70	0.60	10.92	40.00	-29.08	QP	VERTICAL
3	54.64	21.30	12.52	24.70	0.69	9.81	40.00	-30.19	QP	VERTICAL
4	146.37	22.33	12.48	24.70	1.26	11.37	43.50	-32.13	QP	VERTICAL
5	176.27	23.94	11.55	24.60	1.39	12.28	43.50	-31.22	QP	VERTICAL
6	948.76	23.27	23.88	23.80	3.80	27.15	46.00	-18.85	QP	VERTICAL

Note: Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor



Operation Mode: TX

Low CH 2425MHz

Fundamental frequency emission:

Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Receiver Peak Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Peak Result (dBuV/m)	Peak Limit 3m (dBuV/m)	Margin (dB)
2.425	43.87	PK	H	32.4	76.27	114	-37.73
2.425	57.54	PK	V	32.4	89.94	114	-24.06

Remark:

1. For fundamental emission test, no amplifier is employed.
2. Peak Result=Peak Reading+Correction Factors
3. Margin =Corrected Reading – Limit

Spurious emission above 1GHz:

Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4.849	48.85	PK	H	-2.3	46.55	54	-7.45
7.274	39.72	PK	H	3.0	42.72	54	-11.28
4.510	51.75	PK	V	-2.3	49.45	54	-4.55
7.274	40.17	PK	V	3.0	43.17	54	-10.83

Remark:

1. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin =Corrected Reading – Limit
4. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement is performed.



Operation Mode: TX

Mid CH 2450MHz

Fundamental frequency emission:

Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Receiver Peak Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Peak Result (dBuV/m)	Peak Limit 3m (dBuV/m)	Margin (dB)
2.450	39.22	PK	H	32.4	71.62	114	-42.38
2.450	58.15	PK	V	32.4	90.55	114	-23.45

Remark:

1. For fundamental emission test, no amplifier is employed.
2. Peak Result=Peak Reading+Correction Factors
3. Margin =Corrected Reading – Limit

Spurious emission above 1GHz:

Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4.900	48.89	PK	H	-2.1	46.79	54	-7.21
7.350	38.97	PK	H	3.2	42.17	54	-11.83
4.899	50.15	PK	V	-2.1	48.05	54	-5.95
7.351	39.97	PK	V	3.2	43.17	54	-10.83

Remark:

1. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin =Corrected Reading – Limit
4. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.



Operation Mode: TX

High CH 2475MHz

Fundamental frequency emission:

Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Receiver Peak Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Peak Result (dBuV/m)	Peak Limit 3m (dBuV/m)	Margin (dB)
2.475	40.14	PK	H	32.4	72.54	114	-41.46
2.475	58.17	PK	V	32.4	90.57	114	-23.43

Remark:

1. For fundamental emission test, no amplifier is employed.
2. Peak Result=Peak Reading+Correction Factors
3. Margin =Corrected Reading – Limit

Spurious emission above 1GHz:



Radiated Emissions			Ant	Correction Factors	Total	FCC Limit	
Frequency (GHz)	Reading (dBuV)	Detect Mode	Pol.	Ant.(dB/m)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4.950	49.37	PK	H	-2.0	47.37	54	-6.63
7.425	39.93	PK	H	3.0	42.93	54	-11.07
4.950	50.30	PK	V	-2.0	48.30	54	-5.70
7.425	40.17	PK	V	3.0	43.17	54	-10.83

Remark:



1. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin =Corrected Reading – Limit
4. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Bandedge Test Plot:

Horizontal, Peak Detector:



Vertical, Peak Detector:



Note: If the test result on peak is lower than average limit, then average measurement needn't be performed.

5.2 20dB Bandwidth

Test Requirement: FCC Part15 215(c)

Test date: Aug. 5.2012


Standard Applicable: Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emission is contained within the allocated frequency band as clause 3.1 shows. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Measurement Procedure: The 20dB Bandwidth per FCC § 15.215(c) is measured using the Spectrum Analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW.

Measurement Result:


CH	Frequency (MHz)	20dB bandwidth (MHz)
15	2425	0.28

20dB Band Width Test Data CH15 2425MHz:




CH	Frequency (MHz)	20dB bandwidth (MHz)
20	2450	0.276

20dB Band Width Test Data CH20 2450MHz:



CH	Frequency (MHz)	20dB bandwidth (MHz)
25	2475	0.273

20dB Band Width Test Data CH25 2475MHz:




5.3 99% Occupied Bandwidth Test

Test Requirement:	RSS-Gen Issue 3 Clause 4.6.1
Test date:	Aug. 5, 2012
Standard Applicable	According to the section RSS-Gen Issue 3 Clause 4.6.1
EUT Setup	The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer with the resolutions set at 30kHz, the video bandwidth set at 100kHz.


Measurement Result:

CH	Frequency (MHz)	Occupied Bandwidth (MHz)
15	2425	0.081
20	2450	0.087
25	2475	0.105


99% Occupied BandWidth Test Data CH15 2425MHz:



99% Occupied BandWidth Test Data CH20 2450MHz:



99% Occupied BandWidth Test Data CH25 2475MHz:





5.4 Antenna Requirement

Test Requirement: FCC Part15 15.203

5.4.1 Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.4.2 Antenna Connected Construction

The antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

5.4.3 Result

The EUT antenna is internal Antenna. It comply with the standard requirement.

End of the Report