

# **RF Exposure Report**

Report No.: SA150127C26K

FCC ID: ZQANC111

Test Model: A00005

Series Model: A0005

Received Date: Sep. 27, 2018

Test Date: Jan. 25 ~ Feb. 15, 2019

**Issued Date:** Feb. 19, 2019

Applicant: Nest Labs Inc.

Address: 3400 Hillview Ave. Palo Alto California, United States 94304

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA150127C26K Page No. 1 / 5 Report Format Version: 6.1.1 Reference No.: 180927C18



## **Table of Contents**

Rel	ease Control Record	3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2	.1 Limits for Maximum Permissible Exposure (MPE)	. 5
3	Calculation Result of Maximum Conducted Power	. 5



## **Release Control Record**

Issue No.	Description	Date Issued
SA150127C26K	Original release.	Feb. 19, 2019

Page No. 3 / 5 Report Format Version: 6.1.1



#### 1 Certificate of Conformity

Product: Wireless Camera

Test Model: A00005

Series Model: A0005

Sample Status: Identical Prototype

Applicant: Nest Labs Inc.

**Test Date:** Jan. 25 ~ Feb. 15, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** , **Date:** Feb. 19, 2019

Pettie Chen / Senior Specialist

**Approved by:** , **Date:** Feb. 19, 2019

Bruce Chen / Project Engineer



## 2 RF Exposure

## 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Power Density Strength (A/m) (mW/cm²)		Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30				
30-300	27.5	0.073 0.2		30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; \*Plane-wave equivalent power density

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

#### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Maximum Target Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN 2412~2462	13.5	0	20	0.0045	1
WLAN 5180~5240	13.5	-1.5	20	0.0032	1
WLAN 5260~5320	14.5	-1.5	20	0.0040	1
WLAN 5500~5700	18.0	-1.5	20	0.0089	1
WLAN 5745~5825	15.5	-1.5	20	0.0050	1
BT LE 2402~2480	-2.5	0	20	0.0001	1

---END---