

FCC ID TEST REPORT

for

Smart Activity and Sleep Tracker

Model: IR122B

FCC ID: ZRR-IR122B

Prepared for: Shenzhen Adition Audio Science & Technology CO., LTD.
Mingzhuo Industry Park, Guangming Main Street, Guangming New
District, Shenzhen, China

Prepared by: Shenzhen TCT Testing Technology Co.,Ltd
1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town,
Baoan District, Shenzhen, Guangdong, China

TEL: +86-0755-27673339

FAX: +86-0755-27673332

Report Number: TCT141017E010

Date of Test: Oct. 20-Oct. 24, 2014

Date of Report: Oct. 27, 2014

The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from TCT Testing Technology

Table of Contents

1.0 General Details	3
1.1 Test Lab Details	3
1.2 Applicant Details	3
1.3 Description of EUT.....	4
1.4 Channel description	4
1.5 Statement	4
1.6 Test Engineer	4
2.0 Test equipments and Associated Equipment used during the test.	5
2.1 Test Equipments.....	5
2.2 AE used during the test.....	5
3.0 Technical Details	6
3.1 Summary of test results	6
3.2 Test Standards	6
4.0 EUT Modification	6
5.0 Measurement Uncertainty (95% confidence levels, k=2)	6
6.0 Power Line Conducted Emission Test	7
7.0 Maximum Peak Output Power	11
8.0 6dB Bandwidth Measurement	12
9.0 Power Spectral Density Measurement	15
10.0 Band age Measurement	18
11.0 Spurious Emission Test	20
12.0 Antenna Requirement	32

1.0 General Details

1.1 Test Lab Details

Name :	Shenzhen Tongce Testing Lab
Address:	1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China
Telephone:	13410377511
Fax:	--

The test facility is recognized, certified, or accredited by the following organizations:

FCC Registration Number: 572331

Shenzhen TCT Testing Technology Co., Ltd., Shenzhen EMC Laboratory: Shenzhen Tongce Testing Lab
The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
Registration Number: 572331

Industry Canada (IC)

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing
Registration Number IC: 10668A-1

1.2 Applicant Details

Applicant:	Shenzhen Adition Audio Science & Technology CO., LTD.
Address:	Mingzhuo Industry Park, Guangming Main Street, Guangming New District, Shenzhen, China
Telephone:	(86) 755-27405088
Fax:	(86) 755-27409830

Manufacturer:	Shenzhen Adition Audio Science & Technology CO., LTD.
Address:	Mingzhuo Industry Park, Guangming Main Street, Guangming New District, Shenzhen, China
Telephone:	(86) 755-27405088
Fax:	(86) 755-27409830

1.3 Description of EUT	
Product:	Smart Activity and Sleep Tracker
Model No.:	IR122B
Additional Model No.:	N/A
Brand Name	ADITION/Keefit
Power supply:	DC 3.7V (Li-lion battery), or DC 5V Via USB Port
Modulation Type:	GFSK
Operation Frequency:	2402 MHz ~ 2480 MHz
Number of Channel:	40
Antenna Designation:	An internal antenna and the maximum antenna gain is 1.0dBi.

1.4 Channel description

Bluetooth :Operate frequency on each channel							
01	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
02	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
03	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
04	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
05	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
06	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
07	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
08	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
09	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note: All tests were conducted in three channels: Low channel: 2402MHz, Middle channel: 2440MHz, High channel: 2480MHz

1.5 Statement

N/A

1.6 Test Engineer

The sample tested by



Printed name: SKY

2.0 Test equipments and Associated Equipment used during the test.

2.1 Test Equipments

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 2, 2014	July 1, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 3, 2014	July 2, 2015
Spectrum Analyzer	Agilent	N9020A	MY49100060	July 3, 2014	July 2, 2015
Power Meter	Agilent	E4416A	MY45101555	July 3, 2014	July 2, 2015
Power Sensor	Agilent	E9327A	MY44421198	July 3, 2014	July 2, 2015
System Controller	CT	SC100	-	July 3, 2014	July 2, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015
Pre-amplifier	Teseq	LAN6900	--	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8447D	83153007374	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 3, 2014	July 2, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3160	--	July 3, 2014	July 2, 2015
EMI Test Receiver	R&S	ESCS30	100139	July 2, 2014	July 1, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015

2.2 AE used during the test

Equipment type	Manufacturer	Model	FCC ID/DoC
Notebook	Lenovo	G480	FCC DOC approved

3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:		
Test Item	CFR 47 Section	Result
AC Power Line Conducted Emission	15.207(a)	Complies
Maximum Peak Output Power	15.247(b)(3)	Complies
6 dB bandwidth	15.247 (a)(2)	Complies
Maximum Power Density	15.247(e)	Complies
Band age Measurement	15.247 (d), 15.205 (a), 15.209 (a)	Complies
Radiated Emission	15.209	Complies
Antenna Requirement	15.203,15.247(c)	Complies
RF Exposure	15.247(b), 1.1307(b)	Complies

Note: N/A=Not Applicable

3.2 Test Standards

FCC Part 15:2012 Subpart C, Paragraph 15.247
KDB 558074 D01 DTS Meas Guidance v03r02

4.0 EUT Modification


No modification by Shenzhen TCT Testing Technology Co., Ltd.

5.0 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	MU
1.	Radio Frequency	$\pm 1 \times 10^{-9}$
2.	Temperature	$\pm 0.1^{\circ}\text{C}$
3.	Humidity	$\pm 1.0\%$
4.	RF power, conducted	$\pm 0.34\text{dB}$
5.	RF power density, conducted	$\pm 1.45\text{dB}$
6.	Spurious emissions, conducted	$\pm 3.70\text{dB}$
7.	All emissions, radiated	$\pm 4.50\text{dB}$

6.0 Power Line Conducted Emission Test

6.1 Schematics of the test



EUT: Equipment Under Test


6.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated.

In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2003 on conducted Emission test.

Test Voltage: 120V~, 60Hz

Block diagram of Test setup



6.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

- A Setup the EUT and simulators as shown on the following
- B Enable AF signal and confirm EUT active to normal condition

6.4 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCS30	100139	July 2, 2014	July 1, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015

6.5 Conducted Emission Limit

Frequency(MHz)	Class A Limits (dB μ V)		Class B Limits (dB μ V)	
	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
0.15 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*
0.50 ~ 5.00	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

- Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The tighter limit shall apply at the transition frequencies

6.6 Test specification:

Environmental conditions: Temperature: 26° C Humidity: 51% Atmospheric pressure: 103kPa

Frequency range: 0.15 MHz – 30 MHz

The test was carried out in the following operation mode(s):

- Tx mode+Charging


6.7 Test result

Min. limit margin >10 dB from 0.15MHz to 30MHz

The requirements are FULFILLED

Remarks: According to FCC part 15.207.


A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)



Site Chamber #1 Phase: **L1** Temperature: 26 (C)
 Limit: FCC PART15 Conduction(QP) Power: Humidity: 51 %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1617	41.32	10.63	51.95	65.37	-13.42	QP	
2	0.1617	22.59	10.63	33.22	55.37	-22.15	AVG	
3 *	0.1695	42.81	10.57	53.38	64.98	-11.60	QP	
4	0.1695	26.50	10.57	37.07	54.98	-17.91	AVG	
5	0.4781	30.03	10.37	40.40	56.37	-15.97	QP	
6	0.4781	18.63	10.37	29.00	46.37	-17.37	AVG	
7	1.0758	21.95	10.47	32.42	56.00	-23.58	QP	
8	1.0758	9.10	10.47	19.57	46.00	-26.43	AVG	
9	1.8062	20.79	10.49	31.28	56.00	-24.72	QP	
10	1.8062	12.46	10.49	22.95	46.00	-23.05	AVG	
11	4.4063	19.67	10.92	30.59	56.00	-25.41	QP	
12	4.4063	12.17	10.92	23.09	46.00	-22.91	AVG	

B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)




Site Chamber #1 Phase: **N** Temperature: 26 (C)
 Limit: FCC PART15 Conduction(QP) Power: Humidity: 51 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1578	43.31	10.67	53.98	65.57	-11.59	QP	
2		0.1578	24.93	10.67	35.60	55.57	-19.97	AVG	
3		0.1695	42.45	10.57	53.02	64.98	-11.96	QP	
4		0.1695	27.99	10.57	38.56	54.98	-16.42	AVG	
5	*	0.5016	34.20	10.45	44.65	56.00	-11.35	QP	
6		0.5016	23.71	10.45	34.16	46.00	-11.84	AVG	
7		4.3320	21.82	10.93	32.75	56.00	-23.25	QP	
8		4.3320	13.75	10.93	24.68	46.00	-21.32	AVG	
9		8.0313	17.40	11.06	28.46	60.00	-31.54	QP	
10		8.0313	9.58	11.06	20.64	50.00	-29.36	AVG	
11		18.7500	12.40	11.04	23.44	60.00	-36.56	QP	
12		18.7500	6.81	11.04	17.85	50.00	-32.15	AVG	

7.0 Maximum Peak Output Power

7.1 Test Setup



7.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

7.3 Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. The RF output of EUT was connected to the power meter by a low loss cable
2. Measure the power by power meter

7.4 Test Equipment:


Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Power Meter	Agilent	E4416A	MY45101555	July 3, 2014	July 2, 2015
Power Sensor	Agilent	E9327A	MY44421198	July 3, 2014	July 2, 2015

7.5 Test Result

Test channel	Peak output power (dBm)	Limit (dBm)	Result
Lowest	-3.35	30	Pass
Middle	-3.66	30	Pass
Highest	-5.23	30	Pass

8.0 6dB Bandwidth Measurement

8.1 Test Setup



8.2 Limits of 6dB Bandwidth Measurement

The minimum of 6 dB Bandwidth is >500 kHz

8.3 Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02, the transmitter output was connected to the spectrum analyzer through an attenuator. The spectrum analyzer is setting as follows: RBW=100 kHz, VBW=300 kHz, Detector=Peak, Trace mode=max hold, Sweep=auto couple. The 6dB bandwidth is defined as the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


8.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	July 3, 2014	July 2, 2015

8.5 Test Result

Test channel	6 dB occupied bandwidth (kHz)	Limit (kHz)	Result
Lowest	702	500	Pass
Middle	657	500	Pass
Highest	729	500	Pass


Low channel



Middle channel




High channel



9.0 Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density is 8 dBm in any 3 kHz.

9.3 Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02, the transmitter output was connected to the spectrum analyzer through an attenuator.

The spectrum analyzer is setting as follows:

- 1) Set analyzer centre frequency to DTS channel centre frequency.
- 2) Set the span to 1.5 times the DTS channel bandwidth.
- 3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- 4) Set the VBW $\geq 3 * \text{RBW}$.
- 5) Detector=peak.
- 6) Sweep time=auto couple.
- 7) Trace mode=max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


9.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	July 3, 2014	July 2, 2015


9.5 Test Result

Test channel	Peak Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-15.918	8	Pass
Middle	-14.139	8	Pass
Highest	-14.220	8	Pass


Low channel



Middle channel



High channel



10.0 Band age Measurement

10.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 3, 2014	July 2, 2015

10.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 50% Atmospheric pressure: 103kPa

10.3 Limit:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with The radiated emission limits specified in 15.209(a)

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (*i.e.*, 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (*i.e.*, 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

10.4 Test Procedure

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

10.5 Test Result:

Low channel




High channel



11.0 Spurious Emission Test

11.1 Conducted emissions Measurement

11.1.1 Test configuration



11.1.2 Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

11.1.3 Test procedure:

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz. Measurements are made over the 30MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

11.1.4 Test Equipment


Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	July 3, 2014	July 2, 2015

11.1.5 Test Result:


Test plots please refer to next pages.

Note: Conducted emissions measurements below 30 MHz were made, and the maximum peak was detected, which is much less the limit. So it is not submitted in the report.


Low channel



Middle channel



High channel



11.2 Radiated emissions Measurement

11.2.1 Test Method and test Procedure:

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

1) The EUT was tested according to ANSI C63.10 –2009.

2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2009.


In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2003 on Radiated Emission test.

3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.


4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.

5) The antenna polarization: Vertical polarization and Horizontal polarization.


Block diagram of Test setup



Block diagram of Test setup for frequency below 30MHz



Block diagram of Test setup for frequency above 1GHz



11.2.2 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

11.2.3 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	20log 2400/F (kHz) + 80
0.490-1.705	3	20log 24000/F (kHz) + 40
1.705-30	3	20log 30 + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- Note:
- 1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
 - 2) In the Above Table, the tighter limit applies at the band edges.
 - 3) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
 - 4) This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
 - 5) All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.
 - 6) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula $Ld1 = Ld2 * (d2/d1)$

11.2.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 2, 2014	July 1, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015
Pre-amplifier	Teseq	LNA6900	--	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8447D	83153007374	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 3, 2014	July 2, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 3, 2014	July 2, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3160	--	July 3, 2014	July 2, 2015

11.2.5 Test specification:

Environmental conditions: Temperature 22° C Humidity: 51% Atmospheric pressure: 103kPa

11.2.6 Test result

A Radiated Emission (9 kHz---30 MHz)

Note: 1) Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor
2) The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Result: Pass


Frequency (MHz)	Level@3m (dB μ V/m)	Limit@3m (dB μ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

B General Radiated Emissions Data

Please refer to following diagram for individual

Radiated Emission In Horizontal (30MHz----1000MHz)


Test mode: Tx mode



Site: Polarization: *Horizontal* Temperature: 26
 Limit: FCC PART15 3M Radiation Power: Humidity: 55 %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	266.8395	47.49	-8.90	38.59	46.00	-7.41	peak	0	
2 *	300.6988	46.56	-7.75	38.81	46.00	-7.19	peak	0	
3	401.1050	39.53	-4.47	35.06	46.00	-10.94	peak	0	
4	468.1650	42.35	-4.22	38.13	46.00	-7.87	peak	0	
5	665.2610	36.80	-5.26	31.54	46.00	-14.46	peak	0	
6	804.2523	35.22	-1.90	33.32	46.00	-12.68	peak	0	

Radiated Emission In Vertical (30MHz----1000MHz)



Site: Polarization: **Vertical** Temperature: 26
 Limit: FCC PART15 3M Radiation Power: Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	!	31.0728	47.68	-13.64	34.04	40.00	-5.96	peak	0	
2		49.0626	31.97	-12.47	19.50	40.00	-20.50	peak	0	
3		200.0432	36.76	-11.58	25.18	43.50	-18.32	peak	0	
4		401.1050	32.35	-4.47	27.88	46.00	-18.12	peak	0	
5		535.0376	34.35	-2.77	31.58	46.00	-14.42	peak	0	
6	*	899.9577	42.49	-1.89	40.60	46.00	-5.40	peak	0	

Note: Measurements were conducted in all three channels (high, middle, low), and the worst case (Low channel) was submitted only.

C Fundamental & Harmonics Radiated Emission Data (1000MHz-25000MHz)

Test mode: Tx mode

Low channel: 2402 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2390.00	H	50.00	---	-4.20	45.80	---	74	54	-8.20
4804.00	H	50.84	---	-3.94	46.90	---	74	54	-7.10
7206.00	H	46.37	---	0.52	46.89	---	74	54	-7.11
--	--	--	---	--	--	---	--	--	--
--	--	--	---	--	--	---	--	--	--
2390.00	V	50.55	---	-4.20	43.35	---	74	54	-7.65
4804.00	V	50.18	---	-3.94	46.24	---	74	54	-7.76
7206.00	V	45.48	---	0.59	46.07	---	74	54	-7.93
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Middle channel: 2440 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
1348.67	H	50.00	---	-4.20	45.80	---	74	54	-820
4880.00	H	50.75	---	-3.98	46.77	---	74	54	-7.23
7320.00	H	45.64	---	0.56	46.2	---	74	54	-7.8
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
1348.28	V	51.35	---	-4.25	47.24	---	74	54	-6.90
4880.00	V	45.31	---	-3.98	41.33	---	74	54	-12.67
7320.00	V	44.61	---	0.57	45.18	---	74	54	-8.82
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

High channel: 2480 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2483.50	H	52.27	---	-4.25	48.02	---	74	54	-5.98
4960.00	H	50.25	---	-3.98	46.27	---	74	54	-7.73
7440.00	H	43.20	---	0.52	43.72	---	74	54	-10.28
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
2483.50	V	51.21	---	-4.25	46.96	---	74	54	-7.04
4960.00	V	52.30	---	-3.98	48.32	---	74	54	-5.68
7440.00	V	45.16	---	0.57	45.73	---	74	54	-8.27
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

12.0 Antenna Requirement


12.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

12.2 Antenna Specification

According to the manufacturer declared, the EUT has an internal antenna; the directional gain of antenna is 1.0dBi, and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.



Bluetooth Antenna

****END OF REPORT****