## **GRANT OF EQUIPMENT AUTHORIZATION**

## Certification

Issued Under the Authority of the **Federal Communications Commission** 

By:

**RFI Global Services Ltd** 

Pavilion A Ashwood Park, Ashwood Way

Date of Grant: 06/05/2009

Basingstoke, Hampshire, RG23 8BG

**United Kingdom** 

Application Dated: 06/04/2009

Telit Communications S.p.A. Viale Stazione di Prosecco 5/b **Trieste, 34010** Italy

Attention: Brian Tucker, Global VP, Quality

## **NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: RI7GE865

Name of Grantee: Telit Communications S.p.A.

**Equipment Class: PCS Licensed Transmitter** Notes: **Quadband GSM/ GPRS Module** 

Modular Type: Single Modular

		Frequency	Output	Frequency	<b>Emission</b>
<b>Grant Notes</b>	FCC Rule Parts	Range (MHZ)	Watts	<u>Tolerance</u>	<b>Designator</b>
	22H	824.2 - 848.8	1.51	1.0 PM	300KGXW
	24E	1850.2 - 1909.8	0.87	1.0 PM	300KGXW

Single modular approval. Power Output listed is conducted. This device contains functions that are not operational in U.S. Territories. This filling is only applicable for US operations. The antenna gain, including cable loss, must not exceed 3.0dBi at 1900 MHz / 1.4dBi at 850 MHz as defined in 2.1091 and 1.1307 of the rules for satisfying RF exposure compliance. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be collocated or operating in conjunction with any other antenna or transmitter. The final product operating with this transmitter must include operating instructions and applicable warnings, as described in this filing for end users and installers to satisfy RF exposure compliance requirements. OEM integrators must be informed of the specific requirements.