

<b>RF Exposure Statement:</b>		Page 1 of 1									
<b>Client:</b>	ANDON HEALTH CO.,LTD No. 3 Jinping Road, Ya An Street Nankai District Tianjin P.R. China										
<b>Test item:</b>	iHealth Wireless Smart Gluco-Monitoring System										
<b>Identification:</b>	<b>BG5</b>										
FCC ID :	ZRYBG5										
<b>FCC Requirement</b>											
According to FCC 2.1091, mobile equipment must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="padding: 5px;">Equipment Use</th> <th style="padding: 5px;">Frequency Range</th> <th style="padding: 5px;">Power Density [mW/cm<sup>2</sup>]</th> <th style="padding: 5px;">Average Time [min]</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">General Population / Uncontrolled Exposure</td> <td style="padding: 5px;">1.5 – 100GHz</td> <td style="padding: 5px;">1</td> <td style="padding: 5px;">6</td> </tr> </tbody> </table>	Equipment Use	Frequency Range	Power Density [mW/cm <sup>2</sup> ]	Average Time [min]	General Population / Uncontrolled Exposure	1.5 – 100GHz	1	6			
Equipment Use	Frequency Range	Power Density [mW/cm <sup>2</sup> ]	Average Time [min]								
General Population / Uncontrolled Exposure	1.5 – 100GHz	1	6								
<b>IC Requirement</b>											
According to RSS-102 (Issue 4), clause 2.5.2, no routine RF exposure evaluation is required if the transmitter power (e.i.r.p.) is below the following threshold:											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="padding: 5px;">Frequency Range</th> <th style="padding: 5px;">SAR Limitation [W]</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">Above 1.5GHz</td> <td style="padding: 5px;">5</td> </tr> </tbody> </table>	Frequency Range	SAR Limitation [W]	Above 1.5GHz	5							
Frequency Range	SAR Limitation [W]										
Above 1.5GHz	5										
<b>Measurement Result</b>											
The maximum measured transmitter power is the following:											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="padding: 5px;">Conducted Output Power P<sub>out</sub> [mW]</th> <th style="padding: 5px;">Maximum Antenna Gain [dBi]</th> <th style="padding: 5px;">P<sub>out</sub> EIRP [mW]</th> <th style="padding: 5px;">Power Density at 20cm [mW/cm<sup>2</sup>]</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">1.05</td> <td style="padding: 5px;">2.45</td> <td style="padding: 5px;">0.24</td> <td style="padding: 5px;">0.00036</td> </tr> </tbody> </table>	Conducted Output Power P <sub>out</sub> [mW]	Maximum Antenna Gain [dBi]	P <sub>out</sub> EIRP [mW]	Power Density at 20cm [mW/cm <sup>2</sup> ]	1.05	2.45	0.24	0.00036			
Conducted Output Power P <sub>out</sub> [mW]	Maximum Antenna Gain [dBi]	P <sub>out</sub> EIRP [mW]	Power Density at 20cm [mW/cm <sup>2</sup> ]								
1.05	2.45	0.24	0.00036								
Note:											
The power density S in mW/cm <sup>2</sup> is calculated according to the Friis formula: $S = (P_{out} \cdot G) / (4\pi \cdot D^2)$ , where											
S = power density in mW/cm <sup>2</sup>											
P <sub>out</sub> = antenna conducted output power in mW											
G = antenna gain in linear scale (here: 2.45dBi=10log(G))											
D = distance between observation point and radiating structure in cm (here: 20cm)											
<b>Conclusion</b>											
The device complies with the FCC and IC RF exposure requirements since the maximum transmitter power density is below the FCC limit and the e.i.r.p. power is below the IC RF exposure evaluation exemption threshold.											
Refer to test report 15058197 001 for more details.											
<b>TÜV Rheinland (Shanghai) Co., Ltd.</b> 10-15/F, Huatsing Building, No.88, Lane 777, Guangzhong Road West, Shanghai 200072, P.R. China											