



**SGS-CSTC Standards
Technical Services
(Shanghai) Co., Ltd.**

588 West Jindu Road, Songjiang District, Shanghai, China

Telephone: +86 (0) 21 6191 5666
Fax: +86 (0) 21 6191 5655
ee.shanghai@sgs.com

Report No.: SHEM120500062301
Page 1 of 79

TEST REPORT

Application No. : SHEM1205000623MD
Applicant: ANDON HEALTH Co., Ltd
FCC ID: ZRYBP7
IC ID: 9775A-BP7
Equipment Under Test (EUT):
Product Name: Wireless blood pressure wrist monitor
Model: KD-972(BP7)
Brand Name: iHealth
Standards: FCC PART 15 Subpart C: 2011
RSS-210 Issue 8 (December 2010)
RSS-Gen Issue 3 (December 2010)
Date of Receipt: May. 18, 2012
Date of Test: May. 21, 2012 to June 15, 2012
Date of Issue: June. 18, 2012

Test Result :	PASS *
----------------------	---------------

*In the configuration tested, the EUT detailed in this report complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives.

E&E Section Head
SGS-CSTC(Shanghai) Co., Ltd.

E&E EMC Engineer
SGS-CSTC(Shanghai) Co., Ltd.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 Test Summary

Test items	FCC REFERANCE	IC REFERANCE	Result
Antenna Requirement	Section 15.247 (c)	---	PASS
20dB Bandwidth	Section 15.247 (a)(1)	RSS-Gen Issue 3 Clause 4.6.1	PASS
Carrier Frequencies Separated	Section 15.247(a)(1)	RSS-210 Issue 8 Annex 8.1(b)	PASS
Hopping Channel Number	Section 15.247(a)(1)(iii)	RSS-210 Issue 8 Annex 8.1(d)	PASS
Dwell Time	Section 15.247(a)(1)(iii)	RSS-210 Issue 8 Annex 8.1(d)	PASS
Maximum Peak Output Power	Section 15.247(b)(1)	RSS-210 Issue 8 Annex 8.4(2)	PASS
RF Exposure Compliance Requirement	15.247(b)(4)	RSS-Gen Issue 3 Clause 5.6	PASS
Conducted Spurious Emission (30MHz to 25GHz)	&15.247(d)	RSS-210 Issue 8 Annex 8.5	PASS
Radiated Spurious Emission (30MHz to 25GHz)	Section 15.209 &15.247(d)	RSS-210 Issue 8 Annex 8.5	PASS
Band Edges Measurement	Section 15.247 (d) &15.205	RSS-Gen Issue 3 Clause 7.2.2	PASS
Power line conducted emission	Section 15.207	RSS-Gen Issue 8 Clause 7.2.4	PASS
Occupied bandwidth	---	RSS-Gen Issue 3 Clause 4.6.1	Tested



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T.	4
4.3 DETAILS OF E.U.T.....	4
4.4 STANDARDS APPLICABLE FOR TESTING.....	4
4.5 TEST LOCATION	4
4.6 TEST FACILITY	5
5 EQUIPMENTS USED DURING TEST.....	6
6 TEST RESULTS.....	8
6.1 E.U.T. TEST CONDITIONS	8
6.2 ANTENNA REQUIREMENT	9
6.2.1 <i>Standard requirement</i>	9
6.2.2 <i>EUT Antenna</i>	9
6.3 20dB BANDWIDTH.....	10
6.4 CARRIER FREQUENCIES SEPARATED	16
6.5 HOPPING CHANNEL NUMBER.....	19
6.6 DWELL TIME.....	21
6.7 MAXIMUM PEAK OUTPUT POWER	31
6.8 RF EXPOSURE COMPLIANCE REQUIREMENT	37
6.8.1 <i>Standard requirement</i>	37
6.8.2 <i>Output power Results</i>	37
6.8.3 <i>EUT RF Exposure</i>	37
6.9 CONDUCTED SPURIOUS EMISSIONS	38
6.10 RADIATED SPURIOUS EMISSIONS.....	41
6.10.1 <i>Radiated Emissions which fall in the restricted bands</i>	50
6.11 BAND EDGES REQUIREMENT	64
6.12 CONDUCTED EMISSION TEST.....	71
6.13 OCCUPIED BANDWIDTH TEST	74

4 General Information

4.1 Client Information

Applicant: ANDON HEALTH Co., Ltd
Address of Applicant: No. 3 Jin Ping Street, Ya An Road, Nankai District, Tianjin 300190, China
Manufacturer: ANDON HEALTH Co., Ltd
Address of Manufacturer: No. 3 Jin Ping Street, Ya An Road, Nankai District, Tianjin 300190, China

4.2 General Description of E.U.T.

Product Name Wireless blood pressure wrist monitor
Model No: KD-972(BP7)
Brand Name: iHealth
Supported Frequency Bands: Bluetooth 2.402GHz to 2.480GHz
Test Frequency Bands: 2.402GHz to 2.480GHz

4.3 Details of E.U.T.

Bluetooth Version: V3.0 (EDR)
Modulation Type: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type: Internal antenna
Antenna Gain: 2.45dBi
AC Adaptor : Input: AC 100V~240V,200mA
Output: DC 5V 1A
Battery: Fix Battery---DC 3.7V

4.4 Standards Applicable for Testing

The standard used were FCC PART 15 Subpart C: 2011, ANSI C63.10: 2009. RSS-210 Issue 8, RSS-Gen Issue 3.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.
No.588 West Jindu Road, Songjiang District, Shanghai, China.201612.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5655

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

Date of expiry: 2014-07-26.

- **FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2015-02-22.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A. Expiry Date: 2014-09-20.



5 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due date
1	EMI test receiver	Rohde & Schwarz	ESU40	100109	2011-06-03	2012-06-01
2	Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-679	2011-06-03	2012-06-01
3	Horn Antenna	Rohde & Schwarz	HF906	100284	2011-06-03	2012-06-01
4	ANTENNA	SCHWARZBECK	VULB9168	9168-313	2011-06-03	2012-06-01
5	Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 373	2012-03-15	2013-03-14
6	Ultra broadband antenna	Rohde & Schwarz	HL562	100227	2011-10-09	2012-10-08
7	Atmosphere pressure meter	Shanghai ZhongXuan Electronic Co;Ltd	BY—2009P	--	2011-10-15	2012-10-14
8	CLAMP METER	FLUKE	316	86080010	2011-06-03	2012-06-01
9	Thermo-Hygrometer	ZHICHEN	ZC1-2	01050033	2011-10-14	2012-10-13
11	High-low temperature cabinet	Shanghai YuanZhen	GW2050	--	2011-06-17	2012-06-16
12	Tunable Notch Filter	Wainwright instruments Gmbh	WRCT1800.0/ 2000.0-0.2/40- 5SSK	11	2011-06-03	2012-06-01
13	Tunable Notch Filter	Wainwright instruments Gmbh	WRCT800.0/88 0.0-0.2/40- 5SSK	9	2011-06-03	2012-06-01
14	High pass Filter	FSCW	HP 12/2800- 5AA2	19A45-02	2011-06-03	2012-06-01

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



15	Low noise amplifier	TESEQ	LNA6900	70133	2011-07-05	2012-07-04
16	EMI test receiver	Rohde & Schwarz	ESCS30	100086	2011-06-04	2012-06-03
17	Line impedance stabilization network	SCHWARZBECK	NSLK8127	8127-490	2011-06-03	2012-06-01

6 Test Results

6.1 E.U.T. test conditions

Power supply:	Input:100-240V, 200mA, Output: 5.0 VDC, 1.0A
Requirements:	15.31(e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.
Type of antenna:	integral
Operating Environment:	
Temperature:	20.0 -25.0 °C
Humidity:	35-75 % RH
Atmospheric Pressure:	992 -1020 mbar
Test frequencies:	According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and. if required. reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top. 1 near middle and 1 near bottom

Pursuant to Part 15.31(c) For swept frequency equipment, measurements shall be made with the frequency sweep stopped at those frequencies chosen for the measurements to be reported.

Test frequency is the lowest channel: 0 channel (2402MHz), middle channel: 39 channel (2441MHz) and highest channel: 78 channel (2480MHz) with fixed at channel.

6.2 Antenna Requirement

6.2.1 Standard requirement

15.203 requirement:

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

6.2.2 EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The gain of the antenna is less than 2.45 dBi.

Test result: The EUT does meet the FCC requirements.

6.3 20dB Bandwidth

Test Requirement: FCC Part 15 C Section 15.247 (a)(1)
RSS-Gen Issue 3 Clause 4.6.1

Test Method: ANSI C63.10:2009 Clause 6.9.1

Test Date: May. 29, 2011

Test Status: Test in fixing operating frequency at lowest, Middle, highest channel with charger or only battery.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20dB bandwidth, centered on the hopping channel;
3. Set the spectrum analyzer: RBW \geq 1% of the 20dB bandwidth (set 100kHz). VBW \geq RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20dB points.

Test result: Pass


Test date

Test Channel	Channel Frequency (MHz)	Modulation	Bandwidth(MHz)
Low	2402	GFSK	1.122
Middle	2441	GFSK	1.116
High	2480	GFSK	1.110
Low	2402	$\pi/4$ DQPSK	1.344
Middle	2441	$\pi/4$ DQPSK	1.362
High	2480	$\pi/4$ DQPSK	1.362
Low	2402	8DPSK	1.350
Middle	2441	8DPSK	1.338
High	2480	8DPSK	1.350




Result plot as follows:

Lowest Channel – GFSK:



Date: 1.JAN.2000 00:33:35


Middle Channel – GFSK:



Date: 1.JAN.2000 00:34:19




Highest Channel – GFSK:



Date: 1.JAN.2000 00:34:58


Lowest Channel – π /4DQPSK:



Date: 1.JAN.2000 00:36:51




Middle Channel $-\pi/4$ DQPSK:



Date: 1.JAN.2000 00:36:16


Highest Channel $-\pi/4$ DQPSK:



Date: 1.JAN.2000 00:35:35




Lowest Channel -8DPSK:



Date: 1.JAN.2000 00:37:26


Middle Channel -8DPSK:



Date: 1.JAN.2000 00:38:01



Highest Channel –8DPSK:



Date: 1.JAN.2000 00:38:35

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

6.4 Carrier Frequencies Separated

Test Requirement: FCC Part 15 C Section 15.247 (a)(1)
RSS-Gen Issue 3 Clause 8.1(b)

Test Method: ANSI C63.10:2009 Clause 7.7.2

Test Date: May 30, 2012

Test requirements: Regulation 15.247(a),(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW \geq 1% of the span (set 100 kHz). VBW \geq RBW , Span = 3MHz. Sweep = auto; Detector Function = Peak. Trace = Max,hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test result: Pass


Test Channel	Modulation	Carrier Frequencies Separated	Limit (25kHz or two-thirds of the 20 dB bandwidth)	PASS/FAIL
Middle Channels (channel 39 and channel 40)	GFSK	990kHz	25kHz/908kHz	PASS
Middle Channels (channel 39 and channel 40)	$\pi/4$ DQPSK	996kHz	25kHz/908kHz	PASS
Middle Channels (channel 39 and channel 40)	8DPSK	996kHz	25kHz/908kHz	PASS



Result plot as follows:

Middle Channels


Modulation: GFSK



Date: 1.JAN.2000 01:26:32

Middle Channels

Modulation: $\pi/4$ DQPSK




Date: 1.JAN.2000 02:17:46



Middle Channels

Modulation: 8DPSK



Date: 1.JAN.2000 02:05:48

Test result: The EUT does meet the FCC requirements.



6.5 Hopping Channel Number

Test Requirement: FCC Part15 C Section 15.247(a)(1)(iii)
RSS-210 Issue 8 Annex 8.1(d)

Test Method: ANSI C63.10:2009 Clause 7.7.3

Test Date: May 30, 2012

Requirements: Regulation 15.247 (a) (1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.


Test result: Total channels are 79 channels. The EUT does meet the FCC requirements.

GFSK






$\pi/4$ DQPSK



Date: 1.JAN.2000 06:18:39

8DPSK



Date: 1.JAN.2000 06:13:04

6.6 Dwell Time

Test Requirement:

FCC Part 15 C Section 15.247(a)(1)(iii)

RSS-210 Issue 8 Annex 8.1(d)

Test Method:

ANSI C63.10:2009 Clause 7.7.3

Test Date:

May 30, 2012

Test requirements:

Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Status:

Hopping transmitting with all kind of modulation.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. centered on a hopping channel;
3. Use Emission width / No. of Hopping Channels in 31.6s to determine the dwell time.



Frequency (MHz)	Modulation	Packet	Emission Width (ms)	Number of Hopping Channel in 31.6s	Average Time of Occupancy(s)	Limit(s)	Result
2441	GFSK	DH1	0.38	201	0.076	0.4	Pass
		DH3	1.66	125	0.208	0.4	Pass
		DH5	2.92	90	0.263	0.4	Pass
2441	$\pi/4$ DQPSK	2DH1	0.40	211	0.084	0.4	Pass
		2DH3	1.66	140	0.232	0.4	Pass
		2DH5	2.92	88	0.257	0.4	Pass
2441	8DPSK	3DH1	0.40	164	0.066	0.4	Pass
		3DH3	1.64	123	0.202	0.4	Pass
		3DH5	2.92	102	0.298	0.4	Pass



Refer testing graph as below:

Frequency 2441MHz:

Modulation: GFSK-DH1




Date: 1.JAN.2000 04:28:57

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: GFSK- DH3



Date: 1.JAN.2000 04:06:28




Date: 1.JAN.2000 04:32:40

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: GFSK- DH5



Date: 1.JAN.2000 04:10:54




Date: 1.JAN.2000 04:36:48

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: $\pi/4$ DQPSK-2DH1



Date: 1.JAN.2000 02:40:40




Date: 1.JAN.2000 04:42:31




Frequency 2441MHz:

Modulation: $\pi/4$ DQPSK-2DH3



Date: 1.JAN.2000 04:01:46




Date: 1.JAN.2000 04:46:42

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: $\pi/4$ DQPSK-2DH5



Date: 1.JAN.2000 04:16:52




Date: 1.JAN.2000 04:52:02

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: 8DPSK-3DH1



Date: 1.JAN.2000 02:43:45




Date: 1.JAN.2000 05:33:30

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: 8DPSK-3DH3



Date: 1.JAN.2000 03:58:05




Date: 1.JAN.2000 05:37:01

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Frequency 2441MHz:

Modulation: 8DPSK-3DH5



Date: 1.JAN.2000 04:19:54




Date: 1.JAN.2000 06:02:02

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

6.7 Maximum Peak Output Power

Test Requirement:	FCC Part 15.247 Section 15.247(b)(1) RSS-210 Issue 8 Annex 8.4(2)
Test Method:	ANSI C64.10:2009 Clause 6.10.1
Test Date:	May 31, 2012
Test Limit:	Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.
Test mode:	Test in fixing frequency transmitting mode.
Test Configuration:	



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, middle and highest channel individually. Record the max value.

Test Results record:

Test Channel	Modulation	Fundamental Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Output Power		Limit (dBm)	Margin (dB)
					(dBm)	(mW)		
Lowest	GFSK	2402	0.06	0.6	0.66	1.164	30	29.34
Middle	GFSK	2441	-0.24	0.6	0.36	1.086	30	29.64
Highest	GFSK	2480	-0.02	0.6	0.58	1.143	30	29.42
Lowest	$\pi/4$ DQPSK	2402	-0.03	0.6	0.57	1.140	30	29.43
Middle	$\pi/4$ DQPSK	2441	-0.26	0.6	0.34	1.081	30	29.66




Highest	$\pi/4$ DQPSK	2480	-0.01	0.6	0.59	1.146	30	29.41
Lowest	8DPSK	2402	0.35	0.6	0.95	1.245	30	29.05
Middle	8DPSK	2441	0.04	0.6	0.64	1.159	30	29.36
Highest	8DPSK	2480	0.27	0.6	0.87	1.222	30	29.13

Test result plot as follows:

Low Channel

Modulation: GFSK




Date: 1.JAN.2000 06:25:31



Middle Channel


Modulation: GFSK



Date: 1.JAN.2000 06:26:24

High Channel

Modulation: GFSK




Date: 1.JAN.2000 06:26:54

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Low Channel



Date: 1.JAN.2000 06:28:32


Middle Channel



Date: 1.JAN.2000 06:28:07




High Channel



Date: 1.JAN.2000 06:27:34

Low Channel




Date: 1.JAN.2000 06:29:00



Middle Channel


Modulation: 8DPSK



Date: 1.JAN.2000 06:29:24

High Channel

Modulation: 8DPSK



Date: 1.JAN.2000 06:29:48

6.8 RF Exposure Compliance Requirement

6.8.1 Standard requirement

15.247(b)(4) requirement:

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TCB Exclusion List (7 July 2002)

Exposure category	low threshold	high threshold
General population	(60/fGHz) mW. $d < 2.5$ cm (120/fGHz) mW. $d \geq 2.5$ cm	(900/fGHz) mW. $d < 20$ cm
Occupational	(375/fGHz) mW. $d < 2.5$ cm (900/fGHz) mW. $d \geq 2.5$ cm	(2250/fGHz) mW. $d < 20$ cm

6.8.2 Output power Results:

Test Channel	Modulation	Fundamental Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Output Power	
					(dBm)	(mW)
Lowest	GFSK	2402	0.06	0.6	0.66	1.164
Middle	GFSK	2441	-0.24	0.6	0.36	1.086
Highest	GFSK	2480	-0.02	0.6	0.58	1.143
Lowest	$\pi/4$ DQPSK	2402	-0.03	0.6	0.57	1.140
Middle	$\pi/4$ DQPSK	2441	-0.26	0.6	0.34	1.081
Highest	$\pi/4$ DQPSK	2480	-0.01	0.6	0.59	1.146
Lowest	8DPSK	2402	0.35	0.6	0.95	1.245
Middle	8DPSK	2441	0.04	0.6	0.64	1.159
Highest	8DPSK	2480	0.27	0.6	0.87	1.222

Mark: the RF output power is from section 6.7. So the test method please reference the report section 6.7.

6.8.3 EUT RF Exposure

The Max Conducted Peak Output Power is 0.95dBm(1.245mW) at 2402MHz.

And the antenna gain at 2402MHz is 2.45dBi PCB integrated in the actual use logarithmic terms convert to numeric result is nearly 1.758;

According to the formula, calculate the EIRP test result:

$$\text{EIRP} = P \times G = 1.245 \text{ mW} \times 1.758 = 2.189 \text{ mW} \text{ ①}$$

SAR requirement:


$$S = 60 / f(\text{GHz}) = 60 / 2.402 = 24.979 \text{ mW} \text{ ②};$$

$$\text{①} < \text{②}.$$

So the SAR test for Bluetooth is not required.

6.9 Conducted Spurious Emissions


Test Requirement:	FCC Part 15 Section 15.207 & 15.247(d) RSS-210 Issue 8 Annex 8.5
Test Method:	ANSI C63.10:2009 Clause 7.7.10
Test Date:	May 30, 2012
Test requirements:	(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Status:	Test the lowest, Middle, highest channel. Remark: 8DPSK Modulation mode is the worst case (base on the 6.1 section Effective Isotropically Radiated Power test result in this report, 8DPSK modulation is the worst case).
Test Configuration:	



Test Procedure:	<ol style="list-style-type: none"> 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. 2. Set the spectrum analyzer: RBW = 100KHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).
Test result	The EUT does meet the FCC requirements.




Low Channel:



Date: 1.JAN.2000 02:07:53

Middle Channel:




Date: 1.JAN.2000 02:09:36

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



High Channel:



Date: 1.JAN.2000 02:13:27

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

6.10 Radiated Spurious Emissions

Test Requirement:	FCC Part 15 Section 15.209 & 15.247(d) RSS-210 Issue 8 Annex 8.5
Test Method:	ANSI C63.10:2009 Clause 6.12
Test Date:	May 31 ,2012
Test Status:	Test the lowest. Middle, highest channel with charger or only battery. Remark: 8DPSK Modulation mode is the worst case (base on the 6.1 section Effective Isotropically Radiated Power test result in this report, 8DPSK modulation is the worst case).
Test site/setup:	Measurement Distance: 3m (Semi-Anechoic Chamber) Test instrumentation resolution bandwidth 120 kHz and Quasi-Peak detector applies (30 MHz - 1000 MHz). For PK value: RBW = 1 MHz for $f \geq 1$ GHz VBW \geq RBW; Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz VBW = 10Hz; Sweep = auto Detector function = peak Trace = max hold Receive antenna scan height 1 m - 4 m. polarization Vertical / Horizontal
15.209 Limit:	40.0 dB μ V/m between 30MHz & 88MHz 43.5 dB μ V/m between 88MHz & 216MHz 46.0 dB μ V/m between 216MHz & 960MHz 54.0 dB μ V/m above 960MHz
15.247(d) limit:	(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration:




Figure 1. 30MHz to 1GHz radiated emissions test configuration




Figure 2. Above 1GHz radiated emissions test configuration

Test Procedure:

The procedure used was ANSI Standard C63.10:2009. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

Low noise amplifier was used below 1GHz, High pass Filter was used above 3GHz.

Between 1G and 3GHz, we did not use any amplifier or filter.

Pre-test was performed on GFSK and EDR mode with charging mode and only battery power mode, Compliance test was performed on worst case (8DPSK mode with charging).

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Test were performed for there spatial orthogonal(X, Y, Z), the worst test data (X orthogonal) was submitted.

1) For this intentional radiator operates below 25 GHz. the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 5rd harmonic.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test Results: The EUT does meet the FCC requirements.


8DPSK with charging mode test data as follows:

Transmitter:

30MHz~1GHz Spurious Emission, Quasi-Peak Measurement

Horizontal

CISPR22 RE 30M-1GHz



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)
47.995680	33.9	1000.000	120.000	112.0	V	326.0	-11.1	6.10
60.514560	27.6	1000.000	120.000	100.0	V	300.0	-11.8	12.40
175.562880	33.3	1000.000	120.000	100.0	V	176.0	-11.6	10.20

(continuation of the "Final Result 1" table from column 9 ...)


Frequency (MHz)	Limit (dBµV/m)	Comment
47.995680	40.00	
60.514560	40.00	
175.562880	43.50	



30MHz~1GHz Spurious Emission, Quasi-Peak Measurement

Vertical

CISPR22 RE 30M-1GHz



Final Result 1

Frequency (MHz)	QuasiPeak (dB _i V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)
174.379520	35.1	1000.000	120.000	170.0	H	52.0	-11.4	8.40
207.425760	29.4	1000.000	120.000	100.0	H	354.0	-13.8	14.10

(continuation of the "Final Result 1" table from column 9 ...)

Frequency (MHz)	Limit (dB _i V/m)	Comment
174.379520	43.50	
207.425760	43.50	

1~25 GHz Harmonics & Spurious Emissions, , Peak & Average Measurement

Test in **Channel Low** in transmitting status- **Vertical** polarization

Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)
4803.75	30.8	1.2	0.5	43.4	65.43	54.53	74.0
7207.50	36.0	1.7	0.8	43.1	59.32	54.72	74.0
9609.31	37.8	2.2	0.9	43.9	54.73	51.73	74.0

Average Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)
4803.75	30.8	1.2	0.5	43.4	55.57	44.67	54.0
7207.50	36.0	1.7	0.8	43.1	46.65	42.05	54.0
9609.31	37.8	2.2	0.9	43.9	42.36	39.36	54.0

Remark: No other radiation has been found.

Test in **Channel Low** in transmitting status- **Horizontal** polarization

Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)
4803.75	30.8	1.2	0.5	43.4	61.79	50.89	74.0
7207.50	36.0	1.7	0.8	43.1	59.37	54.77	74.0
9609.31	37.8	2.2	0.9	43.9	54.07	51.07	74.0

Average Measurement

Frequency (MHz)	Antenna factors(dB/m)	Cable loss(dB)	Filter (dB)	Preamp (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)
4803.75	30.8	1.2	0.5	43.4	50.95	40.05	54.0
7207.50	36.0	1.7	0.8	43.1	47.20	42.60	54.0
9609.31	37.8	2.2	0.9	43.9	42.76	39.76	54.0

Remark: No other radiation has been found.



Test in **Channel Middle** in transmitting status- **Vertical** polarization

Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4882.50	30.8	1.2	0.5	43.4	58.51	47.61	74.0
7323.75	36.0	1.7	0.8	43.1	55.26	50.66	74.0
9765.38	37.8	2.2	0.9	43.9	51.29	48.29	74.0

Average Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4882.50	30.8	1.2	0.5	43.4	47.27	36.37	54.0
7323.75	36.0	1.7	0.8	43.1	47.15	42.55	54.0
9765.38	37.8	2.2	0.9	43.9	35.46	32.46	54.0

Remark: No other radiation has been found.

Test in **Channel Middle** in transmitting status- **Horizontal** polarization

Peak Measurement

Frequency (MHz)	Antenna factors(dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4882.50	30.8	1.2	0.5	43.4	65.67	54.77	74.0
7323.75	36.0	1.7	0.8	43.1	63.33	58.73	74.0
9765.38	37.8	2.2	0.9	43.9	55.10	52.10	74.0

Average Measurement

Frequency (MHz)	Antenna factors(dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4882.50	30.8	1.2	0.5	43.4	54.24	43.34	54.0
7323.75	36.0	1.7	0.8	43.1	54.28	49.68	54.0
9765.38	37.8	2.2	0.9	43.9	43.13	40.13	54.0

Remark: No other radiation has been found.

Test in **Channel High** in transmitting status- **Vertical** polarization

Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4957.50	30.8	1.2	0.5	43.4	58.46	47.56	74.0
7440.00	36.0	1.7	0.8	43.1	65.24	60.64	74.0
9918.74	37.8	2.2	0.9	43.9	54.47	51.47	74.0

Average Measurement.

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4957.50	30.8	1.2	0.5	43.4	47.19	36.29	54.0
7440.00	36.0	1.7	0.8	43.1	56.82	52.22	54.0
9918.74	37.8	2.2	0.9	43.9	41.62	38.62	54.0

Remark: No other radiation has been found.

Test in **Channel High** in transmitting status- **Horizontal** polarization

Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4957.50	30.8	1.2	0.5	43.4	62.27	51.37	74.0
7440.00	36.0	1.7	0.8	43.1	64.68	60.08	74.0
9918.74	37.8	2.2	0.9	43.9	54.69	51.69	74.0

Average Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Filter (dB)	Preamp factor(dB)	Emission Reading (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)
4957.50	30.8	1.2	0.5	43.4	51.19	40.29	54.0
7440.00	36.0	1.7	0.8	43.1	57.32	52.72	54.0
9918.74	37.8	2.2	0.9	43.9	41.83	38.83	54.0

Remark: No other radiation has been found.



Test Level =Receiver Reading + Antenna Factor + Cable Factor+ Filter –Preamplifier Factor.

Remark: No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

6.10.1 Radiated Emissions which fall in the restricted bands

Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI 63.10:2009 Clause 6.12
Test Date:	May 31, 2012
Measurement Distance:	3m (Semi-Anechoic Chamber)
Limit:	40.0 dB μ V/m between 30MHz & 88MHz; 43.5 dB μ V/m between 88MHz & 216MHz; 46.0 dB μ V/m between 216MHz & 960MHz; 54.0 dB μ V/m above 960MHz.
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz VBW \geq RBW; Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz VBW =10Hz; Sweep = auto Detector function = peak Trace = max hold


According to section,15.35(b) for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Pre-test were performed for there spatial orthogonal(X, Y, Z), the worst test data (X orthogonal) was submitted.

Test Result: The EUT does meet the FCC requirements.



Measurement Result:
CH Low 2412MHz Radiated Bandedge **Modulation: GFSK**
Horizontal, Peak Detector:




— MaxPeak-MaxHold — Average-MaxHold — FCC AV

Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2385.60	51.78	27.28	42.50	4.82	41.38	54.00	12.62

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:



— MaxPeak MaxHold
 — Average MaxHold
 — FCC AV


Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2386.2	51.89	27.28	42.5	4.82	41.49	54	12.51

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



CH Low 2480MHz Radiated Bandedge
Horizontal, Peak Detector:

Modulation: GFSK




— MaxPeak-MaxHold
 — Average-MaxHold
 — FCC AV

Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.50	61.17	27.48	42.54	4.82	50.93	54	3.07

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.50	51.76	27.48	42.54	4.82	41.52	54	12.48

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



**CH Low 2412MHz Radiated Bandedge
Horizontal, Peak Detector:**

Modulation: $\pi/4$ DQPSK




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2386.60	50.91	27.28	42.5	4.82	40.51	54	13.49

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:



— MaxPeak-MaxHold — Average-MaxHold — FCC AV


Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2390.0	51.53	27.28	42.5	4.82	41.13	54	12.87

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



CH Low 2480MHz Radiated Bandedge
Horizontal, Peak Detector:

Modulation: $\pi/4$ DQPSK




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.50	62.02	27.48	42.54	4.82	51.78	54	2.22

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.50	57.66	27.48	42.54	4.82	47.42	54	6.58

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



**CH Low 2412MHz Radiated Bandedge
Horizontal, Peak Detector:**

Modulation: 8DPSK




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2390.0	51.57	27.28	42.5	4.82	41.17	54	12.83

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2390	49.17	27.28	42.5	4.82	38.77	54	15.23

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



**CH Low 2480MHz Radiated Bandedge
Horizontal, Peak Detector:**

Modulation: 8DPSK




Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.5	62.3	27.48	42.54	4.82	52.06	54	1.94

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Vertical, Peak Detector:



Frequency (MHz)	Peak Reading (dBuV)	Antenna Factor (dB/m)	PreAmp (dB)	Cable Loss (dB)	Peak Level (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
2483.5	58.76	27.48	42.54	4.82	48.52	54	5.48

Remark: No any other emission which fall in restricted bands can be detected and be reported.

Test Level = Receiver Reading + Antenna Factor + Cable Factor- Preamplifier Factor

All frequencies within the “Restricted bands” have been evaluated to compliance. Section 15.205 Restricted bands of operation.

Except as shown in paragraph of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

6.11 Band Edges Requirement

Test Requirement:	FCC Part 15 C Section 15.247 (d) & 15.205 RSS-Gen Issue 3 Clause 7.2.2
Test Method:	Based on ANSI 63.10 Clause 6.9 Operation within the band 2400M – 2483.5 MHz
Test Date:	May 30,2012
Requirements:	Section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Method of Measurement:	Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.

Test Result: The EUT does meet the FCC requirements.


The graph as below. represents the emissions take for this device.

Test results: The EUT does meet the FCC requirements.



Low Channel


Test Status: GFSK- Static



Date: 1.JAN.2000 01:03:46

High Channel

Test Status: GFSK- Static




Date: 1.JAN.2000 05:45:03

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Low Channel


Test Status: GFSK- Hopping



Date: 1.JAN.2000 01:11:20

High Channel

Test Status: GFSK- Hopping




Date: 1.JAN.2000 01:20:04



Low Channel


Test Status: $\pi/4$ DQPSK - Static



Date: 1.JAN.2000 01:00:33

High Channel

Test Status: $\pi/4$ DQPSK - Static




Date: 1.JAN.2000 05:44:10

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Low Channel


Test Status: $\pi/4$ DQPSK - Hopping



Date: 1.JAN.2000 00:59:13

High Channel

Test Status: $\pi/4$ DQPSK - Hopping




Date: 1.JAN.2000 00:54:48



Low Channel


Test Status: 8DPSK - Static



Date: 1.JAN.2000 00:41:29

High Channel

Test Status: 8DPSK - Static




Date: 1.JAN.2000 05:42:53

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Low Channel


Test Status: 8DPSK - Hopping



Date: 1.JAN.2000 00:46:07

High Channel

Test Status: 8DPSK - Hopping



Date: 1.JAN.2000 00:50:59

6.12 Conducted Emission Test

Test Requirement: FCC Part15 15.207
Test date: May. 28, 2012
Standard Applicable According to section 15.207, frequency 150KHz to 30MHz shall not exceed the limit table as blew.


Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

EUT Setup

- 1.The conducted emission tests were performed in the test site,using the setup in accordance with the ANSI C63.10-2009.
- 2.EUT is charged with PC.The AC Power adaptor of PC was plug-in LISN.The rear of the EUT and periphearals were placed flushed with the rear of the tabletop.
- 3.The LISN was connected with 120V AC/60Hz power source.

Measurement Result Operation mode: Transmitter conducted to Receiver by wireless.
 Note:All test modes have been tested, below show the worst plots.

L line:




Final Measurement Results

Frequency MHz	QP Level dBµV	QP Limit dBµV	QP Delta dB
0.15894	46.88	65.52	18.64
0.19294	41.29	63.91	22.62
0.23845	35.47	62.15	26.68
0.25521	34.98	61.59	26.61
0.28829	32.37	60.57	28.20
0.36131	31.38	58.70	27.32
0.44299	39.45	57.01	17.56
2.36345	24.48	56.00	31.52
5.86624	15.10	60.00	44.90

Frequency MHz	AV Level dBµV	AV Limit dBµV	AV Delta dB
0.15894	29.25	55.52	26.27
0.19294	27.13	53.91	26.78
0.23845	21.42	52.15	30.73
0.25521	25.29	51.59	26.30
0.28829	18.63	50.57	31.94
0.36131	21.80	48.70	26.90
0.44299	31.33	47.01	15.68
2.36345	15.66	46.00	30.34
5.86624	10.90	50.00	39.10

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

N Line:



Final Measurement Results

Frequency MHz	QP Level dBµV	QP Limit dBµV	QP Delta dB
0.1506	47.31	65.97	18.66
0.1691	44.97	65.00	20.03
0.21838	35.56	62.88	27.32
0.44565	32.61	56.96	24.35
0.50847	23.32	56.00	32.68
0.98511	25.08	56.00	30.92
1.24702	25.05	56.00	30.95
1.54426	24.57	56.00	31.43
2.95618	21.29	56.00	34.71

Frequency MHz	AV Level dBµV	AV Limit dBµV	AV Delta dB
0.1506	32.25	55.97	23.72
0.1691	28.81	55.00	26.19
0.21838	22.20	52.88	30.68
0.44565	24.79	46.96	22.17
0.50847	12.99	46.00	33.01
0.98511	15.31	46.00	30.69
1.24702	15.71	46.00	30.29
1.54426	14.92	46.00	31.08
2.95618	14.62	46.00	31.38

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

6.13 Occupied Bandwidth Test

Test Requirement: RSS-Gen Issue 3 Clause 4.6.1
Test date: June 15, 2012
Standard Applicable According to the section RSS-Gen Issue 3 Clause 4.6.1
EUT Setup The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer with the resolutions set at 100kHz, the video bandwidth set at 300kHz.


Test date

Test Channel	Channel Frequency (MHz)	Modulation	Occupied Bandwidth(MHz)
Low	2402	GFSK	0.747
Middle	2441	GFSK	0.741
High	2480	GFSK	0.735
Low	2402	$\pi/4$ DQPSK	1.155
Middle	2441	$\pi/4$ DQPSK	1.158
High	2480	$\pi/4$ DQPSK	1.152
Low	2402	8DPSK	1.143
Middle	2441	8DPSK	1.143
High	2480	8DPSK	1.146




Result plot as follows:

Lowest Channel – GFSK:



Date: 1.JAN.2000 05:31:58

Middle Channel – GFSK:




Date: 1.JAN.2000 05:32:38

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Highest Channel – GFSK:




Date: 1.JAN.2000 05:33:18

Lowest Channel – π /4QPSK:




Date: 1.JAN.2000 05:37:00

Middle Channel $-\pi/4$ DQPSK:



Date: 1.JAN.2000 05:35:43


Highest Channel $-\pi/4$ DQPSK:



Date: 1.JAN.2000 05:35:00




Lowest Channel -8DPSK:




Date: 1.JAN.2000 05:37:41

Middle Channel -8DPSK:



Date: 1.JAN.2000 05:38:38

Highest Channel –8DPSK:



Date: 1.JAN.2000 05:39:38

End of Report