

Produkte  
Products

**RF Exposure Statement: 15044599 001**

Page 1 of 1

**Client:** Andon Health Co., Ltd.  
No. 31 Changjiang Road, Nankai District Tianjin 300193, P.R. China

**Test item:** Bluetooth Body Scale

**Identification:** HS3

**FCC Requirement**

According to FCC 2.1091, mobile equipment must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

Equipment Use	Frequency Range	Power Density [mW/cm <sup>2</sup> ]	Average Time [min]
General Population / Uncontrolled Exposure	1.5 – 100GHz	1	6

**IC Requirement**

According to RSS-102 (Issue 4), clause 2.5.2, no routine RF exposure evaluation is required if the transmitter power (e.i.r.p.) is below the following threshold:

Frequency Range	SAR Limitation [W]
Above 1.5GHz	5

**Measurement Result**

The maximum measured transmitter power is the following:

Conducted Output Power P <sub>out</sub> [mW]	Maximum Antenna Gain [dBi]	P <sub>out</sub> EIRP [mW]	Power Density at 20cm [mW/cm <sup>2</sup> ]
2.98	2.28	5.047	0.001002

Note:

The power density S in mW/cm<sup>2</sup> is calculated according to the Friis formula:  $S = (P_{out} \cdot G) / (4\pi \cdot D^2)$ , where S = power density in mW/cm<sup>2</sup>

P<sub>out</sub> = antenna conducted output power in mW

G = antenna gain in linear scale (here: 2.28dBi = 1.69 linear)

D = distance between observation point and radiating structure in cm (here: 20cm)

**Conclusion**

The device complies with the FCC and IC RF exposure requirements since the maximum transmitter power density is below the FCC limit and the e.i.r.p. power is below the IC RF exposure evaluation exemption threshold.

Refer to test report 15045728 001 for more details.

**TÜV Rheinland (Shanghai) Co., Ltd.**

10-15/F, Huatsing Building, No.88, Lane 777, Guangzhong Road West, Shanghai 200072, P.R. China