

FCC RADIO TEST REPORT

FCC ID: ZSW-30-082

Product: Mobile phone

Trade Mark: Bmobile

Model No.: AX1092

Family Model: N/A

Report No.: S18121903501005

Issue Date: 07 Jan. 2019

Prepared for

b mobile HK Limited

Flat 18; 14/F Block 1; Golden Industrial Building;16-26 KwaiTak Street;
Kwai Chung;New Territories; Hong Kong, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-755-6115 6588

Fax.: +86-755-6115 6599

Website:<http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS.....	4
3	FACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	5
3.3	MEASUREMENT UNCERTAINTY	5
4	GENERAL DESCRIPTION OF EUT	6
5	DESCRIPTION OF TEST MODES	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
7	TEST REQUIREMENTS.....	12
7.1	FIELD STRENGTH OF SPURIOUS RADIATION	12
7.2	EFFECTIVE RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER.....	22
7.3	CONDUCTED OUTPUT POWER.....	28
7.4	FREQUENCY STABILITY	33
7.5	PEAK-TO-AVERAGE RATIO	39
7.6	26DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	45
7.7	CONDUCTED BAND EDGE	51
7.8	CONDUCTED SPURIOUS EMISSION AT ANTENNA TERMINAL	56

1 TEST RESULT CERTIFICATION

Applicant's name	b mobile HK Limited
Address	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 KwaiTak Street; Kwai Chung;New Territories; Hong Kong, China
Manufacturer's Name	b mobile HK Limited
Address	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 KwaiTak Street; Kwai Chung;New Territories; Hong Kong, China
Product description	
Product name	Mobile phone
Model and/or type reference	AX1092
Family Model	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
47 CFR Part 2, Part 22H, Part 24E ANSI/TIA-603-E-2016 FCC KDB 971168 D01 Power Meas License Digital Systems v03 ANSI C63.26:2015	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 20 Dec. 2018 ~ 05 Jan. 2019

Testing Engineer : *Allen Liu*
(Allen Liu)

Technical Manager : *Jason Chen*
(Jason Chen)

Authorized Signatory : *Sam Chen*
(Sam Chen)

2 SUMMARY OF TEST RESULTS

FCC Part22, Subpart H/ FCC Part24, Subpart E			
FCC Rule	Test Item	Verdict	Remark
2.1046	Conducted Output Power	PASS	
24.232(d)	Peak-to-Average Ratio	PASS	
2.1049 22.917(b) 24.238(b)	Occupied Bandwidth	PASS	
2.1051 22.917(a) 24.238(a)	Band Edge	PASS	
22.913(a)(2)	Effective Radiated Power	PASS	
24.232(c)	Equivalent Isotropic Radiated Power	PASS	
2.1053 22.917(a) 24.238(a)	Field Strength of Spurious Radiation	PASS	
2.1055 22.355 24.235	Frequency Stability for Temperature & Voltage	PASS	
2.1051 22.917(a) 24.238(a)	Conducted Emission	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. No modifications are made to the EUT during all test items.
4. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L5516.

IC-Registration The Certificate Registration Number is 9270A-1.

FCC- Accredited Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Mobile phone
Trade Mark	Bmobile
FCC ID	ZSW-30-082
Model No.	AX1092
Family Model	N/A
Model Difference	N/A
Operating Frequency	<input checked="" type="checkbox"/> GSM850: TX824.2MHz~848.8MHz /RX869.2MHz~893.8MHz; <input checked="" type="checkbox"/> UMTS FDD Band V: TX826.4MHz~846.6MHz /RX871.4MHz~891.6MHz; <input checked="" type="checkbox"/> PCS1900: TX1850.2MHz~1909.8MHz /RX1930.2MHz~1989.8MHz; <input checked="" type="checkbox"/> UMTS FDD Band II: TX1852.4MHz~1907.6MHz /RX1932.4MHz~1987.6MHz;
Modulation	<input checked="" type="checkbox"/> GMSK for GSM/GPRS; <input checked="" type="checkbox"/> 8PSK for EGPRS; <input checked="" type="checkbox"/> QPSK for UMTS bands;
Number of Channels	<input checked="" type="checkbox"/> 124 Channels for GSM850; <input checked="" type="checkbox"/> 102 Channels for UMTS FDD Band V; <input checked="" type="checkbox"/> 299 Channels for PCS1900; <input checked="" type="checkbox"/> 277 Channels for UMTS FDD Band II;
GPRS Class	<input checked="" type="checkbox"/> Multi-Class12 <input checked="" type="checkbox"/> Only 4 timeslots are used for GPRS
SIM CARD	The Equipment has one SIM Card socket
Antenna Type	FPCB Antenna
Antenna Gain	Band II :0dBi; Band V:-3dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 3.8V/2500mAh from battery or DC 5V from USB Port.
	<input checked="" type="checkbox"/> Adapter supply: Input: 100-240V~50-60Hz 0.2A Output: 5V---1A
HW Version	MX2555F_MMI_V01
SW Version	Bmobile_AX1092_OM_LTM_V001

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual. The High Voltage 4.4V and Low Voltage 3.6V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.

5 DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester(CMU 200) to ensure max power transmission and proper modulation. Three channels (The low channel, the middle channel and the high channel) were chosen for testing on both GSM/GPRS/EGPRS 850/1900 and WCDMA Band II/V /HSDPA/HSUPA/HSPA⁺ frequency band.

Note: GSM/GPRS/EGPRS 850, GSM/GPRS/EGPRS 1900, WCDMA/HSDPA/HSUPA/HSPA⁺ band II, WCDMA/HSDPA/HSUPA/HSPA⁺ band V modes have been tested during the test. the worst condition (GSM850, GSM1900, RMC 12.2k) be recorded in the test report if no other modes test data.

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850/UMTS FDD Band V.
2. 30 MHz to 10th harmonic for GSM1900/UMTS FDD Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	For Conducted Test Cases	For Radiated Test Cases
GSM 850	GSM Link	GSM Link
GSM 1900	GSM Link	GSM Link
UMTS Band II	RMC 12.2Kbps Link	RMC 12.2Kbps Link
UMTS Band V	RMC 12.2Kbps Link	RMC 12.2Kbps Link


Test Frequency and Channels:

Frequency Band	<input checked="" type="checkbox"/> GSM 850		<input checked="" type="checkbox"/> GSM 1900		<input checked="" type="checkbox"/> UMTS Band II		<input checked="" type="checkbox"/> UMTS Band V	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH_H	251	848.8	810	1909.8	9538	1907.6	4233	846.6
CH_M	190	836.4	661	1880.0	9400	1880.0	4183	836.4
CH_L	128	824.2	512	1850.2	9262	1852.4	4132	826.4


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For Radiated Test Cases




For Conducted Output Power



For Peak-to Average Ratio, Occupied Bandwidth, Conducted Band edge and Conducted Spurious Emission



For Frequency Stability



6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	RF Cable	YES	NO	0.1m
C-2	RF Cable	YES	NO	0.1m
C-3	RF Cable	YES	NO	0.1m
C-4	DC Cable	NO	NO	1.0m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2018.10.08	2019.10.07	1 year
2	Test Receiver	R&S	ESPI	101318	2018.05.19	2019.05.18	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2018.04.08	2019.04.07	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2018.05.19	2019.05.18	1 year
5	Horn Antenna	EM	EM-AH-10180	2011071402	2018.05.19	2019.05.18	1 year
6	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2018.04.08	2019.04.07	1 year
7	Amplifier	EM	EM-30180	060538	2018.08.05	2019.08.04	1 year
8	Loop Antenna	ARA	PLA-1030/B	1029	2018.05.19	2019.05.18	1 year
9	Power Meter	R&S	NRVS	100696	2018.08.05	2019.08.04	1 year
10	Power Sensor	R&S	URV5-Z4	0395.1619.05	2018.05.19	2019.05.18	1 year
11	Test Cable	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
12	Test Cable	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
13	Test Cable	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
14	Test Receiver	R&S	ESCI	101160	2018.05.19	2019.05.18	1 year
15	LISN	R&S	ENV216	101313	2018.04.19	2019.04.18	1 year
16	LISN	EMCO	3816/2	00042990	2018.05.19	2019.05.18	1 year
17	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2018.05.19	2019.05.18	1 year
18	Passive Voltage Probe	R&S	ESH2-Z3	100196	2017.04.21	2020.04.20	3 year
19	Test Cable	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
20	Test Cable	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
21	Test Cable	N/A	C03	N/A	2018.04.19	2019.04.18	1 year
22	Attenuator	MCE	24-10-34	BN9258	2018.04.08	2019.04.07	1 year
23	Spectrum Analyzer	agilent	e4440a	us44300399	2018.05.19	2019.05.18	1 year
24	test receiver	R&S	ESCI	a0304218	2018.05.19	2019.05.18	1 year
25	Communication Tester	R&S	CMU200	A0304247	2018.10.08	2019.10.07	1 year
26	Thermal Chamber	Ten Billion	TTC-B3C	TBN-960502	2018.05.19	2019.05.18	1 year
27	DC Power Source	N/A	PS-6005D	20170402923	2017.06.06	2020.06.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& DC Power Source which is scheduled for calibration every 3 years.

7 TEST REQUIREMENTS

7.1 FIELD STRENGTH OF SPURIOUS RADIATION

7.1.1 Applicable Standard

According to FCC KDB 971168 D01 v03 Section 5.8 and ANSI/TIA-603-E-2016 Section 2.2.12

7.1.2 Conformance Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


7.1.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration

According to the ANSI/TIA-603-E-2016 test method, The Receiver or Spectrum was scanned from 9 KHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II / WCDMA Band V / GSM 850 / GSM 1900.

TEST CONFIGURATION





7.1.5 Test Procedure

1. EUT was placed on a 0.8 meter (For frequency above 1G, EUT should be placed on 1.5m) high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 meter. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (SG Level) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (SG Level) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Cable Loss), the Substitution Antenna Gain should be recorded after test.
The measurement results are obtained as described below:
 $\text{Power(EIRP)} = \text{SG Level} - \text{Cable Loss} + \text{Antenna Gain}$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.

7.1.6 Test Results

EUT:	Mobile phone	Model No.:	AX1092
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	GSM/GPRS/EGPRS 850/ GSM/GPRS/EGPRS 1900 UMTS band II/ UMTS band V	Test By:	Allen Liu

■ Radiated Spurious Emission

GSM 850							
Frequency	SG Level	Cable Loss	Antenna Gain	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 128/824.2 MHz							
1648.4	-45.15	2.80	27.50	-20.45	-13	-7.45	Vertical
1648.4	-44.29	2.80	27.50	-19.59	-13	-6.59	Horizontal
2472.6	-42.85	2.91	27.80	-17.96	-13	-4.96	Vertical
2472.6	-44.98	2.91	27.80	-20.09	-13	-7.09	Horizontal
3296.8	-46.57	4.02	29.87	-20.72	-13	-7.72	Vertical
3296.8	-42.27	4.02	29.87	-16.42	-13	-3.42	Horizontal
Test Results for Channel 190/836.6 MHz							
1673.2	-43.23	2.80	27.48	-18.55	-13	-5.55	Vertical
1673.2	-44.64	2.80	27.48	-19.96	-13	-6.96	Horizontal
2509.8	-44.27	2.91	27.70	-19.48	-13	-6.48	Vertical
2509.8	-44.44	2.91	27.70	-19.65	-13	-6.65	Horizontal
3346.4	-43.97	4.02	29.82	-18.17	-13	-5.17	Vertical
3346.4	-44.26	4.02	29.82	-18.46	-13	-5.46	Horizontal
Test Results for Channel 251/848.8 MHz							
1697.6	-43.45	2.80	27.42	-18.83	-13	-5.83	Vertical
1697.6	-43.69	2.80	27.42	-19.07	-13	-6.07	Horizontal
2546.4	-44.26	2.91	27.68	-19.49	-13	-6.49	Vertical
2546.4	-44.82	2.91	27.68	-20.05	-13	-7.05	Horizontal
3395.2	-42.12	4.02	29.80	-16.34	-13	-3.34	Vertical
3395.2	-43.64	4.02	29.80	-17.86	-13	-4.86	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

GPRS 850							
Frequency	SG Level	Cable Loss	Antenna Gain	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 128/824.2 MHz							
1648.4	-43.98	2.80	27.50	-19.28	-13	-6.28	Vertical
1648.4	-44.64	2.80	27.50	-19.94	-13	-6.94	Horizontal
2472.6	-43.24	2.91	27.80	-18.35	-13	-5.35	Vertical
2472.6	-42.47	2.91	27.80	-17.58	-13	-4.58	Horizontal
3296.8	-43.26	4.02	29.87	-17.41	-13	-4.41	Vertical
3296.8	-44.64	4.02	29.87	-18.79	-13	-5.79	Horizontal
Test Results for Channel 190/836.6 MHz							
1673.2	-45.47	2.80	27.48	-20.79	-13	-7.79	Vertical
1673.2	-42.85	2.80	27.48	-18.17	-13	-5.17	Horizontal
2509.8	-44.26	2.91	27.70	-19.47	-13	-6.47	Vertical
2509.8	-43.68	2.91	27.70	-18.89	-13	-5.89	Horizontal
3346.4	-42.17	4.02	29.82	-16.37	-13	-3.37	Vertical
3346.4	-44.62	4.02	29.82	-18.82	-13	-5.82	Horizontal
Test Results for Channel 251/848.8 MHz							
1697.6	-42.14	2.80	27.42	-17.52	-13	-4.52	Vertical
1697.6	-40.97	2.80	27.42	-16.35	-13	-3.35	Horizontal
2546.4	-42.30	2.91	27.68	-17.53	-13	-4.53	Vertical
2546.4	-42.62	2.91	27.68	-17.85	-13	-4.85	Horizontal
3395.2	-44.64	4.02	29.80	-18.86	-13	-5.86	Vertical
3395.2	-45.47	4.02	29.80	-19.69	-13	-6.69	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

EGPRS 850							
Frequency	SG Level	Cable Loss	Antenna Gain	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 128/824.2 MHz							
1648.4	-43.26	2.80	27.50	-18.56	-13	-5.56	Vertical
1648.4	-43.34	2.80	27.50	-18.64	-13	-5.64	Horizontal
2472.6	-45.14	2.91	27.80	-20.25	-13	-7.25	Vertical
2472.6	-44.69	2.91	27.80	-19.80	-13	-6.80	Horizontal
3296.8	-43.97	4.02	29.87	-18.12	-13	-5.12	Vertical
3296.8	-43.47	4.02	29.87	-17.62	-13	-4.62	Horizontal
Test Results for Channel 190/836.6 MHz							
1673.2	-42.12	2.80	27.48	-17.44	-13	-4.44	Vertical
1673.2	-40.98	2.80	27.48	-16.30	-13	-3.30	Horizontal
2509.8	-44.36	2.91	27.70	-19.57	-13	-6.57	Vertical
2509.8	-45.16	2.91	27.70	-20.37	-13	-7.37	Horizontal
3346.4	-44.21	4.02	29.82	-18.41	-13	-5.41	Vertical
3346.4	-43.36	4.02	29.82	-17.56	-13	-4.56	Horizontal
Test Results for Channel 251/848.8 MHz							
1697.6	-41.85	2.80	27.42	-17.23	-13	-4.23	Vertical
1697.6	-42.58	2.80	27.42	-17.96	-13	-4.96	Horizontal
2546.4	-46.63	2.91	27.68	-21.86	-13	-8.86	Vertical
2546.4	-44.62	2.91	27.68	-19.85	-13	-6.85	Horizontal
3395.2	-46.34	4.02	29.80	-20.56	-13	-7.56	Vertical
3395.2	-42.57	4.02	29.80	-16.79	-13	-3.79	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

GSM 1900							
Frequency	SG Level	Cable Loss	Antenna Factor	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 512/1850.2MHz							
3700.4	-46.63	4.04	33.51	-17.16	-13	-4.16	Vertical
3700.4	-47.57	4.04	33.51	-18.10	-13	-5.10	Horizontal
5550.6	-48.05	5.24	35.84	-17.45	-13	-4.45	Vertical
5550.6	-49.33	5.24	35.84	-18.73	-13	-5.73	Horizontal
Test Results for Channel 661/1880.0MHz							
3760	-47.32	4.04	33.56	-17.80	-13	-4.80	Vertical
3760	-49.56	4.04	33.56	-20.04	-13	-7.04	Horizontal
5640	-48.47	5.24	35.91	-17.80	-13	-4.80	Vertical
5640	-48.12	5.24	35.91	-17.45	-13	-4.45	Horizontal
Test Results for Channel 810/1909.8MHz							
3819.6	-47.62	4.04	34.00	-17.66	-13	-4.66	Vertical
3819.6	-49.52	4.04	34.00	-19.56	-13	-6.56	Horizontal
5729.4	-47.19	5.24	36.04	-16.39	-13	-3.39	Vertical
5729.4	-47.62	5.24	36.04	-16.82	-13	-3.82	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

GPRS 1900							
Frequency	SG Level	Cable Loss	Antenna Factor	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 512/1850.2MHz							
3700.4	-47.64	4.04	33.51	-18.17	-13	-5.17	Vertical
3700.4	-47.41	4.04	33.51	-17.94	-13	-4.94	Horizontal
5550.6	-46.64	5.24	35.84	-16.04	-13	-3.04	Vertical
5550.6	-48.49	5.24	35.84	-17.89	-13	-4.89	Horizontal
Test Results for Channel 661/1880.0MHz							
3760	-46.12	4.04	33.56	-16.60	-13	-3.60	Vertical
3760	-46.67	4.04	33.56	-17.15	-13	-4.15	Horizontal
5640	-48.70	5.24	35.91	-18.03	-13	-5.03	Vertical
5640	-49.56	5.24	35.91	-18.89	-13	-5.89	Horizontal
Test Results for Channel 810/1909.8MHz							
3819.6	-48.62	4.04	34.00	-18.66	-13	-5.66	Vertical
3819.6	-49.48	4.04	34.00	-19.52	-13	-6.52	Horizontal
5729.4	-50.58	5.24	36.04	-19.78	-13	-6.78	Vertical
5729.4	-47.64	5.24	36.04	-16.84	-13	-3.84	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

EGPRS 1900							
Frequency	SG Level	Cable Loss	Antenna Factor	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 512/1850.2MHz							
3700.4	-47.69	4.04	33.51	-18.22	-13	-5.22	Vertical
3700.4	-49.41	4.04	33.51	-19.94	-13	-6.94	Horizontal
5550.6	-48.98	5.24	35.84	-18.38	-13	-5.38	Vertical
5550.6	-48.57	5.24	35.84	-17.97	-13	-4.97	Horizontal
Test Results for Channel 661/1880.0MHz							
3760	-50.54	4.04	33.56	-21.02	-13	-8.02	Vertical
3760	-48.64	4.04	33.56	-19.12	-13	-6.12	Horizontal
5640	-51.67	5.24	35.91	-21	-13	-8	Vertical
5640	-49.41	5.24	35.91	-18.74	-13	-5.74	Horizontal
Test Results for Channel 810/1909.8MHz							
3819.6	-51.59	4.04	34.00	-21.63	-13	-8.63	Vertical
3819.6	-49.48	4.04	34.00	-19.52	-13	-6.52	Horizontal
5729.4	-50.57	5.24	36.04	-19.77	-13	-6.77	Vertical
5729.4	-51.59	5.24	36.04	-20.79	-13	-7.79	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

WCDMA Band II							
Frequency	SG Level	Cable Loss	Antenna Factor	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 9262/1852.4MHz							
3700.8	-51.59	4.04	33.51	-22.12	-13	-9.12	Vertical
3700.8	-52.41	4.04	33.51	-22.94	-13	-9.94	Horizontal
5551.2	-50.52	5.24	35.84	-19.92	-13	-6.92	Vertical
5551.2	-48.62	5.24	35.84	-18.02	-13	-5.02	Horizontal
Test Results for Channel 9400/1880MHz							
3760	-51.61	4.04	33.56	-22.09	-13	-9.09	Vertical
3760	-49.15	4.04	33.56	-19.63	-13	-6.63	Horizontal
5640	-47.98	5.24	35.91	-17.31	-13	-4.31	Vertical
5640	-49.47	5.24	35.91	-18.80	-13	-5.80	Horizontal
Test Results for Channel 9538/1907.6MHz							
3819.2	-51.32	4.04	34.00	-21.36	-13	-8.36	Vertical
3819.2	-47.61	4.04	34.00	-17.65	-13	-4.65	Horizontal
5728.8	-51.64	5.24	36.04	-20.84	-13	-7.84	Vertical
5728.8	-49.49	5.24	36.04	-18.69	-13	-5.69	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

WCDMA Band V							
Frequency	SG Level	Cable Loss	Antenna Gain	Absolute Level	Limit	Over Limit	Polarity
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dBm)	
Test Results for Channel 4233/846.6MHz							
1673.2	-45.64	2.80	27.50	-20.94	-13	-7.94	Vertical
1673.2	-45.34	2.80	27.50	-20.64	-13	-7.64	Horizontal
2509.8	-43.74	2.91	27.80	-18.85	-13	-5.85	Vertical
2509.8	-47.58	2.91	27.80	-22.69	-13	-9.69	Horizontal
3346.4	-44.69	4.02	29.87	-18.84	-13	-5.84	Vertical
3346.4	-44.64	4.02	29.87	-18.79	-13	-5.79	Horizontal
Test Results for Channel 4182/836.4MHz							
1672.8	-41.97	2.80	27.48	-17.29	-13	-4.29	Vertical
1672.8	-45.64	2.80	27.48	-20.96	-13	-7.96	Horizontal
2509.2	-46.47	2.91	27.70	-21.68	-13	-8.68	Vertical
2509.2	-45.21	2.91	27.70	-20.42	-13	-7.42	Horizontal
3345.6	-43.98	4.02	29.82	-18.18	-13	-5.18	Vertical
3345.6	-45.65	4.02	29.82	-19.85	-13	-6.85	Horizontal
Test Results for Channel 4132/826.4MHz							
1652.8	-45.02	2.80	27.42	-20.40	-13	-7.40	Vertical
1652.8	-43.14	2.80	27.42	-18.52	-13	-5.52	Horizontal
2479.2	-45.62	2.91	27.68	-20.85	-13	-7.85	Vertical
2479.2	-47.58	2.91	27.68	-22.81	-13	-9.81	Horizontal
3305.6	-46.48	4.02	29.80	-20.70	-13	-7.70	Vertical
3305.6	-45.62	4.02	29.80	-19.84	-13	-6.84	Horizontal

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2. Absolute Level = SG Level- Cable Loss+ Antenna Gain
3. Over Limit= Absolute Level (dBm)-Limit(dBm)

7.2 EFFECTIVE RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER

7.2.1 Applicable Standard

According to FCC KDB 971168 D01 v03 Section 5.2.1/ Section 5.2.2.2 and ANSI/TIA-603-E-2016 Section 2.2.17

7.2.2 Conformance Limit

The substitution method, in ANSI/TIA-603-E-2016, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v03. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For E.R.P and E.I.R.P Measurements
Please refer to the section 7.1.4 in this report.

7.2.5 Test Procedure

The measurements procedures specified in ANSI/TIA-603-E-2016 were applied.
In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$ERP/EIRP = SGLevel - P_{cl} + G_a$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as SGLevel, typically dBW or dBm);

SGLevel = Signal generator output power or PSD, in dBm or dBW;

G_a = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

P_{cl} = signal attenuation in the connecting cable between the transmitter and antenna, in dB.²

The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.

From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.

The EUT is then put into continuously transmitting mode at its maximum power level.

Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.

This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).

ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Substitution antenna and Receiving Antenna:

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Character	Note
1	Bilog Antenna	TESEQ	CBL6111D	31216	30MHz~2GHz	Receiving Antenna
2	Horn Antenna	EM	EM-AH-10180	2011071402	1GHz~18GHz	Receiving Antenna
3	Bilog Antenna	TESEQ	CBL6111D	31216	30MHz~2GHz	Substitution antenna
4	Horn Antenna	EM	EM-AH-10180	2011071402	1GHz~18GHz	Substitution antenna

Use the following spectrum analyzer settings:

	GSM/GPRS/EGPRS	UMTS band
Span	500KHz	10MHz
RBW	10KHz	300KHz
VBW	30KHz	1MHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

7.2.6 Test Results

EUT:	Mobile phone	Model No.:	AX1092
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	GSM/GPRS/EGPRS 850/ GSM/GPRS/EGPRS 1900 UMTS band II/ UMTS band V	Test By:	Allen Liu

■ Effective Radiated Power

Radiated Power (ERP) for GSM850							
Frequency	Polarization	SG	Pcl	Ga	Correction	ERP	ERP
(MHz)		Level	(dB)	Antenna Gain		(dBm)	(W)
824.2	H	10.94	2.11	23.84	2.15	30.52	1.12720
836.6	H	11.09	2.13	23.15	2.15	29.96	0.99083
848.8	H	11.59	2.13	23.06	2.15	30.37	1.08893
824.2	V	10.88	2.11	23.11	2.15	29.73	0.93972
836.6	V	11.37	2.13	23.07	2.15	30.16	1.03753
848.8	V	10.94	2.13	23.25	2.15	29.91	0.97949

Radiated Power (ERP) for GPRS850							
Frequency	Polarization	SG	Pcl	Ga	Correction	ERP	ERP
(MHz)		Level	(dB)	Antenna Gain		(dBm)	(W)
824.2	H	11.20	2.11	23.84	2.15	30.78	1.19674
836.6	H	11.12	2.13	23.15	2.15	29.99	0.99770
848.8	H	11.29	2.13	23.06	2.15	30.07	1.01625
824.2	V	11.38	2.11	23.11	2.15	30.23	1.05439
836.6	V	11.57	2.13	23.07	2.15	30.36	1.08643
848.8	V	11.44	2.13	23.25	2.15	30.41	1.09901

Radiated Power (ERP) for EGPRS850							
Frequency	Polarization	SG	Pcl	Ga	Correction	ERP	ERP
(MHz)		Level	(dB)	Antenna Gain		(dBm)	(W)
824.2	H	6.18	2.11	23.84	2.15	25.76	0.37670
836.6	H	6.56	2.13	23.15	2.15	25.43	0.34914
848.8	H	6.42	2.13	23.06	2.15	25.20	0.33113
824.2	V	6.26	2.11	23.11	2.15	25.11	0.32434
836.6	V	6.34	2.13	23.07	2.15	25.13	0.32584
848.8	V	6.77	2.13	23.25	2.15	25.74	0.37497

Radiated Power (ERP) for UMTS band V							
Frequency	Polarization	SG	Pcl	Ga	Correction	ERP	ERP
(MHz)		Level	(dB)	Antenna Gain			
826.4	H	0.77	2.11	23.84	2.15	20.35	0.10839
835	H	0.79	2.13	23.15	2.15	19.66	0.09247
846.6	H	0.93	2.13	23.06	2.15	19.71	0.09354
826.4	V	1.22	2.11	23.11	2.15	20.07	0.10162
835	V	1.60	2.13	23.07	2.15	20.39	0.10940
846.6	V	1.42	2.13	23.25	2.15	20.39	0.10940

Note:

SG Level= Signal generator output

Pcl= cable loss

Ga= Antenna Gain

Peak EIRP(dBm)= SGLevel -Pcl +Ga

ERP(dBm)=EIRP-2.15

■ Effective Isotropic Radiated Power

Radiated Power (E.I.R.P) for GSM1900						
Frequency	Polarization	SG	Pcl	Ga	EIRP	EIRP
(MHz)		Level	(dB)	Antenna	(dBm)	(W)
		(dBm)	(dB)	Gain	(dBm)	(W)
1850.2	H	4.44	3.76	28.24	28.92	0.77983
1880	H	4.60	3.91	28.22	28.91	0.77804
1909.8	H	4.51	3.93	28.20	28.78	0.75509
1850.2	V	4.83	3.76	27.32	28.39	0.69024
1880	V	5.08	3.91	27.33	28.50	0.70795
1909.8	V	5.52	3.93	27.31	28.90	0.77625

Radiated Power (E.I.R.P) for GPRS1900						
Frequency	Polarization	SG	Pcl	Ga	EIRP	EIRP
(MHz)		Level	(dB)	Antenna	(dBm)	(W)
		(dBm)	(dB)	Gain	(dBm)	(W)
1850.2	H	4.37	3.76	28.24	28.85	0.76736
1880	H	4.66	3.91	28.22	28.97	0.78886
1909.8	H	4.52	3.93	28.20	28.79	0.75683
1850.2	V	4.54	3.76	27.32	28.10	0.64565
1880	V	4.72	3.91	27.33	28.14	0.65163
1909.8	V	4.76	3.93	27.31	28.14	0.65163

Radiated Power (E.I.R.P) for EGPRS1900						
Frequency	Polarization	SG	Pcl	Ga	EIRP	EIRP
(MHz)		Level	(dB)	Antenna	(dBm)	(W)
		(dBm)	(dB)	Gain	(dBm)	(W)
1850.2	H	1.20	3.76	28.24	25.68	0.36983
1880	H	1.43	3.91	28.22	25.74	0.37497
1909.8	H	1.55	3.93	28.20	25.82	0.38194
1850.2	V	1.66	3.76	27.32	25.22	0.33266
1880	V	2.06	3.91	27.33	25.48	0.35318
1909.8	V	1.71	3.93	27.31	25.09	0.32285

Radiated Power (E.I.R.P) for UMTS band II						
Frequency	Polarization	SG	Pcl	Ga	EIRP	EIRP
(MHz)		Level	(dB)	Antenna Gain	(dBm)	(W)
		(dBm)		(dB)		
1852.4	H	-1.95	3.76	28.24	22.53	0.17906
1880	H	-2.56	3.91	28.22	21.75	0.14962
1907.6	H	-2.03	3.93	28.20	22.24	0.16749
1852.4	V	-1.90	3.76	27.32	21.66	0.14655
1880	V	-1.66	3.91	27.33	21.76	0.14997
1907.6	V	-1.57	3.93	27.31	21.81	0.15171

Note:

SG Level= Signal generator output

Pcl= cable loss

Ga= Antenna Gain

Peak EIRP(dBm)= SGLevel -Pcl+Ga.

7.3 CONDUCTED OUTPUT POWER

7.3.1 Applicable Standard

According to FCC Part 2.1046 and FCC Part 22.913(a)(2) and FCC Part 24.232(c) and FCC KDB 971168 D01 v03 Section 5.2

7.3.2 Conformance Limit

Extend coverage on a secondary basis into cellular unserved areas, as those areas are defined in §22.949, the ERP of base transmitters and cellular repeaters of such systems must not exceed 1000 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts(38.5dBm).

Mobile and portable stations are limited to 2 watts (33dBm)EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

Connect the EUT to Universal Radio Communication Tester CMU200 or CMU500 via the antenna connector. A call is set up by the SS according to the generic call set up procedure on a channel with ARFCN in the ARFCN range, power control level set to Max power. The frequency band is set as selected frequency, The RF output of the transmitter was connected to base station simulator.

Set EUT at maximum average power by base station simulator.

Set RBW = 1-5% of the OBW, not to exceed 1 MHz.

Set VBW $\geq 3 \times$ RBW.

Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)

Sweep time = auto.

Detector = RMS (power averaging).

Set sweep trigger to "free run".

Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.

Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is a constant 25%.

Measure lowest, middle, and highest channels for each bandwidth and different modulation.

Measure and record the results in the test report.

7.3.6 Test Results

EUT:	Mobile phone	Model No.:	AX1092
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	GSM/GPRS/EGPR S850/ GSM/GPRS/EGPRS 1900 UMTS band II/ UMTS band V	Test By:	Allen Liu

Output Power for GSM850

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
GSM850	824.2	31.02
	836.6	31.10
	848.8	31.19
GPRS850 (1 Slot)	824.2	31.03
	836.6	31.10
	848.8	31.17
GPRS850 (2 Slot)	824.2	30.42
	836.6	30.48
	848.8	30.49
GPRS850 (3 Slot)	824.2	29.75
	836.6	29.80
	848.8	29.84
GPRS850 (4 Slot)	824.2	29.10
	836.6	29.16
	848.8	29.24
EGPRS850 (1 Slot)	824.2	26.44
	836.6	26.48
	848.8	21.43
EGPRS850 (2 Slot)	824.2	25.48
	836.6	25.43
	848.8	25.46
EGPRS850 (3 Slot)	824.2	23.46
	836.6	23.42
	848.8	23.41
EGPRS850 (4 Slot)	824.2	22.09
	836.6	22.14
	848.8	22.48

N/A: Not Applicable

Output Power for PCS1900

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
GSM1900	1850.2	29.77
	1880	29.73
	1909.8	29.70
GPRS1900 (1 Slot)	1850.2	29.76
	1880	29.75
	1909.8	29.72
GPRS1900 (2 Slot)	1850.2	28.34
	1880	28.40
	1909.8	28.41
GPRS1900 (3 Slot)	1850.2	26.70
	1880	26.71
	1909.8	26.66
GPRS1900 (4 Slot)	1850.2	25.50
	1880	25.80
	1909.8	25.38
EGPRS1900 (1 Slot)	1850.2	25.20
	1880	25.52
	1909.8	25.45
EGPRS1900 (2 Slot)	1850.2	24.31
	1880	24.65
	1909.8	24.62
EGPRS1900 (3 Slot)	1850.2	24.29
	1880	24.64
	1909.8	24.65
EGPRS1900 (4 Slot)	1850.2	23.56
	1880	23.62
	1909.8	23.28

N/A: Not Applicable

Output Power for UMTS BAND II

Mode	Frequency(MHz)	Maximum Burst-Average Output Power
WCDMA 1900 RMC	1852.4	22.76
	1880	22.85
	1907.6	22.95
WCDMA 1900 AMR	1852.4	22.78
	1880	22.84
	1907.6	22.96
HSDPA Subtest 1	1852.4	21.25
	1880	21.96
	1907.6	21.89
HSDPA Subtest 2	1852.4	21.35
	1880	21.59
	1907.6	21.96
HSDPA Subtest 3	1852.4	21.11
	1880	21.55
	1907.6	21.77
HSDPA Subtest 4	1852.4	21.25
	1880	21.52
	1907.6	21.85
HSUPA Subtest 1	1852.4	21.25
	1880	21.67
	1907.6	21.65
HSUPA Subtest 2	1852.4	21.35
	1880	21.66
	1907.6	21.62
HSUPA Subtest 3	1852.4	21.28
	1880	21.69
	1907.6	21.68
HSUPA Subtest 4	1852.4	21.35
	1880	21.62
	1907.6	21.65
HSUPA Subtest 5	1852.4	21.25
	1880	21.89
	1907.6	21.95
HSPA+	1852.4	21.26
	1880	21.95
	1907.6	21.89

Output Power for UMTS BAND V

Mode	Frequency(MHz)	Maximum Burst-Average Output Power
WCDMA 850 RMC	826.4	22.89
	835	22.94
	846.6	22.99
WCDMA 850 AMR	826.4	22.87
	835	22.95
	846.6	22.97
HSDPA Subtest 1	826.4	21.89
	835	21.94
	846.6	21.95
HSDPA Subtest 2	826.4	21.53
	835	21.39
	846.6	21.47
HSDPA Subtest 3	826.4	21.52
	835	21.38
	846.6	21.41
HSDPA Subtest 4	826.4	21.55
	835	21.39
	846.6	21.43
HSUPA Subtest 1	826.4	21.54
	835	21.41
	846.6	21.49
HSUPA Subtest 2	826.4	21.54
	835	21.44
	846.6	21.40
HSUPA Subtest 3	826.4	21.57
	835	21.49
	846.6	21.42
HSUPA Subtest 4	826.4	21.50
	835	21.42
	846.6	21.46
HSUPA Subtest 5	826.4	21.87
	835	21.96
	846.6	21.65
HSPA+	826.4	21.76
	835	21.58
	846.6	21.55

7.4 FREQUENCY STABILITY

7.4.1 Applicable Standard

According to FCC Part 2.1055 and FCC Part 22.355 and FCC Part 24.235 and FCC KDB 971168 D01 Section 9.0

7.4.2 Conformance Limit

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

Connect the EUT to Universal Radio Communication Tester CMU200 or CMU500 via the antenna connector. A call is set up by the SS according to the generic call set up procedure on a channel with ARFCN in the ARFCN range, power control level set to Max power. MS TXPWR_MAX_CCH is set to the maximum value supported by the Power Class of the Mobile under test.

EUT was placed at temperature chamber and connected to an external power supply.

Temperature and voltage condition shall be tested to confirm frequency stability.

For Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

For Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

7.4.6 Test Results

EUT:	Mobile phone	Model No.:	AX1092
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	GSM/GPRS/EGPRS 850/ GSM/GPRS/EGPRS 1900 UMTS band II/ UMTS band V	Test By:	Allen Liu
Results: PASS			

Frequency Error Against Voltage for GSM 850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	18	0.0215
3.8	12	0.0143
4.4	16	0.0191

Frequency Error Against Temperature for GSM 850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	25	0.0299
-20	23	0.0275
-10	17	0.0203
0	16	0.0191
10	15	0.0179
20	22	0.0263
30	21	0.0251
40	19	0.0227
50	17	0.0203

Frequency Error Against Voltage for GPRS850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	16	0.0191
3.8	15	0.0179
4.4	13	0.0155

Frequency Error Against Temperature for GPRS850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	15	0.0179
-20	13	0.0155
-10	12	0.0143
0	18	0.0215
10	22	0.0263
20	23	0.0275
30	17	0.0203
40	15	0.0179
50	8	0.0096

Frequency Error Against Voltage for EGPRS850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	13	0.0155
3.8	12	0.0143
4.4	8	0.0096

Frequency Error Against Temperature for EGPRS850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	16	0.0191
-20	22	0.0263
-10	25	0.0299
0	24	0.0287
10	7	0.0084
20	9	0.0108
30	15	0.0179
40	12	0.0143
50	13	0.0155

Note:

1. Normal Voltage = 3.8V; Battery End Point (BEP) = 3.6V; Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Frequency Error Against Voltage for PCS 1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	11	0.0059
3.8	9	0.0048
4.4	16	0.0085

Frequency Error Against Temperature for PCS 1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	12	0.0064
-20	15	0.0080
-10	14	0.0074
0	18	0.0096
10	13	0.0069
20	15	0.0080
30	12	0.0064
40	10	0.0053
50	17	0.0090

Frequency Error Against Voltage for GPRS1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	22	0.0117
3.8	26	0.0138
4.4	16	0.0085

Frequency Error Against Temperature for GPRS1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	25	0.0133
-20	24	0.0128
-10	17	0.0090
0	16	0.0085
10	13	0.0069
20	22	0.0117
30	20	0.0106
40	23	0.0122
50	21	0.0112

Frequency Error Against Voltage for EGPRS1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	13	0.0069
3.8	15	0.0080
4.4	11	0.0059

Frequency Error Against Temperature for EGPRS1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	12	0.0064
-20	14	0.0074
-10	18	0.0096
0	11	0.0059
10	9	0.0048
20	16	0.0085
30	15	0.0080
40	14	0.0074
50	10	0.0053

Note:

1. Normal Voltage = 3.8V; Battery End Point (BEP) = 3.6V; Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Frequency Error Against Voltage for UMTS band II		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	12	0.0064
3.8	9	0.0048
4.4	10	0.0053

Frequency Error Against Temperature for UMTS band II		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	18	0.0096
-20	16	0.0085
-10	14	0.0074
0	13	0.0069
10	15	0.0080
20	13	0.0069
30	10	0.0053
40	16	0.0085
50	19	0.0101

Frequency Error Against Voltage for UMTS band V		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	7	0.0084
3.8	15	0.0179
4.4	14	0.0167

Frequency Error Against Temperature for UMTS band V		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	13	0.0155
-20	12	0.0143
-10	17	0.0203
0	15	0.0179
10	10	0.0120
20	23	0.0275
30	11	0.0131
40	15	0.0179
50	14	0.0167

Note:

1. Normal Voltage = 3.8V; Battery End Point (BEP) = 3.6V; Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.