

# FCC Test Report

## FCC ID: ZSW-30-114

**Product:** Mobile Phone  
**Trade Mark:** Bmobile  
**Model Number:** BL53  
**Family Model:** BL50, BL51  
**Report No.:** S23070305502001

**Prepared for**

b mobile HK Limited  
Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak  
Street; Kwai Chung; New Territories; Hong Kong, China

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090  
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name ..... b mobile HK Limited
Address..... Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung;New Territories; Hong Kong,China

Manufacturer's Name ..... b mobile HK Limited
Address..... Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung;New Territories; Hong Kong,China

Product description
Product name ..... Mobile Phone
Model and/or type reference BL53
Family Model..... BL50, BL51

Standards ..... FCC Part15B
ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test .....:
Date (s) of performance of tests .....: Jul 03,2023 ~ Jul 18,2023
Date of Issue.....: Jul 25,2023
Test Result.....: Pass

Testing Engineer : [Signature]
(Allen Liu)

Authorized Signatory : [Signature]
(Alex Li)

**Table of Contents****Page**

<b>1 . TEST SUMMARY</b>	<b>4</b>
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
<b>2 . GENERAL INFORMATION</b>	<b>6</b>
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	9
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	10
2.4 MEASUREMENT INSTRUMENTS LIST	11
<b>3 . EMC EMISSION TEST</b>	<b>12</b>
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION	12
3.1.2 TEST PROCEDURE	13
3.1.3 TEST SETUP	13
3.1.4 EUT OPERATING CONDITIONS	13
3.1.5 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	16
3.2.2 TEST PROCEDURE	16
3.2.3 TEST SETUP	17
3.2.4 TEST RESULTS	18
3.2.5 TEST RESULTS(1000~18000MHz)	20

**1. TEST SUMMARY**

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number:463705; IC Registration Number:9270A-1

CNAS Registration Number:L5516

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

Test Item	Measurement Frequency Range	K	U(dB)
AC Mains Conducted Emission	0.009kHz ~ 0.15MHz	2	2.66
AC Mains Conducted Emission	0.15MHz ~ 30MHz	2	2.80
Telecom Conducted Emission (Cat 3)	0.15MHz ~ 30MHz	2	2.40
Telecom Conducted Emission (Cat 5)	0.15MHz ~ 30MHz	2	2.58
Radiated Emission	30MHz ~ 1000MHz	2	2.64
Radiated Emission	1000MHz ~ 6000MHz	2	5.10
Radiated Emission	6000MHz ~ 18000MHz	2	2.52
Power Clamp	30MHz ~ 300MHz	2	2.20

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mobile Phone	
Trade Mark	Bmobile	
Model Name	BL53	
Family Model	BL50, BL51	
Model Difference	All the model are the same circuit and RF module,except the Model names.	
Product Description	The EUT is a Mobile Phone .	
	Connecting I/O port:	Micro USB, Earphone
	Operation Frequency:	2567.5MHz
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Power Source	DC 3.8V/ 3000mAh from battery or DC 5V from Adapter.	
Adapter	Input: 100-240V~50-60Hz 0.2A Output: 5.0V---1A	
HW Version	Bmobile_BL53_HW_V1.0	
SW Version	Bmobile_BL53_TIGO_LATAM_V001	



### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM
Mode 5	GPS


For Conducted Test	
Final Test Mode	Description
Mode 1	USB Data Transmission

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Data Transmission


Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.  
Only the worst case mode is recorded in the report.



2.2 DESCRIPTION OF TEST SETUP  
CE



RE



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	PC	DELL	N/A	N/A	Peripherals
AE-2	KB	HP	N/A	N/A	Peripherals
AE-3	Mouse	DELL	N/A	N/A	Peripherals
AE-4	Monitor	SHARP	N/A	N/A	Peripherals
AE-5	Printer	Canon	N/A	N/A	Peripherals
AE-6	Earphone	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	NO	1.0m	
C-2	USB Cable	NO	NO	1.2m	
C-3	USB Cable	NO	NO	1.2m	
C-4	HDMI Cable	YES	YES	1.0m	
C-5	USB Cable	NO	NO	1.2m	
C-6	Earphone Cable	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” “with core”; “NO” means “unshielded” “without core”.

## 2.4 MEASUREMENT INSTRUMENTS LIST

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2023.03.27	2024.03.26	1 year
2	Test Receiver	R&S	ESPI	101318	2023.03.27	2024.03.26	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2023.03.27	2024.03.26	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2023.03.27	2024.03.26	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2023.03.27	2024.03.26	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2023.03.27	2024.03.26	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2023.03.27	2024.03.26	1 year
8	Amplifier	EMC	EMC051835SE	980246	2023.05.29	2024.05.28	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2023.03.27	2024.03.26	1 year
10	Power Meter	DARE	RPR3006W	15I00041SN084	2022.11.08	2023.11.07	1 year
11	Power Sensor	R&S	URV4-Z4	0395.1619.05	2023.03.27	2024.03.26	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
13	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2022.06.17	2025.06.16	3 year

### AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2023.03.27	2024.03.26	1 year
2	LISN	R&S	ENV216	101313	2023.03.27	2024.03.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2023.03.27	2024.03.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2023.05.06	2026.05.05	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



**Note: 1.Support units were connected to second LISN.  
2.Both of LISN s (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT:	Mobile Phone	Model Name. :	BL53
Temperature:	22.2 °C	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2023-07-14
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from adapter (AC 120V/60Hz)		

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	46.67	9.93	56.60	65.79	-9.19	QP
0.1539	22.16	9.93	32.09	55.79	-23.70	AVG
0.2429	36.79	10.12	46.91	62.00	-15.09	QP
0.2429	23.36	10.12	33.48	52.00	-18.52	AVG
0.5220	33.12	10.69	43.81	56.00	-12.19	QP
0.5220	19.61	10.69	30.30	46.00	-15.70	AVG
1.5060	33.99	12.68	46.67	56.00	-9.33	QP
1.5060	22.43	12.68	35.11	46.00	-10.89	AVG
3.7540	30.03	9.67	39.70	56.00	-16.30	QP
3.7540	18.35	9.67	28.02	46.00	-17.98	AVG
14.7220	28.96	9.70	38.66	60.00	-21.34	QP
14.7220	19.59	9.70	29.29	50.00	-20.71	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Mobile Phone	Model Name. :	BL53
Temperature:	22.2 °C	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2023-07-14
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from adapter( AC 120V/60Hz)		

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	46.98	9.93	56.91	66.00	-9.09	QP
0.1500	32.18	9.93	42.11	56.00	-13.89	AVG
0.5299	29.05	10.71	39.76	56.00	-16.24	QP
0.5299	20.01	10.71	30.72	46.00	-15.28	AVG
0.9100	32.74	11.48	44.22	56.00	-11.78	QP
0.9100	20.26	11.48	31.74	46.00	-14.26	AVG
1.3860	30.47	12.44	42.91	56.00	-13.09	QP
1.3860	21.08	12.44	33.52	46.00	-12.48	AVG
5.8420	23.90	9.68	33.58	60.00	-26.42	QP
5.8420	13.80	9.68	23.48	50.00	-26.52	AVG
14.8300	28.89	9.70	38.59	60.00	-21.41	QP
14.8300	19.00	9.70	28.70	50.00	-21.30	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

**Notes:**

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

**Test Arrangement for Radiated Emissions up to 1 GHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

**Test Arrangement for Radiated Emissions above 1 GHz.**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength.Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: For the hand-held device, the EUT should be measured for all 3 axes and only the




worst case is recorded in the report  
During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	1 MHz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.4 TEST RESULTS


TEST RESULTS (30~1000 MHz)

EUT:	Mobile Phone	Model Name:	BL53
Temperature:	24.9°C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2023-07-14
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from adapter (AC 120V/60Hz)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	31.3992	6.19	25.70	31.89	40.00	-8.11	QP
H	177.5092	12.42	17.07	29.49	43.50	-14.01	QP
H	226.0994	23.25	17.27	40.52	46.00	-5.48	QP
H	314.3765	19.04	20.40	39.44	46.00	-6.56	QP
H	383.9318	17.32	22.87	40.19	46.00	-5.81	QP
H	993.0114	7.32	32.36	39.68	54.00	-14.32	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level- Limit.




EUT:	Mobile Phone	Model Name :	BL53
Temperature:	24.9 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2023-07-14
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from adapter (AC 120V/60Hz)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	30.9619	6.72	25.93	32.65	40.00	-7.35	QP
V	135.5062	6.51	18.78	25.29	43.50	-18.21	QP
V	226.0994	11.96	17.27	29.23	46.00	-16.77	QP
V	422.0577	6.77	23.68	30.45	46.00	-15.55	QP
V	642.8613	7.75	27.10	34.85	46.00	-11.15	QP
V	979.1804	7.98	31.80	39.78	54.00	-14.22	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level- Limit.



**3.2.5 TEST RESULTS(1000~18000MHz)**

EUT:	Mobile Phone	Model Name :	BL53
Temperature:	24.8℃	Relative Humidity:	52%
Pressure:	1010 hPa	Test Date :	2023-07-14
Test Mode :	Mode 1		
Test Power :	DC 5V from adapter(AC 120V/60Hz)		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Reading	Correct	Result	Limit	Over Limit	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	1090.582	37.19	5.01	42.20	74.00	-31.80	peak
V	1090.582	25.01	5.01	30.02	54.00	-23.98	AVG
V	1447.688	36.52	5.31	41.83	74.00	-32.17	peak
V	1447.688	23.79	5.31	29.10	54.00	-24.90	AVG
V	1978.082	36.70	6.38	43.08	74.00	-30.92	peak
V	1978.082	22.07	6.38	28.45	54.00	-25.55	AVG
V	2298.892	35.71	7.40	43.11	74.00	-30.89	peak
V	2298.892	19.25	7.40	26.65	54.00	-27.35	AVG
V	3289.821	34.43	10.15	44.58	74.00	-29.42	peak
V	3289.821	18.54	10.15	28.69	54.00	-25.31	AVG
V	5386.000	32.61	14.13	46.74	74.00	-27.26	peak
V	5386.000	15.20	14.13	29.33	54.00	-24.67	AVG
H	1175.697	37.46	5.21	42.67	74.00	-31.33	peak
H	1175.697	24.99	5.21	30.20	54.00	-23.80	AVG
H	1447.688	37.30	5.31	42.61	74.00	-31.39	peak
H	1447.688	24.19	5.31	29.50	54.00	-24.50	AVG
H	1877.800	35.95	5.82	41.77	74.00	-32.23	peak
H	1877.800	22.34	5.82	28.16	54.00	-25.84	AVG
H	2352.668	35.66	7.43	43.09	74.00	-30.91	peak
H	2352.668	21.92	7.43	29.35	54.00	-24.65	AVG
H	3168.500	34.31	10.24	44.55	74.00	-29.45	peak
H	3168.500	19.78	10.24	30.02	54.00	-23.98	AVG
H	5046.000	33.74	14.25	47.99	74.00	-26.01	peak
H	5046.000	16.79	14.25	31.04	54.00	-22.96	AVG

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit

Note: Only the worst results data points are reported in the report.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

END OF REPORT