## **OEM Documentation Requirements**

## **RF Exposure for FCC**



**WARNING:** To satisfy FCC RF exposure requirements for mobile transmitting devices, a separation distance of 21.7 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended. The antenna used for this transmitter must not be co-located in conjunction with any other antenna or transmitter.

The preceding statement must be included as a CAUTION statement in OEM product manuals in order to alert users of FCC RF Exposure compliance.

## RF Exposure for IC



**WARNING:** To satisfy IC RF exposure requirements for mobile transmitting devices, a separation distance of 32.1 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended. The antenna used for this transmitter must not be co-located in conjunction with any other antenna or transmitter.



**AVERTISSEMENT:** Pour satisfaire IC RF exigences d'exposition pour les appareils mobiles de transmission, une distance de séparation de 32,1 cm ou plus doit être maintenue entre l'antenne de cet appareil et des personnes pendant le fonctionnement de l'appareil. Pour assurer la conformité, les opérations au plus près que cette distance ne sont pas recommandés. L'antenne utilisée pour cet émetteur ne doit pas être situé en conjonction avec une autre antenne ou émetteur.

The preceding statement must be included as a CAUTION statement in OEM product manuals in order to alert users of IC RF Exposure compliance.

## **OEM Notices**

**IMPORTANT**: The G2XL Module has been certified by the FCC for use with other products without any further certification (as per FCC section 2.1091). Modifications not expressly approved by Monnit Corporation could void the user's authority to operate the equipment.

**IMPORTANT:** OEM Integrators must test final product to comply with unintentional radiators (FCC section 15.107 & 15.109) before declaring compliance of their final product to Part 15 of the FCC Rules. Other compliance testing may also apply (for example, PC peripheral requirements, etc.).

**IMPORTANT:** The G2XL module has been certified for remote and base radio applications. If the module will be used for portable applications, the device must undergo SAR testing.

**IMPORTANT:** In the event that the minimum distance requirement or if the module is co-located with other transmitters, then current FCC and IC authorization is no longer valid and the FCC ID or IC number cannot be used on the final product. In these circumstances, the OEM integrator will be responsible for reevaluating the end product (including the transmitter) and obtaining a separate FCC and IC authorization.