



APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	IP Micro Camera		
Model	NPC-20012-F2WL W; NPC-20012-F2WL		
Model Discrepancy	All the model numbers (list on this report) are identical, just for marketing purpose only except Color.		
	Model Number	Color	
	NPC-20012-F2WL W	White	
	NPC-20012-F2WL	Black	
RF Module	TAITO YUDEN CO., LTD	Model:	WYSAAVDX7
Frequency band (Operating)	☒ 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz ☐ Others		
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others		
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)		
Antenna Specification	2.4GHz: Antenna Gain : 0.20 dBi (Numeric gain 1.05)		
Maximum Average output power	IEEE 802.11b Mode: 12.71 dBm (18.664 mW) IEEE 802.11g Mode: 6.00 dBm (3.981 mW) IEEE 802.11n HT 20 Mode 6.14 dBm (4.111 mW) IEEE 802.11n HT 40 Mode 5.72 dBm (3.733 mW)		
Maximum Tune up Power	IEEE 802.11b Mode: 13.00 dBm (19.953 mW) IEEE 802.11g Mode: 7.00 dBm (5.012 mW) IEEE 802.11n HT 20 Mode 7.00 dBm (5.012 mW) IEEE 802.11n HT 40 Mode 7.00 dBm (5.012 mW)		
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A		



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2014/04/11	Initial Issue	ALL	



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{377 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**Maximum Permissible Exposure**

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	19.953	1.05	20	0.0042	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	5.012	1.05	20	0.0010	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	5.012	1.05	20	0.0010	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	5.012	1.05	20	0.0010	1