



Radio Frequency Exposure

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	High Power Wireless-N 600mW Gigabit Dual Band Access Point
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.725GHz ~ 5.850GHz <input type="checkbox"/> Bluetooth: <u>2.402GHz ~ 2.480 GHz</u>
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	802.11b: 20.49 dBm (111.9 mW) 802.11g: 21.85 dBm (153.1 mW) 802.11n (20MHz): 24.82 dBm (303.23 mW) 802.11n (40MHz): 24.82 dBm (303.43 mW) 802.11a: 23.89 dBm (244.9 mW) 802.11an (20MHz): 26.77 dBm (475.41 mW) 802.11an (40MHz): 26.69 dBm (466.70 mW)
Antenna gain (Max)	802.11b/g/n: 2 dBi ; 802.11a, an: 4 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

Remark:

1. The maximum output power is 26.77 dBm (475.41 mW) at 5785 MHz (with numeric 4.0 antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

- Where $E =$ Field strength in Volts / meter
- $P =$ Power in Watts
- $G =$ Numeric antenna gain
- $d =$ Distance in meters
- $S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$
$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

- Where $d =$ Distance in cm
- $P =$ Power in mW
- $G =$ Numeric antenna gain
- $S =$ Power density in mW / cm²



Maximum Permissible Exposure

ANT R

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
802.11b	2412-2462	20.42	2.0	20	0.035	1
802.11g	2412-2462	25.76	2.0	20	0.119	1
802.11n (20MHz)	2412-2462	25.60	2.0	20	0.114	1
802.11n (40MHz)	2422-2452	25.60	2.0	20	0.114	1
802.11a	5150-5250	8.06	4.0	20	0.003	1
802.11a	5725-5850	23.87	4.0	20	0.122	1
802.11an (20MHz)	5150-5250	8.11	4.0	20	0.003	1
802.11an (20MHz)	5725-5850	23.70	4.0	20	0.117	1
802.11an (40MHz)	5190-5230	9.09	4.0	20	0.004	1
802.11an (40MHz)	5755-5795	23.65	4.0	20	0.116	1

ANT L

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
802.11b	2412-2462	20.49	2.0	20	0.035	1
802.11g	2412-2462	25.80	2.0	20	0.120	1
802.11n (20MHz)	2412-2462	25.59	2.0	20	0.114	1
802.11n (40MHz)	2422-2452	25.86	2.0	20	0.122	1
802.11a	5150-5250	7.64	4.0	20	0.003	1
802.11a	5725-5850	23.89	4.0	20	0.122	1
802.11an (20MHz)	5150-5250	7.09	4.0	20	0.003	1
802.11an (20MHz)	5725-5850	23.82	4.0	20	0.120	1
802.11an (40MHz)	5190-5230	8.15	4.0	20	0.003	1
802.11an (40MHz)	5755-5795	23.71	4.0	20	0.117	1



ANT R+L

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
802.11n (20MHz)	2412-2462	24.82	5.01	20	0.191	1
802.11n (40MHz)	2422-2452	24.82	5.01	20	0.191	1
802.11an (20MHz)	5150-5250	10.52	7.01	20	0.011	1
802.11an (20MHz)	5725-5850	26.71	7.01	20	0.469	1
802.11an (40MHz)	5150-5250	11.66	7.01	20	0.015	1
802.11an (40MHz)	5725-5850	26.66	7.01	20	0.463	1

NOTE:

Total (Chain0+Chain1) , the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density