

FCC Co-Location Test Report

FCC ID : ZTT-REC22P
Equipment : High Power AC1200 Plug-In Wi-Fi Range Extender
Model No. : REC22P 、 REC22PG
(Different case color for marketing purpose only.)
Brand Name : Amped
Applicant : Amped Wireless
Address : 13089 Peyton Dr. #C307 Chino Hills, California 91709 United State
Standard : 47 CFR FCC Part 15.247
47 CFR FCC Part 15.407
Received Date : Dec. 28, 2015
Tested Date : Jan. 19 ~ Feb. 02, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	The Equipment List	6
1.3	Test Standards	7
1.4	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Condition	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS.....	9
3.1	Unwanted Emissions into Restricted Frequency Bands	9
4	TEST LABORATORY INFORMATION	16

Release Record

Report No.	Version	Description	Issued Date
FR5D2803-01CO	Rev. 01	Initial issue	Feb. 19, 2016

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d) 15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]: 500.04MHz 45.49 (Margin -0.51dB) – QP	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5745 ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM/256QAM)

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Antenna Gain (dBi)		
				2400~2483.5MHz	5150~5250 MHz	5725~5850 MHz
1	WAN8010F245M05	Chip	N/A	3.45	--	--
2	ACM3-5036-A1-CC-S	Chip	N/A	3	3.3	3.3
3	8619 replacement antenna	Dipole	N/A	3.48	3.49	3.17

Note1: Ant 1 and 3 are used for 2.4 GHz transmission.

Note2: Ant 2 and 3 are used for 5 GHz transmission.

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	AC 110~120V, 60Hz, 7A
--------------------------	-----------------------

1.1.4 Accessories

N/A

1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Dec. 17, 2015	Dec. 16, 2016
Receiver	R&S	ESR3	101657	Jan. 12, 2016	Jan. 11, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-523	Nov. 09, 2015	Nov. 08, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 07, 2015	Oct. 06, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 10, 2015	Dec. 09, 2016
Preamplifier	Burgeon	BPA-530	100218	Nov. 03, 2015	Nov. 02, 2016
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	EMCC	CFD400-E	CFD400-001	Dec. 10, 2015	Dec. 09, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 14, 2015	Sep. 13, 2016
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 27, 2015	Nov. 26, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Signal Generator	R&S	SMB100A	175727	Oct. 05, 2015	Oct. 04, 2016
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 26, 2015	Oct. 25, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r01

FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission \leq 1GHz	± 3.87 dB
Radiated emission $>$ 1GHz	± 5.60 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH02-WS	20°C / 65-68%	Morgan Chen Aska Huang
Conducted Emissions	TH01-WS	22°C / 64%	Felix Sung

- FCC site registration No.: 657002
- IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Radiated Emissions	2.4G 11b + 5G 11a	CH11 + CH40	1Mbps + 6Mbps	---
Conducted Emissions				
NOTE: The selected channel is the maximum power channel of 2.4GHz and 5GHz				

3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.1.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz




Transmitter Conducted Unwanted Emissions (30MHz~40GHz)



3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	2.4G 11b + 5G 11a	Test Freq. (MHz)	CH11 + CH40						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is constant at 46 dBuV/m from 100 MHz to 1000 MHz. Six vertical blue lines indicate emission levels at specific frequencies: 1 (250.00 MHz, 42.93 dBuV/m), 2 (375.32 MHz, 42.12 dBuV/m), 3 (500.12 MHz, 44.98 dBuV/m), 4 (625.04 MHz, 44.74 dBuV/m), 5 (750.71 MHz, 42.96 dBuV/m), and 6 (875.06 MHz, 44.28 dBuV/m). All emission levels are below the 46 dBuV/m limit.</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	250.00	42.93	46.00	-3.07	55.70	-12.77	Peak	124	255
2	375.32	42.12	46.00	-3.88	51.45	-9.33	Peak	---	---
3	500.12	44.98	46.00	-1.02	51.49	-6.51	QP	195	205
4	625.04	44.74	46.00	-1.26	49.02	-4.28	QP	126	224
5	750.71	42.96	46.00	-3.04	45.32	-2.36	Peak	---	---
6	875.06	44.28	46.00	-1.72	45.20	-0.92	QP	156	208
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>									

Modulation	2.4G 11b + 5G 11a	Test Freq. (MHz)	CH11 + CH40
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	49.40	35.75	40.00	-4.25	47.42	-11.67	Peak	---	---
2	375.02	45.15	46.00	-0.85	54.49	-9.34	QP	128	195
3	500.04	45.49	46.00	-0.51	52.00	-6.51	QP	100	221
4	625.03	43.02	46.00	-2.98	47.30	-4.28	QP	100	213
5	750.71	42.50	46.00	-3.50	44.86	-2.36	Peak	---	---
6	875.05	42.68	46.00	-3.32	43.60	-0.92	QP	100	197


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	2.4G 11b + 5G 11a	Test Freq. (MHz)	CH11 + CH40																																																																																			
Polarization	Horizontal																																																																																					
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 40000). A red line represents the FCC PART 15E limit, which is 74 dBuV/m from 1000 to 10000 MHz and 54 dBuV/m from 10000 to 40000 MHz. A horizontal red line at 54 dBuV/m is labeled 'FCC PART 15E (AVG)'. A blue line represents the test results, showing several peaks. Six specific points are marked with blue vertical lines and numbered 1 through 6. The test results are summarized in the table below.</p>																																																																																						
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High</th> <th>Turn Table</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2738.00</td> <td>42.81</td> <td>54.00</td> <td>-11.19</td> <td>44.68</td> <td>-1.87</td> <td>Average</td> <td>175</td> <td>226</td> </tr> <tr> <td>2</td> <td>2738.00</td> <td>53.68</td> <td>74.00</td> <td>-20.32</td> <td>55.55</td> <td>-1.87</td> <td>Peak</td> <td>175</td> <td>226</td> </tr> <tr> <td>3</td> <td>7662.00</td> <td>47.56</td> <td>54.00</td> <td>-6.44</td> <td>37.85</td> <td>9.71</td> <td>Average</td> <td>229</td> <td>330</td> </tr> <tr> <td>4</td> <td>7662.00</td> <td>54.83</td> <td>74.00</td> <td>-19.17</td> <td>45.12</td> <td>9.71</td> <td>Peak</td> <td>229</td> <td>330</td> </tr> <tr> <td>5</td> <td>15524.00</td> <td>45.87</td> <td>54.00</td> <td>-8.13</td> <td>30.11</td> <td>15.76</td> <td>Average</td> <td>233</td> <td>339</td> </tr> <tr> <td>6</td> <td>15524.00</td> <td>59.00</td> <td>74.00</td> <td>-15.00</td> <td>43.24</td> <td>15.76</td> <td>Peak</td> <td>233</td> <td>339</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	2738.00	42.81	54.00	-11.19	44.68	-1.87	Average	175	226	2	2738.00	53.68	74.00	-20.32	55.55	-1.87	Peak	175	226	3	7662.00	47.56	54.00	-6.44	37.85	9.71	Average	229	330	4	7662.00	54.83	74.00	-19.17	45.12	9.71	Peak	229	330	5	15524.00	45.87	54.00	-8.13	30.11	15.76	Average	233	339	6	15524.00	59.00	74.00	-15.00	43.24	15.76	Peak	233	339							
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																														
1	2738.00	42.81	54.00	-11.19	44.68	-1.87	Average	175	226																																																																													
2	2738.00	53.68	74.00	-20.32	55.55	-1.87	Peak	175	226																																																																													
3	7662.00	47.56	54.00	-6.44	37.85	9.71	Average	229	330																																																																													
4	7662.00	54.83	74.00	-19.17	45.12	9.71	Peak	229	330																																																																													
5	15524.00	45.87	54.00	-8.13	30.11	15.76	Average	233	339																																																																													
6	15524.00	59.00	74.00	-15.00	43.24	15.76	Peak	233	339																																																																													
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																																						

Modulation	2.4G 11b + 5G 11a	Test Freq. (MHz)	CH11 + CH40
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2738.00	41.95	54.00	-12.05	43.82	-1.87	Average	322	299
2	2738.00	52.92	74.00	-21.08	54.79	-1.87	Peak	322	299
3	7662.00	46.85	54.00	-7.15	37.14	9.71	Average	311	189
4	7662.00	53.95	74.00	-20.05	44.24	9.71	Peak	311	189
5	15524.00	45.73	54.00	-8.27	29.97	15.76	Average	322	220
6	15524.00	58.74	74.00	-15.26	42.98	15.76	Peak	322	220

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.1.6 Conducted Emissions (30MHz~40GHz)



Note: 2.4GHz and 5GHz share 1 common antenna since only one test plot is provided.

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==