



SAR Exemption Evaluation

Applicant WOW Tech Canada Ltd.,
FCC ID ZUEMLT20B
Product Lay on vibrator
Brand We-Vibe
Model MLT20B
Report No. R2410A1570-S1V1
Issue Date December 12, 2024

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
TEL: +86-021-50791141/2/3
FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment	4
2	Description of Equipment Under Test	5
3	Test Specification, Methods and Procedures	7
4	Output Power	8
5	Standalone SAR Test Exclusion Considerations	9
	ANNEX A: The EUT Appearance	10

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	December 10, 2024
Rev.1	Update description.	December 12, 2024

Note: This revised report (Report No.: R2410A1570-S1V1) supersedes and replaces the previously issued report (Report No.: R2410A1570-S1). Please discard or destroy the previously issued report and dispose of it accordingly.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	WOW Tech Canada Ltd.,
Applicant address	1545 Carling Avenue, Suite 401. Ottawa, Ontario, Canada, K1Z 8P9
Manufacturer	WOW Tech Europe GmbH
Manufacturer address	Hermann-Blankenstein-Str. 5, 10249 Berlin, Germany

General Technologies

Application Purpose	Original Grant
EUT Stage	Identical Prototype
Model	MLT20B
Lab internal SN	R2410A1570/S01
Hardware Version	MLT20B
Software Version	NA
Antenna Type	Internal Antenna
Date of Testing	October 23, 2024 ~ December 2, 2024
Date of Sample Received	October 23, 2024

Note: The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.

Wireless Technology and Frequency Range

Wireless Technology	Modulation	Operating Mode	Tx (MHz)
Bluetooth LE	2.4G	Version 5.0 + LE	2402 ~2480

3 Test Specification, Methods and Procedures

Reference Standards

KDB 447498 D01 General RF Exposure Guidance v06

4 Output Power

Bluetooth LE	Output Power(dBm)		
	Ch 0/2402 MHz	Ch 19/2440 MHz	Ch 39/2480 MHz
GFSK (1M)	-8.13	-8.92	-10.47
GFSK (2M)	-7.98	-8.81	-10.37

5 Standalone SAR Test Exclusion Considerations

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Band	Configuration	Frequency (MHz)	Distance (mm)	MAX Power (dBm)	Ratio	SAR test exclusion thresholds	Evaluation
Bluetooth LE	Body SAR	2480	0	-7.98	0.05	3	No
	Extremity SAR	2480	0	-7.98	0.05	7.5	No

Note: Based on SAR test exclusion, all values meet the SAR test exclusion thresholds and are exempt from routine evaluation.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****